

COLD WATER – TWO-WHEEL

The **bully**-Series



Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding crank (TST design)

Quick-release fittings

for simple and quick lance changes

Pressure regulation

Fully adjustable control allows operating pressures to be set to suit any task

Neat storage system

Holders for trigger gun with safety catch and lances

Total-stop system

Auto-shutdown feature improves seal life-span and reduces power consumption

Figures: bully 980 TST





		bully 980 TS	bully 980 TST	bully 1180 TS	bully 1180 TST
		without hose drum	incl. hose drum	without hose drum	incl. hose drum
Operating pressure adjustable	bar / MPa	30-180 / 3-18	30-180 / 3-18	30-160 / 3-16	30-160 / 3-16
Max. admissible overpressure	bar / MPa	200 / 20	200 / 20	180 / 18	180 / 18
Connected load	V / ~ / Hz / A	400 / 3 / 50 / 11.5	400 / 3 / 50 / 11.5	400 / 3 / 50 / 11.5	400 / 3 / 50 / 11.5
Motor speed	Rpm	1400	1400	1400	1400
Water output	l/min l/h	16 960	16 960	19 1140	19 1140
Power intake / Power output	kW kW	7.0 5.0	7.0 5.0	7.0 5.0	7.0 5.0
Power supply cable	m	7.5	7.5	7.5	7.5
Dimensions L x W x H	mm	730 / 425 / 970	730 / 425 / 970	730 / 425 / 970	730 / 425 / 970
Weight	kg	65	68	65	68
Cleaning Agent Intake		—	—	—	—
Equipment					
Hose drum		—	●	—	●
Steel braided high-pressure hose	m	10	15	10	15
Trigger gun with safety catch	Model	M2000	M2000	M2000	M2000
Dirtkiller lance	Nozzle size	● 055	● 055	● 075	● 075
Stainless steel lance with flat jet nozzle	Nozzle size	● D25055	● D25055	● D25075	● D25075

Ord.no.	403501	40350	403511	40351
---------	--------	-------	--------	-------

TECHNICAL HIGHLIGHTS!

QUICK-RELEASE FITTINGS

Kränzle quick-release fittings are made with hardened stainless steel components ensuring a simple and perfectly safe connection of the trigger gun with safety catch to the lance.



For detailed technical information, see page 77