

Partner of specialist dealers!

The bully 1000 TST for perfect cleaning results!

- Space-saving, compact and service-friendly design
- Extremely stable and robust Roto-Mold trolley
- Integrated trolley takes steps and rough ground in its stride
- Simple and comfortable handling
- Corrosion-resistant materials
- Integrated hose drum with foldable crank (TST)
- 7.5 m power lead with cable reel
- Trigger gun with safety catch and quick release system
- Dirtkiller lance with stainless steel pipe and quick release nipple, stainless steel lance with flat jet nozzle and quick release nipple
- Storage for trigger gun with safety catch and lance
- Total-stop-system
- Shock absorbing buffers





Germany



Technical specifications	bully 1000 TST
Ord. no.	40.360 10
Operating pressure, continuously adjustable	30-200 bar (3-20 MPa)
Max. admissible overpressure	230 bar (23 MPa)
Water output	16 l/min (960 l/h)
Motor speed	1,400 rpm
Connected load	400 V, 12 A, 50 Hz
Power intake / Power output	7.5 kW / 5.5 kW
Weight	68 kg

Features & Equipment	Ord. no.
Steel braided high-pressure hose NW 8, 15 m	46.411
Trigger gun M2000 with safety catch and quick release system	12.492
Dirtkiller lance 1000 mm with stainless steel pipe and quick release nipple	12.425-055
Stainless steel lance 1000 mm with flat jet nozzle and quick release nipple	12.420-D2505