

turbodevil

Our new turbodevil floor cleaner series



The choice of perfection



turbodevil – the new generation



Especially smooth running and stainless

- Especially designed for professional cleaning applications.
- Completely stainless design.
- Suitable for hot and cold water high pressure pumps.
- Heat-resistant all around protection ensures a safe handling by protection against splashes and stones.
- The precision rotor arm is counterbalanced, precisely equilibrated and welded by robots.
- Guaranteed low vibration & reliable running.
- Suitable for applications up to about 150 hours annual operation hours.
- Swivels are equipped with reinforced, self-lubricating triple bearing made out of stainless steel as developed with a hard metal sealing system for high revolutions per minute.



turbodevil – INDUSTRIAL



To optimally adapt the surface cleaner to the high pressure cleaner, nozzles are excluded. **Nozzles with 1/4" M are required.** All surface cleaner are packed separately.

- Especially designed for industrial cleaning applications.
- Use of a especially high quality, 3-bearing swivel joint with ceramic sealing elements for high durability and extremely long stress.
- Castors made of stainless steel.

Extra sturdy, heat- and chemicalresistant



turbodevil – the new generation



The choice of perfection



Newly developed:
Swivel for high revolutions with pivoting inlet



TD 300



TD 410



3 or 4 industrial castors (60 mm): Easy and flexible steering



TD 520

Includes divisible and adjustable fork

For effortless work:
We recommend our gun ST-2600 with patented LTF technology.



Fork angle:
Variable settings



Foldable handle bar:
For space saving & easy transportation



Swivel:
With triple bearing system

Surface cleaner TD 300 & TD 410

Surface cleaner with a newly developed swivel with pivoting inlet for high revolutions per minute. The bending of the swivel is variably adjustable thus making an easy cleaning of floors and walls possible. 3 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 1800 l/h / 60 °C

R+M Nr.	∅	⊕	P
521 030 300	300 mm	1/4" IG	max. 275 bar
521 042 300	410 mm	1/4" IG	max. 275 bar

Surface cleaner TD 520

Surface cleaner with foldable handle bar for space saving and reasonable transport. Swivel with triple bearing system. 4 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 2400 l/h / 60 °C


R+M Nr.	∅	⊕	P
521 052 300	520 mm	1/4" IG	max. 275 bar

Accessories for TD 300 & TD 410




Lance ST-007. 1/4" M : Plug KW. Stainless steel 1000 mm

R+M Nr.
512 495 90



Lance extension. 1/4" M : M22 M. Stainless steel 500 mm

R+M Nr.
513 129



Adapter. 1/4" M : M18 F. Stainless steel

R+M Nr.
519 70



Professional equipment:
Swivel with ceramic sealing
elements and stainless
steel castors



TDI 410



Extra robust: Swivel with
ceramic sealing elements
and pivoting inlet, triple
bearing system



TDI 520

With 750 mm diameter
a working tool of
high-performance class.



TDI 750

For effortless work:
We recommend our gun ST-2600 with
patented LTF technology.



High performance swivel joint:
For for maximum stress with a
longer life time

Surface cleaner TDI 410 INDUSTRIAL

Surface cleaner with a newly developed swivel with pivoting inlet for high revolutions per minute. The bending of the swivel is variably adjustable thus making an easy cleaning of floors and walls possible. 3 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 1800 l/h / 120 °C

R+M Nr.	∅	G	P
521 042 400	410 mm	1/4" IG	max. 275 bar

Surface cleaner TDI 520 INDUSTRIAL

Surface cleaner with foldable handle bar for space saving and reasonable transport. High performance swivel, stainless steel. 4 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 2400 l/h / 120 °C

R+M Nr.	∅	G	P
521 052 400	520 mm	1/4" IG	max. 275 bar



4 large industry castors:
To move with ease

Precision rotor:
Welded by robots



Surface cleaner TDI 750 INDUSTRIAL

All stainless steel. With reinforced hood and divisible fork. High performance swivel, stainless steel. Precision rotor arm welded by robots. 4 industrial castors (100 mm). 3 nozzles 1/4" M are required. Max. 2400 l/h / 120 °C

R+M Nr.	∅	G	P
521 075 300	750 mm	1/4" IG	max. 275 bar

turbodevil – agriculture-cleaner Big Wheel




The choice of perfection



For professional barn cleaning:
We recommend using the gun
easyfarm365+ with patented
LTF technology.

Adjustable fork support

Space-saving:
Divisible fork



Large wheels:
For good grip



- Wheeled floor cleaner with lance holder for high pressure lance for extra cleaning in corners or on walls.
- Solid stainless steel design with reinforcements for demanding use in agriculture.
- Front-mounted castor in 30 mm width, is ideal for driving on slatted floors and allows easy and flexible steering.
- Connection to the rotating arm via a reinforced hinge with carbide sealings.
- The set-back arrangement of the stable fork allows for easy cleaning under obstacles such as tables or fences.
- 2 very large, foam-filled rear tires allow to go up stairs rearwards.
- Gun and lance with nozzle are not included.
- 2 nozzles 1/4" M are required.
- Max. 1800 l/h / 120 °C

Carefully chosen:
With 30 mm well
equipped for
slatted floors



Lug: The underside
of the connecting
tube remains on
the handle



Extra robust:
Swivel with
carbide sealings



Clean solution:
Extra thick
rubber bristles for
splashback



Always at hand:
Lance holder for attachment to the fork

R+M Nr.	∅	⊘	P
521 052 900	520 mm	1/4" IG	max. 275 bar