

makes a difference



PROGRAMME 2019/2020



TABLE OF CONTENTS

Introduction	Page	4
Connected Cleaning	Page	24
Kärcher Fleet	Page	28
Kärcher Manage	Page	30
Kärcher Services	Page	32
Kärcher Service	Page	34
Kärcher All Brands Service	Page	36
Kärcher service packages	Page	38
Kärcher Original Spare Parts	Page	40
Financing Solutions Kärcher Rent	Page Page	42 43
Kärcher Used	Page	44
High-pressure cleaners	Page	46
Hot water high-pressure cleaners	Page	50
Cold water high-pressure cleaners	Page	74
Accessories	Page	118
Stationary high-pressure cleaners	Page	184
Accessories	Page	196
Ultra high-pressure cleaners	Page	
Accessories	Page	
Cleaning agents	Page	842
Work protection	Page	226
Outdoor Power Equipment	Page	234
Machines	Page	236
Accessories	Page	248
Vacuum cleaners	Page	250
Window/surface vacuum cleaner	Page	252
Wet and dry vacuum cleaners	Page	256
Accessories	Page	300
Industrial vacuums	Page	328
Accessories	Page	356
Dry vacuum cleaners	Page	
Accessories	Page	408
Deep carpet cleaning	Page	422
Machines	Page	426
Accessories	Page	436
Cleaning agents	Page	850
Steam cleaners/Steam vacuum cleaners	Page	442
Machines	Page	
Accessories	Page	450
Water and air	Page	454
Scrubbers/scrubber driers	Page	470
Machines	Page	480
Accessories	Page	552
Manual cleaning equipment	Page	792
Cleaning agents	Page	866

3weepers/vacouii	i sweepers	1 ugc	02
Machines		Page	62
Accessories		Page	66
Municipal equipme	ent	Page	69
Machines	Circ		
Machines		Page	69
Wash systems		Page	72
Machines		Page	73
Cleaning agents		Page	87
Water reclamation	1	Page	75
Machines		Page	75
Treatment chemicals for	or water treatment	Page	88
Industrial solution	S	Page	76
Container cleaning	revetome	Page	76
	3 Systems		
Machines		Page	76
Cleaning agents		Page	88
Dry ice cleaning		Page	77
Machines		Page	77
Accessories		Page	78
Parts cleaning		Page	78
Machines		Page	78
Accessories		Page	79
Cleaning agents		Page	88
Manual cleaning		Page	79
Machines			
Cleaning agents		Page Page	79 85
Clearling agents		rage	03
Cleaning and care	agents	Page	84
Cleaning agents for hig	gh-pressure cleaners	Page	84
Cleaning agents for car	rpet cleaners	Page	85
Cleaning agents for ma	anual cleaning	Page	85
Cleaning agents, care a	gents and disinfection		
for hard and resilient t		Page	86
Cleaning and care ager		Page	87
Treatment chemicals for		Page	88
Cleaning agents for inc		Page	88
Cleaning agents for co	ntainer cleaning	Page	88
Index		Page	88
Machines		Page	88
Cleaning agents		Page	88
Our pictograms		Page	89
		. 480	



TOGETHER WE CAN ACHIEVE MORE

Teams are heroes. All tasks can only be carried out with the right partners. And the best possible results can only be achieved when different talents are combined. We consider ourselves to be a team with you. Your experience and feedback are valuable to us, because we are pursuing the same goal: developing innovations and products which enable you to achieve your objectives more quickly and efficiently.

FOR EVERYTHING. FOR PROFESSIONALS. FOR YOU.

Professionals today do not need general machines that can all do a little. They need targeted solutions that complete specific tasks efficiently. Preferably a complete solution, as a functional, balanced system. For this reason, we constantly analyse the needs of all relevant industries in order to understand them better and recognise trends at an early stage. The result is innovative and efficient industrial solutions that fulfil their purpose in an exemplary manner. Robust and reliable. Efficient and economical. Lightweight and quiet. Handy and hygienic. That is the Kärcher system.





















INNOVATIVE ROBOTS THAT CAN DO MORE

Welcome to the world of autonomous cleaning. We have developed a robot for you that enables you to use the full efficiency and independence of this technology in relatively small areas.

People are always seeking intelligent solutions for relief from monotonous and demanding work. All technology follows this principle – from the washing machine to the robotic lawn mower. Autonomous industrial trucks are well established in industry. Agricultural robots, drones for diverse tasks and last but not least autonomous driving will very soon permanently change the way we work and our lives in general. KIRA represents this in professional cleaning: Kärcher Intelligent Robotic Application. With KIRA we create a platform for all our professional robotic products. And it is our response to your future challenges in cleaning technology.

We laid the foundations for KIRA at an early stage. In the 1990s we developed the first professional robotic scrubber drier. This model was used daily at Schiphol Airport in Amsterdam until 2008. Our Robo Cleaner followed in 2003. The rapid development of the fundamental technologies such as the sensor system and navigation, as well as our own development, are now paving the way for the use of robots in the cleaning world. We developed KIRA B 50 from scratch. As a result, you get a system that bears our signature. And with which you have an autonomous response to price pressure and increasing wage costs.



CLEANING IN ITS PUREST FORM

Kärcher cleaning machines are known around the world for their performance, reliability and simple operation. Our Classic machine concept provides sophisticated, detailed solutions, and, thanks to robustness and mobility, is impressive in hard, constant daily operation. Modern efficiency is ensured by the extremely long service life, maximum availability with low service costs, energy-saving operation and concentration on what's important.



WPC 120 UF



BD 50/70 R Classic



BD 80/100 W Bp Classic









13

B 60/10 C T 8/1 Classic HD 18/50-4 Cage Classic



IT'S ALL IN THE DETAIL

For us, progress means making things better for you. Current examples of this are our new high-pressure cleaners, wet and dry vacuum cleaners, vehicle wash systems and scrubber driers. Discover optimised machine shapes that we have customised to your needs, as well as materials that are even more robust. Be inspired by high-quality design elements. Or by innovative accessories and machine components such as the new flexible cable or our unique K!Dry iQ dryer.











A REAL BUNDLE OF ENERGY

Battery technology is a key technology with unlimited potential for the future. As a leading innovator, we recognised this fact early on and developed our own battery systems in which the battery pack, machine and accessories operate as an efficient overall system. This makes our battery packs as robust, powerful and versatile as you would expect from Kärcher. Our lithium-ion technology gives you significantly more efficiency in conjunction with unprecedented user benefits.









Geprüft nach EU-Norm

Desinfektionsmittelliste

KÄRCHER EASY!FORCE

✓ Handling
✓ Ergonomics

IANLA

DLG Test Report 6772









- High Efficiency Burner
- Low Fuel Consumption
- Low Emission

EFFICIENCY Certified

FOR A CLEAN ENVIRONMENT














EADAND DER AUTOMOBILIND









EUnited

Cleaning • European Cleaning Machines

• High Cleaning Efficiency













TRUST HAS TO BE **EARNED.**

As a professional, you place the highest demands on your machines and equipment: our aim is to meet these demands. But we would not be Kärcher if we were satisfied with that. Because we are also professionals. And because we want to earn your trust. Time and again. That is why we do more. And you get more. More functionality and efficiency. More solutions and innovative services. More certifications and more sustainability. And with that - simply more success.


Our success as a company has always been inextricably linked to Alfred Kärcher and the values that he personified and put into practice. With his passion for people. And this will not change in the future.

Thank you for your trust.

THE KÄRCHER SYSTEM.

Kärcher's development into a system provider follows the principle of achieving more together. In the company itself, as with suppliers and particularly with end users, solutions that benefit all parties are sought together. Innovative products and services which are combined to produce an optimised system: the Kärcher System. Crucially, the Kärcher system meets the customer's most important requirements, and ideally all of their requirements.

As a system supplier, Kärcher does not want to offer anything and everything, only what operators need for their individual cleaning system. It is not the available range that is decisive, but the actual demand. It is important to have an answer to all questions relating to performance, efficiency and sustainability. A system that consists of machines, accessories, cleaning agents, services and digital solutions that can be easily integrated into operating procedures and adds value. A system that makes a difference: the Kärcher System.



SUSTAINABILITY IS MORE THAN ENVIRONMENTAL PROTECTION.

Sustainability means conducting business fairly, with a sense of responsibility towards people and the environment. Kärcher has sustainability as a corporate objective and has been practising it for decades: sound finances and reasonable profits, achieved by dealing fairly with people and using resources responsibly.







BLUE COMPETENCE
Alliance Member

Partner of the Engineering Industry Sustainability Initiative







climate neutral powered by Climate Partner*

Operation | ID: 00000-0000-0000

Less is more. And less can do more

The primary aim of Kärcher ecolefficiency is to reduce the consumption of resources and energy with a cleaning performance that is tailored to specific applications. In order to calculate the possible savings in energy and CO_2 emissions over the service life of the machine and render them comparable, these were calculated based on the example of our T 12/1 and T 12/1 ecolefficiency dry vacuum cleaners. TÜV SÜD Industrie Service GmbH verified and confirmed the plausibility of the methodology for calculating greenhouse gas emissions in the utilisation phase of the T 12/1 ecolefficiency machine against benchmarks. Based on this methodology, Kärcher calculated that all T 12/1 ecolefficiency dry vacuum cleaners sold to date will save around 6,000 tonnes of CO_2 emissions throughout their service life. All Kärcher ecolefficiency machines in total will save approximately 2.5 million tonnes of CO_2 emissions.

Work towards a better world: BlueCompetence

Blue is the colour of sustainability, which takes into account cost efficiency, the environment and society. The "BlueCompetence" initiative, supported by the German Engineering Federation (VDMA), includes about 400 companies and organisations with one common goal: to ensure the quality of life on our planet for years to come.

Do more with less energy

The saving on CO_2 emissions of all machines equates to roughly 1.5 million flights from London to New York*. These figures clearly demonstrate how much energy and emissions can be saved by using Kärcher ecolefficiency machines. When it comes to climate protection, less is always more – and achieves more.

* 1.7 tonnes of CO₂ per flight.

Climate-neutral cleaning

We cannot produce anything without emissions. But we can completely offset greenhouse gas (CO₂) emissions in order to neutralise their effects on the environment. And you can also do this for your industry. For a small surcharge, you can offset the CO₂ emissions of your Kärcher cleaning machines so that they are climate-neutral over their entire operating life.

These contributions, both yours and ours, are fully incorporated into a certified climate protection project from ClimatePartner. For example, "Water treatment in Kenya" gives millions of people access to clean drinking water. The use of filter systems for water treatment saves several million tonnes of CO₂ emissions from firewood each year. At the same time, sustainable jobs for several thousand people are created. A project that is useful for everyone, completely transparent and accountable. Your sales advisor can explain how you can benefit from climate-neutral cleaning.

THE FUTURE OF CLEANING IS NOW.

With Connected Cleaning, we are developing a digital product portfolio for you in which all elements work together perfectly. In the first step, we are bringing two great digital products together on a joint platform. Combined in a single piece of software, Kärcher Fleet and Kärcher Manage connect the entire infrastructure of your cleaning fleet and generate effective synergies. Through Connected Cleaning, you get a completely new and transparent information base. Using this, you can make decisions more easily, increase efficiency and thus work more economically.



Table of contents: Connected Cleaning

Kärcher Fleet Page 28 Kärcher Manage Page 30






Kärcher Fleet

Fleet management

The professional and forward-looking fleet management solution

- Kärcher Fleet – provides an extensive overview of machines and cleaning activities. Kärcher Fleet makes cleaning processes far more transparent and efficient. This results in smooth procedures and attractive cost savings. You can currently use Kärcher Fleet for three product groups: Floor cleaning machines (scrubber driers and sweepers), vehicle wash systems and water dispensers.



Kärcher Manage

Management of manual cleaning

The high-performance management solution for manual cleaning. With Kärcher Manage, we offer you the software solution for the planning, control and quality assurance of your tasks. Easy, fast and precise paperless data acquisition. The benefits are greater transparency and a better result from the outset

KÄRCHER FLEET FOR FLOOR CLEANING MACHINES

The professional and forward-looking fleet management solution - Kärcher Fleet - gives you an extensive overview of your machines, sites and cleaning activities at all times. Kärcher Fleet makes cleaning processes far more transparent and efficient. This results in smooth procedures and attractive cost savings.





1 More efficient machine use

The principle and uses of Kärcher Fleet are based on machine data that is processed to become useful management information. Machines can be used more efficiently and are available when you need them. The coordination of transport and use at different locations is optimised, saving time and resources. Through monitoring "machine health" and automated alarms, downtime is significantly reduced.

2 Simple planning and control

operating perfectly and according to schedule, if cleaning times are being machines in the fleet at all times. This also applies (with restrictions) to observed, if servicing or repairs are needed, and much more. Detailed information is available directly from the overview with just one click. Kärcher Fleet transmits data virtually in real time, allowing the optimisation of fleet utilisation capacities or corrections to be made, if necessary, almost immediately.

3 Complete documentation

Kärcher Fleet allows the preparation of reports at any time through automatic storage and archiving of machine data and fleet information. Prepared reports can be displayed, exported and printed out at the click of a mouse. Information on services provided is therefore available at any time.

4 Immediately ready to use - without installation

Fleet operators can view the fleet status at any time to see if machines are Kärcher Fleet provides fleet operators with an extensive overview of all machines from other manufacturers. Access to the Kärcher Fleet web portal only requires an Internet connection. The telematics box built into the machine sends all information securely encrypted and with modern transmission standards to a global server cloud. Authorised users can conveniently gain access to all relevant data and evaluations via this cloud. It could not be easier.

AVAILABLE MACHINES AND FUNCTIONS



All machines are configurable upon request. To retrofit any of our machines, please see order no. for Kärcher Fleet retrofit kit in the table below.

Order no for Värcher Floot retrofit kit

	Order no. for Karcher Fleet retrof					
Fully supported machines	EU / AUS / JPN	USA / CAN				
BR 45/22 C	2.644-096.0	2.644-106.0				
B 40 C + W / 60 W / 80 W (with Kärcher bus machine control)	2.644-093.0	2.644-103.0				
B 40 C + W / 60 W / 80 W (with CAN bus machine control)	2.644-094.0	2.644-104.0				
B 100	2.644-113.0	2.644-114.0				
B 120 W	2.644-095.0	2.644-105.0				
B 95 RS	2.644-098.0	2.644-108.0				
BD 50/70 R	2.644-097.0	2.644-107.0				
B 150 R, B 150 R Adv, B 200 R	2.644-099.0	2.644-109.0				
B 250 R (manufactured from 2017 onwards)	2.644-100.0	2.644-110.0				
KM 105/100 R, KM 105/110 R, KM 125/130 R	2.852-611.0	2.852-612.0				
KIRA B 50	on request	on request				

Order no. for Kärcher Fleet retrofit kit

27

Partly supported machines	EU / AUS / JPN	USA / CAN
BR 55/40 RS, BD 50/40 RS, BD 60/95 RS, B 90 R, B 140 R, B 250 R (manufactured before 2017)	2.644-102.0	2.644-112.0
B 300 R	2.644-101.0	2.644-111.0
KM 85/50	2.852-532.0	2.852-610.0
KM 90/60 R, KM 100/100 R, KM 120/150 R, CV 60/2	2.644-102.0	2.644-112.0

Functions	Fully supported machines	Partly supported machines
Inventory management: Overview of fleet, assignment to buildings, operational planning	•	
Site monitoring: Monitoring of machine locations, theft protection with geofencing (warning when machine leaves assigned area)	•	
Planning, recording and evaluation of operating hours: Reports about usage times and daily operating hours, active notification in the event of deviations from the schedule	•	•
Total cost of ownership: Manual recording of invoices and service calls per machine	•	•
Battery information: Charging state of battery, notification of potentially limited capacity based on used charge cycles	■ **	
Machine state monitoring: Monitoring of machine state, active notification in the event of malfunctions, automatic detection of machine errors		
Remote diagnosis: Remote diagnosis possible by Kärcher customer service, remote read-out of error codes	•	

More Kärcher cleaning machines upon request. Non-Kärcher machines upon request.

- * Real-time notifications of deviations from the schedule not available for B 150 R UL, B 200 R UL, KM 105/100 R Bp, KM 105/110 R Bp, KM 125/130 R Bp.
- " Notification of potentially limited battery capacity not available for BD 50/70 R, B 150 R UL, B 200 R UL, KM 105/100 R Bp, KM 105/110 R Bp, KM 125/130 R Bp. Not applicable for machines with petrol, diesel or liquid gas fuel (KM 105/100 R D/G/LPG, KM 105/110 R D/G/LPG, KM 125/130 R D/G/LPG).

KÄRCHER FLEET FOR VEHICLE WASH SYSTEMS

Kärcher Fleet gives you a comprehensive overview of all your wash systems at any time. With Kärcher Fleet, you can now efficiently manage even those wash systems located far away without time-consuming on-site visits. Detailed information on the level of capacity utilisation and programme usage make it possible to optimise your offers and avoid fraud. Continuous information about the status of the wash systems will be sent to you in virtually real time, allowing you to react quickly and minimising downtime.







1 Optimal planning and use

Kårcher Fleet measures the level of capacity utilisation of various wash systems: On which days and at what times are the systems being used and how? Recording the use of individual wash programmes allows you to adapt your pricing strategy, e.g. introducing a "happy hour", and improve your investment planning. An important factor for success is also a better view of the running costs, such as the use of water, electricity and oil. This may require additional counters.

2 Higher availability

Kärcher Fleet informs you practically in real time about any extraordinary circumstances that may arise. The immediate alarm that goes off allows you to react faster when a malfunction occurs. Detailed information about the state of the machine and reasons for failure, i.e. machine faults, allow you to eliminate problems faster. At the same time, the way the system distinguishes between technical and operative faults saves you unnecessary service calls. The possibility of remote diagnosis through our Kärcher customer service guarantees that you can solve problems quickly and efficiently.

3 Fraud protection

Kärcher Fleet minimises the risk of fraud. By comparing the data on the actual use of the machine with your income, you always have the full overview of the use of your systems and, if you need it, evidence of the extent of the losses.

4 Time savings

You can access the Kärcher Fleet web portal at any time from any computer with Internet access. Automated documentation and the possibility of exporting the recorded data into different programmes significantly reduces the time spent on reporting and controlling. And you have to be on site far less often to ensure state and operation of your wash system.

Order no. for Kärcher Fleet retrofit kit

Machine	EU / AUS / JPN	USA / CAN
Klean!Star iQ, Klean!Star, CB 3	2.643-967.0	2.644-090.0
SB MU, SB MB	4.643-016.0	4.643-017.0
SB MC 2	4.643-020.0	4.643-021.0
More Kärcher machines	on request	on request

KÄRCHER FLEET FOR WATER DISPENSERS

Kärcher Fleet for water dispensers simplifies the support of water dispensers at a wide range of sites. You always know which dispensers require your attention. This reduces the time you need to spend on maintenance, minimises possible downtime and maximises user satisfaction.





1 Simpler and better support

Kärcher Fleet will immediately send you a message when the operating status of your water dispenser requires it. This might be a full drip tray, an empty CO₂ bottle, a scheduled filter replacement or a defect. Time-consuming regular on-site checks can be practically dispensed with. Remote access to all important machine data also avoids unnecessary service calls. You will be able to see when the next sanitisation procedure, or next filter replacement, is due at a glance. The higher availability of the water dispenser also ensures that the users are happy.

2 Comprehensive documentation

Kärcher Fleet automatically creates documentation on completed sanitisation procedures. In the inventory list, you can look at all the technical details about each machine, e.g. filter type and equipment.

3 Keeping all costs in sight

Thanks to Kärcher Fleet, you know exactly how much each water dispenser costs. You will receive a continuous overview of the usage and flow volume of each water dispenser. The additionally possible manual tracking of costs for service calls, spare parts and consumables gives you a full overview of all accrued costs per machine. Together with the reports on the usage of each individual water dispenser, you will have a measurable foundation for the optimal set-up of the machines and the economic planning of new acquisitions.

4 Simple and secure data access

You can access the Kärcher Fleet web portal at any time from any computer with Internet access. You can also subscribe to receiving automatic alerts by e-mail. The data will be transmitted via an in-built SIM card; no Wi-Fi or Internet access is necessary.


Order no. for Kärcher Fleet Retrofit Kit

Machine	
WPD 100 Adv	2.643-275.0
WPD 200 Adv	2.643-275.0
WPD 600 Adv	2.643-275.0

All water dispensers are configurable upon request.

KÄRCHER MANAGE: SUCCESSFULLY MANAGE YOUR MANUAL CLEANING.


Manage and optimise your manual cleaning processes and operating procedures digitally. With Kärcher Manage, we offer you the software solution for the planning, control and quality assurance of your tasks. All relevant data is transmitted online and then available immediately. Manual cleaning has never been so transparent.












Easily optimise manual cleaning processes.

Kärcher Manage can help you to do this and much more.

- Manage and optimise your manual cleaning processes with Kärcher Manage.
- Electronic data recording instead of manual documentation.
- Recording and mobile transmission of work and cleaning times.
- Simple read-out and charging of the scanners on the Kärcher Manage docking station.
- Measurable quality thanks to specific reports.
- Analysis and reporting of cleaning times.
- Individual barcodes for fast and precise documentation.

- Easy assignment of cleaning personnel to buildings.
- Detailed overview of all performed and outstanding room inspections.
- Damage reports as an additional service for the customer: The barcodes allow you to directly record any defects on site and automatically contact facility management via e-mail.
- Display of additional cleaning activities.
- Generation of reports as Excel or PDF files.





1 Kärcher Manage web portal

- Easy web portal access for facility and branch managers.
- Current status requests on attendance, cleaning activities, working hours, checks and activities.
- Creation of reports and statistics.
- Optimised documentation and information processes.
- Easy facility preparation using barcodes and recording via scanning during cleaning.
- Clearly arranged and intuitive to use interface.
- Management of cleaning personnel and fleet machines on a single platform
- Management, tracking and coordination of activities.
- Correction and subsequent entry of cleaning data.
- Target/actual comparison of planned and actually completed cleaning activities.

2 Kärcher Manage hardware

- Kärcher Manage docking station: Automatic data transfer and simultaneous recharging of up to 10 USB scanners.
- Integrated telematics unit for the intelligent transmission of recorded scan data so that a PC is not necessary.
- Handy and robust scanners for data recording.
- Smart device for recording in real time and for daily management.

3 Kärcher Manage app

- Efficient quality checks via app by the facility manager.
- Selection of quality criteria.
- $\hfill \blacksquare$ View of last quality check, including quality criteria.
- Creation of buildings and rooms.
- Available for Android (from version 4.4) and iOS (from version 8.0).

31

Order no.

Machine	
Kärcher Manage docking station	6.682-469.0
Kärcher Manage Barcode Scanner (USB)	6.999-016.0
Power cable with cold-device plug EU / CH / GB / DK / IT	6.640-672.0 / -278.0 / -277.0 / -276.0 / -279.0

YOU MANAGE YOUR BUSINESS. WE PROVIDE THE SUPPORT.

Things can be much easier when people's talents are combined. Because it is simply more successful to pursue common goals, to complement each other and to learn from one another. You could call it the principle of progress. We call it Kärcher Services. A promise of partnership. Our promise to you.





able of contents. Harener between	
Kärcher Service	Page 3
Kärcher All Brands Service	Page 3
Kärcher Service Packages	Page 3
Kärcher Original Spare Parts	Page 4
Kärcher Financing Solutions	Page 4
Kärcher Rent	Page 4
Kärcher Used	Page 4











1 Competent advice

Kārcher is a global market leader in cleaning technology not least because we always have the right solution for your cleaning problems thanks to continuous further development and innovation. Our friendly and experienced service team only has one objective: to give you fast, practical help. We are here for you if you have any questions, need a problem solved or want information about optimal machine usage. All day, every day.

2 Maintenance and repair

Every machine needs maintenance. And you can't survive without your machines. So we simply combine both in our competent service portfolio. In our global network of certified service partners you have access to 5,000 service engineers who provide fast, reliable on-site service. All necessary tools, spare parts and wear parts. And optimally tailored packages for inspection, maintenance and full service.

3 Training and help

When cleaning you constantly come across new materials that require special cleaning solutions. We keep you up-to-date on cleaning technology with training courses, also in relation to cost-effectiveness, efficiency and environmental protection. In modern training rooms and small training groups so that we can show an interest in every participant and deal with specific issues. Our experienced consultants work with you on cleaning solutions specific to target groups. You become a competent service provider and advisor to your customers.

4 Financing solutions

There are countless options for financing. We work with you to find the optimal solution for you – tailored to the respective cleaning requirement. For example, we offer flexible leasing options, short-term rentals and used machines. The entire service from a single source. Our strength. Your benefit.

You can find more information about our service offer on our website www.kaercher.com

35

KÄRCHER SERVICE

There is service, and there is our Kärcher Service. We claim to offer the best service in the cleaning industry. We are there for you when you need us. In your company. At your job site. Wherever. And around the clock and worldwide.



Top service is an integral part of the Kärcher system. In our comprehensive global service network experienced engineers guarantee first-class support. We respond quickly and stock all necessary spare parts and tools. Our engineers are well-trained and are also very familiar with your machine. We work with you to develop solutions that are tailored to your individual needs and requirements - from the telephone consultation to training offers through to our comprehensive maintenance offer.





Because something can happen every day we are here for you 365 days a For us customer proximity means that we are with you quickly should the year with all our experience and expertise. Our close-knit sales and service worst happen. No matter when and where. Immediately of course in the sidiaries. With our service partners you have access to a total of more than on time for the agreed appointment for regular service tasks. 5,000 service engineers worldwide.

network is spread across 182 countries on all continents. Around 1,000 of event of faults or urgent application problems. The extremely quick response our own service engineers are available to assist you in our over 60 sub-


KÄRCHER ALL BRANDS SERVICE: SERVICE FOR ALL BRANDS.

Would you like the full service for all machines from a single source, but have machines from manufacturers other than Kärcher in your fleet?

Then use our Kärcher All Brands Service for the repair and servicing of machines from other manufacturers. Just as you would expect from our service: competent, reliable and fast.




Over 1,000 expertly trained service engineers are on hand to help you in 60 countries. Regardless of the machines and brands in your fleet, we will take care of it all. Without any difference and in compliance with all standards. And of course, the prescribed safety inspections are also included. With our Kärcher expertise as a global market leader, we can provide the best possible service for your entire fleet. While you concentrate on your business, we make sure that your machines are working. And you have one contact partner for everything – for maintenance and repairs, for spare and wear parts, for accessories and cleaning agents.










KÄRCHER SERVICE PACKAGES: WE GIVE YOU THE AVAILABILITY.

KÄRCHER SERVICE PACKAGES

Prevention is always preferable to repair. Preventive measures such as regular and proper inspections and maintenance play a key role in reducing the probability of machine downtime to a minimum.



A service package must fit like a tailored suit. We offer you service packages and services where you can add or adapt modules as required. Entirely in line with your requirements. You decide how much service you want: from the simple inspection within the framework of prescribed safety checks to regular maintenance work through to the fixed full service offer. With our service packages you also know the costs up front because you only pay for what you actually need.

	Kärcher Full Service	Kärcher Maintain	Kärcher Inspect
Features			
Safety inspection incl. inspection tags		•	•
Inspection acc. to manufacturer's specifications		•	•
Preventive maintenance work		•	-
Repair work		-	-
Functional guarantee		-	-
Replacement machines		-	-
Consumables			
(e.g. brushes or cleaning agents)			
Battery (maintenance, repair, replacement)			
Order no.	2.888-061.0	2.888-059.0	2.888-058.0
with consumables	-062.0	-060.0	-073.0
with battery service	-078.0	-076.0	-074.0
with consumables and battery service	-079.0	-077.0	-075.0
Price			

■ Included in the scope of supply. □ Optional.









1 Kärcher Inspect

The Kärcher Inspect service package includes regular inspections and statutory safety checks, with inspection tags and inspection reports, showing the condition of the machine.

Consumables:

With our extra Consumables package you get all planned consumables throughout the entire term of the contract. There is no need for time-condition.

2 Kärcher Maintain

The Kärcher Maintain service package also includes, in addition to the scope of Kärcher Inspect, the preventive replacement of specific wear parts with Kärcher original spare parts as part of the regular maintenance. This way you minimise downtimes and extend the service life of your machine.

3 Kärcher Full Service

The Kärcher Full Service service package covers all services required for the safe, efficient and reliable operation of the respective machine. You get maximum availability of your machines with full control of the costs at the same time. And you get a functional guarantee from us for your machines. The costs are transparent and fair and can be calculated exactly in advance.

4 Optional service package upgrades

throughout the entire term of the contract. There is no need for time-consuming reordering. You define the type and amount of consumables such as cleaning agents, brushes or suction lips and we supply them within the framework of regular inspection and maintenance visits by our service engineers.

Batteries:

The extra Battery package includes the regular preventive maintenance of the battery, increasing its life cycle and reducing the risk of a battery failure. You receive a new battery free of charge in the event of an irreparable failure, as well as after the technically possible life cycle is reached.

KÄRCHER ORIGINAL SPARE PARTS: MAINTAINING THE VALUE OF YOUR MACHINE.

Your decision to go with our cleaning machines has its reasons: innovative technology, great cleaning performance, reliability, robustness, cost-effectiveness, environmental friendliness. And our globally unique Kärcher System of cleaning machines, accessories and coordinated cleaning agents. Kärcher original spare parts are the logical continuation of your decision. They ensure value retention and a consistent cleaning performance at Kärcher level. They make sure that your Kärcher remains a Kärcher.





1 Kärcher quality forever

When it comes down to the performance, reliability and availability of a machine, there is no one who can rival us in quality. The question of whether or not to use original spare parts is as old as the bottom line question. As a result of our wide range of vertical manufacture, the large majority of our spare parts are produced in-house. This guarantees uncompromising Kärcher quality and ensures maximum availability of your machine. A cheap replica spare part made by somebody else can become very expensive in the long term because of increased downtime or reduced performance.

2 Kärcher long-term availability

Like you, we assume that a Kärcher machine will last for a very long time. Accordingly, we keep our original spare parts in stock for an extremely long time. Much longer than required by law. This way, you can be certain that any spare part you require will be available for many years. And that it can be acquired quickly and easily. This is ensured by our efficient logistics service: with our headquarters in Germany and regional centres and infrastructures on all the main continents, any spare part can be with you in the shortest possible time.









1 Your Kärcher remains a Kärcher

The whole is more than the sum of its parts. Our machines are the perfect example. You will experience what makes a Kärcher every time you use yours: from its handling to its cleaning performance and its reliability. So that it stays this way, you should benefit from the perfect interplay between all the parts - through Kärcher original spare parts. After all, a chain is only ever as strong as its weakest link.

3 Always fits perfectly

How often do engineers despair when the spare parts don't fit? Kärcher original spare parts are always guaranteed to be the exact size, to fit accurately and without problems. It is equally important for us to design wear parts in the design phase in such a way that they can be used for repairs. A typical example are the sleeve and excess pressure limiter on high-pressure cleaners, which you can replace individually if they are worn, without having to change the entire cylinder head at once. This means that not only are our original spare parts a perfect fit, your repair costs are ideal too.

2 Safety means no compromises


Every machine and every part of our production process are 100 per cent tested quality. We manufacture in accordance with high technology standards using suitable materials and have a certified quality management system in accordance with ISO 9001. This includes, for example, welding according to the Pressure Equipment Directive, optimised HD hoses with increased abrasion resistance and longer service life as well as continuous monitoring by independent TÜV (German Technical Inspection Authority) experts. We do not compromise on safety. And you should not either.

4 Reliability means efficiency

How efficiently a machine works technically depends on its construction and precision in day-to-day operation, but especially on its reliability and availability. Nothing is more efficient than a machine whose full performance capacity can be utilised without any unforeseen interruptions. We are talking specifically about avoiding complications such as disruptions, downtime or loss of performance. Kärcher original spare parts guarantee ideal effectiveness as a result of precision, for example with twist spacings on heating coils and sustainable compliance with environmental standards in operations. A vacuum cleaner can cause major problems too if it fails to comply with its dust class because of a faulty filter.

KÄRCHER FINANCING SOLUTIONS: EXACTLY THE FINANCING YOU NEED.

In cooperation with well-known leasing partners we offer a variety of different financing solutions. Tailored to your individual requirements, we specifically find the financing that you need. Irrespective of which model you decide on, our financing solutions offer you many benefits.





No capital tie-up

42

You do not have to use any of your own capital for your new Kärcher equipment that you need for financing your operating resources. This extends your entrepreneurial scope. You pay low monthly instalments and have complete control of the costs.

The bank does not come into play

Invest without a bank loan, this is a good feeling and takes the pressure off you. Your collateral is available for other financing projects.

Everything from a single source

We supply you with the right machine for your cleaning tasks. We also look after the optimal financing, which can be ideally combined with our Kärcher service packages. You can concentrate on your core business.

Current machine fleet

At the end of the leasing contract you can return your machine and conclude a new contract. In this way your machine fleet is continuously renewed without huge investments.

Less administration costs

You receive a monthly invoice and can simply return the machine at the end of the contract. This reduces your administration costs and you don't have to think about the subsequent use of your machine.

Kärcher financing solutions No capital tie-up Bank-independent financing Everything from a single source Current machine fleet Less administration costs

KÄRCHER RENT: WE PROVIDE THE FLEXIBILITY.

Whether you rent or buy a Kärcher machine is not relevant. The crucial factor is what you need. And that it makes financial sense for you. With rental equipment you can use sales potential in the short term without tying up capital. Or protect your start-up capital as a founder of a new business. And you can always use a professional machine pool to meet changing requirements.





Our offer

- The optimal solution if you have higher cleaning requirements in the short term or also have to carry out special cleaning tasks at short ...
- A large selection of professional machines of all sizes and performance classes with compatible accessories.
- Machines that are configured to your seasonal and short-term requirements
- Thorough briefing and application advice in order to ensure that you can exhaust the full potential of the machine.

Kärcher Rent - Your benefits

- State-of-the-art machine fleet.
- Machines incl. full service are always ready for use.
- You don't have to worry about maintenance and repairs.
- Flexible rental periods: you rent your machines for as long as you actually need them.
- Cost security thanks to attractive fixed rental payments.
- No investment costs.
- The machines you need are available at short notice.
- All machines are optimally serviced, cleaned and maintained according to the K\u00e4rcher standard.

KÄRCHER USED: THE BENEFIT OF EXPERIENCE.

You rely on your Kärcher machine every day, even if it has been in use for a few years. Our used machines have also earned the same trust. As has Kärcher Used Equipment GmbH, because we are a wholly owned subsidiary of Alfred Kärcher SE & Co. KG. We are specialised in the professional, cost-oriented refurbishment and worldwide distribution of Kärcher used machines.





1 Ready for a second life

In our complete range you can find the right solution for every one of your Experience the same service you associate with new machines. With leasing, cleaning tasks. From the scrubber drier to the high-pressure cleaner and Because we know the full history, technical condition and particularities of each individual machine that we offer you. Our used machines are maintained exclusively with Kärcher original spare parts according to the Kärcher factory standard and comply with the statutory requirements.

2 Service as new

full service or any other service option you select, you receive the same vacuum cleaner. With fast delivery and precisely the service you need. You services and the same attention that you are accustomed to with your new receive machines from us with a warranty directly from the manufacturer. machine. Just let us know what you need. We will give you an individual consultation and provide you with a free, tailormade quote.




What makes used equipment so interesting

- Lower investments with faster amortisation.
- High machine availability, even if you do not use it constantly.
- Replacement machine for emergencies or spontaneous need.
- Save money without compromising on quality.
- Guaranteed Kärcher quality.
- Safety through warranty.
- Top price/performance ratio.

Trust from experience

The Kärcher name stands for trust. As a customer of Kärcher Used Equipment, you have unlimited access to the global Kärcher service network and the quick-response Kärcher customer service. Kärcher is Kärcher.



EASIER, FASTER, BETTER: THE NEW ACCESSORIES

We develop products that allow you to clean faster, more conveniently and more successfully. With less effort and therefore less physical strain, for example, or with shorter set-up times to save you lots of time. Current examples of this are our revolutionary EASY!Force high-pressure gun and the unique EASY!Lock quick-release couplings.



















EASY!Force high-pressure gun

Effortless, not energy-sapping: the EASY!Force HP trigger gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. So instead of adopting a tense working posture with your hand firmly closed around the trigger, your fingers can move freely. This prevents discomfort and extends the length of time you can work without stopping. Both the ball and the sealing seat of the valve in the EASY!Force Advanced high-pressure gun are ceramic, which is far harder than any conceivable foreign particle. This means the fully ceramic valve ensures a service life of around five times longer than that of other high-pressure

EASY!Lock quick-release couplings

With our patented EASY!Lock quick-release couplings, attachment and removal are five times faster than conventional screw connections, but equally as long-lasting and robust. The system combines the advantages of a quick coupling with the benefits of a thread, minimising set-up times and therefore significantly increasing convenience - without affecting safety and reliability. Having to interrupt work to look for lost seals is a thing of the past, as are additional spare part costs.



Optimal ergonomics is very EASY!

Working with high-pressure cleaners is extremely physically demanding. This is why ergonomics is so important. Holding the trigger of conventional HP trigger guns for long periods of time very quickly leads to fatigue, pain in your hands and a cramped working posture. This means that more demanding cleaning tasks are barely manageable without regular breaks or even a change of operator. Our EASY!Force technology has now changed this once and for all. Holding force is no longer needed and working with high pressure has never been easier. This has been scientifically confirmed by extensive comparison tests on the ergonomics of high-pressure guns. The University of Kassel certifies our EASY!Force high-pressure gun's outstanding handling properties and reduced physical strain on the user.



This has been validated using the subjective evaluations of test subjects as well as objective data from tracking force, motion and eye movements. The decisive advantage of our EASY!Force technology is that it relieves strain on the fingers, since operating the equipment with the ball of the thumb no longer requires a closed fist. No other high-pressure gun can do this. Relieving strain on the fingers also affects the wrist, elbows, shoulders and even the back. This results in vastly improved ergonomics, making work less tiring, more purposeful and more effective. At the same time, a considerable reduction in strain-related injuries (RSI = repetitive strain injury) can also be expected.

UNBEATABLY VERSATILE - HIGH-PRESSURE CLEANING WITH KÄRCHER

The name Kärcher is synonymous with performance, quality and innovation worldwide. As a pioneer of high-pressure cleaning, today Kärcher is the global market leader and has been continuously optimising the principle of high-pressure cleaning - for more power with lower consumption and a longer service life with shorter cleaning times. And for a product range that meets any demand with its innovative technology and versatility: mobile or stationary, using hot or cold water, with an electric motor or a combustion engine. Not to mention an extensive range of accessories that offers the right solution for every application.



Table of contents: High-pressure cleaners

Hot water high-pressure cleaners	Page	50
Cold water high-pressure cleaners	Page	74
High-pressure cleaner accessories	Page	118
Stationary high-pressure cleaners	Page	184
Stationary high-pressure cleaner accessories	Page	196
Ultra high-pressure cleaners	Page	206
Ultra high-pressure cleaner accessories	Page	214
Cleaning agents, care agents and disinfection	Page	842











Kärcher Super Class high-pressure cleaners are the right choice for users who have to carry out ongoing cleaning tasks involving large quantities of dirt and stubborn dirt.

Upright Class

Kärcher Compact Class high-pressure cleaners are the right choice for users Kärcher Special Class high-pressure cleaners are the right choice for who need a mobile high-pressure cleaner almost daily in various locations: users whose main requirements are power, safety and hygiene, and who a machine that is easy to transport despite its high power output.

machines with maximum portability for occasional use in various locations.

Easy to manoeuvre and transport, Kärcher Upright Class high-pressure

cleaners are the right choice for users who need powerful and robust

Middle Class

Kärcher middle class high-pressure cleaners are the right choice for users who require a machine with a large operating radius for daily cleaning of equipment or surfaces - with which they can also clean hard-to-reach places and which takes up little space in the yard or workshop.

Special Class

Super Class

need extremely high pressure for stubborn dirt or large water volumes for two-lance operation.

How to read the machine names


Model	Flow rate	/	Working pressure	Motor	Class	Drive		Equipm	ent
Example: HD	13	/	12	-4	St				
HD = Cold water HDS = Hot water, diesel heated HDS-E = Hot water, electr. heated HG = Hot water generator HWE = Hot water generator HDC = Stat. HP; multiple-lance operation			in MPa / 10 × bar e.g. 12 = 120 bar			G B/Be D/De Gas Gas LPG	= Gasoline = Gasoline/ electro start = Diesel/electro start = Gas = Liquid gas	Edition Cage Tr1 Ex H F/Food	= Standard equipment = Basic equipment d = Higher-level equipment = Edition machines = Robust tubular frame = Trailer, single-axle = Explosion-proof = With hot water supply = Food design c = Incl. surface cleaner FR Classic = Incl. dirt blaster
Model Ta	ank volume /	W	orking pressure	CI	ass D	rive			

AP = Multi-purpose cleaning in I **M** = Middle **Ep** = Mains operation (corded)

OUR PERFORMANCE PROMISE - WE CAN HANDLE PRESSURE.

We develop and produce our pumps and motors ourselves. In contrast to many of our competitors, our complete production process is kept in-house, and we use only carefully selected, high-quality materials for our products. The performance class of the specific high-pressure unit determines the material selection.







Brass cylinder head

All Kärcher professional machines are fitted with a brass cylinder head as standard. This is designed for strong performance and very long runtimes.



Cleaning agents

Our pumps are designed even for use with aggressive cleaning agents. This means we can guarantee the best cleaning result for every application.



Piston

We choose the material for our pistons depending on the requirements placed on our machines. In the low pressure range, stainless steel pistons guarantee optimal gliding characteristics and low wear, while ceramic pistons provide the required robustness even at high working pressures.



Perfect interplay

For each machine we design the perfect combination of high-pressure pump and electric motor. The resulting optimally designed operating point guarantees a long service life and maximum efficiency.



Quiet

The motor and pump are optimally coordinated to ensure low friction and consequently generate less noise.

EFFICIENT WITH HIGH PRESSURE. EVEN MORE EFFICIENT WITH HOT WATER

Kärcher high-pressure cleaners have impressive advantages over pressureless cleaning procedures when it comes to efficiency, cleaning results and eco-friendliness. Hot water high-pressure cleaners (HDS) further enhance these advantages considerably when cleaning surfaces that are encrusted with stubborn dirt. Kärcher HDS machines are the superior solution, particularly for cleaning off oils, fats and proteins. Making them just right for you.



Table of contents: Hot water high-pressure cleaners

HDS Super Class	Page	56
HDS Middle Class	Page	58
HDS Compact Class	Page	60
HDS Upright Class	Page	62
HDS trailers	Page	64
HDS Special Class	Page	68
HDS with combustion engine	Page	70
Accessories	Page	118
Cleaning agents	Page	842







1 Advantages of hot water



Better cleaning result

Hot water dissolves and emulsifies solidified oils and fats considerably better, making them easy to remove. Hot water is particularly effective in dissolving proteins and fats in the food industry.



Shorter working time

Hot water loosens dirt much faster, resulting in significant time savings of up to 35 per cent. This means that a variety of cleaning tasks can be performed efficiently and cost-effectively.



Use less cleaning agent

Fats, oils, resins, etc. can often be dissolved with just hot water. This means that significantly less cleaning agent needs to be used and, in some cases, it can be dispensed with all together. This protects the environment while saving money and resources.





All Kärcher hot water high-pressure cleaners can be operated with biodiesel. Biodiesel is produced from renewable resources and is CO₂-neutral. Emissions are significantly reduced because it has better combustion characteristics than conventional diesel. When you use biodiesel, you support environmental protection in a sustainable manner.



Germ-reducing effect

A significant reduction in germs can be demonstrated after cleaning with hot water. This germ reduction achieved without disinfectant is sufficient for many hygiene requirements.



Shorter drying time

Surfaces that are cleaned with hot water can be dried faster using heat, making them ready for further processing more quickly.



Surface protection

Delicate surfaces are protected and cleaned equally well but at a lower working pressure.

3 Weed removal with hot water



Hot water destroys weeds by quickly penetrating down to the roots, killing the plant proteins, causing lasting damage and wiping out the weeds.

- Environmentally friendly no herbicides.
- Gentle on surfaces.
- Saves time.

		Price	Order no.	Power supply (phases)	Flow rate (I/h)	Working pressure (bar/MPa)	Chassis with integrated fuel tan	Steam stage	Electro start	Integrated hose reel	Soft Damping System (SDS)	4-pole engine (low-speed machi Servo Control	EASVIForce Advanced trigger gu	Exhaust gas thermostat	Spray lance, rotatable	Triple nozzle	Power nozzle	Pole reverse plug (3 phases)	Dry-running protection	Page
	HDS Super Class			ш				1 - 1								-	_		\perp	_
4.5	HDS 13/20-4 S		1.071-927.0	3	600-1300	30-200/3-20			-	-						-		• •		57
	HDS 13/20-4 SX		1.071-932.0	3	600-1300	30-200/3-20			-							-				57
	HDS 12/18-4 S		1.071-914.0	3	600-1200	30-180/3-18			-	-			•			-				_
- Salar	HDS 12/18-4 SX		1.071-925.0	-	600-1200	30-180/3-18			-							-			-	_
	HDS Middle Class							_												
	HDS 10/20-4 M	1	1.071-900.0	3	500-1000	30-200/3-20			-	-						-				59
	HDS 10/20-4 MX		1.071-912.0	-	500-1000	30-200/3-20			-	\rightarrow	-			+ +	•	-			1	
0.0	HDS 9/18-4 M		1.077-911.0	3	450-900	30-180/3-18			-	\rightarrow	\rightarrow					-	-			-
423	HDS 9/18-4 MX		1.077-918.0	3	450-900	30-180/3-18			-	-	_		•			-	-			_
-	HDS 8/18-4 M		1.077-908.0	3	400-800	30-180/3-18	_		-	\rightarrow	\rightarrow		•	+ +	•	-			_	_
	HDS 8/18-4 MX		1.077-910.0	3	400-800	30-180/3-18			-	\rightarrow	\rightarrow			+	-	_	\rightarrow		-	-
	HDS 7/12-4 M		1.077-900.0	1	350-700	30-120/3-12	-	-	-	\rightarrow	\rightarrow	-	•	-	-	_	-	- -	-	_
	HDS 7/12-4 MX		1.077-906.0	1	350-700	30-120/3-12		-	_	-	-	-	-	-	-	_	-	-	_	_
	HDS Compact Class		1.077-300.0	1	330-700	30-120/3-12	-	-		-	-	-		-	-		-			1 33
	HDS 8/18-4 C	1	1.174-900.0	3	300-800	30-180/3-18			_	_ [-1	_ [– L	_ _		61
			1.174-906.0	3	300-800			-		\rightarrow	\rightarrow			-	-	\dashv	=		-	_
	HDS 8/18-4 CX			3	290-760	30-180/3-18		•	-	-		- 0	:	1 1	-	-	-	_	_	_
	HDS 8/17 C		1.174-911.0	3	290-760	30-170/3-17	-	╀	-	-	-	-		+	-	-	-		_	_
T. T.	HDS 8/17 CX		1.174-915.0	-		30-170/3-17	•	+-	-	\rightarrow	-	- 0	-	-	-	-	-	#:	1	-
6000	HDS 7/16 C		1.173-900.0	3	270-660	30-160/3-16	-	+-	-	\vdash	-	- 0		-		-	\rightarrow		_	_
	HDS 7/16 CX		1.173-904.0	3	270-660	30-160/3-16	•	+-	-	\rightarrow	-	- 0	-	+		-	-		_	_
	HDS 6/14-4 C		1.170-900.0	1	240-560	30-140/3-14	•		-	\rightarrow	\rightarrow		-	-		-	-	4	<u> </u>	_
	HDS 6/14-4 CX		1.170-902.0	1	240-560	30-140/3-14	•	-	-	\rightarrow	\rightarrow		-	-	-	\rightarrow	-	-	-	_
	HDS 6/14 C		1.169-900.0	1	240-560	30-140/3-14	•	-	-	\rightarrow	-	- 0		-		\rightarrow	-	-	_	_
	HDS 6/14 CX		1.169-905.0	1	240-560	30-140/3-14		-	-	-	-	- 0	•	-	•	_	•	-	•	_
	HDS 5/12 C		1.272-900.0	1	500	120/12			-	-		- -							1-	61
	HDS Upright Class	1				l .		1			٠,						4			
E	HDS 5/15 U		1.064-912.0	1	450	150/15	-	-	-	-	-	- -	•		\rightarrow	\rightarrow		- -	1-	63
1	HDS 5/15 UX		1.064-913.0	1	450	150/15	-	-	-		-	- -	•		\rightarrow			- -	1-	63
	HDS 5/13 U		1.064-908.0	1	500	125/12.5	-	-	-	-	-	- -	•	-	-	■		- -	1-	63
The same of	HDS 5/13 UX		1.064-909.0	1	500	125/12.5	-	-	-		-	- -	•	-	-	\rightarrow		- -	1-	63
	HDS 5/11 U		1.064-900.0	1	450	110/11	-	-	-	-	-	- -	•	-	-	\rightarrow		- -	<u> -</u>	63
	HDS 5/11 UX		1.064-901.0	1	450	110/11	_		-		-	<u>- -</u>	•					- -	<u> </u>	63
	HDS-Trailers					1					٠,					٠,	٠,			
	HDS 9/50 De Tr1		1.524-521.2	-	500-900	150-500/15-50	-	-			-	- -	Industry			-	-	-	_	_
TO BE	HDS 13/35 De Tr1		1.524-521.2	-	650-1300	100-350/10-35	-	-			-	- -	Industry			-	•	-	_	
1	HDS 17/20 De Tr1		1.524-952.2	-	900-1700	70-200/7-20	-	-			-	-	•	-		-	•	-	_	
1	HDS 13/20 De Tr1		1.524-952.2	-	900-1300	50-200/5-20	-	-			-	-	•			-		-		67
	HDS Special Class																			
0.0	HDS 2000 Super		1.071-934.0	3	800-1850	30-180/3-18	-		-	-	-	• •	•	-		-	-		•	68
	HDS-E 8/16-4 M 36 kW		1.030-906.0	3	300-760	30-160/3-16		-	-	-	-			-		-		-		69
-6	HDS-E 8/16-4 M 24 kW		1.030-904.0	3	300-760	30-160/3-16		-	-	-	-		•	-		-		-		69
1	HDS-E 8/16-4 M 12 kW		1.030-900.0	3	300-760	30-160/3-16		-	-	-	-		•	-		-		- 1		69
	HDS with combustion engine																			
- 4	HDS 1000 De		1.811-943.0	-	450-900	40-200/4-20	-	-		-	- [- 🔳		-		-	•	-	ı 🗀	70
	HDS 1000 Be		1.811-942.0	-	450-900	40-210/4-21	-	-		-	-	- =		-		-	•	-	ı -	70
	HDS 801 D		1.210-901.0	-	600	140/14	-	-	-	-	-	- -		-				- -	-	71
-	HDS 801 B		1.210-900.0	-	600	140/14	-	-	-	-	-	- -		-	•	\rightarrow		- -	-	71
A STATE OF THE STA	HG hot water generator			_								_		_						
2000	HG 64		1.030-510.0	1	300-1300	max. 220	-	-	_	_		- -	_		_	_	-	- -		73
	HG 43		1.030-500.0	-			-	+-	-	\vdash	-	+	_		+	_	_	\pm	+=	73
■ January d			1.030*300.0	1	200-1300	max. 200			Ĺ		-	1								1/3
■ included	in the scope of supply. \square Optional.																			











1 State-of-the-art burner technology

Hot water high-pressure cleaners from Kärcher undergo continuous further development. Thanks to the highly efficient burner and turbo blower, emissions can be lowered and fuel consumption reduced. The independent European Cleaning Machines Association has certified Kärcher, the world's first provider of hot water high-pressure cleaners, for efficiency and compliance with exhaust gas emissions standards. This guarantees:

- Highly efficient burners.
- Low fuel consumption.
- Low emissions.

2 Long-lasting pump engineering

All the pumps used in Kärcher high-pressure cleaners are manufactured in our own factories by specialists. This guarantees the highest "made by Kärcher" quality. The integrated soft damping hose smooths out hydraulic pressure fluctuations in the system, which guarantees a longer service life for the high-pressure cleaner.

3 Save energy and protect the environment

Kärcher's new hot water machines are the first series of hot water highpressure cleaners in the world and offer ecolefficiency. Simply set the main switch to ecolefficiency mode and the machine will change to the most economical temperature range (60 °C) while maintaining full water flow. The advantage of this is that the burner cycles are optimised to such an extent that fuel consumption is 20 per cent lower than in full load operation (80 °C).

4 Exemplary portability

Kärcher high-pressure cleaners are always raising the bar when it comes to portability. The HDS ranges of Compact, Middle and Super Class models are constructed using a "jogger" design with large rubber tyre wheels at the rear and castors at the front. The HDS Upright Class applies the tried-and-tested sack truck principle used in cold water machines to hot water machines for the first time. It also features ergonomic push handles and perfect weight distribution – ideal for guick and safe relocation with minimum effort. Transport is facilitated by forklift compatibility, transport eyelets and a tilting aid.

HDS SUPER CLASS



Super class top performance for non-stop use

Super class heated high-pressure cleaners offer optimum cleaning performance, easy handling and the latest technology, and are suitable for two-lance operation. Wherever dirt is present.



















1 High efficiency

- In eco!efficiency mode the machine operates in the most economical temperature range (60°C) - with full water flow.
- The burner cycles are optimised to reduce fuel consumption by 20% compared to full-load operation.

3 Maximum efficiency

- Highly efficient, tried-and-tested burner technology.
- Four-pole electric motor with three-piston axial pump.
- Water-cooled motor for a high level of performance and durability.

2 Reliability

- The Soft Damping System (SDS) compensates for vibration and pressure Spacious storage compartment, e.g. for cleaning agents, gloves or tools. peaks in the high-pressure system.
- Large, easy-to-reach water fine filter for protecting the pump against dirt particles in the water.
- Machine operational data (duration of use and required service intervals) can be retrieved.

4 Storage

- Within easy reach for left-handed/right-handed operators and ideal for two-spray lance operation.

TECHNICAL DATA AND EQUIPMENT

HDS 13/20-4 S HDS 13/20-4 SX HDS 12/18-4 S HDS 12/18-4 SX

Dual spray lance operation possible	Dual spray lance operation possible
Two detergent tanks	Two detergent tanks
■ Fronomical ecolefficiency mode	■ Fronomical ecolefficiency mode

Technical data			
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50
Connection load	kW	9.3	8.4
Flow rate	l/h	600-1300	600-1200
Working pressure	bar / MPa	30-200 / 3-20	30-180 / 3-18
Max. temperature	°C	80 / 155	80 / 155
Weight	kg	188.5 195	175.1 184
Dimensions (L × W × H)	mm	1330 × 750 × 1060	1330 × 750 × 1060
Fuel tank	I	25	25
Heating oil consumption, full load/ eco!efficiency	kg/h	8.3 / 6.6	7.7 / 6.2

Equipment			
Cleaning agent function		20 + 10 l tank	20 + 10 l tank
Spray gun		EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	10 20	10 20
High-pressure hose type		Long-life	Long-life
Spray lance	mm	1050	1050
Servo Control		•	•
Power nozzle		•	•
Dry-running protection		•	•
Pressure hose reel		- =	- =
Order no.		1.071-927.0 -932.0	1.071-914.0 -925.0
Price			

■ Included in the scope of supply.

Accessories Product name	Order no.	Description	Price
Automatic hose reel attachment kit, HDS M/S	2.110-011.0	Complete automatic hose reel attachment kit for HDS middle and super class. Simple installation, removable for transport, all unit functions are available. Offers maximum convenience when winding and unwinding the HP hose. Contains: automatic hose reel, HP hose and all connection parts.	FIICE
Additional handle for EASY!Lock spray lances	4.321-380.0	Comfortable in every situation - the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360° rotating spray lance, the additional handle can easily be rotated around its axis while working, which makes for greater flexibility.	
Hard Surface Cleaner FR 30 Me	2.111-013.0	High-quality, hot water-resistant surface cleaner with stainless steel casing, double ceramic bearing, non-marking steering rollers, integrated suction hose connection for suction of the spray water. Ideal for interior cleaning and use in the food industry. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 1,300 l/h / 85 °C.	
Rotating wash brush for > 800 l/h machines, nylon bristles	4.113-002.0	Powered by the water stream. For gently removing fine dust and grey film from any surface. Temperature resistant up to 60 °C (replaceable brush insert).	
Cup foam lance Advanced 042	2.112-018.0	Short, handy foam lance with 1-litre cleaning agent container directly on the lance. Thanks to its compact design, it is ideal for cleaning lorries with foam, for example. Rotary connection EASY!Lock, variable cleaning agent dosage via control directly on the lance, adjustable spray angle.	
Telescopic spray lance	4.112-037.0	Can be extended to any length between 1.8 and 5.4 m. For cleaning difficult-to-reach areas (e.g. ceilings, facades). With integrated high-pressure trigger gun and carrier belt.	
Quick coupling	2.115-000.0	For quickly switching between various spray lances/accessories. Perfect for the Karcher spray unit, suitable for the trigger gun/spray lance interface.	
Male coupling	2.115-001.0	Hardened stainless steel barb nipple for quick coupling 2.115-000.0	
Flame monitoring attachment kit for HDS Middle and Super Class	2.641-796.0	A light sensor monitors the burner flame. The fuel supply is shut off if the flame goes out.	
Remote control attachment kit for HDS Middle and Super Class	2.642-157.0	Remote control for the machines of the HDS middle and super class with the functions on/off, hot/cold water and cleaning agent on/off. For wall mounting.	
Coin remote control attachment kit for HDS Middle and Super Class	2.642-158.0	Retrofittable coin acceptor for machines in the HDS middle/super class for self-service operation. For installation on the machine.	

HDS MIDDLE CLASS

The middle class – consistent high-performance

If efficiency, power, operating comfort and durability are just as important to you as environmental protection: ideal for demanding cleaning tasks - from agriculture to industry.



















1 Efficiency

- In eco!efficiency mode the machine operates in the most economical temperature range (60°C) with full water flow.
- The burner cycles are optimised to reduce fuel consumption by 20% compared to full-load operation.

2 Maximum efficiency

- Highly efficient, tried-and-tested burner technology.
- Four-pole electric motor with three-piston axial pump.
- Water-cooled motor for a high level of performance and durability.

3 Operational safety

- The large, integrated water fine filter reliably protects the highpressure pump against small dirt particles.
- The integrated exhaust gas thermostat switches off the drive motor if the emission temperature exceeds 300 °C.
- The Soft Damping System (SDS) compensates for vibration and pressure peaks in the high-pressure system.

4 Storage

- Safe and ample storage for protective gear, accessories and cleaning agents
- Storage hooks for power cable and high-pressure hose.

TECHNICAL DATA AND EQUIPMENT

		HDS 10/20-4 M HDS 10/20-4 MX	HDS 9/18-4 M HDS 9/18-4 MX	HDS 8/18-4 M HDS 8/18-4 MX
		 Economical eco!efficiency mode Two detergent tanks Three-phase motor: water-cooled 	Economical eco!efficiency modeTwo detergent tanksThree-phase motor: water-cooled	Economical ecolefficiency modeAxial pump with turbo blowerThree-phase motor: air-cooled
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Connection load	kW	7.8	6.4	5.5
Flow rate	I/h	500-1000	450-900	400-800
Working pressure	bar / MPa	30-200 / 3-20	30-180 / 3-18	30-180 / 3-18
Max. temperature	°C	80 / 155	80 / 155	80 / 155
Weight	kg	168 172	158.7 164.1	159.3 164.9
Dimensions (L × W × H)	mm	1330 × 750 × 1060	1330 × 750 × 1060	1330 × 750 × 1060
Fuel tank	I	25	25	25
Heating oil consumption, full load/eco!efficiency	kg/h	6.4 / 5.1	5.8 / 4.6	5.3 / 4.2
Equipment				
Cleaning agent function		20 + 10 l tank	20 + 10 l tank	20 + 10 l tank
Spray gun		EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	10 20	10 20	10 20
High-pressure hose type		Long-life	Long-life	Long-life
Spray lance	mm	1050	1050	1050
Servo Control				
Power nozzle				
Dry-running protection		•		
Pressure hose reel		- =	- =	- =
Order no.		1.071-900.0 -912.0	1.077-911.0 -918.0	1.077-908.0 -910.0
Price				

■ Included in the scope of supply.

HDS 7/12-4 M HDS 7/12-4 MX

- Economical eco!efficiency mode
- Axial pump with turbo blower
- Two detergent tanks

Technical data		
Current type	Ph / V / Hz	1 / 230 / 50
Connection load	kW	3.4
Flow rate	l/h	350-700
Working pressure	bar / MPa	30-120 / 3-12
Max. temperature	°C	80 / 155
Weight	kg	155.5 161.5
Dimensions (L × W × H)	mm	1330 × 750 × 1060
Fuel tank	I	25
Heating oil consumption, full load/eco!efficiency	kg/h	4.6 / 3.7

Equipment		
Cleaning agent function		20 + 10 tank
Spray gun		EASY!Force Advanced
High-pressure hose	m	10 20
High-pressure hose type		Long-life
Spray lance	mm	1050
Servo Control		-
Power nozzle		
Dry-running protection		
Pressure hose reel		- ■
Order no.		1.077-900.0 -906.0
Price		

■ Included in the scope of supply.

HDS COMPACT CLASS

The compact class universal all-rounder

Our compact class hot water high-pressure cleaners are true allrounders. As universal professional machines, they meet virtually all of your individual cleaning needs.



















1 Efficiency

- ecolefficiency mode efficient and environmentally friendly, even when used for prolonged periods.
- Reduces fuel consumption and CO₂ emissions by 20%.
- Accurate cleaning agent dosing unit with clear rinse function.

3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cable and high-pressure hose.
- Integrated lance holder for transport.

2 Ease of use

- Intuitive operation thanks to the large single-button selector switch.
- Large tank opening with filling chute.
- Convenient system care bottle can be changed from the outside.

- The Soft Damping System (SDS) compensates for vibration and pressure peaks in the high-pressure system.
- Large water filter protects pump against damage.
- Water softening system protects the heating coil against calcification

TECHNICAL DATA AND EQUIPMENT

		HDS 8/18-4 C HDS 8/18-4 CX	HDS 8/17 C HDS 8/17 CX	HDS 7/16 C HDS 7/16 CX
		 Economical eco!efficiency mode Intuitive single-button selector switch Four-pole water-cooled electric motor 	 Economical ecolefficiency mode Intuitive single-button selector switch Powerful three-phase motor 	 Economical ecolefficiency mode Intuitive single-button selector switch Powerful three-phase motor
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Connection load	kW	6	5.7	4.7
Flow rate	l/h	300-800	290-760	270-660
Working pressure	bar / MPa	30-180 / 3-18	30-170 / 3-17	30-160 / 3-16
Max. temperature	°C	80 / 155	max. 80	max. 80
Weight	kg	119.4 122.8	114.4 109.6	105.8 111
Dimensions (L × W × H)	mm	1060 × 650 × 920 1250 × 650 × 920	1060 × 650 × 920 1215 × 650 × 920	1060 × 650 × 920 1215 × 650 × 920
Fuel tank	I	15	15	15
Heating oil consumption, full load/eco!efficiency	kg/h	5 / 4	4.7 / 3.8	4.1 / 3.3
Equipment				
Cleaning agent function		10 l tank	10 l tank	10 l tank
Spray gun		EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	10 15	10 15	10 15
Spray lance	mm	1050	1050	1050
Servo Control			-	-
Power nozzle		•	•	•
Triple nozzle		-	-	-
Pressure hose reel		- ■	- ■	- ■
Order no.		1.174-900.0 -906.0	1.174-911.0 -915.0	1.173-900.0 -904.0
Price				

■ Included in the scope of supply.

		HDS 6/14-4 C HDS 6/14-4 CX	HDS 6/14 C HDS 6/14 CX	HDS 5/12 C
		 Economical ecolefficiency mode Four-pole water-cooled electric motor 	 Economical ecolefficiency mode Intuitive single-button selector switch Extensive range of standard equipment 	 Economical ecolefficiency mode Intuitive single-button selector switch Entry-level model in the compact class
Technical data				
Current type	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50	1 / 230 / 50
Connection load	kW	3.6	3.6	2.9
Flow rate	I/h	240-560	240-560	500
Working pressure	bar / MPa	30-140 / 3-14	30-140 / 3-14	120 / 12
Max. temperature	°C	80 / 155	max. 80	80
Weight	kg	111 114.4	100 102	92
Dimensions (L × W × H)	mm	1060 × 650 × 920 1215 × 650 × 920	1060 × 650 × 920 1215 × 650 × 920	1060 × 650 × 920
Fuel tank	I	15	15	15
Heating oil consumption, full load/eco!efficiency	kg/h	3.5 / 2.8	3.5 / 2.8	3.2 / 2.6
Equipment				
Cleaning agent function		10 I tank	10 l tank	10 l tank
Spray gun		EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	10 15	10 15	10
Spray lance	mm	1050	1050	840
Servo Control		•	-	-
Power nozzle			•	-
Triple nozzle		-	-	
Pressure hose reel		-	- ■	-
Order no.		1.170-900.0 -902.0	1.169-900.0 -905.0	1.272-900.0
Price				
■ Included in the scope of supply.				

HDS 5/11 U

HDS UPRIGHT CLASS



The upright class for maximum mobility

These high-performance, robust upright machines offer outstanding manoeuvrability, easy transport and intuitive operation. Ideal for tradesmen, commercial use and contract cleaners.















3 Compact design

lacksquare Space-saving storage and transport

Ideal for small service vehicles.

■ Spill-proof pump and fuel tank for flat transport.



1 Innovative upright design

- Effortless transport over landings or stairs.
- Large wheels for unpaved surfaces.

2 Water fine filter

62

- Efficiently protects high-pressure pump against contamination.
- Easy to remove from outside.

- 4 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than screws.

TECHNICAL DATA AND EQUIPMENT

HDS 5/15 U

		HDS 5/15 UX	HDS 5/13 UX	HDS 5/11 UX
		Mobile entry-level modelSpace-saving upright designExhaust temperature monitoring	 Mobile entry-level model Space-saving upright design Exhaust temperature monitoring 	Mobile entry-level modelSpace-saving upright designExhaust temperature monitoring
Technical data				
Current type	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50	1 / 230 / 50
Connection load	kW	2.7	2.6	2.2
Flow rate	I/h	450	500	450
Working pressure	bar / MPa	150 / 15	125 / 12.5	110 / 11
Max. temperature	°C	max. 80	max. 80	max. 80
Weight	kg	71.4 72	65.7 68	61.4 69
Dimensions (L × W × H)	mm	618 × 618 × 994 620 × 620 × 1160	618 × 618 × 994 620 × 620 × 1160	618 × 618 × 994 620 × 620 × 1160
Fuel tank	I	6.5	6.5	6.5
Consumption of heating oil	kg/h	2.4	3.1	2.4

HDS 5/13 U

Equipment				
Cleaning agent function		Suction	Suction	Suction
Spray gun		EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	10 15	10 15	10 15
Spray lance	mm	840	840	840
Servo Control		-	-	-
Triple nozzle				
Pressure hose reel		- ■	- ■	- ■
Order no.		1.064-912.0 -913.0	1.064-908.0 -909.0	1.064-900.0 -901.0
Price				

■ Included in the scope of supply.

Accessories			
Product name	Order no.	Description	Pric
Additional handle for EASY!Lock spray lances	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360° rotating spray lance, the additional handle can easily be rotated around its axis while working, which makes for greater flexibility.	
Dirt blaster, large 035	4.114-040.0	Dirt blaster – rotating point jet – 10 times the cleaning performance. Maximum working time thanks to ceramic nozzle/bearing ring. Max. 300 bar / 30 MPa, 85 $^{\circ}$ C.	
Cup foam lance Advanced 042	2.112-018.0	Short, handy foam lance with 1-litre cleaning agent container directly on the lance. Thanks to its compact design, it is ideal for cleaning lorries with foam, for example. Rotary connection EASY!Lock, variable cleaning agent dosage via control directly on the lance, adjustable spray angle.	
Telescopic spray lance	4.112-037.0	Can be extended to any length between 1.8 and 5.4 m. For cleaning difficult-to-reach areas (e.g. ceilings, facades). With integrated high-pressure trigger gun and carrier belt.	
Quick coupling	2.115-000.0	For quickly switching between various spray lances/accessories. Perfect for the Kärcher spray unit, suitable for the trigger gun/spray lance interface.	
Male coupling	2.115-001.0	Hardened stainless steel barb nipple for quick coupling 2.115-000.0	
Rotating wash brush for < 800 l/h machines, natural bristles	4.113-003.0	Driven by the water stream. For gentle removal of fine dust and grey film on all surfaces. Temperature-resistant up to 60° C (replaceable brush insert).	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	6.110-008.0	Highly flexible high-pressure hoses for cleaning the inside of pipes (threaded connection for R 1/8" nozzle).	
Push-on wash brush	4.113-001.0	For all surface cleaning tasks. Clamps directly on to the spray lance.	
Hard Surface Cleaner FR 30 Me	2.111-013.0	High-quality, hot water-resistant surface cleaner with stainless steel casing, double ceramic bearing, non-marking steering rollers, integrated suction hose connection for suction of the spray water. Ideal for interior cleaning and use in the food industry. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 1,300 l/h / 85 °C.	

HDS-TRAILERS



Outstanding mobility and reliability on the road

The range of trailer-based hot water high-pressure cleaners represents extraordinary manoeuvrability and maximum userfriendliness. The reliable machines are efficient in use, making them ideal for municipalities, industry and construction.




















1 Maximum efficiency

- Tried-and-tested Kärcher burner technology with maximum efficiency. Large 500-litre water tank for up to 30 minutes of cleaning at full
- Heat recovery through the use of engine waste heat in hot water operation generates fuel savings of up to 14 per cent.
- Environmentally friendly operation and lower operating costs thanks to Yanmar diesel engine rated at 19 kW. the Kärcher eco!efficiency mode.

3 Independent of power and water supply

- 100-litre diesel tank ideal for long periods of use.

2 Easy handling

- EASY Operation: the trailer is operated using a central selector switch.
- Two hose reels in the operating area for fast attachment and removal.
- Generous storage space: protective gear, accessories and cleaning agents are always ready to hand and safely stored.

Custom machine configuration

- Thanks to custom configuration options, the trailer can be put together according to the customer's specific requirements.
- $\hfill \blacksquare$ Skid and Cab versions available, for example for transporting on truck
- Available with or without a diesel particle filter and spark arrestor.

CONFIGURATION OPTIONS

Different performance classes:

HDS 17/20 HDS 13/20 500 bar 350 bar 200 bar 200 bar 1300 l/h 1300 l/h 900 I/h 1700 I/h With optional automatic pres-With ontional automatic pres-With optional preparation for sure relief two-spray lance operation sure relief Hose reel Accessories package 30-metre high-pressure hose High-pressure hose reel Water inlet hose reel Power nozzle Spray gun Spray lance **Mobility:** Trailer

Emission regulations

Stationary frame with forklift

Without water tank

Without cover

The Yanmar diesel engines on Kärcher HDS trailers already meet the strict EU STAGE V emission regulations.

Water softening system

The automatic dosing of the PressurePro Machine Protector RM 110 protects the heating coil from calcification. This guarantees that the burner will have a long service life.

Heat recovery

Stationary frame with forklift

Integrated 500-litre water tank

With cover

An additional heat exchanger uses the waste heat from the engine to heat the water. This saves up to 14 per cent on fuel costs in hot water operation.

Antifreeze system

Thanks to the intelligent antifreeze system, the machine is extremely easy to prepare for the winter.

On the chassis

With cover

Integrated 500-litre water tank

With optional shock absorbers

A WIDE RANGE OF APPLICATIONS

A huge range of applications can be covered thanks to the custom configuration options. Here are just a few examples of how our new trailers impress with their flexibility and reliability.









1 Facade cleaning

- For example, removal of environmental pollution from car exhaust fumes, paraffins/oily deposits, calcium/soot/organic deposits such as moss, etc.
- Cleaning prior to facade renovation.
- Cleaning of churches, historical buildings, commercial buildings, residential buildings owned by housing associations, industrial buildings, noise-insulating walls, etc.

2 Construction machines and other equipment

- Cleaning of construction machines, in particular the removal of stubborn concrete or mortar residues.
- Cleaning of planking and scaffolding.

3 Public places and buildings

- Removal of oil stains/oil smears, chewing gum, organic growth, mud deposits and much more.
- Cleaning of car parks, bus stops, swimming pools, underground car parks (ceiling, walls and floor), pavements and patios.
- Weed removal with hot water in combination with a weed remover.

4 Traffic routes, railway stations and bridges

- Cleaning in railway stations, such as on platforms, underpasses and stairways.
- Cleaning of bridges as part of renovation work.
- Tunnels, roads and public spaces.

TECHNICAL DATA AND EQUIPMENT

On the 200-bar machines, the pressure and water volume can be regulated on the lance itself thanks to Servo Control. The machines that generate 350 or 500 bar feature speed-dependant pressure and water flow regulation. The 200-bar machines are also equipped with a cleaning agent dosing unit.



		HDS 9/50 De	HDS 13/35 De	HDS 17/20 De	HDS 13/20 De
		Speed reductionSpeed controlAs a trailer or stationary	Speed reductionSpeed controlAs a trailer or stationary	Speed reductionCleaning agent dosing unitServo Control	Speed reductionCleaning agent dosing unitServo Control
Technical data					
Engine manufacturer		Yanmar	Yanmar	Yanmar	Yanmar
Fuel		Diesel	Diesel	Diesel	Diesel
Motor rating	kW	19	19	19	19
Flow rate	I/h	500-900	650-1300	900-1700	900-1300
Working pressure	bar / MPa	150-500 / 15-50	100-350 / 10-35	70-200 / 7-20	50-200 / 5-20
Max. temperature	°C	85 / 98	85 / 98	80 / 98	85 / 98
Empty weight	kg	950	950	950	950
Dimensions (L × W × H)	mm	3646 × 1747 × 1735	3646 × 1747 × 1735	3646 × 1747 × 1735	3646 × 1747 × 1735
Diesel consumption, full load	kg/h	9.7	12.4	11.8	11.3
Diesel consumption, ecolefficiency mode	kg/h	7.5	9.3	9.7	8.2
Equipment					
Spray gun		Industrial trigger gun	Industrial trigger gun	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	30	30	30	30
Spray lance	mm	700	700	1050	1050
Power nozzle		•			
Servo Control		-	-	•	•
Pressure adjustment via speed regulation		•	•		
Order no.		1.524-521.2	1.524-521.2	1.524-952.2	1.524-952.2
Price					
■ Included in the scope of supply	□ Ontional				

■ Included in the scope of supply.

□ Optional.

HDS SPECIAL CLASS



The super class - the best machine for day-to-day multiple lance operation

Equipped with powerful pumps and efficient burner technology, the super class is used in industry, the construction sector, agriculture and large fleets (e.g. hauliers).














1 Duo drive concept

- 2 fatigue-tested, water-cooled three-phase motors.
- Delayed start prevents power supply overload.

2 Service control

- Electronic machine monitoring for protection against interference.
- Operating data logging with LED display of maintenance intervals based on operating hours.

HDS 2000 Super

- 2 powerful pump setsElectronic service control, with flame monitoring
- Cleaning agent dosing can be controlled from the trigger gun

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Connection load	kW	2 × 6.7
Flow rate	I/h	800-1850
Working pressure	bar / MPa	30-180 / 3-18
Max. temperature	°C	80 / 98
Weight	kg	304.7
Dimensions (L × W × H)	mm	1500 × 834 × 1015
Fuel tank	I	25
Heating oil or gas consumption, full load	kg/h	12.3

Equipment		
Cleaning agent function		25 I tank
Spray gun		EASY!Force Advanced
High-pressure hose	m	15
Spray lance	mm	1050
Servo Control		•
Power nozzle		1
Dry-running protection		•
Pressure hose reel		-
Order no.		1.071-934.0
Price		

■ Included in the scope of supply.

HDS SPECIAL CLASS



The exhaust-free specialist

The exhaust-free HDS-E 8/16-4 M with electrical boiler is used where exhaust gases are unwanted or prohibited. Thanks to innovative boiler insulation and Kärcher's ecolefficiency mode, it is easy both on budgets and the environment.













1 Particularly high working temperature

- Large water reservoir (max. 85°C).
- Up to 58°C in continuous operation under full load or 80°C with Servo Control.
- 2 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock guick-release couplings: durable and robust. And five times faster than screws.

	HDS-E 8/16-4 M 36 kW	HDS-E 8/16-4 M 24 kW	HDS-E 8/16-4 M 12 kW
	 Economical ecolefficiency mode Tilting aid Two cleaning agent tanks with automatic rinsing 	 Economical ecolefficiency mode Tilting aid Two cleaning agent tanks with automatic rinsing 	 Economical ecolefficiency mode High-speed heating chamber Two cleaning agent tanks with automatic rinsing
Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
kW	41.5	29.5	17.5
I/h	300-760	300-760	300-760
bar / MPa	30-160 / 3-16	30-160 / 3-16	30-160 / 3-16
°C	58 / 85	45 / 85	30 / 85
kg	123.5	122.1	119.7
mm	1330 × 750 × 1060	1330 × 750 × 1060	1330 × 750 × 1060
	20 + 10 l tank	20 + 10 l tank	20 + 10 l tank
	EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
m	10	10	10
mm	1050	1050	1050
		•	•
	•	•	•
	-	-	-
	1.030-906.0	1.030-904.0	1.030-900.0
	kW I/h bar / MPa °C kg mm	■ Economical ecolefficiency mode ■ Tilting aid ■ Two cleaning agent tanks with automatic rinsing Ph/V/Hz 3 / 400 / 50 kW 41.5 I/h 300-760 bar / MPa 30-160 / 3-16 °C 58 / 85 kg 123.5 mm 1330 × 750 × 1060 20 + 10 tank EASY!Force Advanced m 10 mm 1050 ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■	Economical ecolefficiency mode Tilting aid Two cleaning agent tanks with automatic rinsing Two cleaning agent tanks with automatic rinsing

■ Included in the scope of supply.

71



Middle class - tireless and professional

High-quality and reliable machine for diverse uses in construction, municipal, agriculture and forestry. Easy to mount on vehicles for space-saving use.













■ Included in the scope of supply.



HDS 1000 De

1 Optimum ease of use

- Automatic burner cut-out in case of water shortage and overheating.
- The ergonomically designed spray gun reduces holding and pulling force.

2 Maximum performance

■ High-output burner with upright heating coil and detonation-free continuous ignition.

HDS 1000 Be

For removing stubborn encrustations.

		1100 000 000	1155 1000 50
		 Diesel engine with electro start EASY!Force Professional high-performance hot water machine 	 Gasoline engine with electro start EASY!Force Professional high-performance hot water machine
Technical data			
Engine manufacturer		Yanmar	Honda
Motor type		L 100 V / diesel	GX 390 / gasoline
Motor rating	kW / hp	7.4 / 10	9.5 / 13
Flow rate	l/h	450-900	450-900
Working pressure	bar / MPa	40-200 / 4-20	40-210 / 4-21
Max. temperature	°C	80 / 98	80 / 98
Weight	kg	188.3	175.7
Dimensions (L × W × H)	mm	1100 × 750 × 785	1100 × 750 × 785
Consumption of heating oil	kg/h	5.6	5.6
Equipment			
Spray gun		EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	15	15
Power nozzle		•	•
Spray lance	mm	1050	1050
Servo Control		•	•
Switchable triple nozzle		-	-
Cage frame			T
Pressure hose reel		-	-
Order no.		1.811-943.0	1.811-942.0

HDS WITH COMBUSTION ENGINE



Compact class - reliable and economical

These entry-level mobile machines feature powerful, economical gasoline and diesel engines and offer useful safety features such as a safety valve against overpressure.











1 Maximum independence

- Efficient four-stroke gasoline or diesel engine with reversing starter.
- The right motor for the right job.

2 For the toughest jobs

- Sturdy tubular steel frame protects all components.
- Crane hook for use in the rental business and in construction, agriculture and forestry.

HDS 801 D

HDS 801 B

	Safety valve protects the unit against overpressureSturdy tubular frame for handling with crane
Hot water compact unit	■ Hot water compact unit

Technical data			
Engine manufacturer		Lombardini	Honda
Motor type		15 LD 225 / diesel	GX 160 K1 / gasoline
Motor rating	kW/hp	3.5 / 4.8	4 / 5.5
Flow rate	l/h	600	600
Working pressure	bar / MPa	140 / 14	140 / 14
Max. temperature	°C	max. 80	max. 80
Weight	kg	130	106.3
Dimensions (L × W × H)	mm	1168 × 862 × 767	1168 × 862 × 767
Consumption of heating oil	kg/h	4.1	4.1

Equipment			
Spray gun		EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	10	10
Power nozzle		-	-
Spray lance	mm	840	840
Servo Control		-	-
Switchable triple nozzle		Manual	Manual
Cage frame			•
Pressure hose reel		-	-
Order no.		1.210-901.0	1.210-900.0
Price			

HOT WATER GENERATOR



The hot water upgrade for your high-pressure cleaner


Whether it is under high pressure or not, hot water has higher cleaning power than cold water. We recommend an upgrade of the existing cold water high-pressure cleaner with our hot water generator for anyone who wants to use this additional benefit. It is connected at the outlet of the high-pressure cleaner and supplies up to 80 °C hot water. Very efficient with low emissions.













1 Durable and robust

72

- Highly efficient, tried-and-tested "Made in Germany" burner technology.
- Tried-and-tested Kärcher safety technology guarantees optimal protection of the machine and user.
- The sturdy tubular frame provides protection in continuous heavy-duty use.

2 Increased cleaning performance thanks to hot water

- $\hfill \blacksquare$ Shorter cleaning times and reduction of labour costs.
- More effective removal of oils, greases and lubricants.
- Germ-killing effect and protection of sensitive surfaces.

3 Especially easy to maintain

- Easy access to all service and maintenance components.
- $\hfill \blacksquare$ Integrated fuel filter and removable fuel tank for cleaning.

4 Very easy to use

- $\hfill \blacksquare$ Intuitive operation thanks to the large single-button selector switch.
- First-class mobility thanks to large wheels and castor with parking
- Storage possibilities for all accessory parts directly on the machine.

TECHNICAL DATA AND EQUIPMENT

HG 64

1.030-510.0

		 Very efficient and low-emission burner technology Robust frame protects even in the toughest working conditions 	 Very efficient and low-emission burner technology Robust frame protects even in the toughest working conditions
Technical data			
Current type	Ph / V / Hz	1 / 220 / 50	1 / 220 / 50
Heating output	kW	64	43
Fuel tank	1	20	20
Consumption of heating oil	kg/h	5.9	3.5
Max. pressure	bar / MPa	max. 220 / max. 22	max. 200 / max. 20
Max. temperature	°C	80	80
Weight	kg	124.2	88.1
Dimensions (L × W × H)	mm	880 × 680 × 860	880 × 680 × 860
Equipment			
Spray gun		Standard hot water	Standard hot water
High-pressure hose	m	10	10
Spray lance	mm	850	850

HG 43

1.030-500.0

■ Included in the scope of supply

Soft Damping System (SDS)

Order no.

*You can continue to use existing nozzles when operating your hot water generator with one of our cold water high-pressure cleaners. Otherwise, you can find the appropriate

Choosing the right nozzle:

			Flow rate of the cold wa	ter high-pressure cleaner				
		400-	700 l/h	700-1300 l/h				
		Nozzle size for HG	Order no.	Nozzle size for HG	Order no.			
	030	033	2.883-043.0	033	2.883-043.0			
aner	035	036	2.883-821.0	036	2.883-821.0			
e cle	040	042	2.883-831.0	042	2.883-831.0			
ssur	045	047	2.883-894.0	048	2.883-804.0			
-pre	050	054	2.883-927.0	054	2.883-927.0			
high	055	060	2.883-402.0	060	2.883-402.0			
ater	060	068	2.885-133.0	068	2.885-133.0			
S D	065	072	2.883-926.0	075	2.883-405.0			
of the cold water high-pressure cleaner	070	080	2.883-406.0	085	2.884-953.0			
of t	075	090	2.883-407.0	090	2.883-407.0			
size	080	100	2.883-408.0	100	2.883-408.0			
Nozzle	085	110	2.883-785.0	110	2.883-785.0			
ž	090	115	2.885-459.0	125	2.885-170.0			

COMPACT AND VERSATILE

Ideal for tradesmen, building service providers, small businesses and anyone else who needs to be mobile at work: our handy and powerful cold water high-pressure cleaners. Their rugged design, practical carrying handle and integrated accessory storage guarantee maximum flexibility of use with minimal weight. Kärcher quality on the go.




Table of contents: Cold water high-pressure cleaners

Table of Contents. Cold Water High-pressure C	icalici 3				
HD Super Class	Page	78	HD Cage Classic	Page	106
HD Middle Class	Page	80	HD Classic with combustion engine	Page	108
HD Compact Class	Page	90	iSolar solar panel cleaner	Page	110
HD Portable Class	Page	92	Water softening	Page	112
HD Trailer	Page	94	Barrel cleaner	Page	113
HD Cage Super Class	Page	96	Weed removal	Page	114
HD Cage Middle Class	Page	97	GS jet gun	Page	116
HD Cage Compact Class	Page	98	Multi-purpose cleaning machine	Page	117
HD Special Class	Page	99	Accessories	Page	118
HD Advanced with combustion engine	Page	102	Cleaning agents	Page	842
HD Classic	Page	104			
	HD Super Class HD Middle Class HD Compact Class HD Portable Class HD Trailer HD Cage Super Class HD Cage Middle Class HD Cage Compact Class HD Special Class HD Advanced with combustion engine	HD Super Class Page HD Middle Class Page HD Compact Class Page HD Portable Class Page HD Trailer Page HD Cage Super Class Page HD Cage Middle Class Page HD Cage Compact Class Page HD Special Class Page HD Advanced with combustion engine Page	HD Super Class Page 78 HD Middle Class Page 80 HD Compact Class Page 90 HD Portable Class Page 92 HD Trailer Page 94 HD Cage Super Class Page 96 HD Cage Middle Class Page 97 HD Cage Compact Class Page 98 HD Special Class Page 99 HD Advanced with combustion engine Page 102	HD Middle Class Page 80 HD Classic with combustion engine HD Compact Class Page 90 iSolar solar panel cleaner HD Portable Class Page 92 Water softening HD Trailer Page 94 Barrel cleaner HD Cage Super Class Page 96 Weed removal HD Cage Middle Class Page 97 GS jet gun HD Cage Compact Class Page 98 Multi-purpose cleaning machine HD Special Class Page 99 Accessories HD Advanced with combustion engine Page 102 Cleaning agents	HD Super Class Page 78 HD Cage Classic Page HD Middle Class Page 80 HD Classic with combustion engine Page HD Compact Class Page 90 iSolar solar panel cleaner Page HD Portable Class Page 92 Water softening Page HD Trailer Page 94 Barrel cleaner Page HD Cage Super Class Page 96 Weed removal Page HD Cage Middle Class Page 97 GS jet gun Page HD Cage Compact Class Page 98 Multi-purpose cleaning machine Page HD Special Class Page 99 Accessories Page HD Advanced with combustion engine Page 102 Cleaning agents Page







1 The right solution for any requirement

The modular design of our new HD middle class series means that we offer not only a standardised solution, but also the choice between different machine concepts depending on your requirements. You can choose between:

- Motor/pump unit (without chassis/wheels, push handle and accessories) for installation in production plants or as a stationary machine for wall mounting.
- Standard machine for mobile use in a range of applications.
- Cage machine in which the pump is protected by a stable metal frame; mobile and stationary versions available.

2 For independent use

Gasoline- or diesel-powered high-pressure cleaners from Kärcher can be used anywhere there is no power supply. If required, water can be siphoned directly from sources such as lakes, making the machines ideal for use in agriculture, construction, or in public sector.

3 Solutions for specific target groups

In addition to the standard range, Kärcher also offers target group-specific cold water high-pressure cleaners that are individually tailored to the requirements of different customers. The HD 10/15-4 Cage Food, for example, is used in the food industry as it boasts high performance values and hot water resistance of up to 85 °C. The high-pressure cleaner is also equipped with specially developed accessories that help satisfy the stringent hygiene regulations.

Hot or cold? Whatever you need

When working with high pressure, the impact pressure is key – perfect for removing non-adhesive soiling and large quantities of dirt such as dust, moss and soil. The advantages of high pressure are:

- Lower acquisition costs.
- No energy costs for hot water generation.
- Fewer components.
- More compact design.
- Cost-effective maintenance and repair.

		Price	Order no.	Power supply (phases)	Flow rate (I/h)	Max. pressure (bar/MPa)	Working pressure (bar/MPa)	Integrated cleaning agent tank (I)	Integrated high-pressure hose reel	Crankshaft pump	Infinitely variable pressure and water flow regulation on the machine	Servo Control	Dirt blaster	Spray gun	Spray lance, rotatable	High-pressure nozzle	Page
	HD Super Class		1		1											1	
_6	HD 17/14-4 S Plus		1.286-915.0	3	650-1700	154 / 15.4	30-140 / 3-14	-	-	-	-	•	•	EASY!Force Advanced	•	Power nozzle	79
	HD 17/14-4 SX Plus		1.286-931.0	3	650-1700	154 / 15.4	30-140 / 3-14	-	•	-	-	•	•	EASY!Force Advanced	•	Power nozzle	79
b/	HD 13/18-4 S Plus		1.286-932.0	3	650-1300	198 / 19.8	30-180 / 3-18	6	-	-	-	•	•	EASY!Force Advanced	•	Power nozzle	79
	HD 13/18-4 SX Plus		1.286-936.0	3	650-1300	198 / 19.8	30-180 / 3-18	6	•	-	-	•	•	EASY!Force Advanced	•	Power nozzle	79
	HD 10/25-4 S / S Plus		1.286-902.0 1.286-913.0	3	500-1000	275 / 27.5	30-250 / 3-25	6	-	-	-	•	□/■	EASY!Force Advanced	•	Power nozzle	79
	HD 10/25-4 SX Plus		1.286-927.0	3	500-1000	275 / 27.5	30-250 / 3-25	6	•	-	-	•	•	EASY!Force Advanced	•	Power nozzle	79
	HD 10/23-4 S / S Plus		1.286-922.0 1.286-923.0	3	1000	253 / 25.3	230 / 23	6	-	-	-	-	□/■	EASY!Force Advanced	•	Power nozzle	79
	HD 10/23-4 SX Plus		1.286-924.0	3	1000	253 / 25.3	230 / 23	6	•	-	-	-	•	EASY!Force Advanced	•	Power nozzle	79
	HD Middle Class		ı														
-b	HD 8/18-4 M / M Plus		1.524-970.0 1.524-972.0	3	250-760	230 / 23	30-180 / 3-18	-	-	-	-	•	□/■	EASY!Force	•	Power nozzle	8
D	HD 8/18-4 MX Plus		1.524-971.0	3	250-760	230 / 23	30-180 / 3-18	-	•	-	-	•	•	EASY!Force	•	Power nozzle	85
1	HD 7/16-4 M / M Plus		1.524-955.0 1.524-957.0	3	240-700	210 / 21	30-160 / 3-16	-	-	-	-	•	□/■	EASY!Force	•	Power nozzle	85
6	HD 7/16-4 MX Plus		1.524-956.0	3	240-700	210 / 21	30-160 / 3-16	-	•	-	-	•	•	EASY!Force		Power nozzle	85
	HD 7/17 M / M Plus		1.151-930.0 1.151-932.0	3	700	220 / 22	170 / 17	-	-	-	-	-	□/■	EASY!Force	•	Power nozzle	85
	HD 7/17 MX Plus		1.151-931.0	3	700	220 / 22	170 / 17	-	•	-	-	-	•	EASY!Force	•	Power nozzle	85
	HD 7/14-4 M / M Plus		1.524-930.0 1.524-932.0	1	690	190 / 19	140 / 14	-	-	-	-	-	□/■	EASY!Force	•	Power nozzle	85
	HD 7/14-4 MX Plus		1.524-931.0	1	690	190 / 19	140 / 14	-	•	-	-	-		EASY!Force	•	Power nozzle	85
	HD 6/15 M / M Plus		1.150-930.0 1.150-932.0	1	560	200 / 20	150 / 15	-	-	-	-	-	□/■	EASY!Force	•	Power nozzle	85
	HD 6/15 MX Plus		1.150-931.0	1	560	200 / 20	150 / 15	-		-	-	_	•	EASY!Force	-	Power nozzle	85
100	HD Middle Class St HD 8/18-4 M St		1.524-980.0	3	250-760	230 / 23	30-180 / 3-18	l_	l _	L	l _	l _	_	_	-	_	8:
-	HD 7/17 M St		1.151-950.0	3	700	220 / 22	170 / 17	-	-	-	-	-	-	_	-	_	87
2	HD 6/15 M St		1.150-950.0	1	560	200 /20	150 / 15	-	-	-	-	-	-	-	†-	-	87
	HD Middle Class Cage					'											
R	HD 8/18-4 M Cage ■		1.524-981.0	3	250-760	230 / 23	30-180 / 3-18	-	-	-	-		-	EASY!Force		Power nozzle	89
1	HD 7/16-4 M Cage ■		1.524-960.0	3	240-700	210 / 21	30-160 / 3-16	-	-	-	-	•	-	EASY!Force	•	Power nozzle	89
	HD 7/17 M Cage ■		1.151-960.0	3	700	220 / 22	170 / 17	-	-	-	-	-	-	EASY!Force	•	Power nozzle	89
10	HD 7/14-4 M Cage ■		1.524-942.0	1	690	190 /19	140 /14	-	-	-	-	-	-	EASY!Force	-	Power nozzle	_
	HD 6/15 M Cage		1.150-970.0	1	560	200 / 20	150 / 15	-	-	-	_	_	-	EASY!Force		Power nozzle	89
	HD Compact Class		1 520 040 0	1	FOC	200 / 20	170 / 17					l -		EACVIE	l -	Triple per-l	9:
K	HD 5/17 C HD 5/17 C Plus		1.520-940.0 1.520-941.0	1	500 500	200 / 20	170 / 17 170 / 17	-	-	1-	 	-	■	EASY!Force EASY!Force		Triple nozzle Triple nozzle	9:
77	HD 5/17 CX Plus		1.520-941.0	1	500	200 / 20	170 / 17	-	•	-	-	-	-	EASY!Force	-	Triple nozzle	-
1	HD 6/13 C		1.520-950.0	1	560	190 / 19	130 / 13	-	-	-	-	-	_	EASY!Force	▐	Triple nozzle	_
TIT.	HD 6/13 C Plus		1.520-951.0	1	560	190 / 19	130 / 13	-	-	-	-	-	•	EASY!Force		Triple nozzle	9:
100	HD 6/13 CX Plus		1.520-952.0	1	560	190 / 19	130 / 13	-	•	-	-	-	•	EASY!Force	•	Triple nozzle	9:
	HD 5/15 C		1.520-930.0	1	500	200 / 20	150 / 15	-	-	-	-	-		EASY!Force		Triple nozzle	9
	HD 5/15 C Plus		1.520-931.0	1	500	200 / 20	150 / 15	-	-	-	-	-	•	EASY!Force		Triple nozzle	9
	HD 5/15 CX Plus		1.520-932.0	1	500	200 / 20	150 / 15	-	•	-	-	-	•	EASY!Force	•	Triple nozzle	9:
	HD 5/12 C		1.520-900.0	1	500	175 / 17.5	120 / 12	-	-	-	-	_		EASY!Force		Triple nozzle	9
	HD 5/12 C Plus		1.520-901.0	1	500	175 / 17.5	120 / 12	-	-	-	-	-		EASY!Force	•	Triple nozzle	9
			1.520-902.0	1		175 / 17.5	120 / 12			T				EASY!Force		Triple nozzle	9

		Price	Order no.	Power supply (phases)	Flow rate (I/h)	Max. pressure (bar/MPa)	Working pressure (bar/MPa)	Integrated cleaning agent tank (I)	Integrated high-pressure hose reel	Crankshaft pump	Infinitely variable pressure and water flow regulation on the machine	Servo Control	Dirt blaster	Spray gun	Spray lance, rotatable	High-pressure nozzle	Page
	HD F (11 D		1 520 060 0	1	100	160 / 16	110 / 11					_		EASY!Force		Dower pozzlo	1 00
-	HD 5/11 P HD 5/11 P Plus		1.520-960.0 1.520-961.0	1		160 / 16 160 / 16	110 / 11 110 / 11	+-	-	_	_	_		EASY!Force	-	Power nozzle Power nozzle	93
-	HD-Trailers		1.520 501.0	1 -	1 430	100 / 10	110 / 11			Ш			_	ENST. Force	_	T OWET TIOZZIC	1 33
	HD 9/23 De Tr1 ■		1.524-954.2	-	400-930	250 / 25	40-230 / 4-23	-		-	-	•	_	EASY!Force Advanced	•	Power nozzle	95
	HD 9/23 Ge Tr1 ■		1.524-954.2	_	400-930	250 / 25	40-230 / 4-23	_		-	-	•		EASY!Force Advanced	•	Power nozzle	95
	HD Special Class									Ш				Advanced			
	HD 25/15-4 Cage Plus		1.353-907.0	3	500-2500	190 / 19	30-150 / 3-15	-	-	•	•	•	•	EASY!Force Advanced	•	Power nozzle	96
	HD 20/15-4 Cage Plus		1.353-906.0	3	500-2000	190 / 19	30-150 / 3-15	-	-	•	•	•	•	EASY!Force Advanced	•	Power nozzle	96
	HD 16/15-4 Cage Plus		1.353-905.0	3	500-1600	190 / 19	30-150 / 3-15	-	-	•	•	•	•	EASY!Force Advanced	•	Power nozzle	96
	HD 10/25-4 Cage Plus		1.353-902.0	3	1000	273 / 27.3	250 / 25	-	-	-	-	-	•	EASY!Force Advanced	•	Power nozzle	97
_	HD 715		1.353-909.0	3	250-700	175 / 17.5	10-150 / 1-15	-	-	-	•	-		EASY!Force	•	Triple nozzle	98
_	HD 10/16-4 Cage Ex		1.353-904.0	3	1000	220 / 22	160 / 16	-	-	•	-	-		EASY!Force Ex protection	•	Power nozzle	99
_	HD 10/15-4 Cage Food		1.353-908.0	3	440-990	175 / 17.5	20-145 / 2-14.5	-	-	-	-	•		EASY!Force Food	•	Power nozzle	100
	HD 7/10 CXF		1.151-906.0	3	250-700	120 / 12	10-100 / 1-10	-	•	-	-	•		EASY!Force Food	•	Triple nozzle	101
	HD with combustion engine																
_	HD 9/23 De		1.187-907.0	-	400-930	250 / 25	40-230 / 4-23	-	-	-	-	•		EASY!Force Advanced	•	Power nozzle	103
_	HD 9/23 G		1.187-906.0	-	400-930	250 / 25	40-230 / 4-23	-	-	-	-	•		EASY!Force Advanced	•	Power nozzle	103
_	HD 9/21 G		1.187-905.0	-	200-850	230 / 23	10-210 / 1-21	-	-	-	•	-		EASY!Force Advanced	•	Power nozzle	103
-	HD 8/20 G		1.187-904.0	-	200-750	230 / 23	10-200 / 1-20	-	-	-	•	-		EASY!Force Advanced		Power nozzle	103
	HD 7/15 G		1.187-903.0	-	650	160 / 16	150 / 15	-	-	-	-	-		EASY!Force Advanced	•	Power nozzle	103
	HD 728 B		1.187-908.0	-	650	160 / 16	150 / 15	-	-	-	-	-		EASY!Force Advanced	•	Triple nozzle	103
	HD Classic		1 267 200 0	٦	520,000	240 / 24	70 200 / 7 20			I 	_			Ctandand		Davis a name	1.05
-	HD 9/20-4 Classic		1.367-308.0 1.367-307.0	3		240 / 24	70-200 / 7-20 70-180 / 7-18	+	-		-	_		Standard Standard	-	Power nozzle Power nozzle	
-	HD 7/18-4 Classic			3		220 / 22 190 / 19		+	-	-	-	_		Standard	ļ-	Power nozzle	1
-	HD 6/15-4 Classic HD 7/11-4 Classic		1.367-306.0 1.367-305.0	1	1	150 / 15	70-150 / 7-15 70-110 / 7-11	+	-	-	-	_		Standard	- -	Power nozzle	-
-	HD 9/18-4 Cage Classic		1.367-315.0	3		240 / 24	70-180 / 7-18	+	-	_	-	_		Standard	+	Power nozzle	
-	HD 7/16-4 Cage Classic		1.353-913.0	3		220 / 22	70-160 / 7-16	-	-	Н	-	_		Standard	-	Power nozzle	
-	HD 7/11-4 Cage Classic		1.367-318.0	1		220 / 22	70-110 / 7-11	-	-		•	_		Standard	-	Power nozzle	+
-	HD 5/11 Cage Classic		1.520-204.0	1	-	160 / 16	110 / 11	-	_	_	_	-		Standard	-	Power nozzle	-
-	HD 8/23 G Classic		1.187-902.0	-	800	280 / 28	230 / 23	-	-		-	-		EASY!Force		Power nozzle	-
-	HD 7/20 G Classic		1.187-901.0	-	700	250 / 25	200 / 20	-	-	Ē	-	-		EASY!Force	•	Power nozzle	+
-	HD 6/15 G Classic		1.187-900.0	-	600	200 / 20	150 / 15	-	-	П	-	-		EASY!Force		Power nozzle	_

HD SUPER CLASS



Super class - perfect for tough jobs in non-stop use

Where vast amounts of dirt accumulate every day, reliable Kärcher Super class models provide indispensable services. Ideal for use in the construction, agricultural and forestry sectors as well as industry and municipal facilities.



















- 1 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than screws.
- 3 For increased safety
- $\hfill \blacksquare$ Integrated electronics system for machine monitoring.
- Automatic switch-off in case of low voltage range or overvoltage.
- Switches off in case of leaks or phase failure.

2 Proven Kärcher quality

- 4-pole water-cooled electric motor.
- Robust brass cylinder head and ceramic piston.
- Reinforced, unbreakable plastic chassis.

4 Outstanding mobility

- Large rubber wheels for negotiating uneven surfaces, stairs and
- Proven sack truck principle for easy, ergonomic transport.

TECHNICAL DATA AND EQUIPMENT

		HD 17/14-4 S Plus HD 17/14-4 SX Plus	HD 13/18-4 S Plus HD 13/18-4 SX Plus	HD 10/25-4 S HD 10/25-4 S Plus HD 10/25-4 SX Plus
		 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings. Water-cooled three-phase motor Outstanding flushing action 	 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings. Water-cooled three-phase motor Outstanding flushing action 	Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings. Water-cooled three-phase motor Maximum impact pressure for stubborn dirt
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Connection load	kW	9.4	9.2	9.2
Flow rate	I/h	650-1700	650-1300	500-1000
Working pressure	bar / MPa	30-140 / 3-14	30-180 / 3-18	30-250 / 3-25
Max. pressure	bar / MPa	154 / 15.4	198 / 19.8	275 / 27.5
Max. inlet temperature	°C	60	60	60
Weight	kg	72.2 76	70 73.6	68 68.6 73.8
Dimensions (L × W × H)	mm	560 × 500 × 1090	560 × 500 × 1090	560 × 500 × 1090
Equipment				
Cleaning agent function		6 I tank	6 I tank	6 I tank
Spray gun		EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	10 15	10 20	10 10 20
High-pressure hose type		Long-life	Long-life	-
Spray lance	mm	1050	1050	1050
Servo Control				
Switchable triple nozzle		-	-	-
Power nozzle		•		
Dirt blaster		•	•	-
Pressure hose reel		- =	- ■	- -
Order no.		1.286-915.0 -931.0	1.286-932.0 -936.0	1.286-902.0 -913.0 -927.0
Price				

■ Included in the scope of supply.

Tankaisal data

HD 10/23-4 S HD 10/23-4 S Plus HD 10/23-4 SX Plus

- Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- Water-cooled three-phase motor
- Features Kärcher power nozzle

recnnical data		
Current type	Ph / V / Hz	3 / 400 / 50
Connection load	kW	7.8
Flow rate	I/h	1000
Working pressure	bar / MPa	230 / 23
Max. pressure	bar / MPa	253 / 25.3
Max. inlet temperature	°C	60
Weight	kg	67 67.8 73
Dimensions (L × W × H)	mm	560 × 500 × 1090

Equipment		
Cleaning agent function		6 I tank
Spray gun		EASY!Force Advanced
High-pressure hose	m	10 10 20
High-pressure hose type		-
Spray lance	mm	1050
Servo Control		-
Switchable triple nozzle		-
Power nozzle		1
Dirt blaster		- 1 1
Pressure hose reel		- - ■
Order no.		1.286-922.0 -923.0 -924.0
Price		

■ Included in the scope of supply

HD MIDDLE CLASS



Middle class - excellent features

These Middle class machines are extremely mobile and userfriendly with low-speed four-pole AC or three-phase motors for continuous use.




















- 1 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than screws.
- 3 Powerful and durable
- Air/water-cooled electric motors for intensive use.
- Four-pole low-speed electric motor.

2 SwitchChem

80

- For precise and infinitely variable cleaning agent dosing.
- Two-way dosing valve for switching between different cleaning agents. Integrated lance holder for transport.
- Easy cleaning agent bottle changeover.

4 Clever features

- Power cord storage at the rear of the unit.
- Parking position for working interruptions.

TECHNICAL DATA AND EQUIPMENT

HD 9/20-4 M HD 9/20-4 M Plus HD 9/20-4 MX Plus

- Air/water-cooled motor
- Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- 3-piston pump with ceramic pistons


Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Connection load	kW	7
Flow rate	I/h	460-900
Working pressure	bar / MPa	40-200 / 4-20
Max. pressure	bar / MPa	220 / 22
Max. inlet temperature	°C	60
Weight	kg	54.2 54.8 57.6
Dimensions (L × W × H)	mm	554 × 425 × 1000 1000 × 425 × 552 554 × 509 × 1000

Price		
Order no.		1.524-924.0 -926.0 -927.0
Triple nozzle		Manual
Power nozzle		-
Spray lance	mm	1050
High-pressure hose	m	10 10 15
Spray gun		EASY!Force
Cleaning agent function		2 x 2.5 L
Equipment		

■ Included in the scope of supply.

THE HD MIDDLE CLASS: A TAILORED ALL-ROUNDER

Our HD middle class unites the classic strengths of a Kärcher high-pressure cleaner – robustness, power and reliability. The automatic pressure relief mechanism safeguards the pump components to ensure a longer service life, while the large water fine filter protects the pump from contamination. The flow-optimised high-pressure pump reduces pressure loss and increases the cleaning efficiency by up to 20 per cent. Our modular HD middle class cleaners are available as a stationary pump unit, an all-round machine, or in the robust cage design.





The pump unit for stationary use

From the simple and compact stationary machine to integrated high-pressure pumps in production processes – the pump units of our modular high-pressure middle class are distinguished by their reliability and durability. Effectively protected by a robust plastic chassis, they can take on the toughest jobs. The pump unit is mounted directly on the wall using the three-point support on the chassis

The versatile all-rounder

Reliable, robust and powerful while also being easy to use, flexible and easy to service. Our HD middle class is suitable for both vertical and horizontal operation and provides space for all the accessories, from the surface cleaner to the foam lance. Both the high-pressure pump and the electrics can be accessed quickly and easily.

The robust cage design

Users working in the cleaning and building trades value the cage versions of our high-pressure middle class. The extremely robust tubular steel frames effectively protect the machines against damage in harsh working conditions and during frequent transportation between different locations. The high-pressure pump is additionally protected against damage and soiling by the fully enclosed chassis. All of which helps to keep service costs and downtimes to a minimum.

HD MIDDLE CLASS



The HD middle class: customised all-rounder

Our middle-class high-pressure cleaners are characterised by their versatile application possibilities. Customers from industry as well as customers from the transport or construction sectors and even from the area of vehicle washes use the powerful, compact and longlife machines.



















1 High-quality equipment

- Automatic pressure relief for protecting the components extends their
- Powerful, 4-pole slow-running electric motor.
- High-quality brass cylinder head.

3 Flexible operation

- Designed for upright and horizontal operation.
- Maximum stability in horizontal operation as the wheels do not touch the ground.

2 Outstanding mobility

- Push handle can be retracted at the push of a button, thus increasing the compactness of the machine and reducing the space requirement.
- Effortless storage in service vehicles.
- Integrated storage options reduce the set-up times.

4 Clever accessory storage

- Bracket for fixing the cup foam lance.
- EASY!Lock TR20 allows the power nozzle or a surface cleaner to be stored directly on the machine.
- Practical nozzle compartment for holding the rotary nozzle.

TECHNICAL DATA AND EQUIPMENT

		HD 8/18-4 M HD 8/18-4 M Plus HD 8/18-4 MX Plus	HD 7/16-4 M HD 7/16-4 M Plus HD 7/16-4 MX Plus	HD 7/17 M HD 7/17 M Plus HD 7/17 MX Plus
		 Robust, 4-pole low-speed three-phase motor Servo Control: variable water and pressure volume regulation direct from the trigger gun. Automatic pressure relief and up to 20 percent higher energy efficiency 	 Robust, 4-pole low-speed three-phase motor Servo Control: variable water and pressure volume regulation direct from the trigger gun. Automatic pressure relief and up to 20 percent higher energy efficiency 	 3-piston axial pump with hardened stainless steel pistons Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings. Automatic pressure relief and up to 20 percent higher energy efficiency
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Connection load	kW	4.6	4.2	4.2
Flow rate	I/h	380-760	350-700	700
Working pressure	bar / MPa	30-180 / 3-18	30-160 / 3-16	170 / 17
Max. pressure	bar / MPa	270 / 27	240 / 24	255 / 25.5
Max. inlet temperature	°C	60	60	60
Weight	kg	40.3 41 43.4	40 40.9 43	32 31.9 35
Dimensions (L × W × H)	mm	455 × 400 × 700 400 × 455 × 700 455 × 400 × 966	455 × 400 × 700 400 × 455 × 700 455 × 400 × 966	455 × 400 × 700 400 × 455 × 700 455 × 400 × 966
Equipment				
Spray gun		EASY!Force	EASY!Force	EASY!Force
High-pressure hose	m	10 10 15	10 10 15	10 10 15
High-pressure hose type		Premium quality	Premium quality	Premium quality
Spray lance	mm	840	840	840
Servo Control		•	•	-
Power nozzle			•	
Dirt blaster		-	-	- ■ ■
Pressure hose reel		- -	- -	- -
Order no.		1.524-970.0 -972.0 -971.0	1.524-955.0 -957.0 -956.0	1.151-930.0 -932.0 -931.0
Price				

■ Included in the scope of supply.

		HD 7/14-4 M HD 7/14-4 M Plus HD 7/14-4 MX Plus	HD 6/15 M HD 6/15 M Plus HD 6/15 MX Plus
		 Four-pole, low-speed, robust AC motor Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings. Automatic pressure relief and up to 20 percent higher energy efficiency 	 3-piston axial pump with hardened stainless steel pistons Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings. Automatic pressure relief and up to 20 percent higher energy efficiency
Technical data			
Current type	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50
Connection load	kW	3.4	3.1
Flow rate	I/h	700	560
Working pressure	bar / MPa	140 / 14	150 / 15
Max. pressure	bar / MPa	210 / 21	225 / 22.5
Max. inlet temperature	°C	60	60
Weight	kg	38 39 42	30 30 33
Dimensions (L × W × H)	mm	455 × 400 × 700 400 × 455 × 700 455 × 400 × 966	400 × 455 × 700 400 × 455 × 700 455 × 400 × 966
Equipment			
Spray gun		EASY!Force	EASY!Force
High-pressure hose	m	10 10 15	10 10 15
High-pressure hose type		Premium quality	Premium quality
Spray lance	mm	840	840
Servo Control		-	-
Power nozzle			
Dirt blaster		-	-
Pressure hose reel		- - ■	- - ■
Order no.		1.524-930.0 -932.0 -931.0	1.150-930.0 -932.0 -931.0
Price			
■ Included in the scope of supp	nlv		

HD MIDDLE CLASS STATIONARY

As reliable and durable as it is simple and compact

Whether it is a solution for integrated high-pressure pumps in production processes or as a simple and compact stationary machine: our pump unit from the modular high-pressure middleclass range knows how to convince with reliability and durability. With effective protection thanks to a robust plastic chassis, it can also be used for tougher applications.



















1 High-quality equipment

- Automatic pressure relief for protecting the components extends their service life.
- Powerful, 4-pole slow-running electric motor.
- High-quality brass cylinder head.

2 Flexible operation

86

Designed for upright and horizontal operation.

3 Prepared for stationary operation

- Simple and robust 3-point attachment for wall mounting on the rear of unit.
- Space-saving, compact design.
- Robust plastic chassis reliably protects the pump against damage

4 Easy servicing

- Easy access to the cylinder head when bottom of machine is opened.
- Fast access to electrical box through simple removal of cover.
- Large, easy-to-reach water fine filter for protecting the pump against dirt particles in the water.

TECHNICAL DATA AND EQUIPMENT

		HD 8/18-4 M St	HD 7/17 M St	HD 6/15 M St
		 Robust, 4-pole low-speed three-phase motor Pump unit in a robust plastic chassis with three-point support for wall mounting Automatic pressure relief and up to 20 percent higher energy efficiency 	 3-piston axial pump with hardened stainless steel pistons Pump unit in a robust plastic chassis with three-point support for wall mounting Automatic pressure relief and up to 20 percent higher energy efficiency 	 3-piston axial pump with hardened stainless steel pistons Pump unit in a robust plastic chassis with three-point support for wall mounting Automatic pressure relief and up to 20 percent higher energy efficiency
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	1 / 230 / 50
Connection load	kW	4.6	4.2	3.1
Flow rate	I/h	760	700	560
Working pressure	bar / MPa	30-180 / 3-18	170 / 17	150 / 15
Max. pressure	bar / MPa	270 / 27	255 / 25.5	225 / 22.5
Max. inlet temperature	°C	60	60	60
Weight	kg	36	23.2	20.8
Dimensions (L × W × H)	mm	290 × 300 × 565	290 × 300 × 565	290 × 300 × 565
Equipment				
Spray gun		-	-	-
High-pressure hose		-	-	-
Spray lance		-	-	-
Servo Control			-	-
Power nozzle		-	-	-
Dirt blaster		-	-	-
Pressure hose reel				
Foam lance		_	-	-
Order no.		1.524-980.0	1.151-950.0	1.150-950.0
Price				

□ Available accessories.

HD MIDDLE CLASS CAGE



Cage: The robust protection against damage

Users, for example from the cleaning or building trades, value the cage versions of our modular high-pressure cleaners in the middle class range. The extremely robust tubular steel frames effectively protect the machines against damage during frequent transportation and the numerous, tough applications at constantly changing locations. All of which helps keep service costs and downtimes to a minimum.




















1 Durable and robust

- Sturdy tubular steel frame protects all components.
- The tubular steel frame is also suitable for simple fastening and lashing Fast access to electrical box through simple removal of cover. of the machine in the service vehicle.
- Robust plastic chassis reliably protects the pump against damage and

3 Easy servicing

- Easy access to the cylinder head when bottom of machine is opened.
- Large, easy-to-reach water fine filter for protecting the pump against dirt particles in the water.

2 High-quality equipment

- Automatic pressure relief for protecting the components extends their
- Powerful, 4-pole slow-running electric motor.
- High-quality brass cylinder head.

4 Increased energy efficiency

- Newly developed 3-piston axial pump with considerably reduced flow
- 20 percent increase in cleaning performance and energy efficiency.

TECHNICAL DATA AND EQUIPMENT

		HD 8/18-4 M Cage	HD 7/16-4 M Cage	HD 7/17 M Cage
		 Robust, 4-pole low-speed three-phase motor Robust, powder-coated tubular steel frame for maximum protection of pump unit Automatic pressure relief and up to 20 percent higher energy efficiency 	 Robust, 4-pole low-speed three-phase motor Robust, powder-coated tubular steel frame for maximum protection of pump unit Automatic pressure relief and up to 20 percent higher energy efficiency 	 3-piston axial pump with hardened stainless steel pistons Robust, powder-coated tubular steel frame for maximum protection of pump unit Automatic pressure relief and up to 20 percent higher energy efficiency
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Connection load	kW	4.6	4.2	4.2
Flow rate	l/h	760	350-700	700
Working pressure	bar / MPa	30-180 / 3-18	30-160 / 3-16	170 / 17
Max. pressure	bar / MPa	270 / 27	240 / 24	255 / 25.5
Max. inlet temperature	°C	60	60	60
Weight	kg	45	43	36
Dimensions (L × W × H)	mm	460 × 420 × 970	460 × 420 × 970	460 × 420 × 970
Equipment				
Spray gun		EASY!Force	EASY!Force	EASY!Force
High-pressure hose	m	10	10	10
High-pressure hose type		Premium quality	Premium quality	Premium quality
Spray lance	mm	840	840	840
Servo Control		-		-
Power nozzle				
Dirt blaster		-	-	-
Pressure hose reel		-	-	-
Foam lance		-	-	-
Order no.		1.524-981.0	1.524-960.0	1.151-960.0
Price				

-	Included	in	tho	ccopo	of	cunnly
	IIICIUUCU	1111	LITE	acohe	UI	suppry.

		HD 7/14-4 M Cage	HD 6/14-4 M Cage	HD 6/15 M Cage
		 Four-pole, low-speed, robust AC motor Robust, powder-coated tubular steel frame for maximum protection of pump unit Automatic pressure relief and up to 20 percent higher energy efficiency 	 Four-pole, low-speed, robust AC motor Robust, powder-coated tubular steel frame for maximum protection of pump unit Automatic pressure relief and up to 20 percent higher energy efficiency 	 Four-pole, low-speed, robust AC motor Robust, powder-coated tubular steel frame for maximum protection of pump unit Automatic pressure relief and up to 20 percent higher energy efficiency
Technical data				
Current type	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50	1 / 230 / 50
Connection load	kW	3.1	3.1	3.1
Flow rate	l/h	700	600	560
Working pressure	bar / MPa	140 / 14	160 / 16	150 / 15
Max. pressure	bar / MPa	210 / 21	240 / 24	225 / 25
Max. inlet temperature	°C	60	60	60
Weight	kg	42	42	33
Dimensions (L × W × H)	mm	460 × 420 × 970	460 × 420 × 970	460 × 420 × 970
Equipment				
Spray gun		EASY!Force	EASY!Force	EASY!Force
High-pressure hose	m	10	10	10
High-pressure hose type		Premium quality	Premium quality	Premium quality
Spray lance	mm	840	840	840
Servo Control		-	-	-
Power nozzle				
Dirt blaster		-	-	-
Pressure hose reel		-	-	-
Foam lance		-	-	-
Order no.		1.524-942.0	1.524-940.0	1.150-970.0
Price				
■ Included in the scope of supply.				

HD COMPACT CLASS



Practical. Everywhere

Light, compact, mobile and versatile. For vertical and horizontal operation. With clever accessory storage and long service life thanks to the brass cylinder head and automatic pressure relief.

















1 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.

- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than screws.

3 Flexibility

- Vertical and horizontal operation possible.
- The wheels are not on during horizontal operation. As such, the machine offers maximum stability.
- Separate park and transport position for the spray unit.

2 Mobility

- Integrated carrying handle on the front of the machine enables easy loading and convenient transport.
- Push handle can be retracted at the push of a button.
- Compact construction.

4 Quality

- The automatic pressure relief protects the components and extends the service life of the machine.
- High-quality brass cylinder head.
- Large, easy-to-reach water fine filter for protecting the pump against dirt particles in the water.

TECHNICAL DATA AND EQUIPMENT

		HD 5/17 C HD 5/17 C Plus HD 5/17 CX Plus	HD 6/13 C HD 6/13 C Plus HD 6/13 CX Plus	HD 5/15 C HD 5/15 C Plus HD 5/15 CX Plus
		 Automatic pressure relief For horizontal and vertical operation Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings. 	 Automatic pressure relief For horizontal and vertical operation Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings. 	 Automatic pressure relief For horizontal and vertical operation Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
Technical data				
Current type	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50	1 / 230 / 50
Connection load	kW	3	2.9	2.8
Flow rate	I/h	480	590	500
Working pressure	bar / MPa	170 / 17	130 / 13	150 / 15
Max. pressure	bar / MPa	200 / 20	190 / 19	200 / 20
Max. inlet temperature	°C	60	60	60
Weight	kg	26 26.2 27.9	25.7 28.8 28.3	25.7 25.7 28.3
Dimensions (L × W × H)	mm	380 × 360 × 930 380 × 360 × 930 380 × 370 × 930	380 × 360 × 930 380 × 360 × 930 380 × 370 × 930	380 × 360 × 930 380 × 360 × 930 380 × 370 × 930
Equipment				
Cleaning agent function		Suction	Suction	Suction
Spray gun		EASY!Force	EASY!Force	EASY!Force
High-pressure hose	m	10 10 15	10 10 15	10 10 15
Spray lance	mm	840	840	840
Servo Control		-	-	J
Switchable triple nozzle		Manual	Manual	Manual
Power nozzle		-	-	-
Dirt blaster		-	-	-
Pressure hose reel		- -	- - -	- -
Order no.		1.520-940.0 -941.0 -942.0	1.520-950.0 -951.0 -952.0	1.520-930.0 -931.0 -932.0
Price				

■ Included in the scope of supply.

HD 5/12 C HD 5/12 C Plus HD 5/12 CX Plus

- Automatic pressure reliefFor horizontal and vertical operation
- Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.

Technical data		
Current type	Ph / V / Hz	1 / 230 / 50
Connection load	kW	2.5
Flow rate	l/h	500
Working pressure	bar / MPa	120 / 12
Max. pressure	bar / MPa	175 / 17.5
Max. inlet temperature	°C	60
Weight	kg	24.4 24.7 26.1
Dimensions (L × W × H)	mm	380 × 360 × 930 380 × 360 × 930 380 × 370 × 930

Equipment		
Cleaning agent function		Suction
Spray gun		EASY!Force
High-pressure hose	m	10 10 15
Spray lance	mm	840
Servo Control		-
Switchable triple nozzle		Manual
Power nozzle		-
Dirt blaster		-
Pressure hose reel		- - ■
Order no.		1.520-900.0 -901.0 -902.0
Price		

■ Included in the scope of supply.

HD PORTABLE CLASS



Maximum performance and minimum space

High-pressure cleaner with compact design and low weight - the best prerequisites for mobile applications. Ideal for tradesmen. With automatic pressure relief.

















1 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.

- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than screws.

3 Flexibility

- Vertical and horizontal operation possible.
- Separate park and transport position for the spray unit.
- The machine offers maximum stability in horizontal operation.

2 Excellent mobility

92

- The integrated carrying handle on the front of the machine enables easy loading and convenient transport.
- Compact construction and low weight.

4 Quality

- The automatic pressure relief protects the components and extends the service life of the machine.
- High-quality brass cylinder head.

TECHNICAL DATA AND EQUIPMENT

■ Included in the scope of supply.

HD 5/11 P **HD 5/11 P Plus**

- Automatic pressure relief
- Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.

Technical data		
Current type	Ph / V / Hz	1 / 230 / 50
Connection load	kW	2.2
Flow rate	l/h	490
Working pressure	bar / MPa	110 / 11
Max. pressure	bar / MPa	160 / 16
Max. inlet temperature	°C	60
Weight	kg	20.6 20.8
Dimensions (L × W × H)	mm	351 × 312 × 904

Equipment		
Spray gun		EASY!Force
High-pressure hose	m	10
Spray lance	mm	840
Servo Control		-
Switchable triple nozzle		-
Power nozzle		I
Dirt blaster		-
Pressure hose reel		-
Order no.		1.520-960.0 -961.0
Price		

Accessories Product name	Order no.	Description	Price
Cup foam lance Advanced 042	2.112-018.0	Short, handy foam lance with 1-litre cleaning agent container directly on the lance. Thanks to its compact design, it is ideal for cleaning lorries with foam, for example. Rotary connection EASY!Lock, variable cleaning agent dosage via control directly on the lance, adjustable spray angle.	
High-pressure hose 2 × EASY!Lock DN 8, 315 bar, 10 m, ANTI!Twist	6.110-031.0	High-pressure hose with EASY!Lock hand screw connection at both ends.	
FR 30 Surface Cleaner	2.111-011.0	Up to 10 times greater area coverage compared with the conventional high-pressure jet. Plastic casing for optimal manoeuvrability, double ceramic bearing for long working times, flexible connection joint for optimal handling and integrated parking position. Machine-specific nozzle kit must be ordered separately. Max. 180 bar $/$ 850 l/h $/$ 60 °C.	
Quick coupling	2.115-000.0	For quickly switching between various spray lances/accessories. Perfect for the Kärcher spray unit, suitable for the trigger gun/spray lance interface.	
Male coupling	2.115-001.0	Hardened stainless steel barb nipple for quick coupling 2.115-000.0	
Pipe cleaning hose, ID 6, 20 m, max. 140 bar	6.110-049.0	Particularly flexible high-pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8").	
Pipe cleaning dirt blaster D 25 / 040	6.415-944.0	With R-1/8" connection for attachment to pipe cleaning hose. 1 x forward rotary nozzle, 3 x 30° backwards.	
Rotating wash brush for < 800 l/h machines, nylon bristles	4.113-004.0	Driven by the water jet. For gentle removal of fine dust and grey film on all surfaces. Temperature- resistant up to 60 °C (replaceable brush insert).	
Telescopic spray lance	4.112-037.0	Can be extended to any length between 1.8 and 5.4 m. For cleaning difficult-to-reach areas (e.g. ceilings, facades). With integrated high-pressure trigger gun and carrier belt.	

HD-TRAILERS

Self-sufficient, mobile and suitable for long periods of work



On new construction sites, for municipal use in parks and inner-city spaces and, of course, for a wide range of requirements from machine rental customers: our highly mobile, trailer-based cold water high-pressure cleaners are the ideal machines in any location where there is no power or water supply. Extremely powerful, independent and with large reserves for long operation time.



















1 Independent of an external power or water supply

- Powerful Yanmar diesel or Honda gasoline engines (both EU STAGE V) Reliable, tried-and-tested Kärcher high-pressure technology with a long enable independent operation
- 1000-litre water tank for at least one hour of work at full performance. Optional front bracket and plate and rear cover for additional
- Integrated trailer concept for high mobility and maximum independ-

3 Robust design for harsh working conditions

- service life
- protection of the machine.
- The integrated antifreeze system enables use all year round.

2 Easy and comfortable to use

- Extremely easy to use and therefore ideal for use in machine rental
- Convenient equipment details such as engine electro start and high-pressure hose reel.
- Accessories and fuel canisters, for example, can be kept in the storage compartment in the rear.

Multiple configurations possible

- Flexible and tailor-made configurations for specific customer require-
- For use on truckbeds or for installation in vehicles a cab version is also available.
- Upon request, the tanks can also be designed in special colours.

CONFIGURATION OPTIONS

Different engine versions:

HD 9/23 De HD 9/23 Ge Yanmar diesel engine Honda gasoline engine 230 bar 230 bar 930 l/h 930 l/h

Standard accessory packet

15-metre high-pressure hose EASY!Force Advanced spray gun Spray lance

Power nozzle

Dirt blaster

30-metre high-pressure hose EASY!Force Advanced spray gun Spray lance Power nozzle



Options (ex works)

High-pressure hose reel

Tarpaulin for the rear Protective guard and

splashback for front

Crane hook

20-litre canister with transport lock

Elapsed time counter

Shock absorber

Mobility:

Stationary frame with forklift pockets Integrated 1000-litre

Trailer

On the chassis Integrated 1000-litre

With optional shock absorbers

1.524-954.2

		HD 9/23 De Tr1	HD 9/23 Ge Tr1
Technical data			
Engine manufacturer		Yanmar	Honda
Motor type		L100 V / diesel	GX 390 / gasoline
Motor rating	kW / hp	7.4 / 10	9.5 / 13
Flow rate	I/h	400-930	400-930
Working pressure	bar / MPa	40-230 / 4-23	40-230 / 4-23
Max. inlet temperature	°C	60	60
Empty weight	kg	500	500
Dimensions (L × W × H)	mm	3560 × 1496 × 1484	3560 × 1496 × 1484
Equipment			
Spray gun		EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	15/30	15/30
Spray lance	mm	1050	1050
Servo Control			

1.524-954.2

■ Included in the scope of supply.

Power nozzle

Order no.



Cage super class - for the toughest jobs

The Cage super class provides high mobility and outstanding performance for prolonged operating periods. Exceptionally high water flow rate quickly removes stubborn dirt and soiling.













1 Cage frame

- Robust outer pipe frame.
- With integrated crane hook and accessory compartment.
- 2 Electronic monitoring for greater operational safety.
- Leakage protection and soft start.
- Overvoltage and undervoltage protection.

		HD 25/15-4 Cage Plus	HD 20/15-4 Cage Plus	HD 16/15-4 Cage Plus
		 High-grade steel frame Automatic soft start, leakage protection, dry-running protection, protection against two-phase short circuit Puncture-proof wheels for maximum mobility 	 Powder-coated tubular steel frame Automatic soft start Puncture-proof wheels for maximum mobility 	 Powder-coated tubular steel frame 4-pole air-cooled electric motor Puncture-proof wheels for maximum mobility
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Connection load	kW	12.5	11	9.5
Flow rate	I/h	500-2500	500-2000	500-1600
Working pressure	bar / MPa	30-150 / 3-15	30-150 / 3-15	30-150 / 3-15
Max. pressure	bar / MPa	190 / 19	190 / 19	190 / 19
Max. inlet temperature	°C	60	60	60
Weight	kg	120	110	110
Dimensions (L × W × H)	mm	957 × 686 × 1080	957 × 686 × 1080	957 × 686 × 1080
Equipment				
Spray gun		EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	15	15	15
Spray lance	mm	1050	1050	1050
Power nozzle				
Order no.		1.353-907.0	1.353-906.0	1.353-905.0
Price				

■ Included in the scope of supply.

HD CAGE MIDDLE CLASS



Cage middle class - for really tough jobs

Machine with sturdy frame and crane attachment point for tough jobs on difficult terrain. Ideal for removing stubborn dirt in the construction industry, agriculture, forestry and municipal facilities.














- Ergonomic handle and hose storage.
- Protection against damage to the machine.

2 Water fine filter

- Protects high-pressure pump from dirt ingress.
- Easy to use, easy to clean

HD 10/25-4 Cage Plus

- With integrated crane attachment point
- Heavy-duty equipment
- Highest pressure in its class

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Connection load	kW	9.2
Flow rate	l/h	max. 1000
Working pressure	bar / MPa	max. 250 / max. 25
Max. pressure	bar / MPa	273 / 27.3
Max. inlet temperature	°C	60
Weight	kg	57.4
Dimensions (L × W × H)	mm	547 × 543 × 1104

Equipment		
Spray gun		EASY!Force Advanced
High-pressure hose	m	10
Spray lance	mm	1050
Servo Control		-
Switchable triple nozzle		-
Power nozzle		
Dirt blaster		ı
Pressure hose reel		-
Order no.		1.353-902.0
Price		

■ Included in the scope of supply.

HD CAGE COMPACT CLASS

Cage compact class can be used everywhere

These special class machines with robust tubular frame are ideal for complex building site use. The integrated handle ensures easy transport on scaffolding and easy loading by crane.











1 Cage frame

- Robust, portable tubular steel frame.
- Integrated carrying handle and crane hook.

Wall mounting

- Space-saving storage.
- Safe storage of machine and accessories.

HD 715

- Specially designed for painters and facade cleaners
- Rotatable stainless steel spray lance
- Infinitely variable pressure regulation

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Connection load	kW	4.7
Flow rate	I/h	250-700
Working pressure	bar / MPa	10-150 / 1-15
Max. pressure	bar / MPa	175 / 17.5
Max. inlet temperature	°C	60
Weight	kg	32.8
Dimensions (L x W x H)	mm	500 × 310 × 350

Dimensions (L × W × H)	mm	500 × 310 × 350
Equipment		
Spray gun		EASY!Force
High-pressure hose	m	15
Spray lance	mm	840
Servo Control		-
Switchable triple nozzle		Manual
Power nozzle		-
Dirt blaster		-
Pressure hose reel		-
Order no.		1.353-909.0
Price		

■ Included in the scope of supply.

HD SPECIAL CLASS



Cage Ex for potentially explosive atmospheres

This machine complies with all safety requirements for use in potentially explosive atmospheres. Technical features and accessories are tailored to meet these special requirements.











- 1 Powder-coated cage frame, electrically conductive
 - Robust tubular steel frame.
 - With integrated crane hook.
 - 2 Explosion-proof equipment
 - Conductive rubber tyres.
 - Surface temperature always under 200 °C.

HD 10/16-4 Cage Ex

- Explosion protection II 2 G c T3
- Crankshaft pump with ceramic pistons
- 4-pole air-cooled electric motor

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Connection load	kW	5.5
Flow rate	I/h	1000
Working pressure	bar / MPa	160 / 16
Max. pressure	bar / MPa	220 / 22
Max. inlet temperature	°C	50
Weight	kg	122.6
Dimensions (L × W × H)	mm	980 × 720 × 1100

Equipment		
Spray gun		EASY!Force Ex protection
High-pressure hose	m	10
Spray lance	mm	1050
Servo Control		-
Switchable triple nozzle		-
Power nozzle		
Dirt blaster		-
Pressure hose reel		-
Order no.		1.353-904.0
Price		

■ Included in the scope of supply.

HD SPECIAL CLASS



Cage Food - for intensive use in the food industry

The high-performance HD 10/15-4 Cage F is resistant to hot water up to 85 °C and ideal for use in the food industry; all components in contact with water are food-grade.















All parts that come into contact with water are made from special food-grade

2 Particularly effective cleaning

- Advance pressure pump for inlet temperature of up to 85 °C.
- Approved for RM 734 chlorinated cleaning agent.

HD 10/15-4 Cage Food

- Grease-resistant high-pressure hose
- 2 cleaning agent tanks with rinse function

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Connection load	kW	6.4
Flow rate	l/h	440-990
Working pressure	bar / MPa	20-145 / 2-14.5
Max. pressure	bar / MPa	175 / 17.5
Max. inlet temperature	°C	85
Weight	kg	78.4
Dimensions (L × W × H)	mm	650 × 521 × 1100

Dimensions (L × W × H)	mm	650 × 521 × 1100
Equipment		
Spray gun		EASY!Force Food
High-pressure hose	m	10
Spray lance	mm	1050
Servo Control		
Switchable triple nozzle		-
Power nozzle		
Dirt blaster		-
Pressure hose reel		-
Order no.		1.353-908.0
Price		

■ Included in the scope of supply.

HD SPECIAL CLASS



Compact food class - for strict hygiene requirements

Cold water high-pressure cleaner for all-purpose use in the sanitary/food industry. This compact machine allows you to regulate pressure and water volume seamlessly.











101

- 1 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than
- 2 Hygiene requirements
- Integrated hose reel with food-grade pressure hose and robust, grey wheels.
- Water inlet temperature up to 80 °C.

HD 7/10 CXF

- For sanitary/hygiene/food industry
- Grey, non-marking wheels

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Connection load	kW	4.5
Flow rate	l/h	250-700
Working pressure	bar / MPa	10-100 / 1-10
Max. pressure	bar / MPa	120 / 12
Max. inlet temperature	°C	80
Weight	kg	33.3
Dimensions (L × W × H)	mm	360 × 375 × 925

Equipment		
Spray gun		EASY!Force Food
High-pressure hose	m	15
Spray lance	mm	840
Servo Control		I
Switchable triple nozzle		Manual
Power nozzle		-
Dirt blaster		-
Pressure hose reel		I
Order no.		1.151-906.0
Price		

■ Included in the scope of supply.

HD ADVANCED WITH COMBUSTION ENGINE



Full power. Anywhere, anytime - even without power

If you require the highest cleaning performance regardless of power supply, you will always be on the safe side with our robust Advanced range of cold water high-pressure cleaners with combustion engine



















1 Maximum independence

- nal power supply.
- Can suck up water e.g. from lakes or ponds and use it for cleaning.

2 Optimum ease of use

- The ergonomic frame concept makes transport on uneven ground
- Storage possibilities for all accessory parts directly on the machine.
- Puncture-proof wheels guarantee permanently high mobility.

3 Highly versatile

- Fitted with reliable Honda or Yanmar engines for use without an exter- Optional cage frame with eyelets for crane loading reliably protects the
 - Hose reel attachment kit for shorter set-up & finishing-off times available as an optional extra.
 - Portable version with robust tubular frame specially designed for painters and plasterers (HD 728 B).

4 For the toughest jobs

- Robust basic frame for daily use in tough conditions.
- Large water filter to protect the pump.
- Thermostat valve to protect the pump from overheating in recirculation

TECHNICAL DATA AND EQUIPMENT

	Economical diesel engine with convenient electro start Infinitely variable water pressure and water flow regulation with Servo Control on the high-pressure lance	 Infinitely variable water pressure and water flow regulation with Servo Con- trol on the high-pressure lance Automatic speed reduction 	 Robust, powder-coated tubular frame Infinitely variable water pressure and
	Automatic speed reduction	Puncture-proof wheels for maximum mobility	water flow regulation on the machine Puncture-proof wheels for maximum mobility
	Yanmar	Honda	Honda
	L 100 V/diesel	GX 390/gasoline	GX 340/gasoline
kW / hp	7.4 / 10	9.5 / 13	8 / 11
l/h	400-930	400-930	200-850
bar / MPa	40-up to 230 / 4-up to 23	40-up to 230 / 4-up to 23	10-up to 210 / 1-up to 21
°C	60	60	60
kg	105.3	63.4	63.8
mm	800 × 700 × 800	870 × 725 × 1170	870 × 725 × 1170
	EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
m	15	15	15
mm	1050	1050	1050
			-
	•	•	•
	-	-	-
	-	-	-
	-	-	-
	1.187-907.0	1.187-906.0	1.187-905.0
	I/h bar / MPa °C kg mm	L 100 V/diesel kW / hp 7.4 / 10 I/h 400-930 bar / MPa 40-up to 230 / 4-up to 23 °C 60 kg 105.3 mm 800 × 700 × 800 EASY!Force Advanced m 15 mm 1050	L 100 V/diesel GX 390/gasoline kW / hp 7.4 / 10 9.5 / 13 I/h 400-930 400-930 bar / MPa 40-up to 230 / 4-up to 23 40-up to 230 / 4-up to 23 °C 60 60 kg 105.3 63.4 mm 800 × 700 × 800 870 × 725 × 1170 EASY!Force Advanced EASY!Force Advanced m 15 15 mm 1050 1050 ——————————————————————————————————

■ Included in the scope of supply. * Available accessories.

		HD 8/20 G	HD 7/15 G	HD 728 B Cage
		Robust, powder-coated tubular frame Infinitely variable water pressure and water flow regulation on the machine Puncture-proof wheels for maximum mobility	 Robust, powder-coated tubular frame Precise cleaning agent dosage Puncture-proof wheels for maximum mobility 	Robust, powder-coated tubular framePortableStainless steel lance
Technical data				
Engine manufacturer		Honda	Honda	Honda
Motor type		GX 270/gasoline	GX 160/gasoline	GX 160/gasoline
Motor rating	kW/hp	6.6 / 9	4 / 5.5	4 / 5.5
Flow rate	l/h	200-750	650	650
Working pressure	bar / MPa	10-up to 200 / 1-20	150 / 15	150 / 15
Max. inlet temperature	°C	60	60	60
Weight	kg	52.2	40.5	34.5
Dimensions (L × W × H)	mm	750 × 580 × 555	800 × 620 × 1105	570 × 434 × 430
Equipment				
Spray gun		EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	15	10	10
Spray lance	mm	840	840	600
Servo Control		-	-	-
Power nozzle		•		-
Switchable triple nozzle		-	-	Manual
Optional cage frame*		-	-	-
Optional hose reel*		-	-	-
Order no.		1.187-904.0	1.187-903.0	1.187-908.0
Price				

■ Included in the scope of supply. * Available accessories.

HD CLASSIC



Powerhouses through and through

Kärcher Classic high-pressure cleaners feature powerful and reliable crankshaft pumps with ceramic pistons. These innovative, high performance pumps are not only highly efficient, but also impress with excellent reliability and long service intervals thanks to the latest sealing technology.
















1 Durable and robust

- Ceramic pistons for reduced wear and tear.
- High performance sealing packages for longer working times.

3 Improved cleaning performance

- Extra large crankshafts and connecting rods with robust ball bearings. force than conventional nozzles.
 - High area coverage and thorough dirt removal.

2 Especially easy to maintain

- Wide-opening machine cover for easy access to all service and mainte- Large wheels and ergonomic push handle ensure optimal turning nance-relevant components.
- Large water fine filter for optimal protection of the pump.
- Integrated nozzle storage.

4 Excellent mobility

- manoeuvrability and easy handling.
- The foldable push handle enables space-saving storage.

TECHNICAL DATA AND EQUIPMENT

		HD 9/20-4 Classic	HD 7/18-4 Classic	HD 6/15-4 Classic
		 Durable crankshaft pump with ceramic-coated pistons Large, transparent water filter Infinitely variable pressure regulation 	 Durable crankshaft pump with ceramic-coated pistons Large, transparent water filter Infinitely variable pressure regulation 	 Durable crankshaft pump with ceramic-coated pistons Large, transparent water filter Infinitely variable pressure regulation
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	1 / 220-240 / 50
Connection load	kW	6.9	4.9	3.4
Flow rate	I/h	520-900	520-700	450-600
Working pressure	bar / MPa	70-200 / 7-20	70-180 / 7-18	70-150 / 7-15
Max. pressure	bar	240	220	190
Max. inlet temperature	°C	60	60	60
Weight	kg	56	56	52
Dimensions (L × W × H)	mm	709 × 469 × 1000	700 × 455 × 1010	709 × 469 × 1000
Equipment				
Spray gun		standard	standard	standard
High-pressure hose	m	10	10	10
Spray lance	mm	600	840	850
Switchable triple nozzle		-	-	-
Power nozzle		•	•	•
Dirt blaster		-	-	-
Pressure hose reel		-	-	-
Servo Control		-	-	-
Order no.		1.367-308.0	1.367-307.0	1.367-306.0
Price				

■ Included in the scope of supply.

HD 7/11-4 Classic

- Durable crankshaft pump with ceramic-coated pistons
- Large, transparent water filter
- Infinitely variable pressure regulation

Technical data		
Current type	Ph / V / Hz	1 / 220-240 / 50
Connection load	kW	2.9
Flow rate	l/h	520-700
Working pressure	bar / MPa	70-110 / 7-11
Max. pressure	bar	150
Max. inlet temperature	°C	60
Weight	kg	52
Dimensions (L × W × H)	mm	700 × 455 × 1010

Equipment		
Spray gun		standard
High-pressure hose	m	10
Spray lance	mm	850
Switchable triple nozzle		-
Power nozzle		•
Dirt blaster		-
Pressure hose reel		-
Servo Control		-
Order no.		1.367-305.0
Price		

■ Included in the scope of supply.

HD CAGE CLASSIC


Robust. Flexible. Reliable



The Cage Classic range is sure to impress with its powerful crankshaft pumps and ceramic pistons. A water filter protects the pump. Mounting on a wall is possible thanks to a robust tubular frame construction. Now available: HD 7/11-4 Cage Classic with single-phase motor.








- 4-pole electric motor.
- Brass cylinder head and ceramic piston.

2 Robust and secure

- Robust tubular frame construction guarantees optimum protection of the machine.
- Built-in handles for transport.



\blacksquare Included in the scope of supply.

HD CAGE CLASSIC

Small, light, robust and affordable



Not only does the HD 5/11 Cage Classic offer high performance for little money, but because of its light weight and the ergonomic handle, it is extremely easy to carry and very robust.







1 Durable and robust

- With its brass cylinder heads, the 3-piston axial-piston motor unit ensures an exceptionally long service life.
- The sturdy pipe frame provides protection in continuous heavy-duty use.

2 Versatile

- The machine can be attached to the floor or the wall.
- $\hfill \blacksquare$ Very compact construction style and minimal weight.

HD 5/11 Cage Classic

- Continuous use possible thanks to durable axial pump
- Robust frame protects even in the toughest working conditions
- Ergonomically designed handle

Technical data		
Current type	Ph / V / Hz	1 / 230 / 50
Connection load	kW	2.2
Flow rate	I/h	500
Working pressure	bar / MPa	up to 110 / up to 11
Max. pressure	bar / MPa	160 / 16
Max. inlet temperature	°C	60
Weight	kg	21.3
Dimensions (L × W × H)	mm	475 × 335 × 340

Equipment		
Spray gun		standard
High-pressure hose	m	10
Spray lance	mm	600
Power nozzle		1
Order no.		1.520-204.0
Price		

■ Included in the scope of supply.

HD CLASSIC WITH COMBUSTION ENGINE

Mobile, independent and service-friendly

The Classic range with combustion engine can be used anywhere that there is no access to a power supply. This makes it the ideal solution for construction, industry and agriculture.

















1 High level of autonomy

- Can be used independently of a power supply thanks to powerful gasoline engines.
- example from ponds and lakes.

3 Outstanding mobility

- Ergonomic push handle for easier transport.
- Large wheels with pneumatic tyres for uneven surfaces.
- The layout of the wheels makes it possible to transport the machine

2 Accessories concept

- Practical intake for hose and high-pressure lance directly on the
- Storage compartment for nozzles, tools and other small parts.

4 Easy to service and durable

- Robust crankshaft pump with proven Kärcher quality.
- Large water filter protects pump against damage.
- Thermostat valve to protect the pump from overheating in recirculation mode.

TECHNICAL DATA AND EQUIPMENT

		HD 8/23 G Classic	HD 7/20 G Classic	HD 6/15 G Classic
		Tubular steel frameRobust crankshaft pump	Tubular steel frameRobust crankshaft pump	Tubular steel frameRobust crankshaft pump
Technical data				
Motor type		G300FA / gasoline	G250FA / gasoline	G200FA / gasoline
Motor rating	kW / hp	6.8 / 9.25	5.2 / 7.1	4.1 / 5.6
Flow rate	I/h	800	700	600
Working pressure	bar / MPa	230 / 23	200 / 20	150 / 15
Max. pressure	bar	280	250	200
Max. inlet temperature	°C	60	60	60
Weight	kg	55.2	46	42.6
Dimensions (L × W × H)	mm	799 × 637 × 1097	799 × 637 × 1097	799 × 637 × 1097
Equipment				
Spray gun		EASY!Force	EASY!Force	EASY!Force
High-pressure hose	m	10	10	10
Spray lance	mm	840	840	840
Power nozzle			•	•
Order no.		1.187-902.0	1.187-901.0	1.187-900.0
Price				

■ Included in the scope of supply.


iSolar SOLAR PANEL CLEANER

9

Clean modules - secure yields

The first cleaning system to be approved for photovoltaic plants by the German Agricultural Society. Sophisticated Kärcher cleaning solutions ensure uncompromisingly clean solar modules – and up to 20 per cent higher yields than with heavily soiled modules.











1 Contra-rotating disc brushes

- Very high cleaning power and area performance.
- Optimal handling thanks to lateral force compensation.
- Pre-rinsing of the adjacent modules.

3 Articulated joint

- Convenient working in different positions.
- Limit stop protects the modules from damage.
- Excellent manoeuvrability due to flexible articulated joint.

2 Carbon/hybrid telescopic lances

- Very large working range and maximum rigidity with low weight.
- Brush operation and speed regulation via integrated ball valve.
- $\hfill \blacksquare$ Quick and convenient extension thanks to quick-release couplings.

4 Modular construction

- $\hfill \blacksquare$ Needs-based combination of individual components.
- Suitable for standard M 18 or M 22 interfaces.
- Compatible with numerous HD/HDS machines.

TECHNICAL DATA AND EQUIPMENT

		iSolar 400	iSolar 800	Fall protection
		 Water-powered disc brush with ball bearing Compact entry-level model for smaller surfaces M 18 × 1.5 connection; compatible with standard HD/HDS machines 	 Contra-rotating disc brushes with ball bearing Robust brass articulated joint for flexible working angles Excellent manoeuvrability 	 Certified, standard-compliant safety system Travelling fall arrestor with shock absorber Robust metal box for storage and transport
Technical data				
Weight	kg	2.8	7	-
Working width	mm	400	800	-
Machine flow rate with HD/HDS	I/h	700-1000 / 1100-1300	700-1000 / 1100-1300	-
Length	m	-	-	-
Connector		M 18 × 1.5 female thread	M 18 × 1.5 female thread	-
Material		-	-	-
Equipment				
Required accessories, internal high-pressure hose		-	-	-
Articulated joint		□ (4.481-039.0)	•	-
Storage box		-	-	•
Order no.		6.368-456.0 / 6.368-457.0	6.368-454.0 / 6.368-455.0	6.988-152.0
Price				

■ Included in the scope of supply.

Available accessories.

		iSolar TL 7 H	iSolar TL 10 H TL 10 C	iSolar TL 14 C
		 Glass/carbon-fibre composite for high rigidity and high strength with low weight Ergonomic handle with ball valve for consummate ease of use Easy deployment thanks to quick-release couplings and internal high-pressure hose 	 High-quality hybrid or full carbon telescopic lance Ergonomic handle with ball valve for consummate ease of use Easy deployment thanks to quick-release couplings and internal high-pressure hose 	 Full carbon material for maximum rigidity, strength and working range Ergonomic handle with ball valve for consummate ease of use Easy deployment thanks to quick-release couplings and internal high-pressure hose
Technical data				
Weight	kg	3.5	4 3.7	5
Working width	mm	-	-	-
Machine flow rate	I/h	-	-	-
Length	m	1.8-7.2	2.4-10.2	2.4-14
Connector		M 18 × 1.5 male thread / M 22 × 1.5 male thread	M 18 × 1.5 male thread / M 22 × 1.5 male thread	M 18 × 1.5 male thread / M 22 × 1.5 male thread
Material		Hybrid	Hybrid Carbon	Carbon
Equipment				
Required accessories, internal high-pressure hose		6.392-978.0	6.392-977.0	6.392-976.0
Lance segments		5	5	7
Storage box		-	-	-
Order no.		4.107-054.0	4.107-053.0 4.107-055.0	4.107-052.0
Order no. with EASY!Lock		4.110-004.0	4.110-003.0 4.110-007.0	4.110-002.0
Price				

113

WATER SOFTENING

For a perfect shine

The Kärcher water softening system with resin filter produces water that dries without leaving residue or scale marks. Available with or without a semi-automatic regeneration station for multiple filter use.

1 Resin filter

- Efficient water softening solution.
- Drying without leaving lime residue.
- Repeated use thanks to simple regeneration.

2 Softening vehicle

- Mobile and easy-to-transport complete system with pneumatic wheels.
- Sophisticated tubular frame construction (e.g. for draining antifreeze).
- Large water fine filter for protection against coarse dirt particles.

		WS 50	WS 100	WS Regenerator
		 Residue-free drying after cleaning Excellent mobility and easy to transport Powder-coated tubular steel frame with large pneumatic-tyred wheels 	 Residue-free drying after cleaning Excellent mobility and easy to transport Powder-coated tubular steel frame with large pneumatic-tyred wheels 	 Semi-automatic regeneration of the resin filter Easy handling (plug 'n' play) Efficient solution for intensive use
Technical data				
Weight	kg	35	40	5.8
Dimensions (L × W × H)	mm	550 × 550 × 1030	550 × 550 × 1030	250 × 300 × 460
Inlet pressure	bar	0-10	0-10	-
Work temperature	°C	1-50	1-50	-
Capacity (at 10 °dH)	1	5000	10000	-
Regeneration time	h	-	-	2
Equipment				
Water fine filter			•	-
Antifreeze draining		•	•	-
Pneumatic-tyred wheels		•	•	-
Water meter		•	•	-
Backflow preventer				-
Order no.		6.368-463.0	6.368-464.0	6.368-465.0
Price				

■ Included in the scope of supply.

Available accessories.

BARREL CLEANER

Barrel cleaning - incredibly convenient



With the BC 14/12 barrel cleaner, Kärcher caters to the specific requirements of drinks manufacturers and winemakers. Oak barrels in particular can now be cleaned effortlessly.





1 User-friendliness

- Easy switching from cleaning to suction in just one action.
- All equipment included in the scope of supply.
- Can be used worldwide (115-240 V/50 and 60 Hz).

2 Cleaning performance

- Each point inside the barrel is reached once within 36 seconds; barrel is clean after approx. 5 minutes.
- Permanent suction during cleaning clears the way for the high-pressure jet.
- Cleaning with up to 120 bar in hot or cold water operation.

Barrel cleaner BC 14/12

- Integrated suction function
 Clean without moving the b
- Clean without moving the barrel
- Water-carrying stainless steel components

Technical data		
Working pressure	bar / MPa	max. 120 / 12
Flow rate	I/h	600-1400
Power consumption	Ph/V/Hz	1 / 115-240 / 50/60
Max. inlet temperature	°C	80
Connection load	W	40
Revolutions	rpm	62
Cleaning cycle	S	36
Min. tank opening	mm	40
Weight	kg	4.8
Max. immersion depth	mm	900

Equipment	
Mains adaptor	1
Nozzle kits	I
Flexible suction tube	350 mm
Suction tube	300 mm
Suction tube	350 mm
Suction tube	550 mm
Extension cable	10 m
Order no.	2.112-020.0
Price	

■ Included in the scope of supply.

WEED REMOVAL WITH HOT WATER



The system solution from Kärcher chemical-free, environmentally friendly and economical

With Kärcher weed removers and a hot water high-pressure cleaner, you can get rid of unwanted growth without using herbicides. All you need is hot water - which does not harm the environment, surfaces or your wallet. Hot water destroys weeds by quickly penetrating down to the roots, killing the plant proteins, causing lasting damage and wiping out the weeds.











1 Included adaptive wheel attachment kit

- Working is comfortable and effortless even over a long period of time. The compact shape allows operation even in confined spaces.
- Optimal working clearance to the ground is guaranteed at all times.

3 Compact design of the weed remover

- The low weight makes working more comfortable.

2 Optimised combination of high-pressure cleaner and weed remover for 4 No danger, no damage effective weed removal

- The integrated nozzle adapter guarantees constant water flow over the
- The latest Kärcher burner technology ensures the optimal water temperature for weed removal (up to 98 °C).

- In contrast to mechanical methods, with hot water there is no risk of damaging or destroying surfaces.
- There is also no risk of fire, unlike with direct flaming.

TECHNICAL DATA AND EQUIPMENT



		WR 100	WR 50	WR 20	WR 10
		ChassisOptimised water flow	Removable and height-ad- justable chassisOptimised water flow	Optimised water flowLight and compact	Round spray headOptimised water flowLight and compact
Technical data					
Working width	mm	1000	500	200	100
Area performance	m²/h	350-500	150v350	80-150	80-150
Temperature	°C	max. 100	max. 100	max. 100	max. 100
Weight	kg	1.2	2.1	0.3	0.3
Inflow rate	I/min	8.3-16.7	8.3-16.7	5.8-8.3	5.8-8.3

Equipment				
Removable chassis	-	•	-	-
Order no.	2.114-015.0	2.114-013.0	2.114-014.0	2.114-016.0
Price				

■ Included in the scope of supply.

Depending on the machine version, different nozzle inserts are required in order to guarantee optimal water volume flow and therefore consistently high temperatures:

HDS	Nozzle insert order no.
HDS 6/14(-4) C	2.113-070.0
HDS 7/16 C	2.113-041.0
HDS 8/17 C	2.113-071.0
HDS 8/18-4 C	2.113-071.0
HDS 7/12-4 M	2.113-006.0
HDS 8/18-4 M	2.113-071.0
HDS 9/18-4 M	2.113-005.0
HDS 10/20-4 M	2.113-021.0
HDS 12/18-4 S	2.113-010.0
HDS 13/20-4 S	2.113-025.0
HDS 1000 De/Be	2.113-071.0
HDS 13/20 De Tr1	2.113-071.0
HDS 17/20 De Tr1	2.113-071.0

GS JET GUN

Jets for small to medium-sized surfaces



Quick to set up, easy to transport, switches off instantly - the GS jet gun is the affordable cleaning method for small to medium-sized surfaces of all kinds. Adjustable pressure/water volume.







1 User-friendliness

The short set-up times and ease of transport make the GS jet gun a real "one-man system".

2 Versatility

Thanks to the ability to adjust the air pressure, water volume and spray agent volume on the trigger gun itself, the GS jet gun is suitable for use on all surfaces.

GS jet gun

Jet gun with air nozzle
Controller directly on the trigger gun
Safety switch-off

		Safety switch-off
Technical data		
Air pressure	bar / MPa	3-12 / 0.3-1.2
Air consumption	m³/min	3-8
Flow rate	I/h	0-120
Spray agent volume	kg/h	max. 200
Weight	kg	3.4
Dimensions (L × W × H)	mm	480 × 80 × 280
Order no.		2.869-067.0
Price		

Special accessories	Order no.
Air hose (10 m) with connectors	6.390-284.0
Air hose (20 m) with connectors	6.390-285.0
Special air nozzle, designed for high	5.130-249.0
power	

MULTI-PURPOSE CLEANING MACHINE



The multi-talented cleaner for mobile use

An on-board water tank makes the AP 100/50 M independent of a local water supply. And that's just one of its many talents – for it also has a 10-metre-long suction hose, a cleaning agent dosing unit for two different cleaning agents and a high-pressure gun with a 0.5-metre-long spray lance.





1 Cleaning with high pressure

- Cleaning solution applied via high-pressure pump.
- 15 m high-pressure hose for large operating radius.
- Spray lance with high-pressure nozzle as standard equipment. Can be enhanced with a wide range of accessories, such as a foam lance.

2 Includes suction

- Washing water can be vacuumed easily with a wet and dry vacuum cleaner, for example if there is no drain nearby.
- The machine can be used by two people simultaneously.
- Very flexible hose, perfectly adapted to the machine and application.

AP 100/50 M

- $\hfill \blacksquare$ High-pressure cleaning and vacuuming in one machine
- On-board fresh water tank
- Includes cleaning agent dosing unit

Technical data		
Fresh/dirty water tank volume	I	100 / 70
Working pressure	bar	Two-stage adjustment
Low pressure	bar	6
High pressure	bar	19 / 50 max.
Flow rate	I/min	5
Pump/suction motor rating	W	1800 / 370
Cable length	m	15
Weight	kg	100
Order no.		1.007-058.0
Price		

Accessory selection	Order no.	Description
Cup foam lance	6.394-668.0	Short and handy foam lance with 1-litre cleaning agent container directly on the lance. Its compact design makes it perfect for cleaning fittings and walls with foam, for example. Swivelling M 22×1.5 connector, variable cleaning agent dosage via control knob on lance, adjustable spray angle.
Connection piece	4.402-022.0	For attaching high-pressure nozzles and accessory parts to the HP trigger gun (with nozzle screws) – $1 \times M$ 22 \times 1.5, $1 \times M$ 18 \times 1.5.
Hard surface and carpet nozzle	2.642-552.0	Floor nozzle for hard surfaces and spray extraction cleaning of textile coverings.

FOR EVEN CLEANER RESULTS: KÄRCHER ORIGINAL ACCESSORIES

Kärcher original accessories and cleaning agents extend the range of applications of the high-pressure cleaner – from cleaning and caring for construction machines through to work preparation and repairing facades and floors. We continuously develop our accessories in order to ensure that we can meet your requirements. This results in innovative products designed to facilitate your daily cleaning tasks.



Table of contents: High-pressure cleaner accessories

Solar cleaning	Page	122	Pipe cleaning	Page	158
High-pressure hoses	Page	126	Barrel and container cleaning	Page	160
Hose reels	Page	132	Surface cleaners	Page	162
Connectors	Page	136	Wet jet units	Page	168
Trigger guns	Page	138	Foam systems	Page	170
Spray lances	Page	140	Cleaning agent injectors	Page	174
Wash brushes	Page	144	Attachment kits	Page	178
Nozzles	Page	146	Other accessories	Page	182


















1 EASY!Force high-pressure gun

Effortless operation: our new EASY!Force HP trigger gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. With the Advanced version, a full ceramic valve is also used, which enables a service life up to five times longer than that of other high-pressure guns.

2 Servo Control

Thanks to Servo Control, the water volume and working pressure can be infinitely and conveniently adjusted directly on the spray gun without having to stop work.

3 Pipe cleaning dirt blaster

We have applied the tried-and-tested advantages of the dirt blaster to pipe cleaning. The forward-tilting powerful rotating point jet can loosen even the most stubborn blockages and clean the entire inside wall of the pipe. The three backward-tilting jets ensure the necessary propulsion into the pipe.

4 Working light

Our new LED nozzle light literally brings light into the darkness. And good visibility is needed for a good cleaning result. There is often insufficient light in the hours of early morning and late evening in particular, and in poorly lit rooms. You can attach our nozzle light with LED technology directly to the spray lance, immediately creating a well-lit working area.

5 PowerControl spray lance

For infinite, interruption-free pressure regulation directly on the spray lance, without reducing the water volume. It is also possible to mix in cleaning agents in low-pressure operation. The perfect addition to machines without Servo Control.

6 High-pressure articulated joint

The articulated joint with infinite angle adjustment (up to 120°) is ideal for cleaning hard-to-access places such as machines, vehicles, underbodies, chassis, roofs or facades. You can fit the articulated joint directly on the spray lance or on a telescopic lance.


7 Basic foam lance

Our newly developed cup foam lance provides excellent foam quality with half the cleaning agent consumption. Dosage in three stages using the integrated shutter prevents unintentional adjustment, while the robust brass base body and high-quality finishing guarantee a long service life.

8 Spray lance extension

If the standard lance is not long enough for your needs, simply fit our one-meter spray lance extension. This makes it much easier to clean hard-to-access areas, facades or large vehicles.

EASY!Lock QUICK-RELEASE COUPLINGS




Durable and robust. And five times faster than screw connections

Tedious attachment and removal and time-consuming accessory replacement are now things of the past. With our new patented EASY!Lock quick-release couplings, you save valuable working time compared to conventional screw connections – without compromising on the quality, robustness and durability of the connections.









1 Quick convenience

Connection – in the truest sense of the word – at the flick of a wrist (360°) and with all interfaces. Set-up times and the process of changing special accessories, such as surface cleaners or wash brushes, are up to five times faster and easier.

3 Intuitive operation


The connection principle is intuitive and easy to understand; it works the same way on all four connection points. In contrast to conventional quick couplings, the EASY!Lock system requires no additional weight.

2 Robust reliability

A specially developed cone ensures that the thread is self-locking. Triedand-tested threaded screw connection without wear parts; resistant to dirt and highly reliable.

4 Uncompromising quality

Instead of an axial O-ring sealing on the spray lance, the EASY!Lock system uses radial sealing. This increases the stability of the O-rings and effectively prevents their potential loss.






You can also find the right adapter for your machines and accessories using our digital adapter finder: www.kaercher.com/adapterfinder-easylock

SOLAR PANEL CLEANING



Contamination resulting from dust, rust and pollen reduces the performance of photovoltaic systems and solar thermal modules by up to 20 %. The natural effects of rain, condensation and wind are not sufficient to effectively clean the modules. For a consistently high energy yield, it is essential to carry out a professional system clean at regular intervals. iSolar has a modular construction and enables the safe and efficient cleaning of photovoltaic systems of any size. Rotating disc brushes on telescopic lances of various lengths are driven by the water from the high-pressure cleaner.









Solar cleaning – telesconic lances	EASY!Lock order no.	Order no. until 2015	Inlet temperature	L ength	Price Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 10/20-4 MX HDS 12/18-4 SX / HDS 10/20-4 MX HDS 9/18-4 MX / HDS 10/20-4 MX HDS 9/18-4 MX / HDS 9/18-4 MX / HDS 8/18-4 CX HDS 8/18-4 MX / HDS 9/18-6 MX / HDS 8/18-4 CX HDS 8/17 C / HDS 13/20 De TT/ 1 HDS-E 8/16-4 M 36 kW HDS 8/17 C / HDS 13/20 De TT/ 1 HDS-E 8/16-4 M 36 kW HDS 8/17 C / HDS 13/20 De TT/ 1 HDS-E 8/16-4 M 36 kW HDS 1000 Be HD 13/18-4 S Plus / HD 10/25-4 S Plus / HD 10/23-4 S HD 10/25-4 S Plus / HD 10/25-4 S Plus / HD 10/23-4 S HD 10/23-4 S Plus / HD 10/23-4 SX Plus / HD 8/18-4 M HD 9/20-4 M Plus / HD 10/23-4 SX Plus / HD 8/18-4 M HD 9/20-4 M Plus / HD 1/13-4 MX Plus / HD 7/17-4 M HD 7/17 M Plus / HD 7/14-4 MX Plus / HD 7/17-4 M HD 7/14-4 M Plus / HD 7/14-4 MX Plus / HD 7/14-4 M HD 7/17 M St / HD 6/15 MX Plus / HD 8/18-4 M sge St / HD 6/15 M St / HD 8/13-4 C / H
Solar cleaning - telescopic lances iSolar TL 14 C (without hose)	1 4 110-002 0	4.107-052.0	l max 60 °C	26-14 m	The full carbon telescopic lance offers maximum rigidity with minimal	1	
					weight. It has a reach of up to 14 m and is fitted with practical quick-release couplings - for convenient extension and retraction. The speed is regulated via ball tap, guaranteeing easy handling. For work safety reasons, the lowest lance element is made from a carbon-fibreglass mixture for electrical insulation.		
iSolar TL 10 C (without hose)	2 4.110-007.0	4.107-055.0	max. 60 °C	2.6-10 m	The full carbon telescopic lance offers maximum rigidity with minimal weight. It has a reach of up to 10 m and is fitted with practical quick-release couplings - for convenient extension and retraction. The speed is regulated via ball tap, guaranteeing easy handling. For work safety reasons, the lowest lance element is made from a carbon-fibreglass mixture for electrical insulation.	2	
iSolar TL 10 H (without hose)	3 4.110-003.0	4.107-053.0	max. 60 °C	2.6-10 m	The telescopic lance is made from a carbon-fibreglass mixture (hybrid) and offers maximum rigidity with minimum weight. It has a reach of up to 10 m and is fitted with practical quick-release couplings – for convenient extension and retraction. The speed is regulated via ball tap, guaranteeing easy handling. The carbon-fibreglass mixture is also on the lowest rod element and ensures electrical insulation and thus work safety.	3	
iSolar TL 7 H (without hose)	4 4.110-004.0	4.107-054.0	max. 60 °C	2-7 m	The telescopic lance is made from a carbon-fibreglass mixture (hybrid) and offers maximum rigidity with minimum weight. It has a reach of up to 7.2 m and is fitted with practical quick-release couplings - for convenient extension and retraction. The speed is regulated via ball tap, guaranteeing easy handling. The carbon-fibreglass mixture is also on the lowest rod element and ensures electrical insulation and thus work safety.	4	
iSolar HP hose 7	5 6.392-978.0	6.392-978.0	max. 155 °C	8.5 m	The high-quality and flexible high-pressure hose with rubber outer covering is suitable for use in combination with the iSolar TL 7. The outer skin of the hose features especially good sliding properties - ideal for extending and retracting the telescopic lance.	5	
iSolar HP hose 10	6 6.392-977.0				The high-quality and flexible high-pressure hose with rubber outer covering is suitable for use in combination with the iSolar TL 10. The outer skin of the hose features especially good sliding properties - ideal for extending and retracting the telescopic lance.	6	
iSolar HP hose 14	7 6.392-976.0	6.392-976.0	max. 155 °C	15 m	The high-quality and flexible high-pressure hose with rubber outer covering is suitable for use in combination with the iSolar TL 14. The outer skin of the hose features especially good sliding properties - ideal for extending and retracting the telescopic lance.	7	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

SOLAR PANEL CLEANING



Hard water can lead to lime residue which can result in a dramatic reduction in the module's performance. Mobile Kärcher water softeners and the Solar Cleaner RM 99 offer reliable protection against lime stains. In the water softener, an ion-exchange resin removes the dissolved limescale from the water and reduces the hardness degree to 0-1 °dH.












	EASY!Lock order no.	Order no. until 2015	Flow rate	Inlet temperature P	rice Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX HDS 12/18-4 SX HDS 12/18-4 SX HDS 10/20-4 M / HDS 10/20-4 MX / HDS 9/18-4 MX HDS 9/18-4 MX / HDS 8/18-4 MX HDS 9/18-6 C / HDS 7/16 CX HDS 13/20 De Tr1 HDS 13/20 De Tr1 HDS 13/20 De Tr1 HDS 13/20 De Tr1 HDS 13/20 A S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 118-4 M / HD 7/14-4 M Plus / HD 7/14-4 MX Plus HD 7/14-4 M / HD 7/17 M Plus / HD 7/17 MX Plus HD 7/14-4 M / HD 7/17 M SY / HD 6/15 M SY Plus HD 6/15 M / HD 7/17 M SY / HD 6/15 M SY Plus HD 6/15 M Cage HD 9/23 DE TT / HD 9/23 GE TT / HD 10/23-4 Cage Plus HD 9/23 DE TT / HD 9/23 GE TT / HD 10/23-4 Cage Plus HD 9/23 DE TT / HD 9/23 GE TT / HD 10/23-4 Cage Plus
iSolar brushes and water sof							
iSolar 400			700-1000 l/h		The water-driven iSolar 400 disc brush features a working	1	
	2 6.368-457.0	6.368-457.0	1100-1300 l/h	ı max. 40 °C	width of 400 mm and is especially suitable for cleaning small to medium-sized photovoltaic systems. Thanks to the low weight and easy handling, even elevated systems can be conveniently cleaned.	2	
iSolar 800	3 6.368-454.0	6.368-454.0	700-1000 l/h	max. 40 °C	The water-driven iSolar 800 brush head with 800 mm working	3	
	4 6.368-455.0	6.368-455.0	1100-1300 l/h		width works with two contra-rotating disc brushes and is used for cleaning photovoltaic systems. The contra-rotating brushes balance out all transversal forces, guaranteeing optimal handling. The flexible angle joint on the brush head's connector also makes cleaning easier. It ensures that the bristles always lie flat, allowing uniform cleaning results. The brush head has an impressively high area performance – ideal for cleaning large systems, for example on barn roofs.	4	
iSolar fall protection	5 6.988-152.0	6.988-152.0			Certified, standard-compliant safety system for safe working on roofs. The fall protection includes a travelling fall arrestor with shock absorber and 15 m kernmantle rope, safety harness, an anchoring loop for fixing the safety machine, as well as a practical metal box for storage and transport.	5	
WS 50	6 6.368-463.0	6.368-463.0		max. 30 °C	The mobile WS 50/WS 100 water softening unit prevents lime	6	
WS 100	7 6.368-464.0			max. 30 °C	residue on cleaned surfaces. An ion-exchange resin removes the dissolved limescale from the water.	7	
WS Regenerator	8 6.368-465.0	6.368-465.0			With the WS Regenerator regeneration system, the softening cartridges of the water softening units WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	8	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

HIGH-PRESSURE HOSES



Our unique EASY!Lock system is designed for fast and reliable connection and disconnection













our offique End 1: Each dystern is designed for fust and renable confidential disconfidential
of machine and hose. The rotary coupling integrated into our high-pressure hoses with yellow
hand screw connection also prevents the hose from twisting. Numerous extension hose
versions are available for a wider operating radius.

	EASY!Lock order no.	Order no. until 2015	ID	Max. working pressure	Length	Price	Description	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	HDS 13/20-4 S HDS 13/20-4 SX HDS 12/18-4 S / HDS 10/20-4 M / HDS 9/18-4 M	4 M	HDS 12/18-4 SX / HDS 10/20-4 MX / HDS 9/18-4 MX HDS 8/18-4 MX / HDS 7/12-4 MX	HDS 8/18-4 C / HDS 8/17 C / HDS 7/16 C	HDS 6/14-4 C / HDS 6/14 C HDS 8/18-4 CX / HDS 7/16 CX / HDS 6/14-4 CX	(X / HDS 5/11 UX	3/20 De	HDS-E 8/16-4 M 36 KW HDS-E 8/16-4 M 34 kW / HDS-E 8/16-4 M 12 kW	00 De / HDS 1000 Be	HDS 801 D / HDS 801 B HD 17/14-4 S Plus / HD 17/14-4 SX Plus	13/18-4 S Plus 13/18-4 SX Plus	10/25-4 S/ HD 10/25 10/23-4 S Plus / HD 9,	10/25-4 SX Plus / HD 10/23-4 SX Plus 9/20-4 MX Plus	8/18-4 M /	7/14-4 M / HD 7/14-4 M Plus / HD 6/15 M	6/15 M FIUS / ND 6/16-4 M St / ND //17 M 6/15 M St / HD 8/18-4 M Cage St / HD 7/16- 7/17 M Cage St / HD 6/15 M Cage	St / HD 6/15 lus / HD 7/16	7/14-4 MX PIUS / HD 6/15 MX PIUS 5/17 C / HD 5/17 C PIUS / HD 6/13 C	6/13 C Plus / HD 5/15 C / HD 5/15 C Plus 5/12 C / HD 5/12 C Plus / HD 5/11 P	5/17 CX Plus / HD 5/15 CX P 6/13 CX Plus	5/11	9/23 G 25/15-4 Care Plus	HD 20/15-4 Cage Plus	16/15-4 Cage Plus 10/25-4 Cage Plus	HD 715 / HD 7/15 G / HD 728 B Cage HD 9/21 G HD 8/20 G	
Standard			1	1																															
High-pressure hose AVS hose reel connection, NW 8, 315 bar, 20 m, ANTI!Twist	1 6.110-011.0		ID 8	315 bar	20 m		High-pressure hose with AVS hose reel 1 connection and EASY!Lock hand screw													•		•												.	
High-pressure hose AVS hose reel connection, NW 8, 315 bar, 15 m, ANTI!Twist	2 6.110-018.0		ID 8	315 bar	15 m		connection.																				\prod					П			
High-pressure hose AVS hose reel connection, ID 6, 250 bar, 15 m, ANTI!Twist	3 6.110-037.0	6.391-417.0	ID 6	250 bar	15 m		3																												
High-pressure hose AVS hose reel connection, ID 6, 250 bar, 15 m	4 6.110-036.0	6.391-417.0	ID 6	250 bar	15 m		4						•	•	•												اد				П	П			
High-pressure hose AVS hose reel connection, ID 6, 300 bar, 15 m	5 6.110-026.0	6.392-277.0	ID 6	300 bar	15 m		5	1																							П	П			
Standard with unions on both sides								_																			$\rightarrow \rightarrow$	\rightarrow	\rightarrow	_	_				
High-pressure hose 2 × EASY!Lock ID 6, 250 bar, 10 m, ANTI!Twist	6 6.110-035.0	6.391-238.0	ID 6	250 bar	10 m		High-pressure hose with EASY!Lock hand 6 screw connection at both ends.	,					•] C	3 0 C									
High-pressure hose, 2 × EASY!Lock, ID 6, 250 bar, 10 m	7 6.110-034.0	6.391-238.0	ID 6	250 bar	10 m		7							•					•] [3 0 0	3 -	• •		•					
High-pressure hose 2 × EASY!Lock ID 6, 300 bar, 10 m, ANT!!Twist	8 6.110-056.0	6.391-875.0	ID 6	300 bar	10 m		8] [3 0 0									
High-pressure hose 2 × EASY!Lock ID 8, 315 bar, 10 m, ANT!!Twist	9 6.110-031.0	6.391-342.0	ID 8	315 bar	10 m		9		A A A		A		A	A 4		•	A A		•	■	- -	A	A			A A A	A A	A	A	A			•	A A	
High-pressure hose, 2 × EASY!Lock, ID 8, 315 bar, 15 m	10 6.110-033.0	6.390-185.0	ID 8	315 bar	15 m		10	1																	\Box						П	П			
High-pressure hose 2 × EASY!Lock ID 8, 315 bar, 15 m, ANT!!Twist	11 6.110-030.0	6.390-010.0	ID 8	315 bar	15 m		11	1	A A	A	A	A	A	A 4		•	A		•		A A	A A	A			A A A	A A	A	A A	A			A	A E A	
High-pressure hose 2 × EASY!Lock ID 8, 315 bar, 20 m, ANT!!Twist	12 6.110-032.0	6.390-031.0	ID 8	315 bar	20 m		12		A A A		A	•	A	A A		•	4		•	A	A A	A	A			A 1		A	A A	A			A	A A	
High-pressure hose, 2 × EASY!Lock, ID 8, 315 bar, 30 m, ANT!!Twist	13 6.110-014.0	6.390-293.0	ID 8	315 bar	30 m		13		A A A	A	A	A	A A	A 4			A A		•		A A	A	A		A 1	A A A	A	A	A A	A			A	A A	
High-pressure hose, 2 × EASY!Lock, ID 10,	14 6.110-042.0	6.390-023.0	ID 10	220 bar	15 m		14				A A	A	A A	A 4		A	A A		A A	A A	A A	A A	A A			A /		A A	A A	A	\prod		•	A A A	
220 bar, 15 m High-pressure hose, 2 × EASY!Lock, ID 10,	15 6.110-043.0	6.390-726.0	ID 10	220 bar	20 m		15	,#			A A	A	A A	A 4		A	A A		A A	A A	A A	A A	A A			A ,	A A	A A	A A	A	+		<u> </u>	A A A	
220 bar, 20 m High-pressure hose, 2 × EASY!Lock, ID 10,	16 6.110-044.0	6.391-513.0	ID 10	220 bar	25 m		16	;			+	Н	+		+		A A		A A	A A	A A	A A	A A			A A A		A A	A A	A	++		A A	A A A	
220 bar, 25 m High-pressure hose, 2 × EASY!Lock, ID 10,	17 6.110-045.0	6.391-510.0	ID 10	220 bar	40 m		17	#		A	+		+		+	+		$\dagger \dagger$	+		+	+		++	++	A A A	++				+	\dagger			
220 bar, 40 m High-pressure hose, 2 × EASY!Lock, ID 12,	18 6.110-059.0	6.391-849.0	ID 12	210 bar	15 m		18	3		A	A A	A	A A	A		A	A		A	A A	A A	A A	A A			A A A	A	A	A A	+			A A	A A A	
210 bar, 15 m High-pressure hose, 2 × EASY!Lock, DN 12,	19 6.110-060.0	6.391-865.0	ID 12	210 bar	40 m		19	#			A A	A	A A	A 4		A	A A		A A	A A	A A	A A	A A			A A A		A A	A A	+	1		A A	A A A	

LONGLIFE HIGH-PRESSURE HOSES



2 × EASY!Lock, ID 8, 400 bar,

Kärcher Longlife 400 hoses meet the highest demands and are guaranteed to have optimal working times. These hoses are dual steel wire reinforced with a robust rubber outer covering. Kärcher Longlife hoses are also pressure-resistant up to 400 bar.











	EASY!Lock order no.	Order no. until 2015	ID	Max. working pressure	Length	Price	Description		HDS 13/20-4 S HDS 13/20-4 SX HDS 13/20-4 SX HDS 12/18-4 S / HDS 10/20-4 M / HDS 9/18-4 M HDS 8/18-4 M / HDS 7/12-4 M HDS 8/18-4 M / HDS 7/12-4 MX HDS 8/18-4 M / HDS 7/12-4 MX HDS 12/18-4 SX / HDS 10/20-4 MX / HDS 9/18-4 MX HDS 12/18-4 SX / HDS 10/20-4 MX / HDS 9/18-4 MX HDS 12/18-4 SX / HDS 7/12-4 MX HDS 13/18-4 C / HDS 8/17 C / HDS 7/16 C HDS 6/14-4 C / HDS 6/14 C / HDS 6/14 C / HDS 6/14-4 M 12 kW / HDS 1000 De HDS 1000 De / HDS 801 D / HDS 801 B HDS 1000 De / HDS 801 D / HDS 801 B HDS 1000 De / HDS 8/13 U / HDS 7/16 CX HDS 5/12 U / HDS 5/13 U / HDS 5/11 U HDS 5/12 U / HDS 5/13 U / HDS 5/11 U HDS 5/15 U / HDS 5/13 U / HDS 5/11 U HDS 13/18-4 SX PIUS HD 10/23-4 S PIUS / HDS 5/11 U HDS 13/18-4 SX PIUS HD 10/23-4 S PIUS / HDS 5/12 C PIUS HD 10/23-4 S PIUS / HD 5/12 C / HD 5/12 C PIUS HD 10/23-4 S PIUS / HD 9/21 G HD 6/13 C PIUS / HD 9/21 G HD 6/13 C PIUS / HD 9/13 C HD 6/13 C PIUS / HD 9/13 C HD 6/13 C PIUS / HD 9/13 C HD 6/13 C PIUS / HD 9/14 C HD 8/10 C / HD 9/13 C / HD 9/15 C HD 6/15 MX PIUS / HD 9/14 C HD 8/18-4 M / HD 9/14-4 M PIUS / HD 7/17 M PIUS HD 7/14-4 M / HD 7/14-4 M PIUS / HD 7/17 M PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS HD 7/14-4 MX PIUS / HD 6/15 MX PIUS
Longlife 400 High-pressure hose Longlife 400, AVS hose reel connection, ID 8,	1 6.110-028.0	6.390-208.0	ID 8	400 bar	20 m		High-pressure hose with double steel reinforcement, AVS hose reel connection and EASY!Lock hand screw	1	
400 bar, 20 m, ANTI!Twist							connection.		
Longlife 400 with unions on both s Longlife 400 high-pressure hose, 2 × EASY!Lock, ID 8, 400 bar, 1.5 m	2 6.110-024.0	6.390-178.0	ID 8	400 bar	1.5 m		Pressure hose with EASY!Lock hand screw connection at both ends.	2	
Longlife 400 high-pressure hose, 1 × EASY!Lock, 1 × M22 × 1.5, ID 8, 400 bar, 1.5 m	3 6.110-069.0	6.392-282.0	ID 8	400 bar	1.5 m		Pressure hose with double steel reinforcement 1 × M 22 × 1.5 as well as EASY!Lock connection.	3	
Longlife 400 high-pressure hose, 2 × EASY!Lock, ID 8, 400 bar, 10 m, ANT!!Twist	4 6.110-038.0	6.388-083.0	ID 8	400 bar	10 m		Pressure hose with double steel reinforcement and EASY!Lock hand screw connection at both ends.	4	
Longlife 400 high-pressure hose, 2 × EASY!Lock, ID 8, 400 bar, 30 m, ANTI!Twist	5 6.110-023.0	6.390-294.0	ID 8	400 bar	30 m			5	
Longlife 400 high-pressure hose, 2 × EASY!Lock, ID 8, 400 bar, 20 m, ANT!!Twist	6 6.110-027.0	6.390-027.0	ID 8	400 bar	20 m			6	
Longlife 400 high-pressure hose,	7 6.110-029.0	6.389-709.0	ID 8	400 bar	15 m			7	

■ Included in the scope of supply.

Available accessories.

Extension hose. More Kärcher original accessories can be found on the following pages.

FOOD-GRADE HOSES



Kärcher also provides high-pressure hoses designed for the special requirements of the food industry. Kärcher grey food-grade hoses have a non-marking outer covering. Longlife food-grade hoses with blue outer covering offer a further advantage: they are resistant to animal fat.















	EASY!Lock order no.	Order no. until 2015	ID	Max. working pressure	Length	Price	Description		13/20-4 S / HDS 13/20-4 SX / HDS	12/18-4 SX / HDS 10/20-4 M / HDS 10/20 9/18-4 M / HDS 9/18-4 MX / HDS 8/18-4	8/18-4 MX / HDS 7/12-4 M / HDS 7 8/18-4 C / HDS 8/18-4 CX / HDS 8/	8/17 CX / HDS 7/16 6/14-4 C / HDS 6/14	6/14 CX / HDS 5/12 C 5/15 U / HDS 5/15 UX / HDS 5/1	5/13 UX / HDS 5/1 17/20 De Tr1 / HD	N / HDS-E 8/	000 Be / HDS 801 D	HD 13/18-4 S Plus / HD 10/25-4 S / HD 10/25-4 S Plus HD 10/23-4 S / HD 10/23-4 S Plus / HD 9/20-4 M	HD 9/20-4 M Pius HD 8/18-4 M / HD 8/18-4 M Pius / HD 8/18-4 MX Pius HD 7/16-4 M / HD 7/16-4 M Pius / HD 7/16-4 MX Pius	일시	M Plus / HD 6/15 MX Plus 7/17 M St / HD 6/15 M St	HD 8/18-4 M Cage St / HD 7/16-4 M Cage St / HD 7/17 M Cage St HD 6/15 M Cage	HD 6/13 C Plus / HD 6/13 CY Plus / HD 5/15 C HD 6/13 C Plus / HD 6/13 CY Plus / HD 5/15 C HD 5/15 C Plus / HD 5/12 C / HD 5/12 C Plus		HD 9/23 De Tr.1 / HD 9/23 Ge Tr.1 HD 16/15-4 Cage Plus / HD 10/25-4 Cage Plus HD 715)/16-4 Cage	HD 10/15-4 Cage Food HD 7/10 CXF	HD 9/23 De / HD 7/15 G / HD 9/21 G HD 8/20 G / HD 7/15 G / HD 728 B Cage
Food industry version	0.44.1101	T C	1.5	pressore																							
High-pressure hose, food grade, 1× EASY!Lock, 1× hose reel connection attachment kit, 15 m, ID 6, grey	1 6.110-074.0	6.391-654.0	ID 6	250 bar	15 m		High-pressure hose with AVS hose reel connection, EASY!Lock hand screw connection as well as grey, non-marking outer covering.	1																		•	
Food industry version with unions on be	oth sides	•							'																		
High-pressure hose, food grade,	2 6.110-063.0		ID 6	250 bar	15 m		High-pressure hose with EASY!Lock hand screw	2											T T'							\top	
2 × EASY!Lock, ID 6, 15 m, ANTI!Twist							connection at both ends as well as grey,			\perp	Ш				Ш			\perp	 '						1	$\perp \perp$	
High-pressure hose, food grade, 2 × EASY!Lock, ID 8, 10 m, ANTI!Twist	3 6.110-051.0	6.389-479.0	ID 8	250 bar	10 m		non-marking outer covering.	3	A	. 🔺 🔺		 	 	•				 	. 0 0 !			A A	 		4	 	
High-pressure hose, food grade,	4 6.110-052.0	6.389-581.0	ID 8	250 bar	20 m			4	A		A A	A A	A A	A	A A					пп			A .			A A	
2 × EASY!Lock, ID 8, 20 m, ANTI!Twist											Ш													\bot		\bot	
Longlife 400 high prossure base		Le 201 0640	Linio	100 bar	10 m	ı	Drossura hasa with EASVII ask hand serroy sannas	1 1		1 1	1 1			1 1				1.1	1 1		1 1	1 1		4	1 1	47	
Longlife 400 high-pressure hose, food grade, 2 × EASY!Lock, ID 8, 10 m, ANT!!Twist	5 6.110-053.0	0.391-804.0	10.6	400 bar	10 111		Pressure hose with EASY!Lock hand screw connection at both ends as well as blue, non-marking and animal fat-resistant outer covering.	5	A		A	A	•	•		A		• - -						A	.	■ ▲ △	•
Longlife 400 high-pressure hose,	6 6.110-054.0	6.391-887.0	ID 8	400 bar	20 m		Pressure hose with double steel reinforcement,	6																		\top	
food grade, 2 × EASY!Lock, ID 8, 20 m, ANTI!Twist							EASY!Lock hand screw connection at both ends as well as blue, non-marking and animal fat-resistant outer covering.																			ו	
Special hoses																											
High-pressure hose, 1 × curved EASY!Lock, 1 × M22 × 1.5, ID 8, 400 bar, 1.5 m	7 6.110-068.0	6.388-886.0	ID 8	400 bar	1.5 m		Pressure hose with double steel reinforcement, M 22 × 1.5 connection for hose reels as well as EASY!Lock hand screw connection.	7																			
High-pressure hose Ex 2 × EASY!Lock, ID 8, 400 bar, 10 m, ANTI!Twist	8 6.110-064.0	6.391-741.0	ID 8	400 bar	10 m		High-pressure hose with double steel reinforce- ment and EASY!Lock hand screw connection at both ends. Verified electrically conductive	8																	-		

■ Included in the scope of supply.

Available accessories.

Extension hose. More Kärcher original accessories can be found on the following pages.

MANUAL HOSE REELS



The hose reel attachment kit can be used to store a high-pressure hose up to 40 m long $\,$ securely and directly on the machine. For quick and easy hose winding and unwinding. Our automatic hose reels offer greater convenience.















	EASY!Lock order no.	Order no. until 2015	Length	Price	Description		HDS 8/18-4 C / HDS 8/17 C / HDS 7/16 C HDS 6/14-4 C / HDS 8/17 C / HDS 7/16 C HDS 6000 De / HDS 1000 Be / HDS 801 D HDS 801 B HD 10/25-4 S Plus / HD 13/18-4 S Plus / HD 10/23-4 S Plus HD 10/25-4 S Plus / HD 13/18-4 M Plus / HD 7/17 M Plus HD 7/14-4 M / HD 7/17 M / HD 7/17 M Plus HD 7/15-4 M Plus / HD 8/18-4 M St / HD 7/17 M St HD 6/15 M St / HD 8/18-4 M Cage St HD 6/15 M St / HD 8/18-4 M Cage St HD 5/15-4 Cage Plus HD 5/15-4 Cage Plus HD 2/15-4 Cage Plus HD 2/15-4 Cage Plus HD 8/18-4 M Cage St HD 8/18-4 M Plus / HD 8/18-4 M Cage St HD 8/15-4 Cage Plus
Manual hose reel attachment kit		•					
Hose reel attachment kit for high-pressure	1 2.110-024.0		15 m		Hose reel attachment kit for installation on the machine. For secure	1	
middle class					and space-saving storage of the high-pressure hose (with a connec-		
Hose reel attachment kit, plastic, for HDS	2 2.110-010.0	2.642-756.0	20 m		tion hose for the machine high-pressure output). Rotatable under	2	
compact class					pressure with connection for male coupling.		
Hose reel attachment kit for HP super class	3 2.110-008.0	2.640-439.0	20 m		Hose reel attachment kit for installation on the machine. For secure and space-saving storage of the high-pressure hose (with a connection hose for the machine high-pressure output). Rotatable under pressure with connection for male coupling.	3	
Stainless steel hose reel attachment kit for HD Cage super class	4 2.110-001.0	2.440-004.0	40 m		Hose reel attachment kit for installation on the machine. For secure and space-saving storage of the high-pressure hose (with a connec-	4	
Hose reel attachment kit, powder-coated	5 2.110-002.0	2.440-005.0	40 m	1	tion hose for the machine high-pressure output).	5	
for HD Cage super class							
Hose reel attachment kit for HD gasoline machines	6 2.110-004.0	2.637-002.0	30 m			6	
Hose reel attachment kit for HDS gasoline machines	7 2.110-005.0	2.637-733.0	20 m			7	
□ Available accessories More Kärcher ori	ginal accordance can	he found on the	following pa	anc			

machines

Available accessories. More Kärcher original accessories can be found on the following pages.

AUTOMATIC HOSE REELS



The automatic hose reels offer maximum convenience when winding and unwinding the high-pressure hose. Thanks to the practical complete attachment kit, they can be very easily installed. Available for mounting on a wall at the point of use or as an attachment kit directly on the machine.
























						8-9 10	11 12 13
	EASY!Lock order no.	Order no. until 2015	Length	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 SX HDS 12/18-4 SX / HDS 10/20-4 M/ HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX / HDS 8/18-4 M HDS 9/18-4 M / HDS 9/18-4 MX / HDS 8/18-4 M HDS 9/12-4 MX HDS 7/12-4 MX HDS 7/12-4 MX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14-6 C HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14-6 C HDS 6/14-6 C / HDS 10/20-6 FT / HDS 6/14-6 C HDS 6/14-6 C / HDS 10/20-6 FT / HDS 6/14-6 C HDS 6/14-6 C / HDS 10/20-6 FT / HDS 6/14-6 C HDS 6/14-6 C / HDS 10/20-6 FT / HDS 6/14-6 C HDS 6/14-6 C / HDS 10/20-6 FT / HDS 6/14-6 C HDS 6/13-0 W / HDS 13/20 De TT / HDS 5/13 U HDS 10/20-6 FT / HDS 13/20 De TT / HDS 5/13 U HDS 10/20-6 FT / HDS 13/20 De TT / HDS 5/13 U HDS 10/20-6 FT / HDS 13/20 De TT / HDS 5/13 U HDS 10/20-6 FT / HDS 13/20 De TT / HDS 5/13 U HDS 10/20-6 FT / HDS 13/20 De TT / HDS 5/13 U HDS 10/20-6 FT / HDS 10/20-6 FT / HDS 10/20-6 FT / HDS 6/14-6 HDS 10/20-6 FT / HDS 10/20-6 FT / HDS 10/20-6 FT / HDS 6/15 W HDS 10/20-6 FT / HDS 10/20-6 FT / HDS 10/20-6 FT / HDS 6/15 W HDS 10/20-6 FT / HDS 10/20-6 FT / HDS 10/20-6 FT / HDS 6/10-6 F
Automatic, self-winding hose reels for wall Automatic hose reel, powder-coated steel /	mounting 1 6.392-074.0	6.392-975.0	20 m		Automatic hose reels provide the highest level of safety and conveni-	1	
plastic	1 0.332 074.0	0.552 575.0	20111		ence for winding and unwinding HP hoses. For example: order no.		
Automatic stainless steel /	2 6.392-083.0	6.392-965.0	20 m		6.110-011.0 (DN 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	2	
Synthetic material hose drum Automatic hose reel, coated	3 6.392-106.0	2.639-919.0	20 m		(18 6, 20 H, 400 but 20HgHe).	3	
Hose reel, automatic, basalt grey-coated	4 6.392-105.0					4	
Automatic hose reel, stainless steel, includes swivel holder	5 6.392-076.0	6.391-421.0	20 m			5	
Automatic stainless steel hose reel	6 6.392-122.0					6	
	7 6.392-442.0		40 m		Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	7	
Powder-coated swivel holder	8 2.639-931.0	2.639-931.0			Swivel holder for fastening the automatic hose reel to the wall.	8	
Stainless steel swivel holder	9 2.641-867.0	2.641-867.0			Offers maximum radius of action and greatest flexibility with the high-pressure hose. Can be swivelled 120°.	9	
Automatic, self-winding hose reel attachme	ent kit						
Attachment kit for automatic hose reel HDS M/S	10 2.110-011.0	2.642-957.0			Complete automatic hose reel attachment kit for HDS middle and super class. Simple installation, removable for transport, all unit functions are available. Offers maximum convenience when winding and unwinding the HP hose. Contains: automatic hose reel, HP hose and all connection parts.	10	
Holder attachment kit, automatic hose drum HDS M/S	11 2.110-020.0	2.643-040.0			Holder includes connection material for installing an automatic hose reel to machines in the HDS Middle and Super classes.	11	
Attachment kit, automatic hose reel HDS C	12 2.110-012.0	2.643-052.0			Complete automatic hose reel attachment kit for HDS compact class. Simple installation and all unit functions are available. Offers maximum convenience when winding and unwinding the HP hose. Contains: automatic hose reel, HP hose and all connection parts.	12	
Holder attachment kit, automatic hose reel HDS C	13 2.110-013.0	2.643-181.0			Holder includes connection material for installing an automatic hose reel to machines fromthe HDS compact class.	13	
☐ Available accessories. More Kärcher o	riginal accessories can	be found on th	e following pa	iges.	·		

CONNECTORS AND ADAPTERS



Extra connection pieces for nozzle attachment directly on the trigger gun allow space-saving handling. Rotary couplings prevent hose chaos and connectors serve as hose extensions.

The EASY!Lock adapter enables use of the new EASY!Force trigger gun in combination with our patented EASY!Lock quick-release couplings.

























1	4

	EASY!Lock order no.	Order no. until 2015	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 10/20-4 M / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX / HDS 9/12-4 MX HDS 9/18-4 M / HDS 9/13-4 M / HDS 7/12-4 MX HDS 8/18-4 M / HDS 9/13-4 M / HDS 7/13-4 MX HDS 8/13-4 M / HDS 9/13-4 M / HDS 9/13-4 MX HDS 9/13-4 M / HD 13/18-4 S Plus HDS 9/13-4 MS Plus / HD 10/23-4 S Plus HD 10/23-4 Cage Plus / HD 10/23-4 Cag
Nozzle screws		·				
Nozzle screws	1 4.112-011.0	5.401-210.0		Nozzle screws with protectors for high-pressure and power nozzles.	1	
Rotary coupling	1 2 4444 024 0	1 4 4 0 4 0 0 4 0		Delichter was to be in the of UD have the discount of the		
Rotary coupling	2 4.111-021.0	4.401-091.0		Reliably prevents twisting of HP hoses. Handle protection.	2	
Coupling Adapter 9 hose extension TR	3 4.111-037.0	4.403-002.0		For connecting and extending high-pressure hoses. Brass with rubber protector.	3	
Connector		1				
Screw socket for surface cleaners and	4 4.111-022.0	4.402-002.0		For attaching triple nozzles and accessory parts directly to the high-pressure	4	4
Servo Control controllers Short spray unit	5 4.111-038.0	4.402-002.0		trigger gun (with nozzle screws). For attaching high-pressure nozzles and accessory parts directly to the high-	5	
Short spray offic	3 4.111 030.0	4.402 002.0		pressure trigger gun (with nozzle screws). Not compatible with triple nozzles.		
EASY!Lock adapter						
Adapter 1 M22AG-TR22AG	6 4.111-029.0			Adapter for connecting high-pressure hoses with EASY!Lock and high-pressure hoses with an M 22×1.5 connection.	6	
Adapter 2 M22IG-TR22AG	7 4.111-030.0			Adapter for connecting high-pressure cleaners or high-pressure guns with M 22 × 1.5 connection and pressure hoses with EASY!Lock.	7	
Adapter 3 M22IG-TR22AG	8 4.111-031.0			Adapter for connecting high-pressure guns with M 22 × 1.5 connection and spray lances or Servo Control controllers with EASY!Lock.	8	
Adapter 4 TR22IG-D11	9 4.111-032.0	4.424-004.0		Adapter for connecting pressure hoses with AVS swivel connection and EASY!Force high-pressure gun.	9	
Adapter 5 TR22IG-M22AG	10 4.111-033.0			Adapter for connecting EASY!Force high-pressure gun and spray lances with M 22×1.5 connection.	10	
Adapter 6 TR22IG-M22AG	11 4.111-034.0			Adapter for connecting pressure hoses with M 22 × 1.5 connection and EASY!Force high-pressure gun or high-pressure cleaners with EASY!Lock.	11	
Adapter 7 M18IG-TR20AG	12 4.111-035.0			Adapter for connecting spray lances with M 18×1.5 connection and nozzles, surface cleaners or wash brushes with EASY!Lock.	12	
Adapter 8 TR20IG-M18AG	13 4.111-036.0			Adapter for connecting nozzles, surface cleaners or wash brushes with M 18 × 1.5 connection and spray lances with EASY!Lock.	13	
Adapter 12 rotary coupling EASY!Lock 22 IG - M22 × 1.8 AG	14 4.111-046.0			Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection.	14	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

TRIGGER GUNS



Equip your high-pressure cleaner with the new high-pressure accessories: the EASY!Force HD trigger gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. Both the ball and the sealing seat of the valve of the EASY!Force high-pressure gun are ceramic, which is far harder than any conceivable foreign particle. The full ceramic valve therefore ensures a five times longer lifetime in comparison to other high-pressure guns.









EASY!Force Advanced 1 4.118-005.0 4.775-466.0 Effortless, not energy-sapping: the EASY!Force high-pressure gun		1 1	ASY!Lock rder no.	Order no. until 2015	Flow rate	Price	Description		HDS 13/20.46 / HDG 13/20.4 GY / HDG 12/18.4 G	12/18-4	M / HDS 8/18-4	HDS 8/18-4 C / HDS 8/18-4 CX HDS 8/17 C	HDS 8/17 CX HDS 7/16 C / HDS 7/16 CX	HDS 4/14-4 C / HDS 6/14-4 CX	HDS 6/14 C / HDS 6/14 CX HDS 5/12 C / HDS 5/15 U / HDS 5/15 UX	HDS 5/13 U HDS 5/13 UX / HDS 5/11 U / HDS 5/11 UX HDS 17/20 De Tr-1 / HDS 13/20 De Tr-1		HDS-E 8/10-4 M 36 KW / HDS-E 8/10-4 M 24 KW / HDS-E 8/10-4 M 12 KW HDS 1000 De / HDS 1000 Be	HDS 801 D / HDS 801 B HD 17/14-4 S Plus / HD 17/14-4 SX Plus / HD 13/18-4 S Plus	Plus / HD 10/25-4 SX	HD 10/23-4 S / HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 9/20-4 M / HD 9/20-4 M Plus / HD 9/20-4 MX Plus	Plus / HD 8/18-4 MX	HD 7/17 M / HD 7/17 M Plus / HD 7/17 MX Plus HD 7/14-4 M / HD 7/14-4 M Plus / HD 7/14-4 MX Plus	HD 6/15 M / HD 6/15 M Plus / HD 6/15 MX Plus HD 8/18-4 M St	HD 7/17 M St / HD 6/15 M St HD 8/18-4 M Cage St / HD 7/16-4 M Cage St	HD //1/ M cage St/ HD 6/15 M cage/ HD 5/17 C Hus/ HD 5/17 C Hus/ HD 5/17 C Hus/ HD 5/13 C Hus/ HD 5/17 C Hus/ HD 5/13 C	HD 5/13 C Plus / HD 5/15 CX Plus / HD 5/12 C HD 5/15 C Plus / HD 5/15 CX Plus / HD 5/12 C HD 5/12 C Plus / HD 5/12 CX Plus / HD 5/11 P	HD 5/11 P Plus HD 9/23 De Tr1 / HD 9/23 Ge Tr1 HD 25/15-4 Cape Plus / HD 70/15-4 Cape Plus		HD 10/15-4 Cage Food HD 7/10 CXF	HD 9/23 De / HD 9/23 G HD 9/21 G / HD 8/20 G / HD 7/15 G HD 778 B Came	חוף / אַט ני ימקקי
Servo control Servo Control Controller with EASYILock A 4.118-005.0 4.775-471.0 1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-015.0 4.775-805.0 750-1100 /h Servo Control Controller with EASYILock 7 4.118-		1 4 4	110 005 0	1 4 77F 466 0	1	1	Percentage and approximate the PACVIP and high approximation							1 1		1 1	1 1					1 1							1 1			
Full ceramic valve enables effortless working due to virtually zero holding force for the operator.	EASY!FUICE AUVAIICEU	1 4.	.118-005.0	4.775-400.0			uses the recoil force of the high-pressure jet to reduce the holding	1	•	• • •		• •		• •	• •	- - -	□ ■ •	• •	• •	• •	• •	• •	• •	•	- • •	• • •	• • •		• •			i
Permitted in explosive zones, developed for fatigue-free work: EASY/Force EX 3 4.118-020.0 4.775-793.0 Permitted in explosive zones, developed for fatigue-free work: EASY/Force high-pressure gun reduces the holding force to zero by using the recoil force of the high-pressure jet.	EASY!Force Food	2 4.	.118-015.0	4.775-825.0			full ceramic valve enables effortless working due to virtually zero	2																						••		
Servo Control controller with EASY!Lock	EASY!Force Ex	3 4.	.118-020.0	4.775-793.0			Permitted in explosive zones, developed for fatigue-free work: EASY!Force high-pressure gun reduces the holding force to zero by	3																					-			
5 4.118-008.0 4.775-470.0 750-1100 l/h gun. 5	Servo control																															
6 4.118-007.0 4.775-526.0 0-750 l/h Servo Control controller with EASY!Lock, 7 4.118-016.0 4.775-805.0 750-1100 l/h Food-grade, parts in contact with water are stainless steel. Quick coupling 8 2.115-000.0 6.401-458.0 Perfect for the Kärcher spray unit, suitable for the trigger gun/s, suitable for the trigger gun/spray 8 2.115-000.0 6.401-458.0 Perfect for the Kärcher spray unit, suitable for the trigger gun/spray	Servo Control controller with EASY!Lock						ł		_									$\perp \perp$				\perp	\perp		$\perp \perp$				1		\Box	4
Servo Control controller with EASY!Lock, 7 4.118-016.0 4.775-805.0 750-1100 I/h Food-grade, parts in contact with water are stainless steel. The control controller with EASY!Lock, 7 4.118-016.0 4.775-805.0 750-1100 I/h Food-grade, parts in contact with water are stainless steel. Quick coupling							guil.			-				44			++'	- -	+				+	+	-	++						4
Food-grade, parts in contact with water are stainless steel. Quick coupling Quick coupling 8 2.115-000.0 6.401-458.0 For quickly switching between various spray lances/accessories. Perfect for the Kärcher spray unit, suitable for the trigger gun/spray	Sorve Control controller with EASVII ack						Water flow and proceure control on the trigger gue		$\overline{}$			-		-	- 		++	++			+	+	-	-	+	++					$\overline{}$	4
Quick coupling 8 2.115-000.0 6.401-458.0 For quickly switching between various spray lances/accessories. 8 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		7 4.	.116-010.0	4.773-803.0	750-1100 1/11																									■□		
Perfect for the Kärcher spray unit, suitable for the trigger gun/spray	Quick coupling				,				,					,			, ,			, ,					, ,							
	Quick coupling	8 2.	.115-000.0	6.401-458.0			Perfect for the Kärcher spray unit, suitable for the trigger gun/spray	8																								1
Male coupling 9 2.115-001.0 6.401-459.0 Hardened stainless steel barb nipple for quick coupling 2.115-000.0. 9 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Male coupling	9 2.	.115-001.0	6.401-459.0			Hardened stainless steel barb nipple for quick coupling 2.115-000.0.	9																								1

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

SPRAY LANCES



Kärcher spray lances, made from high-grade stainless steel and available in various lengths, can be swivelled 360° while under pressure. They feature ergonomically shaped grips and large hand screw connections for easy use and insulation. Special spray lances significantly extend the range of uses of high-pressure cleaners. For example the flexible spray lance – ideal for cleaning difficult-to-reach areas. Or the telescopic spray lance for cleaning ceilings and facades.























16

		EASY!Lock order no.	Order no. until 2015	Max. working pressure	Length Price	Description			HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 10/20-4 M / HDS 10/20-4 MX	HDS 9/18-4 M / HDS 9/18-4 MX / HDS 8/18-4 MX HDS 8/18-4 MX / HDS 7/12-4 M / HDS 7/12-4 MX	HDS 8/18-4 C / HDS 8/18-4 CX / HDS 8/17 C HDS 8/17 CX HDS 7/16 C / HDS 7/16 CX / HDS 6/14-4 C	HDS 6/14-4 CX / HDS 6/14 C / HDS 6/14 CX HDS 6/12-6	5/15 U / HDS 5	HDS 5/13 UX / HDS 5/11 U / HDS 5/11 UX HDS 17/20 DA Tr1 / HDS 13/20 DA Tr1	2000 Super / I	801 D / HDS 801 B 7/14-4 S Plus / HD 17/14-	HD 13/18-4 SX Plus / HD 10/25-4 S / HD 10/25-4 S Plus HD 10/25-4 S V Plus / HD 10/25-4 S Plus / HD 10/25-4 S Plus / HD 10/23-4 S Plus	10/23-4 SX Plus / HD 9/20- 9/20-4 MX Plus	HD 8/18-4 M / HD 8/18-4 M Plus / HD 8/18-4 MX Plus HD 7/16-4 M / HD 7/16-4 M Plus	7/16-4 MX P	HD 7/14-4M / HD 7/14-4M Pius / HD 6/14-4MX Pius HD 6/14-5M / HD 7/14-4MX Pius / HD 6/15-MX Pius	8/18-4 M St /	HD 6/15 M St HD 8/18-4 M Cage St HD 7/16-4 M Cage St	HD 7/16-4 M Cage St HD 7/17 M Cage St HD 6/15 M Cage	17 CX	HD 5/12 C / HD 5/15 C Plus / HD 5/12 CX Plus HD 5/12 C / HD 5/12 C Plus / HD 5/12 CX Plus	5/11 P / HD 5/11 P Plus 9/23 De Tr1 / HD 9/23 Ge Tr1	HD 25/15-4 Cage Plus / HD 20/15-4 Cage Plus / HD 16/15-4 Cage Plus HD 10/25-4 Cage Plus	10/1	HD 7/10 CXF HD 9/23 De / HD 9/23 G / HD 9/21 G HD 8/20 G / HD 7/15 G	HD 728 B Cage
Rotating spray lances		0.00.00	10	p. coso. c	205					-1-1-			1-1-	1-1-	1-1-	1-1-	1-1-	1-1-	1-1-	1-1-		-1-1-							-1-1-		
LED nozzle light	1	2.680-002.0	•		125 mm	Watertight LED work light for assembly on EASY!Force spray lances. Low weight and long life, high light output >170 Lumen. CR123 lithium-ion batteries, 2x included in the scope of supply.	1																3 0 0	3 0 0							
Spray lance, 250 mm, rotating	2	4.112-027.0	4.760-667.0	300 bar	250 mm	Spray lances in different lengths, stainless steel with large manual	2																<u> </u>					0 0 1		<u> </u>	
Spray lance, 400 mm, rotatable	3	4.112-024.0	4.760-665.0	300 bar	400 mm	coupling. Ergonomic handle bowls ensure optimal handling and	3] [[] [[
Spray lance, 600 m, rotatable	4	4.112-007.0	4.760-664.0	300 bar	600 mm	protection. Rotatable under pressure by 360°.	4] [[3 0 0			, 🗆 🗖 r				
Spray lance, 840 mm, rotating	5	4.112-006.0	4.760-663.0	300 bar	840 mm		5															■ [<u> </u>				. = D f				
Spray lance, 1050 mm, rotatable	6	4.112-000.0	4.760-660.0	300 bar	1050 mm		6				- - -]	3 0 0			, 🗆 🔳				
Spray lance, 1550 mm, rotatable	7	4.112-018.0	4.760-661.0	300 bar	1550 mm		7] [[] [[
Spray lance, 2050 mm, rotatable	8	4.112-021.0	4.760-662.0	300 bar	2050 mm		8] [[] [[
EASY!Lock 1000 mm spray lance extender	9	4.112-048.0		300 bar	1000 mm	Spray lance extender with EASY!Lock connection. Length: 1000 mm.	9																<u> </u>	3 0 0			اللل	المال		300	
PowerControl spray lance				1			1 1																4								
PowerControl spray lance 027		4.112-043.0				For the fast, precise and infinitely variable pressure adjustment	10														$\perp \perp$		++	++		\sqcup	\longrightarrow	\dashv			\perp
PowerControl spray lance 034		4.112-045.0				during high-pressure cleaning. Simple operation directly in the grip zone. With low pressure mode and jet level adjustment.	11						<u> </u>							-		4	++	 -				++		++	\perp
PowerControl spray lance 038		4.112-047.0					12	-	-	-				\vdash	+	+	+	++			+		+			\vdash		++		++	+
PowerControl spray lance 042	13	4.112-046.0					13							Ш												ш				$\bot\bot$	Щ
Additional handle Additional handle for EASY!Lock spray lances	14	4.321-380.0				Comfortable in every situation - the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360° rotating spray lance, the additional handle can easily be rotated around its axis while working, which makes for greater flexibility.	14																3 0 0	3 0 0						3 0 0	
Angular spray lance																															
Spray lance for toilets and rain gutters	15	4.112-029.0	4.760-073.0			With nozzle insert. Specially shaped for cleaning gutters and hygienically cleaning WCs. Stainless steel.	15																	3 0 0						3 0 0	
Flexible spray lance			_																												
Flexible lance 1050 mm	16	4.112-035.0	6.394-654.0	210 bar	1050 mm	Continuous adjustment of the angle of the spray lance from 20–140°. Especially suitable for cleaning hard-to-reach places, e.g. roof gutters, car roofs, underbodies or wheel arches.	16																							<u> </u>	

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.











		EASY!Lock	Order no.	Max. workin	80				DS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S	255 12/18-4 SX / HDS 10/20-4 M / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 M / HDS 9/18-4 M	DS 8/18-4 MX / HDS 7/12-4 M / HDS 7/12-4 MX DS 8/18-4 C / HDS 8/18-4 CX / HDS 8/17 C	DS 8/17 CX DS 7/16 C / HDS 7/16 CX / HDS 6/14-4 C DS 6/14-4 CX / HDS 6/14 C / HDS 6/14 CX	DS 5/12 C DS 5/15 U / HDS 5/15 UX	DS 5/13 U DS 5/13 UX / HDS 5/11 U / HDS 5/11 UX	DS 1//20 DE IT1/ HDS 13/20 DE IT1 DS 2000 Super / HDS-E 8/16-4 M 36 KW / HDS-E 8/16-4 M 24 KW SS-E 8/16-4 M 12 KW / HDS 1000 De / HDS 1000 Be	25 801 D / HDS 801 B 20 17/14-4 S Plus / HD 17/14-4 SX Plus / HD 13/18-4 S Plus	2 13/18-4 SX Plus / HD 10/25-4 S / HD 10/25-4 S Plus 2 10/25-4 SX Plus / HD 10/23-4 S / HD 10/23-4 S Plus 3 10/23-4 SX Plus / HD 9/20-4 M / HD 9/20-4 M Plus	29/20-4 MX Plus 39/20-4 MX Plus 38/18-4 M / HD 8/18-4 M Plus / HD 8/18-4 MX Plus	2 7/16-4 M / HD 7/16-4 M Plus 2 7/16-4 MX Plus	27/17 M / HD 7/17 M Plus / HD 7/17 MX Plus 27/14-4 M / HD 7/14-4 M Plus / HD 7/14-4 MX Plus	D 6/15 M / HD 6/15 M Plus / HD 6/15 MX Plus D 8/18-4 M St / HD 7/17 M St D 6/15 M St	28/18-4 M Cage St 7/16-4 M Cage St	2 6/15 M Cage 0 6/15 M Cage 0 5/17 C / HD 5/17 C Plus / HD 5/17 CX Plus	D 6/13 C / HD 6/13 C Plus / HD 6/13 CX Plus D 5/15 C / HD 5/15 C Plus / HD 5/15 CX Plus		HD 25/15-4 Cage Plus / HD 20/15-4 Cage Plus / HD 16/15-4 Cage Plus HD 10/25-4 Cage Plus HD 715	HD 10/15-4 Cage Food HD 7/10 CXF HD 9/23 De / HD 9/23 G / HD 9/21 G	8/20 G / HD 7/15 G 728 B Cage
High-pressure articulated joint	17	4.112-057.0 I	until 2015 4.481-039.0	300 bar	Length	Price	Pescription For places that are difficult to access: high-pressure articulated joint with infinitely variable angle adjustment up to 120°. Simply	17																	1 0 0			
Talanania anuny langa							install directly at the spray lance of the high-pressure cleaner.																					
Telescopic spray lance Telescopic spray lance	18	4.112-037.0	6.394-690.0	225 bar	5400 mr	m	Can be extended to any length between 1.8 and 5.4 m. For cleaning difficult-to-reach areas (e.g. ceilings, facades). With integrated high-pressure trigger gun and carrier belt.	18																	1 0			
Strap for telescopic spray lance	19	6.373-987.0	6.373-987.0				Comfortable carrying strap to facilitate work with the telescopic spray lance.	19																	1 0 0	0 0 0		
Gutter cleaner						•																						
Gutter cleaning lance	20	2.112-015.0	2.642-305.0		960 mm	1	The spray lance is designed for cleaning gutter drainage systems. The lance shape and the special nozzle allow cleaning to be carried out without removing the cover screen.	20																				
Undercarriage spray lance																												
Underbody lance	21	4.112-032.0	4.760-245.0		700 mm	1	Mobile; for convenient and effective cleaning of vehicle underbodies and wheel arches. Stainless steel. Without HP nozzle.	21																				

■ NEW □ Available accessories. More Kärcher original accessories can be found on the following pages.

WASH BRUSHES



Wash brushes are ideal for stubborn dirt and sensitive surfaces. Kärcher offers a wide range of wash brushes for effective and gentle vehicle and facade cleaning. The mechanical cleaning effect of the bristles allows cleaning in the low pressure range. Kärcher wash brushes fit standard spray lances and triple nozzles. The rotating wash brushes have a powerful cleaning action. They are driven by the high-pressure cleaner's water jet.









	EASY!Lock order no.	Order no. until 2015	Flow rate	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 10/20-4 MX HDS 9/18-4 MX / HDS 9/18-4 MX HDS 9/18-4 MX / HDS 9/18-4 MX HDS 8/18-4 C / HDS 9/18-4 MX / HDS 7/12-4 MX HDS 8/18-4 C / HDS 9/18-4 MX / HDS 7/12-4 MX HDS 8/18-4 C / HDS 9/18-4 C / HDS 9/12-4 MX HDS 8/13-4 C / HDS 9/18-4 C / HDS 9/12-4 MX HDS 6/14-4 C / HDS 6/14-4 C / HDS 9/12-4 MX HDS 6/14-4 C / HDS 9/15 U / HDS 5/12 U / HDS 5/12 U / HDS 5/13 U / HDS 5/14 U / HDS 9/10 U
Push-on wash brush							
Push-on wash brush	1 4.113-001.0				For all surface cleaning tasks. Clamps directly on to the spray lance.	1	
	2 4.762-497.0	4.762-497.0			Clamps directly onto the double/triple nozzle of the machine. Suitable for new double/triple nozzles.	2	
Rotating wash brush					Solidole for new double/triple fluzzies.		
Rotating wash brush for < 800 l/h	3 4.113-004.0	4.762-561.0	500-800 l/h		Driven by the water jet. For gentle removal of fine dust and grey film	3	
machines, nylon bristles	13 554.0	, 52 551.0			on all surfaces. Temperature-resistant up to 60°C (replaceable brush		
Rotating wash brush for > 800 l/h machines, nylon bristles	4 4.113-002.0	4.762-559.0	800-1300 l/h	1	insert).	4	
Rotating wash brush for < 800 l/h	5 4.113-003.0	4.762-560.0	500-800 l/h		-	5	
machines, natural bristles							
Rotating wash brush for > 800 l/h machines, natural bristles	6 4.113-005.0		800-1300 l/h			6	

machines, natural bristles

Available accessories. More Kärcher original accessories can be found on the following pages.

POWER NOZZLES



The Kärcher power nozzle cleans large areas much faster and more effectively. The concentrated spray jet delivers up to 40% more impact force. This results in greatly improved cleaning performance.




	EASY!Lock order no.	Order no. until 2015	Nozzle size	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 13/20 De Tr1	HDS 10/20-4 M / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX / HDS 7/12-4 M	HDS 7/12-4 MX / HDS 1000 De / HDS 1000 Be		HDS = 8/16-4 M 12 kW HDS 7/16 C / HDS 7/16 CX	HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C HDS 6/14 CX HDS 6/12 C / HDS 6/14-11 / HDS 6/15 11Y	HDS 5/13 U / HDS 5/13 UX HDS 5/11 U / HDS 5/11 UX	HDS 17/20 De Tr1 HDS 2000 Super	HD 3418-4 S Plus / HD 13/18-4 SX Plus	HD 10/25-4 S / HD 10/25-4 S Plus / HD 10/25-4 SX Plus HD 10/23-4 S / HD 10/23-4 S Plus / HD 10/23-4 SX Plus	HD 9/20-4 M / HD 9/20-4 M Plus / HD 9/20-4 MX Plus	HD 8/18-4 M / HD 8/18-4 M PIUS / HD 8/18-4 MX PIUS HD 7/16-4 M / HD 7/16-4 M PIUS / HD 7/14-4 M HD 7/14-4 M PIUS / HD 7/14-4 MX PIUS / HD 8/18-4 M St	HD 8/18-4 M Cage / HD 7/16-4 M Cage / HD 715 HD 7/16-4 MX Plus	HD 7/17 M / HD 7/17 M Plus / HD 7/17 MX Plus HD 7/17 M St / HD 7/17 M Cage / HD 6/13 C Plus	HD 6/13 CX Plus / HD 7/15 G / HD 728 B Cage HD 6/15 M / HD 6/15 M Plus / HD 6/15 MX Plus	HD 6/15 M St / HD 6/15 M Cage HD 5/17 C / HD 5/17 C Plus / HD 5/17 CX Plus	HD 5/15 C / HD 5/15 C Plus / HD 5/15 CX Plus HD 5/12 C / HD 5/12 C Plus / HD 5/12 CX Plus HD 5/11 P / HD 5/11 P Plus	HD 9/23 De Tr1 / HD 9/23 Ge Tr1 / HD 10/25-4 Cage Plus HD 9/23 De / HD 9/21 G HD 25/15-4 Cage Plus	HD 16/15-4 Cage Plus HD 10/16-4 Cage Ex	HD 10/15-4 Cage Food HD 7/10 CXF HD 8/20 G
HP nozzle spray angle 0°	1 2.113-001.0	2004 5220	40		Solid jet for removing extremely stubborn dirt.	1	1.1		1 1	1.1		1 1		Lle	- I	1.1	1.1	1 1					امامام			
High-pressure nozzle 0° - 040	2 2.113-001.0		45		Solid Jet for removing extremely stobboth dirt.	2			-				1 0 1 0 1		-	+	-							++	+++	\perp
High-pressure nozzle 0° - 045 High-pressure nozzle 0° - 050	3 2.113-034.0		50			3				- - -	1			+	+++								+		+++	+
High-pressure nozzle 0° - 055	4 2.113-035.0	2.884-536.0	55			1				+								++-					+		+++	+
High-pressure nozzle 0° - 060	5 2.113-036.0	2.884-537.0	60			5				+					+	++	++		\vdash				+++	++		+
High-pressure nozzle 0° - 075	6 2.113-037.0	2.884-540.0	75			6									+	+		++-					+++	++	++-+	+++
High-pressure nozzle 0° - 080	7 2.113-038.0	2.884-541.0	80			7								+		+	+	+++						++-	+++	+++
High-pressure nozzle 0° - 110	8 2.113-039.0		110			8				+					+	+	+									111
Power nozzle spray angle 15°			1																							
Power nozzle 15° - 028	9 2.113-041.0	2.883-027.0	28		Flat jet for stubborn dirt.	9																				
Power nozzle 15° - 033	10 2.113-002.0	2.885-437.0	33			10									\top											
Power nozzle 15° - 034	11 2.113-042.0	2.885-224.0	34			11				\top					\top											
Power nozzle 15° - 036	12 2.113-043.0	2.885-225.0	36			12																				
Power nozzle 15° - 038	13 2.113-044.0	2.885-332.0	38			13																				
Power nozzle 15° - 040	14 2.113-045.0	2.883-388.0	40			14																				
		2 000 200 0	4.5			15				ППГ	ılnII					T										
Power nozzle 15° - 045	15 2.113-046.0	2.883-389.0	45					-	_				\perp					- - -					\rightarrow			
Power nozzle 15° - 055	16 2.113-047.0	2.883-389.0	55			16																				
Power nozzle 15° - 055 Power nozzle 15° - 060	16 2.113-047.0 17 2.113-048.0	2.883-390.0 2.883-391.0	_			16 17																				
Power nozzle 15° - 055 Power nozzle 15° - 060 Power nozzle 15° - 070	16 2.113-047.0 17 2.113-048.0 18 2.113-049.0	2.883-390.0 2.883-391.0 2.883-392.0	55 60 70			16 17 18																				
Power nozzle 15° - 055 Power nozzle 15° - 060	16 2.113-047.0 17 2.113-048.0	2.883-390.0 2.883-391.0 2.883-392.0 2.883-394.0	55 60			16 17																				

Power nozzle 15° - 100

20 2.113-052.0 2.883-396.0 100

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

POWER NOZZLES



Kärcher power nozzles clean large areas much faster and more thoroughly. The sharply contoured spray jet, consisting of large, connected drops, offers up to 40% more collision force.



	EASY!Lock order no.	Order no. until 2015	Nozzle size	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX	HDS 12/18-4 S / HDS 12/18-4 SX HDS 10/20-4 M / HDS 10/20-4 MX	HDS 9/18-4 M / HDS 9/18-4 MX / HDS 1000 De HDS 8/18-4 M / HDS 8/18-4 MX / HDS 7/12-4 MX / HDS 1000 Be		HDS 7/16 C / HDS 7/16 CX	HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C / HDS 6/14 CX HDS 5/12 C / HDS 5/15 U / HDS 5/15 UX / HDS 5/13 U / HDS 5/13 UX	HDS 5/11 U HDS 5/11 UX	HDS 17/20 De Tr.1 HDS 13/20 De Tr.1	HDS 2000 Super HDS-E 8/16-4 M 36 KW / HDS-E 8/16-4 M 24 KW / HDS-E 8/16-4 M 12 KW		HD 103/18-4 S Plus / HD 13/18-4 S X Plus HD 103/18-4 S Plus / HD 10/25-4 C Plus Plus / HD 10/25-4 C Plus Plus / HD 10/25-4 C Plus Plus Plus Plus Plus Plus Plus Plus	1 0	HD 10/22-4-3X PIUS HD 9/20-4 M / HD 9/20-4 M PIUS / HD 9/20-4 MX PIUS	HD 6/16-4 M/ HD 6/16-4 M Plus / HD 8/18-4 M Cage / HD 7/16-4 M Cage HD 7/16-4 MX Plus HD 7/16-4 MX Plus	HD 7/17 M / HD 7/17 M Plus / HD 7/17 MX Plus HD 7/17 M Case / HD 728 B Case	HD 7/14-4 M / HD 7/14-4 M Plus / HD 7/14-4 MX Plus HD 6/15 M / HD 6/15 M Plus / HD 6/15 MX Plus / HD 6/15 M Cage	HD 6/13 C Plus / HD 6/13 CX Plus	HD 5/15 C / HD 5/13 C Plus / HD 5/15 CX Plus HD 5/12 C / HD 5/12 C Plus / HD 5/12 CX Plus	HD 9/23 DE Tr1 / HD 9/23 GE Tr1 / HD 9/23 DE / HD 9/23 G / HD 9/21 G HD 25/15-4 Caee Plus	H 16.71.5.4 Cage Plus H 16.71.5.4 Cage Plus H 16.71.5.4 Cage Plus	HD 715	HD 10/10-4 Lagge EX HD 10/15-4 Cage Food HD 7/10 CXF	HD 8/20 G
Power nozzle spray angle 25°																													
Power nozzle 25° - 033	1 2.113-063.0		_		Flat jet nozzle for large area performance and stubborn dirt.	1					\perp	\perp										•							$\perp \perp \perp$
Power nozzle 25° - 034	2 2.113-000.0	2.883-803.0	34			2																	Г						
Power nozzle 25° - 035	3 2.113-004.0	2.885-255.0	35			3																							
Power nozzle 25° - 036	4 2.113-005.0	2.883-821.0	36			4																							
Power nozzle 25° - 038	5 2.113-006.0	2.883-805.0	38			5					П																		
Power nozzle 25° - 040	6 2.113-021.0	2.883-397.0	40			6																							
Power nozzle 25° - 042	7 2.113-007.0	2.883-831.0	42			7					ı																		
Power nozzle 25° - 043	8 2.113-008.0	2.883-829.0	43			8																	\Box						
Power nozzle 25° - 045	9 2.113-022.0	2.883-398.0	45			9																							
Power nozzle 25° - 047	10 2.113-009.0	2.883-894.0	47			10																	\top						
Power nozzle 25° - 048	11 2.113-010.0	2.883-804.0	48			11																	\Box						
Power nozzle 25° - 050	12 2.113-023.0	2.883-399.0	50			12			•			\dashv		\sqcap									\top	\top					
Power nozzle 25° - 052	13 2.113-024.0	2.883-400.0	52			13			\Box			$\dashv \dashv$		\top				1					\top	\top			\top		
Power nozzle 25° - 060	14 2.113-026.0	2.883-402.0	60			14			\sqcap		\top	$\dashv \dashv$		\top		\sqcap			\top	\top	\sqcap	\top	1	\top					
Power nozzle 25° - 062	15 2.113-012.0	2.883-948.0	62			15					\top	$\neg \neg$		\sqcap		\sqcap			$\neg \neg$	\top			\top				\top		
Power nozzle 25° - 068	16 2.113-027.0	2.885-133.0	68			16		•			\top	$\dashv \dashv$		\sqcap					\top				\top	\top					
Power nozzle 25° - 070	17 2.113-028.0	2.883-404.0	70			17						$\neg \neg$							\top										
Power nozzle 25° - 080	18 2.113-015.0	2.883-406.0	80			18			\Box		\top	$\dashv \dashv$		\top					\top					\top			\top		
Power nozzle 25° - 090	19 2.113-016.0	2.883-407.0	90			19					\top	\dashv				\vdash			\top	\top			\top						
Power nozzle 25° - 100	20 2.113-017.0	2.883-408.0	100			20	\dashv		\vdash	+	+	$\dashv \dashv$	\dashv	\top		\vdash	+		+	+	\vdash	+	++	+	+		+		+
Power nozzle 25° - 110	21 2.113-018.0	2.883-785.0	110			21			\vdash		+	\top		\top	•				+	+		+	+				+		+++
Power nozzle 25° - 115	22 2.113-060.0	2.885-459.0	115			22	\dashv	\top	\vdash	+	+	$\dashv \dashv$	\dashv	+	\top	•		++	++	++	\vdash	+	++	++	++	++	++	++	+
Power nozzle 25° - 125	23 2.113-029.0	2.885-170.0	125			23			\vdash		+	+		+		┌┤╴			+	+			++	+	+		+		+
Power nozzle 25° - 155	24 2.113-030.0	2.885-157.0	155			24	\dashv		\vdash	++	+	+	+	+		\vdash	++	++	+	++	+	+	++	++		_	++		+++
25° power nozzle for cleaning agent suction	25 2.113-020.0	2.884-521.0	250		Brass power nozzle for low-pressure operation and cleaning agent suction.	25								\top				•											

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.

		EASY!Lock order no.	Order no. until 2015	Nozzle size Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX	HDS 12/18-4 S / HDS 12/18-4 SX HDS 10/20-4 M / HDS 10/20-4 MX	HDS 9/18-4 M / HDS 9/18-4 MX / HDS 1000 De HDS 8/18-4 M / HDS 8/18-4 MX / HDS 7/12-4 M / HDS 7/12-4 MX / HDS 1000 Be	HDS 8/18-4 C / HDS 8/18-4 CX HDS 8/17 C / HDS 8/17 CX	HDS 7/16 C / HDS 7/16 CX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C / HDS 6/14 CX HDS 6/14-6 C / HDS 6/14-6 CX / HDS 6/14 C / HDS 6/14 CX		HIS 13/20 De Tr.1	HDS 20/05 Super HT. HD 20/05 Super HT. HD 20/05 Super HT. HD 20/05 Super HT. HD 20/05	7.4 M 24 KW / ND3-E 0/10-4 M 12	olus	HD 10/25-4 S / HD 10/25-4 S Plus / HD 10/25-4 SX Plus / HD 10/25-4 Cage Plus HD 10/23-4 S / HD 10/23-4 S Plus	D 9/20	D 8/18-4 MX D 8/18-4 M C	17 MX Plus	0 7/14-4 MX	TID // 14*4 M/ TID // 14*4 M/ PIDS / TID // 14*4 M/ PIDS / TID // 14*4 M/ PID 6/15 M/ HD 6/15 M PIDS / HD 6/15 MZ PIUS /	HD 6/10-4 M 3/1 HD 6/10-4 M 3/1 HD 6/15 M 6/1	HD 6/13 CT VD 6/13 CX Plus HD 6/15 CT VD 6/15 CF Dlus / HD 6/15 CT VD 6/15 CF Dlus	HD 5/12 C HD 5/12 C FIOS HD 5/12 CX PIOS H	HD 5/31 P / HD 5/31 P PIUS HD 9/23 D TT / I / HD 9/23 D C / HD 9/23 G / HD 9/21 G	HD 25/15-4 Cage Plus HD 20/15-4 Cage Plus	HD 16/15-4 Cage Plus HD 715	HD 10/16-4 Cage EX HD 10/15-4 Cage Food	HD 7/10 CXF HD 8/20 G HD 7/15 G
Power nozzle spray angle 40°	20			140	Letting the body and the control of	1 26 1					_ _ _	. - -	. 1		Lel			1 1			I = I	Lel	lele		-1-1-	-				Iele
Power nozzle 40° - 040 Power nozzle 40° - 045			2.884-522.0 2.884-523.0		Flat jet for high area performance - suitable for sensitive surfaces.	26	+	\vdash	++			1	1	+-	14	+	+				14	1	1 4 1 5			-	++	+	++	
						28	-	\vdash			++	++	++	++	1	+					++	1	1		++	+-+	+	+	++	+
Power nozzle 40° - 050 Power nozzle 40° - 055		2.113-054.0 2.113-055.0	2.884-524.0			28	+	 -			++	++	++	++	+	++				\vdash	++	++	+	+	++	\perp	++	++	++	+
					_	30	+	╁┼	++		++	++	+-	+	+	+	+	H^{\sqcup}		\vdash	++	+	+	++	+	++	+	++	++	+
Power nozzle 40° - 075 Power nozzle 40° - 080		2.113-056.0			_	31	\perp		++		++	++	++		+		_					+	++		++	+	+	++	++	+
			2.004-327.0				\vdash	\vdash	++		++	++		++	+	- -	_	+			++	++	++		++	+	+	++	++	+
Power nozzle 40° - 090 Power nozzle 40° - 130		2.113-069.0 2.113-067.0		90	-	32	-	\vdash	++	\vdash	++	++	+		+	+	+			\vdash	+	++	+	++	++	++	+	++	++	+
Available accessories						33																						$\perp \perp \perp$	$\bot\bot$	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

TRIPLE NOZZLES



Kärcher triple nozzles combine quality, flexibility and cleaning power. The robust and high-quality stainless steel nozzle guarantees a long service life. Choose one of three spray types: 0° high-pressure point jet, 25° high-pressure flat jet and 40° low-pressure jet (with cleaning agent inlet). The integrated power nozzle contour in the 25° high-pressure flat jet guarantees maximum cleaning power.





	EASY!Lock order no.	Order no. until 2015	Max. workir	ig Nozzle size	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX	X HDS	/ HDS 7/12-4 HDS 8/17 C	HDS 6	HDS 5/12 C HDS 5/12 L HDS 6/15 LI / HDS 6/15 LIX	MD 55/13 U	HDS 5/11 U / HDS 5/11 UX HDS 2000 Super	HDS 801 D / HDS 801 B HD 17/14-4 SX Plus / HD 13/18-4 S Plus / HD 13/18-4 SX Plus	ıs / HD 10/25-4 SX Plu	SX Plus / HD 9/20-4 MX	HD 8/18-4 M / HD 8/18-4 M Plus / HD 8/18-4 MX Plus HD 7/16-4 M / HD 7/16-4 M Plus / HD 7/16-4 MX Plus	D 7/17 MX Plus	D 6/15 MX Plus		HD 8/18-4 M Cage St / HD 7/16-4 M Cage St HD 7/17 M Cage St	HD 6/15 M Cage HD 5/17 C / HD 5/17 C Plus / HD 5/17 CX Plus	HD 6/13 C / HD 6/13 C Plus HD 5/15 C / HD 5/15 C Plus / HD 5/15 CX Plus HD 5/12 C / HD 5/12 C Plus / HD 5/12 CX Plus	5 유	HD 715 HD 7/10 CKF HD 9/23 De / HD 9/23 G / HD 9/21 G	HD 8/20 G HD 7/15 G / HD 728 B Cage
Triple nozzles		<u>'</u>	'																								
Triple nozzle 028	1 4.117-024.0	4.767-144.0	300 bar	28		Manually switchable triple nozzle with stainless steel nozzle.	1																		T + T	$\Box\Box$	
Triple nozzle 032	2 4.117-027.0	4.767-195.0	300 bar	32		Sturdy, durable and resistant to dirt. Easy jet changeover between	2																				
Triple nozzle 033	3 4.117-028.0	4.767-146.0	300 bar	33		high-pressure point jet (0°), high-pressure flat jet with power nozzle	3																				
Triple nozzle 034	4 4.117-029.0	4.767-147.0	300 bar	34		contour (25°), and low-pressure flat jet (40°). For machines with injectors, low-pressure flat jet is used for cleaning	4																				
Triple nozzle 035	5 4.117-030.0	4.767-212.0	300 bar	35		agent suction and application.	5																		ı		
Triple nozzle 036	6 4.117-031.0	4.767-148.0	300 bar	36		1 -0	6																				
Triple nozzle 038	7 4.117-032.0	4.767-149.0	300 bar	38			7																				
Triple nozzle 040	8 4.117-033.0	4.767-150.0	300 bar	40			8																				
Triple nozzle 042	9 4.117-034.0	4.767-151.0	300 bar	42			9																				
Triple nozzle 045	10 4.117-036.0	4.767-153.0	300 bar	45			10																		1		
Triple nozzle 050	11 4.117-037.0	4.767-154.0	300 bar	50			11										□■										
Triple nozzle 060	12 4.117-040.0	4.767-157.0	300 bar	60			12																				
Angled vario nozzle 0-90°		-																									
Angled Vario nozzle 0-90°	13 4.113-007.0	4.763-039.0		50		Allows variable adjustment of the high-pressure jet spray angle	13																				
	14 4.113-008.0	4.763-058.0		55		from 0-90°. This allows easy adaptation to all types of contamina-	14																				
	15 4.113-006.0	4.763-036.0		80		tions and surfaces.	15															$ \cdot $					

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.

ROTARY NOZZLES



The Kärcher dirt blaster combines the advantages of point jets and flat jets. The nozzle spins at approximately 4,000 rpm on its own axle to apply a powerful cleaning spray to a large area.





	CONT.																														
	EASY!Lock order no.	Order no. until 2015	Max. workin	-1	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 13/20 DE Tr1	HDS 10/20-4 M / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX / HDS 8/18-4 MX HDS 8/18-4 MX / HDS 7/12-4 MX	105 0/10 0 m/s/) 1105 1/12 4 m/s 1105 1/12 4 m/s HDS 1000 De / HDS 1000 De	105 6/ 16-4 C / 105 6/ 16-4 C / 105 6/ 17 C 1DS 8/ 17 CX / HDS-E 8/ 16-4 M 36 kW / HDS-E 8/ 16-4 M 24 kW 105-E 9/ 146-4 M 12 kW	HDS-E 0, LC+2 MT LE RW HDS 7/16 C / HDS 7/16 CX / HDS 6/14-4 C HDS 6/14-4 CX / HDS 6/14 C / HDS 6/14 CX	HDS 801 D / HDS 801 B HDS 5/12 C / HDS 5/15 U / HDS 5/15 UX	HDS 5/13 U / HDS 5/13 UX / HDS 5/11 U HDS 5/11 UX	4DS 17/20 De Tr1 4DS 2000 Super	4D 17/14-4 S Pius / HD 17/14-4 SX Pius 4D 13/18-4 S Pius / HD 13/18-4 SX Pius	4D 10/25-4 S / HD 10/23-4 S / HD 9/20-4 M 4D 9/23 De Tr1 / HD 9/23 Ge Tr1 / HD 10/25-4 Cage Plus	HD 9/23 De / HD 9/23 G / HD 9/21 G HD 10/25-4 S Plus / HD 10/25-4 SX Plus / HD 10/23-4 S Plus	HD 10/23-4 SX Plus / HD 9/20-4 M Plus / HD 9/20-4 MX Plus HD 8/18-4 M / HD 7/16-4 M / HD 7/14-4 M	ID 8/18-4 M St / HD 8/18-4 M Cage St / HD 7/16-4 M Cage St 10 715	10 8/18-4 M Plus / HD 8/18-4 MX Plus / HD 7/16-4 M Plus 10 7/16-4 MX Plus / HD 7/14-4 M Plus / HD 7/14-4 MX Plus	<	4D 6/13 C / HD 5/11 P / HD 7/15 G 4D 728 B Cage	HD 7/17 M Plus / HD 7/17 MX Plus HD 6/15 M / HD 6/15 M St / HD 6/15 M Cage	HD 5/15 C / HD 5/12 C HD 6/15 M Plus / HD 6/15 MX Plus	4D 5/17 C 4D 5/17 C Plus / HD 5/17 CX Plus	HD 6/13 C Plus HD 6/13 CX Plus / HD 5/11 P Plus	HD 5/15 C Plus / HD 5/15 CX Plus / HD 5/12 C Plus HD 5/12 CX Plus	HD 25/13-4 tage rius HD 20/15-4 (age Plus	1D 16/15-4 Cage Plus 1D 10/15-4 Cage Food	1D 7/10 CXF 1D 8/20 G
Dirt Blaster, small	order no.	Ulitii 2015	pressure	Size	Price	резстрион		- -	- - -	- -	- - -	- - -	- -	_ -				- -	- -	1-1-		- - .				- -			-1-1		
Dirt blaster, small 030	1 4.114-018.0	4.767-229.0	180 bar	30		Dirt blaster with rotating point jet for 10 times the power and an	1 1			1.1	1 1	1.1					1					П			1.1		1.1	TT	TT	TI	
Dirt blaster, small 035	2 4.114-019.0	4.767-230.0	180 bar	35		increase in cleaning and area performance of up to 50% over its	2							+								+	+				11,		+	+	+
Dirt blaster, small 040	3 4.114-020.0	4.767-231.0	180 bar	40		predecessor. Ceramic nozzle/bearing ring. Max. 180 bar / 18 MPa,	3			++				$\dashv \dashv$					\vdash		++	101	5 6		\dashv			++	+	+	\top
Dirt blaster, small 045	4 4.114-021.0			45		60°C.	4			+				$\dashv \dashv$	\dashv							1	\top	$\overline{}$	\Box		\top	++	+	++	+
Dirt blaster, large		1																													
Dirt blaster, large 035	5 4.114-040.0	4.763-931.0	300 bar	35		Dirt blaster - rotating point jet - 10 times the cleaning	5															\Box							\top	\Box	
Dirt blaster, large 040	6 4.114-041.0	4.763-252.0	300 bar	40		performance. Maximum working time thanks to ceramic nozzle/	6																								
Dirt blaster, large 045	7 4.114-042.0	4.763-988.0	300 bar	45		bearing ring. Max. 300 bar / 30 MPa, 85 °C.	7															ı									
Dirt blaster, large 050	8 4.114-027.0	4.763-253.0	300 bar	50			8											□■						\Box							
Dirt blaster, large 055/060	9 4.114-036.0	4.763-250.0	300 bar	55			9																	\Box					\top		
Dirt blaster, large 070/080	10 4.114-030.0	4.763-254.0	300 bar	70			10							\Box		•							\sqcap								
Dirt blaster, large 090	11 4.114-043.0	4.767-076.0	300 bar	90			11							\sqcap								\top	\sqcap	\Box				\top	\top	\top	
Dirt blaster, large 100	12 4.114-048.0	4.764-208.0	300 bar	100			12																								
Dirt blaster, large 120	13 4.114-044.0	4.763-930.0	300 bar	120			13									•															
Dirt blaster, large 130	14 4.114-049.0	4.764-209.0	300 bar	130			14																								
Dirt blaster, large 170	15 4.114-046.0	4.764-201.0	300 bar	170			15																					ľ	4		
■ Included in the scope of supply	✓ □ Available acces	corios More l	/ärcher origina	l accossori	e can he	found on the following pages																									

Dirt blaster, large 170 15 4.114-046.0 4.764-201.0 300 bar 170 170 180 Included in the scope of supply. □ Available accessories. More Karcher original accessories can be found on the following pages.

STEAM JET NOZZLES



Whether for thawing and de-icing or depreserving vehicles – thanks to the special brass steam jet nozzles, Kärcher hot water high-pressure cleaners can also be used in steam operation.







	EASY!Loci order no.	Order no.	Nozzle size	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX HDS 12/18-4 S / HDS 12/18-4 SX HDS 10/20-4 M / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX HDS 9/18-4 M / HDS 9/18-4 MX HDS 8/18-4 M / HDS 9/18-4 MX	HDS //12-4 M/ HDS //12-4 MX / HDS 8/18-4 C HDS 8/18-4 CX / HDS 8/17 C / HDS 8/17 CX HDS 7/16 C / HDS 7/16 CX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C	6/14 CX
Steam jet nozzles									
Steam jet nozzle 50°	1 4.116-000	.0 4.766-023.0	1.5 mm	1	50° flat jet for cleaning and thawing in the steam stage, e.g. thawing sand and gravel, de-icing form work, depreserving vehicles.	1			
	2 4.116-003	.0 4.766-024.0	2 mm		and and graver, desicing form work, depreserving vertices.	2			
Steam jet nozzle	3 2.114-000	.0 2.885-045.0	40		Brass steam nozzle for operation of the HDS in steam stage.	3			
		.0 2.885-046.0				4			
	5 2.114-002					5] [Ш
	6 2.114-004					6			Ш
	7 2.114-006		_			7		$\perp \perp \perp$	Ш
	8 2.114-008					8			Ш
	9 2.114-009		_			9		\perp	Ш
	10 2.114-012	.0 2.885-044.0	110			10			Щ
Nozzle protector for steam nozzle	Lautes				The second secon				
Nozzle protector, rubber	11 5.394-059	.0 5.394-059.0			Nozzle protection for steam jet nozzles 4.116-000.0 and 4.116-001.0.	11		1 0 0 0	

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

PIPE CLEANING



Kärcher high-pressure cleaners can be used in combination with a special "pipe cleaning" accessory for optimal cleaning of dirty and blocked drains and pipes. The nozzle jets are set at an angle to allow the nozzle and hose to move freely through the pipe. Stubborn deposits adhering to the pipe walls are dislodged and washed out. Movement through very long or curved pipes may need assistance. The forward-facing rotating pencil jet effortlessly clears stubborn blockages.















22-23


		1	T			Ι			
	EASY!Lock order no.	Order no. until 2015	Max. working pressure	1	Diameter	Price	Description		HDS 13/20-45 / HDS 13/20-4 SX HDS 13/20-45 / HDS 13/20-4 SX HDS 13/20-45 / HDS 12/18-4 SX HDS 10/20-4 MX HDS 9/18-4 M / HDS 10/20-4 MX HDS 9/18-4 M / HDS 10/20-4 MX HDS 9/18-4 M / HDS 9/18-4 MX HDS 9/18-4 M / HDS 9/18-4 MX HDS 8/19-4 M / HDS 7/12-4 MX HDS 8/19-4 M / HDS 7/12-4 MX HDS 8/19-4 C / HDS 8/18-4 CX / HDS 6/14 C HDS 8/17-C A HDS 7/16 CX HDS 7/16-C / HDS 8/13 U / HDS 5/13 U / HDS 8/17 C / HDS 8/17
Pipe cleaning hose, ID 6									
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	1 6.110-046.0		250 bar				Highly flexible high-pressure hoses for cleaning the inside of pipes (threaded connection for R 1/8" nozzle).	1	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	2 6.110-008.0	6.390-030.0	250 bar					2	
Pipe cleaning hose, ID 6, 30 m,	3 6.110-047.0		250 bar					3	
max. 250 bar Pipe cleaning hose, ID 6, 10 m,	4 6.110-048.0		140 bar					4	
max. 140 bar Pipe cleaning hose, ID 6, 20 m,	5 6.110-049.0	6.390-028.0	140 bar					5	
max. 140 bar Pipe cleaning hose, ID 6, 30 m,	6 6.110-050.0	6.390-029.0	140 bar					6	
max. 140 bar Pipe cleaning nozzle									
Pipe cleaning dirt blaster D21/040	7 4.765-001.0	6.415-944.0		40	21 mm		With R-1/8" connection for attachment to pipe cleaning	7	
Pipe cleaning dirt blaster D21/060	8 4.765-002.0			60	21 mm		hose. 1 x forward rotary nozzle, 3 x 30° backwards.	8	
Pipe cleaning dirt blaster D21/090	9 4.765-003.0	1		90	21 mm			9	
Pipe cleaning dirt blaster D30/040	10 4.765-004.0	6.415-946.0		40	30 mm			10	
Pipe cleaning dirt blaster D30/060	11 4.765-005.0	6.415-947.0		60	30 mm			11	
Pipe cleaning dirt blaster D30/090	12 4.765-010.0			90	30 mm			12	
Pipe cleaning nozzle 080	13 5.763-087.0	5.763-087.0		80	24 mm		With R-1/8" connection for attachment to pipe cleaning	13	
Pipe cleaning nozzle 100	14 5.763-088.0	5.763-088.0		100	24 mm		hose. 4 × 30° backwards.	14	
Pipe cleaning nozzle 120	15 5.763-089.0	5.763-089.0		120	24 mm		With R-1/8" connection for attachment to pipe cleaning hose. $8 \times 30^{\circ}$ backwards.	15	
Pipe cleaning nozzle	16 5.763-015.0	5.763-015.0		55	16 mm		With R-1/8" connection for attachment to pipe cleaning	16	
	17 5.763-019.0	5.763-019.0		65	16 mm		hose. 3 × 30° backwards, Ø 16 mm.	17	
	18 5.763-016.0	5.763-016.0		60	16 mm		With R-1/8" connection for attachment to pipe cleaning	18	
	19 5.763-020.0			65	16 mm		hose. 1 × forwards, 3 x 30° backwards, Ø 16 mm.	19	
	20 5.763-017.0			50	30 mm		With R-1/8" connection for attachment to pipe cleaning hose. 3 × 30° backwards, Ø. 30 mm.	20	
Rotating pipe cleaning nozzle	21 5.763-021.0 22 6.415-428.0	_		70 50	30 mm 16 mm		With R-1/8" connection for attachment to pipe cleaning	21 22	
voraring hihe riegillig interie	22 0.415-428.0	0.415-420.0		30	10 1/1111		hose. Four rotating jets.	22	
Rotating pipe cleaning nozzle	23 6.415-440.0	6.415-440.0		65	16 mm		With R-1/8" connection for attachment to pipe cleaning hose. Four rotating jets.	23	

■ NEW ☐ Available accessories. More Kärcher original accessories can be found on the following pages.

BARREL AND CONTAINER CLEANING




Kärcher also offers numerous accessories for barrel and deposit cleaning for perfect results in combination with Kärcher high-pressure cleaners. For example, the spray heads from the HKF range. They are optimally suited to interior cleaning of containers with capacities of up to 3,000 litres and openings from 50 mm. Or the BC 14/12, specially developed for oak barrels, which even has an integrated vacuum function.













	EASY!Lock order no.	Order no. until 2015	Nozzle size Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX HDS 12/18-4 S / HDS 12/18-4 SX HDS 12/18-4 S / HDS 12/18-4 SX HDS 10/20-4 M / HDS 10/20-4 MX / HDS 9/18-4 M HDS 9/18-4 MX HDS 9/18-4 MX HDS 9/18-4 MX HDS 9/18-4 MX / HDS 9/18-4 CX HDS 9/18-4 MX / HDS 9/18-4 CX HDS 9/14-4 CX / HDS 8/17 CX HDS 8/17 C / HDS 8/17 CX HDS 8/17 C / HDS 8/17 CX HDS 8/17 C / HDS 6/14-4 CX HDS 7/16 C / HDS 6/14-4 CX HDS 7/16 C / HDS 6/14-4 CX HDS 10/14-4 S Plus / HD 17/14-4 SX Plus HD 17/14-4 S Plus / HD 17/14-4 SX Plus HD 17/14-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 10/23-4 S Plus / HD 10/23-4 SX Plus
Barrel and tank cleaning						
Barrel cleaner BC 14/12	1 2.112-020.0	2.641-740.0		The BC 14/12 is a spray unit for the economic interior cleaning of containers and drums – particularly oak barrels with capacity between 225 and 600 litres.	1	
HKF 50 spray head, brass						
HKF 50 spray head, brass	2 3.631-039.0	3.631-039.0		Immersion depth 850 mm. Interior cleaning head for barrel and deposit cleaning for bunghole diameters from 50 mm. Can be connected directly to the high-pressure cleaner. Electro motor drive. Vertical and horizontal operation possible.	2	
	3 3.631-058.0	3.631-058.0		Immersion depth 150 mm. Interior cleaning head for barrel and deposit cleaning for bunghole diameters from 50 mm. Can be connected directly to the high-pressure cleaner. Electro motor drive. Vertical and horizontal operation possible.	3	
Nozzle kit for spray head HKF 50 (3.631-009						
Nozzle 030 for 2-nozzle operation HKF 50	4 6.415-444.0			1 x nozzle 030 for 2-nozzle operation.	4	
Nozzle 045 for 2-nozzle operation HKF 50				1 x nozzle 045 for 2-nozzle operation.	5	
Nozzle 090 for 1-nozzle operation HKF 50			90	1 × nozzle 090 for 1-nozzle operation.	6	
Cone for plugging into bungholes	7 4.132-002.0	4.132-002.0		Cone for fixing in bungholes.	7	
Double grip for precise control of spray head	8 2.863-036.0	2.863-036.0		Double grip for precise control of spray head.	8	
Screw plug for using a spray head with one nozzle	9 5.411-061.0	5.411-061.0	following pages	Screw plug for spray head operation with one nozzle.	9	

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

SURFACE CLEANER















Surface Cleaners offer great area performance and clean splash-free. They come with a plas	stic
or stainless steel hood (hot water operation). Tip for extra-large surfaces: the FR 50 Me.	

	EASY!Lock order no.	Order no. until 2015	Flow rate	Nozzle size	Diameter P	ice Description		HDS 13/20-45 / HDS 13/20-4 SX / HDS 12/18-4 SX HDS 13/20-4 M / HDS 10/20-4 MX / HDS 9/18-4 M HDS 9/18-4 MX HDS 9/18-4 MX HDS 9/18-4 MX HDS 9/18-4 MX / HDS 8/18-4 CX HDS 8/13-4 MX / HDS 8/18-4 CX HDS 8/13-4 MX / HDS 8/18-4 CX HDS 8/17-4 MX / HDS 8/18-4 CX HDS 8/17-4 MX / HDS 8/18-4 CX HDS 6/14-4 C / HDS 8/17 CX / HDS 7/16 C HDS 7/12-4 MX / HDS 8/13 CX / HDS 7/16 C HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 CX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 CX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 CX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 CX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 CX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 CX HDS 6/14-4 C / HDS 6/14-4 CX
FR Classic surface cleaner								
FR Classic surface cleaner	1 2.111-016.0	2.643-476.0			300 mm	The entry level model of Kärcher surface cleaners for splash-proof cleaning of surfaces in inside and outside areas. Nozzle kit must be ordered separately. Max. 150 bar / 600 l/h / 40°C.	1	
Hard surface cleaner FR 30								
FR 30 Surface Cleaner	2 2.111-011.0	2.642-997.0			300 mm	Up to 10 times greater area coverage compared with the conventional high-pressure jet. Plastic casing for optimal manoeuvrability, double ceramic bearing for long working times, flexible connection joint for optimal handling and integrated parking position. Machine-specific nozzle kit must be ordered separately. Max. 180 bar / 850 l/h / 60 °C.	2	
FR 30 Me surface cleaner Hard Surface Cleaner FR 30 Me	3 2.111-013.0	2 640-355 0	1	1	300 mm	High-quality, but water-resistant surface cleaner with	3	
natu surface Clediler FR 30 Me	3 2.111-013.0	2.040-355.0			300 111111	High-quality, hot water-resistant surface cleaner with stainless steel casing,double ceramic bearing, non-marking steering rollers, integrated suction hose connection for suction of the spray water. Ideal for interior cleaning and use in the food industry. Machine-specific nozzle kit must be ordered separately.Max. 250 bar / 1,300 l/h / 85 °C.		
Hard Surface Cleaner FR 50								
Surface Cleaner FR 50 Me	4 2.111-023.0	2.640-679.0			500 mm	With 500 mm working width, the FR 50 Me is especially suitable for large surfaces. Hot water-resistant, stainless steel casing, double ceramic bearing, convenient push handle, non-marking steering rollers and integrated cleaning agent dosing at low pressure. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 1,800 l/h / 85 °C.	4	
Machine-specific nozzle kits for I								
Nozzle kit for FR Classic 034	5 2.885-313.0			34		Machine-specific nozzle kit for FR Classic.	5	
Nozzle kit for FR Classic 040	6 2.885-312.0	2.885-312.0		40			6	
Machine-specific nozzle kits for I		12640 4000	450 500 1/5		1	Whether are the marking and the control of the cont	1 21	
Nozzle kit for surface cleaners	7 2.640-482.0					Kärcher power nozzle machine-specific nozzle kit for surface cleaners.	7	
Nozzle kit for surface cleaners	8 2.640-401.0 9 2.639-187.0					Sorrace electricis.	8	
Nozzle kit for surface cleaners Nozzle kit for surface cleaners	10 2.640-442.0					_	10	
Nozzle kit for surface cleaners	11 2.639-188.0						11	
□ Available accessories More	12 2.640-781.0						12	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

SURFACE CLEANER WITH SUCTION















All end to tedious filising: The FRV 30, FRV 30 Me and now the F	KV 30 Me 30 Ide Cledileis
clean with maximum area performance without splashing and au	tomatically vacuum the dirty
water.	

	EASY!Lock order no.	Order no. until 2015	Nozzle size	Price Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S	/ HDS 10/20 HDS 9/18-4 I	8/18-4 MX / HDS 7/12-4 M / HDS 7/12-4 8/18-4 C / HDS 8/18-4 CX / HDS 8/17 C	HDS 8/17 CX / HDS 7/16 C / HDS 7/16 CX HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C	6/14 CX 5/12 C / HDS 5/15 II / HDS 5/15	HDS 5/13 U/ HDS 5/13 UX / HDS 5/11 U HDS 5/13 U/ UX	HDS 17/20 De Tr1 HDS 13/20 De Tr1	HDS 2000 Super HDS-E 8/16-4 M 36 KW / HDS-E 8/16-4 M 24 KW / HDS-E 8/16-4 M 12 KW	Plus	HD 10/25-4	ᅩᆝ부ᆝ	ID 8/18-4 M) ID 7/16-4 M)	HD 7/17 M / HD 7/17 M Plus / HD 7/17 MX Plus HD 7/14-4 M / HD 7/14-4 M Plus / HD 7/14-4 MX Plus	<u>∵</u> । ∣	HD 7/17 M St HD 6/15 M St	HD 8/18-4 M Cage St / HD 7/16-4 M Cage St HD 7/17 M Cage St	17 CX	HD 6/13 C / HD 6/13 C Plus / HD 6/13 CX Plus HD 5/15 C / HD 5/15 C Plus / HD 5/15 CX Plus	12 CX	HD 20/15-4 Cage Plus HD 16/15-4 Cage Plus	HD 10/25-4 Cage Plus HD 715	HD 10/15-4 Cage Food HD 7/10 CXF / HD 9/23 De / HD 9/23 G HD 0/21 C	HD 9/21 G HD 8/20 G HD 7/15 G / HD 728 B Cage
FRV 30 Surface Cleaner FRV 30 Surface Cleaner	1 2.111-010.0	2 642-999 0	1	With the integrated, automatic suction of the dirty water, the FRV 30	1	1.1	1.1	1 1		1 1	П		1 1	1 1	1 1			1.1	1 1		ll			1 1	1 1			
The 30 surface clearer	2.111 010.0	2.042 333.0		makes surface cleaning even more efficient and can be used in both inside and outside areas. There is no longer a need to rinse the surface after cleaning, since the dirty water can be discharged through the 5 m suction hose supplied. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately.Max. 250 bar / 1300 l/h / 60 °C.																								
Rubber lip for FRV 30	2 2.642-910.0	2.642-910.0		For using the FRV 30 on smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means that interior floors are dry in just a few minutes.	2																			0 0				
Extension hose 5 m	3 4.440-939.0	4.440-939.0		5 m extension hose for FRV 30. Includes connection adapters.	3	\dashv		+																				
Hose fastening attachment kit	4 2.642-528.0	2.642-528.0		Suction cup for fixing the suction hose to smooth surfaces.	4			5101																		0 0 0		
Dirt trap attachment kit	5 2.642-532.0	2.642-532.0		Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	5																	0 0	0 0			0 0 0	0 0 [
FRV 30 Me surface cleaner																												
FRV 30 Me Surface Cleaner	6 2.111-012.0	2.642-911.0		Thanks to automatic suction of the waste water, the stainless steel FRV 30 Me surface cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85 °C. The FRV 30 Me features a temperature-resistant 7.5 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately.Max. 250 bar / 1300 l/h / 85 °C.	6																							
Extension hose FRV 30 Me and FRV 50 Me	7 4.441-040.0	4.441-040.0		5 m extension hose for FRV 30 Me. Includes connection adapters.	7																					100	100	
FRV 50 Me Surface Cleaner			'											 1			-			'								
FRV 50 Me surface cleaner	8 2.111-024.0	2.643-598.0		Surface cleaning with automatic suction of the dirty water for very large surfaces – the FRV 50 Me. Hot water cleaning up to 85 °C. The FRV 50 Me features a 10-metre temperature-resistant polyurethane suction hose. Other quality features include the non-marking castors and the double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85 °C.	8																							

☐ Available accessories. More Kärcher original accessories can be found on the following pages.



	EASY!Lock order no.	Order no.	Nozzle size	Price	Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S	HDS LV, 16-4 S.X. / HDS 10/, 20-4 MX HDS 9/18-4 S.X. / HDS 9/18-4 MX / HDS 9/18-4 MX	HDS 8/18-4 MX / HDS 7/12-4 M / HDS 7/12-4 MX HDS 8/18-4 C / HDS 8/18-4 CX / HDS 8/17 C HDS 8/17 CX / HDS 7/16 C / HDS 7/16 CX	HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C HDS 6/14 CX	HDS 5/12 C / HDS 5/15 U / HDS 5/15 UX HDS 5/13 U / HDS 5/13 UX / HDS 5/11 U HDS 6/11 IIY	HDS 17/20 DE Tr1 HDS 13/20 DE Tr1	HDS-E 8/16-4 M 36 kW / HDS-E 8/16-4 M 24 kW / HDS-E 8/16-4 M 12 kW	HDS 1000 De / HDS 1000 Be HDS 801 D / HDS 801 B	HD 17/14-4 S Plus / HD 17/14-4 SX Plus HD 13/18-4 S Plus / HD 13/18-4 SX Plus	HD 10/23-4 S / HD 10/25-4 S PIUS / HD 10/25-4 SX PIUS HD 10/23-4 S / HD 10/23-4 S PIUS / HD 10/23-4 SX PIUS HD 10/23-4 S / HD 10/23-4 S PIUS / HD 10/23-4 SX PIUS	HD 9/20-4 M/ HD 9/20-4 M Plus / HD 9/20-4 MX Plus HD 8/18-4 M/ HD 8/18-4 M Plus / HD 8/18-4 MX Plus	HD 7/16-4 M / HD 7/16-4 M Plus / HD 7/16-4 MX Plus HD 7/17 M / HD 7/17 M Plus / HD 7/17 MX Plus	HD 7/14-4 M / HD 7/14-4 M Plus / HD 7/14-4 MX Plus HD 6/15 M / HD 6/15 M Plus / HD 6/15 MX Plus	HD 8/18-4 M St HD 7/17 M St	HD 6/15 M St HD 8/18-4 M Cage St / HD 7/16-4 M Cage St HD 7/17 M Cage St	HD 6/15 M Cage HD 5/17 C/ HD 5/17 C Plus / HD 5/17 CX Plus	HD 6/13 C / HD 6/13 C Plus / HD 6/13 CX Plus HD 5/15 C / HD 5/15 C Plus / HD 5/15 CX Plus	HD 5/12 C / HD 5/12 C Plus / HD 5/12 CX Plus HD 9/23 DE Tr1 / HD 9/23 GE Tr1	HD 20/15-4 Cage Plus	TID 10/23-4-Lage Flus HD 10/23-4-Lage Flus	HD 10/15-4 Cage Food HD 7/10 CXF / HD 9/23 De / HD 9/23 G	HD 9/21 G HD 8/20 G	HD 7/15 G / HD 728 B Cage
Machine-specific nozzle kits for FRV	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	1	1	111111	1																								
Nozzle kit 035 - for FRV	9 2.642-430.0	2.642-430.0	35		Machine-specific nozzle kit Kärcher power nozzles and jet nozzle for	9																							
Nozzle kit 040 - for FRV	10 2.642-431.0	2.642-431.0	40		FRV 30 and FRV 50.	10																							
Nozzle kit 045 - for FRV	11 2.642-432.0	2.642-432.0	45			11																							
Nozzle kit 050 - for FRV	12 2.642-433.0	2.642-433.0	50			12																						ا د	
Nozzle kit 080 - for FRV	13 2.642-982.0					13														\Box						[]		
Nozzle kit 100 - for FRV	14 2.643-769.0	2.643-769.0	100			14																							
Nozzle kit 126 - for FRV	15 2.643-768.0	2.643-768.0	126			15														\perp				1					

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

WET JET UNIT



The wet jet unit fits easily on Kärcher high-pressure cleaner spray lances. The abrasive is sucked up, entrained in the water jet and applied with a powerful abrasive action. Ideal for removing rust, scale and paint from components as well as graffiti.







	EASY!Lock	Order no.	Nozzle				HDS 13/20-45 / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 13/20-4 SX / HDS 12/18-4 S HDS 12/18-4 SX / HDS 13/20-6 MT / HDS 12/18-4 S HDS 10/20-4 M / HDS 10/20-4 MX / HDS 9/18-4 M HDS 10/20-4 M / HDS 10/20-4 MX / HDS 9/18-4 M HDS 9/18-4 MX / HDS 10/20-4 MX / HDS 1/12-4 M HDS 9/18-4 MX / HDS 1000 De / HDS 1000 Be HDS 8/18-4 C / HDS 8/18-4 CX / HDS 8/17 C HDS 8/18-4 C / HDS 8/18-4 CX / HDS 8/17 C HDS 8/19-4 CX / HDS 6/14-4 CX / HDS 6/14-4 CX HDS 8/19-4 CX / HDS 6/14 C / HDS 6/14-4 CX HDS 8/19-4 CX / HDS 6/14 C / HDS 6/14-4 CX HDS 8/19-4 CX / HDS 6/14 C / HDS 6/14-4 CX HDS 8/19-4 CX / HDS 6/14 C / HDS 6/14-4 CX HDS 8/19-4 CX / HDS 6/14 C / HDS 6/14-4 CX HDS 8/19-4 CX / HDS 6/14 C / HDS 6/14-4 CX HDS 8/19-4 CX / HDS 6/14 C / HDS 6/14 CX HDS 8/19-4 CX / HDS 6/14 C / HDS 6/14 CX HDS 6/14-4 CX / HDS 6/14 C / HDS 6/14 CX HDS 8/19-2 C HDS 6/14 C / HDS 6/14 CX HDS 17/20 De Tr1 HDS 9/20-4 M / HD 9/20-4 M Plus / HD 10/25-4 Cage Plus HD 10/23-4 S / HD 10/23-4 S Plus / HD 10/25-4 Cage Plus HD 9/23 C / HD 9/21 G HD 9/23 C / HD 9/21 G HD 9/23 C / HD 9/21 G HD 7/17 M / HD 7/14-4 M Plus / HD 8/18-4 MX Plus HD 7/15-4 M / HD 8/18-4 M Cage St / HD 7/16-4 M Cage St / HD 7/15-4 M Cage St / HD 6/13 C HD 6/13 C Plus / HD 6/13 C Plus / HD 6/13 C HD 6/13 C Plus / HD 6/13 C Plus / HD 6/13 C HD 6/15 M / HD 6/15 M Plus / HD 5/17 C HD 6/15 M / HD 6/15 M Plus / HD 5/17 C HD 6/15 M St / HD 6/15 M Cage (HD 5/17 C HD 6/15 M St / HD 6/15 M Cage (HD 5/17 C HD 6/15 M St / HD 6/15 M CAGE (HD 5/17 C HD 6/15 M St / HD 6/15 M CAGE (HD 5/17 C HD 6/15 M St / HD 6/15 M CAGE (HD 5/17 C HD 6/15 M St / HD 6/15 M CAGE (HD 5/17 C HD 6/15 M St / HD 6/15 M CAGE (HD 5/17 C	10 5/15 C PIUS / HD 5/15 CX PIUS / HD 5/11 C 10 5/12 C PIUS / HD 5/12 CX PIUS / HD 5/11 P 10 5/11 P PIUS 10 16/15-4 Cage PIUS 10 10/15-4 Cage Food 10 7/10 CXF
	order no.	until 2015	size	Price	Description			
Wet jet unit (without nozzle)		1 . ==== =	1		lander and the second second	1		
Wet jet unit with flow control (without nozzles)	1 4.115-000.0	4.762-010.0			Adds abrasive to high-pressure jet. For removing paint, rust, scaling. Fits on spray lance in place of HP nozzle. With flow control.	1		
Wet jet unit without flow control (nozzles not	2 4.115-006.0	4.762-022.0			Adds abrasive to high-pressure jet. For removing paint, rust, scal-	2		
included)					ing. Fits on spray lance in place of HP nozzle. Without flow control.			3101010101010
Nozzle kits for wet jet unit		1						
Nozzle kit for wet jet unit 035	3 2.112-021.0	2.638-526.0			Consisting of wet jet nozzle and nozzle insert - only for use in	3	3	
Nozzle kit for wet jet unit 040	4 2.112-019.0	2.637-900.0			combination with wet jet unit 4.115-000.0 4.115-006.0.	4	4	
Nozzle kit for wet jet unit 045	5 2.112-022.0	2.637-901.0				5	5	
Nozzle kit for wet jet unit 050	6 2.112-023.0	2.637-902.0				6	6 0000000000000000000000000000000000000	
Nozzle kit for wet jet unit 055	7 2.112-024.0	2.637-903.0				7	7	
Nozzle kit for 060 wet jet unit	8 2.112-025.0	2.637-904.0				8	8	
Nozzle kit for wet jet unit 065	9 2.112-026.0	2.637-905.0				9	9	
Nozzle kit for wet jet unit 070	10 2.112-027.0		70			10		
Nozzle kit for 080 wet jet unit	11 2.112-029.0	2.637-908.0				11		
Nozzle kit for wet jet unit 100	12 2.112-030.0	2.637-910.0	100			12	2	
Boron carbide nozzle		1						
Boron carbide nozzle, for machines up to 1000 l/h	13 6.415-084.0		6 mm		In addition to nozzle kits. Highly wear-resistant spray nozzle with	13		
Boron carbide, for machines from 1000 I/h	14 6.415-083.0		8 mm		boron carbide chuck for continuous use.	14		

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

FOAM SYSTEMS



The handy cup foam lance from Kärcher is particularly suitable for vehicle washes.

The cleaning agent tank is on the lance. The injector for detergent inlet is integrated into the lance and is compatible with numerous Kärcher cleaning appliances.















1

	EASY!Lock order no.	Order no. until 2015	Flow rate	Price	Description		HDS 13/20-4 S / HDS 12/18-4 S / HDS 10/20-4 M	2000 Super 13/20-4 SX / HDS 12/18-4	HDS 17/20 De Tr1 / HDS 13/20 De Tr1 HDS 9/18-4 M / HDS 1000 De / HDS 1000 Be	HDS 9/18-4 MX	HDS 7/16 C / HDS-E 8/16-4 M 3	HDS-E 8/16-4 M 24 kW / HDS-E 8/16-4 M 12 kW HDS 8/18-4 MX / HDS 7/12-4 MX / HDS 8/18-4 CX	HDS 8/17 CX / HDS 7/16 CX HDS 6/14-4 C / HDS 6/14 C	HDS 6/14-4 CX / HDS 6/14 CX HDS 5/12 C	HDS 5/15 U / HDS 5/15 UX / HDS 5/13 U HDS 5/13 UX / HDS 5/11 U / HDS 5/11 UX	HDS 801 D / HDS 801 B HD 17/14.4 C Diuc / HD 17/14.4 CV Diuc		HD 10/25-4 S / HD 10/25-4 S Plus / HD 10/25-4 SX Plus HD 10/23-4 S / HD 10/23-4 S Plus / HD 10/23-4 SX Plus	χ Δ	HD 9/23 G HD 8/18-4 M / HD 8/18-4 M St	HD 8/18-4 MX Plus / HD 7/16-4 MX Plus / HD 7/14-4 MX Plus	HD 7/17 M / HD 7/17 M Plus / HD 7/17 M St	HD 7/17 MX Plus HD 7/14-4 M / HD 7/14-4 M Plus	HD 6/15 M / HD 6/15 M Plus / HD 6/15 M St HD 6/15 MX Plus	HD 8/18-4 M Cage St HD 7/16-4 M Cage St / HD 7/15 G / HD 728 B Cage	HD 7/17 M Cage St HD 6/15 M Cage / HD 5/17 C / HD 5/17 C Plus	HD 5/17 CX Plus / HD 5/15 C/ HD 5/15 C Plus	HD 5/115 CK Plus / HD 5/12 C Plus / HD 5/12 CK Plus HD 5/11 CK Plus HD 5/12 CK		HD 25/15-4 Cage Plus / HD 20/15-4 Cage Plus / HD 16/15-4 Cage Plus HD 10/25-4 Cage Plus	HD 715 UN 10/15-A Case Food	HD 1//15-4 Lage Food HD 7//10 CXF	HD 9/21 G HD 8/20 G
Inno Foam Kit	1 1 2 4 4 2 200	0 100404540																															
Inno Foam Set with detergent injector	1 2.112-000.0	0 2.640-151.0			High-pressure foam system for use with mobile and stationary HP/ HDS machines for cleaning and disinfection. Dual spray lance with foam nozzle and option to switch to high-pressure stream for clear rinsing. The nozzle kits for different ranges must be ordered separate- ly. Cannot be used with machines that have a hose reel.	1																					,						
Inno Foam Set		0 2.640-692.0			HP foam system for use with mobile and stationary HP/HDS machines	2																										از	
Inno Foam Set HD 7/10 CXF with cleaning agent injector and nozzle kit	3 2.112-009.	0 2.641-544.0			for cleaning anddisinfection. Dual jet pipe with foam jet and conversion to HP stream for clear rinsing. The nozzles kits for different unit classes must be ordered separately.	3																											
Easy Foam Set	1 1		1														1 1																
Easy Foam Set with cleaning agent injector	4 2.112-010.0	0 2.640-691.0			High-pressure foam system for mobile and stationary HP/HDS ma- chines for cleaning and disinfection. Foam nozzle for connecting to the high-pressure spray lance. The nozzle kits for different ranges must be ordered separately. Cannot be used with machines that have a hose reel.	4																			<u> </u>		,						
Easy Foam Set	5 2.112-011.0	0 2.640-693.0			HP foam system for mobile and stationary HP/HDS machines for	5																						\Box	\Box				
HD 7/10 CXF with cleaning agent injector and nozzle kit	6 2.112-012.0	0 2.641-564.0			cleaning and disinfection. Foam jet for connection to HP spray lance. The nozzles kits for different unit classes must be ordered separately.	6																											
Nozzle kits for Inno/Easy Foam Set	1 7 2 444 000		14000 4000 1/1/																														
Nozzle kit 110 for Inno / Easy Set 1000-1300 l/h		0 2.640-689.0 0 2.640-688.0			Can be adapted to different unit performances for cost-effective use.	8																					$\perp \perp$		\perp	$\perp \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \!$	\perp	\perp	
Nozzle kit 090 for Inno / Easy Set 700-1000 I/h Nozzle kit 060 for Inno / Easy Set	8 2.111-019. 9 2.111-018.		700-1000 l/h 600-700 l/h			9																					$\perp \perp$	$\perp \downarrow$	\perp]	
600-700 I/h	9 2.111-016.	0 2.040-087.0	000-700 1/11			9																						[
Nozzle kit 055 for Inno / Easy Set 500-600 I/h	10 2.111-009.	0 2.640-870.0	500-600 l/h			10																					100					П	
Nozzle kit 110 for Inno / Easy Set for HD 13/18	11 2.111-022.	0 2.640-694.0	1300 l/h		For HD 13/18.	11																											
Foam nozzle mounting kit	1																						, ,										
Foam nozzle attachment kit	12 2.112-013.	0 2.637-926.0			For applying foam cleaning agent in metered quantities in sanitary and food areas or where long reaction times are necessary; fits to spray lance in place of HP nozzle.	12																						ם נ				ם	

□ Available accessories. More Kärcher original accessories can be found on the following pages.







	EASY!Lock order no.	Order no.	Flow rate	Price Description		HDS 13/20-4 S / HDS 12/18-4 S / HDS 10/20-4 M	HDS 2000 Super HDS 13/20-4 SX / HDS 12/18-4 SX / HDS 10/20-4 MX	HDS 17/20 De Tr1 / HDS 13/20 De Tr1 HDS 9/18-4 M / HDS 1000 De / HDS 1000 Be	7-8 ≥	HDS-E 8/16-4 M 24 kW / HDS-E 8/16-4 M 12 kW HDS 8/18-4 MX / HDS 7/12-4 MX / HDS 8/18-4 CX	HDS 8/17 CX / HDS 7/16 CX HDS 6/14-4 C / HDS 6/14 C	HDS 6/14-4 CX / HDS 6/14 CX HDS 5/12 C	HDS 5/15 U / HDS 5/15 UX / HDS 5/13 U HDS 5/13 UX / HDS 5/11 U / HDS 5/11 UX	HDS 801 D / HDS 801 B HD 17/14-4 S Plus / HD 17/14-4 SX Plus	HD 10/25-4 S / HD 10/25-4 S Plus / HD 10/25-4 SX Plus HD 10/23-4 S / HD 10/23-4 S Plus / HD 10/23-4 SX Plus	0-4 MX P	8-4 M St		HD 7/17 M / HD 7/17 M Plus / HD 7/17 M St HD 7/17 MX Plus	HD //14-4 M / HD //14-4 M PIUS HD 6/15 M / HD 6/15 M PIUS / HD 6/15 M St HD 6/15 MX PIUS	HD 8/18-4 M Cage St HD 7/16-4 M Cage St / HD 7/15 G / HD 728 B Cage	HD 7/17 M Cage St HD 6/15 M Cage / HD 5/17 C / HD 5/17 C Plus	HD 5/17 CX Plus / HD 5/12 C Plus / HD 5/12 CX Plus HD 5/15 CX Plus / HD 5/11 C Plus / HD 5/12 CX Plus HD 5/11 P / HD 5/11 P Plus	Plus	HD 25/15-4 Cage Plus / HD 20/15-4 Cage Plus / HD 16/15-4 Cage Plus HD 10/25-4 Cage Plus HD 715	HD 10/15-4 Cage Food HD 7/10 CXF	HD 8/20 G
Cup foam lance																											
Cup foam lance Basic 1	13 4.112-053.0		350-600 l/h	New development for high-pressure cleaners with flow rate of 350-600 l/h. Optimal foam quality with half the cleaning agent consumption in conjunction with VehiclePro Foam Cleaner RM 838.	13																						
Cup foam lance Basic 2	14 4.112-054.0		700-800 l/h	New development for high-pressure cleaners with flow rate of 700-800 l/h. Optimal foam quality with half the cleaning agent consumption in conjunction with VehiclePro Foam Cleaner RM 838.	14																						
Cup foam lance Basic 3	15 4.112-055.0		900-2500 l/h	New development for high-pressure cleaners with flow rate of 900-2500 l/h. Optimal foam quality with half the cleaning agent consumption in conjunction with VehiclePro Foam Cleaner RM 838.	15																						
Cup foam lance Advanced 025	16 2.112-017.0	6.394-968.0		Short, practical foam lance with 1-litre cleaning agent container directly on the lance. Its compact design makes it perfect for cleaning lorries	16											0 0											
Cup foam lance Advanced 042	17 2.112-018.0	6.394-969.0		with foam, for example. EASY!Lock rotary connection, variable clean- ing agent dosage via a control knob on the lance itself, adjustable	17										1												
				spray angle.																							

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

CLEANING AGENT INJECTORS



The injectors are attached to the high-pressure output of the HD/HDS devices. The dosing is adjusted directly on the cleaning agent injector. Important: use the corresponding nozzle kit for the device











	1																						$\overline{}$		$\overline{}$	$\overline{}$	$\overline{}$	$\overline{}$
		EASY!Lock order no.	Order no.	Price Description		-1DS 13/20-4 S / HDS 2000 Super	HDS 13/20-4 SX 4DS 12/18-4 S 1DS 12/18-4 SX	HDS 10/20-4 M	HDS 9/18-4 M / HDS 8/18-4 M / HDS 7/12-4 M HDS 8/17 C / HDS 7/16 C / HDS-E 8/16-4 M 36 kW	HDS-E8/16-4 M 24 kW / HDS-E8/16-4 M 12 kW 4DS 9/18-4 MX / HDS 8/18-4 MX / HDS 7/12-4 MX	HDS 8/17 CX / HDS 7/16 CX HDS 8/18-4 C	HDS 8/18-4 CX 4DS 6/14-4 C / HDS 6/14 C / HDS 5/12 C	HDS 5/15 U / HDS 5/13 U / HDS 5/11 U HDS 6/14-4 CX / HDS 6/14 CX / HDS 5/15 UX	HDS 5/13 UX / HDS 5/11 UX 1DS 1000 De / HDS 1000 Be	HDS 801 D / HDS 801 B 40 77/14-4 S Plus	10 17/14-4 SX Plus	HD 13/18-4 S Plus HD 13/18-4 SX Plus	HD 10/25-4 S / HD 10/25-4 S Plus / HD 10/23-4 S 4D 10/23-4 S Plus	HD 10/25-4 SX Plus / HD 10/23-4 SX Plus +D 9/20-4 M / HD 9/20-4 M Plus	HD 8/18-4 M / HD 8/18-4 M Plus / HD 7/16-4 M HD 7/16-4 M Plus / HD 7/17 M / HD 7/17 M Plus	HD 7/14-4 M / HD 7/14-4 M Plus / HD 6/15 M	10 6/15 M St / H B 8/18-4 M Cage St / HD 7/16-4 M Cage St	HD 7/17 M Gage SY / HD 6/15 M cage HD 5/17 C / HD 5/17 C Plus / HD 6/13 C	HD 6/13 C Plus / HD 5/15 C / HD 5/15 C Plus HD 5/12 C Plus / HD 5/11 P / HD 5/11 P Plus	HD 5/17 CX Plus / HD 6/13 CX Plus / HD 5/15 CX Plus HD 5/12 CX Plus	HD 5/12 C HD 9/23 De Tr1 / HD 9/23 Ge Tr1 / HD 10/25-4 Cage Plus	HD 715 / HD 10/15-4 Cage Food / HD 9/23 De HD 9/23 G / HD 9/21 G / HD 8/20 G	HD 25/15-4 Cage Plus HD 7/10 CKF HD 7/15 G / HD 728 B Cage
Cleaning agent injector		oraci iio.	31111 Z013 P	The pescription				1-1-	- - -		- -	- -			1-1-	-1-1-	- -				1-1-		-1-1			- -	-1-1-	
Cleaning agent injector Cleaning agent injector for high and low pressure (without nozzles)	1	4.637-032.0	3.637-001.0	Cleaning agent dosing. Separately from the machine in low and high pressure. Dosage up to 15%.	1																						1.1	
Cleaning agent injector for high pressure (without nozzle)	2	4.637-033.0	3.637-170.0	Cleaning agent dosing in high pressure 3–5%.	2																		3 0					
Cleaning agent dosing attachment kit for HD 25/15-4 and HD 20/15-4 Cage Plus	3	4.637-031.0	3.637-250.0	Attachment kit for cleaning agent dosing in low and high pressure 0–5%. Consists of cleaning agent injector + nozzle insert + low pressure nozzle + rollover nozzle holder (for conveniently switching between high and low pressure).	3																						1	
Stainless steel injector kit for HD 6/15C	4	6.645-758.0	6.645-758.0	Specially suitable for high-pressure cleaner HDS 6/15 C, the stainless steel injector ensures precise dosing in cleaning agent and foam applications. With suction hose and filter. For EASY!Lock connection adapters 2 and 6 (4.111-030 and -034) are also required.	4																		3					
Stainless steel injector kit for HD 7/18-4M/ HDS 8/18-4C	5	6.645-759.0	6.645-759.0	The stainless steel injector for our high-pressure cleaners HD 7/18-4 M and HDS 8/18-4 C ensures precise dosing in cleaning agent and foam applications. With suction hose and filter. For EASY!Lock connection adapters 2 and 6 (4.111-030 and -034) are also required.	5																							
Stainless steel injector kit for HD 9/20-4M	6	6.645-760.0	6.645-760.0	Specially suitable for high-pressure cleaner HDS 9/20-4 M, the stainless steel injector ensures precise cleaning agent dosing. Comes complete with suction hose and filter. For EASY!Lock connection adapters 2 and 6 (4.111-030 and -034) are also required.	6																							
Stainless steel injector kit for HD 10/25-4S	7	6.645-761.0	6.645-761.0	Specially suitable for high-pressure cleaner HDS 10/25-4 S, the stainless steel injector ensures precise cleaning agent dosing. Comes complete with suction hose and filter. For EASY!Lock connection adapters 2 and 6 (4.111-030 and -034) are also required.	7																							
Stainless steel injector kit for HDS 10/20-4M	8	8 6.645-762.0	6.645-762.0	Specially suitable for high-pressure cleaner HDS 10/20-4 M, the stainless steel injector ensures precise cleaning agent dosing. Comes complete with suction hose and filter. For EASY!Lock connection adapters 2 and 6 (4.111-030 and -034) are also required.	8]																			
Stainless steel injector kit for HDS 12/18-4S	9	6.645-763.0	6.645-763.0	Especially suitable for high-pressure cleaner HDS 12 / 18-4 S, the stainless steel injector ensures precise dosing in cleaning agent and foam applications. With s uction hose and filter. For EASY!Lock connection adapters 2 and 6 (4.111-030 and -034) are also required.	9			1																				
Dosing valve for stainless steel injector			6.500-000.0	Retrofittable dosing valve for steel injectors. Allows for easy, comfortable and precise adjustment of the cleaning agent dosage by means of a rotary knob.	10																		3					
Cleaning agent injector for high pressure (without nozzle)	11	3.637-170.0	3.637-170.0	Cleaning agent dosing in high pressure 3-5%.	11														Ш									
Nozzle insert with order no. 4.637-032.0	1 40	1 4 760 000 0	14760 00201	High procesure for unite up to 1100 l/b	1 42	1 1	1 1	In In	Jele	Jele					Let	1 1	1 1				I-I-	Jel.						
Nozzle insert up to 1100 l/h - high pressure			4.769-003.0	High pressure for units up to 1100 l/h.	12			-	1110													1	111				44	$+$ \parallel \parallel
Nozzle insert from 1100 l/h - HD Nozzle insert up to 1100 l/h - low pressure			4.769-002.0 4.769-001.0	High pressure for machines from 1100 l/h. Low pressure for units up to 1100 l/h.	13			-								1 4 1	1			+	++	++	+-					
Nozzle insert op to 1100 l/h - ND			4.769-001.0	Low pressure for units up to 1100 l/h. Low pressure for units from 1100 l/h.	15			1 1	. " "					" "			ام ار	- -	1 1	1 1			- 1 - 1	_" "	" "	," "	- -	
□ Available accessories More Kärcher origi				<u> </u>			-1-10	-								. _ _	- -			1-1-	1-1-	-1-1	-111		لــــــــ			

☐ Available accessories. More Kärcher original accessories can be found on the following pages.



		EASY!Lock order no.	Order no.	Price	Description		HDS 13/20-4 S / HDS 2000 Super HDS 13/20-4 SX	HDS 12/18-4 S HDS 12/18-4 SX HDS 10/20-4 M	HDS 10/20-4 MX HDS 9/18-4 M / HDS 8/18-4 M / HDS 7/12-4 M HDS 8/17 C / HDS 7/16 C / HDS-E 8/16-4 M 36 KW	Z Z Z	HDS 8/18-4 C HDS 8/18-4 CX HDS 6/14-4 C / HDS 6/14 C / HDS 5/12 C	HDS 5/15 U / HDS 5/13 U / HDS 5/11 U HDS 6/14-4 CX / HDS 6/14 CX / HDS 5/15 UX	HDS 801 D / HDS 801 B HD 17/14-4 S Plus	HD 17/14-4 SX Plus HD 13/18-4 S Plus	HD 13/18-4 SX Plus HD 10/25-4 S / HD 10/25-4 S Plus / HD 10/23-4 S	HD 10/23-4 S Plus HD 10/25-4 SX Plus / HD 10/23-4 SX Plus	HD 9/20-4M / HD 9/20-4 M PIUS HD 8/18-4 M / HD 8/18-4 M PIUS / HD 7/16-4 M HD 7/16-4 M PIUS / HD 7/17 M / HD 7/17 M PIUS	/15 M /17 M	HD 6/15 M St / HD 8/18-4 M Cage St / HD 7/16-4 M Cage St HD 7/17 M Cage St / HD 6/15 M Cage	HD 5/12 C Plus / HD 5/11 P / HD 5/11 P Plus HD 5/17 CX Plus / HD 6/13 CX Plus / HD 5/15 CX Plus HD 5/12 CX Plus	HD 5/12 C HD 9/23 De Tr1 / HD 9/23 Ge Tr1 / HD 10/25-4 Cage Plus	HD 715 / HD 10/15-4 Cage Food / HD 9/23 De HD 9/23 G / HD 9/21 G / HD 8/20 G	HD 25/15-4 Cage Plus / HD 20/15-4 Cage Plus HD 7/10 CXF
Machine-specific nozzle kit with order	r no. 4.637-033.																						
Nozzle kit HD 500-700 l/h	16	4.769-005.0	4.769-045.0		Consists of nozzle insert + HP power nozzle + coupling.	16																	
Nozzle kit 500-700 l/h	17	4.769-009.0	4.769-046.0			17																	
Nozzle kit 750-1000 l/h	18	4.769-011.0	4.769-047.0			18																	
Nozzle kit 1000-1200 l/h	19	4 769-013 0	4.769-048.0			19																T	

ATTACHMENT KITS



With different attachment kits, machines can be adapted to the requirements of specific areas of use. For example, the crane loading attachment kit makes it easy to transport the machine to construction sites. With the coin remote control attachment kit, 3-phase HDS middle and super class machines can be used for self-service operation. The grey wheel attachment kit makes the machines suitable for use in the food industry or swimming pools.



















Part						•	
Attachment kit for transport Temper yelver distribution bit in Transport perplace for severe fixation of high-persoure Control localing after hereo is in for Torse localing after hereo is in for Sciences 16.00 Torse localing after for sciences 16.00 Torse localing after for sciences 16.00 Torse localing after for sciences 16.00 Torse localing a				Prince			20-4 SX / HDS 12/18-4 S 7/20-4 M / HDS 10/20-4 MX 3-4 MX / HDS 8/18-4 M 12-4 M / HDS 10/20-4 MX 4 CX / HDS 8/17 C C / HDS 7/12-4 MX -4 CX / HDS 8/17 C C / HDS 7/12-4 MX -4 CX / HDS 6/14 C C C / HDS 7/16 CX -4 CX / HDS 6/14 C C X / HDS 5/13 U U / HDS 5/13 U S / HD 10/23-4 S Plus I MPIUS / HD 10/23-4 S Plus I MPIUS / HD 10/23-4 S Plus I MPIUS / HD 10/23-4 S Plus I M PIUS / HD 10/23-4 MX Plus I M PIUS / HD 1/14-4 MX Plus I M PIUS / HD 7/14-4 MX Plus I M PIUS / HD 7/14-4 MX Plus I M PIUS / HD 7/14-4 MX Plus I M PIUS / HD 6/15 M St I W S / HD 6/15 M St I W S / HD 6/15 M St I W S / HD 6/15 CX Plus I M S / HD 6/15 CX Plus I M F 6/15 C
Transport syeld attachment kit 1		order no.	until 2015	Price	Description		
Control colding attachment kit for 2 242 2580 2580 242 2580 2580 242 2580		1 2644 053 0	1	ı	Dobust attachment kit Transport avalets for secure fivation of high pressure	1 1	
All Content and Super class 3 2640 438.0 2640 438	Transport eyelet attachment kit	1 2.644-053.0				1	
Came loading statement kit for HID Support Class		2 2.642-638.0	2.642-638.0		Effortless loading by crane.	2	
Care Indiang Attachment kit from this Ison Bandle and Super Class San Super Class Super Class Super Class San Super Class Super		3 2 640-438 0	2 640-438 0			3	
Mode and Super Class							
Wheel attachment kill for HoS 1000 By/De 5 2637-8200 Convenient manoeuvrability with pneumatic tyres. 5	HDS Middle and Super Class						
Corey wheel attachment kit FOHDS Middle 6 2641-975.0 2641-975.0 2641-975.0 Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. Somewheel suitable for use in sanitary areas, food industry or swimming pools. South of the filter attachment kit for HD 2642-711.0 South of the filter attachment kit for HD 2642-711.0 South of the filter attachment kit for HD 2641-796.0 South of the filter attachment kit for HD 2641-796.0 South of the filter attachment kit for HD 2641-796.0 South of the filter attachment kit for HD 2641-796.0 South of the filter attachment kit for HD 2641-796.0 South of the filter attachment kit for HD 2641-796.0 South of the filter attachment kit for HD 2641-796.0 South of the filter attachment kit for HD 2641-796.0 South of the filter attachment k		-1	1			1 -1	
From monitoring attachment kit for HDS Middle and Super Class Flame monitoring attachment kit for HDS Address with mining policy of the flame of Super Class Flame monitoring attachment kit for HDS Address with mining policy of the flame of Super Class Flame monitoring attachment kit for HDS Address with mining policy of the flame of Super Class Flame monitoring attachment kit for HDS Address with mining policy of the flame of Super Class Flame monitoring attachment kit for HDS Address with mining policy of the flame of Super Class Flame monitoring attachment kit for HDS Address with mining attachment kit for HDS Address with mining attachment kit for HDS 25/15-4 Cage Plus Super Class Water filter attachment kit for HD 25/15-4 Cage Plus Super Class with HDS Address with mining attachment kit for HD 25/15-4 Cage Plus Super Class		5 2.637-820.0	2.637-820.0		Convenient manoeuvrability with pneumatic tyres.	5	
and Super Class Swimming pools. Swimming poo		6 2641-9750	2641-9750	1	Non-marking grow wheels suitable for use in sanitary areas, food industry or	6	
Flame monitoring attackment kit for 7 2.642-711.0 2.642-711.0 2.642-711.0 2.642-711.0 2.642-711.0 2.642-711.0 3 2.641-796.0 3 2.641-		0 2.041-975.0	2.041-375.0			0	
No. Substitutor 13 14 11 12 13 14 11 12 14 11 12 14 11 12 14 11 12 14 11 12 14 12 14 11 12 14 14							
Flame monitoring attachment kit for 8 2.641-796.0 2.641-796.0 8 0 0 0 0 0 0 0 0		7 2.642-711.0	2.642-711.0			7	
Water filter attachment kit for HD 25/15-4 9 2 851-055.0 2851-055.0 For HD 25/15-4 Cage Plus. 9 9 2 851-055.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 and HD 16/15-4 Cage Plus. 10 2 851-252.0 For HD 20/15-4 Cage Plus. 10		8 2641-7960	2.641-796.0		goes out.	Q	
Water filter attachment kit for HD 25/15-4 9 2.851-065.0		0 2.041 750.0	2.041 750.0				
Cage Plus Water filter attachment kit for HD 20/15-4 and HD 16/15-4 Cage Plus. Blapsed time counter attachment kit Elapsed time counter attachment kit 11 2.851-066.0 2.851-066.0 The operating hour counter meters the operating time for contractors and machine hire companies. It also makes it easier to check when the unit needs servicing. Y distributor Y distributor Y distributor Y distributor 12 4.111-024.0 4.405-048.0 Offers the option to connect two spray units to the machine. Installation on the high pressure outlet. Set of puncture-proof wheels Set of puncture-proof wheels 13 2.851-067.0 2.851-067.0 2.851-067.0 The foam-filled wheels combine the ride comfort of pneumatic wheels and the puncture protection of solid rubber wheels.	Water filter attachment kit						
Elapsed time counter attachment kit Elapsed time counter attachment kit 11 2.851-066.0 2.851-066.0 The operating hour counter meters the operating time for contractors and machine hire companies. It also makes it easier to check when the unit needs servicing. Y distributor Y distributor 12 4.111-024.0 4.405-048.0 Offers the option to connect two spray units to the machine. Installation on the high pressure outlet. Set of puncture-proof wheels Set of puncture-proof wheels 13 2.851-067.0 2.851-067.0 2.851-067.0 The foam-filled wheels combine the ride comfort of pneumatic wheels and the puncture protection of solid rubber wheels.		9 2.851-065.0	2.851-065.0		For HD 25/15-4 Cage Plus.	9	
Elapsed time counter attachment kit Elapsed time counter attachment kit I1 2.851-066.0 2.851-066.0 The operating hour counter meters the operating time for contractors and machine hire companies. It also makes it easier to check when the unit needs servicing. Y distributor Y distributor 12 4.111-024.0 4.405-048.0 Offers the option to connect two spray units to the machine. Installation on the high pressure outlet. Set of puncture-proof wheels Set of puncture-proof wheels 13 2.851-067.0 2.851-067.0 2.851-067.0 The foam-filled wheels combine the ride comfort of pneumatic wheels and the puncture protection of solid rubber wheels.	Water filter attachment kit for HD 20/15-4	10 2.851-252.0	2.851-252.0		For HD 20/15-4 and HD 16/15-4 Cage Plus.	10	
Elapsed time counter attachment kit 11 2.851-066.0 2.851-066.0 The operating hour counter meters the operating time for contractors and machine hire companies. It also makes it easier to check when the unit needs servicing. Y distributor Y distributor 12 4.111-024.0 4.405-048.0 Offers the option to connect two spray units to the machine. Installation on the high pressure outlet. Set of puncture-proof wheels Set of puncture-proof wheels 13 2.851-067.0 2.851-067.0 2.851-067.0 The foam-filled wheels combine the ride comfort of pneumatic wheels and the puncture protection of solid rubber wheels.							
Y distributor 12 4.111-024.0 4.405-048.0 Offers the option to connect two spray units to the machine. Installation on the high pressure outlet. Set of puncture-proof wheels Set of puncture-proof wheels 13 2.851-067.0 2.851-067.0 The foam-filled wheels combine the ride comfort of pneumatic wheels and the puncture protection of solid rubber wheels.	Elapsed time counter attachment kit	11 2.851-066.0	2.851-066.0			11	
Set of puncture-proof wheels Set of puncture-proof wheels Set of puncture-proof wheels 13 2.851-067.0 2.851-067.0 The foam-filled wheels combine the ride comfort of pneumatic wheels and the puncture protection of solid rubber wheels.	Y distributor						
Set of puncture-proof wheels Set of puncture-proof wheels 13 2.851-067.0 2.851-067.0 The foam-filled wheels combine the ride comfort of pneumatic wheels and the puncture protection of solid rubber wheels.	Y distributor	12 4.111-024.0	4.405-048.0			12	
puncture protection of solid rubber wheels.	Set of puncture-proof wheels						
Set of guide rolls		13 2.851-067.0	2.851-067.0			13	
	Set of guide rolls						
Set of guide rolls 14 2.851-042.0 2.851-042.0 Two steering rollers for even better mobility and manoeuvrability. 14					, ,	14	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.









						-4 M 12 KW	
	EASY!Lock order no.	Order no. until 2015	Price	Description		HDS 13/20-45 / HDS 13/20-4 SX / HDS 12/18-4 S HDS 13/20-45 / HDS 13/20-4 SX / HDS 10/20-4 MX HDS 9/18-4 MX / HDS 9/18-4 MX / HDS 10/20-4 MX HDS 9/18-4 MX / HDS 9/18-4 MX / HDS 9/18-4 M HDS 9/18-4 MX / HDS 9/18-4 MX / HDS 9/11-4 MX HDS 8/18-4 CX / HDS 8/18-4 CX / HDS 8/14 C HDS 8/14-6 C / HDS 7/10-4 CX / HDS 6/14 C HDS 8/14-6 C / HDS 7/10-6 C / HDS 7/10-6 C / HDS 10/10-6 HDS 6/14-6 C / HDS 7/10-6 C / HDS 1/10-6 HDS 6/14-6 C / HDS 1/10-6 HD 10/15-4 C / HD 6/14-6 HD 10/15-6 HD 6/15 C / HD 6/15 C / HD 6/13 C / HD 6/15 C / HD 6/13 C / HD 6/14-6 HD 6/15 C / HD 6/14-6 HD 6/15 C / HD 6/14-6 HD 6/15 C / HD 6/15 C / HD 6/14-6 HD 6/15 C / HD 6/14-6 HD 10/15-4 C age PUS	HD 8/20 G / HD 7/15 G HD 728 B Cage
Chemical take up attachment kit	101001	1	1 1 1 1 1 1	1			
Chemical take up attachment kit	15 2.641-944.0	2.641-944.0		Extension for cleaning agent suction from drums at ground level.	15		
Foam lance holder attachment kit		1		Language and the second	11		
Foam lance holder attachment kit	16 2.641-947.0	2.641-947.0		Additional spray lance for safe storage, e.g. of the Inno foam lance.	16		
Pressure tank attachment kit Pressure tank attachment kit for HDS Middle and Super Class	17 2.641-803.0	2.641-803.0		The pressure tank can also be mounted on the HDS machine in order to dampen any pressure surges and thus protect the line system of the machine.	17		
Remote control attachment kit		,					
Remote control attachment kit for HDS Middle and Super Class	18 2.642-157.0	2.642-157.0		Remote control for the machines of the HDS middle and super class with the functions on/off, hot/cold water and cleaning agent on/off. For mounting on a wall.	18		
Coin remote control attachment kit Coin remote control attachment kit for HDS Middle and Super Class	19 2.642-158.0	2.642-158.0		Retrofittable coin acceptor for machines in the HDS middle/super class for self-service operation. For installation on the machine.	19		
Cage frame attachment kit							
Cage frame attachment kit, large	20 2.637-007.0			Robust cage frame for the machines in the HD Gasoline Advanced range to protect	20		\perp
Cage frame attachment kit, small	21 2.637-008.0	2.637-008.0		the components, incl. eyelets for loading by crane.	21		

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

OTHER ACCESSORIES



Kärcher high-pressure cleaners can deliver good results even without access to the water mains. We offer a range of high-performance fine-mesh filters for use with industrial water or natural water sources. Additional professional accessories further expand the scope of applications of Kärcher high-pressure cleaners.





















-								ПП			П				\Box		>										П				$\neg \neg$	\Box			\top	\Box	
	EASY!Lock	Order no.	Longth	liameter	Drico	Description		HDS 13/20-4 S / HDS 13/20-4 SX / HDS 12/18-4 S	- α	9/18-4 MX / HD	7/12-4 M / HDS 7/12-4 MX	CX / HDS //1	HDS 6/14-4 C / HDS 6/14-4 CX / HDS 6/14 C	HDS 5/15 U / HDS 5/15 UX / HDS 5/13 U	5/13 UX / HDS 5/1 5/11 UX	HDS 17/20 DE IT1 / HDS 13/20 DE IT1 HDS 2000 Super	HDS-E 8/16-4 M 36 kW / HDS-E 8/16-4 M 24 kW / HDS-E 8/16-4 M 12 kW	4DS 801 D / HDS 801 B	1D 17/14-4 S Plus	HD 13/18-4 S Plus	S Plus / HD 10/25-4 SX	HD 10/23-4 S / HD 10/23-4 S Plus / HD 10/23-4 SX Plus HD 9/20-4 M / HD 9/20-4 M Plus / HD 9/20-4 MX Plus	1 Plus / HD 8/18	M FIUS / HD 7/16-4 IUS / HD 7/17 MX PI	HD 7/14-4 M / HD 7/14-4 M Plus / HD 7/14-4 MX Plus HD 6/15 M / HD 6/15 M Plus / HD 6/15 MX Plus	HD 8/18-4 M St / HD 7/17 M St / HD 6/15 M St HD 8/18-4 M Cape St / HD 7/15-4 M Cape St	900	4D 5/17 C / HD 5/17 C Plus / HD 5/17 CX Plus 4D 6/13 C / HD 6/13 C Plus / HD 6/13 CX Plus	HD 5/15 C / HD 5/15 C Plus / HD 5/15 CX Plus HD 5/12 C / HD 5/12 C Plus / HD 5/12 CX Plus	D 5/11 P	4D 5/11 P Plus 4D 9/23 De Tr1	HD 9/23 Ge Tr.1 HD 25/15-4 Gage Plus	10/25-4 Cage Plus	1D 715	HD 10/15-4 Cage Food HD 7/10 CXF	нр 9/23 ре / нр 9/23 G / нр 9/21 G	HD 8/20 G / HD 7/15 G HD 728 B Cage
Mater emply been	order no.	until 2015	Length D	Diameter	Price	Description	Ш	=	T T	ΙΞ.	=	= =	= 3	= =	= =	E E	= 3	- I	T T	=	= =	= =	= :	E E	= =	= =	: = :	= =	= =	= =	F F	ŦĮŦ	- -	Ξ 3	= =] <u>=</u>]:	I I
Water supply bose	1 4.440-038.0	4.440-038.0	7.5 m	1		NW 13 R 1" / R 3/4", up to 30 °C.	1 1				Lot	اماما		Jol	- I			Lol		1 1	1 1		Loli	-1-1			loli	-1-		Lole			1 1			Let	
Water supply hose	2 4.440-207.0	4.440-207.0				NW 19 R 1" / R 3/4", up to 85°C, for vacuuming operation	2	-																			1 0 1					╫			+		
	3 4.440-270.0	4.440-270.0	7.5 m			with copper strand for earthing the machine. ID 19 R 1" / R 1", up to 85°C.	3	ПП	пГ	1 1 1	\vdash		\vdash	+		П		+			10	пПп	\vdash								+	\vdash		+	+	+	+
Geka coupling	3 1.110 270.0	1.110 270.0	7.5			18 13 11 7 11 7 19 10 00 0.	1 5			- -					1-1					101.		-1-									\perp	\vdash			\perp	\vdash	\perp
Geka connector with hose barb, R 1/2"	4 6.388-461.0	6.388-461.0				With hose barb, R 1/2".	4					اماه	ا د ا	ılol	اماه								lol	اماد	ه ا ه	ا ما	ıloli	ه ا ه	ا ا ا		al '			пΙ	To		
Geka connector with hose barb, R 3/4"	5 6.388-455.0	6.388-455.0				With hose barb, R 3/4".	5														5	\top									7	\vdash	+		-		
Geka connector with hose barb, R 1"	6 6.388-465.0	6.388-465.0				With hose barb, R 1".	6	-										1													$\exists \exists$	TE			+-	1	+
Geka connector with inner thread, R 3/4"	7 6.388-473.0	6.388-473.0				With inner thread, R 3/4".	7				\Box			\top																	一	一				\Box	
Geka connector with internal thread, R 1"	8 6.388-458.0	6.388-458.0				With internal thread, R 1".	8							1				ı					\vdash	\top			\top			\top							
Water fine filter		'																																			
Universal water fine filter, 25 µm	9 2.637-020.0	•				Installation on unit input, 25 µm, with adapter R 3/4" / R 1".	9																														
Water fine filter, 100 µm, R 3/4"	10 2.637-691.0	2.637-691.0				Installation on unit input, 100 µm, R 3/4".	10																														
Water fine filter, 90-120 µm, R 1", suitable	11 2.638-255.0	2.638-255.0				Mounted on the machine, suitable for pressure and vacu-	11											. l														ı					
for pressure and vacuuming operation	12 1720 1020	4700 400 0				uming operations, 90-120 μm, R 1".	10	+	_	-				+++						 			 				+			-	_ _	_	-	_	+-	1	
Water fine filter, with adapter	12 4.730-102.0					Installation on unit input, 125 µm, with adapter R 3/4" / R 1".	12	-		1	-									+ +	-											H			\perp		44
Water fine filter, 100 µm, R 1"	13 2.638-270.0	2.638-270.0				Installation on unit input, 100 µm, R 1".	13			1 1				J				ا ا			7 1		ш								ш	\perp				Ш	\perp
Suction filter Water suction filter	14 6.414-956.0	6.414-956.0	1 1			Suitable for ponds, storage tanks or similar, polyamide filter	14							1 1	1 1			1 1		П	1 1		П	1 1	1		1 1	1		1 1			1 1		4		
water section inter	14 0.414 550.0	0.414 550.0				casing, stainless steel strainer, 800 µm mesh, R 3/4" and	14								الملم			اداد			اماد										اماه						
						R 1" connection, without non-return valve.																															
Suction filter with check valve	15 4.730-012.0	4.730-012.0				With non-return valve, brass, R 1" connection.	15] [
Nonreturn valve																																			4, 7		4.1
Nonreturn valve	16 2.641-374.0	2.641-374.0				To prevent cleaning agent from entering the drinking water circuit when there is a vacuum in the water line. Hot water-	16																														
						resistant up to 80°C – certified according to IEC 60335-2-79. Built-in leakage protection, connector R 1" / R 3/4".									- -]]	- -		- -	- -		[]	_ _			-			_			- -
Flue pipe						DUILTIII IEANAGE PROTECTION, COMMECTOR N. 1. / N. 3/4.					Ш		Щ					ш													\perp	\perp			\perp	\sqcup	
Flue gas adapter	17 4.656-149.0	I	1 1	.50 mm		Connector on unit, oval, 119 mm.	17		In	ıln	ΙпΙ	nlnl	Intr	ПП																					T		
Flue gas adapter	18 4.656-080.0			200 mm		Connector on unit, oval, 119 mm.		-	_	_		_		-		+		+		+	+	+	\vdash	+	+	\vdash	++				+	+	+	+	+	+	+
<u> </u>	19 4.656-079.0			200 mm		Connection on machine, oval, 157 mm.	_		_	Ť				+	+			\top		+	+	\top	\vdash		\neg		+			+	+	\top	+	+	+	+	+
	147	<u> </u>				I The state of the							\perp				$\perp \perp$														-					44	\perp

■ NEW ☐ Available accessories. More Kärcher original accessories can be found on the following pages.

HIGH PRESSURE AT YOUR FINGERTIPS

Our stationary high-pressure units deliver impressive cleaning results in a wide variety of industries and applications due to their high power, efficiency and durability. Applications include all areas of food processing, the automotive industry and vehicle repair shops, the chemical and metal processing industry, municipal facilities like swimming pools and maintenance hangars, as well as livestock farming and agricultural vehicle care. And most certainly in your work area.




Table of contents: Stationary high-pressure cleaners


Stationary HDS - single-lance operation	Page	188
Stationally HDS - Strigie-rance operation	Page	100
HDC Advanced / Standard - multiple-lance operation	Page	190
HDC Classic - multiple-lance operation	Page	191
Stationary HD - single-lance operation	Page	192
Accessories	Page	196
Cleaning agents	Page	842







For many industrial and commercial sectors, as well as the public sector, stationary high-pressure units are essential. In the food processing industry, machine to service. Reduced cleaning times without setting up. No need disinfection ensures compliance with legal requirements. For many other companies to shipping and aviation. In commercial kitchens, drinks and and pharmaceutical industries to paper manufacture. In swimming pools and all types of sanitation areas. Wherever you want to use high-pressure cleaning - our experts for stationary high-pressure units provide you with professional advice when planning your stationary system.






Convenient, safe and always ready to use

High-pressure cleaning systems are an excellent investment. Only one to transport the machine. Space-saving design. Furthermore, stationary sectors, it is equally efficient and economical. From car workshops and fleet high-pressure units make important contributions to operational safety and work protection: Protection of employees against noise and exhaust gases. meat processing, wineries and agriculture. From the metalworking, chemical Prevention of erroneous operation by unauthorised persons. Kärcher offers a comprehensive range of accessories for wash bays to suit individual requirements and virtually unlimited applications. And, last but not least, expert installation and technical monitoring ensure comprehensive system

	Order no.	Power supply (phases)	Flow rate (I/h)	Working pressure (bar/MPa)	3-piston axial pump	Crankshaft pump	Ceramic piston	Stainless steel pistons	4-pole engine (low-speed machine)	Advance pressure pump	Emission temperature limiter	Fuel shortage protection mechanism	Pressure relief	SDS hose / Pressure tank	Dry-running protection	Flame monitoring	Calcification protection	Stainless steel heating coil	Servo Control	Servo Control ready	Remote control ready	Spray gun	High-pressure hose	Spray lance	Triple nozzle	Page
Stationary hot water high	- 1	1												٠,												
HDS 12/14-4 St	1.699-921.0	3	600-1200	30-140 / 3-14		_				-	П							-	-		П	-	-	_	-	189
HDS 12/14-4 St Gas	1.251-901.0	3	600-1200	30-140 / 3-14	_					-	П							П	-		П	-	-	-	-	189
HDS 12/14-4 St Gas LPG	1.251-902.0	3	600-1200	30-140 / 3-14	_					-	П								-			-	-	-	-	189
HDS 9/14-4 St	1.698-917.0	3	500-930	30-140 / 3-14						-								-	-			-	-	-	$\overline{}$	189
HDS 9/16-4 St Gas	1.251-900.0	3	500-960	30-160 / 3-16						-									-			-	-	-	-	189
Stationary cold water hig	h-pressure cleaner	s, 60	/85°C, multipl	e-lance operatio	n																					
HDC 120/10	1.509-502.2	3	700-12000	100 / 10	-		-				-	-	-			-	-	-							-	190
HDC 90/10	1.509-502.2	3	700-9000	100 / 10	-		-				-	-	-			-	-	-							-	190
HDC 60/10	1.509-502.2	3	700-6000	100 / 10	-		-				-	-	-			-	-	-							-	190
HDC 80/16	1.509-500.2	3	700-8000	160 / 16	-		-				-	-	-			-	-	-							-	190
HDC 80/08	1.509-500.2	3	700-8000	80 / 8	-		-				-	-	-			-	-	-							-	190
HDC 60/16	1.509-500.2	3	700-6000	160 / 16	-		-				-	-	-			-	-	-							-	190
HDC 60/08	1.509-500.2	3	700-6000	80 / 8	-		-				-	-	-			-	-	-							-	190
HDC 40/16	1.509-500.2	3	700-4000	160 / 16	-		-				-	-	-			-	-	-							-	190
HDC 40/08	1.509-500.2	3	700-4000	80 / 8	-		-				-	-	-			-	-	-							-	190
HDC 20/16	1.509-501.2	3	700-2000	160 / 16	-		-				-	-	-			-	-	-							-	191
HDC 20/08	1.509-501.2	3	700-2000	80 / 8	-		-				-	-	-			-	-	-			П				-	191
Stationary cold water hig	h-pressure cleaner	s, sin	gle-lance ope	ration																						
HD 13/12-4 St	1.524-950.2	3	650-1300	30-120 / 3-12							-	-				-		-								195
HD 9/18-4 St	1.524-950.2	3	460-900	40-180 / 4-18	_						-	-				-		-			П				-	195
												_	_	-	_	_	$\overline{}$		_						-	



Single-lance operation

Stationary high-pressure units for single-lance operation offer the option to For increased cleaning requirements, Kärcher offers solutions that enable set up several points of use or only one point of use for cold or hot water. These systems are therefore particularly suitable for small and mediumsized companies, e.g. in the automotive, food or agricultural sector.

Multiple-lance operation

different areas to be cleaned simultaneously. From a central supply unit, a constant flow of high-pressure water is conveyed via a pipeline system to fixed points of use and is available in unlimited supply as and when required. Universal, versatile, efficient, safe and economical.

STATIONARY HDS - SINGLE-LANCE OPERATION



High cleaning performance and outstanding efficiency

The oil-heated stationary cleaning systems offer a very high heating output. These machines also ensure a high level of safety thanks to features such as automatic pressure relief, exhaust temperature monitoring, innovative dry-running protection and an SDS hose for absorbing pressure peaks. The gas-heated stationary high-pressure cleaning systems offer the benefit of efficient and eco-friendly combustion.



















1 Water-cooled four-pole electric motor

- Long service life.
- Improved effectiveness.
- Guaranteed quiet operation.

3 High efficiency

- Efficient and economical cleaning thanks to the use of hot water.
- Short set-up times reduce working hours.

2 Burner engineering

- High heating output.
- Spiral heating coil for a compact construction style.
- Upright construction style prevents condensation and corrosion.

4 Flexible operating concept

- Central control panel on the machine.
- Remote controls can be used directly at the point of use.

TECHNICAL DATA AND EQUIPMENT

		HDS 12/14-4 St	HDS 12/14-4 St Gas	HDS 12/14-4 St Gas LPG
		Integrated system pressure reliefSoft Damping System (SDS)Dry-running protection	 Dry-running protection Surface burner technology Water-cooled stainless steel boiler with built-in stainless steel heater coil 	 Dry-running protection Surface burner technology Water-cooled stainless steel boiler with built-in stainless steel heater coil
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Connection load	kW	7.5	7.5	7.5
Flow rate	I/h	600-1200	600-1200	600-1200
Working pressure	bar / MPa	30-140 / 3-14	30-140 / 3-14	30-140 / 3-14
Max. temperature	°C	155 / 80	98 / 98	98
Heating oil consumption, full load	kg/h	7.1	-	-
Gas consumption, full load	kg/h	-	9.8*	7.2
Weight	kg	160.4	196.6	193.5
Dimensions (L × W × H)	mm	1110 × 565 × 700	1110 × 565 × 1080	1110 × 565 × 1080
Equipment				
Soft Damping System (SDS)		•	•	•
System pressure relief		•		
Flame monitoring		•	•	•
Prepared for Servo Control		•		•

1.251-901.0

Order no.

HDS 9/14-4 St

1.699-921.0

HDS 9/16-4 St Gas

1.251-902.0

		Integrated system pressure reliefSoft Damping System (SDS)Dry-running protection	 Dry-running protection Surface burner technology Water-cooled stainless steel boiler with built-in stainless steel heater coil
Technical data			
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50
Connection load	kW	6.4	6.4
Flow rate	I/h	500-930	500-960
Working pressure	bar / MPa	30-140 / 3-14	30-160 / 3-16
Max. temperature	°C	155 / 80	98 / 98
Heating oil consumption, full load	kg/h	5.8	-
Gas consumption, full load	kg/h	-	7.2*
Weight	kg	146.9	172
Dimensions (L × W × H)	mm	1110 × 565 × 690	1110 × 565 × 970
Equipment			
Soft Damping System (SDS)		•	1
System pressure relief			
Flame monitoring		•	
Prepared for Servo Control			
Order no.		1.698-917.0	1.251-900.0
Price			

■ Included in the scope of supply.

191

HDC ADVANCED / STANDARD - MULTIPLE LANCE OPERATION

Highly flexible for all applications

The HDC standard is highly versatile. Various configuration options are available to suit individual requirements.





1 Modular design

The HDC systems can be fitted with up to four pump aggregates upon request. This ensures the utmost flexibility for every purpose of use.

2 Intelligent pump control

Regardless of the required water volume, the control switches other pumps on and off again as required.

HDC Advanced

HDC Standard

For 1 to 12 users at the same time ■ Partial quantity regulation by frequency converter $\hfill \blacksquare$ For 1 to 8 users at the same time Stationary supply unit Stationary supply unit Technical data 700-12000 700-8000 Flow rate Max. pressure 100 / 10 80 / 160 / 8 / 16 2-4 2-4 Number of pumps piece(s) Number of current phases Voltage 400 / others upon request 400 / others upon request 50 50 11-44 22-46 Connection load kW max. 85 max. 85 Inlet temperature 310-610 310-610 Weight 1150 × 750 × 1840 Dimensions (L × W × H) 1150 × 750 × 1840

Configurable equipment			
Frame:			
Powder-coated steel			
Stainless steel			
Machine cover:			
Powder-coated steel			
Stainless steel			
Order no.	1.509-502.2	1.509-500.2	
Price			
E 0.1:			

☐ Optional accessories.

HDC CLASSIC - MULTIPLE LANCE OPERATION

For up to three operators



Whether it be the food industry, a manufacturing enterprise or a local authority, the HDC Classic provides smaller businesses with a simple, on-demand system for up to three operators.





1 Water network separation through preflow container

Any intake of air is avoided as the water is allowed to settle in the preflow container. This protects the pump.

2 Automatic start function

■ The pump starts as soon as the trigger gun is activated, allowing convenient working from any supply point.

HDC Classic

■ For 1 to 3 users at the same time

Can be mounted to the wall or floorStationary supply unit

Technical data		
Flow rate	I/h	700-2000
Max. pressure	bar / MPa	80 / 160 / 8 / 16
Number of pumps	piece(s)	1
Number of current phases	Ph	3
Voltage	V	400 / others upon request
Frequency	Hz	50
Connection load	kW	5.5 / 11
Inlet temperature	°C	max. 85
Weight	kg	135 / 150
Dimensions (L × W × H)	mm	860 × 595 × 580

Configurable equipment	
Frame:	
Powder-coated steel	
Stainless steel	
Machine cover:	
Powder-coated steel	
Stainless steel	
Order no.	1.509-501.2
Price	

□ Optional accessories.

STATIONARY HD - SINGLE-LANCE OPERATION



The tailor-made cleaning solution

Compact stationary high-pressure cleaners that can be configured to suit individual customer requirements. This stationary model series offers the benefits of short set-up times, space-saving storage and individual configuration of cleaning stations.

















- 1 Individual configuration
- For low investment costs: Simply select the basic device and search for the required equipment features.
- Over 50 accessory parts for optimum equipment at the point of use.





- 3 Most equipment features and accessory parts can easily be retrofitted at any time
- Various equipment features can be retrofitted at any time.
- Easy installation.
- Simple Plug 'n' Play system.


2 Excellent cleaning power with hot water supply

- Up to 70°C water inlet temperature even in the entry-level model.
- HWE 860 can also be used to supply the high-pressure cleaner with hot water.

Built to last and retain value

- 4-pole low-speed electric motor.
- Hard-wearing ceramic pistons.
- Large pressure tank protects all pressure-loaded components.

CONFIGURATION OPTIONS







Protects the pump from calcification in hot water operation.



Automatic pressure relief

Relieves all high-pressure components and reduces wear and tear.



Dry-running protection

Switches off the high-pressure pump in the event of water shortage to safeguard against damage.




Operating hour counter Displays the number of hours the machine has been in operation.

Please see our catalogues for further information on other machines, accessories and cleaning agents or go to www.kaercher.com.

TECHNICAL DATA AND EQUIPMENT

Choose from three different basic models: HD 13/12-4 St, HD 9/18-4 St and HD 7/16-4 St. The HWE 860 hot water generator can also be connected upstream for all H versions.





		HD 13/12-4 St	HD 9/18-4 St	HD 7/16-4 St	HWE 860
		 Compact model Includes complete spray unit Single-lance operation 	 Compact model Includes complete spray unit Single-lance operation 	 Compact model Includes complete spray unit Single-lance operation 	 55 I stainless steel tank Electrically heated water heater (80°C) With safety thermostat and water shortage protection
Technical data					
Power supply	Ph/V/Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Flow rate	I/h	650-1300	460-900	300-700	min. 1000
Working pressure	bar / MPa	30-120 / 3-12	40-180 / 4-18	30-160 / 3-16	-
Max. pressure	bar / MPa	150 / 15	210 / 21	190 / 19	-
Max. inlet temperature	°C	70	70	70	80
Connection load	kW	6.4	6.4	4.4	24
Weight	kg	72	62.5	53	42
Dimensions (L × W × H)	mm	533 × 790 × 420	533 × 790 × 420	533 × 790 × 420	440 × 508 × 751
Equipment - Standard					
Spray gun		EASY!Force Advanced	EASY!Force Advanced	EASY!Force Advanced	-
High-pressure hose	m	10	10	10	-
Spray lance	mm	1050	1050	1050	-
Triple nozzle		•	•	•	-
Servo Control ready					-
Order no.		1.524-950.2	1.524-950.2	1.524-950.2	3.070-030.0
Price					

Included in the scope of supply.

194

ATTACHMENT KITS

After selecting the basic version, it can be adapted with various attachment kits and accessories to meet specific customer requirements. Various configuration options are shown in the following table:







	HD 13/12-4 St	HD 9/18-4 St	HD 7/16-4 St
Configuration - optional			
Inlet temperature 85 °C: For tackling stubborn or greasy dirt. Includes advance pressure pump and adjustment of the high-pressure pump	85	85	85
Liquid softener dosing unit: Protects the high-pressure pump against calcification			
Stainless steel chassis: Corrosion resistant and easy to clean			
Dry-running protection: Protects the high-pressure pump should the water inlet volume be insufficient			
Pressure relief: Relieves all high-pressure system components			
Operating hour counter: Displays the number of hours the machine has been in operation			
Remote control ready for dispensing 1 cleaning agent. Application with low-pressure stream			
Remote control ready for dispensing 1 cleaning agent. Application with high-pressure jet			
Remote control ready for dispensing 2 cleaning agents. Application with low-pressure stream			
Remote control ready for dispensing 2 cleaning agents. Application with high-pressure jet			

☐ Available accessories.

ACCESSORIES FOR STATIONARY HIGH-PRESSURE CLEANERS



Wherever high demands are regularly placed on cleaning performance, stationary systems demonstrate their strengths. And in many different areas of use.















7	

							lard	lard ic	lard lard			SE	jas LPG
							and and	and	a a a	2 2	ᇍᇦ	T X Z	St
							3 25 5	1 8 5	8 8 5	ă ă	HDC 120/10 Adv HD 7/16-4 St/H HD 9/18-4 St/H HD 13/12-4 St/H	4 S 4 S	4 4
							1 0 0 1			2 2	.8-4 12-	17 17 19	2 2
							8 8 8	1 2 2 2	1 0 0	9 6 0	2 17 17 13 13 13 13 13 13 13 13 13 13 13 13 13	S 12	S 12
		Order no.	Price	Version	Order no.	Price	- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -	5 黃 黃 ;	된 모 모	휘	후 의 유 의		
Unit list/set-up													\vdash
Wall bracket	1	2.053-005.0		_	-	1	\Box		T + T				
Floor structure		2.210-058.0		Version VA.	2.210-059.0	2	+++	+++	+	+			$\overline{\Box}$
Floor structure		2.210-008.0		-	-	3	+++	+++	+++	+			
Floor structure HDC		2.641-736.0		Floor structure, 4 × floor screw connections,	+-	4	+++		+++	+			HH
Hoor structure Hibe	-	2.041 /30.0		incl. fastening material.					1				
HDC floor screw connections	5	2.638-320.0		1 set of floor screw connections.	-	5		101					HH
Feet, adjustable		2.638-177.0		-	_	6	++++	-1-1-	+				HH
Water hose, 1.5 m, NW 13		6.389-145.0				7	+++	+++	+++	+			
Water hose, 1.5 m, NW 19, R 1"		4.440-733.0			<u> </u>	8	+++	+++	+++	+			HH
Water hose, 1.5 m, NW 13, R 3/4"	_	4.440-282.0				9	+++	+++	+++	+			
Water inlet solenoid valve		4.743-011.0			+-	10	+++	+	+++	+			
	_	2.209-788.0				11	+++	+++	+++	+			
Water inlet solenoid valve High-pressure hose, 1.5 m, NW 8,		6.390-178.0		<u> </u>		11	+++	+++	+++	+			
incl. connection parts	12	0.390-176.0	'		-	12							
Cleaning agent container, 60 I, empty	13	5.070-078.0			_	13	+++	+++	+++	+			
Emergency off switch		2.744-002.0				14	+++	+++	+++	+			
High-pressure hose, 1.5 m, NW 8,	_	6.388-886.0	_		<u> </u>	15			100				
incl. connection parts, curved outflow	15	0.300 000.0						, , , ,	-11-11-11	- -			
Water filter attachment kit	16	2.209-806.0		-	-	16	++	+	+++	+			
(heat-resistant up to 85°C)											- - -	- - -	- -
Filter inlay 250 µm for 2.209-806.0	17	6.414-977.0		-	-	17			+	\Box			
Main switch		6.631-455.0		-	-	18			\top	\Box			
Attachment kits													
Liquid softener dosing unit	19	2.209-777.0		-	-	19			\top	\Box			
Pressure relief		2.209-773.0		-	-	20		\top	+++	\top			\Box
Operating hour counter		2.209-778.0		-	-	21	+++	+	+	+			\Box
Remote control ready LP, 1 cleaning agent		2.209-779.0		-	_	22	+++	+++	+++	+			
Remote control ready LP, 1 + 2 cleaning agents		2.209-780.0		-	-	23	+++	+	+++	\Box			
Remote control ready HP, 1 cleaning agent		2.209-799.0		-	-	24	+++	+++	+++	+			
Remote control ready HP, 1 + 2 cleaning agents		2.209-800.0		-	-	25	+++	+++	+++	+			
Remote control ready HP, 1 cleaning agent		2.637-779.0		-	-	26	++	+++	+++	+			
Remote control ready HP, 2 cleaning agents		2.637-717.0	_	-	-	27	+++	+++	+++	+			
Hot water generation	-	1								\rightarrow			\vdash
Time switch attachment kit	28	2.637-774.0		For hot water generator HWE 860.	-	28	\Box		$T \perp T$	\Box			
Hot/cold switching attachment kit (suction water)		2.209-805.0		For hot water generator HWE 860.	_	29	+++	+++	+++	+			HH
Water inlet		2.203 003.0		To not nate generate the coo.						\rightarrow			\vdash
Free-flow valve	30	6.412-021.0	. I	NW 20, R 3/4", internal thread.	I-	30	T + T						
Double male coupling, brass		6.387-239.0		NW 20, R 3/4", external thread.	1-	31	+++		\rightarrow	+			HH
Bushing, zinc-coated		7.387-151.0		NW 25, R 1", internal thread (if shut-off device).	_	32	+++		-	+			HH
Screw-in piece		6.386-010.0		NW 20, R 3/4"-R 1", external thread.	_	33	+++		$\overline{}$	+			HH
Free-flow valve		6.412-022.0		NW 25, R 1", internal thread.	_	34	+++	111	+++	+			HH
Nut, zinc-coated	_	6.385-245.0		NW 25, R 1", internal thread.	-	35	+++	1111	+++	+			HH
Double male coupling, brass		6.386-011.0	_	NW 25, R 1" - R 1 1/4", external thread.	-	35	+++		+++	+			+++
Free-flow valve		6.412-023.0		NW 32, R 1 1/4", internal thread.	-	37	+++	\rightarrow		+			+++
Bushing, zinc-coated		6.385-246.0		NW 32, R 1 1/4, internal thread.	-	38	+++			=			+++
Available assessories More Kärsher original a	30	0.303-240.0		inve 52, K 1 1/4 , internal tilleau (il silut-oli device	-	36	444		1-1-1				لللا

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

199
















		Order no. Price	Version	Order no.	Price			HDC 80/16 Standard HDC 80/08 Standard	40/16	40/08 20/08	20/16	HDC 60/16 Standard	90/10	HDC 120/10 Adv HD 7/16-4 St/H	HD 9/18-4 St/H	HD 13/12-4 St/H HDS 9/14-4 St	HDS 12/14-4 St HDS 9/16-4 St Gas HDS 12/14-4 St Gas HDS 12/14-4 St Gas
Double male coupling, brass	_	6.387-375.0	NW 32, R 1 1/4", external thread.	-		39		$\perp \!\!\! \perp$	\vdash	'	115	100	1		\perp		\square
Free-flow valve		6.412-024.0	NW 40, R 1 1/2", internal thread.	-		40			\vdash	'	++	++			$\perp \perp$		+
Reduction bushing, zinc-coated	41	6.385-247.0	NW 40, R 1 1/2"–R 1 1/4", internal thread (if shut-off device).	-		41	T I		Ш								
Double male coupling, brass	42	5.409-598.0	NW 40, R 1 1/2", external thread.	-		42				'							
Free-flow valve	43	6.412-031.0	NW 50, R 2", internal thread.	-		43			\perp	'							
Bushing, zinc-coated	44	6.385-248.0	NW 50, R 2", internal thread (if shut-off device).	-		44			\perp	'	\perp	\perp					
Double male coupling, brass	45	5.409-617.0	NW 50, R 2", external thread.	-		45			Ш	'							
High-pressure line								البيا		البيا							
Connection thread, steel, zinc-coated	46	2.638-180.0	Version VA.	2.638-181.0		46			\perp	'	Ш	$\perp \perp$	Ш		1 0 ,		
Shut-off valve, steel, zinc-coated	47	4.580-144.0	Version VA.	4.580-163.0		47		\perp	\perp	'	$\perp \perp$	$\perp \perp$	\perp	_		_	
Pipeline set, steel, zinc-coated, 3 m	48	2.420-004.0	Version VA.	2.420-006.0		48		\perp	\vdash		$\perp \perp$	$\perp \perp$	\perp			_	
T-screw connections, steel, zinc-coate	_		Version VA.	6.386-465.0		49		\perp	\perp	<u></u> '	$\perp \perp$	\perp	\perp	_		_	
Elbow union, steel, zinc-coated	_	6.386-356.0	Version VA.	6.386-466.0		50		\perp	\vdash	<u></u>	$\perp \perp$	$\perp \perp$	\perp	_		_	
Pipe insulation, per running metre		6.286-147.0	-	-		51		\perp	\vdash	'	++	$\perp \perp$	$\perp \perp$	_		_	
Transition piece, steel, zinc-coated	_	2.638-182.0	Version VA.	2.638-183.0		52		$\perp \!\!\! \perp$	\vdash		$\perp \perp$	$\perp \perp$	$\perp \perp$	_		_	
Quick coupling, fixed part	_	6.463-025.0	Loose part.	6.463-023.0		53				ים נב		100		_		_	
Union nut, steel, zinc-coated	_	6.386-423.0	Version VA.	6.386-428.0		54		$\perp \!\!\! \perp$	+		++	+	\perp	_		_	
Cutting ring		6.386-357.0	-	-		55		$\perp \!\!\! \perp \!\!\! \perp$	\vdash	'	$\perp \perp$	++	\perp				
HP ball tap, nickel-plated		6.412-066.0	NW 13, R 1/2", PN 315, internal thread.	-		56				<u> </u>	1915	100	10		+	_	+
HP ball tap, stainless steel		6.412-491.0	NW 15, R 1/2", PN 140, internal thread.	-		57			H	4	₩	44	\perp		\perp		\square
HP ball tap, stainless steel	_	6.413-500.0	NW 13, R 1/2", PN 400, internal thread.	-		58			_	\rightarrow	-				++	_	+
Double connector, brass		5.402-001.0	R 1/2" × M 22 × 1.5 mm.	-		59		49		-			44		++		++++
HP ball tap, nickel-plated	_	6.412-067.0	NW 20, R 3/4", PN 315, internal thread.	-		60		+		44	++	++	+		++		$\overline{}$
HP ball tap, stainless steel		6.413-503.0	NW 20, R 3/4", PN 350, internal thread.	-		61		+		#	+	++	+		++	-	++++
Bushing, zinc-coated	_	6.979-093.0	NW 20, R 3/4", PN 200, internal thread.	-		62		+		#	++	++	+		++		
Double male coupling		5.403-055.0	NW 20, R 3/4"-M 30 × 1.5 mm, external thread.	-		63		+	冸	4	++-	+	+		++		++++
HP ball tap, nickel-plated		6.412-068.0	NW 25, R 1", PN 315, internal thread.	-		64		+	+	+-	++-	1			++		\square
HP ball tap, stainless steel		6.412-493.0	NW 25, R 1", PN 140, internal thread. NW 25, R 1", PN 350, internal thread.	-		65		+	+	+-'	++-	+++			++		
HP ball tap, stainless steel	_	6.413-502.0		-		66		+	+	+-'	++-				++	_	$\overline{}$
Bushing, zinc-coated		6.979-094.0 5.403-057.0	NW 25, R 1", PN 160, internal thread. NW 25, R 1"-M 30 × 1.5 mm, external thread.	- -		67 68		+	+	+-'	++-	╁╬┼	1 		++	+	
Double male coupling HP ball tap, nickel-plated		6.413-505.0	NW 32, R 1 1/4", PN 400, internal thread.	-		69			+	+-'	++-	+++		П	++	-	
HP ball tap, stainless steel		6.413-501.0	NW 32, R 1 1/4', PN 400, internal thread.	-		70			+	+	++	++			++	-	
Bushing, zinc-coated		6.979-095.0	NW 32, R 1 1/4, PN 400, Internal tiread.	-		71			+	+-'	++	++	+	П	++	+	
Double male coupling		5.403-176.0	NW 32, R 1 1/4"-M 38 × 1.5 mm, external thread.	1_		72			+	+	++	++	+		++	_	
Poonic maic coobiing	/2	J.7UJ-17U.U	INVV 32, IN 1 1/4 IVI 30 * 1.3 IIIIII, EXTERNAL UITEAU.	1		12		- -		/	$\perp \perp$	$\perp \perp$		_	\perp		

☐ Available accessories. More Kärcher original accessories can be found on the following pages.





















		Order no. until 2015	Order no. EASY!Lock	Price	Version	Order no. until 2015	Order no. EASY!Lock	Price		HDC 80/16 Standard HDC 80/08 Standard HDC 40/16 Standard HDC 40/08 Standard HDC 20/08 Classic HDC 20/08 Classic HDC 60/08 Standard HDC 60/16 Standard HDC 60/16 Standard HDC 60/10 Adv HDC 90/10 Adv HDC 90/10 Adv HDC 120/10 Adv
Point of use										
EASY!Force HP trigger gun	73	-	4.118-005.0		-	-	-		73	
Easy Press HP trigger gun with soft grip	74	4.775-463.0	-		-	-	-		74	
Easy Press trigger gun, black	75	4.775-466.0	-		For Servo Press operation.	-	-		75	
Easy Press trigger gun, grey	76	4.775-784.0	-		For Servo Press operation, food industry.	_	-		76	
Industrial trigger gun	77	4.775-823.0	4.118-011.0		Without Servo Press operation.	-	-		77	
Industrial trigger gun, grey	78	4.775-825.0	-		Without Servo Press operation, food industry.	-	-		78	
Servo Control controller	79	4.775-470.0	4.118-008.0		-	-	-		79	
Servo Control controller		4.775-471.0			-	_	_		80	
Rotatable spray lance, 600 mm			4.112007.0		-	-	_		81	
Rotatable spray lance, 1050 mm		4.760-660.0		_	-	_	_		82	
Spray lance, stationary, grey, 600 mm		4.760-625.0	_		Food industry.	_	_		83	
Spray lance, stationary, grey, 1050 mm		4.760-626.0			Food industry.	_	_		84	
Spray lance, stationary, grey, 1550 mm		4.760-627.0			Food industry.	_	-		85	
Spray lance, stationary, grey, 2050 mm		4.760-628.0			Food industry.	_	_		86	
Variable pressure spray lance, 960 mm		6.394-665.0			For cleaning agent application.	_	_		87	
Power nozzle, 25° spray angle		2.883-402.0			25060	-	-		88	
Power nozzle, 25° spray angle		2.883-408.0	+		25100	-	_		89	
Power nozzle, 25° spray angle		2.883-401.0			25055	_	_		90	
Power nozzle, 25° spray angle		2.883-829.0			25043	_	_		91	
Power nozzle, 25° spray angle		2.883-406.0			25080	_	-		92	
Triple nozzle 043		4.767-152.0			-	_	_		93	
Triple nozzle 055		4.767-066.0	_		-	_	_		94	
Triple nozzle 100		4.767-205.0			_	_	_		95	
High-pressure hose, 10 m, NW 8	96		6.110-031.0		20 m.		6.110-032.0		96	
High-pressure hose Longlife 400, 10 m, NW 8		_	6.110-038.0		20 m.		6.110-027.0		97	
High-pressure hose Longlife 400, 10 m, NW 8,		6.388-083.0			20 m without rotary coupling.	6.390-027.0	6.110-027.0		98	
incl. rotary coupling										
High-pressure hose, 10 m, NW 8,	99	6.391-864.0	6.110-053.0		20 m.	6.391-887.0	6.110-054.0		99	
food-compatible design, extension piece										
Hose and spray lance holder VA		2.042-003.0			-	-	-		100	
Emergency off switching element		6.635-434.0	_		For installation in remote control.		-		101	
Emergency off switch		6.651-485.0			For installation in remote control.	2.744-015.0 / -011.0	-		102	
Quick coupling		6.401-458.0			-	-	-		103	
Male coupling			6.115-001.0		-	-	-		104	
Nozzle screws	_		5.394-123.0	_	-	-	-		105	
Hose connector			4.111-037.0		-	-	-		106	
Central cleaning agent supply		3.910-005.0	_		-	-	-		107	
Complete dual dosing unit, stainless steel		2.641-702.0			-	-	-		108	
Wall bracket for storage	_	2.641-703.0	_		-	-	-		109	
Mobile cleaning agent unit	110	2.641-704.0	-		-	-	-		110	
■ Included in the scope of supply □ Availab	le acco	eccories M	ore Kärcher orig	ginal acc	ressories can be found on the following	ng nages				















	Order no.	Price	Version	Price		HDC 80/16 Standard	HDC 80/08 Standard	HDC 40/08 Standard	HDC 20/08 Classic HDC 20/16 Classic	HDC 60/08 Standard HDC 60/16 Standard	HDC 60/10 Adv HDC 90/10 Adv HDC 120/10 Adv	HD 7/16-4 St/H HD 9/18-4 St/H HD 13/12-4 St/H	HDS 9/14-4 St HDS 12/14-4 St	HDS 12/14-4 St Gas HDS 12/14-4 St Gas HDS 12/14-4 St Gas LPG
Central fuel supply	0.00.1101	1	1.4.5.5	1										
Fuel oil tank hose set	111 2.440-001.0		-		111			\prod	\top	$\Box \Box$		\Box		\Box
Heating oil filer	112 4.730-033.0		-		112			\Box	\top			\Box		\Box
Fuel oil tank pipe set (5 m)	113 4.421-208.0		-		113			П	\top					
Fuel oil tank, 700 l	114 6.392-071.0		-		114									
Heating oil suction pipeline	115 4.421-068.0		-		115									
Flexible gas hose	116 6.388-228.0		-		116				\perp				ı	
Gas stopcock	117 6.412-389.0		-		117				\perp				ı	
Gas pressure meter	118 6.421-059.0		-		118								l l	
Control cable												L		
Control cable, 3 × 1.5 mm ²	119 6.641-059.0		-		119									
Control cable, 7 × 1.5 mm ²	120 6.641-064.0		-		120			Ш	\perp					
Control cable, 10 × 1.5 mm ²	121 6.641-082.0		-		121									
Control cable, 12 × 1.0 mm ²	122 6.647-222.0		-		122			Ш	\perp					
Installation tube	123 2.420-008.0		-		123									
Clamp	124 6.373-377.0		-		124							اماماد		

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

205



Whether you need to clean working machinery or a fleet of vehicles, either inside or outside: High-pressure cleaners from Kärcher are indispensable wherever effective care and maintenance are required.















	Order no. until 2015	Order no. EASY!Lock	Price	Version	Order no.	Price			HDC 80/16 Standard HDC 80/08 Standard HDC 40/16 Standard HDC 40/08 Standard	HDC 20/16 Classic	HDC 60/16 Standard HDC 60/10 Adv unr 90/10 Adv	HDC 120/10 Adv HD 7/16-4 St/H	HD 13/12-4 St/H HDS 9/14-4 St HDS 12/14-4 St	HDS 9/16-4 St Gas HDS 12/14-4 St Gas HDS 12/14-4 St Gas LPG
Remote control														
Junction box for remote control	125 2.209-807.	0 -		-	-		125							
Junction box remote control	126 2.209-798.	0 -		-	-		126							
Remote control	127 2.637-491.	0 -		-	-		127							
Single remote control, on/off, hot/cold, cleaning agent 1+2	128 2.744-008.	0 -		-	-		128							
Multiple remote control, I-O, hot/cold, RM 1+2	129 2.744-011.	0 -		In combination with 2.744-036.0.	-		129							
Single remote control, I-O, RM 1+2	130 2.744-014.	0 -		In combination with 2.209-798.0.	-		130							
Multiple remote control, I-O, RM 1+2	131 2.744-015.	0 -		In combination with 2.744-036.0 and 2.209-798.0.	-		131							
Priority switch	132 2.638-200.	0 -		-	-		132							
Multiple coin remote control	133 2.642-422.	0 -		-	-		133							
Multiple operation control electronics	134 2.744-036.	0 -		-	-		134							
Coin acceptor 50 cent	135 2.639-912.	0 -		-	-		135							
Coin acceptor €1	136 2.639-913.	0 -		-	-		136							
Coin acceptor €2	137 2.639-914.	0 -		-	-		137			\Box				
Coin acceptor for coins	138 6.768-063.	0 -		-	-		138							
Coin set, imprint	139 6.768-169.	0 -		-	-		139			\Box				
Coin set	140 6.768-172.			-	-		140							
High-pressure cleaner hose guide					·									
C-rail, per running metre	141 6.233-017.	0 -		-	-		141				\Box			
Rail connector	142 6.541-011.			-	-		142			1 0 0	1000			
Limit stop	143 6.541-025.			-	-		143							
Cable trolley	144 6.541-026.			-	-		144							
End terminal	145 6.541-028.			-	-		145				3000			
Handle	146 6.541-029.			-	-		146				<u> </u>	1000		
Wall bracket	147 6.541-039.			-	-		147							
Rail holder, wall	148 6.541-012.			Ceiling.	6.541-027.0		148							
Spring draw	149 6.542-001.			-	-		149				<u> </u>			
Spray lance cart, mobile	150 4.042-610.	_		-	-		150			1	+++			
Swivelling boom column	151 2.637-121.			Wall.	2.637-120.0		151			+++	+++			
Swivelling boom, ceiling	152 4.058-106.						152			+++				
Hose reel, automatic, 20 m, coated	153 2.639-919.	_)	-	-		153				<u> </u>	1000		
Hose reel, automatic, 20 m, stainless steel	154 6.391-421.		_	-	-		154					1000		
Swivel holder	155 2.639-931.	_		In combination with 6.392-106.0.	-		155							
Exhaust gas nozzle														
Boiler connection piece 80/150	156 6.526-266	.0 -		-	-		156				\top			
Oval boiler connection piece/150	157 4.656-149			-	-		157			+++	+++			
Boiler connection piece 80/200	158 6.526-247			-	-		158			+++	+++	+++		
Large oval boiler connection piece/200	159 4.656-079			-	-		159			+++	+++	+++		
Assembly grease	160 6.526-217			-	-		160			+++	+++	+++		
□ Available accessories. More Kärcher original accessor		_	2000		1			<u> </u>					1-1-1	1-1-1

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

EVEN MORE POWER FOR CHALLENGING TASKS: OUR ULTRA HIGH-PRESSURE CLEANERS

With power ratings from around 15 to 30 kW and a pressure of 350 to 1,000 bar, our compact and mobile ultra high-pressure cleaners are ideal for demanding tasks in transport, construction and industry. Kärcher ultra high-pressure cleaners are partly developed in close collaboration with our WOMA UHP centre of expertise.



Table of contents: Ultra high-pressure cleaners

HD Cage 30 kW	Page	208
HD Cage 15 kW	Page	210
WOMA UHP	Page	212
Ultra high-pressure cleaner accessories	Page	214



Two classes - one quality

Our mobile and flexible HD Cage machines are in a class of their own. The 15 kW class consistently generates a working pressure of 350 to 500 bar. In this class, you can choose between an electric motor and a gasoline engine. The 30 kW class delivers up to 30 l/min at 500 bar and up to 15 l/min at 1,000 bar – exactly the power and endurance you need e.g. for cleaning formwork elements.





How to read the machine names:

Machine type	Flow rate	Working		Motor	Drive	Equipment		
			pressure					
Example: HD	18	/	50	-4				
HD = High-pressure cleaner (cold water) × 100 in			in MPa	-4 = 4-pole	Ge = Gasoline engine (gasoline) De = Diesel engine	Cage = Robust pipe frame Skid = Stationary frame		

Classic = Basic equipment Adv = Advanced

HD CAGE 30 KW



Removes even the most stubborn dirt

Even the most stubborn dirt stands no chance against the 1,000 bar working pressure of our new HD 9/100 ultra high-pressure cleaner, which boasts impressive cleaning performance coupled with low water consumption. This is achieved thanks to the high volumetric efficiency of WOMA's powerful industrial high-pressure pump. This versatile machine can be used for many different applications.











1 Powerful industrial high-pressure pump

- Plunger made from carbide for a long service life.
- Maintenance-friendly design that makes replacing wear parts such as valves, seals and plungers easy.

2 User-friendly WOMA trigger gun

- Lightweight with an ergonomically designed handle for ease of operation.
- $\hfill \blacksquare$ Reduced trigger forces for effortless working.

HD 9/100-4 Cage Adv HD 9/100-4 Cage Classic

		 Pressure relief valve that makes it easy and comfortable to use Booster pump as standard Water shortage protection as standard 	Booster pump as standardWater shortage protection as standard
Technical data			
Current type	Ph / V / Hz	3 / 380-415 / 50	3 / 380-415 / 50
Connection load	kW	30	30
Flow rate	l/h	978	978
Working pressure	bar / MPa	1000 / 100	1000 / 100
Max. pressure	bar / MPa	1100 / 110	1100 / 110
Max. inlet temperature	°C	45	45
Weight	kg	398	392
Dimensions (L × W × H)		1385 × 790 × 1090	1385 × 790 × 1090

Equipment			
Spray gun		UHP trigger gun (Dry Shut)	UHP trigger gun (Dump Gun)
High-pressure hose	m	20	20
Spray lance	mm	750	750
Nozzle		-	-
Integrated water filter			
Automatic pressure relief		•	
Dry run protection		•	I
Order no.		1.812-002.0	1.812-000.0
Price			
■ Included in the scope of supr	nlv.		

■ Included in the scope of supply.

HD CAGE 30 KW



For maximised area performance

Developed to tackle large areas of dirt, this versatile, portable model from our UHP compact class can be used for an impressively wide range of applications. The combination of a working pressure of 500 bar and a water delivery rate of 1,800 l/h results in a cleaning performance of 30 kW, which guarantees excellent results even on large areas. And a cage unit protects the machine even in the harshest conditions.







1 Pressure relief valve

- The pressure relief valve reduces the pressure in the hose, so it remains flexible when the trigger gun is closed.
- Prevents any sudden recoil for the user, as the pressure is built up slowly when pulling the trigger gun.

2 Outstanding mobility

- Large wheels, as well as an optimum centre of gravity secure a high degree of mobility for the machine despite its size.
- $\hfill \blacksquare$ A practical crane hook allows simple transport, also over rough terrain.

HD 18/50-4 Cage Adv

HD 18/50-4 Cage Classic

		Automatic pressure reliefBooster pump (optional)Water shortage protection as standard	Booster pump (optional)Water shortage protection as standard
Technical data			
Current type	Ph / V / Hz	3 / 380-415 / 50	3 / 380-415 / 50
Connection load	kW	30	30
Flow rate	I/h	1800	1800
Working pressure	bar / MPa	max. 500 / max. 50	max. 500 / max. 50
Max. pressure	bar / MPa	620 / 62	620 / 62
Max. inlet temperature	°C	max. 60	max. 60
Weight	kg	317	321
Dimensions (L × W × H)	mm	747 × 1317 × 1093	747 × 1317 × 1093
Equipment			
Spray gun		Industrial trigger gun	Industrial trigger gun
High-pressure hose	m	20 / Heavy duty	20 / Heavy duty
Spray lance	mm	700	700
Nozzle		Power nozzle	Power nozzle
Integrated water filter			
Automatic pressure relief			-
Dry run protection		•	
Order no.		1.367-162.0	1.367-160.0

■ Included in the scope of supply.

211

■ Included in the scope of supply.



Enter into the world of ultra high-pressure cleaners

With 350 to 500 bar working pressure, these are entry-level UHP Compact class machines. The machines have a tough cage design, are relentless against dirt, safe to load by crane and very easy to transport with the clever sack truck principle.













Accessories and tools are stored in a protected compartment. This means that everything is always in its place.



HD 13/35-4 Cage

		Robust industrial gunDry run protection (optional)	Robust industrial gunDry run protection (optional)
Technical data			
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50
Connection load	kW	15	15
Flow rate	l/h	500-900	500-1300
Working pressure	bar / MPa	150-max. 500 / 15-max. 50	100-max. 350 / 10-max. 35
Max. pressure	bar / MPa	640 / 64	450 / 45
Max. inlet temperature	°C	max. 60	max. 60
Weight	kg	190	190
Dimensions (L × W × H)	mm	930 × 800 × 920	930 × 800 × 920
Equipment			
Spray gun		Industrial trigger gun	Industrial trigger gun
High-pressure hose	m	10 / Heavy duty	10 / Heavy duty
Spray lance	mm	700	700
Nozzle		Power nozzle	Power nozzle
Integrated water filter		•	•
Automatic pressure relief		-	-
Dry run protection		-	-
Order no.		1.367-156.0	1.367-154.0

HD CAGE 15 KW



Maximum flexibility for tough applications

The economical and reliable combustion engine offers maximum independence. The machine easily copes with the most difficult cleaning tasks thanks to 350 or 500 bar water pressure.





1 Industrial spray gun

Robust and durable: The new Kärcher industrial trigger gun was designed specially

2 Speed regulation

■ The speed is automatically reduced in standby mode. This protects the engine and saves energy.

HD 9/50 Ge Cage

HD 13/35 Ge Cage


		Robust industrial gunDry run protection (optional)Speed regulation	Robust industrial gunDry run protection (optional)Speed regulation
Technical data			
Engine manufacturer		Honda	Honda
Motor type		GX 660/Gasoline	GX 660/Gasoline
Motor rating	kW	16	16
Flow rate	I/h	500-900	500-1300
Working pressure	bar / MPa	150-max. 500 / 15-max. 50	100-max. 350 / 10-35
Max. pressure	bar / MPa	640 / 64	450 / 45
Max. inlet temperature	°C	max. 60	max. 60
Weight	kg	135	135
Dimensions (L × W × H)	mm	930 × 800 × 920	930 × 800 × 920
Equipment			
Spray gun		Industrial trigger gun	Industrial trigger gun
High-pressure hose	m	10 / Heavy duty	10 / Heavy duty
Spray lance	mm	700	700
Nozzle		Power nozzle	Power nozzle
Integrated water filter		I	I
Automatic pressure relief		-	-
Dry run protection		-	-
Order no.		1.367-506.0	1.367-505.0
Price			

■ Included in the scope of supply.

WOMA - INDIVIDUAL CONFIGURATIONS IN 4 STEPS

Thanks to consistent investment in research and development, a pioneering spirit and dedication to innovation, WOMA has been the technological leader and a driver of innovation in high-pressure water stream technology for decades. WOMA develops systems that can achieve water pressures of up to 4,000 bar and flow rates of around 1,800 litres per minute. As part of the Kärcher Group, the world market leader for cleaning technology, WOMA also plays an important role internationally.











1 Pum

Low-speed and low-wear ultra high-pressure pumps from WOMA are characterised by operating pressures of up to 4,000 bar, a long lifetime and long maintenance intervals.

2 System control

WOMA offers the right system based on the requirements of the application and the customer's specifications, from Classic control for dump gun operation through to easy-to-understand Expert control. Expert control impresses with operating state monitoring, pressure-speed control for high operational safety, and efficient use of resources, for example.


3 Driv

The ultra high-pressure pumps can be driven either by robust diesel engines or zero-emission electric motors with energy efficiency class rating IE3. Diesel engines with legal emissions levels are fitted depending on the applicable legislation.

4 Assembly options

Complete assembly flexibility: The ultra-high-pressure unit can be assembled on a simple basic frame or on a moving trailer with hood. It is also easy to install in an ISO container.

Further information is available at www.woma.de.













Suitable for a variety of applications thanks to special accessories

- 1 Heat exchanger cleaning
- 2 Paint stripping
- 3 Formwork cleaning

Further information is available on request.

4 Surface cleaning

5 Concrete restoration

EXTENSIVE ACCESSORIES FOR OPTIMAL RESULTS IN A WIDE RANGE OF APPLICATIONS

Our ultra high-pressure cleaners impress with outstanding power. To enable you to harness this power for a wide variety of applications, such as formwork cleaning or concrete restoration, we offer a variety of perfectly adapted accessories. And if you require further special solutions, our WOMA Competence Centre will always find the right solution for you.



Table of contents: Ultra high-pressure cleaner accessories

UHP accessories Page 216

MACHINE

ACCESSORIES



Surface treatment



Pipe cleaning



Tank interior cleaning



APPLICATION





Ship paint stripping Paint stripping and paint booths



Heat exchanger cleaning Pipe cleaning





Tank and silo cleaning Cleaning of agitator vessels





UHP ACCESSORIES



Spray lances, exchange nozzles, hoses and application-specific water tools: the extensive range of system accessories for ultra high-pressure machines underlines the wide variety of applications and performance of these machines.

















*0
26

	Order no.	ID	Length	Price Description		HD 9/100-4 Cage Adv HD 9/100-4 Cage Classic HD 18/50-4 Cage Classic HD 18/50-4 Cage Classic HD 13/35-4 Cage HD 13/35 Ge Cage HD 13/35 Ge Cage HD 13/35 Ge Cage HD 13/35 Ge Cage
Attachment kits	1					
Filter fleece filter housing 100 µm	1 6.414-074.0			5 pc. filter fleece, 100 μm for filter casing.	1	
Booster pump HD 18/50 attachment kit	2 2.637-017.0			Booster pump attachment kit for reliable high-pressure pump water supply. The advance pressure pump is installed in the machine.	2	
Filter fleece, filter casing	3 6.414-073.0			Packaging unit = 5 pc.	3	
Splash guard	4 9.871-040.0			Splash guard for pushing onto the spray lance.	4	
Pressure screw	5 9.883-492.0			Pressure screw with the connection size M26 × 1.5.	5	
Pressure ring	6 9.883-570.0			Pressure ring, connection size 9/16" UNF.	6	
ABS protection against dry run	7 2.641-922.0			For electric motors.	7	
Albo protection against ary ron	8 2.641-923.0			For gasoline engines.	8	
ABS protection against water shortage					9	
ABS protection against water shortage	9 2.851-028.0			ABS steering rollers.	5	
High-pressure hoses Hose 20 m NW 6, 1100 bar	10 9.919-791.0			Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 24 × 1.5. Suitable for up to 1100 bar working pressure.	10	
Hose sling	11 9.887-583.0			Hose safety loop for securing the high-pressure hose at the machine. Prevents uncontrolled whipping in the event of malfunctions, thus minimising the risk of injury for the injury.	11	
Hose 40 m NW 6, 1100 bar M24 × 1.5 DKO	12 9.919-912.0			Abrasion-resistant and flexible multi-layer steel-reinforced hose with 40 m length. Suitable for up to 1100 bar working pressure. Connection size M 24 × 1.5.	12	
Pressure hose	13 6.391-856.0	ID 8	3 m	Durable, abrasion-resistant and flexible multi-layer steel-reinforced hos	e 13	
	14 6.391-848.0	ID 8	10 m	with connection size M 22 × 1.5. Suitable for up to 640 bar working	14	
	15 6.391-857.0		20 m	pressure.	15	
	16 6.391-020.0	_	30 m		16	
	17 6.391-846.0		10 m	Durable, abrasion-resistant and flexible multi-layer steel-reinforced hos		
	18 6.391-847.0		20 m	with connection size M 22 × 1.5. Suitable for up to 620 bar working	18	
	19 6.391-019.0		30 m	pressure.		
Grease for stainless steel threaded joints		10 10	30 111		19 20	
Hose connector	21 9.877-911.0			Prevents threaded connections getting stuck. For connecting and extending high-pressure hoses with connection	21	
Draccura ceraw	22 0 883-660 0	1		M 24 × 1.5. Proceins screw connection size 1 1/9" LINE	22	
Pressure screw	22 9.883-669.0 23 9.883-670.0			Pressure screw, connection size 1 1/8" UNF. Pressure ring, connection size 9/16" UNF.	22 23	
Pressure ring	23 3.863-070.0			Pressure ring, connection size 3/10 ONF.	23	
Trigger guns Kärcher industry gun	24 4.775-824.0			650 bar – industrial spray gun with optimised flow. Robustness and dura bility for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 × 1.5.	24	
UHP trigger gun	25 9.918-180.0			The UHP trigger gun is suitable for working pressures of up to 1500 bar. The water is recycled into the circulation system when the trigger gun is closed. Connection for high-pressure hose, M24 × 1.5.	25	
	26 9.918-187.0 ■			The bypass trigger gun is suitable for working pressures of up to 3000 b The water flows into a bypass when the trigger gun is closed. Connection for high-pressure hose, 9/16" UNF.		
Shoulder support	27 9.918-752.0	1		Sturdy shoulder support that must be used from a recoil force of more	27	
	28 6.025-301.0			than 150 N.	28	
	29 2.639-251.0			Sturdy shoulder support that must be used from a recoil force of more than 150 N. Fits all Kärcher industrial lances.	29	

than 150 N. Fits all Kärcher industrial lances.

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

























	Outouro		Longth	Peice Permitting			HD 9/100-4 Cage Adv HD 9/100-4 Cage Classic HD 18/50-4 Cage Classic HD 18/50-4 Cage HD 13/35-4 Cage HD 13/35 Ge Cage HD 13/35 Ge Cage
- Harris and the second	Order no.	ID	Length	Price Description	Could be a sought of the bish account have	20	
Hose connection	30 9.871-969.0			at the UHP trigger gun. Th	nent for the assembly of the high-pressure hose e hose is fixed to the trigger gun. Connection for up to 1500 bar working pressure.	30	
Adapter for bypass hose	31 9.897-358.0			Adapter for connecting a		31	
Bypass hose	32 9.887-970.0			Bypass hose for efficient	draining of bypass water from the Dump Gun.	32	
Adapter for pressures of up to 1500 bar when using the dump gun	33 9.918-624.0	•		Adapter for bypass trigge Connection for high-press	r gun for pressures of up to 1500 bar. ure hose. M24 × 1.5.	33	
Bypass pipe	34 9.918-623.0				the bypass water from the bypass trigger gun.	34	
Spray lances							
Nozzle pipe	35 9.891-182.0			Spray lance with connecti	on size 9/16" UNF. Suitable for up to 1500 bar	35	
Spray lance	36 9.891-185.0	_	2000	working pressure.		36	
Spray lance extension	37 4.760-699.0		800	Spray lance extension 80) mm, 65 MPa.	37	
Spray lance	38 4.760-679.0		700 mm		on size M 22 × 1.5 and nozzle intake.	38	
	39 4.760-653.0		1050 mm	Suitable for up to 640 bar		39	
	40 4.760-675.0		1500 mm			40	
	41 4.760-677.0		2050 mm			41	
	42 9.891-183.0		750 mm	Spray Jance with connecti	on size 9/16" UNF. Suitable for up to 1500 bar	42	
	43 9.891-184.0		1000 mm	working pressure.		43	
	44 9.891-207.0	_	1500 mm			44	
Spray lance handle	45 6.025-300.0			Spray lance handle.		45	
Spray lance handle, 90°	46 9.871-675.0				e. 90° angle to spray lance axis. Flexible and	46	
Abrasive blaster							
Required adapter for abrasive blasters	47 5.401-325.0			M 20 × 1 IG to 9/16" UNF	AG.	47	
Abrasive blaster	48 6.025-253.0			Abrasive spray head for v Only includes spray head.	vet sand blasting. Nozzle size: 3 × 0.6 mm. Without hose and lance.	48	
Abrasive blaster, incl. 3 × 0.7 nozzle	49 9.872-435.0				vet sand blasting. Nozzle size: 3 × 0.7 mm.	49	
	50 9.917-716.0				vet sand blasting. Nozzle size: 3 × 0.8 mm.	50	
Replacement nozzle for abrasive blaster	51 6.025-346.0			Replacement nozzle for b	oron carbide abrasive spray head. Colour blue.	51	
F98 nozzle for abrasive blaster	52 6.025-434.0			Three-nozzle kit for abras 0.6 mm.	ive spray head for wet sand blasting. Nozzle size	52	
	53 6.025-256.0			Nozzle for abrasive spray	head for wet sand blasting. Nozzle size 0.6 mm.	53	
	54 9.886-551.0			Three-nozzle kit for abras 0.7 mm.	ive spray head for wet sand blasting. Nozzle size	54	
	55 6.025-255.0	1		Nozzle for abrasive spray	head for wet sand blasting. Nozzle size 0.7 mm.	55	
	56 9.886-552.0			Three-nozzle kit for abras 0.8 mm.	ive spray head for wet sand blasting. Nozzle size	56	
	57 9.886-538.0			Nozzle for abrasive spray	head for wet sand blasting. Nozzle size 0.8 mm.	57	
Suction lance	58 6.025-258.0			For the suction of spray a	gents.	58	
Abrasive material hose	59 6.025-308.0			Abrasive hose.		59	
Mounting tool for nozzle set	60 6.025-257.0			For F98 nozzles.		60	
Abrasive	61 6.025-309.0			25 kg, 0.5-1.00 mm, garn	et sand.	61	
	62 6.025-310.0			25 kg, 0.7-1.40 mm, garn	et sand.	62	
Coupling			'				
Coupler -2 × M22 × 1,5	63 4.403-002.0			For connecting and extend	ling LID bosos, Connection 2 M 22 1 F	63	
					IIIIg HP HOSES. CONNECTION 2 × M 22 × 1.5.	03	

















							9/100-4 Cage Adv 29/100-4 Cage Classic 20/100-4 Cage Classic 20/18/50-4 Cage Classic 20/18/50-4 Cage 20/13/35-4 Cage 20/35-4 Cage 20/35-6 Cage 20/35-6 Cage 20/35-6 Cage 20/35-6 Cage
	Order no.	ID	Length	Price	Description		
Single-jet rotary nozzles						Last	
Nozzle Set D1.00	65 9.884-069.0				Rotary nozzle repair kit, comprising rotor, seat and o-ring. Compatible with our single-jet rotary nozzle (order no. 9.886-666.0). Can be used up to 1500 bar water pressure.	65	
F7 power rotary jet	66 6.415-914.0				350 bar, 1.35 mm, 1300 l/h, M 20 × 1, stainless steel.	66	
Rotary jet	67 4.767-173.0				350 bar, 1.35 mm, 1300 l/h, M 20 × 1, brass.	67	
F8 power rotary jet	68 6.415-915.0				500 bar, 1.05 mm, 900 l/h, M 20 × 1, stainless steel.	68	
F9 power rotary jet	69 6.415-060.0				500 bar, 1.5 mm, 1800 l/h, M 20 × 1, stainless steel.	69	
Power rotary Jet	70 9.886-666.0				Single-jet rotary nozzle, 1.00 mm for up to 1500 bar working pressure.	70	
Power Rotary Jet Repair Kit F7	71 6.025-436.0				Repair kit for Power Rotary Jet, order no. 6.415-914.0. Suitable for 350 bar pressure and 1300 l/h water flow. Includes rotor, seat and 0-ring (28 × 2).	71	
F8 power rotary jet repair kit	72 6.025-437.0				Repair kit for Power Rotary Jet, order no. 6.415-915.0. Suitable for 500 bar pressure and 900 l/h water flow. Includes rotor, seat and 0-ring (28 × 2).	72	
F9 power rotary jet repair kit	73 6.025-526.0				Repair kit for Power Rotary Jet, order no. 6.415 -060.0. Suitable for 500 bar pressure and 1800 l/h water flow. Includes rotor, seat and 0-ring (28×2).	73	
Tool for changing rotor seat	74 6.025-233.0				For single-jet rotary nozzles.	74	
Multi-jet rotary nozzles							
Nozzle shape 21S	75 9.886-211.0				F21 screw-on sapphire round spray nozzle, 0.55 mm diameter, suitable for up to 3000 bar working pressure.	75	
	76 9.886-212.0				F21 screw-on sapphire round spray nozzle, 0.60 mm diameter, suitable for up to 3000 bar working pressure.	76	
Nozzle holder head	77 9.918-067.0				4-jet nozzle holder for F21 nozzle. Suitable for up to 3000 bar working pressure. 45° spray angle, includes guard and flow conditioner.	77	
Nozzle carrier head	78 9.886-875.0 ■				6-jet nozzle holder for F21 nozzle. Suitable for working pressures of up to 3000 bar. 30° spray angle, includes guard and flow conditioner.	78	
	79 9.899-828.0 ■				Nozzle holder for F21 nozzle. Suitable for working pressures of up to 3000 bar. 35° spray angle, includes guard and flow conditioner.	79	
Round spray nozzle F21, Saphir	80 6.025-221.0				Sapphire round spray nozzle F21. Screw-on, with 0.65 mm diameter and suitable for up to 3000 bar working pressure.	80	
Nozzle body	81 9.917-677.0				Rotary transmission lead-through with infinitely variable speed control. Includes protective pipe.	81	
Round jet nozzle	82 9.886-207.0				F21 screw-on sapphire round jet nozzle, 0.30 mm diameter, suitable for working pressures of up to 3000 bar.	82	
	83 9.886-208.0				F21 screw-on sapphire round jet nozzle, 0.35 mm diameter, suitable for working pressures of up to 3000 bar.	83	
	84 9.886-209.0				F21 screw-on sapphire round jet nozzle, 0.40 mm diameter, suitable for working pressures of up to 3000 bar.	84	
	85 6.025-220.0 ■				F21 screw-on sapphire round jet nozzle, 0.45 mm diameter, suitable for working pressures of up to 3000 bar.	85	
	86 9.886-210.0				F21 screw-on sapphire round jet nozzle, 0.50 mm diameter, suitable for working pressures of up to 3000 bar.	86	
	87 6.025-222.0				F21 screw-on sapphire round jet nozzle, 0.70 mm diameter, suitable for working pressures of up to 3000 bar.	87	
	88 9.886-216.0 •				F21 screw-on sapphire round jet nozzle, 0.90 mm diameter, suitable for working pressures of up to 3000 bar.	88	
F21 dummy nozzle - no hole	89 6.025-237.0	•			F21 screw-on dummy nozzle for working pressures of up to 3000 bar.	89	

[■] NEW □ Available accessories. More Kärcher original accessories can be found on the following pages.









	Order no.	ID Leng	th Price	Description		HD 9/100-4 Cage Adv HD 9/100-4 Cage Classic HD 18/50-4 Cage Classic HD 18/50-4 Cage HD 13/35-4 Cage HD 13/35-6 Cage HD 13/35 Ge Cage HD 13/35 Ge Cage HD 13/35 Ge Cage HD 13/35 Ge Cage
Power nozzles						
Flat jet nozzle	90 5.765-165.0			15°, 350 bar, 1300 l/h (gasoline, 60 Hz).	90	
	91 5.765-166.0 92 5.765-163.0			15°, 350 bar, 1300 l/h (electr.). 15°, 500 bar, 900 l/h (gasoline, 60 Hz).	91	
	93 5.765-164.0			15°, 500 bar, 900 l/h (gasoline, 60 Hz). 15°, 500 bar, 900 l/h (electr./HDS trailer).	92	
	94 5.765-190.0			15°, 350 bar, 1300 l/h (HDS trailer).	94	
	95 5.765-263.0			15°, 500 bar, 1800 l/h.	95	
	96 2.113-073.0			15° flat jet nozzle 15075 for high-pressure cleaner HD 18/50. Reduces the	96	
	30 2.113 073.0			water pressure from 500 to 350 bar while retaining flow rate of 1800 l/h.		
	97 2.113-075.0			15° flat jet nozzle 15095 for high-pressure cleaner HD 18/50. Reduces the	97	
				water pressure from 500 to 250 bar while retaining flow rate of 1800 l/h.		
	98 2.113-077.0			15° flat jet nozzle 15120 for high-pressure cleaner HD 18/50. Reduces the	98	
Detail nozzle	99 5.765-161.0			water pressure from 500 to 150 bar while retaining flow rate of 1800 l/h. 350 bar, 1300 l/h (gasoline, 60 Hz).	99	
Betan nozzie	100 5.765-162.0			350 bar, 1300 l/h (electr.).	100	
	101 5.765-159.0			500 bar, 900 l/h (electr.).	101	
	102 5.765-160.0			500 bar, 900 l/h (gasoline, 60 Hz).	102	
	103 5.765-264.0			500 bar, 1800 l/h.	103	
	104 2.113-074.0			Point jet nozzle 075 for high-pressure cleaner HD 18/50. Reduces the	104	
				water pressure from 500 to 350 bar while retaining flow rate of 1800 l/h.		
	105 2.113-076.0			Point jet nozzle 095 for high-pressure cleaner HD 18/50. Reduces the water pressure from 500 to 250 bar while retaining flow rate of 1800 l/h.	105	
	106 2.113-078.0			Point jet nozzle 120 for high-pressure cleaner HD 18/50. Reduces the water pressure from 500 to 150 bar while retaining flow rate of 1800 l/h.	106	
Plug-in nozzles F4/F19		'				
F4/F19 nozzle holder	107 9.872-008.0			Nozzle holder for nozzle F4/F19. Suitable for up to 1500 bar	107	
				working pressure.		
O-ring	108 6.025-168.0			O-ring for sealing between nozzle holder and nozzle F4/F19. This is absolutely necessary as sealing takes place only with the O-ring.	108	
F4 round spray nozzle	109 6.025-470.0			Plug-in round spray nozzle F4, 0.90 mm for up to 1500 bar working pressure.	109	
	110 6.025-198.0			Working pressure. Plug-in round spray nozzle F4, 1.00 mm for up to 1500 bar working pressure.	110	
	111 9.885-951.0			Plug-in round spray nozzle F4, 1.10 mm for up to 1500 bar	111	
	112 6.025-199.0			working pressure. Plug-in round spray nozzle F4, 1.20 mm for up to 1500 bar working	112	
	112 0.025-199.0			pressure.	112	
	113 6.025-196.0			F4 round spray nozzle with 1.3 mm. Pluggable, suitable for up to 250 bar	113	
				working pressure with flow rate of 900 I water per hour.		
F19 flat jet nozzle	114 6.025-466.0			Plug-in flat jet nozzle F19, 1.10 mm, 20°, for up to 1500 bar working pressure.	114	
	115 6.025-467.0			1500 bar, 1.10 mm, 30°.	115	
	116 6.025-207.0			Plug-in flat jet nozzle F19, 1.20 mm, 20° for up to 1500 bar working pressure.	116	
	117 6.025-208.0			Plug-in flat jet nozzle F19, 1.20 mm, 30°, for up to 1500 bar working pressure.	117	
	118 6.025-469.0			Plug-in flat jet nozzle F19, 1.30 mm, 30°, for up to 1500 bar working pressure.	118	

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.













						9/100-4 Cage Adv 9/100-4 Cage Classic 18/50-4 Cage Classic 118/50-4 Cage Classic 118/50-4 Cage Classic 113/35-4 Cage 13/35-6 Cage 13/35 Ge Cage 13/35 Ge Cage 13/35 De Tr1
						100- 100- 100- 100- 100- 100- 100- 100-
						1 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1
		Order no. ID	Length Price	Description		
F19 flat jet nozzle		6.025-211.0		1500 bar, 1.40 mm, 20°.	119	
		6.025-212.0		1500 bar, 1.40 mm, 30°.	120	
	121	6.025-203.0		F19 flat jet nozzle with 1.50 mm and 20°. Suitable for up to 350 bar working pressure with flow rate of 900 litres of water per hour.	121	
	122	6.025-204.0		1500 bar, 1.50 mm, 30°.	122	
Screw nozzles F21	122	0.025 20 1.0		1555 501, 2.55 1111, 55 .	122	
Nozzle shape 21S	123	9.886-213.0		Screw-on F21 sapphire round spray nozzle with 0.75 mm diameter. Suitable for up to 3000 bar working pressure.	123	
Nozzle shape 21	124	9.886-219.0		Screw-in F21 Saphir round spray nozzle with diameter of 1.10 mm. Suitable for working pressures of up to 3000 bar.	124	
F21 nozzle holder		9.878-291.0		Nozzle holder for sapphire nozzle F21. Suitable for up to 3,000 bar working pressure.	125	
F21 round spray nozzle, sapphire		9.886-214.0		Screw-type sapphire round spray nozzle F21, 0.80 mm for up to 3000 bar working pressure.	126	
		9.886-215.0		Screw-type sapphire round spray nozzle F21, 0.85 mm for up to 3000 bar working pressure.	127	
		9.886-217.0		Screw-type sapphire round spray nozzle F21, 0.95 mm for up to 3000 bar working pressure.	128	
	129	9.886-218.0		Screw-type sapphire round spray nozzle F21, 1.00 mm for up to 3000 bar working pressure.	129	
Pipe cleaning	1.00		1 1		Land	
Foot valve for pipe cleaning		6.470-223.0		The foot valve allows safe and convenient use of accessories for effective pipe cleaning.	130	
Pipe cleaning nozzle, standard		5.763-093.0 5.763-090.0		Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	131	
		6.025-527.0		Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection.	133	
Pipe cleaning nozzle, Quattro	134	5.763-094.0		Quattro pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded	134	
	135	5.763-091.0		connection. Nozzle configuration: 3x backward and 1x forward.	135	
	136	6.025-528.0		Chisel point nozzle with forward jet for removing the most stubborn dirt. With G1/4" threaded connection.	136	
Pipe cleaning nozzle, Rotor	137	5.763-095.0		Rotor pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded	137	
		5.763-092.0		connection. Nozzle configuration: 3x backward.	138	
	139	6.025-529.0		Rotor pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection.	139	
Pipe cleaning hose	140	6.392-401.0 ID 8	10	Flexible high-pressure hose (ID 8) for thorough pipe cleaning, 10 m long. Threaded connection for G1/4" nozzle.	140	
	141	6.392-402.0 ID 8	20	Flexible high-pressure hose (ID 8) for thorough pipe cleaning, 20 m long. Threaded connection for G1/4" nozzle.	141	
	142	6.392-403.0 ID 8	30	Flexible high-pressure hose (ID 8) for thorough pipe cleaning, 30 m long. Threaded connection for G1/4" nozzle.	142	
Surface cleaner						
Surface Cleaner FRI 50 Me	143	2.643-577.0		Surface cleaner for efficient surface cleaning up to 500 bar and hot water cleaning up to 100°C. With four convenient castors. Machine-specific	143	
				nozzla kits must be ordared senarately		
Nozzle package 030 FRI 50 Me	144	6.415-059.0		nozzle kits must be ordered separately. Machine-specific nozzle kit for Surface Cleaner FRI 50 Me	144	
Nozzle package 030 FRI 50 Me Nozzle package 015 FRI 50 Me		6.415-059.0 6.415-044.0		nozzle kits must be ordered separately. Machine-specific nozzle kit for Surface Cleaner FRI 50 Me.	144	

Nozzle package 025 FRI 50 Me 146 6.415-045.0

Available accessories. More Kärcher original accessories can be found on the following pages.

EXTRA SAFE. EXTRA ELEGANT.

Working safely has never been so attractive! Our current collection of personal protection equipment sets new standards when it comes to safety and appearance. It not only offers reliable protection against dirt, moisture, noise and injury, but also looks refreshingly stylish. The high-quality materials are low-maintenance, robust and extremely durable, guaranteeing optimal freedom of movement and a high level of wearing comfort. You are sure to find the right work protection solution for every application. And working safely means working better.



Table of contents: Work protection

High-pressure overall	Page	228
Wet work protection suits	Page	230
Hearing and head protection	Page	231
Safety goggles	Page	232
Protective gloves	Page	233



High-pressure protection suit

Our high-pressure protection suit protects you on all sides against water streams up to 1,000 bar. This protection suit is very light, breathable and washable. The seams are also completely waterproof. You are protected against cutting injuries, but can still move freely. Reflectors on the sleeves and legs give you additional security thanks to enhanced visibility.

Wet work protection suits

Kärcher protection suits in the Classic and Advanced versions effectively protect the body from external influences, especially when using high-pressure and ultra high-pressure cleaners.

Hearing and head protection

Whether earplugs with cord, foldable ear defenders or the complete helmet unit - Kärcher offers the right solution for any task.

Safety goggles


The range of Kärcher safety goggles incorporates the expertise of uvex – a leading manufacturer of safety products. Innovative technology and a sporty design make them an important work protection tool, as well as the ideal companion for leisure.

Protective gloves

Kärcher protective gloves ensure that your fingers are always optimally protected.

UHP work protection

Protective clothing for pressure classes up to 3,000 bar is available in the UHP competence centre of WOMA.



Unique. Safe. Certified.

The water jet of our high-pressure and ultra high-pressure cleaners develops a powerful force. In order to effectively protect users and other persons involved, we commissioned the hazard protection experts from DEHN with the development of a protection suit. The result is the first protection suit that resists a high-pressure water jet of up to 1,000 bar according to the testing principle GS-IFA-P15.

















1 Special protection

- Arms and legs are also protected with hard-wearing protectors.
- Reflectors improve visibility and increase safety.

3 Comfortable to wear

- Only weighs 2.3 kg in size M incl. protectors.
- Pleasant-to-wear sensation with great freedom of movement.
- Breathable material.

2 Complete safety

- High-pressure resistant up to 1,000 bar. In every place.
- Completely waterproof i.a.w. EN 343 (Class 3).
- High abrasion and cut resistance.







KÄRCHER WET WORK PROTECTION SUITS



All-round protection

The wear- and tear-resistant. wet work protection suits from Kärcher provide a pleasant sense of safety through and through. They feature an impressively good fit and high level of comfort. Thanks to a water-, oil- and dirt-repellent fluorocarbon impregnation and its hydrophilic membrane, the suits guarantee reliable protection at all times, even for the most demanding cleaning tasks and outdoor work. The high-quality workmanship can be seen and felt.









Good feeling of security

- Noticeably safer working.
- Maximum freedom of movement.

Perfect fit

- Optimal wearing comfort.
- Excellent workmanship.

Attractive appearance

Professional work clothing and an attractive appearance do not have to be mutually exclusive.

Highly effective protection

■ Water-, oil- and dirt-repellent fluorocarbon impregnation, together with the breathable hydrophilic membrane, offers optimal protection against moisture and dirt.

Accessories		Designation	Fig.	Size	Order no.	Price
Protective suits						
_		Wet work protection suit, Classic	1	М	6.025-495.0	
	3	Wet work protection suit, Classic		L	6.025-496.0	
		Wet work protection suit, Classic		XL	6.025-497.0	
		Wet work protection suit, Classic		XXL	6.025-498.0	
	7 (500)	Wet work protection suit, Advanced	2	М	6.025-499.0	
		Wet work protection suit, Advanced		L	6.025-500.0	
# 4 1 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	(COMPANY)	Wet work protection suit, Advanced		XL	6.025-501.0	
		Wet work protection suit, Advanced		XXL	6.025-502.0	
		Wet work protection jacket, Advanced	3	М	6.025-503.0	
		Wet work protection jacket, Advanced		L	6.025-504.0	
	-	Wet work protection jacket, Advanced		XL	6.025-505.0	
		Wet work protection jacket, Advanced		XXL	6.025-506.0	
1 2	4					
1 2	4	Wet work protection trousers, Advanced	4	М	6.025-507.0	
		Wet work protection trousers, Advanced		L	6.025-508.0	
		Wet work protection trousers, Advanced		XL	6.025-509.0	
		Wet work protection trousers, Advanced		XXL	6.025-510.0	

KÄRCHER HEARING AND HEAD PROTECTION



Head and ears safely shielded

A constantly high level of noise puts the body and mind under stress and can permanently damage sensitive human hearing. Therefore, when working with a noise level above 80dB(A), hearing protection measures are not just highly recommended but are even required by law. Kärcher offers reliable hearing protection solutions to prevent hearing impairment. For pleasant and efficient working without constant acoustic stress.













Always keep a cool head

- Ventilation openings in the helmet can be adjusted to the respective climate and weather conditions.
- Best possible ventilation at every stage of the job.

Maximum comfort with optimal sound-damping

- Ear defenders on the helmet feature very soft foam pads.
- High level of wearing comfort with noise insulation of 31dB(A) (SNR value).

Head protection combination

- Perfect adaptation to the surrounding work conditions thanks to three variable ventilation openings.
- Foldable visor offers very good all-round protection.

Foldable ear defenders

- With high-quality steel frame and two-point suspension for optimal protection and comfort
- Perfectly suited for long periods of use.
- All control elements are clearly arranged and easy to access.

Accessories	Designation	Fig.	Size	Order no.	Price
Hearing protection					
	Earplugs	1	One size	6.025-511.0	
	Safety helmet set, with hearing protection and visor	2	One size	6.025-512.0	
1	Ear defenders	3	One size	6.025-513.0	
11	Replacement ear defenders for helmet			6.025-514.0	
	Replacement visor for helmet			6.025-515.0	

THE KÄRCHER SAFETY GOGGLES RANGE



Kärcher safety goggles safe and stylish

The goggles are based on the patented "Duo Component Technology" of the brand manufacturer uvex. This technology perfectly combines hard and soft components for a perfect fit at contact points on the nose, forehead and ears, as well as maximum comfort even during continuous use. Kärcher's innovative safety goggles are not just for work.











Free and clear vision

- Coatings optimally formulated for working with water and steam.
- All panes are permanently mist-free on the inside and have an extremely scratch-resistant coating on the outside.

Safe at work

- Maximum protection against all mechanical hazards in accordance with DIN EN 166 thanks to highly impact-resistant polycarbonate.
- Distortion-free vision with 100% UV protection.

Sophisticated frame design

- Patented hingeless quattroflex side pieces made from highly impactresistant Grilamid. With four soft pads, they ensure a pressureless and comfortable fit in the sensitive ear area.
- The length and tilt angle of the side piece can be individually adjusted.

Innovative frame construction

- Indirect ventilation keeps the eyes comfortable.
- Shock absorber in the forehead area guarantees high impact resistance and a perfect fit.

Accessories		Designation	Fig.	Size	Order no.	Price
Safety goggles						
		Safety goggles, clear	1	One size	6.025-482.0	
		Safety goggles, sun protection	2	One size	6.025-483.0	
		Safety goggles, contrast-enhancing	3	One size	6.025-484.0	
1 2	3	Replacement pane, clear	4	One size	6.025-485.0	
lan a		Replacement pane, sun protection	5	One size	6.025-486.0	
6	(*	Replacement pane, contrast-enhancing	6	One size	6.025-487.0	
4 5	6	Set of safety goggles	7	One size	6.025-488.0	
		Overgoggles	8	One size	6.025-489.0	
10						
100						
	1000					

THE KÄRCHER PROTECTIVE GLOVES RANGE



Kärcher protective gloves a firm grip on safety

Our hands are our most important tools - and are therefore especially worth protecting, ideally with Kärcher's protective gloves. The high-quality gloves with attractive Kärcher design have the optimal ergonomic fit, maximum comfort and maximum freedom of movement. In short: the ideal solution for a firm grip.





Optimal grip and high level of comfort

- Breathable nitrile coating on gloves provides a good moisture barrier
- Very good sense of touch, as well as good wet grip.

Oeko-Tex® Standard 100

Use of high-quality cotton for optimal wearing comfort and a pleasant feel.

Perfect all-rounder

- Excellent wear resistance, highly durable, good cut resistance and excellent dry-wet grip.
- A real all-rounder for applications of all kinds.

Comfortable and safe

■ Excellent ergonomic fit, high wear acceptance and flexibility, as well as good water vapour absorption.

Accessories	Designation	Fig.	Size	Order no.	Price
Protective gloves					
	Protective gloves, short cuff	1	8	6.025-490.0	
	Protective gloves, short cuff	1	9	6.025-491.0	
	Protective gloves, short cuff	1	10	6.025-492.0	
	Drotostiva glavas lang suff		9	6.025-493.0	
	Protective gloves, long cuff			0.025-493.0	



EQUIPMENT AND TECHNOLOGY THAT LET YOU ACHIEVE MORE OUTDOORS

Our 50-volt battery platform gives you everything you want as a professional: extremely high performance combined with efficient operation and ergonomic handling. And so that you really never reach your limits, you can enhance your equipment with high-performance power generators and our petrol-powered waste water pump.



Table of contents for outdoor power equipment

Battery-powered machines with 50-volt technology	Page	23
Leaf blowers	Page	23
Chainsaws	Page	24
Strimmers	Page	24
Hedge trimmers	Page	24
Petrol-powered power generators	Page	24
Petrol-powered waste water pump	Page	24
Accessories	Page	24



Zero-emission power: 50-volt technology

Our powerful 50-volt lithium-ion battery gives you full power, maximum energy efficiency and the greatest possible flexibility. And that's exactly what you need as a professional. Get all your work done without high noise levels and without emissions when working. Our 50-volt battery range has everything a user with high demands such as yourself could want: quiet vibration-free machines with very low operating and maintenance costs.

How to read the machine names:

Model

Example: LB 850 Bp

LB = Leaf Blower CS = Chainsaw

s = Chainsaw **s** = String Trimmer (strimmer)

HT = Hedge Trimmer

Bp = Battery pack

PGG = Power Generator Gasoline

WWP = Waste Water Pump

BATTERY-POWERED MACHINES WITH 50-VOLT TECHNOLOGY



One battery system, a thousand possibilities

The battery-powered leaf blower, strimmer, hedge trimmer and chainsaw from Kärcher are lightweight yet powerful. Thanks to the lithium-ion batteries and 50-volt technology, they offer numerous advantages over petrol-powered machines, making work easier and protecting both the operator and the environment.











1 Batteries in different performance classes

Batteries in different performance classes are available for our machines to The lithium-ion batteries with 50-volt technology are compatible with suit individual requirements. Thanks to 50-volt technology, they charge up to 50 per cent faster than standard lithium-ion batteries.

3 Suitable for all machines

all battery-powered machines from Kärcher. They are quick and easy to replace, making them ready to use when required.

2 Battery backpack Bp 2400 Adv

power for long periods of uninterrupted use. The battery normally lasts a whole day without needing changing (adapter and carrying frame must be ordered separately.)

4 Battery charge display

With a power reserve of 1,169 Wh, the battery backpack delivers sufficient Different coloured LEDs on the 50-volt batteries enable the operator to see the current charge level at a glance.

Bp 2400 Adv Bp 800 Adv ■ Highest energy density on the market ■ The adapter and carrying frame must be ordered ■ Suitable for all machines on the 50-volt platform Battery charge display Technical data Voltage 23.2 7.5 Capacity Energy 1160 375 Weight 9.8 2.87 240 60 Charging time 2.852-204.0

		Bp 400 Adv	Bp 200 Adv
		Suitable for all machines on the 50-volt platformBattery charge display	Suitable for all machines on the 50-volt platformBattery charge display
Technical data			
Voltage	V	50	50
Capacity	Ah	4	2
Energy	Wh	200	100
Weight	kg	2.21	1.26
Charging time	min	30	25
Order no.		2.852-184.0	2.852-183.0

Battery charger: BC Adv

■ Suitable for all 50-volt lithium-ion batteries

Technical data		
Voltage	V	220-240
Frequency	Hz	50
Power	W	550
Weight	kg	1.9
Order no.		2.852-182.0

LEAF BLOWERS

Better together: leaf blowers and municipal vehicles



Tireless, economical, environmentally friendly and very, very quiet: our battery-powered alternative to petrol leaf blowers is an ideal addition to Kärcher municipal vehicles in the day-to-day removal of leaves, refuse and dirt - particularly in hard-to-reach places and also at night after events. Batteries and battery chargers must be ordered separately.









- 1 Infinitely adjustable speed
- For convenient and needs-based adjustment of the blower speed.
- 3 Battery fully compatible with all machines on the 50 V platform
- Maximum flexibility. The compatible battery can be quickly switched to other machines.

- 2 Turbo button for short-term performance increase
- Maximum blower speed for the removal of especially sticky leaves and Environmentally compatible and user-friendly. No petrol fumes when stubborn dirt residues.
- 4 No emissions of harmful substances or CO₂

TECHNICAL DATA AND EQUIPMENT

LB 850 Bp

■ "Turbo button" for brief performance increase

Infinitely variable speed control

V	50
dB(A)	95
dB(A)	82
m/s²	1.07
m/s	40
m³/h	816
min	max. 60
min	max. 120
min	max. 240
min	max. 700
kg	2.3
mm	905 × 165 × 270
	1.442-110.0
	dB(A) dB(A) m/s² m/s m/s m³/h min min min kg

Accessories			
Product name	Order no.	Description	Price
Safety goggles set	6.025-488.0	Safety goggles with UV protection and clear, high-contrast, scratch-resistant and anti-fog lenses that are easy to replace. Comfortable fit thanks to adjustable side piece with soft ends.	

CHAINSAW

Zero-emission power - every day.



Battery-powered, no fumes, hardly any vibrations, yet a fully fledged chainsaw: the CS 330 Bp with innovative 50 V technology impresses with easy handling and high performance. It is so quiet that it can even be used in noise-sensitive areas at any time. Batteries and battery chargers must be ordered separately.









1 User-friendly, automatic chain lubrication

- Less maintenance required with optimal chain lubrication and longer service life.
- 3 Battery fully compatible with all machines on the 50 V platform
- Maximum flexibility. The compatible battery can be quickly transferred to other machines if required.

2 Maximum safety thanks to electric chain brake

- For maximum safety, the chain immediately stops on contact with the Environmentally compatible and user-friendly. No petrol fumes when front hand guard.
- 4 No emissions of harmful substances or CO₂

TECHNICAL DATA AND EQUIPMENT

CS 330 Bp

- Electric chain brake
- Automatic chain lubrication

Technical data		
Voltage	V	50
Guaranteed sound power level	dB(A)	99
Sound pressure level (ΔK = 2.5 dB(A))	dB(A)	86
Guide bar length	cm	35
Chain pitch		3/8"
Chain speed	m/s	12
Run time with Bp 200 Adv	cuts	max. 108
Run time with Bp 400 Adv	cuts	max. 216
Run time with Bp 800 Adv	cuts	max. 405
Runtime with Bp 2400 Adv		-
Weight	kg	3.8
Dimensions (L × W × H)	mm	780 × 240 × 247
Order no.		1.442-111.0
Price		

TDOOR POWER

STRIMMER



Precise working. Even in tight spaces

Mowing in inaccessible, sloping or tight spaces and corners? With our battery-powered ST 400 Bp strimmer, landscape maintenance could not be easier. Wherever you go, it goes. Thanks to its lightweight design, it makes work easier in any situation – the perfect addition to Kärcher municipal vehicles in daily use. Batteries and battery chargers must be ordered separately.









- 1 Ergonomic two-handed grip
- Work comfortably for long periods without getting tired.
- 3 Battery fully compatible with all machines on the 50 V platform
- Maximum flexibility. The compatible battery can be quickly switched to other machines.

- 2 Comfortable double-shoulder carrying strap
- Work more easily for long periods.

- 4 No emissions of harmful substances or CO₂
- Environmentally compatible and user-friendly. No petrol fumes when working

TECHNICAL DATA AND EQUIPMENT

ST 400 Bp

- Comfortable double-shoulder carrying strap
- Ergonomic two-handle handlebar

Technical data		
Voltage	V	50
Guaranteed sound power level	dB(A)	95
Sound pressure level (ΔK = 2.5 dB(A))	dB(A)	82
Cutter		Line head
Line diameter	mm	2.4
Cutting circle diameter	mm	380
Run time with Bp 200 Adv	min	max. 20
Run time with Bp 400 Adv	min	max. 40
Run time with Bp 800 Adv	min	max. 80
Runtime with Bp 2400 Adv	min	max. 230
Weight	kg	3.9
Dimensions (L × W × H)	mm	1833 × 591 × 609
Order no.		1.442-112.0
Price		

TDOOR POWER

HEDGE TRIMMER

Precision cutting. Virtually no noise.



This robust, powerful, professional cordless hedge trimmer can do anything a petrol-powered trimmer can do, and even a little more thanks to its incredibly low operating noise. Its blades are sharpened on both sides, guaranteeing a clean cut. And with a choice of different cutting speeds, you can adapt it perfectly to the material you are cutting.









1 Two cutting speeds can be selected

■ Depending on the task, 2 cutting speeds are available for an optimal cutting pattern.

3 Integrated, effective cutting protection

The bolted cutting protection prevents damage, thus increasing both grip protection and safety.

2 Blades sharpened on both sides

Blades sharpened on both sides (650 mm) for branches up to 33 mm diameter ensure a fine cutting pattern.

4 Battery compatible with all machines in the 50 V platform

The compatible battery can be quickly transferred to other devices if need be - and vice versa.

TECHNICAL DATA AND EQUIPMENT

HT 615 Bp

Integrated cut protection

2-stage control of the cutting speed

Technical data		
Voltage	V	50
Guaranteed sound power level	dB(A)	92
Sound pressure level (ΔK = 2.5 dB(A))	dB(A)	79
Vibration value of front handle (K=1.5 m/s²)		
Cutting length	mm	650
Stroke number/cutter speed	Cuts/min	2800-3200
Run time with Bp 200 Adv	min	max. 35
Run time with Bp 400 Adv	min	max. 70
Run time with Bp 800 Adv	min	max. 140
Runtime with Bp 2400 Adv	min	max. 400
Weight	kg	3.8
Dimensions (L × W × H)	mm	1144 × 221 × 195
Order no.		1.442-113.0
Price		

247

PETROL-POWERED POWER GENERATORS

Power. Any time. Anywhere

On construction sites, in agriculture or in municipalities: our powerful synchronous generators provide independent power supply at all times and in all locations. Reliable petrol engines enable constant power, advanced safety features provide reliable operation, and flat-free wheels enable easy transportation of the user-friendly machine.











1 Excellent user-friendliness

- Folding push handle and flat-free tyres ensure easy transportation.
- Electro start function for conveniently starting the petrol engine.

Ultimate reliability and safety

- Powerful four-stroke engines ensure constant power.
- Functions such as overload protection, low oil trip and socket protection safeguard users and the machine.

		PGG 8/3	PGG 6/1	PGG 3/1
		 Supplies a reliable three-phase current (400 V) Convenient electro start function with key switch Robust cage frame 	 Convenient electro start function with key switch Folding push handle and flat-free tyres Robust cage frame 	 Convenient electro start function with key switch Folding push handle and flat-free tyres Robust cage frame
Technical data				
Rated performance	kW	7	5	2.8
Max. performance	kW	7.5	5.5	3
Voltage (number of phases)	V	400 / 230 (3/1)	230 (1)	230 (1)
Motor	cm³ / type	440 / petrol	390 / petrol	208 / petrol
Motor rating	kW / hp	11.7 / 16	9.5 / 13	5.1 / 7
Tank capacity	I	25	25	15
Weight	kg	89	85	50
Dimensions (L × W × H)	mm	750 × 700 × 665	750 × 700 × 665	605 × 430 × 546
Equipment				
Operating state display		•	•	•
DC output (12 V)				
Protection class IP 23			•	•
Low oil and overload protection				
Fuel gauge		•	•	•
Single phase socket type F (Schuko)			•	•
Three-phase socket CEE (16 A)		•	-	-
Order no.		1.042-209.0	1.042-208.0	1.042-207.0
Price				

[■] Included in the scope of supply.

PETROL-POWERED WASTE WATER PUMP

The multi-talented waste water pump

Our waste water pump is the right choice anywhere where large water volumes, including a wide range of particles, need to be pumped out, such as out of basements or excavation pits that have filled up with water. Thanks to the mobile petrol engine - which does not require a power supply and is also suitable for the toughest applications - the pump can also be used to provide no water supply in the agricultural sector.









1 For tough applications

- A robust tubular steel frame reliably protects the machine against damage.
- Even large particles of up to 30 mm can be pumped without any problems.

2 Maintenance-friendly

- Easy access to all maintenance-related components.
- The extensive service concept ensures continuous readiness for operation.

WWP 45

- Recoil start with manual choke
- Compact dimensions and low weight
- Robust cage frame

Technical data		
Output capacity	m³/h	45
Max. suction head	m	7
Max. delivery head	m	25
Max. particle size	mm	30
Motor	cm³ / type	196 / petrol
Motor rating	kW / hp	4.8/6.5
Tank capacity	I	3.6
Weight	kg	36
Dimensions (L × W × H)	mm	580 × 440 × 450

Equipment	
Manual choke	1
Oil level sight glass	I
Suction basket	I .
2 × hose coupling	I
3 × hose clamp	1
Order no.	1.042-210.0
Price	

■ Included in the scope of supply.

OUR MACHINES GROW WITH YOUR TASKS.



Even more efficient, safe and environmentally friendly: we offer a wide range of accessories for the 50 V platform from Kärcher - from protective gear to consumables. Precisely adapted to the specific machine, as well as quick and easy to use.















	Order no.	Voltage	Frequency	Power	Price Description		LB 850 Bp CS 330 Bp ST 400 Bp
Machine accessories	Oraci no.	Voltage	Trequency	rowci	Price Description		- 5 0, -
Double-shoulder carrying strap	1 6.990-516.0				Ergonomic double-shoulder carrying strap for lon work with the battery-powered leaf blowers from Comfortable and less strain for the user.		
Carrying strap combined	2 6.990-548.0				For battery-powered leaf blowers and strimmers range: ergonomic double-shoulder carrying strap strain on users during long work activities.		
Chainsaw chain	3 6.990-467.0				Replacement saw chain 90PX052X from our well Oregon. With a saw chain pitch of 3/8", it is ideal battery-powered chain saw CS 330 Bp.	·	
Organic chainsaw oil	4 6.990-531.0				Biodegradable saw chain oil reduces the wear of on the saw chain of the battery-powered chainsa Can be used at ambient temperatures of –30 °C.		
Carrying rack Bp 2400 Adv	5 2.852-366.0				Ergonomic carrying frame for the comfortable ca Bp 2400 Adv battery-powered backpack on the b	, ,	
Adapter Bp 2400 Adv	6 2.852-365.0				Adapter for connecting the respective machine to Bp 2400 Adv battery-powered backpack.	our 6	
Trimmer cord	7 6.990-554.0				For use with strimmers from our 50 V range: coil line, twisted, 2.4 mm thick, 15 m long.	vith mowing 7	
Thread spool	8 6.990-547.0				Complete mowing head for strimmer. Two-thread adjustment by pointing to the ground.	ine coil with 8	
Safety goggles set	9 6.025-488.0				Safety goggles with UV protection and clear, high scratch-resistant and anti-fog lenses that are easy Comfortable fit thanks to adjustable side piece w	to replace.	
Suction hose (5 m)	10 2.645-340.0				5 m long suction hose for use with our WWP 45 w pump. The existing suction basket (coarse filter) ca		
Drain hose (10 m)	11 2.645-341.0				10 m long drain hose for draining the dirty water use with our WWP 45 waste water pump.	Suitable for 11	
Battery charger			-				
Battery charger BC Adv, 220-240V	12 2.852-182.0	220-240 \	/ 50 Hz	550 W	Thanks to the innovative 50 V technology from K charger BC Adv charges the batteries of Kärcher Solutions machines up to 50% faster than standar available on the market. The charging progress is charge status display on the compact and lightwe	ark & City chargers ndicated by the	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

FULL SUCTION POWER AHEAD

Our range of vacuum cleaners offers you an impressive variety of machines for use in industry, the automotive sector, building cleaning or trade - Kärcher offers the perfect solution for any application. Whether you need a dry vacuum cleaner or wet and dry vacuum cleaner - all of our machines offer impressively high quality and durability, as well as innovative filter engineering and exceptional ease of use.




Table of contents: Vacuum cleaners

Window/surface vacuum cleaners	Page	252
Wet and dry vacuum cleaners	Page	256
Wet and dry vacuum cleaner accessories	Page	300
Industrial vacuums	Page	328
Industrial vacuum accessories	Page	356
Dry vacuum cleaners	Page	378
Dry vacuum cleaner accessories	Page	408









1 Powerful, versatile and mobile

In industry, when cleaning the car or for cleaning buildings: strong suction power with maximum portability is in demand everywhere. Kärcher wet and dry vacuum cleaners meet these requirements with ease. With the innovative Tact filter cleaning system, Kärcher wet and dry vacuum cleaners master even the toughest building site applications. Special vacuums - for example for potentially explosive atmospheres or fire-fighting complete the versatile Kärcher range of wet and dry vacuum cleaners.

2 Profile solutions for production

People working in industry and manufacturing encounter various different oils, lubricants, granulates, metal shavings or wood dust - Kärcher industrial vacuum cleaner application to deliver flawless cleaning results. vacuums offer the right machine for every cleaning task.

3 Your partner for professional cleanliness

Contract cleaners and facility managers have the highest standards when it comes to power and handling for dry cleaning. Performance and discretion are equally important, especially for daytime cleaning during business hours and for spot cleaning in public areas. Machines must also be quick and easy to transport. Kärcher knows what's important in these specialised areas. The most convincing proof of this is reflected in the sophisticated design of our professional machines.

4 Sector-specific accessories

The range of Kärcher accessories is as diverse as the uses to which our types of stubborn dirt on a daily basis, meaning the demands they place on vacuum cleaners can be put. From individual connecting adapters to special cleaning machines are correspondingly high. Fine dust, coarse dirt, liquids, accessory kits - Kärcher offers the perfect machine configuration for every

YOUR COMPLETE SOLUTION FOR ALL SMOOTH SURFACES

Our Window Vac Professional WVP 10 is a lightweight window and surface vacuum cleaner for all types of smooth surfaces. Effortless, streak-free cleaning with this robust, professional handheld device: horizontal, vertical and even overhead. Perfect for cleaning windows, tiles, mirrors, wine cabinets, etc.



Contents of Window/Surface Vacuum Cleaner

Window/surface vacuum cleaner Accessories

Page 254

Page 255



Easier, more convenient, faster

Short charging times, high power and simple handling. Never before has it been so easy to clean smooth surfaces without leaving any streaks. Our new WVP 10 Adv fits comfortably in the hand, is easy to guide and effortlessly cleans right to the edge. And thanks to the spare battery you can also clean for longer at one time!

The WVP 10 Adv is supplied with 2 batteries, a quick charger, accessory kit, cleaning agent, spray bottle and microfibre cloth.

How to read the unit names:

Unit type	Model Equipment	
Example: WVP	10	Adv
WVP = Window Vac Professional		Adv = Advanced version

WVP 10 *EU

BATTERY-POWERED WINDOW/SURFACE VACUUM CLEANER



The cleaning solution for every type of smooth surface

With the window and surface vacuum cleaners from the WVP 10 range, you have a lightweight, battery-powered device which cleans windows, mirrors, tiles and all other types of smooth surfaces right to the edges without leaving any streaks. The WVP 10 Adv version with fast charge function and replacement battery makes it possible to work virtually without any interruptions. The cleaning agent and other utensils are included with the delivery.







3 Convenient cleaning of edges

manually adjustable spacer.



1 Lightweight, ergonomic and universal

- Comfortable handling and easy to operate.

- even overhead.
- Safe, pleasant handling thanks to rubber handle.

2 Removable, replaceable battery

- Allows external battery charging and, in conjunction with a spare battery, uninterrupted working.
- Charging state is displayed by 3 LEDs above the ON/OFF switch.

4 Large volume of dirty water tank

Reduces work interruptions thanks to frequent emptying, thus increasing productivity.

 $\hfill \blacksquare$ Streak-free cleaning results right up to the edges thanks to the

TECHNICAL DATA AND EQUIPMENT

WVP 10 Adv

		WVP 10 Auv	WVP 10 LO
		WVP 10 Adv with fast charge functionReplaceable batteryVirtually uninterrupted working	 Suitable for all smooth surfaces Excellent cleaning results with horizontal and vertical use Large suction tank
Technical data			
Wastewater tank	ml	200	200
Battery charging time	min	50	180
Working width of vacuum nozzle	mm	280	280
Working width of narrow suction nozzle	mm	170	-
Weight	kg	1	1
Dimensions (L × W × H)	mm	280 × 130 × 335	280 × 130 × 335
Equipment			
Battery			•
Spray bottle			•
Microfibre wiping cloth		1 ×	1 ×
microfibre wiping cloth outdoor		1 ×	-
Cleaning agent 0.5 I			•
Battery charger		-	-
Quick charger			-
2nd Battery		•	-
Narrow suction nozzle			1
Order no.		1.633-560.0	1.633-550.0
Price			

- 1								
	_	Included	in	tho	ccono	of	cunni	١.,

Accessories Product name	Order no.	Description	Pric
Nozzle 170 mm	9.013-535.3	170 mm wide, anthracite-coloured replacement nozzle for WVP window and surface vacuum cleaner.	
Nozzle 280 mm	9.013-530.3	Replacement nozzle, anthracite, 280 mm wide, for WVP window and surface vacuum cleaner.	
Squeegee blade, narrow, 170 mm	2.633-104.0	For the replacement of the squeegee blades of battery-powered window vacuum cleaners WV 50, WV 75, WV 2, WV 5 and WVP 10. For streak-free cleanliness on all smooth surfaces – without any dripping water.	
Squeegee blade, 280 mm	2.633-005.0	For the replacement of the squeegee blades of battery-powered window vacuum cleaners WV 50, WV 75, WV 2, WV 5 and WVP 10. For streak-free cleanliness on all smooth surfaces – without any dripping water.	
Spray Bottle, round, replacement	4.633-153.0	Replacement spray bottle for cleaning agents with 500 ml capacity. For use with WVP window and surface vacuum cleaner.	
WV indoor microfibre wiping cloths	2.633-130.0	The indoor microfibre wiping cloth with hook-and-loop fastener fastener for optimal dirt removal with the WV spray bottle on all smooth surfaces.	
WV outdoor microfibre wiping cloths	2.633-131.0	Ideal for exterior windows: the outdoor microfibre wiping cloth with hook-and-loop fastener fastener and an exceptionally large number of abrasive fibres. Including dirt scraper for stubborn dirt.	
Replacement battery	2.633-123.0	Replacement battery for the WV 5 and WVP 10 Window Vac, for uninterrupted cleaning.	
EU power supply	2.633-107.0	EU replacement power supply for charging the Kärcher window and surface vacuum cleaner.	
PS01 power supply unit	6.654-353.0	MX/JP/TW/KNA replacement power supply for charging the Kärcher window and surface vacuum cleaner.	
Window Vac Battery Charger	2.633-115.0	GB spare power supply unit for charging the Kärcher window vacuum cleaner.	
Replacement charging station WVP 10 Adv	2.633-041.0	Replacement quick-charging station for charging WVP battery 2.633-123.0. Charge time 50 minutes.	
GB replacement charging station WVP 10 Adv	2.633-056.0	Replacement quick-charging station for charging WVP battery 2.633-123.0. Special version for Great Britain. Charge time 50 minutes.	
JP replacement charging station WVP 10 Adv	2.633-055.0	Replacement quick-charging station for charging WVP battery 2.633-123.0. Special version for Japan. Charge time 50 minutes.	

Detergent Product name	Order no.	Description	Price
SanitPro Daily Cleaner CA 20 R eco!perform	6.295-685.0	Ready to use sanitary everyday cleaner. Gentle cleaning action, environmentally-friendly. Pack of 12 bottles including 2 spray heads. One spray head is sufficient for up to 40 applications.	
SurfacePro Surface Cleaner CA 30 R eco!perform	6.295-686.0	Ready-to-use surface cleaner for manual application. Dries quickly and streak-free. Pack of 12 bottles including 2 spray heads. Up to 40 applications per spray head.	
SurfacePro Glass Cleaner CA 40 R eco!perform	6.295-687.0	Ready-to-use glass cleaner – also suitable for plastic surfaces. Dries quickly and streak-free. Pack of 12 bottles including 2 spray heads. Up to 40 applications per spray head.	

PROFESSIONAL WET AND DRY VACUUM CLEANERS **FOR EVERY CLEANING TASK**

As a professional user, you know there's much more to a good wet and dry vacuum cleaner than suction power alone. The overall design - with all filters and control elements, ergonomics, stability and optimal accessories - is the deciding factor. For decades, we have been continuously setting new standards in this area with our innovative technologies - at an excellent price-performance ratio too.




Table of contents: Wet and dry vacuum cleaners

Tact² class	Page	264
Tact class	Page	270
Ap class	Page	276
Standard class	Page	284
NT Classic with two motors	Page	290
NT Classic with single motor	Page	292
Safety vacuum cleaners	Page	294
Special vacuums	Page	298
Accessories	Page	300



NT 50/1 Tact Te L

With its 50-litre container for interruption-free operation, an adjustable push handle, drain hose and many other smart details, the NT 50/1 Tact Te is both the largest machine in the new Tact range and the one with the most comprehensive equipment.

NT 40/1 Tact Te L

The new NT 40/1 Tact Te boasts outstanding suction power - even when it comes to large quantities of fine dust. Its large container capacity and very compact design are also impressive. outstanding power - whether in the workshop or For even easier handling, it can be fitted with a push handle if desired.

NT 30/1 Tact Te L

The NT 30/1 Tact Te is the fine dust expert among wet and dry vacuum cleaners and is perfect for use wherever tradesmen want for tough jobs on construction sites. This makes the robust, durable and powerful machine the tradesman's favourite.

How to read the machine names:


nacilile type	Container Capacity	Turbines	Filtration technology	Type and equipm	ent
xample: NT	75	2	Tact ²	Me Tc	
IT = Wet and dry vacuum cleaner	In machine names with a combination of numbers, the first number indicates the container capacity (in litres).	the second number indicates	Tact ² : Dual automatic filter cleaning, machine with flat pleated filter Tact: Automatic filter cleaning, machine with flat pleated filter Ap: Semi-automatic filter cleaning, machine with flat	Without designation Classic Adv Me Tc Ec Te	= Standard equipment = Machine with basic equipment = Advanced, machine with additional equipment = Stainless steel container = Tilting chassis = Brushless turbine = Automatic power outlet
			pleated filter Without suffix: Machine with cartridge filter	L M	Certified for dust class L dusts that pose a low risk to health Certified for dust class M
				н	dusts that pose a moderate risk to health = Certified for dust class H dusts that pose a high risk to health
				Z22	= Explosion-proof vacuum cleaner for Zone 22
				Mwf	= Fire service vacuum cleaner with PRCD-K circuit breaker
				Есо К	 Water vacuum with integrated waste water pump
				Bs	= Vacuum cleaner for bakeries

Tact class NT 75/2 Tact² Me Tc Adv ■ 1.667-316.0 254 / 25.4 NT 75/2 Tact² Me Tc 265 254 / 25.4 NT 75/2 Tact² Me 254 / 25.4 267 NT 65/2 Tact² Tc 1.667-287.0 65 254 / 25.4 ■ 265 2 × 74 - II NT 65/2 Tact2 1.667-286.0 65 2 × 74 254 / 25.4 ■ 267 NT 55/2 Tact2 Me I 1 667-237 0 2 × 74 254 / 25 4 265 NT 50/1 Tact Te L 1.148-411.0 50 74 254 / 25.4 270 NT 45/1 Tact Te Ec 1.145-826.0 45 63 244 / 24.4 271 NT 40/1 Tact Te L 1.148-311.0 74 254 / 25.4 ■ 272 NT 30/1 Tact Te I NT 30/1 Tact L 1.148-201.0 30 74 254 / 25.4 Ap class 1.667-292.0 NT 75/2 Ap Me To 2 × 74 254 / 25.4 NT 65/2 Ap 1.667-291.0 65 2 × 74 254 / 25.4 277 NT 40/1 Ap L 1.148-321.0 40 74 254 / 25.4 279 NT 30/1 Ap Te L 1.148-231.0 74 254 / 25.4 279 NT 30/1 Ap L 1.148-221.0 NT 22/1 Ap Te L 1.378-610.0 22 71 255 / 25.5 283 - 1 NT 22/1 Ap L 1.378-600.0 255 / 25.5 283 NT 20/1 Ap Te 1.378-510.0 281 74 254 / 25.4 NT 20/1 An 1 378-500 0 74 254 / 25 4 281 Standard class NT 70/3 Me To 1.667-274.0 3 × 74 254 / 25.4 285 NT 70/2 Me To 1.667-272.0 254 / 25.4 285 285 NT 70/3 Tc 1.667-273.0 3 × 74 254 / 25.4 NT 70/2 Tc 285 1.667-271.0 2×74 254 / 25.4 NT 70/2 Adv 287 1.667-278.0 70 2 × 74 254 / 25.4 II. NT 70/2 Me 1.667-275.0 2×74 254 / 25.4 287 NT 70/3 1.667-270.0 287 3 × 74 254 / 25.4 NT 70/2 1.667-269.0 70 2 × 74 254 / 25.4 287 NT 70/1 1 667-268 0 74 287 NT 48/1 Te 1.428-625.0 289 200 / 20 1.428-620.0 NT 27/1 Me Adv 1.428-114.0 289 67 200 / 20 Ш NT 27/1 Me 1.428-100.0 67 200 / 20 Ш 289 NT 27/1 Adv 1 428-520 0 67 200 / 20 - 11 289 NT 27/1 1 428-500 0 27 67 200 / 20 - 11 289 Classic range NT 90/2 Me Classic 1.667-700.0 225 / 22.5 291 NT 70/2 Me Classic NT 50/2 Me Classic 1.667-030.0 50 225 / 22.5 291 2 × 53 ll ll NT 50/1 Me Classic 1.667-010.0 50 53 225 / 22.5 291 NT 38/1 Me Classic 1.428-538.0 59 293 38 227 / 22.7 II. NT 30/1 Me Classic 1.428-568.0 30 59 227 / 22.7 293 NT 20/1 Me Classic 1.428-548.0 59 227 / 22.7 293 Special vacuums NT 80/1 B1 M S 1.667-267.0 235 / 23.5 NT 75/1 Me Ec H Z22 1.667-239.0 220 / 22 295 NT 75/1 Tact Me Te H 74 254 / 25.4 ■ 297 NT 50/1 Tact Te M 1.148-435.0 50 74 254 / 25.4 - 1 NT 30/1 Tact Te M 1.148-235.0 30 74 254 / 25.4 ■ 297 NT 50/1 Tact Te H 1 148-437 0 74 254 / 25.4 296 NT 30/1 Tact Te H 1.148-237.0 30 74 254 / 25.4 296 NT 611 Mwf 1.146-601.0 57 298 235 / 23.5 NT 611 Eco K 298 1.146-209.0 235 / 23.5 NT 35/1 Tact Bs 1.184-700.0 61 230 / 23 ■ 299

■ NEW ■ Included in the scope of supply. ◆ Antistatic preparation. ▲ Complete antistatic system.

ELIMINATING DUST PROTECTS HEALTH

Every form of dust can be a health hazard. The common goal of legislators, trade associations and employers is to avoid the formation of dust before it occurs or to bind dust directly, quickly and as completely as possible. Brushes, dustpans and high-pressure guns are entirely unsuitable for this purpose. Powerful safety vacuum cleaners that are connected either directly to dust generating tools or used in conjunction with suitable accessories for picking up dust from floors and equipment offer the ideal solution.



1 Not all dust is the same

Dust is classified according to size. Coarse dust has a particle size of more than 10 μ m (1 micrometre is a thousandth of a millimetre) and is generally reliably retained by nose hair and mucous membranes. Small to ultrafine dust particles (also known as fine dust), by contrast, can penetrate deep into the lungs via the windpipe and bronchial tubes. This respirable dust poses the greatest health risks.

2 Every type of dust can pose a health hazard

Fine dust is always dangerous to health. However, every type of dust – even coarse dust – can cause respiratory disease after prolonged exposure due to the harmful substances it contains. Mineral mixed dust from sand, lime, gypsum, cement or concrete, which occurs regularly in the building industry, almost always contains quartz fine dust, which can cause silicosis and lung cancer.

The effects of dust on health depend on the type of dust, as well as the particle size, duration of exposure and the intensity of dust impact. Inhaling large amounts of dust over a short period of time is particularly dangerous. And because dust is widely distributed, protection against dust concerns us all

3 Avoid dust, Before it forms


The best protection against dust is to prevent it from forming in the first place. Kärcher safety vacuum cleaners can easily be connected to all standard power tools with a special tool adapter. This form of direct suction ensures a virtually dust-free environment. Dust on floors and machines can be removed efficiently and reliably with the accessories supplied as standard. And you can forget brushes, dustpans and compressed-air guns – these only kick the dust up again. Using approved safety vacuum cleaners is the only way to reliably protect the health of users and others in the surrounding area.

WET AND DRY VACUUM CLEANER: POWERFUL AND VERSATILE

The Kärcher range of wet and dry vacuum cleaners is the result of decades of experience with operators throughout the world. Whether for tradesmen, building service contractors or vehicle finishers – this wide selection includes wet and dry vacuum cleaners specially tailored to suit individual applications.

	NT 65/2 Tact ² to NT 75/2 Tact ²	NT 30/1 Tact to NT 50/1 Tact	NT 65/2 Ap to NT 75/2 Ap	NT 20/1 Ap to NT 40/1 Ap	NT 70/1 to NT 70/3	NT 27/1 to NT 48/1
	Tact	class	Ар	class	Standa	rd class
Liquids						
Small quantities						•
Large quantities					•	
Coarse dirt						
Small quantities				•		
Large quantities			•			
Fine dust						
Small quantities			•	•		
Large quantities		•				
Very large quantities						







The perfect vacuum cleaner for every application

Kärcher wet and dry vacuum cleaners are designed for all wet and dry applications. With all-round and specialist machines.

- 1 Tact vacuum cleaners: developed to handle large quantities of fine dust for working with and without power tools.
- 2 Ap vacuum cleaners: powerful all-rounders for liquid and moist dirt to medium-fine dust.
- 3 Standard vacuum cleaners: designed for picking up large quantities of liquids and coarse dirt.







3 EN 60335-2-69/IEC 60335-2-69

Dust class	Max. permeation degree	Suitable for	Application
LEADL	≤ 1.0%	■ Dusts with MAC values > 1 mg/m³	■ Lime dusts ■ Gypsum dusts
M A COM	< 0.1%	■ Dusts with MAC values ≥ 0.1 mg/m³ ■ Wood dusts up to 1200 W/50 I	 Wood dusts (beech, oak) Paint dust particles Ceramic dusts Dusts from plastics
н (< 0.005%	■ Dusts with MAC values < 0.1 mg/m³ ■ Carcinogenic dusts (Section 35 GeStoffV [German Ordinance on Hazardous Substances]) ■ Pathogenic dusts	 Carcinogenic dusts (lead, coal, cobalt, nickel, tar, copper, cadmium, etc.) Mould, bacteria Germs Formaldehyde
Special requirement: asbestos*	< 0.005%	■ Dusts containing asbestos	Asbestos dust from night storage heaters or firewalls
Explosive dusts (ATEX zone 22)	Such as dust class L, M or H with special requirements	■ Dusts in dust explosion classes in Zone 22	■ Paper dusts ■ Flour dusts

^{*} Obligatory for Germany in accordance with TRGS 519. MAC = maximum allowable concentration.

1 Tact - the automatic filter cleaning system

Our professional wet and dry vacuum cleaners with the patented Tact system allow uninterrupted operation, even with large quantities of fine dust. The filter automatically cleans itself with targeted, powerful blasts of air. The procedure is triggered automatically whilst maintaining constant high suction power. Other benefits include low maintenance costs and a long filter service life.

Dust: Category A mineral dust.

Temperature: Room temperature.

Accessories: Main filter and hoses included in the scope of supply. Competitor machines: Comparable container size and equipment.

Kärcher 180* Competitor A 19* Competitor B 10*

3 Dust classes

L class: Dusts in dust class L are only slightly hazardous. An L filter cannot allow more than 1 per cent of the test dust to pass through. All Kärcher flat pleated filters easily comply with this requirement - they are all certified for dust class M. The legal maximum allowable concentration of L dust must not exceed 1 mg/m³. There are no special precautions for the disposal of L

M class: Dusts in dust class M are hazardous. The maximum permeation 2 Filter service life when vacuuming fine dust with the NT 30/1 Tact Te L degree of a tested M vacuum cleaner is less than 0.1 per cent. The legal maximum allowable concentration of M dust must not exceed 0.1 mg/m³. M dust must be disposed of with minimal dust spillage.

> H class: Dusts in dust class H are highly hazardous. The maximum permeation degree of a tested H vacuum cleaner must be less than 0.005 per cent. The legal maximum allowable concentration of H dust is less than 0.1 mg/ m³. Due to the high risk posed by these carcinogenic and pathogenic dusts, dust must not be able to escape during disposal.

Order no.	Machine designation	Suitable for dust class	Recommended for fine dust
1.667-316.0	NT 75/2 Tact² Me Tc Adv		Very large quantities
1.667-289.0	NT 75/2 Tact² Me Tc		
1.667-288.0	NT 75/2 Tact² Me		
1.667-287.0	NT 65/2 Tact² Tc		
1.667-286.0	NT 65/2 Tact ²		
1.667-237.0	NT 55/2 Tact ² Me		
1.667-294.0	NT 75/1 Tact Me Te H		Large quantities
1.148-437.0	NT 50/1 Tact Te H	AMERICAN Dissess load a similar association/growth 2 r Ordering. Including all others for containing frequency personnel agreement accounts, in paging personnel and includent personnel agreement accounts, in paging personnel and includent personnel agreement accounts. The paging personnel accounts are accounts as a personnel account personnel accounts and account personnel accounts are accounted as a personnel account personnel accounts and account personnel accounts are accounted as a personnel account person	
1.148-237.0	NT 30/1 Tact Te H	o futos de aj municipal proprié voj.	
1.148-435.0	NT 50/1 Tact Te M		Large quantities
1.148-235.0	NT 30/1 Tact Te M	MMAIM	3.4.
1.148-411.0	NT 50/1 Tact Te L		Large quantities
1.148-311.0	NT 40/1 Tact Te L		
1.148-211.0	NT 30/1 Tact Te L		
1.148-201.0	NT 30/1 Tact L		
1.667-292.0	NT 75/2 Ap Me Tc		Small to medium quantities
1.667-291.0	NT 65/2 Ap	LMATIL	
1.148-321.0	NT 40/1 Ap L		
1.148-231.0	NT 30/1 Ap Te L		
1.148-221.0	NT 30/1 Ap L		
1.378-610.0	NT 22/1 Ap Te L		
1.378-600.0	NT 22/1 Ap L		
1.378-510.0	NT 20/1 Ap Te		
1.378-500.0	NT 20/1 Ap		
		1	
1.667-267.0	NT 80/1 B1 M S	+ explosive dusts	Medium quantities
1.667-266.0	NT 80/1 B1 M	+ explosive dusts	Medium quantities
1.667-239.0	NT 75/1 Me Ec H Z22	+ explosive dusts	Medium quantities

^{*} Weights in kg, maximum quantity of dust that can be vacuumed until the main filter requires manual cleaning or changing.

265

Tact² CLASS



Professional from head to toe

High mobility and power, stamina, robustness and a wide range of practical equipment features make Kärcher vacuum cleaners with Tact² sought-after specialists and all-rounders. The models with tilting chassis offer advantages, particularly for industrial applications, in the disposal of liquids and coarse dirt.











- 1 Tilting chassis with container lock
- The container is always securely attached to the chassis.
- 3 Suction tubes and floor nozzles can be stored in any direction in the accessory holders
- For easy access from all sides.
- \blacksquare Ample storage for a 4 m hose and rubber power cable (10 m)

- 2 Drain hose for emptying liquids.
- Cover remains tightly closed until the contents are drained.
- 4 Easy in, easy out with tilting chassis
- $\hfill \blacksquare$ Simply tilt back the container and empty into the drain.
- High stability for easy emptying.

TECHNICAL DATA AND EQUIPMENT

		NT 75/2 Tact ² Me Tc Adv	NT 75/2 Tact ² Me Tc	NT 65/2 Tact ² Tc
		 Automatic Filter Cleaning System Tact² Push handle and drain hose Wide nozzle 	 Automatic Filter Cleaning System Tact² Push handle and drain hose Moisture-proof PES filter 	 Automatic Filter Cleaning System Tact² Accessory/suction hose storage Moisture-proof PES filter
Technical data				
Air flow rate	I/s	2 × 74	2 × 74	2 × 74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4	254 / 25.4
Container capacity	1	75	75	65
Max. rated input power	W	max. 2760	max. 2760	max. 2760
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 40	ID 40	ID 40
Cable length	m	30	10	10
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	73	73	73
Weight	kg	28.6	27.5	26.5
Dimensions (L × W × H)	mm	670 × 560 × 930	670 × 560 × 930	670 × 560 × 915
Equipment				
Suction hose	m	4 / with bend	4 / with bend	4 / with bend
Suction tube, metal 2 × 0.5 m			•	
Filter bag		-	Paper	Paper
Wet and dry floor nozzle	mm	360	360	360
Crevice nozzle			•	•
Stainless steel container				-
Flat pleated filter		PES	PES	PES
Order no.		1.667-316.0	1.667-289.0	1.667-287.0
Price				

■ Included in the scope of supply.

NT 55/2 Tact² Me I

- Mobile stainless steel container
- Set-down mechanis
- Automatic Filter Cleaning System Tact²

Technical data		
Air flow rate	I/s	2 × 74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	1	55
Max. rated input power	W	2760
Voltage	V	220-240
Standard nominal width		ID 40
Cable length	m	10
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	73
Weight	kg	44.8
Dimensions (L × W × H)	mm	710 × 570 × 1070

Equipment		
Suction hose	m	4 / with bend
Suction tube, metal 2 × 0.5 m		
Filter bag		-
Wet and dry floor nozzle	mm	360
Crevice nozzle		I
Stainless steel container		
Flat pleated filter		Paper
Order no.		1.667-237.0
Price		

■ Included in the scope of supply.

Tact² CLASS




Constant high suction power even with large dust quantities

The Tact² machines have a wealth of standard features for picking up large quantities of fine dust as well as coarse dirt: the unique Tact² is designed for long periods of uninterrupted use with constant high suction power. It comes with a complete anti-static package and 4 m suction hose. Designed for cleaning tasks otherwise reserved for larger and heavier vacuum cleaners.











1 Easy to transport

Adjustable push handle and large wheels make transport easy even on

The flat pleated filter can be removed from the clean side; it is divided uneven surfaces.

3 Automatic Filter Cleaning System Tact²

- into two halves, which are cleaned alternately by targeted blasts of air.
- Fine dusts cannot block the filter. A constant high air flow is main-

2 Intelligent accessory storage

For example, the floor nozzle can be quickly fixed any way round.

4 Secure and close to hand

■ Tools can be stored in the on-board practical storage area, including small parts and bottles.

TECHNICAL DATA AND EQUIPMENT

Paper 1.667-288.0

		NT 75/2 Tact ² Me	NT 65/2 Tact ²
		 Automatic Filter Cleaning System Tact² Antistatic preparation On-board storage on the casing head 	 Automatic Filter Cleaning System Tact² Antistatic preparation Adjustable push handle
Technical data			
Air flow rate	I/s	2 × 74	2 × 74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4
Container capacity	I	75	65
Max. rated input power	W	max. 2760	max. 2760
Voltage	V	220-240	220-240
Standard nominal width		ID 40	ID 40
Cable length	m	10	10
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	73	73
Weight	kg	27.5	24.5
Dimensions (L × W × H)	mm	630 × 545 × 920	575 × 490 × 880
Equipment			
Suction hose	m	4 / with bend	4 / electrically conductive
Suction tube, metal 2 × 0.5 m			•
Filter bag		Paper	Paper
Wet and dry floor nozzle	mm	360	360

■ Included in the scope of supply.

Crevice nozzle

Flat pleated filter

Order no.

Accessories			
Product name	Order no.	Description	Price
Flat pleated filter, paper	6.907-276.0	Paper, approved for dust class M.	
Flat pleated filter, PES	6.907-277.0	Polyester fleece, rot-proof, dust class M.	
Multi-purpose nozzle, wet/dry	6.903-018.0	Aluminium with height-adjustable rollers, brush strips (6.903-064.0) and squeegees (6.903-081.0, oil-resistant).	
Suction hose	6.906-546.0	With bayonet and clip connection, electrically conductive, C 40.	
Bend, plastic, electrically conductive	5.032-427.0	Plastic, with C 40 clip system, electrically conductive.	
Suction tube	6.902-081.0	For use in wet or damp environments or for wet vacuuming.	

1.667-286.0


THE NEW Tact CLASS: THE NEXT GENERATION OF FINE DUST VACUUM CLEANERS

With the new Tact range, we've thought of everything that's important to professional users: outstanding suction power, simple and comfortable operation, as well as durability and longevity. Our tried-and-tested Tact filter cleaning system is now even quieter and more efficient. And when it comes to equipment and accessories, we have done everything to ensure that your work is faster, easier and more convenient.













1 Overview of machine features

- 1 Central rotary switch for adjusting filter cleaning as required.
- 2 Suction hose connection in the machine head for a greater net volume and easy emptying.
- **3** Robust container with bumper and handhold for a long service life and convenient handling.
- 4 Case storage and attachment solution for toolboxes.
- **5** Flexible hose and power cable storage for secure attachment of different hoses.
- **6** Side storage of crevice nozzle and special tool adapter to ensure nothing is lost.
- **7** Large and robust metal castors for optimal manoeuvrability, even for tough jobs on construction sites.

2 Overview of accessory features

- **1** Special tool adapter with air-flow regulator and rubber attachment for optimum compatibility with power tools.
- **2** Wide floor nozzle with quick-change inserts for wet and dry applications.
- **3** Ergonomic bend with soft grip for comfortable working.
- 4 Improved clip system for easy switching, for example from bend to tool adapter.
- **5** Dirt-repellent bayonet fastener for easily detaching the hose from the machine.

Tact CLASS



The biggest of its kind

Even our most demanding customers in industry and construction will be impressed by NT 50/1 Tact Te L the wet and dry vacuum cleaner NT 50/1 Tact Te L. Powerful and reliable, it also vacuums very large quantities of fine dust, coarse dirt or liquids into its 50-litre container, ensuring long periods of uninterrupted use in a clean, dust-free environment.









1 Adjustable, ergonomic push handle

- Thanks to a quick lock, the adjustable push handle adapts to the size
- The push handle can be easily folded away to save space when storing the machine.

2 Oil-resistant drain hose

Oil-resistant, integrated drain hose for easy emptying of liquids.

NT 50/1 Tact Te L

- Adjustable push handle
- Drain hose

1.148-411.0

Antistatic preparation

Technical data		
Air flow rate	I/s	74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	1	50
Max. rated input power	W	1380
Voltage	V	220-240
Standard nominal width		ID 35
Rubber power cable length	m	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	68
Weight	kg	18.3
Dimensions (L × W × H)	mm	640 × 370 × 1045
Equipment		
Suction hose	m	4 / with bend
Suction tubes, stainless steel, 2 \times 0.55 m		I
Filter bag		fleece
Wet and dry floor nozzle	mm	360
Crevice nozzle		

■ Included in the scope of supply.

Order no.

Tact CLASS



Built to last.

Highly effective, less wear and tear: the NT 45/1 Tact Te Ec motor has no carbon brushes - ideal for heavy-duty, uninterrupted industrial use with a service life of 5,000 hours.



1 Brushless EC drive

The brushless EC drive has a life expectancy of 5,000 hours. This makes the NT 45/1 Tact Te Ec ideal for continuous use.

2 Variable speed control

Adjustable suction power.

NT 45/1 Tact Te Ec

- Brushless EC drive (5,000 h)
- Antistatic preparation
 Automatic on/off switch

Air flow rate	I/s	63
Vacuum	mbar / kPa	244 / 24.4
Container capacity	I	45
Max. rated input power	W	1380
Voltage	V	220-240
Standard nominal width		ID 35
Rubber power cable length	m	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	71
Weight	kg	13.5
Dimensions (L × W × H)	mm	517 × 375 × 687
Equipment		
Suction hose	m	2.5 / with bend
Suction tubes, stainless steel, 2 \times 0.5 m		1
Filter bag		fleece
Wet and dry floor nozzle	mm	300
Crevice nozzle		
Order no		1 1/5-826 0

■ Included in the scope of supply.

Technical data

273

Tact CLASS



Just the right size

Not too large, not too small, just right: the NT 40/1 Tact Te L is perfect for those who want it all. Compact, easy to transport and a large container capacity for long operating periods. Also available with a push handle on request.











- 1 Suction hose connection in the machine head
- The suction hose port in the machine head enables a larger usable container
- Easy emptying of the container by connecting the hose and machine head.

2 Storage rack and fixing options

- Tool boxes can be placed on the flat machine head without slipping thanks to its rubberised surfaces.
- Transport eyelets facilitate secure fixing with conventional anchoring straps.

NT 40/1 Tact Te L

- PES flat pleated filter
- Antistatic preparation
- Optional push handle

rechnical data		
Air flow rate	I/s	74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	1	40
Max. rated input power	W	1380
Voltage	V	220-240
Standard nominal width		ID 35
Rubber power cable length	m	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	68
Weight	kg	14.4
Dimensions (L × W × H)	mm	560 × 370 × 655

Equipment		
Suction hose	m	4 / with bend
Suction tubes, stainless steel, 2 × 0.55 m		
Filter bag		fleece
Wet and dry floor nozzle	mm	360
Crevice nozzle		1
Power tool connection adaptor		1
Order no.		1.148-311.0
Price		
■ Included in the scope of supply.		

Tochnical data

Tact CLASS



Indispensable on construction sites and in workshops

The compact NT 30/1 Tact Te L is our mobile fine dust expert for tradesmen. It impresses with extraordinary power wherever large quantities of fine dust are generated - whether for heavy-duty use on construction sites or in workshops.









- 1 Tact automatic filter cleaning system
- Fully automatic filter cleaning through powerful bursts of air with no loss of
- Market-wide unique filter service life of at least 180 kg of fine dust.

2 Tool sleeve with false air valve and rubber attachment

- The new tool sleeve ensures optimal connection to the power tool.
- The suction power can be regulated via the rotating ring on the base body of the

NT 30/1 Tact Te L

- PES flat pleated filter
- Antistatic preparation Automatic on/off switch

Technical data		
Air flow rate	I/s	74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	1	30
Max. rated input power	W	1380
Voltage	V	220-240
Standard nominal width		ID 35
Rubber power cable length	m	7.5
Sound pressure level EN 60335-2-69 un- certainty K = 1 dB(A)	dB(A)	69
Weight	kg	13.5
Dimensions (L x W x H)	mm	560 x 370 x 580

Equipment		
Suction hose	m	4 / with bend
Suction tubes, stainless steel, 2 × 0.55 m		1
Filter bag		fleece
Wet and dry floor nozzle	mm	360
Crevice nozzle		
Power tool connection adaptor		1
Order no.		1.148-211.0
Price		

■ Included in the scope of supply.

Tact CLASS



The all-rounder for everything and everyone

For cleaning machines, vehicles, workshop floors, and much more: the NT 30/1 Tact L is a robust and compact all-rounder for operators in diverse industries - with excellent suction power for brilliant results in all situations.















1 Rugged container with bumpers and metal castors.

- mobility on construction sites
- $\hfill \blacksquare$ The rugged container protects the machine from bumps and knocks.

3 Detachable filter casing

- Sturdy metal castors guarantee good manoeuvrability and unrestricted With the detachable filter casing, removal and replacement of the filter
 - It is impossible to insert the flat pleated filter incorrectly.

2 Flexible hose and power cable storage

- Enables secure fixing of hoses of different lengths and diameters.
- The power cable is always stored safely for transport.

4 Central rotary switch

Convenient switching via central rotary switch.

TECHNICAL DATA AND EQUIPMENT

NT 30/1 Tact L

- PES flat pleated filterMetal castors
- Antistatic preparation

Technical data		
Air flow rate	I/s	74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	1	30
Max. rated input power	w	1380
Voltage	V	220-240
Standard nominal width		ID 35
Rubber power cable length	m	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	69
Weight	kg	13.5
Dimensions (L × W × H)	mm	560 × 370 × 580

Equipment		
Suction hose	m	2.5 / with bend
Suction tubes, stainless steel, 2 × 0.55 m		
Filter bag		fleece
Wet and dry floor nozzle	mm	360
Crevice nozzle		1
Power tool connection adaptor		-
Order no.		1.148-201.0
Price		

■ Included in the scope of supply.

Accessories			
Product name	Order no.	Description	Price
Fleece filter bags	2.889-154.0	Fleece filter bag with 30 litre volume. Tear-resistant, dust class M, for suction hose port in machine head.	
Fleece filter bags Adv	2.889-156.0	5 pcs. extra tear-resistant fleece filter bags, dust class M, for suction hose port in machine head.	
Flat pleated filter, PES	6.904-360.0	Polyester fleece, rot-proof, dust class M.	
Flat pleated filter, PTFE	6.907-455.0	Polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners,dust class M. Particularly suitable for very adhesive materials.	
Suction hose	2.889-134.0	2.5 m suction hose with new bayonet and clip fastener.	
Suction hose	2.889-135.0	4 m suction hose with new bayonet and clip fastener.	
Electrically conductive suction hose	2.889-136.0	Electrically conductive suction hose with new bayonet and clip fastener. Length: 2.5 m.	
Electrically conductive suction hose	2.889-137.0	4 m suction hose with new bayonet and clip fastener. Electrically conductive.	
Bend	2.889-148.0	Ergonomic bend for the new clip system. With airflow control slide, in an antistatic design.	
Tool collar ID 35, clip-on	2.889-151.0	Tool adapter with a rubber fixture and airflow control slide for the new clip system. Suitable for all current electric tools.	
Wet and dry floor nozzle Adv for ID 35 nominal width	2.889-152.0	360 mm wide wet and dry floor nozzle with easy-to-change inserts. Including brush strips and squeegees.	
Wet and dry floor nozzle Adv for ID 40 nominal width	2.889-153.0	360 mm wide wet and dry floor nozzle with easy-to-change inserts, squeegees.	



For a range of jobs - suitable for industrial and commercial use

Two powerful turbines, patented filter system, semi-automatic filter cleaning and large container capacity permit long periods of uninterrupted use with constant suction power.









1 On-board storage

■ The large on-board storage space on the casing head ensures that tools ■ The free filter means that the user can work for long intervals without and accessories are always stored and close to hand.

3 ApClean (semi-automatic filter cleaning system)

- interruption.
- $\hfill \blacksquare$ Optimum suction power with high efficiency.

2 Integrated drain hose

Easily accessible drain hose for convenient liquid disposal.

4 Hose and bend attachment

■ Convenient suction hose and bend attachment for easy transport and

TECHNICAL DATA AND EQUIPMENT

■ Included in the scope of supply.

		NT 75/2 Ap Me Tc	NT 65/2 Ap	
		 Semi-automatic filter cleaning Tilting chassis Flat pleated filter (dust class M) 	Semi-automatic filter cleaningFlat pleated filter (dust class M)Drain hose and push handle	
Technical data				
Air flow rate	I/s	2 × 74	2 × 74	
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4	
Container capacity	I	75	65	
Max. rated input power	W	max. 2760	max. 2760	
Voltage	V	220-240	220-240	
Standard nominal width		ID 40	ID 40	
Cable length	m	10	10	
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	73	73	
Weight	kg	26.5	20	
Dimensions (L × W × H)	mm	700 × 505 × 995	600 × 480 × 920	
Equipment				
Suction hose	m	4 / with bend	4 / with bend	
Suction tube, metal 2 × 0.5 m				
Filter bag		Paper	Paper	
Wet and dry floor nozzle	mm	360	360	
Crevice nozzle		•	•	
Stainless steel container			-	
Flat pleated filter		Paper	Paper	
Order no.		1.667-292.0	1.667-291.0	

Accessories			
Product name	Order no.	Description	Price
Flat pleated filter, PES	6.904-284.0	Polyester fleece, rot-proof, dust class M (also for NT 65/2 Eco / Me / Tc and NT 72/2 Eco Tc).	
Flat pleated filter, paper	6.904-283.0	Paper, dust class M (also NT 65/2 Eco / opt. for NT 75/2 Eco Tc models).	
Multi-purpose nozzle, wet/dry	6.903-018.0	Aluminium with height-adjustable rollers, brush strips (6.903-064.0) and squeegees (6.903-081.0, oil-resistant).	
Suction hose	6.906-321.0	With bayonet and clip connection, C 40.	
Plastic bend	5.031-904.0	Plastic with C 40 clip system.	
Suction tube	6.902-081.0	For use in wet or damp environments or for wet vacuuming.	

Premium in the middle class

Whether it is for vehicle interior cleaning, professional applications of building service contractors, in the hotel and gastronomy sector or in many other industries: The new Ap range of powerful and compact wet and dry vacuum cleaners impresses with excellent suction power, semi-automatic filter cleaning, simple operation, clever accessory storage and high-quality, durable components.














1 Semi-automatic filter cleaning

- Semi-automatic filter cleaning guarantees constantly high suction
- The positioning of the Ap cleaning button simplifies handling.

3 Removable filter casing

- Permits dust-free removal of the filter.
- Effectively prevents incorrect insertion of the flat pleated filter.

2 Flexible hose and power cable storage

- Enables secure fixing of hoses of different lengths and diameters.
- Transport-proof storage of the power cable.

4 Clever integrated storage options for accessories

Accessories are stored safely and are always ready to hand.

TECHNICAL DATA AND EQUIPMENT

		NT 40/1 Ap L	NT 30/1 Ap Te L	NT 30/1 Ap L
		 Semi-automatic filter cleaning Flat pleated filter with filter casing Flexible hose and cable storage 	 Semi-automatic filter cleaning Power outlet with automatic on/off switch Connection adapter for power tools 	 Semi-automatic filter cleaning Flat pleated filter with filter casing Flexible hose and cable storage
Technical data				
Air flow rate	I/s	74	74	74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4	254 / 25.4
Container capacity	1	40	30	30
Max. rated input power	W	1380	1380	1380
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 35	ID 35	ID 35
Cable length	m	7.5	7.5	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	70	70	70
Weight	kg	12.4	11.8	11.8
Dimensions (L × W × H)	mm	525 × 370 × 630	525 × 370 × 560	525 × 370 × 560
Equipment				
Suction hose	m	2.5 / with bend	2.5 / with bend	2.5 / with bend
Suction tube, metal, 2 x 0.55 m				
Filter bag		fleece	fleece	fleece
Wet and dry floor nozzle	mm	300	300	300
Crevice nozzle		•	•	•
Power tool connection adaptor		-		-
Order no.		1.148-321.0	1.148-231.0	1.148-221.0

Included in the scope of supply.

Accessories			
Product name	Order no.	Description	Price
Flat-pleated filter packaged PES	6.907-662.0	Flat pleated filter made from polyester fleece, rot-resistant and suitable for dust class M.	
Flat pleated filter, PES	6.904-360.0	Polyester fleece, rot-proof, dust class M.	
Flat pleated filter, PTFE	6.907-455.0	Polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners,dust class M. Particularly suitable for very adhesive materials.	
Fleece filter bags	2.889-154.0	Fleece filter bag with 30 litre volume. Tear-resistant, dust class M, for suction hose port in machine head.	
Fleece filter bags	2.889-155.0	Fleece filter bag with 40-50 litre volume. Tear-resistant, dust class M, for suction hose port in machine head.	
Suction hose	2.889-134.0	2.5 m suction hose with new bayonet and clip fastener.	
Suction hose	2.889-135.0	4 m suction hose with new bayonet and clip fastener.	
Electrically conductive suction hose	2.889-137.0	4 m suction hose with new bayonet and clip fastener. Electrically conductive.	
Electrically conductive suction hose	2.889-136.0	Electrically conductive suction hose with new bayonet and clip fastener. Length: 2.5 m.	
ID 40 bend, electrically conductive	2.889-172.0	Bend for the new clip system in nominal size ID 40. Electrically conductive design. Particularly suited to high concentrations of fine dust.	
Tool collar ID 35, clip-on	2.889-151.0	Tool adapter with a rubber fixture and airflow control slide for the new clip system. Suitable for all current electric tools.	



Compact, powerful and for use anywhere

Handy, powerful, quiet and mobile: the wet and dry vacuum cleaner with its semi-automatic filter cleaning system is an ideal machine for workshops and construction sites.









1 Compact dimensions

■ Ergonomic handle and compact, square dimensions for easy transport ■ Easy, dirt-free removal. The flat pleated filter can be tapped clean and storage.

3 Removable filter box

without damaging it.

2 Semi-automatic filter cleaning

- Semi-automatic filter cleaning effectively ensures constantly high
- With an air flow rate of 74 l/s and a vacuum of 254 mbar, the suction power of the machine is outstanding.

4 Integrated accessory storage

All of the accessories can be stowed conveniently on the machine and are therefore always close at hand.

TECHNICAL DATA AND EQUIPMENT

		NT 20/1 Ap Te	NT 20/1 Ap
		 Semi-automatic filter cleaning Automatic on/off switch (power tools) Removable filter box 	Semi-automatic filter cleaningAccessory/suction hose storageRemovable filter box
Technical data			
Air flow rate	I/s	74	74
Vacuum	mbar / kPa	254 / 25	254 / 25
Container capacity	1	20	20
Max. rated input power	W	1380	1380
Voltage	V	220-240	220-240
Standard nominal width		ID 35	ID 35
Cable length	m	6	6
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	66	66
Weight	kg	8.5	8.5
Dimensions (L × W × H)	mm	440 × 380 × 470	440 × 380 × 470
Equipment			
Suction hose with bend	m	2.5 / with bend	2.5 / with bend
Suction tube, metal 2 × 0.5 m			
Filter bag		fleece	fleece
Wet and dry floor nozzle	mm	300	300
Crevice nozzle		•	•
Power tool connection adaptor			-
Order no.		1.378-510.0	1.378-500.0
Price			

	_					
Included	in	the	scope	of	supply.	

Accessories			
Product name	Order no.	Description	Price
Flat pleated filter, paper	6.904-367.0	Paper, dust class M.	
Flat pleated filter, PES	6.904-360.0	Polyester fleece, rot-proof, dust class M.	
Fleece filter bags	6.907-469.0	Fleece filter bag, tear-resistant, dust class M.	
Adv fleece filter bags	6.904-351.0	Fleece filter bag, extra tear-resistant, dust class M.	
All-purpose brush	6.903-863.0	Natural bristles (ox hair), bristle element 120 \times 45 mm, ID 35.	


When you need the strong stuff

Whether for trade use, vehicle cleaning, retail or any other kind of business: the NT 22/1 Ap will help you deal with all volumes of dirt. The entry-level class in the world of professional wet/dry vacuum cleaners boasts low weight, high manoeuvrability and, most importantly, the high suction power typical of Kärcher products











1 Lightweight with compact dimensions

■ The machine is easy and convenient to transport and store.

3 Moisture-resistant PES cartridge filter

It is possible to change from wet to dry vacuum cleaning easily without having to dry the PES cartridge filter first.

2 Semi-automatic filter cleaning

Semi-automatic filter cleaning effectively ensures constantly high suction power

4 Socket for electric tools (with automatic start-up)

- The appliance's socket acts as a "remote control" for the vacuum
- The vacuum cleaner starts automatically when the attached power tool is started.

TECHNICAL DATA AND EQUIPMENT

Included in the scope of supply.

		NT 22/1 Ap Te L	NT 22/1 Ap L
		 Efficient semi-automatic filter cleaning Socket with automatic start-up for electric tools Moisture-resistant PES cartridge filter 	 Efficient semi-automatic filter cleaning Suction hose port in the head of the machine Moisture-resistant PES cartridge filter
Technical data			
Air flow rate	I/s	71	71
Vacuum	mbar / kPa	255 / 25.5	255 / 25.5
Container capacity	1	22	22
Max. rated input power	W	1300	1300
Voltage	V	220-240	220-240
Standard nominal width		ID 35	ID 35
Cable length	m	6	6
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	72	72
Weight	kg	6.1	5.7
Dimensions (L × W × H)	mm	380 × 370 × 480	380 × 370 × 480
Equipment			
Suction hose	m	1.9 / with bend	1.9 / with bend
Suction pipe, plastic 2 × 0.5 m		-	
Suction tube, metal 2 × 0.5 m		•	-
Filter bag		fleece	fleece
Wet and dry floor nozzle	mm	300	300
Crevice nozzle			
Order no.		1.378-610.0	1.378-600.0
Price			

Accessories			
Product name	Order no.	Description	Price
Fleece filter bags	2.889-217.0	Fleece filter bag, tear-resistant, for NT 22/1 Ap and NT 22/1 Ap Te machines. Dust class-L-certified.	
Cartridge filter packaged PES	2.889-219.0	Moisture-resistant PES cartridge filter for wet and dry vacuum cleaning. Dust class L-certified.	
Elbow, standard	2.889-199.0	Plastic bend, grey, with C 35 clip system.	
Suction tube set	2.889-218.0	Plastic suction tube set, NW 35, grey, 2-piece, each 0.5 m.	
Wet/Dry floor nozzle standard	2.889-263.0	Wet/Dry floor nozzle, NW 35, 300 mm wide, grey. Including brush strips and squeegees. Easy-to-change inserts.	

STANDARD CLASS

Tilt & Empty

Time-saving, with no need to bend - the NT 70 range with tilting chassis makes it easy to empty the large container: simply lift the handle and empty the dirt. Ideal for contract cleaners for wet application after floor cleaning with a single disc machine.









1 Integrated accessory storage

Large bumper with accessory storage.

3 Tilting chassis

 $\hfill \blacksquare$ Quick and easy: the container tilts back for easy emptying.

2 Ergonomic push handle

■ The NT 70 has an ergonomic push handle so that the machine can be pushed along.

4 Ergonomic lifting handle

The ergonomic handle – at the bottom front of the container – makes

TECHNICAL DATA AND EQUIPMENT

		NT 70/3 Me Tc	NT 70/2 Me Tc	NT 70/3 Tc
		Tilting chassis and large wheelsErgonomic push handleStainless steel container	Tilting chassis and large wheelsErgonomic push handleStainless steel container	Tilting chassis and large wheelsErgonomic push handleOptional wet filter available
Technical data				
Air flow rate	I/s	3 × 74	2 × 74	3 × 74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4	254 / 25.4
Container capacity	1	70	70	70
Max. rated input power	W	3600	2400	3600
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 40	ID 40	ID 40
Cable length	m	10	10	10
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	79	75	79
Weight	kg	28.8	26.7	27.6
Dimensions (L × W × H)	mm	510 × 645 × 990	510 × 645 × 990	510 × 645 × 990
Equipment				
Suction hose	m	4 / with bend	4 / with bend	4 / with bend
Suction tube, metal 2 × 0.5 m			•	
Wet and dry floor nozzle	mm	400	400	400
Crevice nozzle		•		
Cartridge filter		Paper	Paper	Paper
Order no.		1.667-274.0	1.667-272.0	1.667-273.0
Price				

■ Included in the scope of supply.

NT 70/2 Tc

■ Tilting chassis and large wheels

Ergonomic push handleOptional wet filter available

Technical data Air flow rate 2 × 74 Vacuum mbar / kPa 254 / 25.4 Container capacity 70 Max. rated input power 2400 220-240 Voltage Standard nominal width ID 40 Cable length 10 Sound pressure level EN 60335-2-69 dB(A) 75 uncertainty K = 1 dB(A) Weight 25.4 510 × 645 × 990

Equipment		
Suction hose	m	4 / with bend
Suction tube, metal 2 × 0.5 m		1
Wet and dry floor nozzle	mm	400
Crevice nozzle		1
Cartridge filter		Paper
Order no.		1.667-271.0
Price		

lacksquare Included in the scope of supply.



The vacuuming professionals

Kärcher quality at an affordable price: the NT 70 range offers powerful vacuum cleaners with up to three motors. With their high suction power, these vacuum cleaners effortlessly pick up liquids and coarse dirt.









1 2 motors

- Choose between one or two motors. Both can be switched on and off at Large bumper with accessory storage. the front as required.
- 3 Integrated accessory storage

2 Easy to use

■ The container is easy to empty via the drain hose. Extremely practical ■ The NT 70 has an ergonomic push handle so that the machine due to the very large 70 litre container capacity.

4 Ergonomic push handle

can be pushed along.

TECHNICAL DATA AND EQUIPMENT

		NT 70/2 Adv	NT 70/2 Me	NT 70/3
		Robust bumper, large wheelsErgonomic push handleWide nozzle	Stainless steel containerErgonomic push handleOptional wet filter available	Robust bumper, large wheelsErgonomic push handleOptional wet filter available
Technical data				
Air flow rate	I/s	2 × 74	2 × 74	3 × 74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4	254 / 25.4
Container capacity	I	70	70	70
Max. rated input power	W	2400	2400	3600
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 40	ID 40	ID 40
Cable length	m	10	10	10
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	75	75	79
Weight	kg	26	25.6	27.6
Dimensions (L × W × H)	mm	510 × 740 × 1010	510 × 740 × 1010	510 × 740 × 1010
Equipment				
Suction hose	m	4 / with bend	4 / with bend	4 / with bend
Suction tube, metal 2 × 0.5 m		•	•	•
Wet and dry floor nozzle	mm	400	400	400
Crevice nozzle		•	•	•
Cartridge filter		Paper	Paper	Paper
Order no.		1.667-278.0	1.667-275.0	1.667-270.0
Price				

Included in the scope of supply.

		NT 70/2	NT 70/1
		Robust bumper, large wheelsErgonomic push handleOptional wet filter available	Robust bumper, large wheelsErgonomic push handleOptional wet filter available
Technical data			
Air flow rate	I/s	2 × 74	74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4
Container capacity	I	70	70
Max. rated input power	W	2400	1200
Voltage	V	220-240	220-240
Standard nominal width		ID 40	ID 40
Cable length	m	10	10
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	75	73
Weight	kg	24.9	22.6
Dimensions (L × W × H)	mm	510 × 740 × 1010	510 × 740 × 1010
Equipment			
Suction hose	m	4 / with bend	4 / with bend
Suction tube, metal 2 × 0.5 m			
Wet and dry floor nozzle	mm	400	400
Crevice nozzle			
Cartridge filter		Paper	Paper
Order no.		1.667-269.0	1.667-268.0
Price			
■ Included in the scope of supply			

■ Included in the scope of supply.

STANDARD CLASS



The high suction power standard class

Robust, affordable, versatile: these standard high-performance entry-level wet and dry vacuum cleaners easily pick up dirt and water, are mobile and ideal for cleaning small to medium-sized











1 Container emptying

■ Easily accessible drain hose for convenient liquid disposal.

3 Robust metal latches

■ These extremely robust latches lock more reliably.

2 Accessory storage

4 Robust bumper

Accessories can be attached to the container at the rear of the machine. The NT 48/1 has a bumper to protect both the vacuum cleaner and walls, machines and other items against damage.

TECHNICAL DATA AND EQUIPMENT

		NT 48/1 Te	NT 48/1	NT 27/1 Me Adv
		Plastic containerDrain hosePower outlet	All-purpose brushCartridge filter with enlarged filter areaDrain hose	Cartridge filter with enlarged filter areaStainless steel containerWide wet suction nozzle
Technical data				
Air flow rate	I/s	67	67	67
Vacuum	mbar / kPa	200 / 20	200 / 20	200 / 20
Container capacity	1	48	48	27
Max. rated input power	W	max. 1380	max. 1380	max. 1380
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 35	ID 35	ID 35
Cable length	m	7.5	7.5	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	72	72	72
Weight	kg	10.5	10.5	8.2
Dimensions (L × W × H)	mm	490 × 390 × 780	490 × 390 × 780	420 × 420 × 540
Equipment				
Suction hose with bend	m	2.5 / with bend	2.5 / with bend	2.5 / with bend
Suction tube, metal 2 × 0.5 m			•	
Filter bag		Paper	Paper	Paper
Wet and dry floor nozzle	mm	400	400	400
Crevice nozzle			•	•
Cartridge filter		Paper	Paper	Paper
Order no.		1.428-625.0	1.428-620.0	1.428-114.0
Price				

Included in the scope of supply.

		NT 27/1 Me	NT 27/1 Adv	NT 27/1
		With cartridge and wet filtersStainless steel containerAccessory storage and cable hook	 Cartridge filter with enlarged filter area Plastic container Wide wet suction nozzle 	With cartridge and wet filtersPlastic containerAccessory storage and cable hook
Technical data				
Air flow rate	I/s	67	67	67
Vacuum	mbar / kPa	200 / 20	200 / 20	200 / 20
Container capacity	1	27	27	27
Max. rated input power	W	max. 1380	max. 1380	max. 1380
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 35	ID 35	ID 35
Cable length	m	7.5	7.5	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	72	72	72
Weight	kg	8.2	7.5	7.5
Dimensions (L × W × H)	mm	420 × 420 × 540	420 × 420 × 525	420 × 420 × 525
Equipment				
Suction hose with bend	m	2.5 / with bend	2.5 / with bend	2.5 / with bend
Suction tube, metal 2 × 0.5 m			•	•
Filter bag		Paper	Paper	Paper
Wet and dry floor nozzle	mm	300	400	300
Crevice nozzle		-	•	•
Cartridge filter		Paper	Paper	Paper
Order no.		1.428-100.0	1.428-520.0	1.428-500.0
Price				
■ Included in the scope of supply.				

NT CLASSIC WITH TWO-MOTOR



NT Classic range: extra powerful and easy to use

High suction power, easy handling, robust - these two-motor wet and dry vacuum cleaners provide outstanding performance for all wet and coarse dirt vacuuming. With cartridge filter and Easy Service Concept.









1 Robust and easy to transport

- Extremely mobile on all surfaces thanks to the robust chassis, large wheels and metal castors.
- The standard push handle ensures convenient transport.

3 Drain hose

Easily accessible drain hose for convenient liquid disposal.

2 Excellent suction power

- 2 powerful turbines ensure outstanding suction power.
- The strong suction power ensures excellent cleaning results and the utmost efficiency.

4 Vacuum without filter bags

- The two-motor NT Classic vacuum cleaners are fitted with the tried-and-tested Kärcher cartridge filter.
- The cartridge filter enables sustained suction without a filter bag.

TECHNICAL DATA AND EQUIPMENT

		NT 90/2 Me Classic Edition	NT 70/2 Me Classic Edition	NT 50/2 Me Classic Edition
		Strong suction powerSimple turbine changeDrain hose	Strong suction powerSimple turbine changeDrain hose	Strong suction powerSimple turbine changeRobust chassis
Technical data				
Air flow rate	I/s	2 × 53	2 × 53	2 × 53
Vacuum	mbar / kPa	225 / 22.5	225 / 22.5	225 / 22.5
Container capacity	1	90	70	50
Max. rated input power	W	max. 2300	max. 2300	max. 2300
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 40	ID 40	ID 40
Cable length	m	7.5	7.5	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	76	76	76
Weight	kg	19	18.5	17.5
Dimensions (L × W × H)	mm	580 × 510 × 995	580 × 510 × 850	580 × 510 × 850
Equipment				
Suction hose	m	2.5 / with bend	2.5 / with bend	2.5 / with bend
Suction tube, metal 2 × 0.5 m		•	•	
Stainless steel container		•		•
Crevice nozzle		•	•	
Cartridge filter			•	•
Wet and dry floor nozzle	mm	360	360	360
Dry floor nozzle	mm	360	360	360
Order no.		1.667-700.0	1.667-306.0	1.667-030.0
Price				

■ Included in the scope of supply.

NT 50/1 Me Classic Edition

Stror	ng	SUC	tion	power	

Simple turbine changeRobust chassis

Technical data		
Air flow rate	I/s	53
Vacuum	mbar / kPa	225 / 22.5
Container capacity	1	50
Max. rated input power	W	max. 1150
Voltage	V	220-240
Standard nominal width		ID 40
Cable length	m	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	73
Weight	kg	16
Dimensions (L × W × H)	mm	580 × 510 × 850

Equipment		
Suction hose	m	2.5 / with bend
Suction tube, metal 2 × 0.5 m		
Stainless steel container		ı
Crevice nozzle		
Cartridge filter		I
Wet and dry floor nozzle	mm	360
Dry floor nozzle	mm	360
Order no.		1.667-010.0
Price		

■ Included in the scope of supply.

NT CLASSIC SINGLE-MOTOR



Compact universal units in the **NT Classic range**

The compact, robust wet and dry vacuum cleaners in the singlemotor Kärcher NT Classic range stand out with their Easy Service Concept, low operation and maintenance costs, and reliable filter engineering.









1 Compact, robust and mobile

- Excellent stability, easy manoeuvrability and convenient transport thanks to its slimline form and 4 castors.
- The bumper offers secure all-round protection for the vacuum cleaner The rapid turbine change saves an enormous amount of time, but also and equipment.

3 Service and comfort

- Sensationally fast: the Easy Service Concept allows removal of the turbine in just 44 seconds.

2 Excellent suction power

- NT Classic devices with a powerful 1,500 W turbine reliably remove a NT Classic single-motor machines feature tried-and-tested Kärcher
- For excellent cleaning results.

4 Vacuum without filter bags

- The cartridge filter enables sustained suction without a filter bag.

TECHNICAL DATA AND EQUIPMENT

		NT 38/1 Me Classic Edition	NT 30/1 Me Classic Edition	NT 20/1 Me Classic Edition
		Easy Service ConceptStrong suction powerCartridge filter or permanent filter basket	 Easy Service Concept Strong suction power Cartridge filter or permanent filter basket 	Easy Service ConceptStrong suction powerCartridge filter or permanent filter basket
Technical data				
Air flow rate	I/s	59	59	59
Vacuum	mbar / kPa	227 / 22.7	227 / 22.7	227 / 22.7
Container capacity	1	38	30	20
Max. rated input power	W	1500	1500	1500
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 35	ID 35	ID 35
Cable length	m	6.5	6.5	6.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	78	78	78
Weight	kg	8.6	8	7.4
Dimensions (L × W × H)	mm	375 × 360 × 735	375 × 360 × 645	375 × 360 × 520
Equipment				
Suction hose	m	2.5 / with bend	2.5 / with bend	2.5 / with bend
Suction tube, metal 2 × 0.5 m		•	•	
Stainless steel container		•	•	•
Crevice nozzle		•	•	•
Filter bag		Paper	Paper	Paper
Wet and dry floor nozzle	mm	360	360	360
Dry floor nozzle	mm	360	360	360
Order no.		1.428-538.0	1.428-568.0	1.428-548.0
Price				

■ Included in the scope of supply.

SAFETY VACUUM CLEANERS

Built for explosive dust

Our explosion-proof wet and dry vacuum cleaners are approved for danger class Zone 22 and are thus ideal for use in potentially explosive atmospheres and for vacuuming explosive dust.















1 Zone 22 + dust class H

For combustible dusts in dust explosion classes, Zone 22 and health-endangering dusts, dust class H.

3 Brushless EC drive

■ The brushless EC drive has a life expectancy of 5,000 hours – ideal for continuous use.

2 Antistatic system

All K\u00e4rcher safety vacuum cleaners feature a continuous antistatic system with conductive accessories.

4 Safety first

■ The NT 80/1 B1 M S features automatic water level control and can only be operated with a sufficient water level.

TECHNICAL DATA AND EQUIPMENT

		NT 75/1 Me Ec H Z22	NT 80/1 B1 M S
		Brushless EC drive (5,000 h)Antistatic systemSuitable for asbestos	Antistatic systemStainless steel containerFor drive load powder residue
Technical data			
Air flow rate	I/s	61	56
Vacuum	mbar / kPa	220 / 22	235 / 23.5
Container capacity	1	75	80
Max. rated input power	W	1000	max. 1380
Voltage	V	220-240	220-240
Standard nominal width		ID 40	ID 40
Cable length	m	10	10
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	76	70
Weight	kg	24.8	32
Dimensions (L × W × H)	mm	640 × 540 × 925	660 × 520 × 1078
Equipment			
Suction hose	m	4 / with bend (electrically conductive)	4 / with bend (electrically conductive)
Metal suction tube, 1 × 1.0 m			
Filter bag		fleece	-
Safety filter set			-
Wet and dry floor nozzle	mm	360	370
Crevice nozzle			
Stainless steel container			•
Flat pleated filter		Fibreglass	-
Order no.		1.667-239.0	1.667-267.0
Price			

■ Included in the scope of supply.

MINISTRA

SAFETY VACUUM CLEANERS



Certified safety - even with asbestos

In older buildings, renovation work often releases dust that may contain asbestos and other harmful or carcinogenic particles. The safe removal of this dust is only possible with a certified safety vacuum cleaner for dust class H, such as our new Tact machines. They guarantee a dust retention capacity of 99.995 percent and, thanks to the cleanable H filter, can also handle large amounts of dust.











1 Hose selector switch

■ The diameter of the connected suction hose can be selected on the control panel.

2 Approved for asbestos dust

Only dust class H safety vacuum cleaners approved with the additional test for asbestos (according to TRGS 519) may be used for dust containing asbestos in Germany. Our H class safety vacuum cleaners have this approval.

		NT 75/1 Tact Me Te H	NT 50/1 Tact Te H	NT 30/1 Tact Te H
		Antistatic systemAutomatic on/off switch (power tools)Suitable for asbestos	Complete antistatic system, incl. conductive accessories Socket with automatic start-up for electric tools Licensed for asbestos abatement	Complete antistatic system, incl. conductive accessories Socket with automatic start-up for electric tools Licensed for asbestos abatement
Technical data				
Air flow rate	I/s	74	74	74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4	254 / 25.4
Container capacity	I	75	50	30
Max. rated input power	w	1000	1380	1380
Voltage	V	220-240	220-240	220-240
Standard nominal width		ID 35	ID 35	ID 35
Rubber power cable length	m	10	7.5	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	67	69	69
Weight	kg	24.6	19.6	14.4
Dimensions (L × W × H)	mm	640 × 540 × 925	640 × 370 × 1045	560 × 370 × 580
Equipment				
Suction hose	m	2.5 / with bend (electrically conductive)	4 / with bend (electrically conductive)	4 / with bend (electrically conductive)
Suction tubes, stainless steel, 2 × 0.5 m		•	•	
Filter bag		Paper	fleece	fleece
Safety filter set			•	
Wet and dry floor nozzle	mm	360	360	360
Crevice nozzle				•
Flat pleated filter		Fibreglass	PTFE HEPA	PTFE HEPA
Order no.		1.667-294.0	1.148-437.0	1.148-237.0
Price				

■ Included in the scope of supply.

SAFETY VACUUM CLEANERS



The fine dust removers on your building site

With dust class M safety vacuum cleaners, you will be fully protected against inhalable fine dust. The fully-automatic sensor control system in our new Tact appliances guarantees optimum filter cleaning and high suction power at all times. The vacuum cleaners also have electronic volume flow monitoring and a complete antistatic system.







1 Fully automatic filter cleaning

Sensor-controlled electronics for optimal filter cleaning efficiency and therefore maximum suction power.

2 Tested filtration efficiency of 99.9 per cent

The removal of almost all fine dust makes for clean, safe workplaces.

Clean Filter Constant Airflow

The removal of almost all fine dust makes for clean, safe workplaces.

		NT 50/1 Tact Te M	NT 30/1 Tact Te M
		 Complete antistatic system, incl. conductive accessories Socket with automatic start-up for electric tools Cooling air filtration 	 Complete antistatic system, incl. conductive accessories Socket with automatic start-up for electric tools Cooling air filtration
Technical data			
Air flow rate	I/s	74	74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4
Container capacity	1	50	30
Max. rated input power	W	1380	1380
Voltage	V	220-240	220-240
Standard nominal width		ID 35	ID 35
Rubber power cable length	m	7.5	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	69	69
Weight	kg	19	14.2
Dimensions (L × W × H)	mm	640 × 370 × 1045	560 × 370 × 580
Equipment			
Suction hose	m	4 / with bend (electrically conductive)	4 / with bend (electrically conductive)
Suction tubes, stainless steel, 2 \times 0.5 m	ı		
Filter bag		fleece	fleece
Wet and dry floor nozzle	mm	360	360
Crevice nozzle		•	
Flat pleated filter		PES	PES
Order no.		1.148-435.0	1.148-235.0
Price			
■ Included in the scope of supply			

 \blacksquare Included in the scope of supply.

SPECIAL VACUUMS

299

DECEMBER OF THE PARTY OF THE PA

Integrated wastewater pump

Professional wet and dry vacuum cleaner with integrated disposal pump for industry, building service contractors and fire brigades. With its electrical safety features, our NT 611 Mwf is state-of-the-art and fulfils even the strictest safety requirements of fire brigades. With the new, robust prefilter basket, the pump is effectively protected against blocking.



- 1 Integrated accessory storage
- Large bumper with accessory storage.
- 2 Integrated wastewater pump
- Large quantities of liquid can be disposed of via the disposal pump to allow continuous use.

		NT 611 Mwf	NT 611 Eco K
		 With wastewater pump IP68 connector; PRCD-K switch C-coupling with shut-off valve 	Filter cleaning mechanismFor dry vacuuming (with optional filter)With integrated wastewater pump
Technical data			
Air flow rate	I/s	57	57
Vacuum	mbar / kPa	235 / 23.5	235 / 23.5
Container capacity	1	55	55
Max. rated input power	W	2350	max. 2350
Voltage	V	220-240	220-240
Disposal pump power rating	W	800	800
Standard nominal width		ID 40	ID 40
Cable length	m	10	10
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	63	63
Weight	kg	23	23
Dimensions (L × W × H)	mm	570 × 430 × 860	570 × 370 × 860
Equipment			
Suction hose	m	4 / with bend	4 / with bend
Suction tube, metal 2 × 0.5 m		•	•
Wet and dry floor nozzle	mm	370 / Aluminium	360
Crevice nozzle		•	•
Coarse filter for wet vacuuming			•
Order no.		1.146-601.0	1.146-209.0
Price			
■ Included in the scope of supply.			

SPECIAL VACUUMS



Special vacuum cleaners for special cleaning tasks

The Bs model series features heat-resistant containers and PES flat pleated filters in dust class M - ideal for bakeries for example. With Tact system for constant suction power.



- 1 The vacuum cleaner for bakeries
- The plastic container is acid, lye and heat resistant.
- The optional accessory kits were developed specially for use in bakeries.

2 Heat-resistant PES flat pleated filter

■ The machine has a heat-resistant PES flat pleated filter, dust class M – ideal for effortless removal of dust and dirt in bakeries.

NT 55/1 Tact Bs

NT 35/1 Tact Bs

		 Antistatic preparation Tact automatic filter cleaning system Accessory holder for oven nozzle 	 Antistatic preparation Tact automatic filter cleaning system Accessory holder for oven nozzle
Technical data			
Air flow rate	I/s	61	61
Vacuum	mbar / kPa	230 / 23	230 / 23
Container capacity	1	55	35
Max. rated input power	W	1380	1380
Voltage	V	220-240	220-240
Standard nominal width		ID 35	ID 35
Cable length	m	7.5	7.5
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	63	63
Weight	kg	15	12.8
Dimensions (L × W × H)	mm	580 × 375 × 865	580 × 375 × 517
Equipment			
Flat pleated filter		PES	PES
Order no.		1.146-700.0	1.184-700.0

■ Included in the scope of supply.

ACCESSORIES FOR UNLIMITED APPLICATIONS

Kärcher wet and dry vacuum cleaners offer exemplary functionality and safety – and remove dirt and liquids without leaving anything behind. The comprehensive range of accessories makes the vacuum cleaners suitable for a wide range of tasks. Because only the perfect interplay of machine and optimally adapted accessories guarantees maximum cleaning performance and the best results. All accessories can be stored safely on the machine – making them quick to hand and easy to put away again.



Table of contents: Wet and dry vacuum cleaner accessories

Target-group-specific accessory kits	Page	30
Filter bags	Page	30
Filters	Page	30
Suction nozzles, suction tubes and bends	Page	31
Connecting adapters	Page	32
Suction hoses	Page	32
Other accessories	Page	32







1 Easy to use

The smarter and better the individual parts fit together, the easier it is to work. With our new wet and dry accessories, we have completely redesigned all the interfaces. The result is that all accessories can now be separated and joined much more quickly and easily, while the connections are even sturdier.

2 Optimal connections

With its flexible rubber attachment, the new tool adapter fits all common power tools perfectly. The suction power is conveniently adjusted using a rotating ring on the adapter itself.

3 Optimal accessory storage

What use are the best accessories if in practice users always have to search for them? With our wet and dry vacuum cleaners, all standard accessories are stored on and in the machine itself, making them ready to hand and near impossible to lose. For example, the crevice nozzle and the tool adapter are integrated into the side of the machine head. Equally as clever is the new flexible hose storage solution for hoses of different lengths and

4 Safety thanks to colour coding

Thanks to our new colour coding, you can now see which accessory is right for which application at a glance. All suction hoses have rings in different colours on the bayonet connection.

An anthracite ring indicates standard, i.e. for normal applications. A white ring with the word "conductive" indicates an electrically conductive version, which we recommend if you frequently vacuum a lot of fine dust. With this version, the hose and bend are also black. Oil-resistant hoses are marked with a blue ring, while heat-resistant hoses are marked with an orange ring.

TARGET-GROUP-SPECIFIC ACCESSORY KITS



From heating boilers to vehicle cleaning: Kärcher accessory kits offer the right equipment for specific uses, transforming vacuums into special vacuums in next to no time.

























		Order no.	ID	Price	Description		NT 75/2 Tact² Me Tc Adv / NT 75/2 Tact² Me Tc / NT 6 NT 55/2 Tact² Me NT 75/2 Tact² Me NT 65/2 Tact² Me NT 65/2 Tact² NT 50/1 Tact Te L NT 45/1 Tact Te EC NT 40/1 Tact Te EC NT 40/1 Tact Te L / NT 30/1 Tact Te L / NT 30/1 Tact In To/2 Ap Me Tc NT 75/2 Ap Me Tc NT 75/2 Ap Me Tc NT 75/2 Adv / NT 70/2 Me / NT 70/3 NT 75/2 Adv / NT 70/1 NT 75/2 In 76/1 NT 75/1 Me Adv NT 55/1 Tact Bs / NT 35/1 Tact Bs
Target-group-specific accessory kits for vacuum cleaners							
Wet and dry vacuuming kit, ID 40, electrically conductive	1 2	2.638-147.0	ID 40		Wet and dry vacuuming kit, electrically conductive.	1	
Horse kit, electrically conductive	2 2	2.637-248.0	ID 40		Horse kit, electrically conductive.	2	
Accessory kit for sanding, electrically conductive	3 2	2.862-167.0	ID 27		Accessory kit for power tools, electrically conductive.	3	
Bus kit attachment kit	4	2.640-560.0	ID 40		Bus kit attachment kit.	4	
Oven kit	5	2.640-341.0	ID 35		Oven kit.	5	
Bakery kit, electrically conductive	6	2.640-436.0	ID 40		Bakery kit, electrically conductive.	6	
Universal kit for industrial and commercial use	7	2.637-595.0	ID 35		Universal kit for industrial and commercial use.	7	
Heating boiler cleaning kit	8 2	2.638-852.0	ID 35		Heating boiler cleaning kit.	8	
Construction kit	9 2	2.637-352.0	ID 40		Construction kit.	9	
Professional cleaning kit	10	2.637-353.0	ID 40		Professional cleaning kit.	10	
Car cleaning accessory kit	11	2.862-166.0	ID 35		Car cleaning kit.	11	
Fire brigade kit	12	2.637-360.0	ID 40		Fire brigade kit.	12	
Industrial kit	13	2.637-355.0	ID 61		Industrial kit.	13	
Swarf kit	14	2.640-760.0	ID 61		Swarf kit.	14	
□ Available accessories — More Kärcher original accessorie	oc can h	so found on the	o following na	700	·	<u> </u>	

□ Available accessories. More Kärcher original accessories can be found on the following pages.

FILTER BAGS



With Kärcher filter bags made from paper and fleece material, dry dirt and dust can be conveniently disposed of.



















	60
	16
_	

	Order no.	Quantity	Price	Description		NT 75/2 Tact* Me Tc Adv / NT 75/2 Tact* Me Tc / NT 65/2 Tact* Tr NT 55/2 Tact* Me IT 55/2 Tact* Me IT 55/2 Tact* Me IT 75/2 Tact* Te Ec NT 76/1 Tact Te Ec NT 40/1 Tact Te L NT 30/1 Tact Te L NT 30/1 Tact Te L NT 30/1 Ap Te L / NT 70/2 Me IT / NT 20/1 Ap IT Ap IT NT 20/1 Ap I
Paper filter bags (two-ply)						
Filter bag set replacement	1 9.755-358.0	10 piece(s)		Filter bag set, dust class M.	1	
Filter bag set	2 9.755-360.0	10 piece(s)			2	
Paper filter bags	3 6.904-290.0	5 piece(s)		Dust class M.	3	
	4 6.904-285.0	5 piece(s)		Dust class M, triple-ply, reinforced outer layer, tear-resistant.	4	
Paper filter bags	5 6.904-208.0	5 piece(s)		Dust class M.	5	
Fleece filter bags (three-ply)		•	,			
Fleece filter bags	6 2.889-155.0	5 piece(s)		Fleece filter bag with 40-50 litre volume. Tear-resistant, dust class M, for suction hose port in machine head.	6	
	7 2.889-154.0	5 piece(s)		Fleece filter bag with 30 litre volume. Tear-resistant, dust class M, for suction hose port in machine head.	7	
	8 6.907-469.0	5 piece(s)		Fleece filter bag, tear-resistant, dust class M.	8	
Fleece filter bags	9 2.889-217.0	5 piece(s)		Fleece filter bag, tear-resistant, for NT 22/1 Ap and NT 22/1 Ap Te machines. Dust class-L-certified.	9	
Fleece filter bags	10 6.907-480.0	5 piece(s)		Fleece filter bag, tear-resistant, dust class M.	10	
Adv fleece filter bags	11 6.907-361.0	5 piece(s)		Fleece filter bag, extra tear-resistant, dust class M.	11	
	12 6.904-351.0	5 piece(s)			12	
Safety filter sets/bags						
Safety filter bag NT 50/1	13 2.889-184.0	5 piece(s)		Safety filter set with dust disposal bag, for dust class H safety vacuum cleaners.	13	
Safety filter bag NT 30/1	14 2.889-183.0			Guarantees the dust-free disposal of dangerous dust.	14	
Filters and waste disposal bags						
Disposal bags, PE	15 6.904-348.0	20 piece(s)		Disposal bag, PE, 20 pcs, 60-100 I, for low-dust disposal of suction waste.	15	
Safety filter bags	16 6.904-420.0			For dust-free/low-dust emptying in conjunction with the 4.070-930.0 container, with dust disposal bag, electrically conductive. Checked and approved for dust class H.	16	

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.

FILTERS



The ideal filter for every application: Kärcher flat pleated filters are available in a variety of materials – from standard cellulose filters to PTFE filters for problem dusts like moist concrete.























3 504-311.0 5 5 5 5 5 5 5 5 5							NT 75/2 Tact* Me Tr Adv / NT 75/2 Tact* Me Tc / NT 65/2 Tact* Tact* Me Tr 75/2 Tact* Te Tr 75/2 Tact* Te Tr 75/2 Tact* Te Tr 75/2 Ap Me Tc / NT 30/1 Ap Te L / NT 20/1 Ap Te L / NT 20/2 Me Tc / NT 70/2 Me Tc / NT
## Titler law ## ## ## ## ## ## ##	March Cities In a second	Order no.	Quantity	Price	Description		
2 69.04-252.0 59.06(9) 1 69.04-252.0 59.06(9) 1 69.04-252.0 59.06(9) 1 69.04-252.0 1 1 1 1 1 1 1 1 1		1 6004 211 0	E pioco(c)	1	Dust class L general cleaning dry and wet tear resistant	1	
Septiment Sept	Wet filter bag			-	Dust class L, general cleaning, dry and wet, tear-resistant.		
New York Class H Miscr Fate potent of this or FTR Class 4 6.007-671.0 1 necess 6.007-6				+	-		
Flax pleased filter, PITE H class	UEDA duet elece U filter	3 0.304-171.0	3 piece(s)			3	
Fig. 2 1 1 1 1 1 1 1 1 1		4 6.907-671.0	1 piece(s)	T	HEPA flat pleated filter made from PTFE. Suitable for dust class H (HEPA 13).	4	
S 5904-36A0 pieces							
Carridge filter paper				+			
Flat pleated filter, paper Flat pleated f	Cartridge filter paper						
Section Paper/metal, vacuum filter, filter for fan motor. 9		7 6.414-789.0	1 piece(s)		Paper, larger filter area.	7	
Cartridge filter PES Cartridge filter packaged PES 10 2.889-219.0 1 piece(s) Moisture-resistant PES cartridge filter for wet and dry vacuum cleaning. Dust class L certified. Flat pleated filter, paper Flat pleated filter, paper 11 6.904-287.0 1 piece(s) Paper, dust class M. Glso NT 65/2 Eco / opt. for NT 75/2 Eco Tc models). Flat pleated filter, paper Flat pleated filter, paper 13 6.907-276.0 1 piece(s) Paper, approved for dust class M. Flat pleated filter, paper Flat pleated filter packaged PES 14 6.907-662.0 1 piece(s) Flat pleated filter made from polyester fleece, rot-resistant and suitable for dust class M. Flat pleated filter, PES 15 6.904-280.0 1 piece(s) Polyester fleece, rot-proof, dust class M. 15 16 6.904-280.0 1 piece(s) Polyester fleece, rot-proof, dust class M. 17 Flat pleated filter, PEF Flat pleated filter, PEF 18 6.907-277.0 1 piece(s) Polyester fleece, rot-proof, dust class M. 17 Flat pleated filter, PIFE Flat pleated filter, PIFE 18 6.907-455.0 1 piece(s) Polyester fleece, rot-proof, dust class M. 19 Polyester fleece, rot-proof, dust class M. Polyester fleece, rot-proof, dust class M.						8	
Paper, dust class L. certridge filter packaged PES 10 2889-219.0 1 piece(s) Moisture-resistant PS cartridge filter for wet and dry vacuum cleaning. 10		9 6.414-808.0	1 piece(s)		Paper/metal, vacuum filter, filter for fan motor.	9	
Dust class L-certified. Dust class L-cer	Cartridge filter PES						
Flat pleated filter, paper 11 6.904-267.0 1 piece(s) Paper, dust class M. 11	Cartridge filter packaged PES	10 2.889-219.0	1 piece(s)			10	
12 6.904-283.0 1 piece(s) Paper, dust class M (also NT 65/2 Eco / opt. for NT 75/2 Eco Tc models). 12			1				
Flat pleated filter, paper 13 6.907-276.0 1 piece(s) 2 piece(s) 3 3 3 3 3 3 3 3 3	Flat pleated filter, paper						
Flat pleated filter, PES Flat pleated filter packaged PES 14 6.907-662.0 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. Particularly suitable for very adhesive materials. 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating, dust class M. polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece wi		12 6.904-283.0	1 piece(s)		Paper, dust class M (also NT 65/2 Eco / opt. for NT 75/2 Eco Tc models).	12	
Flat pleated filter, PES Flat pleated filter packaged PES 14 6.907-662.0 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece, rot-proof, dust class M. 1 piece(s) 2 polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. Particularly suitable for very adhesive materials. 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 1 piece(s) 2 polyester fleece with PTFE coating, dust class M. for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating, dust class M. polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece with PTFE coating for Tact' vacuum cleaners. 2 polyester fleece wi	Flat pleated filter paper	13 6.907-276.0	1 piece(s)	+	Paper, approved for dust class M.	13	
Flat pleated filter, PES 14 6.907-662.0 1 piece(s) Flat pleated filter made from polyester fleece, rot-resistant and suitable for dust class M. Flat pleated filter, PES 15 6.904-360.0 1 piece(s) Polyester fleece, rot-proof, dust class M. 15 15 15 15 15 15 15 15			,(.)			-5	
Flat pleated filter, PTFE 18 6.907-455.0 1 piece(s) Polyester fleece, rot-proof, dust class M (also for NT 65/2 Eco / Me / Tc and NT 72/2 Eco Tc). 19 6.907-449.0 1 piece(s) Polyester fleece, rot-proof, dust class M (also for NT 65/2 Eco / Me / Tc and NT 72/2 Eco Tc). 19 6.907-449.0 1 piece(s) Polyester fleece, rot-proof, dust class M. Particularly suitable for very adhesive materials. 19 6.907-449.0 1 piece(s) Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners. 19 6.907-449.0 1 piece(s) Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners. 19 6.907-449.0 1 piece(s) Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners. 19 6.907-449.0 1 piece(s) Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners.	-	14 6.907-662.0	1 piece(s)			14	
NT 72/2 Eco Tc). 17 6.907-277.0 1 piece(s) Polyester fleece, rot-proof, dust class M. 17 18 18 19 19 19 19 19	Flat pleated filter, PES					15	
Flat pleated filter, PTFE 18 6.907-455.0 1 piece(s) Polyester fleece, rot-proof, dust class M. 17 18 18 18 18 18 18		16 6.904-284.0	1 piece(s)			16	
Flat pleated filter, PTFE Flat pleated filter, PTFE 18 6.907-455.0 1 piece(s) Polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners, dust class M. Particularly suitable for very adhesive materials. 19 6.907-449.0 1 piece(s) Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners. 19 0.907-449.0 1 piece(s) Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners.		17 6007 2770	1 pieco(c)	+		17	
Flat pleated filter, PTFE 18 6.907-455.0 1 piece(s) Polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners, dust class M. Particularly suitable for very adhesive materials. 19 6.907-449.0 1 piece(s) Polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners, dust class M. Particularly suitable for very adhesive materials. 19 6.907-449.0 1 piece(s) Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners. 19 6.907-449.0 1 piece(s)	Elat pleated filter DTEE	17 0.907-277.0	1 hiere(2)		rotyester freece, for-proof, dost class M.	17	
dust class M. Particularly suitable for very adhesive materials. 19 6.907-449.0 1 piece(s) Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners.		18 6.907-455 0	1 piece(s)	1	Polyester fleece with PTFE coating for single-motor Tact and An vacuum cleaners	18	
Particularly suitable for very adhesive materials.		19 6.907-449.0	1 piece(s)			19	
■ NEW ■ Included in the scope of supply. □ Available accessories. More Kārcher original accessories can be found on the following pages.			1		Particularly suitable for very adhesive materials.		











	Order	no. Quantity	Price	Description		NT 75/2 Tact* Me Tr Adv / NT 75/2 Tact* Me Tc / NT 65/2 Tact* Tact* Me NT 75/2 Tact* Me NT 75/2 Tact* Me NT 75/2 Tact* Me NT 75/2 Tact* Me NT 75/1 Tact Te Cc NT 40/1 Tact Te L NT 30/1 AD Te L / NT 30/1 AD Te L NT 30/1 AD Te L / NT 30/1 AD Te L NT 20/1 AD Te L / NT 20/1 AD L NT 20/1 AD Te L / NT 20/1 AD L NT 20/2 Adv NT 70/2 Adv NT 70/1 Adv NT 7
Coarse dirt filter for wet vacuuming						
Coarse dirt filter	20 6.904	-287.0 1 piece(s)		Metal, perforated, not suitable for dry use.	20	
Foam filter	21 2.889	-083.0 1 piece(s)		Foam filter for wet vacuuming, alternative to cartridge filter.	21	
Fabric filter						
Membrane filter for the new Tact and Ap range	22 2.889	-281.0		Additional fleece membrane filter for machines in the Tact and Ap range. Pulled directly over the container, it allows vacuuming without a filter bag. Washable and reusable.	22	
Membrane filter	23 6.906	-103.0 1 piece(s)		Polyester needle fleece, washable (40 °C).	23	
	24 6.904	-282.0 1 piece(s)		Polyester needle fleece, dust class M, washable (40 °C). Not suitable for dust class H	24	
				applications.		
Plastic bag for dust-free disposal	1 25 2 222	4500 140 : 1		DE statistic transfer del Constituent 40 m	25	
Plastic bag for dust-free disposal		-158.0 10 piece(s		PE plastic bag for dust-free disposal. 10 pc.	25	
Disposal bag PU certified for M and H class					26	
Plastic bag for dust-free disposal						
r lastic bag for dost free disposar		-698.0 10 piece(s -886.0 10 piece(s	_		27	

28 | 6.596-886.0 | 10 piece(s) |

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kârcher original accessories can be found on the following pages.

SUCTION NOZZLES, SUCTION TUBES AND BENDS



Only the right accessories in the right combination make a vacuum cleaner the ideal machine. Every cleaning task can be carried out using efficient and durable floor nozzles and small











	Order no. Quantity ID	Length Width Price	e Description		NT 75/2 Tact* Me Tc Adv NT 75/2 Tact* Me Tc Adv NT 75/2 Tact* Me Tc / NT 65/2 Tact* NT 75/2 Tact* Me V NT 65/2 Tact* NT 75/2 Tact* Me / NT 65/2 Tact* NT 75/2 Tact* Me / NT 65/2 Tact* NT 75/2 Tact* De / NT 65/2 Ap NT 75/2 Ap Me Tc / NT 65/2 Ap NT 75/2 Ap Me Tc / NT 65/2 Ap NT 75/2 Ap Me Tc / NT 65/2 Ap NT 75/2 Ap Tec / NT 76/2 Ap NT 76/3 Ap Tec / NT 76/3 Ab NT 76/3 Ab Tc / Ab NT 76/4 Ab Tc /	VT 55/1 Tact Bs VT 35/1 Tact Bs
Car cleaning nozzles	Order no. Quantity ID	Length Width Price	Description			2 2
Car nozzle	1 6.900-952.0 1 piece(s) ID 40	90 mm	Plastic.	1		
	2 6.906-108.0 1 piece(s) ID 35	90 mm		2		
Turbo nozzles						
Turbo upholstery nozzle	3 2.860-113.0 1 piece(s) ID 32	160 mm	Upholstery nozzle, plastic, with reduction bushing ID 35/32.	3		
Turbo floor nozzle	4 2.860-114.0 1 piece(s) ID 32	270 mm	Floor nozzle, plastic, with reduction bushing ID 35/32,			
		[270 11111]		4		
Figur nozzies		276 11111	270 mm.	4		
Floor nozzles ID 40 wet/dry floor nozzle	5 6.907-408.0 1 piece(s) ID 40	360 mm		5		
ID 40 wet/dry floor nozzle Wet/Dry floor nozzle standard	6 2.889-173.0 ■ 1 piece(s) ID 35		270 mm. Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees	5 6		
ID 40 wet/dry floor nozzle		360 mm	270 mm. Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). 300 mm wide, anthracite-coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Including brush strips	5		
ID 40 wet/dry floor nozzle Wet/Dry floor nozzle standard	6 2.889-173.0 ■ 1 piece(s) ID 35	360 mm	270 mm. Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). 300 mm wide, anthracite-coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Including brush strips and squeegees. Standard floor nozzle, anthracite-coloured, NW 40, with replaceable brush strips and squeegees. Suitable for all wet	5		
ID 40 wet/dry floor nozzle Wet/Dry floor nozzle standard Standard floor nozzle NW40	6 2.889-173.0 1 piece(s) ID 35 7 2.889-174.0	360 mm 300 mm	Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). 300 mm wide, anthracite-coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Including brush strips and squeegees. Standard floor nozzle, anthracite-coloured, NW 40, with replaceable brush strips and squeegees. Suitable for all wet and dry applications. 360 mm wide wet and dry floor nozzle with easy-to-change inserts. Including brush strips and squeegees. Multi-purpose nozzle (ID 35) for wet vacuum cleaning of large areas. The squeegee and brush can be replaced quickly and easily.	6		
ID 40 wet/dry floor nozzle Wet/Dry floor nozzle standard Standard floor nozzle NW40 Wet and dry floor nozzle Adv	6 2.889-173.0 ■ 1 piece(s) ID 35 7 2.889-174.0 8 2.889-152.0 ■ 1 piece(s) ID 35	360 mm 300 mm	Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). 300 mm wide, anthracite-coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Including brush strips and squeegees. Standard floor nozzle, anthracite-coloured, NW 40, with replaceable brush strips and squeegees. Suitable for all wet and dry applications. 360 mm wide wet and dry floor nozzle with easy-to-change inserts. Including brush strips and squeegees. Multi-purpose nozzle (ID 35) for wet vacuum cleaning of large areas. The squeegee and brush can be replaced quickly and easily. 360 mm wide wet and dry floor nozzle with easy-to-change	6 7		
ID 40 wet/dry floor nozzle Wet/Dry floor nozzle standard Standard floor nozzle NW40 Wet and dry floor nozzle Adv Wet and dry floor nozzle	6 2.889-173.0 1 piece(s) ID 35 7 2.889-174.0 8 2.889-152.0 1 piece(s) ID 35 9 2.889-118.0 1 piece(s) ID 35	360 mm 300 mm 360 mm	Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). 300 mm wide, anthracite-coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Including brush strips and squeegees. Standard floor nozzle, anthracite-coloured, NW 40, with replaceable brush strips and squeegees. Suitable for all wet and dry applications. 360 mm wide wet and dry floor nozzle with easy-to-change inserts. Including brush strips and squeegees. Multi-purpose nozzle (ID 35) for wet vacuum cleaning of large areas. The squeegee and brush can be replaced quickly and easily.	5 6 7 8 8 9 9		
Wet/Dry floor nozzle standard Standard floor nozzle NW40 Wet and dry floor nozzle Adv Wet and dry floor nozzle Wet and dry floor nozzle	6 2.889-173.0 1 piece(s) ID 35 7 2.889-174.0 8 2.889-152.0 1 piece(s) ID 35 9 2.889-118.0 1 piece(s) ID 35 10 2.889-153.0 1 piece(s) ID 40	360 mm 360 mm 400 mm	Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). 300 mm wide, anthracite-coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Including brush strips and squeegees. Standard floor nozzle, anthracite-coloured, NW 40, with replaceable brush strips and squeegees. Suitable for all wet and dry applications. 360 mm wide wet and dry floor nozzle with easy-to-change inserts. Including brush strips and squeegees. Multi-purpose nozzle (ID 35) for wet vacuum cleaning of large areas. The squeegee and brush can be replaced quickly and easily. 360 mm wide wet and dry floor nozzle with easy-to-change inserts, squeegees. Wet/Dry floor nozzle, NW 35, 300 mm wide, grey. Including	5 6 6 7 8 8 9 10 10		

NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

























	Order no.	Quantity		Length		_	Description		NT 75/2 Tact* Me Tc Adv NT 75/2 Tact* Me Tc Adv NT 75/2 Tact* Me Tc Adv NT 55/2 Tact* Me Tc Adv NT 55/2 Tact* Me Tc Adv NT 50/1 Tact Te L NT 40/1 Tact Te L NT 30/1 Tact Te L NT 30/1 Apt E NT 30/1 Apt E NT 30/1 Apt E NT 30/1 Apt E NT 20/1 Apt Tc Art 20/1 Ap NT 20/2 Abt Tc Art 20/1 Ap NT 20/2 Abt Tc Art 20/1 Ap NT 70/2 Abt Tc Art 20/2 Abt Classic Edition NT 70/2 Abt Classic Edition NT 70/2 Abt Classic Edition NT 50/2 Abt Classic Edition NT 50/1 Abt Classic Edition NT 50/2 Abt Classic Edition NT 50/1 Abt Classic Edition
Wet and dry floor nozzle	14 4.763-244.0	J 1 piece(s)	ID 40		360 mm		Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0).	14	
Wet and dry floor nozzle, non-interchangeable	15 4.130-399.0	1 piece(s)	ID 40		450 mm	1	Aluminium floor nozzle, grounded, non-interchangeable, 450 mm, height adjustable. As a standard accessory for NT 80/1 B1 M S and optional for NT 75/1 Me Ec H Z22.	15	
Wet and dry floor nozzle	16 6.906-512.0	1 piece(s)	ID 35		300 mm		Plastic with rollers, brush strips (6.903-278.0), squeegees (6.903-277.0).	16	
Multi-purpose nozzle, wet/dry	17 6.903-018.0	1 piece(s)	ID 40		370 mm	1	Aluminium with height-adjustable rollers, brush strips (6.903-064.0) and squeegees (6.903-081.0, oil-resistant).	17	
Multi-purpose nozzle, wet/dry	18 6.906-383.0	1 piece(s)	ID 40		450 mm		Aluminium with height-adjustable rollers, brush strips (6.903-065.0) and squeegees (6.906-146.0).	18	
	19 6.906-384.0	1 piece(s)	ID 35		370 mm		Aluminium with height-adjustable rollers, brush strips (6.903-064.0) and squeegees (6.903-081.0, oil-resistant).	19	
Combi-nozzles, dry Combi-nozzle, dry	20 6.906-511.0	1 piece(s)	ID 35		270 mm	1	Plastic with stainless steel soleplate, switchable, with ID 35 connection.	20	
Radiator brushes							1		
Radiator brush	21 6.903-034.0	1 piece(s)	ID 35				Plastic, for crevice nozzle (6.900-385.0).	21	
Oven nozzles Oven nozzle	22 4.130-104.0	1 piece(s)	ID 35		350 mm		Aluminium, for oven cleaning with squeegee 6.900-517.0	22	
	23 4.130-173.0	1 pioco/s)	ID 3E		350 mm		and support lip 6.900-518.0, each 2 ×.	22	
Crevice nozzles	25 7.130-1/3.0	T bicce(2)	10000		220 11111	1	For cleaning ovens with scraper.	23	
Crevice nozzle NT Tact ID 35	24 2.889-159.0	1 niere(s)	ID 35	225 mm			Crevice nozzle ID 35, for new Tact range.	24	
Crevice nozzle NT Tact ID 40	25 2.889-160.0			225 mm			Crevice nozzle ID 40, for new Tact range.	25	
Crevice nozzle	26 9.770-877.0			300 mm		1	Plastic.	26	
	27 9.770-638.0	_		350 mm				27	
	28 6.900-385.0			210 mm				28	
	29 6.900-922.0	_		500 mm		1	Metal.	29	
	30 6.903-033.0			290 mm			Plastic.	30	
	31 6.905-817.0	1 piece(s)	ID 40	400 mm			Metal.	31	
	32 4.763-243.0			290 mm			Plastic, non-interchangeable.	32	
	33 6.906-240.0	1 piece(s)	ID 35	250 mm			Plastic.	33	
■ Included in the scope of supply	. Available acces	ssories. Mor	re Kärcher o	riginal access	ories can b	oe found	on the following pages.		

VACUUM CLEANERS





















	Order no	Quantity	ID.	Length	Width	rice. Description		NT 75/2 Tact² Me Tc Adv NT 75/2 Tact² Me Tc / NT 65/2 Tact² Tc NT 55/2 Tact² Me I	NT 75/2 Tact? Me / NT 65/2 Tact? NT 50/1 Tact Te L NT 45/1 Tact Te E	VT 40/1 Tact Te L NT 30/1 Tact Te L / NT 30/1 Tact L	NT 75/2 Ap Me Tc / NT 65/2 Ap NT 40/1 Ap L NT 30/1 An Te I	VT 30/1 Ap Te / NT 20/1 Ap VT 22/1 Ap Te / NT 20/1 Ap Te / NT 20/1 Ap	VT 22/1 Ap L VT 70/3 Me Tc VT 70/2 Me Tc	NT 70/3 TC NT 70/2 TC NT 70/2 Adv	NT 70/2 Me NT 70/3 NT 70/2	NT 70/1 NT 48/1 Te / NT 48/1 NT 27/1 Me Adv	VT 27/1 Me VT 27/1 Adv VT 27/1	VT 90/2 Me Classic Edition VT 70/2 Me Classic Edition	NT 50/1 Me Classic Edition NT 30/1 Me Classic Edition / NT 30/1 Me Classic Edition / NT 20/1 Me Classic Edition NT 75/1 Me Ec H Z22	VT 80/1 B1 M S NT 75/1 Tact Me Te H NT 50/1 Tact Te H / NT 30/1 Tact Te H / NT 50/1 Tact Te M	VT 30/1 Tact Te M VT 611 Mwf VT 611 Eco K
Pipe dusting nozzles	Order no.	Quantity	ID	Length	Width P	rice Description		ZZZZ	ZZZ	ZZZ	ZZZZ	z z z z	ZZZZ	z z z	z z z	ZZZZ	z z z		z z z z	zzz	z z z z
Pipe brush 35/100	34 6.903-035.0	1 piece(s)	ID 35			Plastic, tube diameter 100 mm.	34	0 0 0													
ipe brush 35/100	34 6.903-035.0 35 6.903-036.0					Plastic, tube diameter 100 mm. Plastic, tube diameter 200 mm.	34						 	 	$\overline{}$						
Pipe brush 35/100 Pipe brush 35/200													 	 	$\overline{}$	 					
Pipe brush 35/100 Pipe brush 35/200 Suction brushes	35 6.903-036.0	1 piece(s)	ID 35		70 mm		35						 	 		 					
ipe brush 35/100 ipe brush 35/200 uction brushes	35 6.903-036.0 36 6.903-862.0	1 piece(s)	ID 35		70 mm 70 mm	Plastic, tube diameter 200 mm.							 	 							
ipe brush 35/100 ipe brush 35/200 uction brushes uction brush	35 6.903-036.0	1 piece(s)	ID 35			Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable.	35						 	 							
ipe brush 35/100 ipe brush 35/200 uction brushes uction brush ubber suction tools, nose 45°	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0	1 piece(s) 1 piece(s) 1 piece(s)	ID 35 ID 35 ID 32	220 mm		Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable.	35 36 37														
pe brush 35/100 pe brush 35/200 uction brushes uction brush ubber suction tools, nose 45°	35 6.903-862.0 37 6.903-887.0 38 6.902-104.0	1 piece(s) 1 piece(s) 1 piece(s) 1 piece(s)	ID 35 ID 35 ID 32 ID 35	220 mm 220 mm		Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable.	35 36 37 38														
ipe brush 35/100 ipe brush 35/200 uction brushes uction brush ubber suction tools, nose 45° ubber suction tool, nose 45°	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0	1 piece(s) 1 piece(s) 1 piece(s) 1 piece(s)	ID 35 ID 35 ID 32 ID 35			Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable.	35 36 37														
ipe brush 35/100 ipe brush 35/200 uction brushes uction brush ubber suction tools, nose 45° ubber suction tool, nose 45°	35 6.903-862.0 37 6.903-887.0 38 6.902-104.0	1 piece(s) 1 piece(s) 1 piece(s) 1 piece(s) 1 piece(s)	ID 35 ID 35 ID 32 ID 35 ID 40			Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2	35 36 37 38														
pe brush 35/100 pe brush 35/200 ction brushes ction brush bber suction tools, nose 45° bber suction tool, nose 45° de nozzles	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0	1 piece(s)	ID 35 ID 35 ID 32 ID 35 ID 40 ID 40		70 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv.	35 36 37 38 39														
pe brush 35/100 pe brush 35/200 ction brushes ction brush bber suction tools, nose 45° bber suction tool, nose 45° ide nozzles	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0	1 piece(s)	ID 35 ID 35 ID 32 ID 35 ID 40 ID 40		70 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L.	35 36 37 38 39														
pe brush 35/100 pe brush 35/200 ction brushes ction brush bber suction tools, nose 45° bber suction tool, nose 45° ide nozzles	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0	1 piece(s)	ID 35 ID 35 ID 32 ID 35 ID 40 ID 40		70 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv.	35 36 37 38 39 40														
pe brush 35/100 pe brush 35/200 uction brushes uction brush ubber suction tools, nose 45° ubber suction tool, nose 45° ide nozzles ide nozzle	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0	1 piece(s)	ID 35 ID 35 ID 32 ID 35 ID 40 ID 40 ID 40 ID 40		70 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L. For vacuuming large areas in combination with NT 70/1,	35 36 37 38 39 40														
pe brush 35/100 pe brush 35/200 Juction brushes Juction brush Jubber suction tools, nose 45° Jubber suction tool, nose 45°	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0 ■ 41 4.130-029.0 42 4.130-432.0	1 piece(s)	ID 35 ID 35 ID 32 ID 35 ID 40 ID 40 ID 40 ID 40 ID 40		660 mm 611 mm 644 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L. For vacuuming large areas in combination with NT 70/1, NT 70/2 or NT 70/3. Metal, height-adjustable, with brush strip set 6.906-751.0 and rubber strip set 6.906-750.0 for NT 55/1 Tact and NT 611 Eco. Metal, height-adjustable, brush strips, squeegees (for	35 36 37 38 39 40 41 42														
pe brush 35/100 pe brush 35/200 petion brushes ction brush pubber suction tools, nose 45° pubber suction tool, nose 45° pubber	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0 41 4.130-029.0 42 4.130-432.0 43 4.130-401.0	1 piece(s)	ID 35 ID 35 ID 32 ID 35 ID 40 ID 40 ID 40 ID 40 ID 40		660 mm 611 mm 611 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L. For vacuuming large areas in combination with NT 70/1, NT 70/2 or NT 70/3. Metal, height-adjustable, with brush strip set 6.906-751.0 and rubber strip set 6.906-750.0 for NT 55/1 Tact and NT 611 Eco.	36 37 38 39 40 41 42 43														
ipe brush 35/100 ipe brush 35/200 uction brushes uction brush ubber suction tools, nose 45° ubber suction tool, nose 45° vide nozzles vide nozzle vide nozzle vide nozzle	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0 41 4.130-029.0 42 4.130-432.0 43 4.130-401.0	1 piece(s)	ID 35 ID 35 ID 32 ID 35 ID 40		660 mm 611 mm 611 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L. For vacuuming large areas in combination with NT 70/1, NT 70/2 or NT 70/3. Metal, height-adjustable, with brush strip set 6.906-751.0 and rubber strip set 6.906-750.0 for NT 55/1 Tact and NT 611 Eco. Metal, height-adjustable, brush strips, squeegees (for	36 37 38 39 40 41 42 43														
ripe brush 35/100 ripe brush 35/200 uction brushes uction brush ubber suction tools, nose 45° ubber suction tool, nose 45° ubber suction tool, nose 45° vide nozzles Vide nozzle Vide nozzle Vide nozzle lozzle kits lozzle kits	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0 ■ 41 4.130-029.0 42 4.130-432.0 43 4.130-401.0 44 4.130-400.0	1 piece(s)	ID 35 ID 35 ID 35 ID 32 ID 35 ID 40	220 mm	660 mm 611 mm 611 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L. For vacuuming large areas in combination with NT 70/1, NT 70/2 or NT 70/3. Metal, height-adjustable, with brush strip set 6.906-751.0 and rubber strip set 6.906-750.0 for NT 55/1 Tact and NT 611 Eco. Metal, height-adjustable, brush strips, squeegees (for Tc variants). (Also for NT 72/2 Eco Tc). Crevice nozzle, upholstery nozzle, round brush, electrically conductive.	35 36 37 38 39 40 41 42 43 44														
Pripe brush 35/100 Pripe brush 35/200 Pripe brush 3	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0 41 4.130-029.0 42 4.130-432.0 43 4.130-401.0 44 4.130-400.0 45 2.860-116.0	1 piece(s)	ID 35 ID 35 ID 35 ID 32 ID 35 ID 40 ID 40 ID 40 ID 40 ID 40 ID 40 ID 35	220 mm	660 mm 611 mm 611 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L. For vacuuming large areas in combination with NT 70/1, NT 70/2 or NT 70/3. Metal, height-adjustable, with brush strip set 6.906-751.0 and rubber strip set 6.906-750.0 for NT 55/1 Tact and NT 611 Eco. Metal, height-adjustable, brush strips, squeegees (for Tc variants). (Also for NT 72/2 Eco Tc). Crevice nozzle, upholstery nozzle, round brush, electrically conductive. Plastic, hard transparent bristles, 120 × 45 mm.	35 36 37 38 39 40 41 42 43 44 45														
	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0 ■ 41 4.130-029.0 42 4.130-432.0 43 4.130-401.0 44 4.130-400.0	1 piece(s)	ID 35 ID 35 ID 35 ID 32 ID 35 ID 40 ID 40 ID 40 ID 40 ID 40 ID 40 ID 35	220 mm	660 mm 611 mm 611 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L. For vacuuming large areas in combination with NT 70/1, NT 70/2 or NT 70/3. Metal, height-adjustable, with brush strip set 6.906-751.0 and rubber strip set 6.906-750.0 for NT 55/1 Tact and NT 611 Eco. Metal, height-adjustable, brush strips, squeegees (for Tc variants). (Also for NT 72/2 Eco Tc). Crevice nozzle, upholstery nozzle, round brush, electrically conductive.	35 36 37 38 39 40 41 42 43 44														
ripe brush 35/100 ripe brush 35/200 uction brushes uction brush ubber suction tools, nose 45° rubber suction tool, nose 45° rubber suction tool, nose 45° vide nozzles Vide nozzle Vide nozzle lozzle kits lozzle kit ult-purpose brush Multi-purpose brush,	35 6.903-036.0 36 6.903-862.0 37 6.903-887.0 38 6.902-104.0 39 6.902-105.0 40 2.130-002.0 41 4.130-029.0 42 4.130-432.0 43 4.130-401.0 44 4.130-400.0 45 2.860-116.0	1 piece(s)	ID 35 ID 35 ID 35 ID 32 ID 35 ID 40 ID 40 ID 40 ID 40 ID 40 ID 40 ID 35	220 mm	660 mm 611 mm 611 mm	Plastic, tube diameter 200 mm. Natural bristles (ox hair), rotatable. Plastic brush, rotatable. For vacuuming machines, oil-resistant. Height-adjustable wide metal nozzle with brush strips: exclusively for wet and dry vacuum cleaner NT 75/2 Tact Me Tc Adv. For vacuuming large areas with the NT 50/1 Tact Te L. For vacuuming large areas in combination with NT 70/1, NT 70/2 or NT 70/3. Metal, height-adjustable, with brush strip set 6.906-751.0 and rubber strip set 6.906-750.0 for NT 55/1 Tact and NT 611 Eco. Metal, height-adjustable, brush strips, squeegees (for Tc variants). (Also for NT 72/2 Eco Tc). Crevice nozzle, upholstery nozzle, round brush, electrically conductive. Plastic, hard transparent bristles, 120 × 45 mm. Natural bristles (ox hair), bristle attachment 120 × 45 mm,	35 36 37 38 39 40 41 42 43 44 45														

VACUUM CLEANERS













Chairless steel systim tube set	40	Order no.	Quantity			Width	Price	Description Strickers tree outside tube set (2, v. 0.5.5 m)		NT 75/2 Tact² Me Tc Adv	NT 75/2 Tact ² Me Tc / NT 65/2 Tact ² Tc	NT 55/2 Tact* Me / NT 65/2 Tact*	NT 50/1 Tack Te L NT 45/1 Tack Te Ec	40/1 Tact Te L 30/1 Tact Te L / NT	75/2 Ap Me Tc / NT 65/2 40/1 Ap L	30/1 Ap Te L 30/1 Ap L	NT 20/1 Ap Te / NT 20/1 Ap NT 22/1 Ap Te L	NT 22/1 Ap L NT 70/3 MP TC		NT 70/2 TC NT 70/2 Adv	70/2	NT 70/2 NT 70/1	NT 48/1 TE / NT 48/1 NT 27/1 Me Adv	NT 27/1 Me NT 27/1 Adv	27/1 90/2 Me	70/2 Me 50/2 Me	50/1 Me 38/1 Me	75/1 Me Ec H Z22 80/1 B1 M S 75/1 Tart Mo To H	NT 50/1 Tact Te H / NT 30/1 Tact Te H / NT 50/1 Tact Te M NT 30/1 Tact Te M	NT 611 Mwf NT 611 Eco K	NT 35/1 Tact Bs NT 35/1 Tact Bs
Stainless steel suction tube set NW35, 550 mm	49	2.889-192.0	1 piece(s)	ID 35	550 mm			Stainless steel suction tube set $(2 \times 0.55 \text{ m})$.	49				•																		
Stainless steel suction tube set NW40, 550 mm	50	2.889-194.0	1 piece(s)	ID 40	550 mm			Stainless steel suction tube set (2 × 0.55 m).	50																						
Suction tube set	51	2.889-175.0 ■	1 piece(s)	ID 35	505 mm			Stainless steel suction tube set, NW 35, 2-piece, each 0.55 mm.	51																						
Suction tube		6.902-081.0	1 piece(s)		0.5 m			For use in wet or damp environments or for wet vacuuming.	52			_ _																			
	53	6.906-531.0	1 piece(s)	ID 40	1 m			For use in wet or damp environments or for wet vacuuming.	53																				Ш		
Suction tubes, plastic	l =4	1 2 000 210 0	1 1 20050(5)	LID 25	FOE mm			Plastic systian tube set NIM 25 gray 2 piece each 0.5 m	-4			1 1		1 1				1 – 1	1 1				1 1	1 1 1				1 1			
Suction tube set Suction tube	_	2.889-218.0 a 6.900-384.0	_		505 mm 0.5 m			Plastic suction tube set, NW 35, grey, 2-piece, each 0.5 m. Plastic.	54 55					,				-							П				+++		
Suction tubes, metal	33	0.300-384.0	1 piece(s)	10 33	0.5 111			FIOSIL.	33					1											ш				\bot	\dashv	
Suction tube set, chrome-plated, NW35, 550 mm	56	2.889-191.0	1 piece(s)	ID 35	550 mm			Suction tube set, metal, chrome-plated, NW 35, 2-piece, each 0.55 mm.	56						-																\Box
Suction tube, chrome-plated	57	6.902-074.0	1 piece(s)	ID 35	505 mm			Suction tube, metal, chrome-plated, NW 35, length: 0.5 m.	57				\top				•												+	\Box	
Suction tube	58	6.900-514.0	1 piece(s)	ID 35	0.5 m			Metal, chromium-plated.	58																•			•			
Suction tube		6.900-275.0	1 piece(s)		0.55 m			The suction tube (NW 40, 2×0.5 m) made from chrome- plated metal is standard in almost all commercial vacuum cleaners with twin motor. Optional for commercial single motor NT vacuum cleaner with suction hose NW 40.	59	•		• •			•			•		• •	• •			0 0	- -		•				
		6.902-152.0	1 piece(s)		0.33 m			Suction pipe, metal, chrome-plated, 0.33 m, ID 35.	60		\vdash	\perp	_	\perp			•						$\perp \perp$		_				$\perp \perp \mid$	\square	
Suction tube, non-interchangeable	61	4.025-372.0	1 piece(s)	ID 40	1 m			Metal, chrome-plated – non-interchangeable with screw connection. Only suitable for use with NT 80/1 B1 M, NT 80/1 B1 M S and NT 75/1 Me Ec H Z22.	61																			• •			
Bends, stainless steel		1																													
Bend, stainless steel, ID 35		6.903-141.0 6.902-079.0						Stainless steel.	62																						
Bend, plastic					, .																							, ,			
Bend Adv		2.889-170.0						Ergonomic bend for the new clip system.	64			\rightarrow	•																	\Box	\perp
ID 40 bend	65	2.889-171.0	1 piece(s)	ID 40				Bend for the new clip system in nominal size ID 40.	65																					Ш	

■ NEW ■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.















78

												IT 75/2 Tact² Me Tc Adv	ة إ	IT 75/2 Tact* Me / NT 65/2 Tact* IT 50/1 Tact Te L	1 .	IT 75/2 Ap Me TC / NT 65/2 Ap IT 40/1 Ap L	T 30/1 Ap Te L T 30/1 Ap L	IT 20/1 Ap Te / NT 20/1 Ap IT 22/1 Ap Te L	T 22/1 ApL	I 70/2 Me IC IT 70/3 TC	17.7/2.17 17.7/2.Me	Τ 70/3 Τ 70/2	IT 70/1 IT 48/1 Te / NT 48/1	17.27/1 Me 17.27/1 Adv	T 27/1 IT 90/2 Me Classic Edition	IT 70/2 Me Classic Edition IT 50/2 Me Classic Edition	NT 50/1 Me Classic Edition NT 38/1 Me Classic Edition / NT 30/1 Me Classic Edition NT 75/1 Me EC H 222	oT that 10 U / U at that 1/0	IT 50/1 Tact Te H / NT 30/1 Tact Te H / NT 50/1 Tact Te M IT 30/1 Tact Te M IT 30/1 Tact Te M	T 51 Tack BS	IT 35/1 Tact Bs
ID 40 bend, electrically conductive	Order no. 66 2.889-172		ty ID e(s) ID 40	Leng	th Width	riico	Bend for the new clip sys	stem in nominal si	ize ID 40.		66	+		- - .																+-+-	7
,,							Electrically conductive de high concentrations of fin	esign. Particularly																							
Bend	67 2.889-148	3.0 1 piece	e(s) ID 35				Ergonomic bend for the n	new clip system. W	With airflow		67																				_
							control slide, in an antista						\perp		1010							\square	\perp				\perp	$\rightarrow \rightarrow$		+	_
Bend Adv, electrically conductive	68 2.889-168	3.0 1 piece	e(s) ID 35				Ergonomic bend for the n conductive design. Particution of fine dust.			ons	68																		• •		
Elbow, standard	69 2.889-199	0.0 ■ 1 piece	e(s) ID 35				Plastic bend, grey, with C	. 35 clip system.			 69																				
Plastic bend	70 5.031-718		e(s) ID 35				Plastic with C 35 clip syst	tem.			70																				ב
Bend, plastic, electrically conductive	71 5.031-939	0.0 1 piece	e(s) ID 35				Plastic, ID 35 with C 35 cl	lip system, electri	ically conductive	e.	71																				٥
Bend, plastic	72 6.902-009	0.0 1 piece	e(s) ID 35				Plastic, ID 35.				72																				J
Bend, plastic, electrically conductive	73 5.032-427	7.0 1 piece	e(s) ID 40				Plastic, with C 40 clip sys	tem, electrically c	conductive.		73																				
Bend, plastic, antistatic	74 5.033-583	3.0 1 piece	e(s) ID 35				Plastic, C 35 clip system,	anti-static design.	l.		74																				
Plastic bend	75 5.031-904	1.0 1 piece	e(s) ID 40				Plastic with C 40 clip syst	tem.			75																				
Bends, metal																															
Bend, metal	76 6.900-519	0.0 1 piece	e(s) ID 35				Metal, ID 35.				76																				١
	77 6.900-276						Metal, ID 40.				 77						\Box											$\bot \bot $		1 0 0	
Bend, metal, non-interchangeable	78 4.036-032	2.0 1 piece	e(s) ID 40				Non-interchangeable bene vacuum cleaners.	d ID 40, for type 7	Z22 safety		78																=	-			
			-																												_

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

ADAPTERS



With connection adapters from Kärcher, suction hoses can be connected to all conventional power tools.

























-	

	Order no.	Quantity	ID	Price	Description		NT 75/2 Tact² Me Tc Adv / NT 75/2 Tact² Me Tc / NT 65/2 Tact² NT 55/2 Tact² Me I / NT 75/2 Tact² Me / NT 65/2 Tact² NT 55/2 Tact² Me I / NT 75/2 Tact² Me / NT 65/2 Tact² NT 55/2 Tact² Me I / NT 75/2 Tact² Me / NT 65/2 Tact² NT 40/1 Tact Te L NT 40/1 Tact Te L NT 30/1 Apt Te NT 30/1 Apt Te NT 30/1 Apt Te NT 20/1 Apt Te NT 75/2 Apt Te I NT 70/2 Apt NT 70/2 Me I NT 70/3 Tc NT 70/2 Apt I Te I NT 48/1 NT 70/2 Apt I Te I NT 48/1 NT 70/2 Apt Te I NT 70/2 Apt I Tact Te I NT 70/2 Apt I Te I Te I NT 70/2 Apt I Te I NT 70/2 Apt I Te I NT 70/2 Apt I Te I T
Set of reduction/expansion bushings							
Set of reduction/expansion bushings	1 2.860-117.0	1 piece(s)			ID 40/35, ID 35/32 (tube -> nozzle), plastic.	1	
Reducers (tube -> nozzle) Peduction bushing	2 6.902-017.0	1 nioco(s)	LID 40	1	From ID 40 to ID 35, plastic.	2	
Reduction bushing Reducer from ID 35 to ID 32	3 6.902-072.0			+	From ID 35 to ID 32, metal.	3	
Expansion pieces (tube -> nozzle)	3 0.302-072.0	1 piece(s)	10 33		Trom ib 55 to ib 52, metal.		
Adapter	4 5.453-019.0	1 piece(s)	ID 40	I	From ID 40 to ID 61, plastic.	4	
Adapter ID 35-40 (tube -> nozzle)	5 6.902-084.0			_	From ID 35 to ID 40, plastic.	5	
Connection adapter C ID (clip to cone), election							
Connection adapter C ID 35	6 5.407-112.0	1 piece(s)	ID 35		C 35 hose connection for ID 35 accessories, electrically conductive.	6	
Connection adapter C ID 40	7 5.407-109.0		ID 40		C 40 hose connection for ID 35 accessories, electrically conductive.	7	
	8 5.407-111.0	1 piece(s)	ID 40		C 40 hose connection for ID 40 accessories, electrically conductive.	8	
Adapter for electric power tools, screwable			1			1 -1	
Attachment rubber sleeve	9 5.303-877.0				Rubber tool socket for screwing onto the suction hose.	9	
Adapter for electric power tools, screwable, ID 35		_			Plastic, adjustable from ID 26-36.	10	
15 33	11 5.453-026.0 12 6.902-059.0		ID 35		Inside Ø 28.6 mm, outside Ø 37.3 mm / 38.8 mm. Inside Ø 32 mm, outside Ø 39 mm.	11	
	13 6.902-095.0				Inside Ø 32 mm, outside Ø 34 / 38.8 mm, electrically conductive.	13	
Connection adapter for power tools, clip-on			10 33		miside & 20 mm, obtaide & 547 50.0 mm, electrically conductive.	13	
Tool collar ID 35, clip-on	14 2.889-151.0	1	ID 35		Tool adapter with a rubber fixture and airflow control slide for the new clip system. Suitable for all current electric tools.	14	
Connection adapter for power tools, C 35,	15 5.453-042.0	1 piece(s)	ID 35		Plastic, adjustable from ID 26-36 (Te / Eco M / H), electrically conductive.	15	
electrically conductive	16 5.453-048.0				Inside Ø 25.4 mm, outside Ø 34.6 mm / 38 mm, electrically conductive.	16	
	17 5.453-050.0	1 piece(s)	ID 35		Inside Ø 27 mm, outside Ø 36.5 mm / 38.8 mm, electrically conductive.	17	
Reduction bushings Reduction bushing	18 5.407-108.0	1 piece(s)	ID 40		From C 40 hose with outer thread 35 for connection adapter,	18	
			ļ		screwable, ID 35.		
	19 5.407-113.0	1 piece(s)	ID 40		Reduction bushing from clip C 40 to clip C 35.	19	
Connection adapters Adapter, ID 32/35,	20 6.902-077.0	1 ninco(c)	ID 22		For connecting two suction hoses (not ESB 28 and 34).	20	
with internal thread	20 6.902-077.0	1 piece(s)	ID 32		For conflecting two socioin noses (not est 26 and 34).	20	
Adapter, ID 40, with internal thread	21 6.900-286.0	1 piece(s)	ID 40		For connecting two suction hoses, threaded at both ends.	21	
Adapter, ID 61, with female thread	22 6.902-078.0	1 piece(s)	ID 61		1	22	
Y-adapter kit			•				
Y-adapter kit	23 2.637-217.0	1 piece(s)	ID 35		Distributor, plastic.	23	
■ NEW ■ Included in the scope of supply	y. 🛘 Available ac	cessories. N	lore Kärcher o	original ac	cessories can be found on the following pages.		

SUCTION HOSES



Extension hoses with the Kärcher clip system permit many hoses to be extended to the required length in a matter of seconds.

























Custing bases complete	Order no.	Quantity	ID	Length	Price	Description		NT 75/2 Tact² Me Tc Adv / NT 75/2 Tact² Me Tc / NT 65/2 Tact² Tc NT 55/2 Tact² Me I	NT 75/2 Tact² Me NT 65/2 Tact²	NT 50/1 Tact Te L NT 45/1 Tact Te EC	N 1 40,1 1 dCt Le L / N 1 30,1 1 dCt Le L NT 30,1 Tact L NT 75,2 Ap Me Tc / NT 65,2 Ap	NT 40/1 Ap L / NT 30/1 Ap Te L / NT 30/1 Ap L NT 20/1 Ap Te / NT 20/1 Ap	NT 22/1 Ap Te L / NT 22/1 Ap L NT 70/3 Me Tc / NT 70/2 Me Tc / NT 70/3 Tc	NT 70/2 TC NT 70/2 Adv NT 70/2 Adv	N 7 / / 2 / Me N 7 7 / 3 / N 7 7 / 2 N 7 7 / 1	NT 48/1 Te	NT 27/1 Me Adv NT 27/1 Me / NT 27/1 Adv	NT 27/1 NT 90/2 Me Classic Edition / NT 70/2 Me Classic Edition / NT 50/2 Me Classic	NT 50/1 Me Classic Edition NT 38/1 Me Classic Edition / NT 30/1 Me Classic NT 38/1 Me Ec H 222 / NT 80/1 B1 M S	NT 75/1 Tact Me Te H NT 50/1 Tact He / NT 30/1 Tact Te H / NT 50/1 Tact Te M	NT 30/1 Tact Te M NT 611 Mwf / NT 611 Eco K NT 55/1 Tact Bs / NT 35/1 Tact Bs
Suction hoses complete Suction hose, complete	1 4.440-263.0	1 nioco(s)	ID 40	4 m		Plastic.	1				_			ا ا ا							
Suction mose, complete	2 4.440-303.0			4 m	+	Oil-resistant.	2					-	-				+-	+++		+++	
	3 4.440-463.0	_	+	10 m	-	Plastic.	3		-			-				+	+	+++	+	+++	
	4 4.440-466.0	1 piece(s)	ID 40	10 m	+	Electrically conductive, plastic.	4					-	-			++-	+	+++		+++	+
Suction hose, complete, oil-resistant		1 piece(s)	ID 40	10 m		Oil-resistant.	5	-				-			-	++-	+	+++		+++	
Suction hose compl. B1 M L=8m	6 4.440-013.0	-		8 m	+	8 m long, electrically conductive suction hose, NW 35.	6	+	1515		++-	\Box	++;	7-1-	7	++	+-	+++	++-'	+++	
Section nose compiled in 2 cm		I piece(s)	1.5 .0	J		Screw connections cannot be mixed up.							.		ا اد						
Suction hose, complete	7 9.770-881.0	1 piece(s)	ID 40	2.5 m		Plastic.	7												•		
	8 9.755-263.0	1 piece(s)	ID 35	2.5 m		Plastic, with bend.	8														
	9 4.440-287.0	1 piece(s)	ID 35	4 m		Plastic.	9														
Suction hose, complete, 120°C	10 4.440-339.0	1 piece(s)	ID 35	2.5 m		Temperature resistant to 120 °C.	10														
Suction hose, complete	11 4.440-264.0	1 piece(s)	ID 61	4 m		Plastic.	11								3 0 0	1					
Suction hose, complete	12 4.440-328.0	1 piece(s)	ID 61	3 m		Industrial hose, PVC / elastomer with steel spiral, smooth inside.	12								J 0 0	1	П			\Box	
Suction hose, complete	13 4.440-467.0	1 piece(s)	ID 61	10 m		Plastic.	13								J 0 0	1					
Suction hose, complete, oil-resistant	14 4.440-613.0	1 piece(s)	ID 61	4 m		Oil-resistant.	14									1					
	15 4.440-614.0	1 piece(s)	ID 61	10 m			15]	1					
Suction hose, complete, electrically conductive	16 4.440-616.0	1 piece(s)	ID 61	4 m		Electrically conductive.	16						0 1		3 0 0	1					
Suction hose, complete	17 4.440-446.0	1 piece(s)	ID 27	3.5 m		Plastic, with connection bushing for power tools.	17														
	18 4.440-461.0	1 piece(s)	ID 27	7 m			18					$\sqcup \sqcup$	\rightarrow	$\bot\bot$	$\perp \perp$		$\perp \perp$	$\sqcup \sqcup$		$\sqcup \sqcup$	
Suction hose, complete, non-inter- changeable, electrically conductive	19 4.440-558.0	1 piece(s)	ID 40	4 m		Electrically conductive ID 40, 4 m, with non-interchangeable screw connections.	19]				•		
	20 4.440-815.0	1 piece(s)	ID 40	8 m		Electrically conductive ID 40, 8 m, with non-interchangeable	20							[
Commission to a contract to the contract to th						screw connections.			Ш			Ш					Щ	Ш		ш	
Complete suction hoses (clip system)	21 2.889-133.0	1 pioco(c)	I ID 35	2.5 m	1	2.5 m long suction hose with new clip fastener, C 35.	21	lolo			alol					1.1		1 1 1		LIGI	
Suction hose	22 2.889-133.0			2.5 III		2.5 m long suction nose with new clip fastener, C 35. 2 m suction hose with new clip fastener, C 35.	21		-			+++	++	++	++	++	+	+++		++++	
	23 2.889-135.0			4 m		4 m suction hose with new bayonet and clip fastener.	23	1414					++	++	++	++	+	+++		++++	
	24 2.889-134.0		ID 35	2.5 m		2.5 m suction hose with new bayonet and clip fastener.	24	++	+		-			++	++	++	+	+++		+++++	
Electrically conductive suction hose			_	2.5 m		Electrically conductive suction hose with new bayonet and clip	25	++	++		-	-		++	++	++	+	++	++-	++-+	_
					al accessor	fastener. Length: 2.5 m. les can be found on the following pages.															























-
47

	Order no.	Quantity		Length	Price	Description		NT 75/2 Tact² Me Tc Adv / NT 75/2 Tact² Me Tc / NT 65/2 Tact² Tc NT 55/2 Tact² Me I NT 75/2 Tact² Me	NT 65/2 Tact* NT 50/1 Tact Te L NT 45/1 Tact Te Ec	NT 40/1 Tact Te L / NT 30/1 Tact Te L NT 30/1 Tact L	NT 75/2 Ap Me TC / NT 65/2 Ap NT 40/1 Ap L / NT 30/1 Ap Te L / NT 30/1 Ap L	20/1 Ap Te / NT 20/1 Ap	N I 22/1 AP Le L / N I 22/1 AP L NT 70/3 Me Tc / NT 70/2 Me Tc / NT 70/3 Tc	NT70/2 TC NT70/2 Adv	NT 70/2 Me NT 70/3 / NT 70/2	NT 70/1 NT 48/1 Te	48/1	NT 27/1 Me / NT 27/1 Adv NT 27/1	NT FOLA Me Classic Edition / NT 70/2 Me Classic Edition / NT 50/2 Me Classic Edition	N 1 30/1 Me classic cotition N 1 30/1 Me classic Edition / NT 20/1 Me Classic Edition / NT 20/1 Me Classic Edition	75/1 Tact Me Te H 50/1 Tact Te H / NT 30/1 Tact Te H	30/1 Tact Te M 511 Mwf / NT 611 Eco K 55/1 Tact Bs / NT 35/1 Tact Bs
Electrically conductive suction hose	26 2.889-137	0 1 piece(s)	ID 35	4 m		4 m suction hose with new bayonet and clip fastener. Electrically conductive.	26														-	-
Suction hose	27 2.889-138	0 1 piece(s)	ID 40	4 m		4 m long suction hose with new bayonet and clip fastener.	27															
	28 2.889-139	0 1 piece(s)	ID 40	2.5 m		Suction hose with new bayonet and clip fastener. Length: 2.5 m.	28															
Suction hose, oil-resistant	29 2.889-140	0 1 piece(s)	ID 40	4 m		Oil-resistant suction hose with new bayonet and clip fastener. Length: 4 m.	29															
Electrically conductive suction hose	30 2.889-141			4 m		4 m long, electrically conductive suction hose with new bayonet and clip fastener.	30										Ш	Ш				
	31 2.889-142			2.5 m		Suction hose, electrically conductive, with new bayonet and clip fastener. 2.5 m long,	31											Ш				
Suction hose, electrically conductive, C40 4m				4 m		Electrically conductive suction hose, ID 40. Length: 4 metres.	32					Ш						Ш		<u> </u>	ı	
Suction hose	33 4.440-626	_	_	2.5 m		With bend, C ID 35.	33						\perp						44	\perp		
Suction hose, electrically conductive				2.5 m		With bend, electrically conductive, C ID 35.	34			\perp	\vdash	-	+	\perp	\perp	\Box	\Box	44	++	++	•	
Suction hose	35 4.440-678	_		4 m	-	With bend, C ID 40.	35		' 	+	-	+	-				\vdash	++	++	+		-
Suction hose + ID 40 bushing Suction hose + PFC module	36 4.440-784 37 4.440-679			16 m 4 m	-	C ID 40, 16 m, with bayonet connection and straight sleeve. With bend and module (4.060-474.0).	36		+								\vdash	++	++	++		
Suction hose + PFC module,	38 4.440-728			4 m		With bend and module (4.000-974.0). With bend and module (4.060-533.0), electrically conductive.	38											\forall				
electrically conductive Extension hoses (clip system)						I										\perp						
Extension hose	39 2.889-145	0 1 piece(s)	ID 35	2.5 m		Extension hose for new clip system ID 35. Length: 2.5 m.	39															
	40 2.889-146	0 1 piece(s)	ID 40	2.5 m		Extension hose for new clip system ID 40. Length: 2.5 m.	40															
	41 6.906-344	0 1 piece(s)	ID 40	2.5 m		For all C-40 hoses.	41															
Special hoses																						
Special suction hose, heat-resistant	42 4.440-731	0 1 piece(s)	ID 35	2.5 m		Special suction hose, ID 35, 2.5 m, e.g. for oven cleaning, temperature-resistant up to 140°C, plastic, metal.	42															
Repair kits				_						Ι,								, ,				
Repair kit ID 35	43 2.889-149					Repair kit ID 35 for the new clip system.	43					++	\perp	+	\perp		\vdash	+	++	++		
Repair kit ID 40	44 2.889-150			1	-	Repair kit ID 40 for the new clip system.	44	+++			\vdash	+	+	+	+	H_	H-	+-	+	+		
Repair kit, C 35	45 2.639-682				-	Suction hose repair kit (clip system).	45			+		+	-			H	H	+++-	++	++		
Repair kit, C 40	46 2.639-873					Suction base repair kit	46			+		++					+	+	++	++		
Repair kit, ID 61	47 2.862-038	o 1 piece(s)	ן מעון	Landa de la contracta de la co	1	Suction hose repair kit.	47										Ш	$\perp \perp$				

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

OTHER ACCESSORIES



Our drill dust nozzle lets you drill holes while the dust is conveniently removed. Suitable for Kärcher dry and wet and dry vacuum cleaners.











	Order no.	Quantity	ID	Price Description		NT 75/2 Tact* Me Tc Adv NT 75/2 Tact* Me Tc / NT 65/2 Tact* Tc NT 55/2 Tact* Me Ic / NT 65/2 Tact* Tc NT 55/2 Tact* Me Ic / NT 65/2 Tact* NT 75/2 Tact* Me Ic / NT 65/2 Tact* NT 75/2 Tact* Me Ic / NT 30/1 Tact Te Lc NT 75/2 AD Me Tc / NT 65/2 AD NT 40/1 Apt 1c / NT 30/1 Apt Lc NT 75/2 AD Me Tc / NT 30/1 Apt Lc NT 70/3 Me Tc / NT 70/2 Me Tc / NT 70/3 Me NT 70/3 Me Tc / NT 70/2 Me Tc / NT 70/3 Me NT 70/3 / NT 70/2 / NT 70/1 NT 70/3 / NT 70/1 Adv / NT 70/1 Me Adv NT 70/3 / NT 70/1 Adv / NT 27/1 Me Adv NT 70/1 Me V / NT 27/1 Adv / NT 27/1 Me Adv NT 70/1 Me Classic Edition / NT 30/1 Me Classic Edition / NT 50/1 Me Classic Edition NT 50/1 Tact Te H / NT 30/1 Tact Te H / NT 50/1 Tact Te M NT 50/1 Tact Te H / NT 30/1 Tact Te H / NT 50/1 Tact Te M NT 50/1 Tact Te M
Other CS 40 Me	1 2.863-026.0	1 niece(s)		Cyclone preseparator for use with wet and dry vacuum cleaners for	1	
CS 40 MC	2.003 020.0	1 piccc(s)		very large quantities of dust.		
Drill dust nozzle	2 2.679-000.0	1 piece(s)		Drill dust nozzle for dust-free vacuuming of drill holes. Suitable for and wet and dry vacuum cleaners from Kärcher.	dry 2	
Push handle for NT 40/1 Tact Te L	3 2.643-868.0	1 piece(s)		Ergonomic push handle for NT 40/1 Tact Te L.	3	
Adapters and spare parts						
IVC accessories adapter for	4 6.902-002.0	1 piece(s)	ID 52	For using IVC accessories on NT vacuum cleaners.	4	
wet/dry vacuum cleaners						
Modification kit, non-conductive media		Lauteres		I see this of the control of the con		
ABS non-conductive media	5 2.641-560.0			For switching off when vacuuming non-conductive fluids such as oil		
Modification kit, non-conductive media	6 2.882-517.0			and greases.	6	
Attachment kit, non-conductive media Tact² + Ap	7 2.642-602.0	1 piece(s)				

Tact* + Ap

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

POWER FOR WHEN YOU NEED IT MOST

With power ratings from 1.2 to 7.5 kW and container sizes of between 30 and 120 litres, you will find the right machine for every application in our range of industrial vacuums. These powerful and reliable vacuum cleaners are ideal for non-stop operation. The machines also come with dust explosion protection (Zone 22) and are suitable for dust classes M and H.



Table of contents: Industrial vacuums

Super Class	Page	334
Middle Class	Page	337
Compact Class	Page	340
Ex vacuums	Page	345
Build-in units	Page	349
Liquid and swarf vacuums	Page	350
Accessories	Page	356



IVS, IVS Longopac, IVS Z22

Our new generation of industrial vacuum cleaners in the highest performance class for mobile and stationary operation. Using the optional remote phase side channel blower are mobile and have a large filter for handling control, you can even operate these masters of endurance with ergonomic details conveniently from a distance.



Our new Middle Class vacuums with a three-motor brush head or threehigh volumes of dust and coarse material.

How to read the machine names:


macnine type	Cor	ntainer	Connection load	Motor	version	Equipment
Example: IV	60	0	30		С	
IVS = Industria Super Cla		olume Litres	in kW/10 (without decimal point)	-3 = 1 phase, 3 motors	Ap: Manual or semi-automatic filter cleaning with/without flat	without designation: Standard equipment
IVM = Industria Middle C			e.g.: 30 = 3.0	-2 = 1 phase, 2 motors	pleated filter Tact/Tact ² : Fully automatic filter	Ex: Explosion protection Tc: Tilting chassis
IVC = Industria Compact				-1 = 1 phase, 1 motor	cleaning Pf: Pocket filter	Me: Stainless steel (container) Lp: with Longopac hose bag
IV(R)-L = Industria (Robust)				without des. = 3 phases,		Dp: Barrel pump Ec: Long-life motor
	I vacuum, robust I vacuum, robust Inits			1 motor		Safety vacuum cleaner for explosive dust (alt B1): Z22: Dust in explosion protection zone 22 Safety vacuum cleaner for dust classes: H: Extremely harmful dust
						 (high hazard) M: Moderately harmful dust (medium hazard) L: Slightly harmful dust (light hazard)

FROM THE MOBILE MACHINE TO THE **TURNKEY VACUUMING SYSTEM**

Whether flexible and mobile or fixed and stationary, for small or large quantities, liquids or solids, unproblematic dust or hazardous debris - the Kärcher industrial vacuum range offers solutions for countless vacuuming problems.

		Order no.	Price	Container capacity (I)	Power supply Ph/V/Hz	Rated input power (kW)	Max. air flow rate (I/s / m³/h)	Vacuum (mbar/kPa)	Flat pleated filter	Star/pocket filter	Cartridge filter	Surface filter	Page
	Super Class												
9	IVS 100/75 M	1.573-822.0		100	3 / 400 / 50-60	7.5	149 / 536	360 / 36	-		-	-	335
CAR	IVS 100/55 M	1.573-722.0		100	3 / 400 / 50-60	5.5	139 / 500	250 / 25	-		-	-	335
1	IVS 100/40	1.573-620.0		100	3 / 400 / 50-60	4.0	139 / 500	150 / 15	-		-	-	335
40	IVS 100/40 M	1.573-622.0		100	3 / 400 / 50-60	4.0	139 / 500	150 / 15	-		-	-	335
-	IVS 100/75 Longopac	1.573-821.0		100	3 / 400 / 50-60	7.5	149 / 536	360 / 36	-	•	-	-	335
	IVS 100/55 Longopac	1.573-721.0		100	3 / 400 / 50-60	5.5	139 / 500	250 / 25	-		-	-	335
	IVS 100/40 Longopac	1.573-621.0		100	3 / 400 / 50-60	4.0	139 / 500	150 / 15	-		-	-	335
	IVR 100/40 Pf	9.986-069.0		100	3 / 400 / 50-60	4.0	144 / 520	150 / 15	-	•	-	-	336
	Middle Class												
-	IVM 60/30	1.573-520.0		60	3 / 400 / 50	3.0	68 / 245	286 / 28.6	-	•	-	-	337
1 1000	IVM 60/36-3	1.573-320.0		60	1 / 220-240 / 50-60	3.6	221 / 799	254 / 25.4	-	•	-	-	337
(0)	IVR 50/40 Pf	9.986-068.0		50	3 / 400 / 50	4.0	144 / 520	150 / 15	-		-	-	338
Oi a	IVR 40/30 Pf	9.986-067.0		40	3 / 400 / 50	3.0	89 / 320	260 / 26	-	•	-	-	338
ALC: N	IVR 40/15 Pf	9.986-066.0		40	3 / 400 / 50	1.5	58 / 210	210 / 21	-	•	-	-	338
	IVR 35/20-2 Pf Me	9.986-065.0		35	1 / 220-240 / 50-60	2.0	100 / 360	220 / 22	-	-	-	_	339
	Compact Class												
	IVC 60/30 Tact ²	1.576-101.0		60	3 / 400 / 50	3.0	68 / 245	286 / 28.6	•	-	-	-	340
2.	IVC 60/30 Ap	1.576-107.0		60	3 / 400 / 50	3.0	68 / 245	286 / 28.6	•	-	-	-	340
	IVC 60/24-2 Tact ²	1.576-100.0		60	1 / 220-240 / 50-60	2.4	2 × 74 / 533	254 / 25.4		-	-	-	341
51	IVC 60/24-2 Ap	1.576-104.0		60	1 / 220-240 / 50-60	2.4	2 × 74 / 533	254 / 25.4	•	-	-	-	341
0	IVC 60/24-2 Tact ² M	1.576-105.0		60	1 / 220-240 / 50-60	2.4	2 × 74 / 533	254 / 25.4	•	-	-	-	341
- Car	IVC 60/12-1 Tact Ec	1.576-102.0		60	1 / 220-240 / 50-60	1.2	62.5 / 225	244 / 24.4	•	-	-	-	343
	IVC 60/30 Tact² Lp	1.576-115.0		60	3 / 400 / 50	3.0	68 / 245	286 / 28.6		-	-	-	342
	IVC 60/24-2 Tact ² Lp	1.576-114.0		60	1 / 220-240 / 50-60	2.4	2 × 74 / 533	254 / 25.4		-		_	342
-	Ex vacuums												
0	IVS 100/75 M Z22	9.987-900.0		100	3 / 400 / 50-60	7.5	149 / 536	360 / 36	-	•	-	-	347
E-6	IVS 100/55 M Z22	9.987-899.0		100	3 / 400 / 50-60	5.5	139 / 500	250 / 25	-	•	-	-	347
139	IVM 60/30 M Z22	1.573-521.0		60	3 / 400 / 50	3.0	68 / 245	286 / 28.6	-	•	-	-	345
0	IVC 60/30 Ap M Z22	1.576-106.0		60	3 / 400 / 50	3.0	68 / 245	250 / 25		-	-	-	348
	IVC 60/12-1 Ec H Z22	1.576-103.0		60	1 / 220-240 / 50-60	1.2	62.5 / 225	244 / 24.4		-	<u> </u>	_	348
100	Build-in units	l		l =0	0 / 100 / 50			000 / 00			1 _		
= 10	IVR-B 50/30	9.986-073.0		50	3 / 400 / 50	3.0	89 / 320	260 / 26	-	-	•	-	349
-	IVR-B 30/15	9.986-072.0		30	3 / 400 / 50	1.5	58 / 210	210 / 21	-			_	349
	Liquid and swarf vacuums				0 / 100 / 50						1	_	
-	IVR-L 100/30	9.986-064.0		100	3 / 400 / 50	3.0	89 / 320	260 / 26	-	-	-	•	350
100	IVR-L 120/24-2 Tc Me Dp	9.987-890.0			1 / 220-240 / 50-60	_		235 / 23.5	-	-	-	-	351
2 TX /	IVR-L 120/24-2 Tc Me	9.987-889.0		120	1 / 220-240 / 50-60			235 / 23.5	-	-	-	•	353
AA	IVR-L 120/24-2 Tc	9.987-888.0		120		2.4		235 / 23.5	-		-	•	351
6	IVR-L 100/24-2 Tc Me Dp	9.987-887.0		100		_		235 / 23.5	-		+-	•	353
	IVR-L 100/24-2 Tc Me	9.987-886.0		100	1 / 220-240 / 50-60	_		235 / 23.5	-	-	-	•	353
·h	IVR-L 100/24-2 Tc	9.987-885.0		100	1 / 220-240 / 50-60			235 / 23.5	-		-	•	353
1 7	IVR-L 100/24-2 Me	9.987-884.0		100	1 / 220-240 / 50-60			235 / 23.5	-	_	-	•	353
	IVR-L 100/24-2	9.987-883.0		100	1 / 220-240 / 50-60	2.4	148 / 532	235 / 23.5	-		-	•	353
4	IVR-L 65/12-1 Tc	9.986-055.0		65	1 / 220-240 / 50-60	1.2	60 / 215	230 / 23	-	_	-		354
10	IVR-L 40/12-1	9.986-054.0		40	1 / 220-240 / 50-60	_		230 / 23	-	-	-	•	354
■ NEW ■	IVL 50/24-2 Included in the scope of supply.	1.573-952.0		50	1 / 220-240 / 50-60	2.4	2 × 56 / 403	235 / 23.5					355

■ NEW ■ Included in the scope of supply.



Mobile use in metal processing

example using an IVR-L in mobile use after processing.

A mixture of aggressive coolant and sharp-edged swarf is often produced as the waste product of metal processing. Both substances can be recycled if separated cleanly, for

Example machine: IVR-L 100/24-2 Tc

Example accessory: PU hose or ME-PU hose, swarf basket, bend and tube, floor nozzle,

flexible crevice nozzle, elastic nozzle



Stationary use in the food industry

If equally numerous or large amounts of material are created during production, it makes sense to vacuum these up during the manufacturing process.

Kärcher IVS and IVR machines can be integrated directly into the production process. In the food industry, for example, they can be used to vacuum ground coffee, breadcrumb coating residues, crumbs, dried fruit, etc.

Example machine: IVS 100/40

Example accessory: PVC hose directly connected to the production machine,

or manual suction



The manufacturing of chemical bases requires particular cleanliness in the production environment. The types of waste that are produced are often hazardous to health or even explosive. With an explosion-proof IVS or IVC vacuum cleaner, production areas can be vacuumed safely.

Example machine: IVC 60/30 M Z22

Example accessory: PVC hose, bend and tube, floor nozzle, flexible crevice nozzle,

elastic nozzle



VACUUM CLEANERS

Kärcher industrial vacuum application overview

Coarse, dry		Fine, dry		Potentially explosive	e dust	Liquids	
Ø 2-3 h/day	Ø up to 24 h/day	Ø 2-3 h/day	Ø up to 24 h/day	Ø 2-3 h/day	Ø up to 24 h/day	Ø 2-3 h/day	Ø up to 24 h/day
Automotive indust	ry/machinery and pla	nt engineering/tool ma	nufacture/metal proce	essing			
Metal shavings fror	n machining	Dust from metal prod		Paint dust		Cutting fluid from	metal processing
(milling, drilling, pu					1		
IVR-L 40 IVR-L 65 IVR-L 100/24-2	IVR-L 100/30 IVR-B	IVR 35 IVM 60/36-3	IVM 60/30 IVS 100		IVC 60 Z22 IVM 60/30 M Z22 IVS 100 Z22	IVR-L 40 IVR-L 65 IVR-L 100	IVR-L 100/30
IVR-L 120						IVR-L 120	
Metallurgy and me	etal forming			Flammable metal du	et og iron		
Slag IVR-L 40	IVR-L 100/30			riaiiiiiavie metal 00	IVS 100 Z22		
IVR-L 65 IVR-L 100/24-2 IVR-L 120	IVR-B				11/3 100 222		
Coking and minera	I oil processing						
Lumps of coal				Coal (daytime)			
IVR-L 40 IVR-L 65 IVR-L 100/24-2	IVR-L 100/30 IVR-B IVS 100				IVS 100 Z22		
IVR-L 120							
Glass and stone pro		Cunerum com and	agrata aless dest			Church	
Cullet, gravel, crush	IVC 60/30 Ap	Gypsum, cement, con	IVC 60/30 Tact ²			Slurry IVR-L 65	IVR-L 100/30
IVC 60/24-2 Ap IVR-L 40 IVR-L 65 IVR-L 100/24-2 IVR-L 120	IVR-L 100/30 IVR-B IVS 100	IVR 35	IVM 60/30 IVS 100			IVR-L 100 Tc IVR-L 120 Tc	TVR-L 100/30
Paper manufacture	e/manufacture of prin	t media					
Cardboard packagir	- T	Cellulose fibres		Paper dust		Liquid dyes, printi	
IVC 60/24-2 Ap	IVC 60/12-1 IVC 60/30 Ap IVS 100	IVC 60/24-2 Tact ² IVM 60/36-3	IVC 60/12-1 Tact IVC 60/30 Tact ² IVM 60/30 IVS 100		IVC 60/30 Ap M Z22 IVM 60/30 M Z22 IVS 100 Z22	IVC 60/24-2 IVL 50/24-2 IVR-L 100 IVR-L 120	IVC 60/30 IVR-L 100/30
Food industry							
Broken food productine, e.g. broken bis	cts on the production cuits, chocolate	In the production pro	ocess, e.g. ground	Flour, sugar, coffee, p	powdered foods	Food oil, drinks	
IVC 60/24-2 Ap	IVC 60/12-1 IVC 60/30 Ap IVS 100	IVM 60/36-3	IVM 60/30 IVS 100		IVC 60 Z22 IVM 60/30 M Z22 IVS 100 Z22	IVC 60/24-2 IVL 50/24-2 IVR-L 100 Me IVR-L 120 Me	IVC 60/30
Production of stare	ch and tobacco						
		Tobacco dust		Starch			
		IVC 60/24-2 Tact ²	IVC 60/12-1 Tact IVC 60/30 Tact ² IVS 100		IVC 60 Z22 IVM 60/30 M Z22		
Production of rubb	er and plastic						
	lastic casting residues	Plastic dust			1	Water	
IVC 60/24-2 Ap	IVC 60/12-1 IVC 60/30 Ap IVS 100	IVC 60/24-2 Tact ² IVR 35 IVM 60/36-3	IVC 60/12-1 IVC 60/30 IVM 60/30 IVS 100			IVC 60/24-2 IVL 50/24-2 IVR-L 100 Me IVR-L 120 Me	IVC 60/30
Wood processing/f	furniture manufacture						
	ngs and small pieces			Wood dust			
of wood IVC 60/24-2 Ap	IVC 60/30 Ap	IVC 60/24-2 Tact ² M			IVC 60 Z22		
	IVS 100	14C 50/24 2 Idet IVI			IVM 60/30 M Z22		
Chemical industry		Plant I		Fautili .		Potent i	alian Ha I I
Granulate	IVC 60/12 1	Plastic dust	IVC 60/12 1	Fertiliser, pigment	IVC 60 722	Detergents, aggres	
IVC 60/24-2 Ap	IVC 60/12-1 IVC 60/30 Ap	IVC 60/24-2 Tact ² IVR 35 IVM 60/36-3	IVC 60/12-1 IVM 60/30 IVS 100		IVC 60 Z22 IVM 60/30 M Z22 IVS 100 Z22	IVR-L 100 Me IVR-L 120 Me	IVR-L 100/30
	IVS 100						
Pharmaceutical inc							
Pharmaceutical inc		In the production pro	ocess, e.g. tablet	Medicines, e.g. vitam	nins, oestrogen, acids		

Performance class dimensioning: 1st air speed table: Application overview

		Air speed [m/s]			Air speed [m/s]
The minimum require	d air speeds are listed				
Wood	Wood shavings with pieces	25-30	Minerals	Coarse dry sand without gravel	21-25
	Damp sawdust	22-24		Foundry sand	35-45
ne minimum required air	Coarse wood shavings without pieces	18-22*		Cement dust	25-30
	Wood shavings	18-20*		Pebble stones up to Ø 5 cm	60-65
	Small pieces of wood and chips	16-18*		Sand Ø < 2 cm / Ø 2-3 cm	21-26 / 50-60
	Ultra-fine wood dust	12-14*		Ultra-fine dry sand dust	12-14
The minimum require	d air speeds are listed		-		
Paper, plastics	Plastic granulate	20-23	Metal	Coarse metal dust	20-25
apei, plastics	Plastic powder	20-25		Metal dust	20-22
	Paper chips	15-22*		Fine metal dust	18-20*
	Rubber dust	18-20*		Shavings (dry)	25-27
	Edge strip suction	16-18*		Shavings (wet)	27-32
	Abrasive dust, leather	15-16*		Metal smoke (welding)	14-16
	Paint mist spray booths	14-16*		Steel balls	45-55
	Shorter textile fibres	12-16*		Oil (low viscosity), cooling lubricants	25-30
	Expanded polystyrene	8-10*		Oil (high viscosity), slurry	30-40
The minimum require	d air speeds are listed				
Food	Tobacco dusts	15-16*	Max. flow rate	ID 42	approx. 90 m³/h
	Grain and fodder dusts	14-16*	depending on hose diameter	ID 51/52	approx. 140 m³/h
	Flour	12-14*	nose diameter	ID 61	approx. 200 m³/h
	Food residues, e.g. pasta	30+		ID 72	approx. 270 m³/h

^{*} Safety vacuum cleaners and Ex vacuums may only be operated with a minimum air speed of 20 m/s. If the minimum speed is not met, this is signalled by an indicator light.

Performance class dimensioning: 2nd air speed table

Drive performan	ce		Suction hose dia	meter		
IVR drive heads			ID [Ø mm]	40	50	70
AC	Max. volume flow [m³/h]	Max. vacuum [kPa]	Area [cm²]	12.6	19.6	38.5
1.2 kW	215	23		46.4	29.7	15.1
2.0 kW	360	22		79.6	50.9	26.0
2.4 kW	532	23		117.6	75.2	38.4
Three-phase current						
1.5 kW	210	20		46.4	29.7	15.2
3.0 kW	315	26		70.7	45.3	23.1
4.0 kW	495	14		114.9	73.6	37.5
IVC/IVM drive he	ads	·				
AC	Max. volume flow [m³/h]	Max. vacuum [kPa]	Air speed [m/s]	40	50	70
1.2 kW (Ec)	225	24	All specu [m/s]	49.0	31.8	-
2.4 kW	532	25		117.6	75.2	-
3.6 kW	799	25.4		133.7	85.6	43.7
Three-phase current						
3.0 kW	244	28		53.9	34.5	17.6
IVS drive heads						
Three-phase current						
4.0 kW	500	18		110.5	70.6	36.0
5.5 kW	500	25		110.5	70.6	36.0
7.5 kW	536	33		118.5	75.8	38.7

Example

Application example:

A customer would like to purchase an industrial vacuum for vacuuming metal shavings.

Refer to Table 1 for the required minimum air speed: For metal shavings (dry), an air speed of 25-27 m/s is required.

Table 2 shows the air speed generated during the suction process depending on the drive performance and suction hose diameter.

Example: An 1.2 kW IVR drive head with a ID 40 suction hose enables an air speed of 46.4 m/s → Dimensioning sufficient.

Choosing a ID 70 suction hose and 1.2 kW drive performance would result in an air speed of 15.1 m/s

→ Dimensioning insufficient.

ATTENTION:

➤ Values apply to suction hoses up to 10 metres long. Pressure losses in the suction hose must also be taken into account. ▶ For safety vacuum cleaners, the air speed must never be < 20 m/s.

- | 2.273-001.0

1.573-620.0 | -622.0

SUPER CLASS



High-power machines with stamina

The new Kärcher Super class IVS 100 industrial vacuums are powerful, robust and highly reliable machines. With a motor running time of about 20,000 hours - which corresponds to 2,500 days in continuous operation for eight hours a day it is a real workhorse. The large star filter ensures optimum suction power.















1 Optional remote control

- Optional radio remote control for machine operation from a distance of up to 30 m.
- Convenient, time-saving operation of the machine in a single forward
- Optimal space utilisation: the vacuum cleaner can be stored in unused or safety areas.

2 Power-saving soft start

- Low starting current prevents power supply voltage dips.
- Low energy peaks ensure lower energy costs.
- Only low machine fuse protection necessary. (Up to 5.5 A,16 A fuse protection is sufficient.)

3 User-friendly machine handling

- Hose hook and accessory storage ensure fast tool access and tidy
- Integrated cable hook for secure cable storage.
- All hooks can be hung freely on the machine via a clip system.

4 Horizontal operation of filter cleaning system

- The handle for manual filter cleaning is located at a convenient operating height and makes working comfortable.
- Regardless of the amount of force applied by the user, a gearbox ensures consistent cleaning results.
- Longer filter downtime due to more frequent filter cleaning and metered power transmission to the filter.

TECHNICAL DATA AND EQUIPMENT

		IVS 100/75 M	IVS 100/55 M	IVS 100/40 IVS 100/40 M
		Certified for dust class MExtra-large filter areaPole reverse plug	Certified for dust class MExtra-large filter areaPole reverse plug	 Anti-static equipment Extra-large filter area Pole reverse plug Certified for dust class M
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Rated input power during operation	kW	7.5	5.5	4.2
Max. air quantity	l/s / m³/h	148 / 536	138 / 500	138 / 500
Max. vacuum	mbar / kPa	350 / 35	250 / 25	150 / 15
Container capacity	I	100	100	100
Filter area	m²	2.2	2.2	2.2
Main filter dust class		M	M	M
Sound pressure level	dB(A)	73	77	75
Cable length	m	8	8	8
Nominal diameter of connection		ID 72	ID 72	ID 72
Nominal diameter of accessory		ID 72 / ID 52	ID 72 / ID 52	ID 72 / ID 52
Weight	kg	165	148	142
Dimensions (L × W × H)	mm	1202 × 686 × 1465	1202 × 686 × 1465	1202 × 771 × 1470 1202 × 686 × 1465
Equipment				
Container in scope of delivery		100 l	100 l	100 l
Filter cleaning		Manual	Manual	Manual

2.273-001.0

1.573-722.0

2.273-001.0

1.573-822.0

Included	in the	 of cupply	

		IVS 100/75 Lp	IVS 100/55 Lp	IVS 100/40 Lp
		Longopac disposal systemExtra-large filter areaPole reverse plug	Longopac disposal systemExtra-large filter areaPole reverse plug	Longopac disposal systemExtra-large filter areaPole reverse plug
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Rated input power during operation	kW	7.5	5.5	4.2
Max. air quantity	I/s / m³/h	148 / 536	138 / 500	138 / 500
Max. vacuum	mbar / kPa	350 / 35	250 / 25	175 / 17.5
Container capacity	1	-	-	-
Filter area	m²	2.2	2.2	2.2
Main filter dust class		M	М	M
Sound pressure level	dB(A)	73	77	75
Cable length	m	8	8	8
Nominal diameter of connection		ID 72	ID 72	ID 72
Nominal diameter of accessory		ID 72 / ID 52	ID 72 / ID 52	ID 72 / ID 52
Weight	kg	173	158	155
Dimensions (L × W × H)	mm	1202 × 686 × 1465	1202 × 771 × 1470	1202 × 686 × 1465
Equipment				
Container in scope of delivery		Longopac	Longopac	Longopac
Filter cleaning		Manual	Manual	Manual
Optional remote control		2.273-001.0	2.273-001.0	-
Order no.		1.573-821.0	1.573-721.0	1.573-621.0
Price				
■ Included in the scope of supply.				

SUPER CLASS




The Super class – super compact

Despite its high filling capacity, the IVR 100/40 Pf is characterised by its compact size. In this respect, the space-saving machine is considerably ahead of the competition.







- Longer service life, less maintenance effort and lower costs. Ideal for industrial use.
- Unrivalled effective manual filter cleaning thanks to reinforcement lattice in every filter bag.

2 Highly efficient IE2 motor for higher suction power

■ With comparably rated input power, the IE2 motor delivers 5% more suction power than conventional motors.

IVR 100/40 Pf

- Compact construction style that takes up very little floor space
- Sound reduction

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Rated input power during operation	kW	4.7
Max. air quantity	I/s / m³/h	137.5 / 495
Max. vacuum	mbar / kPa	140 / 14
Container capacity	1	100
Filter area	m²	1.75
Main filter dust class		M
Sound pressure level	dB(A)	62
Cable length	m	6
Nominal diameter of connection		ID 72
Nominal diameter of accessory		ID 72 / ID 52
Weight	kg	184
Dimensions (L × W × H)	mm	910 × 760 × 2270

Equipment	
Container in scope of delivery	100
Filter cleaning	Manual
Optional remote control	-
Order no.	9.986-069.0
Price	

■ Included in the scope of supply.

MIDDLE CLASS



Excellent performance and runtimes

Developed especially for demanding applications in the industry and ideal for removing solids such as fine dusts. Maximum performance in 1-phase area thanks to the three-motor suction head, while in the 3-phase area, the durable side channel blower ensures long runtimes.











- Hose hook and accessory storage ensure fast tool access and tidy storage.
- Integrated cable hook for secure cable storage.

Manual filter vibration for low operating costs

- The manual filter vibration increases the working time of the permanent filter, thereby reducing the maintenance required.
- Regardless of the amount of force applied by the user, a gearbox ensures consistent cleaning results.

IVM 60/30

IVM 60/36-3

		Anti-static equipmentExtra-large filter areaRobust wheels and castors	Anti-static equipmentExtra-large filter areaRobust wheels and castors
Technical data			
Current type	Ph / V / Hz	3 / 400 / 50	1 / 220-240 / 50-60
Rated input power during operation	kW	3	3.6
Max. air quantity	I/s / m³/h	68 / 244.8	221 / 799
Max. vacuum	mbar / kPa	286 / 28.6	254 / 25.4
Container capacity	I	60	60
Filter area	m²	2.2	2.2
Main filter dust class		M	M
Sound pressure level	dB(A)	77	79
Cable length	m	7.5	10
Nominal diameter of connection		ID 72	ID 72
Nominal diameter of accessory		ID 72 / ID 52 / ID 42	ID 72 / ID 52 / ID 72
Weight	kg	96	72
Dimensions (L × W × H)	mm	970 × 690 × 1630	970 × 690 × 1530
Equipment			
Container in scope of delivery		60	60
Filter cleaning		Manual	Manual
Optional remote control		-	-
Order no.		1.573-520.0	1.573-320.0
Drice		2.57 5 22.0	1070 010.0

MIDDLE CLASS

■ Included in the scope of supply.



Full power - continuously

Thanks to their durable side channel blower, the powerful IVR 40 and IVR 50 industrial vacuums are extremely reliable and therefore ideal for long operating cycles.









Pressure compensation hose and downholder for low-dust vacuuming directly into a waste disposal bag.

2 Cyclone-like pre-separation system

Protects the filter and increases its working time. This saves on costs and increases versatility.

		IVR 50/40 Pf	IVR 40/30 Pf	IVR 40/15 Pf
		Cyclone-like pre-separation systemSound reductionErgonomic container control	Cyclone-like pre-separation systemSound reductionSafe accessory storage	Cyclone-like pre-separation systemSound reductionSafe accessory storage
Technical data				
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50
Rated input power during operation	kW	4.7	3	1.5
Max. air quantity	I/s / m³/h	137.5 / 495	87.5 / 315	58 / 210
Max. vacuum	mbar / kPa	140 / 14	260 / 26	200 / 20
Container capacity	1	50	40	40
Filter area	m²	1.75	1.75	1.75
Main filter dust class		M	M	M
Sound pressure level	dB(A)	62	60	56
Cable length	m	6	6	6
Nominal diameter of connection		ID 72	ID 72	ID 72
Nominal diameter of accessory		ID 72 / ID 52	ID 72 / ID 52	ID 52 / ID 42
Weight	kg	178	128	113
Dimensions (L × W × H)	mm	850 × 760 × 1970	890 × 670 × 1560	890 × 670 × 1560
Equipment				
Container in scope of delivery		50 I	40 I	40 I
Filter cleaning		Manual	Manual	Manual
Optional remote control		-	-	-
Order no.		9.986-068.0	9.986-067.0	9.986-066.0

MIDDLE CLASS



Introduction to the IVR series

Industrial vacuums in the IVR series are characterised by agility, robustness and durability. Powerful turbines with intelligent sound reduction combine convenient working with excellent performance.





1 Robust material and a design suitable for industrial purposes

- Ideal for use in the metals processing industry.
- The material thickness of 1.25 mm and mostly welded connections ensure a long service life - even with abrasive suction waste.

2 Pleasant operating noise

■ Sound absorbers on the air outlet pipes make for a comfortable operating noise with high suction power.

IVR 35/20-2 Pf Me

- Compact construction style that takes up very little floor space
- Cyclone-like pre-separation system
- Stainless steel container

Technical data		
Current type	Ph / V / Hz	1 / 220-240 / 50-60
Rated input power during operation	kW	2
Max. air quantity	$l/s / m^3/h$	100 / 360
Max. vacuum	mbar / kPa	220 / 22
Container capacity	1	35
Filter area	m²	1.4
Main filter dust class		M
Sound pressure level	dB(A)	75
Cable length	m	6
Nominal diameter of connection		ID 52
Nominal diameter of accessory		ID 52 / ID 42
Weight	kg	53
Dimensions (L × W × H)	mm	740 × 580 × 1105

Equipment	
Container in scope of delivery	35
Filter cleaning	Manual
Optional remote control	-
Order no.	9.986-065.0
Price	

■ Included in the scope of supply.

COMPACT CLASS

■ Included in the scope of supply.



With three-phase drive for continuous use

The IVC 60/30 features a low-maintenance three-phase motor for multiple shift operation with high loads. With reliable liquid cut-off function and efficient Tact² technology: this vacuum is ideal for both dry and wet cleaning tasks.







1 Wear-resistant side channel blower

■ A side channel blower delivers high suction power with a very long lifetime of at least 20,000 hours. These machines are therefore ideal for multiple shift

2 Automatic Filter Cleaning System Tact²

- The two filters are cleaned with targeted, powerful blasts of air. The procedure is triggered automatically, the suction power remains constantly high, and the work can be continued without interruption.
- Filter designed to allow uninterrupted use with constant high suction power.

COMPACT CLASS

Powerful machines with twin motors

These entry-level machines feature two powerful motors. The basic and standard variants feature an easy-moving and sturdy set-down trolley and stainless steel suction containers. The electronic motor control ensures low starting currents.







1 Automatic Filter Cleaning System Tact²

- The filter automatically cleans itself with targeted, powerful blasts of air. The procedure is triggered automatically whilst maintaining constant high suction power. Further benefits: low maintenance costs, long filter service life.
- Filter designed to allow uninterrupted use with constant high suction power.

2 2 blower motors

Powerful cleaning performance with 2 blowers. Electronically controlled motors avoid high starting currents.

		IVC 60/30 Tact ²	IVC 60/30 Ap
		 Anti-static equipment Liquid cut-off Integrated cyclone for pre-separation system 	 Anti-static equipment Manual filter cleaning Integrated cyclone for pre-separation system
Technical data	,		
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50
Rated input power during operation	kW	3	3
Max. air quantity	I/s / m³/h	68 / 244.8	68 / 244.8
Max. vacuum	mbar / kPa	286 / 28.6	286 / 28.6
Container capacity	I	60	60
Filter area	m²	1.9	1.9
Main filter dust class		M	M
Sound pressure level	dB(A)	77	77
Cable length	m	7.5	5
Nominal diameter of connection		ID 72	ID 72
Nominal diameter of accessory		ID 52 / ID 42	ID 72 / ID 52 / ID 42
Weight	kg	95	95
Dimensions (L × W × H)	mm	970 × 690 × 1240	970 × 690 × 1240
Equipment			
Container in scope of delivery		60 I	60 I
Filter cleaning		automatic	Manual
Optional remote control		-	-
Order no.		1.576-101.0	1.576-107.0

		IVC 60/24-2 Tact ²	IVC 60/24-2 Ap	IVC 60/24-2 Tact ² M
		 Anti-static equipment Liquid cut-off Integrated cyclone for pre-separation system 	 Anti-static equipment Manual filter cleaning Integrated cyclone for pre-separation system 	 Anti-static equipment Certified for dust class M Integrated cyclone for pre-separation system
Technical data				
Current type	Ph / V / Hz	1 / 220-240 / 50-60	1 / 220-240 / 50-60	1 / 220-240 / 50-60
Rated input power during operation	kW	2.4	2.4	2.4
Max. air quantity	l/s / m³/h	148 / 532	148 / 532	148 / 532
Max. vacuum	mbar / kPa	254 / 25.4	254 / 25.4	254 / 25.4
Container capacity	1	60	60	60
Filter area	m²	0.95	0.95	0.95
Main filter dust class		M	M	M
Sound pressure level	dB(A)	73	73	73
Cable length	m	10	8	8
Nominal diameter of connection		ID 72	ID 72	ID 72
Nominal diameter of accessory		ID 52 / ID 42	ID 72 / ID 52 / ID 42	ID 52 / ID 42
Weight	kg	-	59	60
Dimensions (L × W × H)	mm	970 × 690 × 995	970 × 690 × 995	970 × 690 × 995
Equipment				
Container in scope of delivery		60 I	60 I	60 I
Filter cleaning		Fully automatic	Semi-automatic	Fully automatic
Optional remote control		-	-	-
Order no.		1.576-100.0	1.576-104.0	1.576-105.0
Price				

■ Included in the scope of supply.

COMPACT CLASS




Save time and money with Longopac

Our basic models IVC 60/24-2 and IVC 60/30 feature the Longopac disposal system as standard. Compared to conventional disposal bags, these save time and reduce costs considerably.










Constant Airflow



- The adaptable 22 m long disposal bag ensures time-saving bag disposal.
- Far more economical than conventional dust disposal bags.

2 Automatic Filter Cleaning System Tact²

- The two filters are cleaned with targeted, powerful blasts of air. The procedure is triggered automatically, the suction power remains constantly high, and the work can be continued without interruption.
- Filter designed to allow uninterrupted use with constant high suction power.

COMPACT CLASS

Non-stop suction

The IVC 60/12-1 vacuum cleaner is perfect for stationary non-stop use thanks to an electronically controlled drive and compact design. The Ec's brushless motor provides superb performance, low power consumption and very long life.





1 Designed for continuous operation

■ The brushless Ec motors are wear-resistant and have a minimum service life of 5,000 hours, ideal for three-shift operation.

2 Tact system (Tact Automatic Filter Cleaning System)

■ The two filters are cleaned with targeted, powerful blasts of air for constant high suction power.

IVC 60/30 Tact² Lp

IVC 60/24-2 Tact² Lp

		 Longopac disposal system Anti-static equipment Integrated cyclone for pre-separation system 	 Longopac disposal system Anti-static equipment Integrated cyclone for pre-separation system
Technical data			
Current type	Ph / V / Hz	3 / 400 / 50	1 / 220-240 / 50-60
Rated input power during operation	kW	3	2.4
Max. air quantity	$l/s / m^3/h$	68 / 244.8	148 / 532
Max. vacuum	mbar / kPa	286 / 28.6	254 / 25.4
Container capacity	1	60	60
Filter area	m²	1.9	0.95
Main filter dust class		M	M
Sound pressure level	dB(A)	77	73
Cable length	m	7.5	10
Nominal diameter of connection		ID 72	ID 72
Nominal diameter of accessory		ID 52 / ID 42	ID 52 / ID 42
Weight	kg	108	73
Dimensions (L × W × H)	mm	970 × 690 × 1240	950 × 690 × 1170

Equipment		
Container in scope of delivery	-	-
Filter cleaning	Fully automatic	Fully automatic
Optional remote control	-	-
Order no.	1.576-115.0	1.576-114.0
Price		

■ Included in the scope of supply.

IVC 60/12-1 Tact Ec

- Anti-static equipment

Constant Airflow

■ Integrated cyclone for pre-separation system

Technical data		
Current type	Ph / V / Hz	1 / 220-240 / 50-60
Rated input power during operation	kW	1.2
Max. air quantity	$I/s / m^3/h$	62.5 / 225
Max. vacuum	mbar / kPa	244 / 24.4
Container capacity	1	60
Filter area	m²	0.95
Main filter dust class		M
Sound pressure level	dB(A)	74
Cable length	m	10
Nominal diameter of connection		ID 72
Nominal diameter of accessory		ID 52 / ID 42
Weight	kg	59
Dimensions (L × W × H)	mm	970 × 690 × 995

Equipment			
Container in scope of delivery	60		
Filter cleaning	Fully automatic		
Optional remote control	-		
Order no.	1.576-102.0		
Price			

■ Included in the scope of supply.


JM CLEANERS

Zone

CERTIFIED SAFETY FOR POTENTIALLY EXPLOSIVE ATMOSPHERES

Vacuuming in potentially explosive atmospheres places the highest demands on machine quality. This is regulated across Europe by Directive 2014/34/EU and the associated country-specific standards, such as DIN EN 60335-2-69. With directive-compliant certification from TÜV Süd and IBexU, Kärcher Ex vacuums offer you maximum possible safety.





Zoning Typical industries for Ex zones

The greatest risk of explosion occurs if a hazardous quantity of flammable dust or gas forms and mixes with air, which could then be ignited by a suitable ignition source. If conditions within the production areas are favourable to the formation of a flammable mixture, the operator is legally required to divide the affected areas

Paper manufacture
 You can find more examples in the application overview on page 332.

Food industry

Metalworking industry

Zone 22

All Kärcher Ex vacuums are certified for operation in Ex zone 22. They have been developed for areas where there is a temporary explosive atmosphere due to flammable types of dust. Possible ignition sources are avoided or, where unavoidable, encapsulated.

into zones in accordance with Directive 999/92/EC.

Flammable dustsThe formation of an explosive mixture is largely dependent on the grain size

of the dust dispersed in the air. Flammable dusts are generally deemed to be

hazardous if they have a grain size of less than 0.5 mm. Examples of potentially explosive dusts

Pharmaceutical and chemical industry

Powder coatings; swarf from metal, plastic and wood processing, grain flour, powdered milk, medication powder such as ascorbic acid, carrageenans, ibuprofen and others.

EX VACUUMS

Maximum safety. Maximum convenience

Our Middle Class ex vacuums for industrial applications permit work in potentially explosive atmospheres to be carried out safely and simultaneously provide impressive ease of use. The durable side channel blower and extra large filter area ensure long operating periods.











Illustration can differ from the original.



1 Certified according to 94/9/EC (ATEX)

- Explosion-proof industrial vacuum certified according to 94/9/EC (ATEX) for zone 22 and dust filter class M.
- Reliable vacuuming of substances which could put health at risk such as explosive dusts.

2 User-friendly machine handling

- Hose hook and accessory storage ensure fast tool access and tidy storage.
- Integrated cable hook for secure cable storage.

IVM 60/30 M Z22

- Certified according to 94/9/ECManual filter cleaning
- Anti-static equipment

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Rated input power during operation		-
Max. air quantity	$l/s / m^3/h$	68 / 244
Max. vacuum	mbar / kPa	286 / 28.6
Container capacity	1	60
Filter area	m²	2.2
Main filter dust class		M
Sound pressure level	dB(A)	77
Cable length	m	7.5
Nominal diameter of connection		ID 72
Nominal diameter of accessory		ID 42
Weight	kg	96
Dimensions (L × W × H)	mm	970 × 690 × 1630

Equipment	
Container in scope of delivery	60 I
Container for dry applications	-
Dust class	M
Туре	-
Filter cleaning	Manual
Order no.	1.573-521.0
Price	

■ Included in the scope of supply.

EX VACUUMS



Uncompromising safety: the Super Class

Safety at the highest level with excellent suction power and filter lifetime: our new explosion-proof vacuum cleaners stand out in every respect. The large star filters provide continuous protection against explosive suction waste, even in large quantities.




















1 Suitable for zone 22

- IVS Ex vacuums guarantee the highest level of safety thanks to the
- Reliable vacuuming of substances which could put health at risk such

- latest technology.
- as explosive dusts.

2 Power-saving soft start

- Low starting current prevents power supply voltage dips.
- Low energy peaks ensure lower energy costs.
- Only low machine fuse protection necessary. (Up to 5.5 A,16 A fuse protection is sufficient.)

3 User-friendly set-down mechanism

- Easy and time-saving container removal directly on the handle.
- The practical container handle serves as an aid for pulling and pushing the machine to the emptying point.
- Large industrial rollers ensure maximum mobility even on uneven floors and under heavy load.

4 Horizontal operation of filter cleaning system

- The handle for manual filter cleaning is located at a convenient operating height and makes working comfortable.
- Regardless of the amount of force applied by the user, a gearbox ensures consistent cleaning results.
- Longer filter downtime due to more frequent filter cleaning and metered power transmission to the filter.

TECHNICAL DATA AND EQUIPMENT

		IVS 100/75 M Z22	IVS 100/55 M Z22
		 Constructed in conformity with DIN EN 60335-2-69:2010 Extra-large filter area Manual filter cleaning 	 Constructed in conformity with DIN EN 60335-2-69:2010 Extra-large filter area Manual filter cleaning
Technical data			
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50
Rated input power during operation	kW	7.5	5.5
Max. air quantity	I/s / m³/h	148 / 373	138 / 353
Max. vacuum	mbar / kPa	350 / 35	250 / 25
Container capacity	1	100	100
Filter area	m²	2	2
Main filter dust class		M	M
Sound pressure level	dB(A)	73	77
Cable length	m	8	8
Nominal diameter of connection		ID 72	ID 72
Nominal diameter of accessory		ID 72 / ID 52	ID 72 / ID 52
Weight	kg	180	157
Dimensions (L × W × H)	mm	1202 × 686 × 1495	1202 × 686 × 1500
Equipment			
Container in scope of delivery		100	100
Container for dry applications		-	-
Dust class		M	M
Туре		722	Z22
Filter cleaning		Manual	Manual
Order no.		9.987-900.0	9.987-899.0
Price			

■ Included in the scope of supply.

EX VACUUMS



Cleaners for zone 22

The compact-class, ATEX-certified industrial vacuums are approved for potentially explosive zone 22 atmospheres. Thanks to innovative motor technology, the machines are ideal for continuous use.














1 With compact flat pleated filter

The compact flat pleated filter allows a large filter area with a small and clear design.

2 Two-stage filter concept permits vacuuming with and without dust filter class H in ATEX zone 22

- Health protection thanks to filter class H when vacuuming health-endangering dusts via bottom branch.
- If class H is not required in zone 22, the upper part can be used instead.

		IVC 60/30 Ap M Z22	IVC 60/12-1 Ec H Z22
		 Certified according to 94/9/EC Manual filter cleaning Anti-static equipment 	 Certified according to DIN EN 60335-2-69:2010 Dust-free and low-dust disposal Anti-static equipment
Technical data			
Current type	Ph / V / Hz	3 / 400 / 50	1 / 220-240 / 50-60
Rated input power during operation	kW	3	1.2
Max. air quantity	$I/s / m^3/h$	68 / 244	62.5 / 225
Max. vacuum	mbar / kPa	286 / 28.6	244 / 24.4
Container capacity	1	60	60
Filter area	m²	1.9	0.95
Main filter dust class		M	Н
Sound pressure level	dB(A)	77	76
Cable length	m	8	10
Nominal diameter of connection		ID 72	ID 72
Nominal diameter of accessory		ID 42	ID 42
Weight	kg	95	59
Dimensions (L × W × H)	mm	970 × 690 × 1240	970 × 690 × 995
Equipment			
Container in scope of delivery		60 I	60 I
Container for dry applications		-	-
Dust class		M	Н
Туре		Z22	Z22
Filter cleaning		Manual	-
Order no.		1.576-106.0	1.576-103.0
Price			
■ Included in the scope of supply.			

BUILD-IN UNITS



Space-saving compact vacuum for dust and swarf

There is always space for IVR-B vacuums, even in the smallest corners of production halls, thanks to their compact size and low installation height.







1 Optional castors increase mobility

Using the optionally available castors allows mobile applications.



2 Large-area cartridge filters

For professional use and long operating periods.

IVR-B 50/30

IVR-B 30/15 Me

		Low installation heightCartridge filterSound absorber	Low installation heightCartridge filterStainless steel container
Technical data			
Current type	Ph/V/Hz	3 / 400 / 50	3 / 400 / 50
Rated input power during operation	kW	3	1.5
Max. air quantity	$l/s / m^3/h$	87.5 / 315	58 / 210
Max. vacuum	mbar / kPa	260 / 26	200 / 20
Container capacity	1	50	30
Filter area	m²	0.7	0.7
Main filter dust class		M	M
Sound pressure level	dB(A)	70	70
Cable length	m	6	6
Nominal diameter of connection		ID 52	ID 52
Nominal diameter of accessory		ID 52 / ID 42	ID 52 / ID 42
Weight	kg	83	52
Dimensions (L × W × H)	mm	890 × 715 × 540	769 × 430 × 640
Equipment			
Container in scope of delivery		yes	yes
Optional machine parts		9.986-099.0	9.986-099.0
Order no.		9.986-073.0	9.986-072.0

■ Included in the scope of supply.

MCIEANEDS

LIQUID AND SWARF VACUUMS




Built for endurance

Whether you need to vacuum coolants, emulsions, oil or water, with or without swarf - the powerful liquid and swarf vacuums with a range of drive types are ideal for heavy-duty industrial uses.







A side channel blower offers high suction power and durability. These machines are therefore ideal for multiple shift operation.

2 Visual filling level indicator

- Always up-to-date on the current status: the filling level is visible at all times during vacuuming.
- Emptying can be carried out as required via the filling level hose.

LIQUID AND SWARF VACUUMS




Specialist machines with stamina

With a 120-litre capacity, IVR-L 120 vacuums offer the longest emptying intervals. The oil-resistant design makes the machine ideal for removing oil.







- The low weight of the drive head ensures easier handling during transport, emptying and servicing.
- Greater work safety during transport due to cable storage on the machine head.

2 360° working radius

Clean in all directions thanks to the rotatable hose connection on the suction head. Tangle-free suction hose.

IVR-L 120/24-2 Tc

ID 52

ID 52 / ID 42

351

IVR-L 100/30

- Set-down trolley
- Compact construction style that takes up very little floor space
- Sound reduction

Technical data		
Current type	Ph / V / Hz	3 / 400 / 50
Rated input power during operation	kW	3
Air flow rate	I/s / m³/h	89 / 320
Vacuum	mbar / kPa	260 / 26
Container capacity	I	100
Filter area	m²	0.45
Sound pressure level	dB(A)	60
Cable length	m	6
Nominal diameter of connection		ID 72
Nominal diameter of accessory		ID 72 / ID 52
Weight	kg	141
Dimensions (L × W × H)	mm	850 × 760 × 1800

Equipment

Automatic filling level shut-off	-
Order no.	9.986-064.0
Price	

■ Included in the scope of supply.

		Tilting chassisStainless steel casing and containerDrum pump function	Tilting chassisStainless steel casing and containerVisual filling level indicator	Tilting chassisVisual filling level indicator
Technical data				
Current type	Ph / V / Hz	1 / 220-240 / 50-60	1 / 220-240 / 50-60	1 / 220-240 / 50-60
Rated input power during operation	kW	2.4	2.4	2.4
Air flow rate	I/s / m³/h	148 / 532	148 / 532	148 / 532
Vacuum	mbar / kPa	235 / 23	235 / 23	235 / 23
Container capacity	1	120	120	120
Filter area	m²	0.45	0.45	0.45
Sound pressure level	dB(A)	68	68	68

Weight	kg	72	65	66
Dimensions (L × W × H)	mm	745 × 710 × 1420	740 × 620 × 1180	740 × 620 × 1180
Equipment				
Automatic filling level shut-off		-	-	-
Order no.		9.987-890.0	9.987-889.0	9.987-888.0
Price				

ID 52

ID 52 / ID 42

ID 52

ID 52 / ID 42

Included in the scope of supply.

Nominal diameter of accessory

Cable length

LIQUID AND SWARF VACUUMS



The power of twin motors

Whether with stainless steel container, tilting chassis or drum pump function: the dual-motor IVR-L variants offer the greatest versatility and the right solution for any application.













1 New drive head for increased safety, convenience and power

- The low weight of the drive head ensures easier handling during transport, emptying and servicing.
- Greater work safety during transport due to cable storage on the machine head
- Integrated exhaust air cover prevents dirt ingress in the motor compartment.

2 360° working radius

Clean in all directions thanks to the rotatable hose connection on the suction head. Tangle-free suction hose.

3 Practical tilting chassis

Quick and easy emptying of the container: just tip backwards and you are done!

4 Safe accessory storage

Suction hose storage hook and defined accessory storage for a clean, tidy and ready-to-use machine.

TECHNICAL DATA AND EQUIPMENT

		IVR-L 100/24-2 Tc Me Dp	IVR-L 100/24-2 Tc Me	IVR-L 100/24-2 Tc
		Tilting chassisStainless steel casing and containerDrum pump function	Tilting chassisStainless steel casing and containerVisual filling level indicator	Tilting chassisVisual filling level indicator
Technical data				
Current type	V / Hz	220-240 / 50-60	220-240 / 50-60	220-240 / 50-60
Rated input power during operation	kW	2.4	2.4	2.4
Air flow rate	I/s / m³/h	148 / 532	148 / 532	148 / 532
Vacuum	mbar / kPa	235 / 23	235 / 23	235 / 23
Container capacity	I	100	100	100
Filter area	m²	0.45	0.45	0.45
Sound pressure level	dB(A)	68	68	68
Cable length	m	6	6	6
Nominal diameter of connection		ID 52	ID 52	ID 52
Nominal diameter of accessory		ID 52 / ID 42	ID 52 / ID 42	ID 52 / ID 42
Weight	kg	56	58.8	50
Dimensions (L × W × H)	mm	740 × 620 × 1180	640 × 620 × 1060	640 × 620 × 1060
Equipment				
Automatic filling level shut-off		-	-	-
Order no.		9.987-887.0	9.987-886.0	9.987-885.0
Price				

■ Included in the scope of supply

		IVR-L 100/24-2 Me	IVR-L 100/24-2
		 Compact construction style that takes up very little floor space 	Compact construction style that takes up very little floor space
		Stainless steel casing and container	■ Visual filling level indicator
Technical data			
Current type	V / Hz	220-240 / 50-60	220-240 / 50-60
Rated input power during operation	kW	2.4	2.4
Air flow rate	I/s / m³/h	148 / 532	148 / 532
Vacuum	mbar / kPa	235 / 23	235 / 23
Container capacity	I	100	100
Filter area	m²	0.45	0.45
Sound pressure level	dB(A)	68	68
Cable length	m	6	6
Nominal diameter of connection		ID 52	ID 52
Nominal diameter of accessory		ID 52 / ID 42	ID 52 / ID 42
Weight	kg	41	44
Dimensions (L × W × H)	mm	640 × 620 × 1060	640 × 620 × 1060
Equipment			
Automatic filling level shut-off		-	-
Order no.		9.987-884.0	9.987-883.0
Price			
■ Included in the scope of supply			

■ Included in the scope of supply.

LIQUID AND SWARF VACUUMS



The powerful introduction to liquid vacuuming

Machines in the IVR-L range for the metalworking industry are exceptionally robust and durable, and deliver outstanding results in day-to-day heavy-duty use.





1 Float ball for volume flow disruption

- A float ball in the machine head interrupts the suction flow as soon as the maximum filling capacity is reached.
- Use as an emergency circuit. The filter must be dry when restarting.

2 Long-lasting

- $\hfill \blacksquare$ High-quality materials and robust welding techniques guarantee a long service
- An oil-resistant power cable is included as standard and further prolongs the machine's service life.

LIQUID AND SWARF VACUUMS



The reliable vacuum with air flow reversal

The powerful liquid vacuum has two bypass motors. Liquids that have been vacuumed up can be released very quickly using the air flow reversal





- 1 Convenient air flow reversal function
- The air stream can be switched over. This makes it easy to empty the container.
- 2 2 electronically controlled tangential blowers
- 2 blowers for high suction power. The machine switches off automatically when the container is full.

IVR-L 65/12-1 Tc

IVR-L 40/12-1

		 Tilting chassis Compact construction style that takes up very little floor space Visual filling level indicator 	Compact construction style that takes up very little floor spaceVisual filling level indicator
Technical data			
Current type	Ph / V / Hz	1 / 220-240 / 50-60	1 / 220-240 / 50-60
Rated input power during operation	kW	1.2	1.2
Air flow rate	I/s / m³/h	59 / 212.4	59 / 212.4
Vacuum	mbar / kPa	230 / 23	230 / 23
Container capacity	1	65	40
Filter area	m²	0.25	0.25
Sound pressure level	dB(A)	71	70
Cable length	m	6	6
Nominal diameter of connection		ID 52	ID 52
Nominal diameter of accessory		ID 42	ID 42
Weight	kg	40	33
Dimensions (L × W × H)	mm	742 × 500 × 1100	711 × 523 × 960

Equipment		
Automatic filling level shut-off	•	I
Order no.	9.986-055.0	9.986-054.0
Price		

■ Included in the scope of supply.

IVL 50/24-2

- Easy-to-use air reversal feature
- Electronic motor control
- Stainless steel container

Technical data		
Current type	Ph / V / Hz	1 / 220-240 / 50-60
Rated input power during operation	kW	2.4
Air flow rate	$l/s / m^3/h$	112 / 403
Vacuum	mbar / kPa	235 / 23.5
Container capacity	1	50
Filter area	m²	1
Sound pressure level	dB(A)	73
Cable length	m	8
Nominal diameter of connection		ID 51
Nominal diameter of accessory		ID 51
Weight	kg	88
Dimensions (L × W × H)	mm	980 × 650 × 1250

|--|

omatic filling level shut-off	
er no.	1.573-952.0

■ Included in the scope of supply.


EVERYTHING YOU NEED: THE RIGHT ACCESSORIES FOR ALL INDUSTRIES

The wide range of accessory parts offers almost unlimited applications. Even the hoses have the right diameter and structure for the material to be vacuumed and they can be extended with ease. All accessories are electrically conductive.



Table of contents: Industrial vacuum accessories

rubic of contents. Indostrial vaccom accessories		
Accessory kits	Page	358
Suction hoses	Page	360
Nozzles	Page	364
Bends and suction tubes	Page	368
Containers and pre-separators	Page	370
Adapters and spare parts	Page	372
Filters and waste disposal bags	Page	374
Other accessories	Page	376



1 Nominal size designation of industrial vacuums

The nominal size designation of industrial vacuums indicates the accessory All accessories for industrial vacuums are electrically conductive. The accessories generation. Generation 1 with the designations ID 51 and 61 is suitable for IV and IVL vacuum cleaners. Generation 2 with the designations ID 42, cleaner. These vacuum cleaners may only be operated with specially designations. 52 and 72 is suitable for IVC and IVR vacuum cleaners. The two accessory nated accessories. systems can be combined using adapters.

2 Accessories for Ex vacuums

sories for Ex vacuums are certified separately together with the vacuum

Hose assembly available by bulk stock

	Designation	Piece(s)	ID 42	ID 52	ID 72
	Suction hose available by bulk stock in the required material and length	1			
and	ID 72 vacuum connector on selected hose diameter for IVC machine connection	1	6.902-178.0	6.902-177.0	6.902-173.0
or	Connector for IVR and extension hoses	1	6.902-170.0	6.902-168.0	6.902-173.0
and	Rotatable accessory adapter	1	6.902-172.0	6.902-169.0	6.902-175.0
and	40-60 mm hose clamp	2	6.902-167.0	6.902-167.0	6.902-176.0
and	Hose sleeve	2	6.902-171.0	6.902-166.0	6.902-174.0

IV ACCESSORY KITS



Kärcher's versatile industrial accessories are made from high-quality materials, facilitate working and ensure safe operation, even for sharp-edged waste like metal shavings.




















	Orde	er no.	Quantity	ID	Price	Description		IVS 100/75 M IVS 100/75 M IVS 100/40 IVS 100/40 IVS 100/40 M IVS 100/75 Lp IVS 100/75 Lp IVS 100/40 Pf IVS 100/40 Pf IVS 100/40 Pf IVM 60/30 IVM 60/30 IVM 60/30 IVM 60/30 Ap
Accessory kits IVC, IVS, IVR (3 phases)	4 2 2 2	0.400.0		LID 40		DV6 - 45-4 by 2 - 4D 42 (5 007 200 0) by 4 1D 42 (5 002 200 0)	1 41	
Dry vacuuming kit for fine dust, screw connection	1 2.86	9-106.0	6 -part	ID 42		PVC suction hose 3 m ID 42 (6.907-292.0), bend ID 42 (6.902-202.0), suction tube 750 mm ID 42 (6.902-182.0), floor nozzle 370 mm ID 42 (6.902-185.0), plastic crevice nozzle 13 mm ID 42 (6.902-195.0), round brush, angled ID 42 (6.902-193.0).		
Vacuuming kit for liquids with solids, screw connection	2 2.86	9-107.0	6 -part	ID 42		3 m ME-PU suction hose ID 42 (6.907-304.0), bend ID 42 (6.902-202.0), 750 mm suction tube ID 42 (6.902-182.0), 370 mm floor tool ID 42 (6.902-185.0), nozzle, flexible ID 42 (6.902-197.0), round suction nozzle, rubber ID 42 (6.902-200.0).	2	
Vacuuming kit for solids/small quantities of liquids, screw connection	3 2.86	9-108.0	6 -part	ID 52		3 m ME-PU suction hose ID 52 (6.907-306.0), bend ID 52 (6.902-201.0), 850 mm suction tube ID 52 (6.902-181.0), 370 mm floor tool ID 52 (6.902-184.0), nozzle, flexible ID 52 (6.902-196.0), 150 mm aluminium surface nozzle ID 52 (6.902-187.0).	3	
Vacuuming kit for dry/coarse particles, screw connection	4 2.86	9-109.0	6 -part	ID 52		3 m PU suction hose ID 52 (6.907-300.0), bend ID 52 (6.902-201.0), 850 mm suction tube ID 52 (6.902-181.0), 370 mm floor tool ID 52 (6.902-184.0), nozzle, flexible ID 52 (6.902-196.0), 150 mm aluminium surface nozzle ID 52 (6.902-187.0).	4	
Vacuuming kit for explosive dusts	5 9.98	8-127.0	6 -part	ID 42		PVC suction hose, 3 m, ID 42 (6.907-292.0), bend, ID 42 (6.902-202.0), suction tube, 750 mm, ID 42 (6.902-182.0), floor nozzle Ex (6.902-213.0), crevice nozzle, plastic, ID 42 (6.902-195), surface brush, ID 42 (6.902-204).	5	
Accessory kit IVR (1 phase)								
Vacuuming kit for liquids, screw connection	6 9.98	6-271.0	6 -part	ID 42		Reducer ID 52 to ID 42 (6.902-179.0), PU suction hose, 3 m, ID 42 (6.907-314.0), bend ID 42 (6.902-202.0), suction tube, 750 mm, ID 42 (6.902-182.0), floor nozzle, 370 mm, ID 42 (6.902-185.0), elongated round nozzle, rubber, ID 42 (6.902-200.0).	6	
Vacuuming kit for liquids and swarf, screw connection	7 9.98	6-280.0	6 -part	ID 42		Reducer ID 52 to ID 42 (6.902-179.0), ME-PU suction hose, 3 m, ID 42 (6.907-318.0), bend ID 42 (6.902-202.0), suction tube, 750 mm, ID 42 (6.902-182.0), floor nozzle, 370 mm, ID 42 (6.902-185.0), flexible nozzle, plastic, ID 42 (6.902-197.0).	7	
Vacuuming kit for liquids, screw connection	8 9.98	6-281.0	5 -part	ID 52		PU suction hose, 3 m, ID 52 (6.907-316.0), bend ID 52 (6.902-201.0), suction tube, 850 mm, ID 52 (6.902-181.0), floor nozzle, 370 mm, ID 52 (6.902-184.0), flexible nozzle, plastic, ID 52 (6.902-196.0).	8	
Vacuuming kit for liquids and swarf, screw connection	9 9.98	6-282.0	5 -part	ID 52		ME-PU suction hose, 3 m, ID 52 (6.907-320.0), bend ID 52 (6.902-201.0), suction tube, 850 mm, ID 52 (6.902-181.0), floor nozzle, 370 mm, ID 52 (6.902-184.0), surface nozzle, aluminium, ID 52 (6.902-187.0).	9	
Stainless steel vacuuming kit	10 9.98	8-126.0	6 -part	ID 52		Connection hose, light PU (9.988-124.0), stainless steel bend (9.988-111.0), stainless steel suction tube (9.988-114.0), stainless steel floor nozzle (9.988-115.0), stainless steel crevice nozzle (9.988-123.0), rubber nozzle, angled (9.988-118.0).	10	
Accessory kits IV, IVL								
Industrial kit for demanding applications, socket plug connection	11 2.64	1-178.0		ID 51		$1\times6.906\text{-}793.0$ floor tool ID 51, H-D, 500 mm. $1\times6.906\text{-}773.0$ suction nozzle ID 51, plastic. $1\times6.906\text{-}768.0$ crevice nozzle ID 51, plastic. $1\times6.906\text{-}767.0$ bend ID 51, stainless steel. $2\times6.906\text{-}766.0$ suction tube 0.5 m, ID 51, stainless steel. $1\times6.906\text{-}786.0$ PU suction hose ID 51, 5 m.	11	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

IV SUCTION HOSES



You can find the right hose for your application here. Ensure that you select the appropriate nominal diameter of accessories and hose length for the machine.

PVC fine and light suction waste, e.g. plastic granulate, concrete dust

VA very light suction waste, entry-level applications, e.g. mineral dust

J liquid and abrasive suction waste, e.g. cooling lubricants, oil, swarf with liquid

ME very hot, dry suction waste, e.g. slag

ME-PU very abrasive suction waste with liquid, e.g. metal shavings with cooling lubricants









	Order no.	Quantity	ID	Length	Price	Description		IVS 100/75 M IVS 100/40 IVS 100/40 M IVS 100/40 M IVS 100/40 M IVS 100/40 PF IVM 60/30 IVM 60/30 PF IVM 60/30 PF IVM 60/30 APP IVC 60/24-2 PGt** IVC 60/30 APP IVC 60/24-2 PGt** IVC 60/30 APP IVC 60/30
PVC hoses Suction hose, PVC,	1 6 007 202 0	1 ninco(c)	LID 42	l 2 m	1	Electrically conductive ID 72 machine connection with star cerear clitand		
screw connection	1 6.907-292.0		ID 42	3 m		Electrically conductive, ID 72 machine connection with star screw, slitand ID 42 accessory end hinge, max. temperature 85 °C, for fine andlight	1	
Serew connection	2 6.907-293.0	1 piece(s)	ID 42	5 m		suction waste.	2	
	3 6.907-294.0	1 piece(s)	ID 52	3 m		Electrically conductive, ID 72 machine connection with star screw, slitand	3	
	4 6.907-295.0	1 piece(s)	ID 52	5 m		ID 52 accessory end hinge, max. temperature 85 °C, for fine and light	4	
	5 6.907-296.0			2 m	-	Suction waste.	5	
		1 piece(s)	ID 72	3 m		Electrically conductive, ID 72 machine connection with star screw, slit and ID 72 accessory end hinge, max. temperature 85 °C, for fine and light suc-		
	6 6.907-297.0	1 piece(s)	ID 72	5 m		tion waste. Can also be used as an extension hose.	6	
Connection hose, PVC,	7 6.907-310.0	1 piece(s)	ID 42	3 m		Electrically conductive, ID 42 connection at both ends, slit andaccessory	7	
screw connection	8 6.907-311.0	1 piece(s)	ID 42	5 m		end hinge, max. temperature 85 °C, for fine and light suctionwaste. IVC only	8	
	9 6.907-312.0		ID 52	3 m		as an extension hose, IVR only with reduction. Electrically conductive, ID 52 connection at both ends, slit and accessory	9	
	9 0.907-312.0	1 piece(s)	10 32	3111		end hinge, max. temperature 85 °C, for fine and light suction waste. IVC only as an extension hose, 3 ~ IVR reduction required.	9	
	10 6.907-313.0	1 piece(s)	ID 52	5 m		Electrically conductive, ID 52 connection at both ends, slit and accessory end hinge, max. temperature 85 °C, for fine and light suction waste. IVC	10	
				-		only as an extension hose, 3~ IVR reduction required.		
Suction hose, available by the metre, PVC, screw connection	11 9.980-645.0		ID 42			Suction hose available in bulk, PVC, ID 40; without tap adapters, max. 15 m.	11	
metre, FVC, screw connection	12 9.980-646.0 13 9.980-677.0		ID 52 ID 72	+	+	Electrically conductive, without connections, whole metres up tomax. 15 m, price per metre, max. temperature 85 °C, for fine and lightsuction waste.	12	
EVA hoses	15 3.500 077.0		10 72			price per metre, max. temperatore 65°C, for mic and highesterior waste.	15	
Suction hose EVA, screw connection	14 9.988-092.0 15 9.988-093.0					EVA material, electrically conductive, ID 72 machine connection with star screw, slit and ID 42 accessory end hinge, highly flexible, for fine and light suction waste.	14	
	16 9.988-094.0	1 piece(s)	ID 52	3 m		EVA material, electrically conductive, ID 72 machine connection with star	16	
	17 9.988-095.0			5 m		screw, slit and ID 52 accessory end hinge, highly flexible, for fine and light suction waste.	17	
Connection hose EVA, screw connection	18 9.988-088.0 19 9.988-089.0		ID 42	3 m		EVA material, electrically conductive, ID 42 connection at both ends, slit and accessory end hinge, highly flexible, for fine and light suction waste.	18	
Screw connection	15 5.566-065.0	1 piece(s)	10 42	3 111		IVC only as an extension hose, IVR only with reduction.	13	
	20 9.988-090.0					EVA material, electrically conductive, ID 52 connection at both ends, slit	20	
	21 9.988-091.0	1 piece(s)	ID 52	5 m		and accessory end hinge, highly flexible, for fine and light suction waste.	21	
PU hoses						IVC only as an extension hose, IVR only with reduction.		
Suction hose, PU, screw connection	22 6.907-298.0		ID 42	3 m		Electrically conductive, ID 72 machine connection with star screw, slitand ID 42 accessory end hinge, max. temperature 80 °C, for liquidsand abrasive	22	
Serew connection	23 6.907-299.0	1 piece(s)	ID 42	5 m		solids.	23	
	24 6.907-300.0		ID 52	3 m		Electrically conductive, ID 72 machine connection with star screw, slitand ID 52 accessory end hinge, max. temperature 80 °C, for liquidsand abrasive	24	
	25 6.907-301.0	1 piece(s)	ID 52	5 m		solids.	25	
	26 6.907-302.0	1 piece(s)	ID 72	3 m		Electrically conductive, ID 72 machine connection with star screw, slitand	26	
	27 6.907-303.0		ID 72			ID 72 accessory end hinge, max. temperature 80 °C, for liquidsand abrasive solids. Can also be used as an extension hose.	27	
Connection hose, PU,	28 6.907-314.0	1 piece(s)	ID 42	3 m		Electrically conductive, ID 42 connection at both ends, slit and accessory	28	
screw connection	29 6.907-315.0		ID 42			end hinge, max. temperature 80 °C, for liquids and abrasivesolids. IVC only as an extension hose, IVR only with reduction.	29	
	30 6.907-316.0	1 piece(s)	ID 52	3 m		Electrically conductive, ID 52 connection at both ends, slit and accessory end hinge, max. temperature 80 °C, for liquids and abrasivesolids. IVC only as an extension hose, 3~ IVR reduction required.	30	
			1		1	as an extension nose, 5.1 Mit reduction regulied.		

□ Available accessories. More Kärcher original accessories can be found on the following pages.











		Order no.	Quantity	ID	Length	Price	Description		IVS 100/75 M IVS 100/40 IVS 100/40 IVS 100/40 IVS 100/40 IVS 100/75 Lp IVS 100/40 Lp IVS 60/30 Tact² IVS 60/30 Tact² IVS 60/24-2 Tact² IVS 60/30 M Z22 IVS 60/30 M Z22 IVS 60/30 A D M Z D D M M Z D D D M D D D M D D D M D D D M D D D M D
Connection hose, PU,	31	6.907-317.0	1 piece(s)	ID 52	5 m		Electrically conductive, ID 52 connection at both ends, slit and accessory	31	
screw connection							end hinge, max. temperature 80 °C, for liquids and abrasivesolids. IVC only as an extension hose, 3~ IVR reduction required.		
Suction hose, available by the	32	9.980-678.0		ID 42			Electrically conductive, without connections, whole metres up tomax. 15 m,	32	
metre, PU, screw connection	33	9.980-649.0		ID 52			price per metre, max. temperature 80 °C, for liquids andabrasive solids.	33	
	34	9.980-650.0		ID 72				34	
Suction hose, available by the metre, light PU, screw connection	35	9.980-679.0		ID 42			Electrically conductive, without connections, whole metres up tomax. 15 m, price per metre, max. temperature 80 °C, for liquids and solids.	35	
	36	9.980-680.0		ID 52			Suction hose available in bulk, lightweight, PU (max. 15 m), ID 50, without tap adapters.	36	
	37	9.980-681.0		ID 72			Electrically conductive, without connections, whole metres up tomax. 15 m, price per metre, max. temperature 80 °C, for liquids and solids.	37	
Suction hose, PU,	38	6.906-786.0	1 piece(s)	ID 51	5 m		Electrically conductive, ID 51 connection and hinge at both ends,	38	
socket plug connection	39	6.906-788.0	1 piece(s)	ID 51	10 m		max. temperature 80 °C, for liquids and abrasive solids.	39	
Metal hoses									
Suction hose, ME-PU,	40	6.907-304.0	1 piece(s)	ID 42	3 m		Electrically conductive, ID 72 machine connection with star screw, slit and	40	
screw connection		6.907-305.0	1 piece(s)	ID 42			ID 42 accessory end hinge, max. temperature 110 °C, for metalshavings with liquids.	41	
	42	6.907-306.0	1 piece(s)	ID 52	3 m		Electrically conductive, ID 72 machine connection with star screw, slit and	42	
	43	6.907-307.0	1 piece(s)	ID 52	5 m		ID 52 accessory end hinge, max. temperature 110 °C, for metalshavings with liquids.	43	
	44	6.907-308.0	1 piece(s)	ID 72	3 m		Electrically conductive, ID 72 machine connection with star screw, slit and	44	
	45	6.907-309.0	1 piece(s)	ID 72	5 m		ID 72 accessory end hinge, max. temperature 110 °C, for metalshavings with liquids. Can also be used as an extension hose.	45	
Connection hose, ME-PU,	46	6.907-318.0	1 piece(s)	ID 42	3 m		Electrically conductive, ID 42 connection at both ends, slit and accessory	46	
screw connection	47	6.907-319.0	1 piece(s)	ID 42	5 m		end hinge, max. temperature 110 °C, for metal shavingswith liquids. IVC only as an extension hose, IVR only with reduction.	47	
	48	6.907-320.0	1 piece(s)	ID 52	3 m		Electrically conductive, ID 52 connection at both ends, slit and accessory	48	
	49	6.907-321.0	1 piece(s)	ID 52	5 m		end hinge, max. temperature 110 °C, for metal shavingswith liquids. IVC only as an extension hose, 3~ IVR reduction required.	49	
Suction hose, available by the	-	9.980-647.0		ID 42			Electrically conductive, without connections, whole metres up tomax. 15 m,	50	
metre, ME-PU, screw connection	51	9 980-707 0		ID 52			price per metre, max. temperature 110 °C, for metalshavings with liquids.	51	

metre, ME-PU, screw connection

51 9.980-707.0 | ID 52 | price per metre, max. temperature 110 °C, for metalshavings with liquids.

□ Available accessories. More Kärcher original accessories can be found on the following pages.

IV NOZZLES



For small or large surfaces, wet or dry suction material – the robust nozzles for industrial vacuums are designed for the toughest jobs.

























18

									100/75 M 100/55 M	100/40	100/75 Lp	100/55 Lp 100/40 Lp	100/40 Pf 60/30	50/40 Pf	40/30 PT 40/15 Pf	35/20-2 Pf Me 60/30 Tact²	60/30 Ap 60/24-2 Tact ²	60/24-2 Ap 60/24-2 Tact ² M	60/30 Tact² Lp	60/24-2 Tact Ec	160/30 M Z22 100/75 M Z22	100/55 M 222 60/30 Ap M 222	60/12-1 Ec H Z22 -B 50/30	-B 30/15 Me -L 100/30	-L 120/24-2 Tc Me Dp	L 120/24-2 TC	-L 100/24-2 Tc Me Dp -L 100/24-2 Tc Me	-L 100/24-2 Tc	IVR-L 100/24-2 Me IVR-L 100/24-2 IVR-L 65/12-1 Tc	-L 40/12-1 50/24-2
	Order no.	Quantity	ID	Length	Width	Price	Description		IVS IVS	S		S S	<u> </u>		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	₹ ≥	2 2	2 2		2 2	<u> </u>	2 ≥	≥	∑ S S	N N N N N N N N N N	. <u>S</u>	₹	N S	₹ Ş Ş	돌물
Floor nozzles																						L /	L, J			4	4.7		4	L, I
Multi-purpose floor nozzle, wet/dry					370 mm		Multi-purpose nozzle for floor cleaning, width 370 mm.	1			\perp				\rightarrow	-		-	-	\rightarrow		\perp	'			101				
	2 6.902-184.0	_			370 mm			2																		101			ם נ	
	3 6.902-186.0	1 piece(s)	ID 52		500 mm		Multi-purpose nozzle for floor cleaning, width 500 mm.	3												1	\perp	\perp				101] [\perp
Brush strip	4 6.903-067.0	1			500 mm		Brush strip for multi-purpose nozzle 500 mm 6.902-186.0.	4														\perp				1 0 1			ם נ	
Multi-purpose nozzle, Ex approved	5 6.902-213.0	1 piece(s)	ID 42		370 mm		Multi-purpose nozzle for floor cleaning, electrically conductive, ATEX-approved, width 370 mm, ID 42.	5																						
Heavy-duty floor nozzle	6 6.906-793.0	1 piece(s)	ID 51		500 mm		Cast aluminium floor nozzle with height-adjustable rollers for demanding applications.	6																						
Crevice tools																														
Crevice nozzle, lightweight plastic	7 9.988-116.0	1 piece(s)	ID 42				Multi-purpose crevice nozzle, plastic, ID 42.	7] 🔲 '				
	8 9.988-117.0	1 piece(s)	ID 52				Multi-purpose crevice nozzle, plastic, ID 52.	8] [[
Crevice nozzle, plastic	9 6.902-195.0	1 piece(s)	ID 42	290 mm	13 mm		Crevice nozzle, plastic, steel connection, nozzle width	9																		1 0 1	<u> </u>			
	10 6.902-194.0	1 piece(s)		340 mm	13 mm		13 mm.	10																		1 0 1			ם נ	\perp
Crevice nozzle, plastic, flexible	11 6.902-210.0	1 piece(s)	ID 42	340 mm	20 mm		Bendable plastic crevice nozzle (ID 42) with a nozzle width of 20 mm. Ideal for flexible applications thanks to high manoeuvrability.	11																		ים נ			3 0 0	
	12 6.902-211.0	1 piece(s)	ID 52	425 mm	20 mm		Bendable crevice nozzle (ID 52) of plastic for flexible applications, with a nozzle width of 20 mm.	12																		1 0				
Crevice nozzle, galvanised	13 6.902-189.0	1 piece(s)	ID 52	350 mm	17 mm		Crevice nozzle, zinc coated, ID 52, nozzle width 17 mm.	13] 🗆 [
	14 6.902-191.0	1 piece(s)	ID 72	350 mm	30 mm		Crevice nozzle, zinc coated, ID 72, nozzle width 30 mm.	14							П							JII				\Box	T			
Crevice nozzle, zinc coated, flexible	15 6.902-190.0	1 piece(s)	ID 42	490 mm	10 mm		Crevice nozzle, steel, flexible, ID 42, nozzle width 10 mm.	15] 🗆 [
Crevice nozzle, plastic	16 6.906-768.0	1 piece(s)		370 mm	50 mm		Crevice nozzle, plastic, ID 51, nozzle width 50 mm.	16								Ш							'		Ш	\perp	'			
Crevice nozzle, stainless steel	17 6.906-771.0	1 piece(s)	ID 51	400 mm	70 mm		Crevice nozzle, stainless steel, ID 51, nozzle width 70 mm.	17																						
Other nozzles				,																			4,7			4	4,7		4	L, I
Flexible nozzle, plastic	18 6.902-197.0			220 mm			Flexible nozzle, plastic, ID 42.	18			\perp												-		-	-	-			
	19 6.902-196.0			250 mm			Flexible nozzle, plastic, steel connection.	19												1						101				
	20 6.902-198.0	_		260 mm				20							1	\perp			\perp				'			101	<u> </u>			
Elongated round nozzle, rubber	21 6.902-200.0	1 piece(s)	ID 42	315 mm			Suction nozzle, rubber, round, for cutting to the required suction diameter.	21																		1 0] 0 0	
	22 6.902-199.0	1 piece(s)	ID 52	315 mm			Suction nozzle, rubber, round, for cutting to the required suction diameter.	22																		י 🗖 נ				
Round brush, angled	23 6.902-193.0	1 piece(s)	ID 42				Suction brush, round, 45°.	23			$\perp \perp$															1 0 1	<u> </u>			
	24 6.902-192.0	1 piece(s)					Suction brush, round 45°.	24												1						101			ם נ	\perp
Straight suction and air nozzle	25 6.902-205.0	1 piece(s)	ID 42				For vacuuming out blind holes and other uneven surfaces. Separate compressed air connection required.	25																		י 🗀 נ				
Surface brushes	26 6.902-204.0	1 piece(s)	ID 42		120 mm		Surface nozzle with brush insert, plastic, width 120 mm, ID 42.	26						-												ין ם נ				
Surface nozzle, aluminium	27 6.902-188.0	1 piece(s)	ID 42		150 mm		Surface nozzle, aluminium, width 150 mm.	27]				
	28 6.902-187.0				150 mm			28														٦] 🗆			ם כ	
Tube suction nozzle	29 6.902-207.0	1 piece(s)	ID 42				For cleaning tubes and other line systems with a diameter of up to 200 mm.	29																		J -				
Rubber suction nozzle, 45°	30 6.902-146.0	1 piece(s)	ID 51	220 mm			Angled 45°, for vacuuming of machines, oil-resistant.	30			\top		$\neg \uparrow \uparrow$	\top	\top	$\neg \neg \neg$			\top	\top		\top	7			\top	\top			
Elongated round nozzle, rubber	31 6.906-764.0	1 piece(s)	ID 51	370 mm			Suction nozzle, rubber, round, for cutting to the required suction diameter.	31												П										
Scratcher and scraper nozzle, plastic	32 6.906-773.0	1 piece(s)	ID 51		100 mm		Suction nozzle, plastic, for vacuuming machines and small surfaces.	32														\top				\prod				

☐ Available accessories. More Kärcher original accessories can be found on the following pages.







	Order no.	Quantity	ID	Length	Width Price	Description		IVS 100/75 M IVS 100/55 M IVS 100/40 IVS 100/40 IVS 100/40 IVS 100/40 M IVS 100/40 M IVS 100/40 Lp IVS 100/75 Lp IVS 100/75 Lp IVS 100/75 Lp IVS 100/75 Lp IVS 100/40 Pf IVM 60/30 IVM 60/30 IVM 60/30 IVM 60/30 Pf IVM 60/30 M Z22 IVM 60/30 T T T T T T T T T T T T T T T T T T T
Suction nozzles								
Suction and air nozzle, 90° angled	34 9.981-926.0	1 piece(s)	ID 42			For easy vacuuming of all kinds of recesses – for example blind holes. Please note that a separate compressed air connection is required.	34	
Vacuum brush	35 9.981-911.0	1 piece(s)	ID 42		300 mm	Vacuum brush, 300 mm, with 45° connection,	35	
	36 9.981-912.0	1 piece(s)	ID 52		300 mm	with star screw, horsehair bristles.	36	
Crevice nozzle, zinc coated, flexible	37 9.981-423.0	1 piece(s)	ID 42	490 mm	20 mm	Crevice nozzle, steel, zinc coated, flexible, slit width	37	
	38 9.981-425.0	1 piece(s)	ID 52	490 mm	20 mm	20 mm.	38	
Nozzle, zinc coated, flexible, with rubber tip	39 9.981-420.0	1 piece(s)	ID 42		30 mm	Round nozzle, steel, zinc coated, flexible, with rubber tip ID 30.	39	
Nozzle, zinc coated, flexible, with rubber tip	40 9.981-421.0	1 piece(s)	ID 52		30 mm		40	

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

VACUUM CLEANERS

IV BENDS AND SUCTION TUBES



Bends and suction tubes for an ergonomic working posture while vacuuming.















	Order no.	Quantity	ID	Length	Width	Price	Description		IVS 100/75 M IVS 100/75 M IVS 100/40 IVS 100/40 M IVS 100/40 M IVS 100/40 PF IVS 60/30 PF IVS 60/30 PF IVS 60/30 PF IVS 60/24-2 PF Me IVC 60/24-2 Tact² IVS 100/75 M Z22 IVC 60/24-2 Tact Me IVR-100/24-2 Tc Me IVR-100/24-2 Tc Me IVR-100/24-2 Tc Me IVR-100/24-2 Tc
Bend, coated									
Bend, screw connection	1 6.902-202.0		ID 42				Bend, powder-coated steel, electrically conductive,	1	
	2 6.902-201.0						with star screw.	2	
	3 6.902-203.0	1 piece(s)	ID 72				Bend, coated, electrically conductive, ID 72; without tap adapters.	3	
Suction tube, coated									
Suction tube, screw connection	4 6.902-182.0	1 piece(s)	ID 42		750 mm		For floor cleaning in combination with bend (6.902-202.0) and ID 42 floor nozzles.	4	
	5 6.902-181.0	1 piece(s)	ID 52		850 mm		For floor cleaning in combination with bend (6.902-201.0) and ID 52 floor nozzles.	5	
	6 9.981-910.0	1 piece(s)	ID 72		750 mm		Suction tube ID 72, tube length ID 750 mm. For connection with hose and bend ID 72 (6.902-203.0).	6	
Stainless steel bends									
Bend, stainless steel, socket plug connection	7 6.906-767.0	1 piece(s)	ID 51				The stainless steel bend has a nylon ring in the upper cone area. This ring makes it easy to detach the bend even after prolonged use.	7	
Suction tubes stainless steel									
Suction tube, stainless steel, socket plug connection	8 6.906-766.0	1 piece(s)	ID 51	500 mm			The suction tube (500 mm) has a nylon ring in the upper cone area. This ring makes it easy to detach the bend even after prolonged use.	8	
Bend									
Bend with hook,	9 9.981-327.0						Bend, powder-coated steel, electrically conductive,	9	
screw connection	10 9.981-320.0	1 piece(s)	ID 52				with star grip and hook for hanging hose.	10	

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

IV CONTAINERS AND PRE-SEPERATORS



Choose the right container for your machine and application.























~							
	Order no.	Quantity	ID	Width	Price Description		IVR 100/40 Pf IVM 60/30 IVM 60/30-30 IVM 60/36-3 IVR 50/40 Pf IVR 50/40 Pf IVR 60/30-2 Pf Me IVC 60/30 Tact² IVC 60/30 Tact² IVC 60/24-2 Tact² Lp IVR-1 100/24-2 Tact² Lp
Suction container and swarf bask	ets		•	·			
UBS Longopac disposal system	1 2.013-050.0	1 piece(s)			Clever feature of the Longopac disposal system: instead of the suction container, this attachment kit can also be used for disposal bags with the part number 6.907-506.0.	1	
Container, stainless steel, 60 l	2 4.070-837.0	1 piece(s)			60 I stainless steel container for IV and IVC.	2	
Container, stainless steel, 60 l, with suction hose port	3 4.070-930.0	1 piece(s)			60 I stainless steel container with suction hose port, compatible with IVC and IV 60. For the use of paper filter bags (6.904-285.0) and safety filter bags (6.904-420.0).	3	
Container, stainless steel, 100 l	4 4.070-838.0	1 piece(s)			Stainless steel container, 100 I, with 2 heights for IVC and IV.	4	
Conversion kit liquid	5 2.882-695.0	1 piece(s)			Ball tap and chip sieve, suitable for 4.070-837.0 and 4.070-838.0.	5	
Swarf basket IVC	6 2.860-268.0	1 piece(s)			For separating liquid and coarse solid suction waste (e.g. swarf), suitable for 4.070-837.0, 4.070-838.0 and all IVC containers.	6	
Drum separator	7 9.982-081.0	1 piece(s)	ID 52		Filling device with ID 52 connections, screw connection, for filling of e.g. 200 l drums via the bunghole.	7	
Pre-separator cover for 200 I drum	8 9.986-371.0	1 piece(s)	ID 52		Pre-separator cover for 200 I standard drum with ball float for overfill prevention. Screw connection ID 52.	8	
	9 9.986-370.0	1 piece(s)	ID 52		Pre-separator cover for 200 l standard drum. Screw connection ID 52.	9	
Pre-separator, 125 I, complete	10 9.986-372.0	1 piece(s)	ID 52		Pre-separator, coated, complete with cover, ID 52 connections, ball float for overfill prevention, 125 I container and tilting chassis.	10	
Swarf basket, 20 I	11 9.980-852.0	1 piece(s)		400 mm	For separating liquid and coarse suction waste. Stainless steel, 20 I capacity, hole diameter 1.5 mm.	11	
Swarf basket 40 I	12 9.980-849.0	1 piece(s)		495 mm	Strainer basket, stainless steel, 40 l, hole diameter 1.5 mm.	12	
Fine fleece, 40 I swarf basket	13 9.981-048.0	1 piece(s)		465 mm	Fine polyester fleece for separating fine metal shavings and liquids. With clamping ring suitable for 40 I swarf basket.	13	
Float insert	14 9.982-118.0			435 mm	Float insert, stainless steel, for overfill prevention with ball float,	14 15	
	15 9.982-117.0	1 piece(s)		540 mm	central suction.	15	

[■] Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

IV ADAPTERS AND SPARE PARTS



With Kärcher individual parts, you can construct your customised suction hose. Simply select the suction hose in the desired length and combine it with the connection pieces.



























	5
•	23-25

	Order no.	Quantity	ID	Price	Description		IVS 100/75 M IVS 100/55 M	IVS 100/40	IVS 100/40 M IVS 100/75 Lp IVS 100/55 Lp	IVS 100/40 Lp IVR 100/40 Pf	IVM 60/30 IVM 60/36-3	IVR 50/40 Pf	IVR 40/15 Pf	IVC 60/30 Tact ²	IVC 60/24-2 Tact ²	IVC 60/24-2 Tact ² M	IVC 60/24-2 Tact ² Lp	IVC 60/12-1 Tact Ec IVM 60/30 M Z22 IVC 100/75 M Z22	IVS 100/55 M Z22	IVC 60/12-1 Ec H Z22 IVR-B 50/30	IVR-L 120/24-2 Tc Me Dp IVR-L 120/24-2 Tc Me	IVR-L 120/24-2 TC IVR-L 100/24-2 TC Me Dp	00/24-2 TC 00/24-2 TC	IVR-L 100/24-2 Me IVR-L 100/24-2 IVB-I 65/12-1 Tc	IVR-L 65/12-1 TC IVR-L 40/12-1 IVL 50/24-2
Adapters and spare parts																									
Adapter IVC/IVR to ID 61	1 6.902-001.0	1 piece(s)	ID 61		For using IV accessories on IVC and IVR.	1												J							
Reducer ID 52 to ID 42	2 6.902-179.0	1 piece(s)	ID 52		Reducer from ID 52 to ID 42.	2												5					J 0 C] [[
Reducer, ID 72 to ID 52	3 6.902-180.0	1 piece(s)	ID 72		Reducer piece from ID 72 to ID 52.	3																			
Vacuum connector, ID 72 to ID 42	4 6.902-178.0	1 piece(s)	ID 72		For attaching to ID 72 suction hose ports and reductionon ID 42 hoses.	4																			
Vacuum connector, ID 72 to ID 52.	5 6.902-177.0	1 piece(s)	ID 72		For attaching to ID 72 suction hose ports and reductionon ID 52 hoses.	5																			
Hose connection	6 6.902-170.0	1 piece(s)	ID 42		For attachment to hose ID 42, with star screw.	6																	J 0 C	J 0 C	
	7 6.902-168.0	1 piece(s)	ID 52		For attachment to hose ID 52, with star screw.	7																	J 0 C		
	8 6.902-173.0	1 piece(s)	ID 72		For attachment to hose ID 72, with star screw.	8]												
Hose connection, rotatable	9 6.902-172.0	1 piece(s)	ID 42		Rotatable, for attachment to hose ID 42, with star screw.	9] [J 0 C	J 0 C	
	10 6.902-169.0	1 piece(s)	ID 52		Rotatable, for attachment to hose ID 52, with star screw.	10																	J 0 C		
	11 6.902-175.0	1 piece(s)	ID 72		Rotatable, for attachment to hose ID 72, with star screw.	11]												
Hose clamp	12 6.902-167.0	1 piece(s)	ID 42		For attaching hose to connection ID 42/52.	12											1 0 1	<u> </u>					J 0 C	J 0 C	
Hose clamp	13 6.902-176.0	1 piece(s)	ID 72		For attaching hose to connection ID 72.	13																			
Hose sleeve	14 6.902-171.0	1 piece(s)	ID 42		For covering the hose clamp connection ID 42.	14																	J 0 C	J 0 C	
	15 6.902-166.0	1 piece(s)	ID 52		For covering the hose clamp connection ID 52.	15] [
	16 6.902-174.0	1 piece(s)	ID 72		For covering the hose clamp connection ID 72.	16]												
Star grip M 6	17 6.303-555.0	1 piece(s)	ID 42		M 6 star knob, replacement for all bends and connectors ID 42.	17												<u> </u>					J 0 C	J 0 C	
Star grip M 8	18 6.303-554.0	1 piece(s)	ID 52		Star grip M 8 as replacement for all bends and ID 52/72 tap adapters.	18																			
Y connector ID 72 to 2 × ID 52	19 6.902-206.0	1 piece(s)	ID 72		Junction for machine connection ID 72 to two ID 52 connections.	19																			
Adapter	20 6.906-799.0	1 piece(s)	ID 51		Connecting adapter for connecting 2 ID 51 suction hoses.	20																			
Vacuum connector, 90°	21 9.981-313.0	1 piece(s)	ID 72		90° connector for IVR vacuums with connection adapter ID 72 and hook for hose attachment, rotatable by 360°.	21				•			•												
Vacuum connector 115°	22 9.986-213.0	1 piece(s)	ID 52		115° connector for IVR-L vacuums with connection adapter ID 52 and hook for hose attachment, rotatable 360°.	22							-											1	
Hose connection	23 9.981-260.0	1 piece(s)	ID 42		For attachment to hose ID 42, with slit and hook for hose attachment.	23												J] [[] [[
	24 9.981-261.0	1 piece(s)	ID 52		For attachment to hose ID 52, with slit and hook for hose attachment.	24																	J 0 C		
	25 9.981-145.0	1 piece(s)	ID 72		Hose connection piece with hooks and internal cone ID 70.	25] [
Accessories connection	26 9.981-325.0	1 piece(s)	ID 52		Rotatable, for attachment to hose ID 52, inner taper for attaching accessories.	26] [[
	27 9.981-326.0	1 piece(s)	ID 72		Rotatable, for attachment to hose ID 72, inner taper for attaching accessories.	27																			
Y-adapter ID 52 to 2 × ID 42	28 9.981-149.0	1 piece(s)	ID 52		Hose pipe ID 50/40/40; external cone ID 50 on 2 × internal cone ID 40.	28																	3 0 0		
Roller attachment kit	29 9.986-099.0	4 -part			Roller attachment kit for attaching to build-in units. For using IVR-B for mobile applications.	29																			

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

IV FILTERS AND WASTE DISPOSAL BAGS



Flat pleated filters save time, space and resources. Star and pocket filters have long working times and are particularly suitable for adhesive suction waste with a high level of residual moisture

























		Order no.	Quantity	Width	Price	Description		IVS 100/75 M IVS 100/55 M IVS 100/40	IVS 100/40 M IVS 100/75 Lp	IVS 100/40 Lp IVR 100/40 Pf IVM 60/30	IVR 50/40 Pf	IVR 40/15 Pf IVR 35/20-2 Pf Me	IVC 60/24-2 Tact ²	IVC 60/24-2 Ap IVC 60/24-2 Tact ² M	IVC 60/20-1 Tact Lp IVC 60/12-1 Tact Ec IVM 60/30 M Z22	IVS 100/75 M Z22 IVS 100/55 M Z22	IVC 60/30 Ap M Z22 IVC 60/12-1 Ec H Z22 IVR-B 50/30	IVR-B 30/15 Me IVR-L 100/30	IVR-L 120/24-2 TC Me Dp IVR-L 120/24-2 TC Me IVR-L 120/24-2 TC	IVR-L 100/24-2 TC Me Dp IVR-L 100/24-2 TC Me IVR-L 100/24-2 TC	IVR-L 100/24-2 Me IVR-L 100/24-2 IVR-L 65/12-1 Tc IVR-L 40/12-1
Flat pleated filter, PTFE																					
Flat pleated filter, PTFE	1	6.907-449.0	1 piece(s)			Polyester fleece with PTFE coating, dust class M, for Tact ² vacuum cleaners. Particularly suitable for very adhesive materials.	1														
Flat pleated filter, paper																					
Flat pleated filter, paper		6.904-283.0				Paper, dust class M (also NT 65/2 Eco / opt. for NT 75/2 Eco Tc models).	2									<u> </u>	•				
Flat pleated filter, paper	3	6.907-276.0	1 piece(s)			Paper, approved for dust class M.	3														
Flat pleated filter, PES																					
Flat pleated filter, PES	4	6.907-277.0	1 piece(s)			Polyester fleece, rot-proof, dust class M.	4						• •								
HEPA, dust class H filter																					
HEPA flat pleated filter	5	6.904-364.0	1 piece(s)			HEPA flat pleated filter, dust class H (HEPA 13).	5														
Filters and waste disposal bags																					
Star filter IVS	6	6.907-611.0	1 piece(s)			Microfibre star filter, dust class M, replacement for IVS and IVS Lp.	6			ı ∎											
Star filter IVS Z22	7	9.988-120.0	1 piece(s)			Microfibre star filter, electrically conductive, dust class M, replacement for IVS Z22.	7	• • •													
Longopac disposal bag Mini	8	6.907-506.0	4 piece(s)			Longopac disposal bag for use with special attachment kit (part number 2.013-050) from the Longopac disposal system programme.	8														
Disposal bags, paper	9	6.904-346.0	10 piece(s)			Disposal bag, paper, 60 I, for low-dust disposal of suction waste.	9														
	10	6.904-347.0	10 piece(s)			Disposal bag, paper, 60-100 I, for low-dust disposal of suction waste.	10														
Disposal bags, PE	11	6.904-348.0	20 piece(s)			Disposal bag, PE, 20 pcs, 60-100 l, for low-dust disposal of suction waste.	11														
	12	6.907-336.0	5 piece(s)			Disposal bag, PE, 5 pcs, 100 l, for low-dust disposal of suction waste.	12														
	13	6.907-347.0	5 piece(s)			Disposal bag, PE, 5 pcs, 50 l, for low-dust disposal of suction waste.	13									1					
Disposal bags, PE, for IVS	14	6.907-609.0	5 piece(s)			Disposal bags, PE, 5 pcs, 100 I, for low-dust disposal of suction waste, with integrated pressure compensation.	14														
Safety filter bags	15	6.904-420.0	5 piece(s)			For dust-free/low-dust emptying in conjunction with the 4.070-930.0 container, with dust disposal bag, electrically conductive. Checked and approved for dust class H.	15										•				
Surface filter	16	9.980-225.0	1 piece(s)	370 mm		Surface filter, 0.25 m², polyester needle felt, dust filter class L.	16														
	17	9.980-179.0	1 piece(s)	480 mm		Surface filter, 0.45 m², polyester needle felt, dust filter class L.	17											I			• •
Pocket filter	18	9.980-227.0	1 piece(s)	400 mm		Pocket filter, 1.4 m², antistatic, dust filter class M.	18														
	19	9.981-681.0	1 piece(s)	490 mm		Pocket filter, 1.75 m², antistatic, dust filter class M.	19														
Cartridge filter	20	9.980-219.0	1 piece(s)	190 mm		Cartridge filter, 0.7 m², antistatic, dust filter class M.	20														
Downholder	21	9.980-140.0	1 piece(s)			Downholder for waste disposal bags, 50 I, 6.907-347.0. Prevents the bag from being vacuumed up during vacuuming operation.	21				•										
	22	9.980-141.0	1 piece(s)			Downholder for waste disposal bags, 100 I, 6.907-336.0. Prevents the bag from being vacuumed up during vacuuming operation.	22			•											

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

IIM CI EANED

IV OTHER ACCESSORIES



By emptying with a crane or forklift truck you can quickly and easily empty filled containers up to 260 kg.















		Order no.	Quantity	ID	Width	Price	Description		IVS 100/75 M IVS 100/55 M IVS 100/40 IVS 100/40 M IVS 100/75 Lp	IVS 100/55 Lp IVS 100/40 Lp IVR 100/40 Pf IVM 60/30	IVM 50/30 Pf IVR 40/30 Pf IVR 40/15 Pf	IVC 60/30 Tact ² IVC 60/30 Ap IVC 60/24-2 Tact ²	IVC 60/24-2 Ap IVC 60/24-2 Tact² M	IVC 60/30 Tact* Lp IVC 60/24-2 Tact* Lp IVC 60/12-1 Tact Ec	IVM 60/30 M Z22	IVS 100/55 M Z22 IVC 60/30 Ap M Z22	IVC 60/12-1 EC H 2.22 IVR-L 100/30
Miscellaneous																	
Remote control IVS 100	1	2.273-001.0	1 piece(s)				Remote control for IVS machines. For control panel with up to 30 m distance.	1									
Crane and forklift emptying device	2	2.642-842.0	1 piece(s)				For container emptying of all IV and IVC containers with a crane or forklift truck. Empty using a crank mechanism. Max. 260 kg.	2							J 🗆 📗		
IVC wide nozzle	3	2.642-864.0	1 piece(s)	ID 42	877 mm		For cleaning large areas. Height adjustable +/- 4 mm, 877 mm working width.	3]		
Metal funnel IVS, IVC	4	5.013-097.0	1 piece(s)				IVS spacer with cone. For cyclone-like pre-separation of suction waste.	4									
Cable drum with 25 m cable	5	9.982-080.0	1 piece(s)				AC cable drum with 25 m cable, for fixing in accessories holder 6.645-412.0.	5									
Power cable storage compartment	6	5.037-240.0	1 piece(s)				For hanging the power cord on the push handle.	6							ı		
IVC accessories holder	7	4.645-412.0	1 piece(s)				For attaching IVC accessories with nominal widths ID 42 and ID 52. Attaches to IVC frame.	7			3				1		
IVC drip tray	8	5.039-065.0	1 piece(s)				For collecting dirt residues from the floor nozzle.	8							1		
Accessories for Ringler machines																	
Pre-separator station RI 300	9	9.982-235.0					Pre-separation system RI 300; with cover, with or without float ball as overfill protection, emptying hose filling level indicator, moveable and tilting, forklift transport for liquids and shavings.	9			ם						

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

DRY VACUUM CLEANERS FOR PROFESSIONAL MAINTENANCE CLEANING

Our dry vacuum cleaners have to pass stringent tests before we let them leave the factory. These machines are extremely lightweight, robust, durable and quiet. They have been specially developed for professional use in hotels, offices and retail, and they satisfy the highest requirements in the professional building cleaning sector. Our new battery-powered vacuum cleaners are now also considerably more powerful, meaning you can achieve the same excellent cleaning results you get from mains-operated machines – only cordlessly and flexibly.




Table of contents: Dry vacuum cleaners

Dry vacuum cleaners	Page	38
Battery-operated dry vacuum cleaners	Page	39
Backpack vacuums	Page	39
Battery-powered handheld vacuum cleaners	Page	39
Battery-powered electric brooms	Page	39
Upright brush-type vacuum cleaners	Page	40
Accessories	Page	40



eco!efficiency dry vacuum cleaners

Our dry vacuum cleaners with ecolefficiency function consume less and do more. And they are quiet enough for use in noise-sensitive areas.

Battery-operated dry vacuum cleaners

Flexibility without compromise or power cords: our battery-operated dry vacuum cleaners.

Battery-powered handheld vacuum cleaners

Our innovation for powerful cleaning without a power cord. With compatible accessories for building cleaning, industry and the automotive sector

How to read the machine names:

Model	Container capacity	Turbines	Type and equipment		Configuration options	
	Working width					
Example: T Example: CV Example: EB Example: HV	15 38 30 1	1 2 1 1	eco!efficiency Adv		Li-ion Bp Fs	
T = Dry vacuum cleaner BV = Backpack Vacuum EB = Electric Broom (battery-powered) CV = Carpet Vacuum,	In machine names for dry vacuum cleaners with a combination of numbers, the first number indicates the container capacity (in litres).	In machine names with a combination of numbers, the second number indicates the number of turbines.	Classic Adv	 Standard equipment Basic equipment Advanced, with additional equipment Ride-on/step-on machine 		 Battery-powered Package (battery and battery charger included in the scope of supply) Lithium-ion battery
upright brush-type vacuum cleaner HV = Handheld Vacuum (battery-powered)	For EB and CV machines , the first number indicates the working width of the roller brush (in centimetres).		eco!efficiency	= Machine with eco!efficiency function	As Cs Fs	Automotive setConstruction setFacility set

DRY VACUUM CLEANERS: INDEPENDENT AND QUIET


In many industries, it's the intelligent solutions that count, such as significantly quieter operation, easy and quick cable replacement and complete accessory integration. These are the features of Kärcher dry vacuum cleaners that impress professional operators such as building service contractors or cleaning personnel in hotels and retail.

		Order no.	Container capacity (I)	Air flow rate (I/s)	Vacuum (mbar / kPa)	Protection class	Antistatic bend	Energy efficiency class*	Annual energy consumption* in kWh/year	Carpet cleaning performance class	Hard floor cleaning performance class	Dust re-emission class	Sound power level dB(A)	Nominal power consumption (W)	Page
	Dry vacuum cleaners														
-	T 15/1 ecolefficiency	1.355-246.0	15	46	185 / 18.5	II	•	A+	19	С	С	D	74	500	385
	T 12/1 ecolefficiency	1.355-135.0	12	46	185 / 18.5	II	•	A+	18.5	С	С	D	73	500	385
/	T 10/1 eco!efficiency	1.527-413.0	10	46	185 / 18.5	II	•	A+	19	С	С	D	71	500	385
/	T 7/1 ecolefficiency	1.527-145.0	7	46	185 / 18.5	II		A+	19.1	С	С	E	75	500	385
1_1	T 15/1 HEPA	1.355-235.0	15	53	240 / 24	II	•	В	30	С	D	В	76	800	387
1	T 15/1	1.355-200.0	15	53	240 / 24	II	•	В	30.4	D	С	D	76	800	387
/	T 12/1	1.355-100.0	12	53	240 / 24	II	•	В	31.4	D	С	D	75	800	389
1	T 12/1 Hf	1.355-147.0	12	53	240 / 24	II	•	С	36	E	D	C	75	800	389
-	T 10/1 Adv	1.527-154.0	10	53	240 / 24	II		В	30.1	D	С	D	73	800	390
	T 10/1	1.527-150.0	10	53	240 / 24	II		В	30.1	D	С	D	73	800	390
	T 14/1 Classic	1.527-170.0	14	40	285 / 28.5	II	-	-	-	-	-	-	-	-	393
	T 8/1 L	1.527-188.0	8	40	235 / 23.5	II	-	Α	27	-	D	D	76	850	391
	T 8/1 Classic	1.527-160.0	8	47	285 / 28.5	II	-	-	-	-	-	-	-	-	393
	T 7/1 Classic	1.527-181.0	7.5	40	235 / 23.5	II	-	С	37.5	Е	С	D	75	850	393
	BV 5/1	1.394-200.0	5	53	240 / 24	Ш		В	30.5	D	С	С	76	800	395
1	Cordless machines														
/ \	T 9/1 Bp	1.528-111.0	9	46	207 / 20.7	II	•	-	-	-	-	-	-	650	394
/_ QR	BV 5/1 Bp	1.394-219.0	5	46	207 / 20.7	II		-	-	-	-	-	-	650	395
/G 7	HV 1/1 Bp Fs ■	1.394-221.0	1	34	47 / 4.7	II	-	-	-	-	-	-	79	100	397
/	HV 1/1 Bp Cs ■	1.394-222.0	1	34	47 / 4.7	II	-	-	-	-	-	-	79	100	397
1 10	HV 1/1 Bp As ■	1.394-223.0	1	34	47 / 4.7	II	-	-	-	-	-	-	79	100	397
-	EB machines														
	EB 30/1 Adv Li-Ion	1.545-127.0	1	-	-	III	-	-	-	-	-	-	-	-	399
	EB 30/1 Li-lon	1.545-126.0	1	-	-	III	-	-	-	-	-	-	-	-	399
	Upright brush-type vacuum c	leaners													
a	CV 60/2 RS Bp Pack	1.011-028.0	17	34	117 / 11.7	II	-	-	-	-	-	-	-	-	401
rX.	CV 60/2 RS	1.011-027.0	17	34	117 / 11.7	Ш	-	-	-	-	-	-	-	-	401
-	CV 66/2	1.012-585.0	35	2 × 52	143 / 14.3	II	-	-	-	-	-	-	-	-	403
	CV 48/2 Adv	1.057-329.0	5.5	40	200 / 20	Ш	-	A+	21.8	D	-	F	80	850	405
	CV 48/2	1.057-328.0	5.5	40	200 / 20	II	-	A+	21.8	D	-	F	80	850	405
	CV 38/2 Adv	1.033-336.0	5.5	40	200 / 20	II	-	Α	25.8	С	-	F	79	850	405
	CV 38/2	1.033-335.0	5.5	40	200 / 20	II	-	А	25.8	С	-	F	79	850	405
	CV 30/1	1.023-121.0	5.5	43	193 / 19.3	П	-	В	32.5	В	-	F	80	850	407

- NEW
- Included in the scope of supply.
- Indicative annual energy consumption (kWh per year) based on 50 cleaning processes.
 The actual annual energy consumption depends on how the machine is used.

THE EUROPEAN ENERGY LABEL FOR VACUUM CLEANERS

What Kärcher has long proven with our ecolefficiency vacuum cleaners is now law throughout Europe: successful cleaning with less power. The EU energy label for vacuum cleaners, applicable since 1st September 2017, limits the nominal power of mains-operated dry vacuum cleaners to a maximum of 900 watts. Every machine sold in Europe must have the EU energy label. Kärcher's "Standard" and "ecolefficiency" dry vacuum cleaner lines are powerful and efficient, giving customers everything they could possibly want.



Efficiency at a glance

The efficiency class is a standardised classification applicable throughout Europe and is instantly recognisable. The classification from A+++ to D, which came into force on 1st September 2017, allows for direct comparison. Classification in an efficiency class depends on the annual energy consumption (AE), which is calculated from a range of different parameters. The power input of the vacuum cleaner is therefore particularly important, but cleaning power is part of the assessment criteria

A reference for comparison

The annual energy consumption (AE) is based on a defined number of cleaning processes (50 per year) in a standard

living area (87 m^2) and is indicated as a reference value on the energy label. This value must be < 43 kWh/a (Class D) and is highlighted on the energy label. The actual annual energy consumption depends on user behaviour, however, and in particular on the degree of soiling, the surface being cleaned and the frequency with which cleaning is carried out.

All the power without the noise

18,5

Saving energy isn't the only thing that's good for the environment – reducing noise is too. A difference in the noise level of ± 3 dB(A) corresponds to twice or half the perceived

noise level. This means that a vacuum cleaner with a sound power level of 77 dB(A) is perceived as being only half as loud as one with a maximum permissible level of 80 dB(A). By listing the sound power level, the energy label provides an additional objective aid to decision-making.

Vacuuming and retaining dust

With vacuuming, the amount of dust emitted into the air is a crucial factor too. In addition to the cleaning performance, the quantity of dust that escapes from the vacuum ("dust re-emission") is also important and is classified on the energy label from A

re-emission") is also important and is classified on the energy label from A to G. The new limit for dust re-emission is < 1.00%.

Clean division between hard and soft

The differences between cleaning hard floors and carpets are significant and the surfaces cannot be directly compared. The classes for hard floors and carpets are therefore shown separately. In addition to the energy efficiency class for universal vacuum cleaners, the hard floor cleaning performance class and carpet cleaning performance class are also shown on the energy label in classes from A to G. Special vacuum cleaners do not have a label for the other type of flooring. The minimum requirements for dust intake are dpu $_c \ge 75\%$ for carpets and dpu $_{hf} \ge 98\%$ for hard surfaces.







1 Visibly safe and reliable


The yellow Highflex cord is extremely tough, flexible and twist-proof. Its bright colour makes it easy to see immediately, thus preventing tripping hazards.

2 It really works: doing more with less

Maximum cleaning power using 40 per cent less electricity. And much quieter too – a quarter of the normal noise level. Our ecolefficiency machines impressively demonstrate that eco-friendliness and efficiency can go hand in hand.

3 Lithium-ion technology

The powerful 36-Volt lithium-ion battery ensures that you can work for long periods without stopping yet with excellent cleaning performance, making our battery-powered machines as powerful as their mains-operated counterparts.







4 The six-stage filter system including HEPA

The six-stage filter system with three-ply fleece filter bag, permanent main filter, motor protection filter and exhaust/HEPA filter ensures a separation degree of up to 99.997 per cent for optimal dust separation in HEPA quality.

5 Fleece filter technology

Kärcher fleece filters achieve higher and more constant suction power than normal filters. Compared with conventional paper filter bags, they retain more than double the amount of dust – with a 10 per cent better separation degree too. Kärcher fleece filters are extremely tear-resistant and can therefore withstand sharp-edged items such as grit or paper clips. They also last longer and are more cost-effective overall.

6 Low operating noise

The noise level of our eco!efficiency machines has been significantly reduced by using sound-proofed motors and optimum flow ducts. This allows our vacuum cleaners to be used in noise-sensitive areas such as hotels, or during normal business hours.

eco!efficiency DRY VACUUM CLEANER



eco!efficiency: maximum cleaning performance, lower consumption

T-eco!efficiency machines are characterised by 40% lower energy consumption and outstanding cleaning performance. They are very quiet and ideal for noise-sensitive places. The plug-in power cable reduces servicing costs.











1 Saving energy has never been so much fun!

■ Using only 500 W, the ecolefficiency dry vacuum cleaners clean almost ■ The cable can be replaced quickly and easily by simply loosening as thoroughly as the basic version. This allows energy-efficient working with exceptional cleaning performance.

3 Easy to service

2 screws. This saves time and service costs.

2 Low noise

■ Thanks to their low noise level, dry vacuum cleaners from the ecolefficiency range are ideal for noise-sensitive areas.

TECHNICAL DATA AND EQUIPMENT

Reduced power consumption Reduced power consumption ■ Plug-in power cable ■ Plug-in power cable Technical data ENERG VIA Energy efficiency class Α+ (out of A+++ to D) Air flow rate KARCHER KARCHER T 12/1 eco!efficienc 185 / 18.5 185 / 18.5 Container capacity Rated input power 500 500 A⁺ Voltage 220-240 220-240 Standard nominal width ID 35 ID 35 Cable length 15 12 Sound pressure level EN 60335-2-69 dB(A) 60 uncertainty K = 1 dB(A) 19,0 18,5 Sound power level 74 Weight 6.6 435 × 315 × 400 410 × 315 × 340 Dimensions (L x W x H) ABC**D**EFG ABC**D**EFG))) **73**dB Equipment Suction hose 2.5 / with bend 2.5 / with bend AB**C**DEFG AB**C**DEFG AB**C**DEFG AB**C**DEFG Telescopic suction tube standard Filter bag fleece fleece

Included in the scope of supply.

Permanent filter basket, nylon

Switchable floor nozzle

T 10/1 eco!efficiency

285

T 15/1 ecolefficiency

T 7/1 eco!efficiency

T 12/1 eco!efficiency

Reduced power consumption	
Plug-in power cable	
Low noise	

- Reduced power consumption
- Plug-in power cable


1.527-145.0

285

1.355-135.0

Technical data **Energy efficiency class** (out of A+++ to D) Air flow rate I/s 46 mbar / kPa 185 / 18.5 Vacuum Container capacity 500 Rated input power 220-240 Voltage Cable length 12 Sound pressure level EN 60335-2-69 dB(A) uncertainty K = 1 dB(A)Sound power level dB(A) 71 Weight Dimensions (L × W × H) 355 × 310 × 410 Equipment

> 270 1.527-413.0



ENERG

KARCHER A⁺ ABCD**E**FG_ **75**dB AB**C**DEFG AB**C**DEFG

ENERG Y UA

385

■ Included in the scope of supply.

Permanent filter basket, fleece

Telescopic suction tube

Switchable floor nozzle

Filter bag

Order no.

IIM CI EANEDS

DRY VACUUM CLEANER - 15 LITRES



The quietest in its class

Ideal for noise-sensitive areas like hotels, offices and hospitals: the new T 15/1 is the quietest vacuum machine of its class at just 60 dB(A) – for noise-free, effortless cleaning.









1 HEPA hygiene filter (EN 1882:1998)

- This vacuum cleaner features a Hepa filter (EN 1822:1998) for hygienically pure, particle-free exhaust air in hotels, hospitals, nurseries and many other areas.
- 3 Integrated accessory storage
- Accessory storage at the rear for easy access in any cleaning situation.

2 Highflex power cable

■ The yellow Highflex cable is extremely tough, flexible and anti-twist.

TECHNICAL DATA AND EQUIPMENT

T 15/1 HEPA

■ HEPA hygiene filter (EN 1882:1998) Integrated accessory storage Integrated accessory storage Integrated power cable/suction hose storage ■ Flexible cable Technical data Energy efficiency class ENERG Y UA (out of A+++ to D) Air flow rate KARCHER KARCHER 240 / 24 **mbar / kPa** 240 / 24 Container capacity 15 Rated input power 800 800 Voltage 220-240 220-240 Standard nominal width ID 35 ID 35 Cable length 15 Sound pressure level EN 60335-2-69 dB(A) 62 62 uncertainty K = 1 dB(A) 30,4 30,0 Sound power level Weight 435 × 315 × 400 435 × 315 × 400 Dimensions (L × W × H) A**B**CDEFG **∢))) 76**dB ABC**D**EFG_ (**))) 76**dB Equipment 2.5 / with bend ABC**D**EFG 2.5 / with bend Suction hose AB**C**DEFG ABC**D**EFG AB**C**DEFG Telescopic suction tube standard standard fleece Filter bag fleece Permanent filter basket, nylon 285 Switchable floor nozzle 285 1.355-235.0

T 15/1

■ Included in the scope of supply.

DRY VACUUM CLEANER - 12 LITRES



Dry vacuum cleaner T 12/1: you'll fly through your work

Pleasant low-noise operation, which makes it ideally suited for maintenance cleaning in noise-sensitive areas: our T 12/1 dry vacuum cleaner. Practical details, such as the ergonomic foot switch and the handy carrying handle, also make vacuuming far easier. The T 12/1 Hf machine operates with on-board voltage (110 V, 400 Hz) and is ideal for cleaning aircraft.









1 HEPA filter for clean exhaust air

■ The optional HEPA filter ensures particle-free, hygienically pure exhaust air.

3 Main filter basket

Large permanent main filter made from washable nylon for optimum dust separation. For use with or without filter bag.

2 Adapter for electrical suction brushes

■ The ESB 28 and ESB 34 transform the T 12/1 into an extra powerful yet quiet vacuum brush.

4 Foot switch for added convenience

No need to bend down.

TECHNICAL DATA AND EQUIPMENT

T 12/1 T 12/1 Hf


■ On-board voltage with 110 V and 400 Hz ■ Clip system ■ Power outlet for ESB 28 electric brush ■ Foot switch for added convenience ■ Ergonomic foot switch Technical data Energy efficiency class ENERG Y UA (out of A+++ to D) Air flow rate KARCHER KARCHER T 12/1 Hf 240 / 24 **mbar / kPa** 240 / 24 Container capacity Rated input power 800 900 220-240 110 Standard nominal width ID 35 ID 32 Cable length 12

Weight	kg	6.6	1
Dimensions (L × W × H)	mm	410 × 315 × 340	A
Equipment			— ₋
Suction hose	m	2.5 / with bend	
Suction tube, metal 2 × 0.5 m			66
Telescopic suction tube		-	_
Filter bag		fleece	
Washable permanent filter basket		-	
Washable nylon filter (main filter)		-	

dB(A)

62

1.355-100.0



■ Included in the scope of supply.

Sound level (mains operation)

EN 60335-2-69:2010

Uncertainty K = 1 dB(A) Sound power level

391

DRY VACUUM CLEANER - 10 LITRES



Developed by professionals, for professionals

The T 10/1 Adv is the ideal vacuum machine for contract cleaners. Development took place in close cooperation with professionals from the cleaning industry. Benefits: the plug-in power cable can be replaced quickly and easily and the vacuum cleaner can be operated with or without a filter bag. The antistatic bend in combination with the yellow mains plug makes working easier.



■ Included in the scope of supply.

- 1 Large, round permanent main filter of washable fleece
- Extremely strong and dense enough to allow vacuuming for longer times without a filter bag.

2 Easy to service

The cable can be replaced quickly and easily by simply loosening 2 screws. This saves time and service costs.

T 10/1 Adv

T 10/1

Plug-in power cable	
Parking position for	floor nozzle

- Parking position for floor nozzle
- Cable hook

		Extra strong permanent main filter		Accessory storage		
Technical data						
Energy efficiency class (out of A+++ to D)		В	ENERG Y (IA) EHEPTUR - EVEPYELO (IB) (IA)	В	ENERG V (IA) EHEPTUR - EVEDVEIG (IE) (IA)	
Air flow rate	I/s	53	KÄRCHER	53	KÄRCHER	
Vacuum	mbar / kPa	240 / 24	T 10/1	240 / 24	T 10/1	
Container capacity	1	10	A***	10	A***	
Rated input power	W	800	A++	800	A++	
Voltage	V	220-240	A+	220-240	A+	
Standard nominal width		ID 35	B	ID 35	B	
Cable length	m	12	C	10	C	
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	59	D	59	D	
Sound power level	dB(A)	73	ENERGIA - EHERGY - ENERGIE - ENERGI KWh/annum	73	ENERGUA - ENERGY - ENERGIE - ENERGI ENERGUA - ENERGY - ENERGIE - ENERGI kWh/annum	
Weight	kg	6.5		6		
Dimensions (L × W × H)	mm	355 × 310 × 410	ABCDEFG (4)) 73dB	355 × 310 × 385	ABCDEFG (1)) 73dB	
Equipment						
Suction hose	m	2.5 / with bend	ABC D EFG AB C DEFG	2.5 / with bend	ABCDEFG ABCDEFG	
Suction tube, metal 2 × 0.5 m			ABCDEFG ABCDEFG		ABCDEFG ABCDEFG	
Filter bag		fleece	665/2013 - II	fleece	665/2013 - II	
Permanent filter basket, fleece				-		
Permanent filter basket, nylon		-				
Switchable floor nozzle	mm	270		270		
Order no.		1.527-154.0		1.527-150.0		
Price						

DRY VACUUM CLEANER - 8 LITRES



T 8/1 L: tradesmen love it

Tough and powerful: the T 8/1 L dry vacuum cleaner has been specially developed for tradesmen who have to work in dusty environments (filter class certification L) or on ladders (weighs just 3.5 kg). Practical on-board accessory storage for easy access.





- 1 Ergonomic carrying strap
- Allows easy transport of the light machine and makes it possible to work on ladders, for example.
- 2 Secure storage options for accessories
- Accessories are stowed directly on the back of the machine while the hose and power cable are securely fixed.

T 8/1 L

- Ergonomic carrying strapFilter class certification L
- Weighs only 3.5 kg extremely light.

Technical data		
Energy efficiency class (out of A+++ to D)		A
Air flow rate	I/s	40
Vacuum	mbar / kPa	235 / 23.5
Container capacity	1	8
Rated input power	w	850
Voltage	V	220-240
Standard nominal width		ID 35
Cable length	m	7.5
Sound level (mains operation) EN 60335-2-69:2010 Uncertainty K = 1 dB(A)	dB(A)	62
Sound power level	dB(A)	76
Weight	kg	3.5
Dimensions (L × W × H)	mm	382 × 285 × 324

Equipment		
Suction hose	m	2.5 / with bend
Suction tube, metal 2 × 0.5 m		1
Filter bag		fleece
Permanent filter basket, fleece		1
Permanent filter basket, nylon		-
Switchable floor nozzle		-
Order no.		1.527-188.0
Price		

■ Included in the scope of supply.

CLASSIC DRY VACUUM CLEANERS



Simply practical: the T Classic range

With our Classic dry vacuum cleaners, we demonstrate how well high professional standards can now be met with entry-level machines. These ergonomically designed, robust machines are compact, versatile and powerful, yet extremely quiet - with a large container capacity for non-stop use. In short: they provide everything you need for maintenance cleaning.









1 Low weight

■ Compared to competitor models up to 50 percent lower weight with identical container volume.

3 Maximum suction power with simultaneously minimal energy use

- Optimised airflow ensures excellent suction power, thus making oversized turbines superfluous.
- Compared to competitor models almost 25 percent lower power consumption.
- Higher suction power at the floor nozzle compared to competitor models with 25 percent lower power consumption.

2 Main filter basket for optimal dust separation

■ The permanent main filter ensures optimum dust separation, allowing operation without a filter bag.

4 Convenient foot switch

No need to bend down: on/off foot switch for speed and ease of use.

TECHNICAL DATA AND EQUIPMENT

		T 14/1 Classic	T 8/1 Classic
		Foot switchAccessories holderCable hook	Foot switchAccessories holderCable hook
Technical data			
Energy efficiency class (out of A+++ to D)		-	-
Air flow rate	I/s	47	47
Vacuum	mbar / kPa	285 / 28.5	285 / 28.5
Container capacity	I	14	8
Max. rated input power	W	1600	1600
Voltage	V	220-240	220-240
Standard nominal width		ID 35	ID 35
Cable length	m	7.5	7.5
Sound level (mains operation) EN 60335-2-69:2010 Uncertainty K = 1 dB(A)	dB(A)	69	69
Sound power level	dB(A)	-	-
Weight	kg	5.3	5
Dimensions (L × W × H)	mm	355 × 310 × 466	355 × 310 × 350
Equipment			
Suction hose	m	1.7	1.7
Suction tube, metal 2 × 0.5 m		•	•
Suction tube, plastic 3 × 0.35 m		-	-
Filter bag		Paper	Paper
Dry floor nozzle	mm	360	360
Crevice nozzle		•	
Round brush			•
Upholstery nozzle		•	•
Order no.		1.527-170.0	1.527-160.0
Price			

T 7/1 Classic

Extremely lightweight (< 3.5 kg)Strong suction power

Technical data				
Energy efficiency class (out of A+++ to D)		C	." ENED	- Y) (JA
Air flow rate	I/s	40	ENERC eneprus · evepye	
Vacuum	mbar / kPa	235 / 23.5	KARCHER	
Container capacity	I	7.5	T 7/1 Cla	assic
Max. rated input power	W	max. 850	A***	
Voltage	V	220-240	A++	
Standard nominal width		ID 35	A+ A	
Cable length	m	7.5	В	
Sound level (mains operation) EN 60335-2-69:2010 Uncertainty K = 1 dB(A)	dB(A)	62	C D	C
Sound power level	dB(A)	75	ENERGIA - EHEPTIAR - ENEPTEIA	27 E
Weight	kg	3.5	ENERGIJA - ENERGY - ENERGIE - ENERGI	37,5 Wh/annum
Dimensions (L × W × H)	mm	375 × 285 × 322	_ ABC D EFG_	√))) 75 dB
Equipment				
Suction hose	m	2 / with bend		
Suction tube, metal 2 × 0.5 m		-	ABCD E FG	AB C DEFG
Suction tube, plastic 3 × 0.35 m			* H*	1,545610
Filter bag		fleece	665/2013 - II	
Dry floor nozzle	mm	270		
Crevice nozzle		-		
Round brush		-		
Uphoistery nozzle		-		
Order no.		1.527-181.0		
Price				
■ Included in the scope of supply.				

■ Included in the scope of supply.

BATTERY-OPERATED DRY VACUUM




Battery-operated dry vacuum cleaner T 9/1 Bp: cordless power without compromise

With the new, extremely powerful battery-operated dry vacuum cleaner T 9/1 Bp, you will definitely not have to compromise on power and the quality of the cleaning results compared with mains-operated dry vacuum cleaners, and will benefit from the cordless flexibility of this machine. The powerful battery has a running time of 24 minutes in standard operation and 46 minutes in ecolefficiency mode.







■ Included in the scope of supply

1 eco!efficiency mode

The eco!efficiency mode reduces the machine's energy requirements and noise level, and also extends its battery life.

2 Ergonomic bend

■ The ergonomic bend sits comfortably in the hand and allows fatigue-free working over long periods of time.

T 9/1 Bp

- Lithium-ion battery (36 V) with battery charge display

		■ Quick charger
		■ Energy-saving ecolefficiency mode
Technical data		
Energy efficiency class (out of A+++ to D)		-
Air flow rate	I/s	46
Vacuum	mbar / kPa	207 / 20.7
Container capacity	1	9
Rated input power for battery operation	W	650
Voltage	V	220-240
Standard nominal width		ID 35
Sound level EN 60335-2-69: 2010 uncer- tainty K = 1 dB(A)	dB(A)	62
Weight	kg	7.5
Dimensions (L × W × H)	mm	380 × 325 × 420
Equipment		
Suction hose	m	2.5 / with bend
Telescopic suction tube		standard
Filter bag		fleece
Washable nylon filter (main filter)		1
Switchable floor nozzle	mm	290
Order no.		1.528-111.0
Price		

BACKPACK VACUUM.



Backpack vacuum BV 5/1 Bp: the perfect solution for small spaces

In confined spaces, such as cinemas, buses, trains, aircraft or on stairs, the BV 5/1 Bp is practically unbeatable. Battery-operated, extremely powerful and featuring an ergonomic and patented carrying frame for maximum comfort, it is also very easy to use as all functions are controlled directly via the control panel on the waist harness.





1 Patented, ergonomic carrying frame

Carrying frame with Air Stream Comfort system prevents irritating vibrations and

2 Simple operation of all functions

Control panel on the waist harness allows convenient control and monitoring of all functions.

BV 5/1 Bp BV 5/1

- Lithium-ion battery (36 V) with battery charge display Battery charge display on control panel
 - Clip system Air Stream Comfort carrying frame
- Energy-saving ecolefficiency mode
- Parking position for floor nozzle

		0, 0		
Technical data				
Energy efficiency class (out of A+++	to D)	-	В	ENERG MA
Air flow rate	I/s	46	53	ENERG Y UA ENERG Y UA ENERG Y UA ENERGY UA ENERGY UA ENERGY UA
Vacuum (battery mode)	mbar / kPa	207 / 20.7	-	KARCHER
Vacuum	mbar / kPa	-	240 / 24	BV 5/1
Container capacity	1	5	5	A+++
Nominal power	W	650	max. 800	A++ A+
Voltage	V	220-240	220-240	A
Standard nominal width		ID 35	ID 35	В
Cable length	m	-	15	С
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	57	62	D
Sound power level	dB(A)	-	76	ENERGIA - EHEPTUR - ENERGIE - ENERGI ENERGIA - ENERGY - ENERGIE - ENERGI kWh/annum
Weight	kg	8.7	5.3	KWIYaiiidiii
Dimensions (L × W × H)	mm	400 × 320 × 636	400 × 320 × 540	(AB C DEFG
Equipment				
Suction hose	m	1.5 / with bend	1.5 / with bend	ABC D EFG AB C DEFG
Telescopic suction tube		standard	standard	
Filter bag		fleece	fleece	665/2013 - II
Washable nylon filter (main filter)		•		
Switchable floor nozzle	mm	290	290	
Order no.		1.394-219.0	1.394-200.0	
Drico				

■ Included in the scope of supply.

BATTERY-POWERED HANDHELD VACUUM CLEANER

FORR CHER Indicated

Compact, strong, cordless!

Always close to hand, impressively strong suction power and convincing endurance: the battery-powered HV 1/1 Bp handheld vacuum cleaner for tradesmen and service providers in the building or vehicle cleaning industry. It has various attachments and is therefore suitable for a multitude of specific cleaning tasks – from furniture cleaning to removing drilling dust during installation work.











- 1 With large filter area and efficient turbine
- Strong cleaning performance on all surfaces.

- 3 With our efficient eco!efficiency mode
- Saves energy and extends battery life.
- Reduces operating noise.

- 2 Compact, lightweight and flexible to use
- Permits working in all directions (360° application).
- 4 Lithium-ion battery technology with battery charge display
- See the battery charging state at a glance.

TECHNICAL DATA AND EQUIPMENT

		HV 1/1 Bp Fs	HV 1/1 Bp Cs	HV 1/1 Bp As
		 Application-specific accessories for building cleaning service providers Energy-saving ecolefficiency mode Time-saving quick charger 	 Application-specific accessories for tradesmen Energy-saving ecolefficiency mode Time-saving quick charger 	 Application-specific accessories for vehicle interior cleaning service providers Energy-saving ecolefficiency mode Time-saving quick charger
Technical data				
Air flow rate	I/s	33	33	33
Vacuum	mbar / kPa	47 / 4.7	47 / 4.7	47 / 4.7
Container capacity	1	0.9	0.9	0.9
Nominal power	W	115	115	115
Voltage	V	18	18	18
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	69	69	69
Weight	kg	1.8	1.8	1.8
Dimensions (L × W × H)	mm	305 × 115 × 291	305 × 115 × 291	305 × 115 × 291
Equipment				
Battery		•	•	•
Suction brush		•	•	-
Crevice nozzle		•	•	•
Suction pipe, plastic 2 × 0.5 m		•	-	-
Floor nozzle		•	-	-
		_		

1.394-221.0

1.394-222.0

1.394-223.0

■ Included in the scope of supply.

Car interior suction nozzle Flexible suction hose Carrying strap

BATTERY-POWERED ELECTRIC BROOM



As quiet as it is thorough: the electric broom

When cleaning has to be fast and thorough, our whisper-quiet electric brooms are there to help. Equipped with lithium-ion technology, they offer a battery performance of 82 minutes for carpets and up to 104 minutes for hard surfaces. Replacement battery and BC 1/1.8 quick charger included for uninterrupted







1 Quick charger

Short charging time, long run time: the BC 1/1.8 quick charger fully charges batteries in only 65 minutes.

3 Brush replacement without tools

■ The roller brush can be removed without tools for easier cleaning.

2 Easy battery replacement

■ The powerful lithium-ion battery is easy to remove and change in a few simple steps.

TECHNICAL DATA AND EQUIPMENT

		EB 30/1 Adv Li-Ion	EB 30/1 Li-lon
		Lithium-ion technologyHigh-performance batteriesQuick charger	Lithium-ion technologyParking positionRemovable roller brush
Technical data			
Working width	mm	300	300
Container capacity	I	1	1
Voltage	V	220-240	220-240
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	56	56
Operating time (textile/hard surface)	min / min	82 / 104	41 / 52
Battery charging time	h	1	5
Weight	kg	2.8	2.8
Dimensions (L × W × H)	mm	250 × 300 × 1340	250 × 300 × 1340
Equipment			
Battery 7.2 V/2.6 Ah			•
Replacement battery 7.2 V / 2.6 Ah			-
Plug, power supply, BC 1/0.45 charger		-	T
Quick charger BC 1/1.8			-
Roller brush, standard			T
Order no.		1.545-127.0	1.545-126.0
Price			

■ Included in the scope of supply.

UPRIGHT BRUSH-TYPE VACUUM CLEANER - 60 CM WORKING WIDTH

Flexible all-round talent

Compact, innovative upright brush-type vacuum cleaner with a small turning circle. Ideal for carpets and hard surfaces. With contra-rotating roller brushes, side brushes, suction tube and HEPA filter (optional accessories). Convenient on-board battery









1 Contra-rotating roller brush system

- For hard and textile floor coverings without brush replacement. The Easy replacement of battery and filter bag. rollers adjust automatically to any floor covering.
- 3 The machine can be fully opened

 - Very easy to service.

2 Suction tube with extra long hose

- The suction tube allows easy step and corner cleaning, even in hard-to
 Extremely manoeuvrable. reach places. The hose can also be lengthened as required.
- 4 Slim design
- - Fits in any lift ideal for cleaning in multi-storey buildings.

TECHNICAL DATA AND EQUIPMENT

		CV 60/2 RS Bp	CV 60/2 RS
		 For hard floors and textile floor coverings Stretchable suction hose with removable suction tube Including battery and built-in charger 	 For hard floors and textile floor coverings Stretchable suction hose with removable suction tube Built-in charger included in delivery
Technical data			
Working width	mm	610	610
Air flow rate	I/s	34	34
Vacuum	mbar / kPa	117 / 11.7	117 / 11.7
Container capacity	I	17	17
Max. rated input power	W	1224	1224
Voltage	V	36	220-240
Standard nominal width		ID 32	ID 32
Cable length		-	-
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	68	68
Brush motor power	W	373	373
Weight	kg	203	123
Dimensions (L × W × H)	mm	1120 × 622 × 1316	1120 × 622 × 1316
Equipment			
Crevice nozzle and upholstery nozzle		■/■	■/■
Suction tube, detachable		•	
Corrugated suction hose, removable		•	•
Filter bag		Paper	Paper
Filter status indicator		•	
Roller brush	piece(s)	2	2
Order no.		1.011-028.0	1.011-027.0
Price			

■ Included in the scope of supply.

M CLEANERS

UPRIGHT BRUSH-TYPE VACUUM CLEANER - 66 CM WORKING WIDTH

Large areas cleaned efficiently

The CV 66/2 with contra-rotating roller brush system is ideal for efficient and thorough cleaning of large carpeted areas. Ideal for hotels, airports and municipal use.







1 Easy filter replacement.

■ The filter system is easily accessible for quick and easy replacement.

- 3 Always ready to use.
- The hook is rotatable for easy removal of the power cable.

2 Contra-rotating roller brush system

■ The innovative contra-rotating roller brush system cleans deep into the fibres and raises the pile.

TECHNICAL DATA AND EQUIPMENT

CV 66/2

1.012-585.0

piece(s)

■ Contra-rotating roller brush system

Height-adjustable handle

		2 fixed and 1 adjustable power cable hooks
Technical data		
Working width	mm	660
Air flow rate	I/s	2 × 52
Vacuum	mbar / kPa	143 / 14.3
Container capacity	I	35
Max. rated input power	W	1650
Voltage	V	220-240
Cable length	m	20
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	73
Brush motor power	W	400
Weight	kg	72
Dimensions (L × W × H)	mm	1120 × 790 × 1330
Equipment		
Crevice nozzle and upholstery nozzle		-/-
Suction tube, detachable		-
Stretchable suction hose		-
Filter bag		Paper

■ Included in the scope of supply.

Roller brush, quantity

405

UPRIGHT BRUSH-TYPE VACUUM CLEANER -48-38 CM WORKING WIDTH



Fast, thorough, comfortable, service-friendly

Large carpet areas in retail, offices and the hotel and gastronomy sector require particularly thorough and fast care and maintenance. Our twin-motor upright brush-type vacuum cleaners with generous working widths are the ideal choice here. With brush overload protection, comfortable handling and thanks to the quick-change system for power cable and roller brush also very service-friendly.











1 Indicator light

404

■ The indicator light shows when the roller brush needs to be adjusted to ■ The stretchable suction hose can be removed easily, meaning that achieve optimum cleaning results.

3 Flexible cleaning option

blockages can be removed quickly and effortlessly.

2 Quick-change system for power cable


■ Time- and cost-saving replacement of power cable without any prior knowledge.

4 Brush replacement without tools

Rapid change of roller brush without the need for any tools.

TECHNICAL DATA AND EQUIPMENT

CV 48/2 Adv CV 48/2 Visual brush adjustment aid Visual brush adjustment aid ■ Flexible cable ■ Electronic brush overload protection



■ Included in the scope of supply.

Price

CV 38/2 Adv CV 38/2

■ Flexible cable ■ 2 motors

Visual brush adjustment aid ■ Electronic brush overload protection

■ 2 motors

		2 11101013		2 11101013	
Technical data					
Energy efficiency class (out of A+++ to D)		А	ENERG VUA eneptrua - Evepyzia (E) (A)	А	ENE eneprus - EN
Working width	mm	380	KÄRCHER	380	KÄRCHER
Air flow rate	I/s	40	CV 38/2	40	CV 3
Vacuum	mbar / kPa	200 / 20	A***	200 / 20	A***
Container capacity	1	5.5	A++	5.5	A++
Rated input power	W	850	A+	850	A ⁺
Voltage	V	220-240	A	220-240	A B
Standard nominal width		ID 35	C	ID 35	С
Cable length	m	12	D	12	D
Sound pressure level EN 60335-2-69 uncertainty K = 1 dB(A)	dB(A)	65	EMERGIA - EMEPTINA - EMEPTEIA EMERGY - EMERGI - EMERGI - KWh/annum	65	ENERGIA - EHEPTUR - ENEPTEIA ENERGIIA - ENERGY - ENERGIE - ENERGI
Sound power level	dB(A)	79	KWIIyaIIIIIIII	79	
Brush motor power	W	150	ABCDE F G / (4)) 79 dB	150	ABCDE F G
Weight	kg	9.5		9.5	
Dimensions (L × W × H)	mm	1215 × 390 × 350	AB C DEFG	1215 × 390 × 350	- AB C DEFG
Equipment			- ABCDEFG **		ABCDEFG *
Crevice nozzle and upholstery nozzle		■ / ■	665/2013 - II	■/■	665/2013 - II
Suction tube, detachable					
Stretchable suction hose, removable		•			
Filter bag		fleece		fleece	
Filter status indicator		•			
Roller brush	piece(s)	1		1	
Order no.		1.033-336.0		1.033-335.0	
Price					

■ Included in the scope of supply

MCIEANEDS

UPRIGHT BRUSH-TYPE VACUUM CLEANER - 38-30 CM WORKING WIDTH



Brush and vacuum: thorough carpet cleaning

On the one hand upright brush-type vacuum cleaners are classic vacuum cleaners. On the other hand they have an electrically driven brush that does two jobs: it removes stubborn dirt such as hair from the fibres. And also straightens the fibres again so that the carpet is freshly brushed. Thanks to the quick-change system for power cable and roller brush, our machines are also very service-friendly.











1 Manual roller brush adjustment

Thanks to the height adjustment, the roller brush can be adjusted to any carpet pile height.

3 Quick-change system for power cable

Time- and cost-saving replacement of power cable without any prior knowledge.

2 Brush replacement without tools

Rapid change of roller brush without the need for any tools.

4 Patented centrifugal coupling

For longer service life: the innovative patented centrifugal coupling protects the whole brush head from being overloaded, thereby avoiding high service costs.


TECHNICAL DATA AND EQUIPMENT

CV 30/1

Height-adjustable handle

■ Manual roller brush adjustment

■ Rubber bumper



■ Included in the scope of supply.

SMALL EXTRAS, BIG EFFECT

Our extensive range of dry vacuum cleaner accessories makes your day-to-day work even easier and more efficient. Thanks to integrated storage – on or in the machine itself – accessories are always within easy reach and can be stored quickly and safely ready for the next time. Dry vacuum cleaners form a perfectly coordinated system with suction nozzles, hoses and suction tubes for typical applications. The visible result? Exemplary cleaning processes and uncompromising cleanliness.



Table of contents: Dry vacuum cleaner and carpet cleaner accessories

Filters	Page	410
Suction nozzles, suction tubes and bends	Page	412
Connecting adapters	Page	416
Suction hoses	Page	418
Other accessories	Page	420





1 Simultaneous vacuuming and brushing

With the ESB 28 and ESB 34 electrical suction brushes, carpets can be thoroughly vacuumed and brushed at the same time.

2 Healthy air

Kärcher HEPA filters ensure that the exhaust air is perfectly hygienic, for example in hotels, hospitals and nurseries.

3 Bagless filtration

Kärcher permanent filters allow you to vacuum without a filter bag.

4 Better filtration for more efficiency

Kärcher fleece filter bags are more economical: double the dust intake capacity of paper filter bags, a 10 per cent higher separation degree and a long service life reduces material costs considerably.

FILTERS



Large filter bag volume with compact construction style - a principle followed by Kärcher with every new development. The result: outstanding efficiency, low maintenance costs and long operating time.

























6	
Y	(Colon

	Order no.	Quantity	Price	Description		T 15/1 ecolefficiency T 12/1 ecolefficiency T 10/1 ecolefficiency T 10/1 ecolefficiency T 15/1 HEPA T 15/1 HEPA T 15/1 T 15/1 T 15/1 T 12/1 T
Paper filter bags (two-ply)		l.a · //	ı			
Paper filter bag		10 piece(s)		Paper filter bag for dust-free disposal.	1	
Paper filter bag	2 9.755-252.0	10 piece(s)		AT Phys Cillian accepts	2	
Paper filter bags	3 8.634-104.0	10 piece(s)		17-litre filling capacity.	3	
Dance filter have built and	4 6.904-333.0	10 piece(s)		Dust class M.	4	
Paper filter bags, bulk pack	5 6.904-337.0	300 piece(s)		Dust class M. Bulk value pack.	5	
Paper filter bags	6 6.904-312.0	10 piece(s)		Dust class M.	6	
Paper filter bags, bulk pack	7 6.904-318.0	200 piece(s)		Dust class M. Bulk value pack.	7	
Daniel Charles	8 6.907-016.0	200 piece(s)		C.L. (10 circus) of consecution (DIA C. L. et al. e	8	
Paper filter bags	9 6.907-019.0	10 piece(s)		Set (10 pieces) of paper filter bags (BIA C dust class M) for use in all commercial dry vacuum cleaners.	9	
	10 6.904-403.0	10 piece(s)		Dust class M.	10	
		10 piece(s)		Two-ply, for low-dust disposal.	11	
Paper filter bags	12 6.904-370.0	10 piece(s)		Affordable paper filter bag for dust-free disposal.	12	
Fabric filter bag	12 0.304 370.0	10 piece(s)	L	Autoradate paper inter aug for dost free disposal.	12	
Fabric filter bag	13 6.904-425.0	1 niece(s)	1	Cotton, washable (40°C).	13	
Tablic fitter bas	14 6.904-316.0			Cotton, washable (40°C), reusable.	14	
Fleece filter bags (three-ply)	11 0.30 1 310.0	1 piece(s)		Cotton, manage (10 c), reduce.		
Fleece filter bags	15 6.904-084.0	10 piece(s)		Fleece filter bags (10 pieces). Tear-resistant, 3-ply fabric approved for dust class M.	15	
	16 6.904-335.0	10 piece(s)		Fleece filter bag, tear-resistant, dust class M.	16	
Fleece filter bags, bulk value pack	17 6.904-336.0	300 piece(s)		Fleece filter bag, tear-resistant, dust class M. Bulk value pack.	17	
Fleece filter bags	18 6.904-315.0	10 piece(s)		Fleece filter bag, tear-resistant, dust class M.	18	
Fleece filter bags, bulk value pack	19 6.904-321.0	200 piece(s)		Fleece filter bag, tear-resistant, dust class M. Bulk value pack.	19	
Fleece filter bags	20 6.907-017.0	10 piece(s)		Fleece filter bag, tear-resistant, dust class M.	20	
Fleece filter bags, bulk value pack	21 6.907-018.0	200 piece(s)		Fleece filter bag, tear-resistant, dust class M. Bulk value pack.	21	
HEPA, dust class H filter						
Filter packaged HEPA	22 6.414-080.0	1 piece(s)		Optional HEPA filter box (paper/plastic) for use instead of the standard blower air filter box. Increases the filter capacity and improves the blower air.	22	
HEPA filter cartridge	23 8.634-529.0	1 piece(s)		HEPA filter cartridge with carbon content for dust-free and odour-reduced exhaust air recirculation.	23	
HEPA flat pleated filter	24 6.414-801.0	1 piece(s)		HEPA filter cartridge, paper/plastic (HEPA 12).	24	
Main filter baskets						
Permanent main filter basket	25 2.889-099.0	1 piece(s)		Extra strong fleece material.	25	
filter basket	26 5.731-658.0	1 piece(s)		Nylon, washable up to 40 °C	26	
Permanent main filter basket	27 5.731-649.0	1 piece(s)		Reinforced polyester needle fleece, washable up to 40°C.	27	
	28 5.731-624.0	1 piece(s)		Nylon, washable up to 40 °C.	28	
	29 4.731-011.0	1 piece(s)		Reinforced polyester needle fleece, washable up to 40°C.	29	
	30 5.731-640.0	1 piece(s)		Nylon, washable up to approx. 40°C.	30	
	31 5.731-632.0				31	
	32 5.731-628.0	1 piece(s)			32	
Exhaust air filter						
Filter foam	33 6.414-765.0	3 piece(s)		Standard exhaust filter.	33	
Motor protection filter set	34 2.889-119.0	3 piece(s)		Motor protection filter, removable fleece, which can be replaced when heavily soiled.	34	
Standard exhaust filter	35 6.414-802.0	3 piece(s)		Standard exhaust filter.	35	
Motor protection filter	36 6.414-611.0	5 piece(s)		Change the motor filter and interchangeable fleece when heavily soiled.	36	

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

SUCTION NOZZLES, SUCTION TUBES AND BENDS



The right nozzle can considerably improve cleaning performance. Carpets regain their quality appearance and hard surfaces are left completely dust-free.

























	_
	21

	Order no.	Quantity	ID	Length	Width	Price Description		T 15/1 ecolefficiency T 12/1 ecolefficiency T 10/1 ecolefficiency T 7/1 ecolefficiency T 7/1 ecolefficiency T 15/1 HEPA T 15/1 HEPA T 15/1 HEPA T 12/1 HF T 12/1 HF T 12/1 HF T 14/1 Classic T 14/1 Classic T 14/1 Classic T 14/1 Classic T 17/1 Classic T 18/1 BP BV 5/1 BP BV 5/1 BP BV 5/1 BP C 17/1 BP SS HV 1/1 BP SS HV 1/1 BP SS CV 60/2 RS BP CV 60/2 RS CV 60/2 RS
Turbo nozzles	1 2 060 112 0	1 pinco(s)	l ID 22	1	160 mm	Habaleton, pazzla plastic with reduction buching ID 35/33	1 1	
Turbo upholstery nozzle	1 2.860-113.0	1 piece(s)			160 mm	Upholstery nozzle, plastic, with reduction bushing ID 35/32.	1	
Turbo floor nozzle	2 2.860-114.0	1 piece(s)	ID 32		270 mm	Floor nozzle, plastic, with reduction bushing ID 35/32, 270mm.	2	
Upholstery nozzles								
Upholstery nozzle NW 35	3 6.905-998.0					Plastic upholstery nozzle.	3	
Upholstery nozzle	4 9.770-605.0	1 piece(s)	ID 35		120 mm	Plastic upholstery nozzle.	4	
Floor nozzles				<u> </u>	•			
Floor nozzle	5 9.770-606.0	1 piece(s)	35		260 mm	Plastic, switchable, 260 mm.	5	
Floor nozzle	6 2.889-220.0	1 piece(s)	ID 35	220 mm		Floor nozzle, NW 35, width: 220 mm.	6	
Combi-nozzles, dry								
Combi-nozzle	7 2.889-179.0	1 piece(s)	ID 35		295 mm	Plastic floor nozzle, NW 35 switchable.	7	
Parquet nozzle	8 2.889-196.0	1 piece(s)	ID 35		360 mm	Parquet nozzle with wide working width.	8	
	9 2.889-197.0	1 piece(s)	ID 35		300 mm		9	
Parquet nozzle	10 6.905-078.0	1 piece(s)	ID 32		360 mm	Parquet nozzle NW 32 with generous 360 mm working width.	10	
Combi-nozzle	11 2.889-129.0	1 piece(s)	ID 35		295 mm	Plastic floor nozzle, ID 35 and switchable.	11	
	12 2.840-038.0	1 piece(s)	ID 35		300 mm	Switchable plastic floor nozzle (combi-nozzle) with internal connecting taper ID 35.	12	
Combi-nozzle	13 6.907-496.0	1 piece(s)	ID 35		270 mm	Made of plastic, switchable and equipped with ID 35 connection.	13	
Combi-nozzle	14 6.907-410.0	1 piece(s)	ID 32		270 mm	Plastic, ID 32, switchable.	14	
Radiator brushes				•	,			
Radiator brush	15 6.903-034.0	1 piece(s)	ID 35			Plastic, for crevice nozzle (6.900-385.0).	15	
Crevice nozzles								
Crevice nozzle	16 2.889-130.0	1 piece(s)	ID 35	210 mm		Plastic crevice nozzle.	16	
Crevice nozzle	17 2.840-039.0	1 piece(s)	ID 35	195 mm		Plastic crevice nozzle for industrial dry vacuum cleaners.	17	
Crevice nozzle	18 9.770-638.0	1 piece(s)	+	350 mm		Plastic.	18	
	19 9.770-607.0	1 piece(s)		213 mm		Plastic crevice nozzle.	19	
Car nozzle	20 6.906-385.0	1 piece(s)			90 mm	Plastic.	20	
Crevice nozzle	21 6.903-403.0	1 piece(s)	ID 32	210 mm			21	
ESB 28 electric suction brush	22 2.641-815.0	1 piece(s)	ID 32		280 mm	ESB 28 with suction hose, electric cord and telescopic vacuum tube, only for T 201, T 12/1 (230 V).	22	
Brush head ESB 34	23 2.642-442.0	1 piece(s)	ID 32		340 mm	ESB 34, suction hose with electric cord and telescopic	23	
Suction brushes						vacuum tube (230 V).		
Suction brushes Suction brush	24 9.770-656.0	1 piece(s)	I ID 35			Natural bristles, cow hair.	24	
Socion brosii	25 2.889-221.0		_			Suction brush NW 35 with horsehair natural bristles.	25	
Suction brush	26 6.903-862.0		_		70 mm	Natural bristles (ox hair), rotatable.	26	
222.0.1 5. 65.1	27 6.903-887.0				70 mm	Plastic brush, rotatable.	27	
Suction tubes, stainless steel	2. 0.303 007.0	1 p.ccc(3)	1.5 52		7.0.11111	1		
Suction tube set	28 2.840-041.0	2 piece(s)	ID 35	0.5 m		Stainless steel suction tube set (2 × 50 cm) as a replacement	28	
			<u></u>			or extension, e.g. for vacuuming ceilings.		
Suction tubes, plastic		,						
Suction tube	29 5.481-010.0			0.35 m		Three included in standard accessories (T 7/1 Classic).	29	
	30 9.770-584.0			0.5 m		Plastic, black, 0.5 m.	30	
Suction tube set	31 2.889-218.0			505 mm		Plastic suction tube set, NW 35, grey, 2-piece, each 0.5 m.	31	
Suction tube	32 8.600-009.0	1 piece(s)	ID 32	0.5 m		Plastic, black, 0.5 m.	32	

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.













		Order no.	Quantity	ID	Length	Width	Price	Description		T 15/1 ecolefficiency T 12/1 ecolefficiency T 12/1 ecolefficiency T 10/1 ecolefficiency T 7/1 ecolefficiency T 15/1 HEPA T 15/1 T 15/1 T 12/1 T 12/1 T 12/1 T 12/1 T 12/1 T 12/1 HY 1/1 Bp B By 5/1 By
Suction tubes, metal										
Telescopic suction tube	33	2.862-008.0	1 piece(s)	ID 35	0.61 m			Telescopic suction tube, metal, chrome-plated, ID 35. Length from 0.61 to 1.0 m.	33	
Suction tube, chrome-plated	34	6.902-074.0	1 piece(s)	ID 35	505 mm			Suction tube, metal, chrome-plated, NW 35, length: 0.5 m.	34	
Suction tube set	35	2.643-464.0	2 piece(s)	ID 35	0.5 m			Metal suction tubes, 50 cm long.	35	
Suction pipe, metal, ID 35	36	9.770-654.0	1 piece(s)	ID 35	0.5 m			Metal, chrome-plated.	36	
Suction tube	37	6.906-618.0	1 piece(s)	ID 32	0.5 m			Metal, black coated, ID 32, 0.5 m.	37	
ACCESSORY TOOL, NUWAV, KIT	38	8.630-501.0	1 piece(s)	ID 32				Optional accessories for CV 66/2 upright vacuum cleaner for large areas.	38	
Bend, plastic										
Bend	39	2.889-148.0	1 piece(s)	ID 35				Ergonomic bend for the new clip system. With airflow control slide, in an antistatic design.	39	
Bend, plastic, C-35 clip system	40	2.840-040.0	1 piece(s)	ID 35				Plastic bend with practical C-35 clip system.	40	
Bend, plastic	41	4.408-051.0	1 piece(s)	ID 32				Plastic with C 32 clip system.	41	

■ NEW ■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.

UUM CLEANERS

ADAPTERS



With Kärcher's connecting adapters, two suction hoses can be quickly and reliably joined together to increase the working radius.









	Order no.	Quantity	ID	Price	Description		T 15/1 ecolefficiency T 12/1 ecolefficiency T 10/1 ecolefficiency T 7/1 ecolefficiency T 15/1 HEPA T 15/1 T 15/1 T 10/1 T 10/1 B PS 5/1
Reduction/expansion bushings Set of reduction/expansion bushings	1 2.860-117.0	1 niece(s)		1	ID 40/35, ID 35/32 (tube -> nozzle), plastic.	1	
Reducers (tube -> nozzle)	1 2.000 117.0	I piece(s)			10 10/30, 10 30/32 (1000 Hozzio), piosite.		
Reducer from ID 35 to ID 32	2 6.902-072.0	1 piece(s)	ID 35		From ID 35 to ID 32, metal.	2	
Expansion pieces (tube -> nozzle)							
Adapter	3 6.902-083.0	1 piece(s)	ID 32		From ID 32 to ID 35, plastic.	3	
Connecting adapters							
Adapter, ID 32/35, with internal thread	4 6.902-077.0	1 piece(s)	ID 32		For connecting two suction hoses (not ESB 28 and 34).	4	

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

JUM CLEANERS

SUCTION HOSES



Our robust, flexible suction hoses follow your every move. Electrically conductive suction hoses reliably protect against electrostatic discharge between the operator and the machine.










	Order no.	Quantity	ID	Length	Price	Description			T 15/1 ecolefficiency T 12/1 ecolefficiency T 10/1 ecolefficiency T 7/1 ecolefficiency T 7/1 ecolefficiency T 15/1 HEPA T 15/1 T 12/1 T 12/1 T 12/1 T 10/1 HY 1/1 Classic T 19/1 Bp BV 5/1 Bp BV 5/1 BP BV 5/1 BP HY 1/1 Bp Cs
Complete suction hoses (clip system)			,	'	,				
Suction hose	1 2.889-13	8.0 1 piece(s)	ID 35	2.5 m		2.5 m long suction hose with new clip fastener, C 35.	1		
	2 2.889-16	0 1 piece(s)	ID 35	2 m		2 m suction hose with new clip fastener, C 35.	2		
Suction hose, complete, replacement	3 2.889-100	0.0 1 piece(s)	ID 35	2 m		2 m, with dry vacuum cleaner connection C 35.	3		
Suction hose	4 2.889-13	2.0 1 piece(s)	ID 35	1.5 m		1.5 m long suction hose with new clip fastener, C 35.	4		
Complete suction hoses									
Stretchable suction hose	5 2.889-22	2.0 ■ 1 piece(s)	ID 35	0.55 m		Flexible suction hose (NW 35) for battery-powered upright vacuum cleaner HV 1/1 Bp. Length: 0.55 m.	5		
Suction hoses (clip system)						·			
Suction hose	6 2.889-163	8.0 ■ 1 piece(s)	ID 35	2.5 m		Electroconductive suction hose, NW 35. Length: 2.5 m.	6		
Suction hose	7 4.440-91	0 1 piece(s)	ID 32	2.5 m		With dry vacuum cleaner and clip connection, C 32.	7		

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

OTHER ACCESSORIES



Our carrying strap leaves your hands free and is comfortable to wear. It reliably secures the machine during transportation or when you are working on a ladder.















				10	13
	Quantity	Price	Description		
nn I	1 niece(s)		Soft black standard bristles 2 brushes required	1	

								8/1	5 2	귀.	1	CV 60 30 CV 60 CV
	Order no.	Quantity	Price	Description			Į i	FF	6	f	되	
Upright brush-type vacuum cleaner accessor	ry											
Roller brush	1 8.634-050.0	1 piece(s)		Soft, black standard bristles. 2 brushes required.	1	1						
Side brush	2 8.634-216.0	1 piece(s)		Side brush, black.	2	2						
Roller brush	3 8.621-611.0	1 piece(s)		Black, normal (top).	3	3						
	4 8.621-612.0	1 piece(s)		Black, normal (bottom).	4	4						
Roller brushes for electric broom EB 30/1												
Roller brush	5 4.762-400.0	1 piece(s)		Black standard bristles, material PA.	5	5						
	6 4.762-401.0	1 piece(s)		Mixed bristles (natural and synthetic bristles, red), particularly suitable for hard surfaces and parquet flooring.	6	6						
Rechargeable batteries + chargers												
Quick charger	7 6.654-354.0	1 piece(s)		The single-slot BC 1/7 quick charger is designed for high-performance lithium-ion batteries, type BP 750.	7	7		•				
36 V Li-ion battery	8 4.654-016.0	1 piece(s)		High-performance lithium-ion battery BP 750 (36 V, 7.5 Ah).	8	8						
BC 1/2	9 6.654-361.0	1 piece(s)		Quick charger for batteries from the Kärcher 18 Volt platform.	9	9						
Battery pack BP 250/18	10 6.654-364.0	1 piece(s)		18 V Li-ion battery.	10	0						
Replacement battery with lithium-ion cells, 7.2 V/2.6 Ah	11 6.654-328.0	1 piece(s)		Li-ion, 7.2 V/2.6 Ah.	11	1						
Universal quick charger	12 6.654-190.0	1 piece(s)		BC 1/1,8, 1-channel quick charger.	12	2						
Replacement battery with lithium-ion cells, 7.2 V / 1.3 Ah	13 4.654-273.0	1 piece(s)		Li-lon, 7.2 V / 1.3 Ah.	13	3						
Other				·	· ·							
Drill dust nozzle	14 2.679-000.0	1 piece(s)		Drill dust nozzle for dust-free vacuuming of drill holes. Suitable for dry and wet and dry vacuum cleaners from Kärcher.	14	4						

Carrying strap 15 2.889-268.0 ■ 1 piece(s) Carrying strap, adjustable.

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

SO THAT NO DIRT REMAINS IN THE CARPET.

Carpets in offices, hotels and schools are subject to heavy traffic every day. This is where our carpet cleaners have proven invaluable. They are robust, powerful, versatile and suitable for deep and intermediate cleaning of carpets and removing stains on textile surfaces. Our carpet cleaners are also ideal for deep cleaning upholstery and car seats. And, with the right accessories, they can even be used to clean tiles.




Table of contents: Carpet cleaners

Spray extraction machines	Page	426
Professional power brushes	Page	430
Air blowers	Page	431
Deep carpet cleaners	Page	432
Accessories	Page	436
Cleaning agents	Dago	250



WISITOR'S CHOICE AMSTERDAM INNOVATION AWARD 2016

Your fast and silent drying aid: AB 20 Ec


Our new AB 20 Ec air blower convinces with particularly low operating noise and high performance at the same time. You'll be amazed at how quickly you can walk on the carpet again after deep cleaning. And this also impress your customers.

The first of its kind: BRC 40/22 C

As the first deep carpet cleaner on the market, the BRC 40/22 C is capable of cleaning forwards, avoiding the need to walk back and forth during the cleaning process. This means you save at least 30 percent work time while at the same time significantly increasing productivity. This is made possible by the brush head with integrated suction, which rotates 200° in both directions. Your BRC 40/22 C: for fibre-deep and efficient carpet cleaning.

How to read the unit names:

Unit type	Water tank	Spray pressure	Type and equipment
Example: Puzzi	30	4	
Puzzi = product name	In unit names with a combination of figures, the first number indicates the capacity of the fresh water tank (in litres).	In unit names with a combination of figures, the second number indicates the spray pressure (in bar).	Adv = Advanced, machine with additional equipment E = Electrically heated C = Compact, machine with compact dimensions
Unit type	Working width	Tank volume	Type and equipment
Example: BRC	30	15	С
BRC = Floor cleaner with carpet roller	In unit names with a combination of figures, the first number indicates the working width in cm.	In unit names with a combination of figures, the second number indicates the tank volume.	C = Compact, machine without traction drive
Unit type	Working width	Rotation speed	Type and equipment
Example: BRS	43	500	С
BRS = Scrubber with roller	In unit names with a combination of figures, the first number indicates the working width in cm.	In unit names with a combination of figures, the second figure indicates the rotation speed (rpm).	C = Compact, machine without traction drive







1 Quick-drying

The powerful suction turbine of Kärcher Puzzi machines leaves carpets virtually touch-dry in minutes. Carpets dry up to 63% faster than with comparable products and can be walked on in a very short time.

11111111111111111

2 Spray extraction principle

With the spray extraction method, the water and cleaning agent are sprayed deep into the carpet while simultaneously vacuuming the dirty solution back again. Dirt is dissolved and removed in a single pass. Due to the low residual moisture, carpets are dry in next to no time.

3 Thoroughly clean

The brush mechanism of carpet cleaners with roller brush intensifies the cleaning power of the cleaning agent. This raises the carpet pile.

4 Twice as versatile

The BRC 45/45 C and BRC 40/22 C with pre-sweep function are multifunctional all-rounders. They feature fibre-deep carpet cleaning with spray extraction, mechanical brush support and contra-rotating roller brushes for quiet operation and constant brush contact. The cleaning agent CarpetPro Cleaner iCapsol RM 768 from Kärcher is recommended for the efficient cleaning of carpets as it greatly reduces the drying time.

5 Innovative accessories

The accessories for the Puzzi come with a large number of innovations. A flexible joint enables the best possible extraction at any angle. Cleaning under objects is easy – incorrect use is prevented. The modular system allows for quick changes between floor, upholstery and crevice nozzles.





Our BRC 40/22 C and the CarpetPro cleaner iCapsol RM 768 are an unbeatable team for intermediate carpet cleaning. They enable you to reach the dirt even deep into the carpet. The dirt is loosened from the fibres and encapsulated. The carpet is ready to walk on again in just 30 minutes. Then you simply vacuum up the encapsulated dirt in the next maintenance cleaning session.





7 Cleaning agents from Kärcher

The CarpetPro Cleaner iCapsol, powder RM 760 OA is a spray extraction deep cleaner with encapsulation technology and odour eliminator. It permanently eliminates unpleasant odours. No need for time-consuming rinsing. CarpetPro Conditioner RM 763 removes residual dirt and surfactant residues from carpet floor coverings and textile surfaces. Reduces the need for rinsing. Refreshes fibres and colours.

8 One for all: the handle with trigger

The indispensable handle with trigger fits into all carpet cleaners from Puzzi 8/1 to Puzzi 30/4. Since all accessories are compatible, the right accessories are available for every cleaning task and every machine.

SPRAY EXTRACTION MACHINES - 30 LITRES



The professional for large textile surfaces

Puzzi 30/4, the quietest wet vacuum cleaner of its kind (66 dB[A]). Very good handling, space-saving transport and storage thanks to its upright design. With flexible suction lip, 350 mm floor nozzle and 30% faster drying time compared with the competition thanks to a very high air flow.









1 Power outlet for PW 30/1

- The integrated power outlet enables flexible use of the PW 30/1 without an additional power source.
- When not in use, the power outlet is effectively protected by an automatically closing flap.
- The PW 30/1 increases the area performance, cleans the pile with a rotating brush and aligns it in one direction.

2 Removable waste water tank

- To protect against dirt, the waste water tank's handle is attached to the outside
- The waste water tank is easy to remove and can also be used to fill the fresh water tank.
- A short description on the rear of the waste water tank explains the work process simply and clearly.

3 Extremely quiet

- At just 66 dB(A), the Puzzi 30/4 is the quietest wet vacuum cleaner of
- Thanks to the low noise volume, the machine can be used everywhere, even during business hours and in hotels.
- The low noise emissions protect the operator and allow longer work intervals

4 Large tank volume

- Even with a full 30-litre fresh water tank, the Puzzi 30/4 can be easily transported lying on its back.
- An integrated level indicator display shows the current fresh water level
- The fresh water filter protects the components and can be removed without tools for cleaning.

TECHNICAL DATA AND EQUIPMENT

		Puzzi 30/4	Puzzi 30/4 E
		 Removable waste water tank Fresh water tank filling level display Horizontal transport possible with full fresh water tank 	 Heating rods integrated in fresh water tank Integrated overheating-protection Heating can be easily operated with EASY Operation
Technical data			
Max. area performance	m²/h	60-75	60-75
Air flow rate	I/s	74	74
Vacuum	mbar / kPa	254 / 25.4	254 / 25.4
Spray rate	I/min	3	3
Spray pressure	bar	4	4
Tank, fresh washer	I	30	30
Tank, dirty water	I	15	15
Turbine power	W	1200	1200
Pump power	W	70	70
Voltage	V	220-240	220-240
Weight	kg	26	28
Dimensions (L × W × H)	mm	580 × 460 × 930	580 × 460 × 930
Equipment			
Spray hose with integrated water feed	m	4	4
Narrow floor nozzle, complete with flexible suction lip		-	-
Handle with trigger			•
Power outlet for professional power brush		PW 30/1	PW 30/1
Order no.		1.101-120.0	1.101-122.0
Price			

■ Included in the scope of supply.

SPRAY EXTRACTION MACHINES - 10 LITRES



For well-maintained carpets

Puzzi 10/1 and Puzzi 10/2 Adv clean carpeted floor areas of 20 to 45 $\rm m^2$ par excellence. The modular accessories are stored directly on the machine. The carrying handle has storage for the suction tube.



1 Perfectly suitable for everyday use.

- Adjustment of the handle without any tools; accessory/cord fixings; quick change from floor to upholstery nozzle.
- Quickly adapts to different requirements.

2 Improved cleaning performance

- With integrated adapter for the PW 30/1 additional power brush.
- High cleaning performance.

		Puzzi 10/2 Adv	Puzzi 10/1
		 Defoamer dosing Storage compartment for cleaning agent tablets Power outlet for PW 30/1 	Removable waste water tankRubber mounted pump / turbineExtra handle on floor nozzle
Technical data			
Max. area performance	m²/h	30-45	20-25
Air flow rate	I/s	54	54
Vacuum	mbar / kPa	220 / 22	220 / 22
Spray rate	l/min	2	1
Spray pressure	bar	2	1
Tank, fresh washer	I	10	10
Tank, dirty water	1	9	9
Turbine power	W	1250	1250
Pump power	W	80	40
Voltage	V	220-240	220-240
Weight	kg	11.5	10.7
Dimensions (L × W × H)	mm	705 × 320 × 435	705 × 320 × 435
Equipment			
Spray hose with integrated water feed	m	2.5	2.5
Narrow floor nozzle, complete with flexible suction lip		1	1
Handle with trigger			•
Upholstery nozzle		-	•
Crevice nozzle		-	-
Power outlet for professional power brush		PW 30/1	-
Order no.		1.193-120.0	1.100-130.0
Price			
■ Included in the scope of supply			

\blacksquare Included in the scope of supply.

SPRAY EXTRACTION MACHINES - 8 LITRES



Compact and portable - perfect for valeting

The handy, compact and powerful Puzzi 8/1 C spray extraction cleaner is ideal for small areas and upholstery cleaning with excellent cleaning results.





1 Low weigh

- At 9.8 kg, the Puzzi 8/1 C is easy to carry and 35% lighter than the competition. Ideal for intermediate cleaning, thanks to rapid drying.
- Easily transported, even over obstacles and stairs.

2 Compact design

- The Puzzi 8/1 C also shows its strengths when cleaning upholstery and vehicle interiors.
- Compact, space-saving design.

Puzzi 8/1 C

Foldable cable hook
Large foot switch
Accessory storage for hand nozzle

Technical data		
Max. area performance	m²/h	12-18
Air flow rate	I/s	61
Vacuum	mbar / kPa	230 / 23
Spray rate	I/min	1
Spray pressure	bar	1
Tank, fresh washer	1	8
Tank, dirty water	1	7
Turbine power	w	1200
Pump power	W	40
Voltage	V	220-240
Weight	kg	9.8
Dimensions (L × W × H)	mm	530 × 330 × 440

Equipment		
Spray hose with integrated water feed	m	2.5
Handle with trigger		
Upholstery nozzle		
Order no.		1.100-225.0
Price		

■ Included in the scope of supply.


SMINA IS EASING

PROFESSIONAL POWER BRUSH



Increase performance, reduce effort

The professional power brush increases Puzzi area performance by up to 80% – reducing cleaning time and improving cleaning results.



1 Rotating brushes

A rotating brush intensifies the cleaning and raises the carpet pile.

2 Improved cleaning performance

■ The PW 30/1 professional power brush increases the cleaning performance by a further 25% compared to its predecessor.

PW 30/1 PW 30/1 ■ Motor-driven brush ■ Power brush for Puzzi 10/2 Adv ■ Power brush for Puzzi 30/4 and Puzzi 30/4 E Technical data Max. area performance 40-55 70-110 Brush motor power 60 220-240 220-240 Voltage 5.7 5.9 Weight Dimensions (L × W × H) 350 × 260 × 835 350 × 260 × 835 1.913-102.0 1.913-103.0

AIR BLOWER



Highly efficient drying accelerator

Damp textile surfaces generally require long drying phases. Our AB 20 Ec air blower shortens the drying phases up to 50 percent. The machine is compact and easy to transport thanks to the lightweight design and low operating noise and can also be used during business hours. The low-wear Ec motor guarantees a long life.



RAPORT .



- 1 Low-wear Ec motor
- Long-lasting, robust and thus very economical machine.
- Motor with 3-stage control.
- 2 Low-noise operation
- Trouble-free operation also during daytime cleaning.
- Barely noticeable noise when used during opening hours.

AB 20 Ec

- Housing made from robust and durable plastic
- Operation possible in 4 different positions

Technical data		
Voltage	V	220-240
Rated input power	W	120
Volumetric flow	m³/h	1200
Rotational speed	rpm	1450
Sound pressure level		-
Cable length	m	7.5
Weight	kg	7.1
Dimensions (L × W × H)	mm	375 × 353 × 371

Equipment	
On-board power cable storage	ı
Sturdy plastic casing	
Ergonomic carrying handle	ı
Order no.	1.004-062.0
Price	

■ Included in the scope of supply.

ONING IS THE

DEEP CARPET CLEANERS



Deep carpet cleaning: now at least 30% faster

In contrast to other deep carpet cleaners, the very manoeuvrable BRC 40/22 C can, thanks to a rotatable brush head which ensures propulsion, also clean forwards, meaning that additional inconvenient passes can be avoided. In this way, it results in time savings of at least 30% in comparison and improves productivity to a previously unknown level.











1 200° rotatable cleaning head

- A carpet roller brush supports thorough cleaning.
- Extremely easy to manoeuvre even on cluttered surfaces.

3 Optional hand nozzle

For cleaning corners or for spray extraction of chairs and cushions.

2 For deep and intermediate carpet cleaning

- For both deep cleaning and intermediate cleaning applications on carnets
- Deep cleaning of carpets with the cleaning roller supports cleaning of carpet fibres.

4 Forwards working direction only

- Prevention of unnecessary empty runs.
- Up to 30% higher area performance than conventional spray extraction

TECHNICAL DATA AND EQUIPMENT

BRC 40/22 C

- Forwards working direction
- Contact pressure and brush pressure can be adjusted to the degree of soiling or fibre height
- Compact, for small to medium-sized surfaces

Technical data		
Area performance (deep cleaning/ iCapsol intermediate cleaning)	m²/h	500 / 900
Air flow rate	I/s	47
Vacuum	mbar / kPa	299 / 30
Spray pressure, deep cleaning	bar	7
Spray rate, deep cleaning	I/min	2.5
Brush working width	cm	40
Working width, vacuuming	cm	48
Fresh/waste water tank	I	22 / 19
Turbine/brush motor rating	W	1119 / 400
Mains voltage	V	220-240
Frequency	Hz	50-60
Weight	kg	65
Dimensions (L × W × H)	mm	889 × 470 × 1118

Equipment		
Working direction		Forwards
Roller brush		1
2-tank system		T .
iCapsol mode		1
Optional handle with trigger		T .
Variable contact pressure		1
Number of rollers	piece(s)	1
Order no.		1.008-062.0
Price		

■ Included in the scope of supply.

ET CLEANING

DEEP CARPET CLEANERS



For interim or deep cleaning of larger carpeted areas

Kärcher carpet cleaners are used for basic cleaning of large carpeted areas economically and efficiently. Suitable for conventional spray extraction and interim carpet cleaning using the new detergent RM 768 iCapsol. Dirt dries within 20 minutes and crystallises. The dirt only has to be vacuumed.



1 Floating brush head with contra-rotating roller brushes

- Two roller brushes for high cleaning performance.
- Simultaneously cleans deep into the pile from two sides.

2 Working direction, forwards or backwards

- Working direction adjustable to carpet.
- $\hfill \blacksquare$ Cleaning direction selectable by folding push handle.

BRC 45/45 C

- For medium-sized areas
- Works forwards and backwards
- Two contra-rotating roller brushes with constant contact pressure

		Two contra-rotating roller brushes with constant contact pressure
Technical data		
Area performance (deep cleaning/ iCapsol intermediate cleaning)	m²/h	350 / 1000
Air flow rate	I/s	45
Vacuum	mbar / kPa	300 / 30
Spray pressure, deep cleaning	bar	7
Spray rate, deep cleaning	I/min	3.2
Brush working width	mm	410
Working width, vacuuming	mm	450
Fresh/waste water tank	I	45 / 38
Turbine power	W	1100
Brush motor power	W	600
Mains voltage	V	220-240
Frequency	Hz	50
Weight	kg	48
Dimensions (L × W × H)	mm	770 × 545 × 1250
Equipment		
Working direction		Forward or backwards
Optional handle with trigger		I
iCapsol mode		
Number of rollers	piece(s)	2
Order no.		1.008-056.0

■ Included in the scope of supply.

DEEP CARPET CLEANERS



For quick and deep cleaning of carpets

Easy to use with deep cleaning performance. Can be used with optional Kärcher upholstery and floor nozzles for deep cleaning in difficult-to-reach areas.





1 High cleaning performance

- Roller brush assists fibre-deep cleaning.
- Floating roller brush for uniform cleaning performance.

2 Compact dimensions

- Ideal for areas between 200 and 800 m².
- Easy storage.

BRC 30/15 C

- Compact, for small to medium-sized surfaces
- Working direction, backwards
- 1 roller brush with constant contact pressure

Technical data		
Area performance (deep cleaning/ iCapsol intermediate cleaning)	m²/h	150
Air flow rate	I/s	20
Vacuum	mbar / kPa	300 / 30
Spray pressure, deep cleaning	bar	3.5
Spray rate, deep cleaning	I/min	1
Brush working width	mm	270
Working width, vacuuming	mm	315
Fresh/waste water tank	I	15 / 17
Turbine power	W	1130
Brush motor power	W	80
Mains voltage	V	220-240
Frequency	Hz	50
Weight	kg	36
Dimensions (L × W × H)	mm	920 × 360 × 750

Equipment		
Working direction		Backwards
Optional handle with trigger		
iCapsol mode		-
Number of rollers	piece(s)	1
Order no.		1.008-057.0
Price		

■ Included in the scope of supply.

FOR MORE APPLICATION OPTIONS

Using the right accessories utilises the full power of our spray extraction cleaners. For example, the professional power brush PW 30/1 makes every spray extraction cleaner suitable for cleaning large areas. Open up new areas of application with the right accessories. Whether floors, walls or ceilings: cleaning is much easier with our machines and accessories.



Table of contents: Carpet cleaner accessories

Accessories Page 438







Thanks to the optimal suction angle, the innovative and flexible squeegee always ensures perfect cleaning results. Even under sofas, cabinets, etc. – irrespective of the operator's height – thorough, immaculate carpet cleaning is always possible. Thanks to the outstanding extraction capability of the machines, carpets are dry in next to no time. The modular system enables fast conversion to other working widths, hard surface adapters or nozzles. The additional handle on the tube can be adjusted without tools. The operator can see the flow of dirty water through the additional transparent section in the handle with trigger.

2 Left-hand, or right-hand use

With our unique handle with trigger for spray extraction cleaners, every operator can clean ergonomically and comfortably – regardless of their height and whether they are right- or left-handed. The new design with large transparent section allows a continuous view of the flow of dirty water



3 Cleaning in vehicles

Thanks to the optimal suction angle, the innovative and flexible squeegee always ensures perfect cleaning results. Even under sofas, cabinets, etc. - irrespective of the operator's height - thorough, immaculate carpet cleaning is always possible. Thanks to the outstanding extraction capability of the

SPRAY EXTRACTION CLEANER



The new, modular accessories are well thought out in every detail. They offer, for example, a movable joint for better ergonomics, guaranteeing optimal vacuuming in every angle position.















18	

WWW.								15	
	Order no.	Quantity	ID	Width	Length	Price Description			Puzzi 30/4 Puzzi 30/4 Puzzi 30/4 E Puzzi 10/2 Adv Puzzi 10/1 Puzzi 10/1 Puzzi 10/1 Puzzi 10/1
Spray/suction hoses									
Spray/suction hose, 4 m	1 6.394-874	.0 1 piece(s)	ID 32		4 m	Standard spray/suct	on hose.	1	
Spray/suction hose, 2.5 m	2 6.394-826	.0 1 piece(s)	ID 32		2.5 m			2	
Spray/suction hose, 4 m	3 6.394-375	.0 1 piece(s)	ID 32		4 m	Optional 4 m spray/s	uction hose.	3	
Floor tools									
Flexible floor nozzle, 240 mm, complete	4 4.130-007	.0 1 piece(s)	ID 32	240 mm			r nozzle (240 mm), suction pipe and at field of view for checking the er. Flexible squeegee.	4	
Flexible floor nozzle, 240 mm, individual	5 4.130-008	.0 1 piece(s)	ID 32	240 mm			n), individual. Transparent field of e vacuumed dirty water. Flexible in kit 4.130-007.0.	5	
Flexible floor nozzle, 350 mm, complete	6 4.130-011	.0 1 piece(s)	ID 32	350 mm			r nozzle (350 mm), suction pipe and at field of view for checking the ar. Flexible squeegee.	6	
Flexible floor nozzle, 350 mm, individual	7 4.130-009	.0 1 piece(s)	ID 32	350 mm			n), individual. Transparent field of e vacuumed dirty water. Flexible in kit 4.130-011.0.	7	
Roller brush PW 30/1	8 6.286-569	.0 1 piece(s)		285 mm		Standard bristles for	PW 30/1 professional washing head.	8	
Hard surface adapters									
Hard floor rubber adapter, small 240 mm	9 4.762-014	.0 1 piece(s)		240 mm		Hard surface adapte	for floor nozzle, 240 mm.	9	
Hard floor rubber adapter, large 350 mm	10 4.762-017	.0 1 piece(s)		350 mm		Hard surface adapte	for floor nozzle, 350 mm.	10	
Upholstery tools		·							
Upholstery nozzle	11 4.130-001	.0 1 piece(s)	ID 32	110 mm		Upholstery nozzle, 1	10 mm.	11	
Other									
Handle	12 4.130-000	.0 1 piece(s)	ID 32			nozzles. With sight g	e of floor, upholstery and crevice lass for checking the vacuumed s for spray and suction hose.	12	
Extension tube	13 4.025-004		ID 32	780 mm		Extension tube, indiv		13	
Cleaning agent container, complete	14 4.070-006	.0 1 piece(s)					ning agent container and Home nnecting Home Base Rail.	14	
D-handle	15 4.321-001	.0 1 piece(s)				D-handle, individual adjustable without to	for extension tube 4.025-004.0 pols.	15	
Cleaning agent tank, individual	16 5.070-010	.0 1 piece(s)				For attaching to Hon	e Base adapter.	16	
Defoamer dosage	17 4.006-907	.0 1 piece(s)	ID 32			Container for defoar	er solution.	17	
Crevice nozzle	18 4.130-010	.0 1 piece(s)	ID 32			Crevice nozzle for st	ray extraction cleaners.	18	

[■] Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

CARPET CLEANING MACHINES



The hand and floor nozzle accessories are the perfect complement to your carpet cleaning machines BRC 45/45 C, BRC 40/22 C or BRC 30/15 C. These accessories can be used to extend the fields of application of the BRC and also clean delicate upholstery and hard-to-reach, cluttered carpets gently and thoroughly, just as with the economical spray extraction cleaner on medium to very large carpeted areas.





















)	40
	11

	Order no.	Quantity	ID.	Width	Length	Price Description		BRC 40/22 C BRC 45/45 C
Spray/suction hoses	Order 110.	Qualitity	טו	width	Lengui	Price Description		11 11
Spray/suction hose, 4 m	1 4.440-644.0	1 piece(s)	ID 38	4 m	I	Complete, metal coupling.	1	000
Floor tools		1 1 1 1 1 1 1						- - -
Floor tool	2 4.130-061.0	1 piece(s)	ID 38	330 mm		Three nozzles, extended, high-pressure 1–14 bar.	2	0 0 0
Upholstery tools								
Hand nozzle	3 4.130-163.0	1 piece(s)	ID 38	110 mm		Stainless steel with transparent nozzle, ID 38. For cleaning upholstery or small surfaces that cannot be reached with the floor nozzle.	3	
Roller brushes		'		'	'			
Roller brush	4 8.621-604.0	1 piece(s)			300 mm	Standard, black, suitable for all types of carpets.	4	
	5 8.621-605.0	1 piece(s)			450 mm	Standard, black, 2 required.	5	
	6 8.629-552.0	1 piece(s)			450 mm	Soft, 2 required. For hard carpets such as needle felt or short loop-pile carpets.	6	
	7 4.762-254.0	1 piece(s)			400 mm	Carpet brush for loop-pile carpets.	7	
	8 4.762-000.0	1 piece(s)			400 mm	Carpet brush for velour.	8	
Other accessories								
Adapter	9 8.631-030.0	1 piece(s)				For floor tool 4.130-061.0 and handle with trigger 4.130-163.0.	9	
Miscellaneous								·
Filling hose	10 6.680-124.0	1 piece(s)			1.5 m	Hose for convenient fresh water filling from all standard taps.	10	
Extension cable	11 6.647-022.0	1 piece(s)			20 m	20 m.	11	

[■] Included in the scope of supply.

□ Available accessories. More Kärcher original accessories can be found on the following pages.

STEAM CLEANERS STEAM VACUUM CLEANERS

HOT AND TOUGH ON DIRT

Our professional steam cleaners and steam vacuum cleaners prove that steam is more than just hot air. For cleaning reliably without the use of chemicals, these machines are efficient and hygienic. Steam cleaners and steam vacuum cleaners are used in wet and hygiene areas, on all hard floors, glass and tiled surfaces, as well as fittings and, with the right accessories, textile surfaces.



Table of contents: Steam cleaners/Steam vacuum cleaners

Steam vacuum cleaners	Page	44
Steam cleaners	Page	440
Battery-powered chewing gum removers	Page	448
Accessories	Page	450



Compact and economical

Our SG 4/4 steam cleaner combines compact dimensions with astounding power at 4 bar steam pressure. The two-tank system reduces heat-up times for uninterrupted use. Long work intervals are possible with a total filling capacity of 4 litres. With the VapoHydro function, you can adapt the steam flow and saturation to the respective surface. And with corresponding accessories you can also clean both hard surfaces and textile surfaces without chemicals with the SG 4/4.

Cleaning with full steam

Our SGV 8/5 steam vacuum cleaner is perfect for removing stubborn dirt hygienically and effectively. From hard surfaces and stainless steel to glass surfaces throughout the industrial sector. Its eco!efficiency mode opens up new opportunities in terms of sustainability and makes quiet and energy-saving operation possible. In many cases, first-class cleaning results can be achieved even without cleaning agent. The innovative self-cleaning function reliably removes deposits in the machine and extends the service life.

Chewing gum problem? Solved!

Our new SGG 1 chewing gum remover guarantees to remove all chewing gum from any floor. In just 3 to 5 seconds, the SGG 1 completely removes all chewing gum. Eco-friendly with only water steam and a biologically degradable cleaning agent based on cereal extract. With the SGG 1, you are highly mobile and completely independent. The lightweight backpack with li-ion battery supplies power for over 8 hours of continuous use.

How to read the unit names:

Unit type Example: SGV

SGV = Steam Generator Vac, steam vacuum cleaner

= Steam Generator, steam cleaner

SGG = Steam Generating Gum Remover, steam-powered chewing gum remover

Steam pressure

In unit names with a combination of figures, for steam

In unit names with a combination of figures, for steam vacuum cleaners and steam cleaners the first figure indicates the steam pressure (in bar).

Tank capacity

vacuum cleaners and steam cleaners the second figure stands for the tank capacity (in litres).

STEAM VACUUM CLEANERS



Hygiene, non-stop

The user-friendly SGV 6/5 and SGV 8/5 steam vacuum cleaners ensure optimal hygiene. They are steam cleaners and wet and dry vacuum cleaners in one, with an EASY Operation switch, secure accessory integration and a hand tool for controlling the steam/ vacuum function. With the chemical and self-cleaning functions, the SGV 8/5 provides very hygienic results.











1 Extremely user-friendly thanks to EASY Operation

- One rotary switch for all functions. Simple and quick handling, with no
 Self-cleaning mode: cleaning of hoses, pumps and tubes. For restoring need for extensive training.
- Self-explanatory symbols make the machine easy to understand and simplify operation.

3 Programs for every application (SGV 8/5)

- hygiene and cleanliness.
- Chemical function for solvating stubborn dirt with chemical agents (rinse programme protects against aerosols).

2 Handle with trigger for convenient function control

- Time-saving, flexible, easy and direct control of functions during use.
- The most important functions, like water/steam regulation, can be adjusted and there is an on/off switch for the vacuum function.
- Easily accessible and securely stored. A carrying frame allows easy removal of the nozzle accessories.

4 Cleaning without chemicals

- Hygienic cleaning of hard surfaces without the use of chemical
- Dispensing with the use of chemicals protects the environment
- Easy removal and disposal of dirty water without direct contact.

TECHNICAL DATA AND EQUIPMENT

		SGV 8/5	SGV 6/5
		EASY Operation switchSelf-cleaning functionChemical function	EASY Operation switchConvenient operation using the hand toolVapoHydro function
Technical data			
Voltage	V	220-240	220-240
Heating output	w	3000	3000
Tank capacity	I	5	5
Cable length	m	7.5	7.5
Steam pressure	bar	8	6
Weight without accessories	kg	40	39
Dimensions (L × W × H)	mm	640 × 495 × 965	640 × 495 × 965
Equipment			
Steam suction hose with handle			
Steam tubes × 2			
Floor nozzle			
Hand nozzle		•	
Order no.		1.092-010.0	1.092-000.0
Price			

■ Included in the scope of supply.

TEAM VACUUM

STEAM CLEANERS



Compact powerhouse

User-friendly SG 4/4 steam cleaner with sophisticated filling technology, infinite adjustment of steam pressure and saturation (VapoHydro), two-tank system, accessory holder and storage compartment. Very handy and compact.







3 Accessory storage compartment



1 2-tank system

- The fresh water tank can be continuously filled as the boiler and tank are separate. The integrated storage compartment enables the storage of a variety of accessories.
- Because only part of the overall volume is heated at any one time, it takes very little time for a consistent steam pattern to form.
- With a total capacity of over 4 litres, the SG 4/4 can be used for long periods without refilling.

2 VapoHydro

- Thanks to VapoHydro, the steam level can be infinitely adjusted to the cleaning task.
- In addition to the steam pressure, the saturation can be infinitely adjusted from full steam to hot water.
- With the hot water jet, even stubborn dirt can be effectively dissolved from the start.

4 Hygienic cleaning

Hygienic cleaning without the use of chemical substances.

Even the tubes can be stored on the rear of the unit.

The avoidance of aggressive cleaning agents protects the operator and treated surfaces.

■ Special small parts are always safely stored and do not get lost.

Only water is used for cleaning - unharmful to health and cost-effective.

TECHNICAL DATA AND EQUIPMENT

SG 4/4

2-tank system
Short heat-up time
Pump for hot boiler filling

Technical data		
Voltage	V	220-240
Heating output	W	2300
Tank capacity	I	4
Cable length	m	7.5
Steam pressure	bar	4
Weight without accessories	kg	8
Dimensions (L × W × H)	mm	475 × 320 × 275

Equipment	
Steam hose with handle	•
Steam tubes × 2	1
Floor nozzle	1
Round brush	1
Upholstery nozzle with brush	1
Order no.	1.092-104.0
Price	

■ Included in the scope of supply.

STEAM CLEANER STEAM VACUUM CLEANERS


BATTERY-POWERED CHEWING GUM REMOVER



Remove chewing gum in seconds

Our SGG 1 steam cleaner is incredibly effective when it comes to removing stubborn chewing gum remnants, and is kind to the environment too. The combination of steam and biodegradable cleaning agent makes light work of removing dried-on chewing gum - just a few seconds and it's gone. This helps the battery in the comfortable backpack system last even longer: with a battery life of around 8 hours, you can keep on working uninterrupted for long periods.









- 1 Biodegradable cleaning agent made from vegetable extract
- Environmentally friendly and safe for the operator.
- Removes all traces of chewing gum.

- 3 Cordless working
- $\quad \blacksquare \quad \mbox{Optimal working radius coupled with excellent productivity.}$

- 2 Powerful, long-lasting lithium-ion battery
- Enables you to work for up to 8 hours.

- 4 Comfortable, convenient rucksack carrying system
- Affords fantastic flexibility to make your work easier.

TECHNICAL DATA AND EQUIPMENT

SGG 1

Long runtime thanks to the powerful lithium-ion battery

■ Comfortable, convenient, ergonomically designed backpack system

Technical data		
Battery running time	h	8
Battery charging time	h	4
Battery voltage	V / Ah	lithium-ion battery / 14.8 / 9
Sound pressure level	dB(A)	70
Battery charger	V / Hz	110-240 / 50-60
Weight without accessories	kg	8.3
Dimensions (L × W × H)	mm	250 × 300 × 550

quipment		
team lance	m	1.2
team hose	m	1.6
attery charger	V / Hz	I
onsumable Kit		-
rder no.		1.092-900.0
rice		

■ Included in the scope of supply.

Accessories			
Product name	Order no.	Description	Price
Consumables kit	4.071-252.0	The consumables kit for our SGG 1 chewing gum remover contains four bottles of biodegradable cleaning	

STEAM CLEANER/STEAM VACUUM CLEANER ACCESSORIES



The extensive accessory range makes Kärcher's steam cleaners and steam vacuum cleaners versatile, multitalented machines. In addition to hard surfaces, with the right accessories textile surfaces can also be optimally cleaned.

















						ADS
						1 8/4
	Order no.	Quantity	Price	Description		SGV 8/5 / SG 4/4 SGG 1
Cloth kit						
Terry cloth cover	1 6.370-990.0	5 piece(s)		Cloth kit with five high-quality cotton covers for the hand nozzle.	1	
Microfibre cloth kit, cover	2 2.863-174.0	2 piece(s)		2 microfibre covers for the hand nozzle. For even better loosening and intake of dirt	2	
				and grease. Ideal for particularly heavy and stubborn dirt in bathrooms and kitchens.		
Microfibre cloth set for bathrooms	3 2.863-171.0	4 pioco(s)		Effortlessly removes even stubborn stains on hobs.	3	
MICIOIDIE CIOUI SELIOI DALIIOOIIIS	3 2.803-1/1.0	4 piece(s)		Two special microfibre floor cloths (for floor nozzle Classic and Comfort), one microfibre abrasive cloth for removing stubborn limescale and soap residue and one microfibre		
				polishing cloth for polishing mirrors and other smooth surfaces – for optimal use of the		
				steam cleaner in bathrooms.		
Microfibre cloth set for kitchens	4 2.863-172.0	4 piece(s)		Two special microfibre floor cloths (for the floor nozzle Classic and Comfort), one soft	4	
				microfibre cover for the hand nozzle for loosening stubborn dirt, e.g. on hobs. One micro-		
				fibre stainless steel cloth for perfect cleaning of all stainless steel surfaces – for optimal use of the steam cleaner in kitchens.		
Microfibre cloth kit for floor nozzle	5 2.863-173.0	2 piece(s)		2 microfibre floor cloths for the floor nozzle Classic and Comfort for easier dirt removal	5	
Classic and Comfort		- p		and pick-up. For easy floor cleaning and brilliant results on flooring such as tiles, natural		
				stone, linoleum and PVC.		
Microfibre cover set	6 2.863-270.0	2 piece(s)		Two high-quality microfibre covers for the hand nozzle. Dirt and grease are picked up and	6	
for the hand nozzle				removed more effectively. Ideal for stubborn dirt in bathrooms and kitchens – even on stove-		
Town relation wide	7 6 260 401 0			tops.		
Terry cloths, wide	7 6.369-481.0	5 piece(s)		Lint-free, absorbent and hard-wearing. Five wide floor cleaning cloths (for floor nozzle Classic and Comfort) made of high-quality cotton.	7	
Steam cleaners/Steam vacuum clean	ners			classic and connord made of high quanty cotton.		
Floor nozzle SG 4/4	8 2.885-465.0			The innovative floor nozzle now promises even better cleaning performance - thanks to	8	
				optimised steam utilisation and a larger cleaning surface. For use with all available floor		
				cleaning cloths.		
Consumables kit	9 4.071-252.0			The consumables kit for our SGG 1 chewing gum remover contains four bottles of	9	
				biodegradable cleaning agent, two butane or propane gas cartridges and two stainless		
Brush Set, stainless steel	10 6.425-030.0	10 pioco(s)		steel brushes.	10	
Brush Set, nylon	11 6.425-031.0	_	_	High-quality brush set made from durable stainless steel. Brush set made from high-quality and hard-wearing nylon.		
Bristle rink set	12 2.863-077.0			Plastic bristles, 2x red (hard), 1x black.	12	
Round brush set	13 2.863-011.0			Set consisting of stainless steel, brass and Pekalon round brushes.	13	
Floor nozzle, 300 mm,	14 2.889-005.0	-		Floor nozzle for steam and vacuuming applications.	14	
with Pekalon brushes		- p. ccc (c)		Floor flozzle for steam and vaccoming applications.		
Rubber strip, 300 mm	15 2.889-007.0	1 piece(s)		Rubber strip for floor nozzle 2.889-005.0.	1.5	
Hand nozzle, 150 mm	16 2.889-008.0	1 piece(s)		Hand nozzle for steam and vacuuming applications.	16	
Brush strips, 150 mm	17 2.889-009.0	1 piece(s)		Brush strips for hand nozzle 2.889-008.0.	17	
Rubber strip, 150 mm	18 2.889-010.0	1 piece(s)		Rubber strip for hand nozzle 2.889-008.0.	18	
Adapter	19 2.889-011.0			Adapter for accessories.	19	
Crevice nozzle	20 2.889-028.0			Crevice nozzle, 200 mm.	20	
Extension piece adapter	21 2.889-052.0			Adapter for attaching round brushes.	21	
Steam suction hose	22 4.440-009.0	-		Steam suction hose for steam and vacuuming applications, length 4 m.	22	
Triangular floor nozzle	23 2.889-053.0			Triangular floor nozzle for cleaning corners.	23	
Suction hose	24 2.889-127.0	1 piece(s)		Suction hose (1 m) for easier cleaning of corners and other tight spaces with our SGV	24	
Round brush stainless steel set	25 2.863-007.0	3 nieco(c)		steam vacuum cleaners. And of course, compatible with hand nozzles and accessories.	25 L	
Round brush brass set	26 2.863-007.0			Very hard bristles.	26	
Pekalon round brush set	26 2.863-008.0	+ -		Hard bristles.	27	
Stainless steel round brush	28 6.907-539.0			Medium-hard bristles. Pound brush with very hard stainless steel bristles and metal thread.	28	
Pekalon round brush	29 6.907-540.0			Round brush with very hard stainless steel bristles and metal thread. Round brush with medium-hard Pekalon (PEK) bristles and	29	
. Example Footing Droom	25 0.507 540.0	I picce(3)		metal thread.		
- NEW - Included in the cases of	face and a second	<u> </u>		Kärcher original accessories can be found on the following pages.		

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kārcher original accessories can be found on the following pages.

























		Order no.	Quantity	Price Description		SGV 8/5 / SGV 6/5 SG 4/4 SGG 1
Brass round brush	30	6.907-541.0	1 piece(s)	Round brush with hard brass bristles and metal thread.	30	
Round brush, black, Pekalon	31	6.907-439.0	1 piece(s)	Black round brush with medium-hard Pekalon (PEK) bristles for Kärcher SGV 6/5 and SGV 8/5 steam vacuum cleaners.	31	
Round brush, blue, Pekalon	32	6.907-587.0 ■	1 piece(s)	Blue round brush with medium-hard Pekalon (PEK) bristles for Kärcher SGV 6/5 and SGV 8/5 steam vacuum cleaners.	32	
Round brush, green, Pekalon	33	6.907-588.0 ■	1 piece(s)	Green round brush with medium-hard Pekalon (PEK) bristles for Kärcher SGV 6/5 and SGV 8/5 steam vacuum cleaners.	33	
Round brush, yellow, Pekalon	34	6.907-589.0 ■	1 piece(s)	Yellow round brush with medium-hard Pekalon (PEK) bristles for Kärcher SGV 6/5 and SGV 8/5 steam vacuum cleaners.	34	
Round brush, red, Pekalon	35	6.907-590.0	1 piece(s)	Red round brush with medium-hard Pekalon (PEK) bristles for Kärcher SGV 6/5 and SGV 8/5 steam vacuum cleaners.	35	
Funnel	36	4.013-030.0	1 piece(s)	Filling funnel with integrated sieve, for easy and secure filling of the water tank.	36	
Extension tube	37	4.127-024.0	2 piece(s)	Two plug-in tubes for convenient floor cleaning.	37	
Steam hose	38	4.322-020.0	1 piece(s)	Connection hose with handle and switch, length 2.5 m.	38	
Floor nozzle	39	6.906-185.0	1 piece(s)	Floor nozzle with additional bristles for removing stubborn dirt. Can be used with or without floor cleaning cloth.	39	
Trolley	40	6.962-239.0	1 piece(s)	Metal, chrome-plated, with storage tray.	40	
Filling funnel	41	6.962-097.0	1 piece(s)	Funnel inlet with integrated sieve, for easy and secure filling of the water tank.	41	
Extension tube, metal						
Extension tube set	42	2.889-004.0	2 piece(s)	The kit contains two steam suction tubes.	42	
Nozzles		'	'			
Window nozzle	43	2.863-025.0	1 piece(s)	Streak-free cleaning of glass surfaces can easily be achieved by using the window nozzle with the steam cleaner. This not only extends the range of applications for Karcher steam cleaners but also ensures sparkling clean windows and mirrors.	43	
Hand nozzle	44	2.884-280.0	1 piece(s)	Hand nozzle with extra bristles for cleaning small surfaces such as shower cabins, wall tiles and much more. Suitable for use with or without cover.	44	
Power nozzle and extension	45	2.884-282.0	2 piece(s)	The power nozzle with extension considerably increases the cleaning power of the detail nozzle. Ideal for easy and eco-friendly cleaning of difficult to reach areas, e.g. corners.	45	
Rubber squeegee for window tool	46	6.273-140.0	1 piece(s)	Rubber squeegee for the steam cleaner window nozzle.	46	
Detail nozzle		2.884-281.0		Point jet nozzle, ideal for cleaning in crevices, corners, edges and other difficult to reach areas. Can be used in combination with round brush for greater versatility.	47	
Floor tool	48	2.885-142.0	1 piece(s)	The innovative floor nozzle now promises even better cleaning performance - thanks to optimised steam utilisation and a larger cleaning surface. For use with all available floor cleaning cloths.	48	

■ NEW ■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.

452

STEAM CLEANERS / STEAM VACUUM CLEANERS

WATER AND AIR - THE BASIS OF OUR LIFE

Like every human being you need clean water and clean air to live. To be healthy and fit we need 2 to 3 litres of water to drink and around 12,000 litres of air to breathe per day. Dirty water and air have dramatic effects on your health and performance. Protect your health with our WPD water dispensers, the WPC water treatment systems and the AF and AFG air purifiers. Now there is a healthier way to breath air and drink water.





Air cleaning Page 458 Water dispensers Page 462 Water treatment Page 468



AF 100 / AFG 100 - for clear, clean air

When the indoor air is polluted and you feel unwell - simply get some fresh


Our WPD 50 Ws is the new middle class of our water dispenser range. air at the touch of a button. Our new AF 100 and AFG 100 Air Purifiers generate clean and fresh air for you wherever you need it and in any circumstances. With the different air filters you have the right solution for every type of dirt particles.

WPD 50 Ws - for a new water class

This compact water dispenser is ideal when space is limited, providing chilled and ambient-temperature still water and chilled sparkling water. You will love the intuitive operation with the capacitive buttons.

How to read the unit names:

Model	Filter capacity	Filter type
Example: WPC	100	RO
WPC = Water Purifier Commercial WPD = Water Purifier Dispenser	Litres per hour	RO = Reverse Osmosis UF = Ultra Filtration
Example: AFG	100	
AF = Air Filter AFG = Air Filter Germicidal	suitable for room of 100 m ²	



1 Fresh air - always and anywhere

Polluted air is always a problem, caused by vapours from carpets, pollen count, germs, poor air quality after a long conference in the meeting room or odours at the hairdresser's or in treatment rooms. All this can result in an inability to concentrate, headaches, a blocked nose and even asthma attacks. Say goodbye to these problems with our air purifier: switch on the air purifier – and breathe freely.



2 Our water dispensers - water in a class of its own

Potable tap water is good. Water from a Kärcher WPD water dispenser is better. Water for life. Thanks to its unique filter and hygiene concept, our WPD produces water of the highest quality around the clock. Depending on the machine, there is a choice of ambient, chilled, sparkling or hot water at the push of a button. Hygienic, calorie-free and pure. We achieve this through automatic thermal disinfection, contact protection for the water dispensing valve and the innovative filter concept consisting of Active-Pure filter and Hy-Protect filter. The Active-Pure filter ensures that the water tastes pure. The Hy-Protect filter works with ultra filtration without the addition of chemicals. Its fine-pore membrane reliably filters out bacteria and viruses.

AFG 100 AIR PURIFIER



Breathe deeply

Thanks to new plasma technology and an innovative combination of prefilter and three-stage filter (HEPA*, catalyser and active carbon filter), our AFG 100 air purifier eliminates all types of air pollution. Nothing is left behind, no hair, no dust, no mites, no smoke. Not even any bacteria or viruses. Rooms of up to 60 m² are purified in no time, allowing you to breathe deeply once again.



















1 Multi-stage filter system

- Combination of prefilter, 3-stage filter (HEPA*, active carbon, catalyser). * EN 1822:1998.
- Removes particles, gases and germs from the ambient air and effectively destroys them.
- A high air throughput guarantees very effective air purification.

2 Modern, slim and compact machine design

- Fits into every space unobtrusively.
- Lighting can be adapted if required.

3 Unique plasma treatment

- ensures that it is sterile.
- When used together HEPA* and active carbon can remove all harmful substances from the ambient air. * EN 1822:1998.
- Suitable for any type of air pollution. Does not emit ozone (according to ECARF).

4 Easy handling

- Intuitive operation and control of the machine.
- With filter change indicator. The filter can be replaced independently
- Wear-free and maintenance-free plasma generator guarantees constantly high cleaning performance.

TECHNICAL DATA AND EQUIPMENT

		AFG 100, white	AFG 100, anthracite
		 Complete solution for cleaning and disinfecting ambient air Sensor-based, automatic measurement of air quality Flexible operating times with timer function 	 Complete solution for cleaning and disinfecting ambient air Sensor-based, automatic measurement of air quality Flexible operating times with timer function
Technical data			
Current type	Ph / V / Hz	1 / 110-240 / 50-60	1 / 110-240 / 50-60
Sound pressure level	dB(A)	min. 25-max. 53	min. 25-max. 53
CADR PM 2,5	m³/h	> 120	> 120
CADR smoke	m³/h	> 127	> 127
CADR pollen	m³/h	> 139	> 139
Equipment			
Prefilter		1	1
Plasma generator			•
HEPA filter (EN 1822:1998)			•
Active carbon filter			•
Automatic mode		•	1
Operating panel			•
Adjustable lighting			•
Order no.		1.024-800.0	1.024-801.0
Price			

■ Included in the scope of supply.

ATER AND AIR

AF 100 AIR CLEANER



A breath of fresh air

Our AF 100 needs only a couple of minutes to produce fresh, clean air in rooms up to 100 m². Customisable with five special filters - from antibacterial action to eliminating volatile organic compounds. A highly precise sensor monitors the air quality, shows this on the display and regulates the machine automatically.

















1 Five filter options for various applications

- Special filters for eliminating bacteria, allergens, odours and volatile organic compounds.
- 3 Powerful motor for rooms up to 100 m²
- Fan with three speed settings.

2 Compact design with high mobility

■ Easy to move between rooms thanks to the unit's robust rollers.

4 Intuitive operation and simple maintenance

Filter service life can be read off the display. Customers can replace the filter easily themselves.

TECHNICAL DATA AND EQUIPMENT

AF 100

Different	filters	for	anv	annl	ication

■ Precise sensor-based air quality measurement

Robust rollers ensure excellent mobility

Technical data		
Current type	Ph / V / Hz	1 / 220-240 / 50-60
Sound pressure level	dB(A)	min. 30-max. 48
CADR PM 2,5	m³/h	> 750
CADR formaldehyde	m³/h	> 350
CCM PM 2.5		P4
CCM formaldehyde		F4

Equipment	
Prefilter	1
Universal Pure filter	1
Allergy filter	optional
Anti-bacterial filter	optional
Smoke filter	optional
TVOC filter	optional
Filter replacement indicator	1
Automatic mode	
Night mode	1
Operating panel	
Rollers	1
Order no.	1.024-810.0
Price	

■ Included in the scope of supply.

WATER DISPENSER WPD 100 / 200 / 600



Unique: customised water dispenser

The configurable water dispensers can be individually tailored to different customer requirements (e.g. country, target group, installation site) in terms of cooling capacity, software functionality and product features.



















1 A real eye-catcher

- Available in white or black.
- Individually printable glass panel ideal as a free advertising surface or for displaying your company logo.
- Water dispensing area with LED lights.
- Extra-high water dispensing area.

2 Healthy water from a constantly pure, hygienic source

- All water-conducting pipes, the heating and cooling module, ultra filter and output valve are regularly disinfected automatically with hot water 📗 In the WPD 100, you can use any standard 425 g bottle of CO₂. - without the use of chemicals.
- Bacteria and viruses are reliably killed. Rinsing after disinfection takes place automatically, without any effort, and can be set to run at any
- Kärcher's patented thermal disinfection offers maximum safety.


3 All important information at a glance

- Advanced package: Using the high-resolution colour display, you can adjust the dispensing quantity, CO₂ intensity and water temperature. The display informs you when the filter needs to be replaced and the status of the CO₂ supply.
- Kärcher Fleet M2M* communication establishes direct communication between the water dispenser and a PC or smartphone. You have comprehensive monitoring options which allow you to avoid unnecessary service work. (*machine-to-machine)

4 Easy CO₂ supply

- The smallest 425 g bottle of CO₂ provides over 60 litres of sparkling
- The bottle is easy to change in the machine.
- Empty CO₂ bottles can be refilled do your part to protect the environment

AS INDIVIDUAL AS GOOD TASTE.







Depending on the electronics package, there are up to 6 different water types available: ambient, chilled, chilled with Medium (lightly sparkling) or Classic (strongly sparkling) CO₂, as well as hot and extra hot.



Colour variations

In pure white and classic black, the WPD stands out in any surroundings.



Filter combination

Choose the best combination configuration for your requirements: Active-Pure filter, Hy-Protect filter, Hy-Pure filter or UV Protect.



Individual front design

The glass panel can be designed with customer-specific background (e.g. colours of the company's CI) or used as a free advertising surface.

TOP PATENTED TECHNOLOGY GUARANTEES THE HIGHEST QUALITY.



		WPE	0 600	WPI	200	WPD 100		
		Adv	Basic	Adv	Basic	Adv	Basic	
Technical data								
Power supply	V / Hz	220-240 / 50	220-240 / 50	220-240 / 50	220-240 / 50-60	220-240 / 50	220-240 / 50	
Power input	kW	1.9	0.6	1.9	0.3	1.9	0.3	
Sound pressure level	dB(A)	45	45	45	45	45	45	
R134a coolant	kg	0.15	0.15	0.10	0.10	0.07	0.07	
Water quantity, still, ambient	I/h	120	120	120	120	120	120	
Water quantity, still, chilled	l/h	80	80	40	40	20	20	
Cold water temperature	°C	4-12	4-12	4-12	4-12	4-12	4-12	
Water quantity, still, hot	l/h	10	-	10	-	10	-	
Hot water temperature	°C	80-95	-	80-95	-	80-95	-	
Water quantity, chilled with CO ₂	l/h	80	80	40	40	20	20	
CO ₂ content in the water	g/l	4.5 (Medium) 6.5 (Classic)	6.5 (Classic)	4.5 (Medium) 6.5 (Classic)	6.5 (Classic)	4.5 (Medium)	4.5 (Medium)	
CO ₂ bottle size in table top unit	kg	-	-	-	-	0.425	0.425	
CO ₂ bottle size in stand-alone unit	kg	max. 10	max. 10	max. 10	max. 10	max. 10	max. 10	
Weight, table top unit	kg	-	-	35	35	30	30	
Weight, stand-alone unit	kg	65	65	50	50	45	45	
Dimensions table top unit (L × W × H)	mm	-	-	465 × 365 × 528	465 × 365 × 528	465 × 365 × 528	465 × 365 × 528	
Dimensions stand-alone unit (L × W × H	l) mm	1432 × 365 × 528	1432 × 365 × 528	1432 × 365 × 528	1432 × 365 × 528	1432 × 365 × 528	1432 × 365 × 528	
Water outlet height	mm	300	300	300	300	300	300	
Number of users		more than 100	more than 100	up to 100	up to 100	up to 50	up to 50	
Order no.		1.024-920.2	1.024-920.2	1.024-920.2	1.024-920.2	1.024-920.2	1.024-920.2	

CONFIGURATION OPTIONS

	WPD 600		WPD 200		WPD 100	
	Adv	Basic	Adv	Basic	Adv	Basic
Versions		-				
Table top unit	-	-				
Stand-alone unit with base	•	•				
Casing colour, white						
Casing colour, black						
Water type						
Water, still, ambient	•		•	•	•	
Water, still, chilled	•	•	•	•	•	
WPD, Medium CO₂		-		-		
WPD, Classic CO₂					-	-
Water, hot		-		-		-
Water, extra hot		-		-		-
Water treatment						
Active-Pure filter (active carbon filtration)						
Hy-Protect filter (ultra filtration)	•		•		•	
Hy-Pure filter (2-in-1 filter)	-	-	-	-		
UV-Protect (UV lamp)	-		-		-	
Thermal disinfection		-	•	-	•	-
Chemical cleaning	-	•	-	•	-	-
WPC 100 RO drinking water production	-	-	-		-	
Electronic equipment						
Multifunction colour display		-		-		-
Display, filter replacement	•	-	•	-	•	-
Display, change CO₂ bottle		-	•	-	•	-
Adjustable portion size		-	•	-	•	-
Adjustable CO₂ intensity		-	•	-	-	-
Adjustable hot water temperature	•	-	•	-	•	-
Error indication						•
Interface for Kärcher Fleet services (M2M communication)		-		-		-
Illuminated dispensing area	•	-	•	-	•	-
Accessories						
Drip tray draining						
Drink accessories (jugs, carafes, bottles, cups, etc.)						
Cup dispenser (in base)						
Waterblock leak protection						

WATER DISPENSER WPD 50




Small, affordable - the perfect entry-level machine

Our new middle class water dispenser is ideal for use in confined spaces. Active carbon filters and UV lamp ensure that the dispensed still water is pure and free from bacteria and viruses - chilled or ambient.











1 Compact design

- Intuitive operating concept with easy-to-read sensor buttons.
- drinking vessel.

- The perfect fit where there is limited available space.
- Clearly recognisable dispensing area for optimal positioning of the

2 Pure enjoyment - the healthy and safe choice

- The active-pure filter ensures the best taste and removes chlorine and heavy metals from the pipe.
- UV lamp: UV-protect kills bacteria and viruses.
- All water pipes, the cooling module and the water outlet are sanitised using high performance sanitising tabs.

3 Affordable enjoyment

- $\hfill \blacksquare$ No inconvenient transportation of gallon containers or bottles. Very easy handling.
- Energy-efficient cooling system.
- Uncomplicated filter changing and maintenance of the UV lamp thanks to extremely easy access.

4 Very easy to use

- Supplies pure still water chilled or ambient temperature.
- Glass front which is easy and quick to clean.

TECHNICAL DATA AND EQUIPMENT

		WPD 50	WPD 50 Ws
		Space-saving and compactIntuitive operation thanks to user-friendly icons	Space-saving and compactIntuitive operation thanks to user-friendly icons
Technical data			
Current type	Ph/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50
Input pressure without carbonation	bar / MPa	1.5-max. 6 / 0.15-max. 0.6	1.5-max. 6 / 0.15-max. 0.6
Coolant		R134a	R134a
Amount of Coolant	kg	0.035	0.035
Water amount, quantity	I/h	max. 15	max. 15
Water quantity, ambient	I/h	max. 85	-
Water quantity, chilled, carbonated	I/h	-	max. 15
Rated input power	W	max. 200	max. 300
Inlet temperature	°C	5-30	5-30
Water outlet height	mm	290	290
Dimensions (L × W × H)	mm	350 × 300 × 395	350 × 300 × 395
Equipment			
Hygienic cleaning		Detergent	Detergent
Active-Pure active carbon filter			•
2-in-1 filter "Hy-pure"			•
UV-Protect UV lamp			-
Water dispensing valve with contact protection		•	T
Positioning aid for drinking cup			
Drip tray with level indicator		•	•
Order no.		1.024-404.0	1.024-405.0
Price			

■ Included in the scope of supply.

WATER TREATMENT WPC 100 RO



Providing clean drinking water where there is none

Unfortunately, clean and potable tap water is not a given in many regions. Our compact water treatment system WPC 100 RO is a remedy for this and, using the principle of reverse osmosis, provides pure drinking water wherever it is needed. In doing so, it produces around 70% less waste water than comparable competitor products.






- 1 Optional integration into a water dispenser from the WPD range
- Makes it possible to use WPD water dispensers even in regions without
- Reverse osmosis solution for integration in the WPD machine range.
- 2 Can be installed directly in the cupboard under the sink
- For hygienically safe drinking water that can be used both for drinking and cooking.
- Easy and intuitive operation.



WPC 120 UF / WPC 80 RO WATER TREATMENT

Clean drinking water. Without a lot of technology

Wherever tap water is not potable, our water treatment systems use modern ultra filtration or reverse osmosis to produce hygienically pure drinking water. All systems can be operated without a storage tank and work extremely economically. Our RO reverse osmosis models produces around 70% less waste water than comparable products.



- 1 WPC 120 UF: The water treatment system with state-of-the-art ultra filtration
- All particles > 0.02 μm are reliably removed.
- The three-stage membrane filtration reduces bacteria and other pathogens by 99.9999 per cent, while viruses are reduced by 99.95 percent.
- 2 Compact and space-saving design
- Low space requirements, even fits under the sink unit.

WPC 100 RO

- Five-stage membrane filtration
- No storage tank required

		■ Space-saving
Technical data		
Filter capacity	I/h	up to 100
Water inlet pressure	MPa / bar	0.1-0.3 / 1-3
Max. inlet temperature	°C	5-38
Operating voltage	Ph / V / Hz	1 / 110-240 / 50-60
Connection load	w	80
Weight	kg	13.5
Dimensions (L × W × H)	mm	372 × 240 × 530
Order no.		1.024-510.0
Price		

WPC 120 UF WPC 80 RO

■ Three-stage membrane filtration ■ Four-stage membrane filtration No power supply or storage tank required
 With reverse osmosis No power supply or storage tank required ■ With ultra filtration Technical data Filter capacity 0.02 0.005 Filter fineness

Water inlet pressure 1-4 / 0.1-0.4 1-6 / 0.1-0.6 Max. inlet temperature 5-38 5-38 3.5 Weight Dimensions (L × W × H) 323.8 × 148.2 × 303.4 467 × 197.3 × 415.7 1.024-752.0

PROGRAMMED TO GLEAM

Our scrubber driers are indispensable assets for professional cleaning companies. They are ideal for cleaning and caring for both hard and supple surfaces effectively, including deep cleaning, maintenance care and polishing. Flawless on flat surfaces and on the edges. If there's one thing that's indispensable for you, it's that floors are always perfectly cleaned and maintained - hygienically and to a shine.



Table of contents: Scrubbers/Scrubber driers

Ride-on scrubber driers	Page	480
Step-on scrubber driers	Page	504
Walk-behind scrubber driers	Page	510
Accessories	Page	552
Manual Cleaning equipment	Page	792
Cleaning agents, care agents and disinfection	Page	866



Cleans all by itself: KIRA B 50

With our KIRA B 50 scrubber drier robot, you benefit from fully autonomous cleaning and cost-effectiveness even in small areas. Thanks to various autonomous cleaning programs, KIRA B 50 offers maximum flexibility during use. The multisensor system and the automated intelligent route planning feature ensure reliable and safe operation at all times. At the optional docking station, KIRA B 50 can autonomously recharge, refill with fresh water and dispose of the dirty water.

Huge range: BD 80/100 W Classic

The largest Classic machine in our walk-behind class is extremely robust and surprisingly compact. With a tank volume of 100 litres, you can also take on larger cleaning tasks effortlessly surfaces. Stairs, sinks, bathrooms - with the new and without interruption.

Perfect at every level: BD 17/5 C

Our BD 17/5 C stair cleaning machine is your ideal companion for scrubbing and polishing in small or narrow spaces, and even on vertical ergonomic handle, you always have good balance and can work without getting tired. And you can now replace the brush without any tools.

How to read the machine names:

маспіпе туре	working width voidine/speed		i ype and equipment	Configuration options		
Example: BR	35	12	С			
B = Body unit without brush head or different working widths to choose from BR = Scrubber drier with roller	In machine names with a combination of numbers, the first number indi-	For scrubber driers, the second number indicates the volume of the fresh water/dirty water tank	 C = Compact, machines without traction drive W = Walk-behind, machines with traction drive 	Ep Bc	= Battery-powered = Mains-powered (corded = Battery-powered (incl. battery charger)	
BD = Scrubber drier with disc BRS = Scrubber with roller BDS = Scrubber with disc BDP = Polishing machine with disc	cates the working width (in centimetres).	(in litres). For scrubbers and polishing machines, the second number indicates the speed	R = Ride-on machine RS = Ride-on/Step-on machine I = Industry	Pack Esc	 Package (battery and battery charger included in the scope of supply) For escalator cleaning 	
		(rpm).	Abbreviations for brush heads: R = Roller head	Fact	 Three preset cleaning programs 	
			D = Disc head	Dose	= Cleaning agent dosing unit	
			S = Square cleaning head with circular vibrating motion	Classic	= simple equipment	
			O = Orbital disc head with rotating and			

oscillating rotary motions


OVERVIEW OF KÄRCHER FLOOR CLEANING MACHINES

	Price	Order no.	Working width of brushes (mm)	Max. battery runtime (hrs)	Max. theoretical area performance (m²/h)	Fresh/dirty water tank (I)	Traction drive via motor (yes/no)	Variable contact pressure	Sweeping function	On-board battery charger	Max. driving speed (km/h)	Page
Ride-on scrubber driers		1				1 .						
B 300 R I		1.480-235.2	1045 / 1755	-	10450-17550		•	•	•	-	10	483
B 250 R I		1.480-231.2	1000 / 1200	5	8000-9600	250 / 250	_	-	□¹)	_2)	8	487
B 250 R B 200 R		1.480-231.2	1000 / 1200	6 5	8000-9600	250 / 250		-	□¹)	_2)	8	487
B 150 R Adv		1.246-200.2 1.246-020.2	750 / 900 / 1100 750 / 900	4.5	4500-6600 7500-9000	200 / 200 150 / 150	-		□ ¹⁾		6	491 495
B 150 R		1.246-020.2	750 / 900	5	4500-5400	150 / 150	-	-	□ ¹⁾		6	495
B 90 R Configured		1.161-000.2	550-750	3.5	3300-4500	90 / 90	•		□ ¹⁾		6	501
B 90 R Adv Dose Bp Pack		1.161-310.0 -311.0	550-750	2.5	3300-4500	90 / 90	•	•	□ ¹⁾		6	501
B 90 R Adv Bp Pack		1.161-308.0 -309.0	550-750	2.5	3300-4500	90 / 90	•		□ ¹⁾		6	501
B 90 R Classic Bp Pack		1.161-306.0 -307.0	550-750	2.5	3300-4500	90 / 90			□ ¹⁾		6	501
BD 50/70 R Bp Pack Classic Fleet		1.161-071.0 -073.0	510	2.5	2800	70 / 75	•	-	-	_2)	5.5	503
BD 50/70 R Bp Classic Fleet		1.161-070.0 -072.0	510	2.5	2800	70 / 75	•	-	-	_2)	5.5	503
Step-on scrubber driers					Lance	l ac :						
B 95 RS		1.006-200.2	650 / 750	3.5	3900-4500	95 / 95	•	-	□ ¹⁾		6	507
BD 50/40 RS Bp Pack		1.533-170.0 -171.0	510	2.5	2800	40 / 40	•		-		4.5	509
BR 55/40 RS Bp Pack Walk-behind scrubber driers		1.533-172.0 -173.0	550	2.5	3025	40 / 40	•	-	•		4.5	508
B 120 W		1.005-100.2	750 / 900 / 1100	5.5	4500-6600	120 / 120			□ ¹⁾		6	513
BD 80/100 W Bp Classic Fleet		1.127-012.0 -016.0		5.5	4050	100 / 100			-	-	5	527
BD 80/100 W Bp Classic Fleet		1.127-012.0 -010.0		5	4050	100 / 100		-	-	-	5	527
B 80 W Bp		1.259-010.2	650 / 750	4	3900-4500	80 / 80	-	-	□ ¹⁾	•	6	516
B 60 W Bp		1.384-020.2	550 / 650	3	3300-3900	60 / 60	•	•	□ ¹⁾	•	6	521
B 60 C Bp Classic		1.384-020.2	510 / 550	3.5	2295-2475	60 / 60	-	-	□ ¹⁾	_2)	-	520
B 60 W Ep		1.384-020.2	510 / 550	-	3060-3300	60 / 60	-		□ ¹⁾	-	-	520
B 40 W Bp		1.533-210.2	430 / 550	3.5	3060-3300	40 / 40	•	-	□ ¹⁾		6	524
B 40 C Bp		1.533-210.2	430 / 550	3	1935-2475	40 / 40	-	-	□ ¹⁾	•	-	525
B 40 C Bp Classic		1.533-210.2	430 / 550	3	1935-2475	40 / 40	-	-	□ ¹⁾	_2)	-	525
B 40 C Ep		1.533-210.2	430 / 550	-	1935-2475	40 / 40	-	-	□ ¹⁾	<u> </u>	_	525
Push/Compact scrubber driers		4 407 004 0		2	1 2205	1 50 / 50				1 2		1
BD 50/50 C Bp Classic		1.127-001.0	510	3	2295	50 / 50	-	-	-	_2)	-	529
BD 50/50 C Bp Pack Classic		1.127-006.0	510	3	2295	50 / 50	-	-	-	_2)	-	529
BD 50/60 C Ep Classic BR 45/22 C Bp Pack Fleet		1.127-002.0 1.783-460.0 -465.0	510 450	2	2295 1800	60 / 60	-	-	-	-	-	529 533
BD 43/25 C Bp Bp Pack		1.515-400.0 -403.0	430	2	1720	25 / 25	-	_	-	_2)	-	531
BD 43/35 C Ep		1.515-400.0 -403.0	430	-	1720	35 / 35	-	-	-	-	-	531
BD 38/12 C Bp Pack		1.783-430.0	380	1.5	1520	12 / 12		-	-	-	-	534
BR 35/12 C Bp Pack		1.783-450.0	350	1.5	1400	12 / 12	-		•	-	-	535
BR 40/10 C Adv		1.783-316.0	400	-	400	10 / 10	-	-	-	-	-	536
BR 40/10 C Adv		1.783-311.0	400	-	400	10 / 10	-	•	-	-	-	536
BR 30/4 C Bp Pack		1.783-225.0	300	0.5	200	4 / 4	-	_	_	_2)	_	537
BR 30/4 C Adv		1.783-213.0	300	-	200	4 / 4	-	-	-	-	-	537
BR 30/4 C MF		1.783-220.0 -223.0		-	200	4 / 4	-	-	-	-	-	537
BD 30/4 C Bp Pack		1.783-230.0	300	1	900	4 / 4	-	-	-	_2)	-	539
Mopvac B 60/10 C		1.006-711.0	600	-	2400	10 / 10	-	-	-	_	-	541
Single-disc machines		1 201 242 2	122			10						L
BDS 43/150 C Classic		1.291-243.0	430	-	-	10	-	-	-	-	-	543
BDS 51/180 C Adv BDS 43/180 C Adv		1.291-227.0 1.291-226.0	510 430	-	-	10	-	-	-	-	-	545 545
BDS 33/180 C Adv		1.291-220.0	330		-	8	-	-	+-	-	+-	545
BDS 43/Duo C I Adv		1.291-241.0	430		-	10	-	-	-	-	-	545
BDS 43/Duo C Adv		1.291-223.0	430	_	-	10	-	-	-	-	-	545
BDP 43/450 C Adv		1.291-225.0	430	-	-	-	-	-	-	-	-	545
Staircase/escalator cleaners												
BR 47/35 Esc		1.310-109.0	470	-	-	35 / 35	-	-	-	-	-	546
BR 45/10 Esc		1.310-121.0	450	-	-	-	-	-	-	-	-	547
BD 17/5 C ■		1.737-107.0	170 / 200	-	-	-	-	-	-	-	-	549
Polishing machines												
BDP 50/2000 RS Bp Pack		1.002-039.0	510	-	1780	-	•	-	-	•	-	550
BDP 50/2000 RS Bp		1.002-041.0	510	-	1780	-	•	-	-	-	-	550
BDP 50/1500 C		1.291-141.0	510									551

WHICH IS THE RIGHT ONE?

The optimal scrubber drier for every surface

It's best to choose the right model of scrubber drier according to cost. You need to know the size of the area you wish to clean and how often you would like to clean it, and then you can make your selection from a cost point of view. The table below gives you an overview of reference values for each model.



INTERCLEAN

WHICH SCRUBBER DRIER IS THE RIGHT ONE?





Ride-on/Step-on scrubber drier

Cleaning area:

1,200 to 30,000 m²

Suitable for cleaning:

Large areas that are mostly clear of objects, e.g. storage spaces, production facilities, shopping centres, multi-storey car parks, exhibition centres, airports

Walk-behind scrubber drier

Cleaning area:

400 to 5,000 m²

Suitable for cleaning:

Medium-sized areas that are largely or mostly clear of objects, e.g. retail, sports halls, corridors and hallways, educational institutions, swimming pools, entrance halls







Properties:

- High area performance
- Long runtimes of up to 6 hours
- High operating comfort for effortless working

Accessories for special applications:

- Protective roof
- Flashing beacon
- Side brush
- Dose cleaning agent dosing unit





Properties:

- Good control of the result
- Extremely safe thanks to easy handling
- Runtimes of up to 5.5 hours

Accessories for special applications:

- "Box" Home Base kit
- Suction hose
- Spray suction
- Climate-neutral cleaning













Push/Compact scrubber drier

Cleaning area:

200 to 1,000 m²

Suitable for cleaning:

Small areas that are full of objects and furniture, e.g. bistros, boutiques, service stations, showrooms, spas, GP surgeries, kitchens, bakeries



Autonomous scrubber drier


Cleaning area:

From 500 m²

Suitable for cleaning:

Small and medium-sized areas that are largely or mostly clear of objects, e.g. supermarkets, corridors and hallways, shopping centres





Properties:

- High manoeuvrability
- Mobility (transport)
- Low weight
- Runtimes of up to 3 hours

Accessories for special applications:

- "Mop" Home Base kit
- DS 3 cleaning agent dosing station
- Filling hose
- Carpet cleaning





- Fully autonomous cleaning with docking station
- Targeted and flexible cleaning of different areas
- Intelligent automated route planning
- Cleaning right up to the edge

Accessories for special applications:

- Docking station
- Flashing beacon









BRUSH HEAD SELECTION

Brush head with disc engineering



Ideal for delicate floors


Low level of brush wear

Particularly quiet running



Particularly for unstructured floor coverings













Brush head with roller technology








- High contact pressure
- For heavily soiled surfaces
- Sweeping function
- Self-cleaning rollers
- Good corner cleaning

SQUEEGEE SELECTION

Straight squeegees






- Particularly for crevice-free floor coverings
- Easy to adjust
- Sufficient for numerous floor coverings

Curved/V-shaped squeegees





- Particularly for floor coverings with joints
- Optimum joint drying
- Improved coarse dirt pick-up (V-shape)

THE RIGHT ACCESSORY FOR EVERY APPLICATION


	Roller tech	nology R		Disc engi- neering D	D/O disc er	gineering	Vibrating technology	Detergent recommendatio
	The same of the sa	0	MARIA MI			٥		
	Roller brush Structured floor coverings	Roller pad Unstructured floor coverings	Microfibre roller	Disc brush Structured floor coverings	Disc pad Unstructured floor coverings	Microfibre pad	Pad	
Deep cleaning								
Supple floor coverings								
PVC, linoleum, rubber, PUR								RM 752 ¹⁾ /754
Natural stone floors (granite, marble, slate, etc.)								
Matt	2)							RM 752 ¹⁾ /754/7
Glossy								RM 754/751 ³⁾
Artificial stone floors (tiles, concrete, artificial stone, et	c.)							
Matt	1 2)							RM 752 ¹⁾ /754/7
Glossy	2)							RM 754/751 ³⁾
Fine stoneware tiles								RM 752
Synthetic resin coats								
PUR, epoxy resin, stone carpet Restoring shine	2)	•						RM 752/751 ³⁾
Coatings								RM 756
Maintenance cleaning								
Supple floor coverings								
PVC, linoleum, rubber, PUR	2)							RM 756
Natural stone floors (granite, marble, slate, etc.)								
Matt	2)						•	RM 756
Glossy	2)							RM 755
Artificial stone floors (tiles, concrete, artificial stone, et	c.)							
Matt	2)							RM 756
Glossy	2)							RM 755
Fine stoneware tiles								RM 753
Synthetic resin coats								
PUR, epoxy resin, stone carpet	2)							RM 69
Diamond cleaning system (natural stone floors, artificia	l stone, synthet	ic resin coats	5)					
Deep cleaning					♦♦			RM 756
Maintenance cleaning					♦			RM 755
Polishing								
Supple floor coverings								
PVC, linoleum, rubber, PUR		-						RM 748
Natural stone floors (granite, marble, slate, etc.)								
Glossy		_						RM 748/746
Artificial stone floors (tiles, concrete, artificial stone, et	c.)							
Glossy		_						RM 748
Synthetic resin coats								
PUR, epoxy resin, stone carpet		_						RM 748
Crystallising								
Floor coverings containing lime (marble, terrazzo, artificial stone, etc.)					♦			RM 749/775 ⁴⁾

¹⁾ Not for alkali-sensitive surfaces (linoleum, rubber, polished limestone, etc.).

 $^{^{\}mbox{\tiny 2)}}\mbox{For crevices}$ and heavily structured floor coverings.

 $^{^{\}mbox{\tiny 3)}}$ For mineral soiling on acid-resistant floor coverings (cement film, lime residue, etc.).

⁴⁾ Can only be used with pad discs.



Lithium-ion batteries are extremely powerful and fully maintenancefree. to recharge conventional gel batteries. The charge can be topped up at any and tank is full. Tank rinsing system: Once the cleaning work is complete, the time, which means that the machine is always ready for use.

2 Order on board: Home Base kit


Many scrubber driers are fitted with a Home Base kit, the storage system for all the equipment you need. The "Mop" kit comes with a mop clip, mop bottles, as well as cloths, scrapers, replacement rubbish bags, gloves, etc.

3 Auto-Fill and tank rinsing system

Auto-Fill: Simply connect the water hose to the machine using the hose They have a long service life and can be recharged in half the time it takes connector and fill the tank. The water supply stops automatically once the dirty water tank can be easily and conveniently cleaned using the integrated tank rinsing function. Simply connect the water hose to the machine using the hose connector and rinse the tank. The rinse water is drained via the drain hose. This cleans the tank without splashing and supports the HACCP concept.

4 Quiet, economical, easy-to-use and efficient

In ecolefficiency mode, energy consumption, cleaning agent consumption and even water consumption are reduced to varying degrees depending on support and bottle holder. The "Box" kit offers space to securely store three the model of the machine. This means that not only can the machine work for considerably longer, but it also saves money. The machine is also noticeably quieter. Different preconfigured cleaning programs can be selected using the EASY Operation rotary switch, which provides the operator with greater protection against incorrect operation.







5 Dose - the intelligent cleaning agent dosing unit

Dose technology enables precise dosing of the cleaning agent by means of a controller, as well as switching to a different cleaning agent or emptying the tank - even while the machine is in use. This saves on cleaning agent and working time. Since the cleaning agent and fresh water supply are sepa- each cleaning task or for the building. The operator only needs to insert rated, the growth of micro-organisms is prevented.

6 Colour coding

Simple and easy-to-understand operation thanks to the colour coding: used are self-explanatory and arranged clearly. After a short familiarisation parent and allows for complete documentation. period, the operator soon finds their way and can switch to a different machine at any time because the coding is the same.

The KIK system offers a higher level of protection against erroneous operation of the scrubber drier. Operators cannot change the machine's basic default settings. These have been previously preset by the supervisor for their key and use the EASY button to select the cleaning program. Only the correctly coded key can start the machine. This offers maximum security.

8 Fleet

Kärcher Fleet guarantees reliable fleet management. It provides an overview Control elements are yellow, while service elements are grey. The symbols of the fleet and the cleaning activities. This makes cleaning processes trans-

300-LITRE CLASS

A marvel of productivity: B 300 R I

KARCHER

With this combined scrubber drier/vacuum sweeper, you can kill two birds with one stone. It can overcome even the toughest challenges in a single operation, thereby practically halving the working time. It is also highly manoeuvrable and agile; it can withstand even tough applications easily and it excels on large areas with working widths of up to 1.65 metres (scrub vacuuming) or even 1.75 metres (sweeping). The powerful and robust combustion engines, powered either by liquid gas or diesel, combined with fresh and dirty water tank capacities of 300 litres each, ensure that you can work for very long periods without stopping.













1 Hydraulic high container emptying

The operator never comes into contact with dust or dirt thanks to the convenient hydraulic high container emptying up to a height of 1.55 metres. The waste container simply tips backwards, making it possible to dispose of the waste without touching it.

2 Side brushes and side scrubbing decks

You can use optional side brushes or side scrubbing decks to increase the working width on the right- or left-hand side of the machine by up to 1,755 millimetres. To ensure that neither the machine nor the area being cleaned is impacted by possible collisions, the side attachments kits are spring-mounted and simply moved under the machine in the event of heavy contact.

3 Robust design

Extremely sturdy machine components, such as the solid steel frame, make the B 300 R I perfect even for the toughest jobs. Robust industrial engines and the fully hydraulic traction drive also guarantee an extremely low susceptibility to errors.

4 Combination of scrub vacuuming and sweeping

Scrub vacuuming and sweep vacuuming in a single step saves a lot of time, particularly on large surfaces. It therefore also saves a lot on costs for staff, machines and consumables.

CONFIGURATION OPTIONS

- 1. Select the drive type: Diesel or liquid gas (LPG)
- 2. Attachment kits



Protective roof without glass



StVZO (approved for road use)



Right/left side scrubbing deck






Kärcher Fleet







Drive: Diesel/LPG



Working light

Brings light into the darkness in poor lighting conditions and significantly improves operational safety for the user and others in the vicinity.



Side scrubbing deck

The optional side scrubbing deck can be attached on either side, is spring-mounted for collision protection and extends the working width to up to 1,655 mm.



peration

Very simple and wear-resistant operation using a robust handle ensures relaxed handling of the machine.



Road approval

The B 300 R I is approved for use on public roads in accordance with the German Road Traffic Licensing Regulations (StVZO) and can therefore also be used in public areas without concern.

CONFIGURATION OF THE FULLY CUSTOMISED B 300 R I MACHINE

You have two basic models to choose from: The B 300 R I LPG with a low-emission, gas-powered combustion engine, which can also be used inside buildings, or the B 300 R I D, which is fitted with a robust, low-consumption diesel engine. Side brushes or side scrubbing decks can be used to extend the working width and other useful attachment kits are also available.





1 Manual tank rinsing

For manual tank rinsing, use the remaining fresh water to rinse out the dirty water tank and clean it with ease.

2 Squeegee

The very robust, spring-mounted squeegee ensures optimal vacuuming results in a wide variety of applications.

3 Liquid gas (LPG) engine

The low-emission, gas-powered combustion engine also allows cleaning of very large indoor areas, such as exhibition centres.





		B 300 R I D	B 300 R I LPG
Technical data			
Working width, brushes	mm	1045	1045
Working width, sweeping, with 2 side brushes	mm	1755	1755
Working width, wet scrubbing, with 2 side scrubbing decks	mm	1655	1655
Working width, vacuuming	mm	1440	1440
Theoretical area performance	m²/h	17550	17550
Fresh/dirty water tank	I	300 / 300	300 / 300
Max. speed	km/h	12	12
Max. cleaning speed	km/h	10	10
Brush contact pressure (max.)	g/cm² / kg	250 / 150	250 / 150
Brush speed	rpm	460	460
Waste container	I	180	180
Water flow (max.)	I/min	12	12
Voltage supply to machine	V	12	12
Motor rating	kW	25	39
Weight	kg	1750	1745
Dimensions (L × W × H) (including protective roof)	mm	2400 × 1540 × 2040	2400 × 1540 × 2040
Dimensions (L × W × H) (without attachments)	mm	2400 × 1540 × 1760	2400 × 1540 × 1760
Equipment			
Roller brush		•	•
Sweep vacuuming unit		•	•
Integrated sweeping mechanism		•	•
Flashing beacon		•	•
Side mirror		•	•
Working light		•	•
Squeegee		•	•
Automatic brush head and squeegee raising function		•	•
Electrically adjustable contact pressure		•	•
Special equipment			
Right/left side brush Right/left side scrubbing deck			
Protective roof without glass StVZO (approved for road use)			
Kärcher Fleet			
Order no.		1.480-235.2	1.480-235.2

■ Included in the scope of supply.

□ Available accessories.

250-LITRE CLASS

Powerhouse on three wheels

For cleaning hard surfaces in large premises, the B 250 R scrubber drier or combination machine is the right choice. The sturdy tubular steel frame meets even the toughest operational demands. Powerful batteries and large water tank ensure you can work for a long time without stopping. Single-button operation and coloured control elements make the machine especially easy to use.



















1 Very small turning circle

The short wheelbase and the minimal machine width ensure high manoeuvrability and large area coverage, meaning that even narrow areas can be cleaned efficiently.

- Very small turning circle.
- High manoeuvrability.
- Good area coverage.

2 All-in-one sweep vacuuming and scrubber drier - R I model

For tackling larger amounts of dirt, the B 250 R is also available with an upstream vacuum sweeping module. The round filter with 4 $\,\mathrm{m}^2$ filter area in combination with automatic filter cleaning allows for continuously dust-free working.

- Sweep vacuuming and scrub vacuuming in a single work step.
- Floating main sweeper roller.
- Includes two side brushes.

3 Extra large working width

In the roller version, a larger working width is also available as an option with 20 per cent higher area performance. The protruding brush head is protected against damage by a massive deflector.

- Extra-large working width of 1,200 mm.
- High area performance.
- Very robust thanks to the extremely strong deflector.

4 Safety: A key function

The KIK system offers much greater protection against erroneous operation. Operators cannot alter the machine's basic default settings. These have been preset beforehand by the supervisor for each cleaning task or for the building. All the operator needs to do is insert the key and the default program will start via EASY Operation. For even greater safety, all B 250 R machines feature simple, quick and intuitive menu navigation with clear designations, as well as innovative technical features such as suction power, brush speed, cleaning agent dosing, driving speed, approval for operators with a yellow key, switch-off delay for turbine and brushes, and the ability to chose the battery type. The B 250 R can only be started with a correctly coded key and is consequently protected against unauthorised operation.

CONFIGURATION OPTIONS







Roller heads (R) have advantages for cleaning textured floors and in deep crevices, while disc heads (D) offer the greatest benefits on smooth surfaces.



Working light

In poorly lit areas such as car parks or logistics areas, the working light improves vision and makes the machine easier to see.



Cleaning agent dosing unit

With the Dose cleaning agent dosing system, the cleaning agent is added to the fresh water when required. The dosing can be adjusted from 0 to 3 per cent.



Side scrubbing deck

Makes it possible to scrub right up to edges and contours. If it makes contact with an edge, it automatically moves inwards under the machine and out of the way.

CONFIGURE YOUR VERY OWN B 250 R MACHINE

Two different basic models are available: B 250 R, the compact scrubber drier, and B 250 R I, the vacuum sweeper/scrubber drier. There are three brush heads to choose from for each. You can also select the squeegee that is right for you, and many other configuration options.







1 Filling made easy

With the automatic filling system, a hose is simply connected with a conventional hose connector. The water flow stops automatically as soon as the tank is full. This makes the waiting time shorter and means that other tasks can be carried out while the tank is being filled. A conventional quick coupling with a non-return valve is recommended for the hose connection.

2 Operator protection

The operation of vehicles in warehouse areas is often subject to regulations designed to protect staff from falling objects. This is why the B 250 R is available with a protective roof. The particularly sturdy protective roof offers reliable protection without restricting the operator's movements and has been tested in accordance with the requirements for protective roofs on cleaning machines.

3 Spray vacuum nozzle for difficult-to-reach areas

For places the machine is unable to reach, there's a useful optional extra that can be carried on board: The spray vacuum nozzle, which enables corners and other areas the machine cannot access to be cleaned and vacuumed. Installation couldn't be easier - the suction hose is simply connected from the squeegee to the accessory as necessary.







		B 250 R I			B 250 R		
+ brush head		R 120	R 100	D 100	R 120	R 100	D 100
Technical data							
Working width, brushes	mm	1200	1000	1000	1200	1000	1000
Working width, vacuuming	mm	1420	1060	1060	1420	1060	1060
Theoretical area performance	m²/h	9600	8000	8000	9600	8000	8000
Fresh/dirty water tank	I	250 / 250	250 / 250	250 / 250	250 / 250	250 / 250	250 / 250
Brush contact pressure (max.)	g/cm² / kg	230 / 150	260 / 150	35 / 150	230 / 150	260 / 150	35 / 150
Brush speed	rpm	600-1200	600-1200	140	600-1200	600-1200	140
Waste container	I	60 + 24	60 + 20	60	24	20	-
Max. water flow	I/min	8	8	8	8	8	8
Voltage supply to machine	v	36	36	36	36	36	36
Rated input power, total machine	w	6900	6900	6500	5200	5200	4600
Weight (with battery)	kg	1470	1450	1450	1270	1250	1250
Dimensions without attachments (L × W × H) mm	2730×1260×1550	2730×1060×1550	2730×1060×1550	1900×1260×1550	1900×1060×1550	1900×1060×155
Equipment							
Roller brush		•	•	-		•	-
Disc brush		-	-		-	-	•
Integrated sweeping mechanism		•	•	-	•	•	-
Sweep vacuuming unit		-	•	•	-	-	-
Auto-Fill			•		•	•	•
Fact		•	•	-	•	•	-
ecolefficiency mode			•		•	•	•
Additional brake		•	•	•	•	•	•
Automatic brush head and squeegee raisi	ng function		•		•	•	•
Electrically adjustable contact pressure		•	•	•	•	•	•
KIK (Kärcher Intelligent Key)		•	•	•	•	•	•
Configuration options							
Battery, low-maintenance, 36 V / 630 Ah							
Battery charger (external)							
Squeegee, straight, oil-resistant polyuretha	ne lips (1160)						
Squeegee, curved, oil-resistant polyuretha	ne lips (1160)						
Squeegee, straight, oil-resistant polyuretha	ne lips (1400)						
Squeegee, curved, oil-resistant polyurethan	ne lips (1400)						
Special equipment							
Side brushes		□*	□*	□*			-
Dose cleaning agent dosing unit							
Spray suction							
Protective roof							
Flashing beacon							
Working light							
Side scrubbing deck		-	-	-	-		
Kärcher Fleet							
Order no.		1.480-231.2	1.480-231.2	1.480-231.2	1.480-231.2	1.480-231.2	1.480-231.2

^{*} Required accessories. $\ \blacksquare$ Included in the scope of supply. $\ \square$ Available accessories.

200-LITRE CLASS



Compact, convenient, clearly arranged

The B 200 R is the ride-on scrubber drier of choice for thorough and effective cleaning of indoor areas measuring between 2,500 and 7,000 m². Different cleaning modes can be conveniently selected via the large colour display. And the innovative, patented KIK key system provides the machine with effective protection against erroneous operation by unauthorised persons.




















1 Optional side brush

In conjunction with the R 75 or R 90 roller head, the optional side brush makes the B 200 R a real all-rounder and enables sweeping, scrubbing and vacuuming in a single operation. If required, the side brush can of course also be switched off.

2 Manual tank rinsing

For efficient cleaning of the dirty water tank, simply use the residual water

To further increase security, the machine features simple, fast and intuitive left in the fresh water tank for manual rinsing.

3 Brush heads to suit you

You can choose between roller or disc brush engineering and specify the right working width (75, 90 or 110 cm) for your needs.

4 Safety: A key function

With our KIK key system, erroneous operation of the machine can be avoided and unauthorised start-up completely prevented. The use of different keys (colour-coded yellow and grey) to which different access rights are assigned makes it possible, for example, for an authorised person to configure the default settings for the upcoming cleaning task and lock them. All the operator then needs to do is insert the key and the default program will start via EASY Operation.

menu navigation with clear descriptions, such as:

- Suction power.
- Brush speed.
- Cleaning agent dosing unit.
- Driving speed.
- Approval for operators with a yellow key.
- Switch-off delay for turbines and brushes.
- Battery type selection.

CONFIGURATION OPTIONS







The short and narrow design makes the machine very agile and easy to manoeuvre.



Cleaning agent dosing system

The Dose cleaning agent dosing system provides even and precise dosing of the cleaning agent volume.



Auto-Fill function

Time-saving and reliable automatic filling of the fresh water tank.



Additional lights

Standard daytime running light, brush head lighting and optional working lights increase safety and convenience for the user.

CONFIGURE YOUR VERY OWN B 200 R MACHINE

So that we can offer you the perfect machine for your needs, the B 200 R is available in different working widths, with disc brushes or roller brushes, and with the matching squeegee. You can choose precisely the features you need for the application you have in mind. Now available also with daytime running light fitted as standard.











With the automatic tank rinsing system, a fresh water hose is connected with a conventional hose connector. Splash water is completely avoided.

2 Extra large working width

The 110 cm working width and the associated disc brush head are ideal for cleaning particularly large areas. Impact protection is included as standard.

Our web-based fleet management system gives you an overview of all important parameters of each individual machine – in real time. This me

3 Home Base

Additional cleaning utensils can be carried on board the B 200 R thanks to the Kärcher Home Base kit, which enables bottles, bags, cloths and even a mop to be carried with ease.

4 Kärcher Fleet

Our web-based fleet management system gives you an overview of all important parameters of each individual machine – in real time. This means you're always up to date and you can react faster and more effectively to unforeseen events.





В	200	R
_	200	•

+ brush head		R 90	D 90	R 75	D 75	D 110
Technical data						
Working width, brushes	mm	900	900	750	750	1100
Working width, vacuuming	mm	1060	1060	940	940	1200
Theoretical area performance	m²/h	5400	5400	4500	4500	6600
Fresh / dirty water tank volume	1	200 / 200	200 / 200	200 / 200	200 / 200	200 / 200
Driving and cleaning speed	km/h	6	6	6	6	6
Max. brush contact pressure	g/cm² / kg	505 / 89	34 / 96	560 / 82	46 / 87	23 / 102
Brush speed	rpm	600-1300	180	600-1300	180	180
Waste container	I	9	-	7	-	-
Max. water flow	I/min	9	9	9	9	9
Voltage supply to machine	V	36	36	36	36	36
Voltage supply to battery charger	V / Hz	230 / 50-60	230 / 50-60	230 / 50-60	230 / 50-60	230 / 50-60
Rated input power, total machine (eco!efficiency mode)	w	2800 (1680)	2800 (1680)	2800 (1680)	2800 (1680)	2800 (1680)
Weight (with battery)	kg	475 (565)	475 (565)	475 (565)	475 (565)	475 (565)
Dimensions without attachments (L × W × H)	mm	1860 × 910 × 1410	1860 × 910 × 1410	1860 × 910 × 1410	1860 × 910 × 1410	1860 × 1120 × 1410
Equipment						
Roller brush		•	-	•	-	-
Disc brush		-	•	-	•	
Integrated sweeping mechanism		•	_	•	-	-
All-wheel drive		-	_	-	-	-
Auto-Fill						
Fact		•	-	•	-	-
eco!efficiency mode		•	•	•	•	•
Automatic brush head and squeegee raising functi	on	•	•	•	•	•
Electrically adjustable contact pressure		•	•	•	•	•
Long-term/short-term climbing ability	%	10 / 15	10 / 15	10 / 15	10 / 15	10 / 15
KIK (Kärcher Intelligent Key)		•	•	•	•	•
Large colour display		•	•	•	•	•
Built-in charger						
Configuration options						
Battery, maintenance-free, 36 V / 180 Ah / 36 V /	240 Ah					
Squeegee, straight, oil-resistant polyurethane lips	(940 mm)	-	-			-
Squeegee, curved, oil-resistant polyurethane lips	940 mm)	-	_			-
Squeegee, straight, oil-resistant polyurethane lips	(1060 mm)			-	-	-
Squeegee, curved, oil-resistant polyurethane lips	1060 mm)			-	-	-
Special equipment						
Side brushes			-		-	-
Dose cleaning agent dosing unit						
Side scrubbing deck						
Flashing beacon/working lights						
Automatic/manual rinsing system		0/0	0/0	0/0	0/0	0/0
Kärcher Fleet						
Impact protection						
Order no.		1.246-200.2	1.246-200.2	1.246-200.2	1.246-200.2	1.246-200.2

150-LITRE CLASS

Efficient and well thought-out in every detail

The B 150 R is the perfect ride-on scrubber drier for mediumsized areas of 2,500 to 6,000 m². It is highly compact and provides good all-round visibility for cleaning interiors. The machine offers ultimate convenience too: Automatic lowering of the brush head and squeegee, large colour display, automatic adjustment of contact pressure and configurable cleaning modes. The KIK key system and the colour-coded control elements make operation particularly easy.



















1 Safety: A key function

The KIK system offers much greater protection against erroneous operation. Operators cannot alter the machine's basic default settings. These have been preset beforehand by the supervisor for each cleaning task or for the building. All the operator needs to do is insert the key and the default program will start via EASY Operation.

For even greater safety, all B 150 R machines feature simple, quick and intuitive menu navigation with clear designations, as well as innovative technical features such as:

- Suction power
- Brush speed.
- Cleaning agent dosing unit.
- Driving speed.
- Approval for operators with a yellow key.
- Switch-off delay for turbines and brushes.
- Battery type selection.

The B 150 R can only be started with a correctly coded key and is consequently protected against unauthorised operation.

2 Home Base kit

Thanks to the Home Base kit, transporting cleaning utensils such as bottles, bags, cloths or mops is no problem at all.

3 Sweeping, scrubbing and vacuuming

The optional side brush in conjunction with a roller head makes the machine a real all-rounder.

- Sweeping, scrubbing and vacuuming in a single procedure.
- In combination with the R 75 or R 90 roller head.
- Side brush can be switched off.

4 Extremely manoeuvrable

The short and narrow design makes the machine highly manoeuvrable. It is ideal for angled interiors and provides a very good overview as well. This makes cleaning faster, safer and more efficient.

- Only 1,400 mm long and 800 mm wide (R/D 75).
- Very good overview.
- Safe and efficient.

CONFIGURATION OPTIONS





Side scrubbing deck

Makes it possible to scrub right up to edges and contours. If it makes contact with an edge, it automatically moves inwards under the machine and out of the way.




Auto-Fill

With the automatic filling system, the tank can be filled with an external hose with a conventional hose connector.



With the automatic tank rinsing system, a fresh water hose is connected with a conventional hose connector. 90 cm) are available depending on



Roller brushes or disc brushes in various working widths (from 75 to the application requirements. Roller or disc system.

Two different basic models are available: Standard and Advanced. The Advanced version is distinguished primarily by the all-wheel drive for better traction and extra features such as automatic filling, as well as four brush heads in two working widths as disc and roller. You can also choose other equipment such as different batteries or squeegees.











All-wheel drive. Increases safety, improves performance

With all-wheel drive, everything is better, easier, quicker and safer. The Advanced version of our B 150 R effortlessly masters inclines of up to 25 per cent and has no problem cleaning ramps up to a gradient of 15 per cent. An increased driving speed of 10 km/h generates up to 66 per cent more area performance per hour. Furthermore, the all-wheel drive also improves the directional stability on wet and slippery surfaces as well as the traction. Together with the steering angle sensor and the automatic improved.



Twin tyres. Reduce the contact pressure

Even delicate surfaces in airports, shopping centres and sports complexes need to be cleaned on a regular basis. With the twin tyre version of the B 150 R, this is possible even in places where the weight of other scrubber driers would exert too much contact pressure on the ground. Typical examples include marble and tiles, as well as floors which are only partly glued or laid over heating pipes, along with wooden floors. The twin tyres on the machine with rear-wheel drive and extra wide rear wheels reduce the braking system for driving curves, safety when working is now significantly contact pressure to just 0.3 N/mm² and therefore prevent damage to the surface as well as increasing comfort for the user.







		B 150 R Adv		B 150 R	
brush head		R 90 / D 90	R 75 / D 75	R 90 / D 90	R 75 / D 75
Technical data					
Vorking width, brushes	mm	900	750	900	750
Norking width, vacuuming	mm	1060	940	1060	940
heoretical area performance	m²/h	9000	7500	5400	4500
resh / dirty water tank volume	1	150 / 150	150 / 150	150 / 150	150 / 150
Priving and cleaning speed	km/h	10	10	6	6
Max. brush contact pressure	g/cm² kg	505 / 89 34 / 96	560 / 82 46 / 87	505 / 89 34 / 96	560 / 82 46 / 87
Brush speed	rpm	600-1300 / 180	600-1300 / 180	600-1300 / 180	600-1300 / 180
Vaste container	I	9 / -	7 / -	9 / -	7 / -
Max. water flow	I/min	9	9	9	9
Oltage supply to machine	V	36	36	36	36
oltage supply to battery charger	V / Hz	230 / 50-60	230 / 50-60	230 / 50-60	230 / 50-60
Rated input power, total machine eco!efficiency mode)	W	3240 (1950)	3240 (1950)	2800 (1680)	2800 (1680)
Veight (with battery)	kg	435-520	435-520	435-520	435-520
Dimensions without attachments (L × W × H) Equipment	mm	1790 × 910 × 1410	1790 × 800 × 1410	1790 × 910 × 1410	1790 × 800 × 1410
Roller brush		■/-	■ / -	■/-	■ / -
Disc brush		- / =	-/■	-/■	-/■
ntegrated sweeping mechanism		■/-	■/-	■/-	■/-
All-wheel drive				-	-
Auto-Fill					
ecolefficiency mode					
Automatic brush head and squeegee raising functi	on				
Electrically adjustable contact pressure					
ong-term/short-term climbing ability	%	15 / 18	15 / 18	10 / 15	10 / 15
(IK (Kärcher Intelligent Key)					
arge colour display					
Built-in charger					
-					
Configuration options	240 Ab				
Battery, maintenance-free, 36 V / 180 Ah / 36 V / 3					
iqueegee, straight, oil-resistant polyurethane lips		-		-	
queegee, curved, oil-resistant polyurethane lips (
queegee, straight, oil-resistant polyurethane lips			-		-
queegee, curved, oil-resistant polyurethane lips (1060 mm)		-		-
Special equipment					
ide brushes		□/-	□/-	□/-	□/-
iide scrubbing deck					
Pose cleaning agent dosing unit					
lashing beacon/working lights					
Automatic/manual rinsing system		0/0	0/0	0/0	0/0
Cärcher Fleet					

■ Included in the scope of supply.

□ Available accessories.

90-LITRE CLASS

The real dream cleaning machine



The B 90 R ride-on scrubber drier offers everything you could possible want: The equipment, working width, squeegee length, configuration and scrubbing technology can all be combined in a one-off machine, which is then built specifically to the customer's requirements.




















1 Machines to meet your needs

- Choose from a number of different configuration options, from the economical Classic to the fully equipped Dose model.
- A choice of three working widths and three different squeegees is available.

2 Different scrubbing technologies

- Disc cleaning models, especially for use on smooth surfaces.
- For textured floors or extremely stubborn dirt, roller brushes provide more benefits. They also scrub and sweep in a single step.

3 With or without Dose


- With the automatic Dose cleaning agent dosing unit, the cleaning agent is added to the fresh water as required, up to 3 per cent.
- The tank only contains fresh water. This saves time and prevents the risk of bacteria forming during longer periods of downtime.

4 Working width of your choice

- Three working widths are available, depending on requirements:
- This makes the cleaning machine even more economical even on large surfaces.
- Can be set to many different modes.
- Easy to use.

CONFIGURATION OPTIONS





Brush heads

Various brush head types are available: Roller heads (R) and disc heads (D) are especially useful on smooth surfaces.



For optimal suction, even around bends, squeegees are available in various widths: 850 mm for working widths up to 55 cm, 940 mm for a working width of 65 cm.



Classic or Advanced

operation. On the Advanced, you can select settings such as the brush automatic filling, tyres with particuspeed or turbine performance via the menu (Dose only in combination different brushes and pads. with Adv).



The Classic is characterised by simple
There is a wide variety of special equipment available too, such as larly good traction, flashing light or

CUSTOM CONFIGURATION

The B 90 R is available in various working widths, with disc brushes or roller brushes and the matching squeegee. This means that the machine is always optimally tailored to the customer's requests and requirements.

Configuration - optional	Description	
Equipment sets		
Classic Pack	■ Batteries (180 Ah, maintenance-free).	■ On-board battery charger for 180 Ah batteries.
Adv	Setting options via the display: Turbine speed (x2), language selection, max. cleaning speed presetting.	■ Settings: Brush delay time, test modes for service. ■ Fact (for roller heads).
Adv Pack	Setting options via the display: Language selection, max. cleaning speed presetting.	 ■ Settings: Brush delay time, test modes for service. ■ Fact (for roller heads). ■ Batteries (180 Ah, maintenance-free). ■ On-board battery charger for 180 Ah batteries.
Dose	Setting options via the display: Turbine speed (x2), language selection, max. cleaning speed presetting, Dose setting.	 ■ Settings: Brush delay time, test modes for service. ■ Fact (for roller heads). ■ Dose cleaning agent dosing unit. ■ FloorPro Deep Cleaner RM 69, 2.5 litres.
Dose Pack	Setting options via the display: Turbine speed (x2), language selection, max. cleaning speed presetting, Dose setting.	 Settings: Brush delay time, test modes for service. Fact (for roller heads). Dose cleaning agent dosing unit. FloorPro Deep Cleaner RM 69, 2.5 litres. Batteries (180 Ah, maintenance-free). On-board battery charger for 180 Ah batteries.







1 Where cleanliness counts

Cleanliness is of the utmost importance in the retail sector. The cleaning equipment must be easy to use, and the machine should be quiet and inconspicuous because cleaning often takes place during public opening hours.

2 Hygiene as a priority

There is no other area of application where hygiene requirements are as important as in the health service. A scrubber drier has to clean large surfaces, but it also has to be hygienic. The B 90 R has proven itself to be an essential aid in this area.

3 Thorough cleaning

The B 90 R efficiently removes dirt and dust, even on large surfaces. This ensures that production processes do not have to be interrupted and reduces the dust impact in warehouses to a minimum.

Configuration - optional	Description	
Brush heads		
550 mm, roller	■ Working width 550 mm. ■ 2 x roller brushes, 532 mm each. ■ Sweeping function.	 Runs close to the wall on the right-hand side. 2 x red roller brushes, incl. Quick brush replacement.
550 mm, disc	■ Working width 550 mm. ■ 2 x discs, 300 mm each.	 ■ Runs close to the wall on the right-hand side. ■ 2 x red disc brushes, incl. ■ Quick brush replacement.
650 mm, roller	■ Working width 650 mm. ■ 2 x roller brushes, 638 mm each. ■ Sweeping function.	 Runs close to the wall on the right-hand side. 2 x red roller brushes, incl. Quick brush replacement.
650 mm, disc	■ Working width 650 mm. ■ 2 x discs, 355 mm each.	 ■ Runs close to the wall on the right-hand side. ■ 2 x red disc brushes, incl. ■ Quick brush replacement.
750 mm, roller	■ Working width 750 mm. ■ 2 x roller brushes, 700 mm each. ■ Sweeping function.	 ■ Runs close to the wall on both sides. ■ 2 x red roller brushes, incl. ■ Quick brush replacement.
750 mm, disc	■ Working width 750 mm. ■ 2 x discs, 385 mm each.	 Runs close to the wall on both sides. 2 x red disc brushes, incl. Quick brush replacement.

Squeegee	
Straight, 850 mm	■ With support rollers and wear- and oil-resistant polyurethane lips, suitable for a max. working width of 650 mm.
Curved, 850 mm	■ With support rollers and wear- and oil-resistant polyurethane lips, suitable for a max. working width of 650 mm.
Straight, 940 mm	■ With support rollers and wear- and oil-resistant polyurethane lips, suitable for a max. working width of 750 mm.
Curved, 940 mm	■ With support rollers and wear- and oil-resistant polyurethane lips, suitable for a max. working width of 750 mm.
V-shaped, 900 mm	■ With support rollers and wear- and oil-resistant polyurethane lips, suitable for a max. working width of 650 mm.
V-shaped, 1000 mm	■ With support rollers and wear- and oil-resistant polyurethane lips, suitable for a max. working width of 750 mm.
Order no.	1.161-000.2

90-LITRE CLASS

For a clean environment

Highly compact ride-on scrubber drier for effortless use on medium and large areas. Available with disc brushes or roller brushes with sweeping mechanism.















1 Extremely easy to manoeuvre

- very agile and easy to manoeuver despite large water volumes.
- The 90° steering system allows you to turn on the spot.
- A low centre of gravity ensures excellent road adherence.

3 Long running time

- Thanks to its very short and narrow construction style, the machine is Large compartment for a large battery capacity. Maintenance-free gel batteries in the pack variants.
 - Two-level turbo power saves energy in the WHISPER setting.

2 Simple operation

- The basic functions are controlled with the EASY switch.
- Operating hours can be viewed on the display.
- Additionally, the roller brushes ensure that water and therefore also cleaning agent are saved.

4 Quick replacement

- If required, the brush head can be replaced quickly with no need for
- The rollers on the R head can be changed in next to no time.
- The brushes or pad drive boards on the D head are discarded using the

TECHNICAL DATA AND EQUIPMENT

		B 90 R Adv Dose Bp Pack B 90 R Adv Dose Bp	B 90 R Adv Bp Pack B 90 R Adv Bp	B 90 R Classic Bp Pack B 90 R Classic Bp
		 Adjustable brush contact pressure With cleaning agent dosing With two-level suction performance 	 Adjustable brush contact pressure With two-level suction performance With tank level display 	Very easy to useWith operating hour counterFor maintenance cleaning
Technical data				
Brush working width	mm	550-750	550-750	550-750
Working width, vacuuming	mm	850-940	850-940	850-940
Fresh/dirty water tank	I	90 / 90	90 / 90	90 / 90
Brush contact pressure	g/cm² / kg	20-315 / 28-35	20-315 / 28-35	20-315 / 28-35
Battery	V / Ah	24 / 170 24 / -	24 / 170 24 / -	24 / 170 24 / -
Battery charger	V / Hz	230 / 50-60 - / -	230 / 50-60 - / -	230 / 50-60 - / -
Weight	kg	275 152	273 150	272 149
Dimensions (L × W × H)	mm	1450 × 800 × 1200	1450 × 800 × 1200	1450 × 800 × 1200
Equipment				
Traction drive			•	•
Automatic water stop		•	•	•
Variable contact pressure			•	-
Dose		•	-	-
FACT		•	•	-
Battery and built-in charger included		■ -	■ -	■ -
Order no.		1.161-311.0 -310.0	1.161-309.0 -308.0	1.161-307.0 -306.0
Price				

■ Included in the scope of supply.

Brush head R 75 R 75 | R 65 | R 55 Brush head D 75 | D 65 | D 55

		Two contra-rotating roller brushesScrubbing and sweeping in one goHigh scrubbing performance	Two disc brushesMit integriertem SpritzschutzEinfacher Bürstenauswurf
Technical data			
Theoretical area performance	m²/h	4500 3900 3300	4500 3900 3300
Working widths	mm	750 650 550	750 650 550
Rotational speed	U/min	600-1300	180
Rated input power	w	2 × 600	2 × 600
Weight	kg	30 29 28	35 33 30
Contact pressure	g/cm²	200-315	20-35
Kehrvolumen	I	7 6 5	-
Dimensions (L × W × H)	für 750 mm	810 × 520 × 280	810 × 490 × 280
Dimensions (L × W × H)	für 650 mm	750 × 520 × 280	745 × 505 × 280
Dimensions (L × W × H)	für 550 mm	640 × 520 × 280	640 × 490 × 280

Equipment		
Roller brushes		-
Disc brushes	-	
Splash guard		
Sweeping function		-
Easy brush replacement		
Order no.	2.763-006.0 -004.0 -002.0	2.763 -005.0 -003.0 -001.0
Price		

Included in the scope of supply.

Accessories	Product		
Product name	name	Order no.	Description
DS 3 Cleaning Agent Dosing Station	2.641-811.0	Can be connected to the water tap; water and cleaning agent are simply filled into the fresh water tank. Can also be used with the ABS filling system. Not for Dose variants.	
Flashing beacon	2.641-718.0	Increases the safety of the working environment.	
Auto-Fill	2.641-748.0	Automatic filling system. Water supply automatically stops when the tanks is full. With safety overflow.	
Tyres, supergrip	6.435-403.0	Oil-resistant, with especially good traction.	

70-LITRE CLASS



Battery-operated, compact and exceptionally manoeuvrable

The affordable entry-level model into the world of ride-on scrubber driers is driven by a powerful 105 Ah battery and impresses with its slimline and compact construction style and incredible manoeuvrability. The machine, which is equipped with disc brush engineering, is easy to manoeuvre and transport, can even fit in lifts and offers many other clever and useful details.











1 Simple operation

- Self-explanatory symbols and clear control panel.
- Brief familiarisation phases.
- Simple, yellow colour-coded control elements make the machine easy to use.

3 Compact, slim design

- Extremely manoeuvrable machine.
- Clear view of surfaces to be cleaned.
- Easy to transport.

2 Disc brush engineering

- Rugged construction style with integrated disc brush head.
- High area performance thanks to large working width.
- Brush replacement via pedal ejection.

4 Optional accessories: pre-sweep mop

- Picks up dry dirt, thus supporting the cleaning process.
- Helps to prevent blockages in the suction channel.

TECHNICAL DATA AND EQUIPMENT

BD 50/70 R Classic Bp Pack BD 50/70 R Classic Fleet Bp Pack

BD 50/70 R Classic Bp BD 50/70 R Classic Fleet Bp

Compact slim design and extremely manoeuv	rable
---	-------

- Extremely easy and intuitive operation
- Powerful battery and charger included in the scope of
- Compact slim design and extremely manoeuvrable
- Extremely easy and intuitive operation

Disc brush engineering (c	one disc)
---------------------------	-----------

Technical data			
Brush working width	mm	510	510
Working width, vacuuming	mm	850	850
Theoretical area performance	m²/h	2805	2805
Fresh/dirty water tank	1	70 / 75	70 / 75
Brush contact pressure	g/cm² / kg	13 / 20	13 / 20
Brush speed	rpm	180	180
Battery	V / Ah	24 / 105	24 / -
Battery charger	V / Hz	95-253 / 50-60	-/-
Rated input power	W	1400	1400
Weight	kg	190.3 194	112.1 116
Dimensions (L × W × H)	mm	1310 × 590 × 1060	1310 × 590 × 1060

Drice		
Order no.	1.161-071.0 -073.0	1.161-070.0 -072.0
Variable contact pressure	-	-
Battery and charger	•	-
Automatic water stop	•	•
Disc brush		
Traction drive		•
Equipment		

■ Included in the scope of supply.

Accessories Product name	Product name	Order no.	Description
DS 3 Cleaning Agent Dosing Station	2.641-811.0	Can be connected to the water tap; water and cleaning agent are simply filled into the fresh water tank. Can also be used with the ABS filling system. Not for Dose variants.	
Attachment kit for the 60 cm pre-sweep mop	4.039-270.0	The pre-sweep mop can sweep up coarse dirt and it prevents coarse dirt from getting onto the brush head and into the squeegee.	
Bin liner holder attachment kit	4.039-269.0	Time-saving and useful accessory part: holder for convenient attachment of a bin liner or bin bag directly to the machine.	
Home Base Kit mop holder	4.039-271.0	Mop holder allows you to carry a mop on the machine. Easy attachment, convenient handling.	
Squeegee, straight	4.777-401.0	Straight, with support rollers. Suction lips of oil-resistant, transparent polyurethane.	
Squeegee, curved	4.777-411.0	Curved, with support rollers. Suction lips of oil-resistant, transparent polyurethane.	
Home Base Box Kit	4.035-406.0	Safe storage of cloths, cleaning agent bottles, etc., whilst cleaning.	
Flashing beacon	4.039-267.0	Non-glare flashing beacon increases safety when working in dark buildings.	
Battery	4.035-182.0	Machines with 36 V require three batteries.	
Battery charger	6.654-329.0	Standby battery charger for maintenance-free 24 V batteries of 70 to 105 Ah with order no. 6.654-093.0, 6.654-141.0 and 4.035-449.0.	
Disc brush	4.905-026.0	For general cleaning of all floors. Standard with D 51.	
Disc brush	4.905-029.0	For stubborn dirt and deep cleaning.Only for hard-wearing surfaces. Fits D 51.	
Disc brush	4.905-027.0	Made of natural fibres for cleaning and polishing. Fits D 51.	
Pad drive board STRONG	4.762-593.0	Required for use of melamine pads, but can also be used for normal pads. Pad drive board with many hooks for holding pads. Extra-strong hold of pad at pad drive board of D 51 cleaning head.	
Pad	6.369-078.0	For removing stubborn dirt and deep cleaning.	
Pad	6.369-079.0	For cleaning all types of floors.	
Diamond pad	6.371-260.0	For coarse cleaning/restoring. Removes small scratches, for a clean, silky matt surface. For surface preparation prior to using the yellow pad. Also suitable as a crystallisation pad for basic crystallisation.	
Diamond pad	6.371-261.0	For coarse cleaning/restoring. Removes fine scratches for a more homogeneous and shinier surface. For surface preparation prior to using the green diamond pad. Also suitable as a crystallisation pad for high-gloss crystallisation.	
Microfibre pad	6.371-271.0	Excellent cleaning power. Also effectively cleans fine stoneware tiles.	
Melamine pad	6.371-029.0	Melamine pad set for the effective cleaning of microporous surfaces.	

Clean from the start

Kärcher's step-on scrubber driers make cleaning the floor a pleasure. The ergonomic standing position and intuitive operation make for fatigue-free working.

















1 eco!efficiency

Program selector switch with eco!efficiency mode.

- The program selector switch lowers the brush head and the squeegee, and starts the suction turbine and the water supply.
- In eco!efficiency mode, power consumption is reduced considerably and the runtime consequently extended.

2 Three times the safety

The machine is secured against being started unintentionally in several different ways. For example, the machine can only be started if the driver is standing on the machine.

cleaning agent can be set from 0 to 3 per cent, and the cleaning agent can be replaced in no time at all.

4 Good overview

3 Dose

Thanks to the raised standing position, the operator is more easily seen by others in the vicinity and has a better overview of the cleaning progress. This increases safety and improves the cleaning results.

Dose is an automatic on-board dosing system, developed by Kärcher, which


saves on cleaning agent and is kind to the environment. With the help

of Dose, the cleaning agent can be accurately dosed into the fresh water

is always clean water in the fresh water tank. The concentration of the

from the on-board cleaning agent bottles as needed. This means that there

CONFIGURATION OPTIONS





Turbine protection

An easily accessible fine filter is built into the dirty water cover, which protects the turbine and prolongs its service life.



Home Base kit

Utensils can even be carried on such a compact machine as the B 95 RS thanks to Kärcher's Home Base kit, which enables bottles, bags, cloths and even a mop to be carried with ease.



Good manoeuvrability

Because the user is optimally integrated into the machine, in spite of its 95-litre tank volume the machine or roller technology (for textured is very short overall - and therefore extremely manoeuvrable. This ensures excellent surface coverage even in irregularly-shaped areas.



The B 95 RS is available with disc engineering (for smooth floors) floors and stubborn dirt). The roller heads are also fitted with a sweeping function and are available in two working widths.

CUSTOM CONFIGURATION

The B 95 RS is available in various working widths. The disc version offers 65 centimetres, while the roller machine is available in a working width of 65 centimetres or 75 centimetres. The additional equipment options such as Dose, the "Mop" Home Base kit or the battery exchange cartridge kit make the machine even more economical.







1 Battery charger on board

types. The various charging characteristics are tailored to the batteries and not wasted but can be put to good use. Simply connect a fresh water hose preserve battery life, thus ensuring a long battery runtime. The battery charger is very accessible from behind and is always on board. This means that the machine can be recharged anywhere and the battery charger will not be forgotten.

2 Efficient filling

The high-quality, integrated battery charger is suitable for different battery

Thanks to the standard Auto-Fill system, time spent filling the machine is and the system will stop automatically as soon as the tank is full.

3 High user-friendliness

The B 95 RS is equipped with a large graphical display that shows the key functions clearly and understandably. In combination with the KIK key system, this makes operating the machine considerably simpler and safer: The foreman or manager configures the settings and then the user cleans according to these settings.







В	95	RS	

+ brush head		R 75	R 65	D 65 R
Technical data				
Working width, brushes	mm	750	650	650
Working width, vacuuming	mm	940	940	940
Theoretical area performance	m²/h	4500	3900	3900
Fresh / dirty water tank volume	1	95 / 95	95 / 95	95 / 95
Max. brush contact pressure	g/cm² / kg	193 / 30	215 / 29	24 / 29
Max. speed	rpm	600-1300	600-1300	180
Max. water flow	I/min	3.5	3.5	3.5
Cleaning agent dosing unit*	%	0-3	0-3	0-3
Voltage supply to machine	V	24	24	24
Voltage supply to battery charger	V / Hz	230 / 50-60	230 / 50-60	230 / 50-60
Rated input power, total machine	w	1800	1800	1800
Rated input power, traction motor	w	600	600	600
Weight (without battery)	kg	207	206	210
Weight with battery	kg	331	330	334
Dimensions (L × W × H)	mm	1425 × 771 × 1270	1425 × 765 × 1270	1425 × 765 × 1270
Equipment				
Roller brush		•	•	-
Disc brush		-	-	•
KIK (Kärcher Intelligent Key)		•	•	•
Display		•	•	•
ecolefficiency mode		•	•	•
Battery operation		•	•	•
Fact		•	•	-
On-board battery charger		•	•	•
Automatic brush head raising function		•	•	•
Automatic squeegee raising function		•		•
Electrically adjustable contact pressure		•	•	•
Auto-Fill (fresh water filling)		•		•
Tank rinsing		•	•	•
Configuration options				
Battery 4 × 6 V / 180 Ah, maintenance-free				
Battery 4 × 6 V / 170 Ah, maintenance-free				
Battery 4 × 6 V / 180 Ah, low-maintenance				
Battery 2 × 12 V / 198 Ah, maintenance-free				
Special equipment				
Dose cleaning agent dosing unit				
"Mop" Home Base kit				
Kärcher Fleet				
Order no.		1.006-200.2	1.006-200.2	1.006-200.2


 * Option $\ lacktriangledown$ Included in the scope of supply. $\ \Box$ Available accessories.

Cleaning power in a compact package


Step-on scrubber drier in the 40 litre class. The BR 55/40 RS is a powerful, compact and easily manoeuvrable roller machine with a working with of 55 cm, which is ideal for small to medium-sized areas.







- Full view from 30 cm in front of the vehicle. For predictive cleaning.
- Compact dimensions allow narrow clearance widths as well as easy storage



- Coarse dirt is picked up by 2 contra-rotating rollers and collected in a waste
- Coarse dirt is picked up in advance by 2 rollers to maintain suction power.

BR 55/40 RS Bp Pack BR 55/40 RS Bp

- With two roller brushes
- Includes sweeping attachment
- Includes battery and charger (for 1.533-173.0)

Technical data		
Brush working width	mm	550
Working width, vacuuming	mm	716
Theoretical area performance	m²/h	3025 2350
Fresh/dirty water tank	I	40 / 40
Brush contact pressure	kg	315 / 24
Brush speed	rpm	1200
Voltage, battery	V / Ah	36 / 76 36 / -
Voltage, charger	V / Hz	230 / 50-60 - / -
Rated input power	W	max. 1480
Traction motor	W	157
Weight	kg	216 112
Dimensions (L × W × H)	mm	1118 × 691 × 1316

Equipment	
Traction drive	T .
Sweeping function	I
Battery and built-in charger included	I -
2-tank system	I
Squeegees, curved	1
Squeegee, straight	-
Order no.	1.533-173.0 -172.0
Price	
= 1lll	

■ Included in the scope of supply.

40-LITRE CLASS



Compact and powerful

Powerful, compact, agile: the BD 50/40 RS step-on scrubber drier is a disc machine with a working width of 51 cm, which is ideal for efficient and environmentally-friendly cleaning of small to medium-sized areas.







1 Simple operation

- eco!efficiency mode saves time, energy, water and cleaning agent.

2 Automatic filling option

- The machine is simply connected to the water supply. The water supply is automatically shut off when the machine is filled to capacity.
- This saves time, as the operator can do other jobs in the meantime.

BD 50/40 RS Bp Pack BD 50/40 RS Bp

- With disc brush
- Innovative squeegee rotation
- Includes battery and charger (for 1.533-171.0)

		and the state of the change (to 1.555 171.0)
Technical data		
Brush working width	mm	510
Working width, vacuuming	mm	691
Theoretical area performance	m²/h	2805
Fresh/dirty water tank	1	40 / 40
Brush contact pressure	g/cm² / kg	20 / 26
Brush speed	rpm	180
Voltage, battery	V / Ah	36 / 76 36 / -
Voltage, charger	V / Hz	230 / 50-60 - / -
Rated input power	w	max. 1080
Traction motor	w	157
Weight	kg	200 96
Dimensions (L × W × H)	mm	1118 × 691 × 1316

Equipment	
Traction drive	
Sweeping function	-
Battery and built-in charger included	■ -
2-tank system	
Squeegees, curved	1
Squeegee, straight	-
Order no.	1.533-171.0 -170.0
Price	

Our most powerful scrubber drier

The largest and most powerful machine in its class. Quick, clean and astonishingly manoeuvrable, it takes care of any and all cleaning tasks. Its robust design style makes the machine ideal for industrial use.



















1 Maximum convenience

All the settings - contact pressure, water volume, turbine power, cleaning agent dosing unit, roller speed, etc. - can be configured via the control panel with its large colour display. The machine also provides other information, such as the current water level or the remaining running time. The brush head and the squeegee are automatically lowered for cleaning and raised when the machine is reversed. The required cleaning program is selected quickly and easily via a program selection switch.

2 For extremely long working hours

The machine is designed to be used for long periods of time and demanding Being equipped with the optional D 110 brush head expands the working cleaning tasks. It has a 36 V power supply and, thanks to the high battery capacity of up to 240 Ah and the large tank volume, it can work for up to 5.5 hours without stopping. Furthermore, the Dose version carries two bottles of cleaning agent - more than enough reserves, even on long working days. After the cleaning, the integrated battery charger is set to the charging curve that best suits the battery via a selection on the display.

3 Asymmetrical line guidance

Particularly with larger machines, improved visibility reduces the risk of damaging other objects or the machine itself. It's for this reason that the B 120 W is fitted with asymmetrical line guidance, which guarantees an optimum view of the surface to be cleaned and of the brush head on the side next to the edge. This results in greater safety and enables faster

4 Large area performance

width from 90 cm (the standard for this class) to 110 cm. This increases the area performance by an enormous 22 per cent.

CONFIGURATION OPTIONS





Innovative tank rinsing system

Always on board: For fast, simple and thorough cleaning of the dirty water tank.



The non-slip main wheels are especially large to compensate better for uneven surfaces.



Always informed

The display provides information about any maintenance work due, e.g. inspection of the brushes or suction lips.




Reliably protected

The fresh-water pump and the suction turbine are effectively protected against dirt particles by a filter.

CUSTOM CONFIGURATION

The choice is yours: Kärcher customers can assemble their machine according to their needs. There are four different brush heads to choose from, as well as three working widths (75, 90 and 110 cm) and the choice of a disc version (D) or a roller version (R). The special "Home Base" option enables cleaning utensils to be carried on the machine, while the special spray vacuum option enables wet cleaning and suctioning of areas that would otherwise be difficult or impossible to reach with the machine.







1 Everything in view - and everything to hand

Thanks to the clearly laid-out control panel, the operator always has everything in view. The maximum speed and water volume can be set using compartment easily accessible. This enables the acid level of low-maintethe large graphical display. With the KIK system, various access rights to the yellow and optional white keys are for the operator. Cleaning- and safety-related parameters such as water volume, maximum cleaning speed, 170 and 240 Ah are available. brush speed, suction power and runtime per key can be pre-defined with the white key by the person responsible. This makes work convenient, efficient and safe.

2 Good accessibility

The two-part tank on the B 120 W is easy to open, making the battery nance batteries, for example, to be checked quickly and easily at any time. the settings are assigned. The grey key is for the foreman or manager, and Depending entirely on your individual requirements, both low-maintenance wet batteries and maintenance-free gel batteries with capacities between

3 Perfect suction

The specially offset squeegee can pivot over an especially large range, enabling it to pick up the water reliably even during turning manoeuvres. The suction lip is made of oil-resistant polyurethane with an exceptionally long service life. Thanks to the easily adjustable rollers, the squeegee can be perfectly matched to the contours of the surface being cleaned.







B 120 W

		B 120 W							
+ brush head		D 110	R 90	D 90	R 75	D 75			
Technical data									
Working width, brushes	nm	1100	900	900	750	750			
Working width, vacuuming n	nm	1160	1060 / 1160	1060 / 1160	940	940			
Theoretical area performance n	n²/h	6600	5400	5400	4500	4500			
Fresh / dirty water tank volume		120 / 120	120 / 120	120 / 120	120 / 120	120 / 120			
Max. brush contact pressure g	/cm² / kg	18 / 77	425 / 57.5	25 / 54.5	459 / 46.8	40 / 51			
Max. speed r	pm	180	600-1300	180	600-1300	180			
Max. water flow	/min	10	10	10	10	10			
Cleaning agent dosing unit* %	6	0-3	0-3	0-3	0-3	0-3			
Voltage supply to machine V	,	36	36	36	36	36			
	/ / Hz	220-240 / 50-60	220-240 / 50-60	220-240 / 50-60	220-240 / 50-60	220-240 / 50-60			
Rated input power, total machine V		2200	2200	2200	2200	2200			
	g	376 / 365 / 359 / 432 / 465	356 / 350 / 412 / 338 / 454	362 / 356 / 418 / 344 / 454	349 / 343 / 405 / 331 / 415	358 / 352 / 414 / 340 / 445			
	nm	1900 × 1100 × 1153	1653 × 910 × 1153	1782 × 977 × 1153	1653 × 810 × 1153	1722 × 809 × 115			
Equipment									
Roller brush		-	•	-	•	-			
Disc brush			-		-				
KIK (Kärcher Intelligent Key)									
EUnited cleaning certificate		-	-		-				
eco!efficiency mode									
Battery operation									
Fact		-		-		-			
Traction drive			•	•					
On-board battery charger			-						
Parking brake			•						
Automatic brush head raising function			_						
Automatic squeegee raising function		-	-	-	-				
Electrically adjustable contact pressure			-						
Auto-Fill (fresh water filling)		-	-	-	-	-			
Tank rinsing		•	•		•				
Configuration options									
Battery, maintenance-free (6 × 6 V), 170 Ah / 180 Al	h / 240 Ah								
Battery, low-maintenance 180 Ah (6 × 6 V or 1 ×									
Battery 1 × 36 V / 180 Ah, low-maintenance, con									
Squeegee, straight, 940 mm / 1060 mm / 1180 n		-/-/□	-/0/0	-/0/0		□/-/-			
Squeegee, curved, 940 mm / 1060 / 1160 mm		-/-/□	-/0/0	-/0/0	0/0/-	0/0/-			
Squeegee, offset, 1160 mm					-	-			
V-shaped squeegee, 1100 mm / 1200 mm		-/□	-/□	-/□	0/0	0/0			
Special equipment									
Dose cleaning agent dosing unit									
"Mop" Home Base kit/"Box" Home Base kit									
Spray suction									
Kärcher Fleet									
		_	_	_	_	_			

High area performance and optimal convenience in industrial use

The B 80 W scrubber drier presents itself at the highest level with numerous practical equipment features for cleaning large areas. This includes, for example, the KIK intelligent key system, automatic brush head and squeegee raising function, electric contact pressure adjustment, convenient adjustment of the water volume directly on the control panel, the effective parking brake, different battery sizes and working widths, as well as a large display. In short, the B 80 W is the convenient ideal solution for cleaning large industrial surfaces.

















3 Secure footing: The parking brake

even when operating on inclines.



1 Automatically good: Raising the squeegee and brush head

2 Smart keys: The KIK system (Kärcher Intelligent Key)

The B 80 W lowers and raises the brush head automatically when moving off and stopping. The squeegee is also automatically lowered when the machine starts moving and automatically raised when the machine reverses. This means that the machine can be easily manoeuvred without hesitation and damage to the floor or the machine can be avoided.

Two working widths: 65 or 75 centimetres

Two keys, two colours: Grey for supervisors or adjusters, yellow for operators. With the grey key, user access rights can be granted for the yellow keys and settings defined as standard (e.g. driving speed, brush speed, or cleaning agent dosing unit). This makes operating errors virtually impossible.

Choose either roller heads with two effective roller brushes and integrated sweeping function, or disc heads with two disc brushes. Both heads are available in two working widths (65 and 75 cm) for theoretical area performances of 3,900 to 4,500 m²/h. The S 65 oscillating scrubber head with 65 cm working width is perfect for stripping and is particularly suitable for covering edges and corners.


To prevent the machine from accidentally rolling away - for example when

switched off on an uneven surface, when emptying or filling or being trans-

ported in vehicles - the B 80 W is fitted with a parking brake as standard.

This means the machine offers significantly greater safety and convenience,

CONFIGURATION OPTIONS




Clear-cut colour coding

To make operation intuitive and easy to teach, as well as ensure a low rate of operating errors, the control elements yellow while maintenance elements are grey.



The right squeegee for every floor texture: The straight version is particularly suited to smooth and crevice-free floors, while the curved and V-shaped versions are ideal for structured floors and floors with lots of crevices.



Roller heads (R) are good for cleaning textured floors and deep dirt. Disc heads (D) are especially useful on smooth surfaces.



To make the machine more efficient, other special equipment such as the crevices, and for removing stubborn cleaning agent dosing unit (Dose) or the Home Base system ("Mop" or "Box") is available.

TECHNICAL DATA AND EQUIPMENT

	B 80 WBp					
Standard equipment	R 75	D 75	R 65	D 65	S 65	
Roller brush	•	-	•	-	-	
Disc brush	-	•	-	•	-	
KIK (Kärcher Intelligent Key)	•	•	•	•	•	
EUnited cleaning certificate	-	•	-	•	-	
ecolefficiency mode	•	•	•	•	•	
Battery operation	•	•	•	•	•	
Fact	•	-	•	-	-	
Traction drive	•	•	•	•	•	
On-board battery charger (100-240 V)	•	•	•	•	•	
Parking brake	•	•	•	•	•	
Automatic brush head raising function	•	•	•	•	•	
Automatic squeegee raising function	•	•	•	•	•	
Electrically adjustable contact pressure	•	•	•	•	•	
Auto-Fill (fresh water filling system)	•	•	•	•	•	
Tank rinsing	•	•	•	•	•	
Sweeping function	•	-	•	-	-	
Special equipment						
Dose cleaning agent dosing unit						
"Mop" Home Base kit						
"Box" Home Base kit						
Kärcher Fleet						
Order no.	1.259-010.2	1.259-010.2	1.259-010.2	1.259-010.2	1.259-010.2	

■ Included in the scope of supply.

□ Available accessories.




Simply always clean

The B 80 W comes with integrated tank rinsing as standard. The dirty water tank can be cleaned using a nozzle system once cleaning is complete by connecting a water hose using a quick coupling and opening the drain hose of the dirty water tank. In this way, the B 80 W supports the HACCP concept and easily ensures hygiene and health protection.



Simply scrub and sweep in a single step

The sweeping function is included with all roller heads (R 65 and R 75). This makes it possible to sweep, scrub and vacuum in a single operation with no need for laborious and time-consuming pre-sweeping.



Simply turn and click

The control knob makes adjusting the squeegee angle for different types of flooring quick and easy.

CUSTOM CONFIGURATION

		B 80 W Bp						
+ brush head		R 75	D 75	R 65	D 65	S 65		
Working width, brushes	mm	750	750	650	650	650		
Working width, vacuuming	mm	940	940	850	850	850		
Theoretical area performance	m²/h	4500	4500	3900	3900	3900		
Fresh / dirty water tank volume	1	80 / 80	80 / 80	80 / 80	80 / 80	80 / 80		
Max. brush contact pressure	g/cm²/kg	374 / 51.5	28 / 52.8	430 / 51.5	32 / 49.1	23 / 54.6		
Max. speed	rpm	600-1300	180	600-1300	180	2000		
Max. water flow	I/min	7	7	7	7	7		
Cleaning agent dosing unit*	%	0-3	0-3	0-3	0-3	0-3		
Voltage supply to machine	V	24	24	24	24	24		
Voltage supply to battery charger	V / Hz	100-240 / 50-60	100-240 / 50-60	100-240 / 50-60	100-240 / 50-60	100-240 / 50-60		
Rated input power, total machine	W	2200	2200	2200	2200	900		
Rated input power, traction motor W		350	350	350	350	350		
Weight (without battery)	kg	129	133	128	131	133		
Weight with 170 / 180 / 240 battery	kg	262 / 257 / 311	261 / 256 / 310	261 / 256 / 310	264 / 259 / 313	261 / 256 / 310		
Dimensions (L × W × H) mm		1550 × 809 × 1154	1617 × 810 × 1154	1550 × 748 × 1154	1577 × 746 × 1154	1497 × 700 × 1154		
Configuration options								
Battery, gel, maintenance-free (170, 180 or 2	40 Ah)							
Battery, gel, low-maintenance (180 Ah)								
Squeegee, straight, with support rollers, oil-resistant polyurethane lips (850 mm)								
Squeegee, curved, with support rollers, oil-resistant polyurethane lips (850 mm)								
Squeegee, straight, with support rollers, oil-resistant polyurethane lips (940 mm)								
Squeegee, curved, with support rollers, oil-resistant polyurethane lips (940 mm)								
V-shaped squeegee, 900 mm / 1000 mm								
Order no.		1.259-010.2	1.259-010.2	1.259-010.2	1.259-010.2	1.259-010.2		

* Option.

Available accessories.









1 Auto-Fill

The fresh water tank is automatically filled as follows: Connect a hose using a conventional quick coupling and open the tap. The supply stops automatically once the tank is full. The epitome of ease and convenience – and already included in the scope of supply.

2 Dosing made easy

With the Dose cleaning agent dosing system, the cleaning agent is added to the fresh water when required. The dosing can be adjusted from 0 to 3 per cent.

3 Everything on board

The practical Home Base system enables additional utensils to be carried on the machine. With the "Mop" Home Base kit, for example, you can carry a mop for surfaces that cannot be reached with the machine, while the "Box" Home Base kit can be used for bottles, cloths, scrapers, etc.

4 Customised runtime

24-volt batteries from 170 to 240 Ah for runtimes of up to 4 hours are available. The built-in charger is perfectly adapted for the different batteries. This protects the batteries and ensures a long service life.



For maximum flexibility on medium-sized surfaces

Efficient cleaning has a new name: B 60 W. The machine is not just economical, but also offers an impressively high area performance. For cleanliness made to measure, the equipment configuration, working width and squeegee shape can be selected according to the requirements profile. The KIK system guarantees especially simple and secure operation. The operator's setting options can be precisely defined in advance. In addition, ecolefficiency mode reduces the effective power of the motors only slightly, but extends the battery runtime by up to 30 per cent.


















1 Needs-based setting: The adjustable contact pressure

The contact pressure can be set manually in different lock-in positions. The benefits are obvious:

- No danger of "burn-in" on delicate floors.
- Reduced power consumption of the motor for a longer battery runtime.
- Less wear and tear of brushes and pads.

2 Smart keys: The KIK system (Kärcher Intelligent Key)

Two keys, two colours: Grey for supervisors or adjusters, yellow for operators. With the grey key, user access rights can be granted for the yellow keys and settings defined as standard (e.g. driving speed, brush speed, or cleaning agent dosing unit). This makes operating errors virtually impossible

3 Outstandingly efficient: eco!efficiency mode

ecolefficiency mode can extend the battery runtime by up to 30 per cent. In this mode, the power of the suction turbine and the brush motors is only minimally reduced. On smooth floors in particular, low turbine power is enough to achieve perfect results.

4 Cleanliness guaranteed: Tank rinsing

The B 60 W can also be equipped with integrated tank rinsing. The dirty water tank can be cleaned using a nozzle system once cleaning is complete by connecting a water hose using a quick coupling and opening the drain hose of the dirty water tank. In this way, the B 60 W supports the HACCP concept and easily ensures hygiene and health protection.

CONFIGURATION OPTIONS






Mains or battery operation

The B 60 W can be run off the mains or a battery. With the mains-powered model and the B 60 C version, the forward motion is provided by the brushes.



Additional special equipment

Kärcher Home Base kits make it easier to carry additional equipment on board.



rush heads


Various brush head types are available: Roller heads (R), disc heads (D) and an oscillating scrubber head (S).




Squeege

For optimal suction, even around bends, squeegees are available in various widths: 850 mm for working widths up to 55 cm, 900 and 940 mm for a working width of 65 cm. Two different basic models are available: The B 60 W Ep for mains operation and the B 60 W Bp with a battery. There are also four brush heads available in disc and roller versions and with various working widths. Furthermore, you can choose between two different battery types and five different squeegees. Attractive special equipment, such as the Kärcher tank rinsing system, the Dose automatic cleaning agent dosing unit or the practical Home Base kits, complete the package.

		B 60 W Ep / B 60 C Bp Class	sic
+ brush head		R 55	D 51
Working width, brushes	mm	550	510
Working width, vacuuming	mm	850	850
Theoretical area performance	m²/h	3300 / 2475	3060 / 2295
Fresh / dirty water tank volume	I	60	60
Max. brush contact pressure	g/cm²/kg	170 / 32.6	20 / 34.5
Max. speed	rpm	1100	180
Max. water flow	I/min	3.6	3.6
Cleaning agent dosing unit*	%	-	-
Voltage supply to machine	V/Hz / V/Ah	230/50 / 24/-	230/50 / 24/-
Rated input power, total machine	w	1450	1450
Rated input power, traction motor	w	-	-
Weight (without battery)	kg	88.5	88.5
Weight with 105 / 170 / 180 Ah	kg	- / 185 / 232 / 231	- / 185 / 232 / 231
Dimensions (L × W × H)	mm	1381 × 649 × 1147	1500 × 638 × 1147
Standard equipment			
Roller brush		•	-
Disc brush		-	•
KIK (Kärcher Intelligent Key)		-	-
EUnited cleaning certificate		-	-
eco!efficiency mode		-	-
Mains operation		■/-	■/-
Battery operation		- / I	-/■
Fact		-	-
Traction drive		-/-	-/-
On-board battery charger (100-240 V / 50-60 Hz)		-	-
Adjustable contact pressure		■/-	■/-
Configuration options			
Battery, gel, maintenance-free (105, 170 or 180 Ah)		-/□	-/□
Battery, gel, low-maintenance (180 Ah)		-/□	-/□
Squeegee, straight, with support rollers, oil-resistant polyurethane			
Squeegee, curved, with support rollers, oil-resistant polyurethane			
Squeegee, straight, with support rollers, oil-resistant polyurethane			
Squeegee, curved, with support rollers, oil-resistant polyurethane	lips (940 mm)		
V-shaped squeegee, 900 mm			
Special equipment			
Dose cleaning agent dosing unit		-	-
"Mop" Home Base kit			
"Box" Home Base kit			
Auto-Fill (fresh water filling system)			
Tank rinsing system			
Kärcher Fleet		-	-
Order no.		1.384-020.2	1.384-020.2











B 60 W Bp

B OO W BP				
R 65	D 65	R 55	D 55	S 65
650	650	550	550	650
940	940	850	850	850
3900	3900	3300	3300	3900
60	60	60	60	60
265 / 34.1	26 / 36.9	315 / 32.7	35 / 34.5	18 / 37.2
600-1300	180	600-1300	180	2000
3.6	3.6	3.6	3.6	3.6
0-3	0-3	0-3	0-3	0-3
24 / -	24 / -	24 / -	24 / -	24 / -
2100	2100	2100	2100	900
300	300	300	300	300
109	109	109	109	115
185 / 232 / 231	185 / 232 / 231	185 / 232 / 231	185 / 232 / 231	191 / 248 / 243
1520 × 748 × 1147	1520 × 746 × 1147	1490 × 672 × 1147	1480 × 666 × 1147	1436 × 700 × 1147
	_	•	_	-
_		_		_
	-		-	
-	-	-	-	_
	-			
•	-	•	-	-
-	-	-	-	-
•	•	-	•	•
•	_		_	_
•	•		•	•
•	•	•		•
•	•	•	•	•
1.384-020.2	1.384-020.2	1.384-020.2	1.384-020.2	1.384-020.2

Quiet and compact, with an innovative operating concept

Why should a machine just be easy to operate, when it could be even easier? As well as safer and more convenient in many ways? With Kärcher Intelligent Key and the advanced EASY Operation concept, the B 40 C/W family offers a level of safety and protection for the operator, machine and work area that's never been seen before.




















1 Safety: A key function

The KIK system offers much greater protection against erroneous operation. The fresh water tank is quickly filled as follows: Connect a hose using a con-Operators cannot alter the machine's basic default settings. These have been preset beforehand by the supervisor for each cleaning task or for the building. All the operator needs to do is insert the key and the default program will start via EASY Operation. The B 40 R can only be started with a correctly coded key and is consequently protected against unauthorised operation.

3 Auto-Fill

ventional quick coupling and open the tap. The supply stops automatically once the tank is full. It couldn't be easier or more convenient.

2 Quiet, strong and efficient

With the option to reduce power in ecolefficiency mode and thereby reduce The B 40 W with integrated traction drive is a particularly convenient the noise level by up to 4dB(A), the B 40 C/W is also a good choice for sensitive work areas. In maintenance cleaning, its efficiency impresses in every configuration, as does its remarkably long battery runtime.

4 With or without drive?

scrubber drier. It enables long transport distances, inclines and even long, uninterrupted periods of work to be tackled with little effort. For smaller areas, the B 40 C without traction drive is also an economical solution, since the operator is assisted by the forward motion of the cleaning brushes.

CONFIGURATION OPTIONS





O 51 orbital disc head

Ideal for restoring care films: Using a combination of rotating and oscillating motions, you can easily and thoroughly remove all coverings on hard and resilient flooring.



Choice of battery power or mains operation. Different battery types to choose from. Runtime of up to 3.5 hours.



There are several squeegees to choose from: Straight, curved or V-shaped, with suction lips made from rubber or wear-resistant, oil-resistant polyurethane.



Special equipment

Various optional extras are available: Tank rinsing system to support the HACCP concept, Dose cleaning agent dosing unit, automatic filling, mop holder, automatic rinsing system.

CUSTOM CONFIGURATION

Three different basic models are available: For mains operation (B 40 C Ep), with battery (B 40 C Bp) or with battery and powerful drive motor (B 40 W Bp). In addition, five working heads in two different working widths, and with disc or roller. You can choose between three different battery types and five different squeegees. And choose unique special equipment, such as the tank rinsing system.

chronish head V 24			B 40 W Bp				
Norwine width, brushes	+ brush head		R 55	D 51	R 45	D 43	0 51
Note	Nominal voltage	v	24	24	24	24	24
Troch ordical area performance m/h 3000 3000 2000 2580 3060 Fresh / firty water fank volume I 40 / 40 40 / 4	Working width, brushes	mm	550	510	450	430	510
Fresh / dirty water tank volume	Working width, vacuuming	mm	850	850	850	850	850
140 140	Theoretical area performance	m²/h	3300	3060	2700	2580	3060
Max. speed rpm 1200 180 1200 180 26 26 26 26 26 26 26 2	Fresh / dirty water tank volume	I	40 / 40	40 / 40	40 / 40	40 / 40	40 / 40
Name	Brush contact pressure	g/cm²/kg	140 / 24.9	30 / 25.7	160 / 21.8	50 / 23.9	15 /23-32
Cleaning agent dosing unit* % 0 0 0 0 0 0 0 0 0	Max. speed	rpm	1200	180	1200	180	30
Max. rated input power, traction motor W 1300 1400 1300 1400 1400 1300 1400 1300 1400 1400 1400 1400 1400 1400 1400 1400 1400 1400 1400 1400 1400 1400 1400	Max. water flow	I/min	2.6	2.6	2.6	2.6	2.6
Rated input power, traction motor W 130	Cleaning agent dosing unit*	%	0-3	0-3	0-3	0-3	0-3
Weight with bott battery) kg 88 93 87 91 100 Weight with 76 Ah, maintenance-free kg 164 199 163 176 176 Weight with 96 Ah, maintenance-free kg 160 163 167 176 Weight with 96 Ah, maintenance-free kg 150 159 149 153 162 Weight with 96 Ah, maintenance-free kg 150 155 149 153 162 Weight with 96 Ah, maintenance-free kg 150 155 149 153 162 Weight with 96 Ah, maintenance-free kg 150 159 149 153 162 Standard equipment mm 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1145 1249 × 575 × 1245	Max. rated input power, total machine	w	1300	1300	1300	1300	1300
Weight with 76 Ah, maintenance-free kg 130 135 129 133 142 Weight with 105 Ah, maintenance-free kg 164 169 163 167 176 Weight with 80 Ah, low-maintenance kg 150 155 149 153 162 Dimensions (L * W * H) mm 1249 * 620 * 1145 155 149 153 162 Standard equipment " Standard equipment <t< th=""><th>Rated input power, traction motor</th><th>w</th><th>130</th><th>130</th><th>130</th><th>130</th><th>130</th></t<>	Rated input power, traction motor	w	130	130	130	130	130
Meight with 105 Ah, maintenance-free	Weight (without battery)	kg	88	93	87	91	100
Meight with 80 Ah, low-maintenance kg 150 155 149 153 162 149 150 163 162 149 150 163 162 149 150 163	Weight with 76 Ah, maintenance-free	kg	130	135	129	133	142
Dimensions (L * W * H)	Weight with 105 Ah, maintenance-free	kg	164	169	163	167	176
Standard equipment	Weight with 80 Ah, low-maintenance	kg	150	155	149	153	162
	Dimensions (L × W × H)	mm	1249 × 620 × 1145	1249 × 575 × 1145	1249 × 520 × 1145	1249 × 537 × 1145	1249 × 575 × 1145
Disc brush	Standard equipment						
Pad drive board -	Roller brush		•	-	•	-	-
KIK (Kârcher Intelligent Key) EUnited cleaning certificate -	Disc brush		-	•	-	•	-
EUnited cleaning certificate			-	-	-	-	•
Mains operation	KIK (Kärcher Intelligent Key)		•	•	•	•	•
Battery operation I I I I I I I I I I I I I I I I I I I	EUnited cleaning certificate		-	•	-	•	-
Fact				-	-	-	-
Traction drive On-board battery charger Battery, gel, maintenance-free (70 Ah) Battery, gel, maintenance-free (105 Ah) Battery, wet, low-maintenance (80 Ah) Squeegee, straight, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, straight, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system	Battery operation		•	•	•	•	•
On-board battery charger			•	-	•	-	-
Configuration options Battery, gel, maintenance-free (70 Ah) Battery, gel, maintenance-free (105 Ah) Battery, wet, low-maintenance (80 Ah) Squeegee, straight, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, curved, with support rollers, oil-resistant polyurethane lips Squeegee, curved, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system	Traction drive		•	•	•	•	•
Battery, gel, maintenance-free (70 Ah) Battery, gel, maintenance-free (105 Ah) Battery, gel, maintenance (80 Ah) Battery, wet, low-maintenance (80 Ah) Squeegee, straight, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, straight, with support rollers, oil-resistant polyurethane lips Squeegee, curved, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system	On-board battery charger		•	•	•	•	•
Battery, gel, maintenance-free (105 Ah) Battery, wet, low-maintenance (80 Ah) Squeegee, straight, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, straight, with support rollers, oil-resistant polyurethane lips Squeegee, curved, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system							
Battery, wet, low-maintenance (80 Ah) Squeegee, straight, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, straight, with support rollers, oil-resistant polyurethane lips Squeegee, curved, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system							
Squeegee, straight, natural rubber suction lips Squeegee, curved, natural rubber suction lips Squeegee, straight, with support rollers, oil-resistant polyurethane lips Squeegee, curved, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit							
Squeegee, curved, natural rubber suction lips Squeegee, straight, with support rollers, oil-resistant polyurethane lips Squeegee, curved, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system							
Squeegee, straight, with support rollers, oil-resistant polyurethane lips Squeegee, curved, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit							
Squeegee, curved, with support rollers, oil-resistant polyurethane lips V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system							
V-shaped squeegee, 900 mm Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system							
Special equipment Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system Special equipment Special eq		ethane lips					
Dose cleaning agent dosing unit "Mop" Home Base kit "Box" Home Base kit Auto-Fill (fresh water filling system) Tank rinsing system	v-snaped squeegee, 900 mm						
"Mop" Home Base kit	Special equipment						
"Box" Home Base kit	Dose cleaning agent dosing unit						
Auto-Fill (fresh water filling system) Tank rinsing system Description:	"Mop" Home Base kit						
Tank rinsing system	"Box" Home Base kit						
	Auto-Fill (fresh water filling system)						
Order no. 1.533-210.2 1.533-210.2 1.533-210.2 1.533-210.2 1.533-210.2	Tank rinsing system						
	Order no.		1.533-210.2	1.533-210.2	1.533-210.2	1.533-210.2	1.533-210.2









3 40 C Bp / C	lassic
---------------	--------

D 40 C Dp / Clu	13310		
R 55	D 51	R 45	D 43
24	24	24	24
550	510	450	430
850	850	850	850
2475	2295	2025	1935
40 / 40	40 / 40	40 / 40	40 / 40
140	30	160	50
1200	180	1200	180
2.6	2.6	2.6	2.6
0-3 / -	0-3 / -	0-3 / -	0-3 / -
1100	1100	1100	1100
-	-	-	-
81	86	80	84
123	128	122	126
157	162	156	160
143	1240 × 575 × 1145	142	146
1249 × 620 × 1145	1249 × 575 × 1145	1249 × 520 × 1145	1249 × 537 × 1145
	_	•	
•			_
-	•	-	•
-	-	-	-
■ / -	■ / -	■ / -	■ / -
-	-	-	-
-	-	-	-
•	•	•	•
■ / -	-	■ / -	-
-	-	-	-
■ / -	■ / -	■ / -	■ / -
□/-	□/-	□/-	□/-
1.533-210.2	1.533-210.2	1.533-210.2	1.533-210.2

B 40 C Ep

R 55	D 51	R 45	D 43
230-240	230-240	230-240	230-240
550	510	450	430
850	850	850	850
2475	2295	2025	1935
40 / 40	40 / 40	40 / 40	40 / 40
170	20	190	26
1100	180	1100	180
2.6	2.6	2.6	2.6
-	-	-	-
1300	1300	1300	1300
-	-	-	-
77	79	76	77
-	-	-	-
_	_	_	-
_	_	-	-
1249 × 620 × 1145	1249 × 575 × 1145	1249 × 520 × 1145	1249 × 537 × 11
	-	•	-
-		-	
-	-	-	-
-	_	-	-
-	-	-	-
-	-	-	-
-	_	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

* Option ■ Included in the scope of supply. □ Available accessories.

FLOOR S SCRUBBI

80-TO 100-LITRE CLASS



Robust compactness. Impressive area performance

Brush head and squeegee are the most stressed components of a scrubber drier. That's why we make these components for our new 80 to 100 l class in the Classic segment from sturdy and durable aluminium. The simple operation, 81 cm working width for high area performance and the excellent price-performance ratio round off the clever overall concept.











1 Highly stressed parts such as squeegee and brush head are made from high-quality aluminium

- Robust machine concept for tough working conditions with low failure rates.
- Also developed for applications in harsh conditions.

3 Efficient and powerful 300 Watt traction motor

- Also helps to easily climb slopes, and saves the user energy.
- Driving speed can be adjusted via accessible potentiometer.

2 Brush contact pressure can be adjusted in 2 stages

- Can be manually increased from standard 40 to 68 kilogrammes if required.
- Lower contact pressure for lighter soiling or on sensitive floors.
- Higher contact pressure for stubborn dirt or for decoating.

4 Coloured, clearly visible operating elements

 Colour-coded operating elements simplify operation and shorten the training time

TECHNICAL DATA AND EQUIPMENT

BD 80/100 W Bp Classic BD 80/100 W Bp Classic Fleet

1.127-012.0 | -016.0

BD 80/100 W Bp Pack Classic BD 80/100 W Bp Pack Classic Fleet

1.127-018.0 | -020.0

		 Extremely robust and durable components for tough applications Very simple, intuitive operating concept With tried-and-tested disc brush engineering (double disc) 	 Extremely robust and durable components for tough applications Very simple, intuitive operating concept Powerful battery and off-board battery charger included in the scope of supply
Technical data			
Brush working width	mm	810	810
Working width, vacuuming	mm	1160	1060
Theoretical area performance	m²/h	4050	4050
Fresh/dirty water tank	I	100 / 100	100 / 100
Brush contact pressure	g/cm² / kg	21.3-36.2 / 40-68	21.3-36.2 / 40-68
Brush speed	rpm	180	180
Voltage, battery	V / Ah	24 / -	24 / 285
Voltage, charger		24 / -	24 / -
Rated input power	W	max. 1900	max. 1900
Weight	kg	120	320
Dimensions (L × W × H)	mm	1500 × 835 × 1065	1500 × 835 × 1065
Equipment			
Disc brush			•
Battery operation		•	•
Rattery and hattery		_	

■ Included in the scope of supply.

charger included

526

50-TO 60-LITRE CLASS



Compact and manoeuvrable for medium-sized areas

The compact dimensions of these scrubber driers provides amazing manoeuvrability as well as visibility of the surface to be cleaned. This makes them extremely easy to operate.











1 Affordable entry-level model

- Excellent price-performance ratio.
- Reduced to the most important functions.

3 Large tank volume with compact dimensions

- Extremely manoeuvrable.
- Offers a clear view of the cleaning surface.

2 Simple operation thanks to EASY-Operation Panel

- Self-explanatory symbols and clear control panel.
- Brief familiarisation phases.
- Simple, yellow colour-coded control elements make the machine easy to use.

4 Large working width

- Integrated disc brush head with 51-centimetre/20 inch brush.
- For efficient cleaning of medium-sized areas.

TECHNICAL DATA AND EQUIPMENT

		BD 50/50 C Bp Pack Classic	BD 50/50 C Bp Classic	BD 50/60 C Ep Classic
		Battery-poweredOne discExtremely easy to use	Battery-poweredOne discExtremely easy to use	Mains operationOne discExtremely easy to use
Technical data				
Brush working width	mm	510	510	510
Working width, vacuuming	mm	850	850	850
Theoretical area performance	m²/h	2040	2040	2040
Fresh/dirty water tank	I	50 / 50	50 / 50	60 / 60
Brush contact pressure	g/cm² / kg	27.3-28.5 / 20-23	27.3-28.5 / 20-23	27.3-28.5 / 20-23
Brush speed	rpm	180	180	180
Mains voltage	V	-	-	230
Frequency	Hz	-	-	50
Voltage, battery	V / Ah	24 / 105	24 / -	-/-
Voltage, charger	V / Hz	100-240 / 50-60	- / -	- / -
Rated input power	W	max. 1100	max. 1100	max. 1100
Weight	kg	130.6	63	52
Dimensions (L × W × H)	mm	1170 × 570 × 1025	1170 × 570 × 1025	1170 × 570 × 1025
Equipment				
Disc brush		•	•	•
Mains operation		-	-	
Battery operation			•	-

1.127-001.0

1.127-002.0

1.127-006.0

■ Included in the scope of supply.

Includes squeegee

Battery and battery charger included

Accessories Product name	Product name	Order no.	Description
Disc brush	4.905-027.0	Made of natural fibres for cleaning and polishing. Fits D 51.	
Disc brush	4.905-026.0	For general cleaning of all floors. Standard with D 51.	
Disc brush	4.905-029.0	For stubborn dirt and deep cleaning.Only for hard-wearing surfaces. Fits D 51.	
Pad drive board	4.762-534.0	For cleaning with pads. With quick-change coupling and Centerlock. Fits D 51.	
Pad	6.371-146.0	With natural hair, for polishing. Effectively removes scuff marks.	
Pad	6.369-468.0	Light grit, suitable for polishing floors.	
Pad	6.369-079.0	For cleaning all types of floors.	
Pad	6.369-078.0	For removing stubborn dirt and deep cleaning.	
Pad	6.369-077.0	For cleaning heavily soiled floors and for deep cleaning.	
V-squeegee	4.777-079.0	900 mm-long, V-shaped squeegee with suction lips made from wear- and oil-resistant polyurethane with a long lifetime and for all floors. With spirit level for precise adjustment.	
Squeegee, straight	4.777-401.0	Straight, with support rollers. Suction lips of oil-resistant, transparent polyurethane.	
Squeegee, curved	4.777-411.0	Curved, with support rollers. Suction lips of oil-resistant,transparent polyurethane.	
ABS drain hose ball valve	2.643-986.0	Drain hose for metered draining of dirty water from the tanks in our BD 50/50 C Classic and BD 50/60 C Classic scrubber driers. Water flow regulation using a ball valve.	
Battery kit	4.035-447.0	Maintenance-free battery set. Includes 2x 12 V batteries and connection cable.	
Battery kit	4.035-450.0	Low-maintenance battery set. Includes 2x 12 V batteries and connection cable.	
Battery kit	4.035-449.0	Maintenance-free battery set. Includes 2x 12 V batteries and connection cable.	
Battery charger	6.654-329.0	Standby battery charger for maintenance-free 24 V batteries of 70 to 105 Ah with order no. 6.654-093.0, 6.654-141.0 and 4.035-449.0.	
Charger	6.654-332.0	Standby battery charger for low-maintenance 24 V batteries with 80 Ah storage capacity (6.654-290.0 and 4.035-450.0).	
Battery charger	6.654-344.0	Standby battery charger for low-maintenance $24\ V$ batteries with 80 Ah storage capacity (6.654-290.0 and 4.035-450.0).	
Battery charger	6.654-179.0	For operation with 100-230 V. For low-maintenance 24 V batteries with 80 Ah (6.654-097.0).	

22-TO 35-LITRE CLASS

Small and manoeuvrable. Quick and thorough

Whether for quick interim cleaning or scheduled maintenance cleaning: these 25 to 35 liter class compact scrubber driers do a superior job. Thanks to their compact dimensions and manoeuvrability, these walk-behind machines with disc technology are ideal for smaller areas. They are very easy to operate.











1 Robust and durable control elements

- Designed for daily use.
- Robust, durable, reliable machine.

- 3 Small, compact machine
- Extremely manoeuvrable machine.
- Clear view of surfaces to be cleaned.

2 Simple operation thanks to EASY-Operation Panel

- Self-explanatory symbols and clear control panel.
- Brief familiarisation phases.
- Simple, yellow colour-coded control elements make the machine easy to use.

4 Large battery compartment for all standard battery types

- Easily accessible battery compartment for battery replacement.
- Also suitable for multiple shift operation.

TECHNICAL DATA AND EQUIPMENT

		BD 43/25 C Bp Pack	BD 43/25 C Bp	BD 43/35 C Ep
		Efficient single-disc engineeringBattery-poweredNon-corrosive frame	Efficient single-disc engineeringBattery-poweredNon-corrosive frame	Efficient single-disc engineerinMains operationNon-corrosive frame
Technical data				
Brush working width	mm	430	430	430
Working width, vacuuming	mm	850	850	850
Theoretical area performance	m²/h	1720	1720	1720
Fresh/dirty water tank	I	25 / 25	25 / 25	35 / 35
Brush contact pressure	g/cm² / kg	30-40 / 22.5-28	30-40 / 22.5-28	30-40 / 26.5-28.5
Brush speed	rpm	180	180	180
Mains voltage	V	-	-	230
Frequency	Hz	-	-	50
Voltage, battery	V / Ah	24 / 76	24	-
Voltage, charger	V / Hz	230 / 50-60	-	-
Rated input power	W	1100	1100	1400
Weight	kg	107	48	51
Dimensions (L × W × H)	mm	1135 × 520 × 1025	1135 × 520 × 1025	1135 × 520 × 1025
Equipment				
Roller brush		-	-	-
Disc brush				
2-tank system				
Mains operation		-	-	
Battery and battery charger included			-	-
Variable contact pressure		-	-	-
Tuescan autbasis				

1.515-400.0

1.515-401.0

1.515-403.0

Included	in	the	scone	οf	sunnly

Accessories Product name	Product name	Order no.	Description
Disc brush	4.905-023.0	Made of natural fibres for cleaning and polishing. Fits D 43.	
Disc brush	4.905-022.0	For general cleaning of all floors. Standard with D 43.	
Disc brush	4.905-025.0	For stubborn dirt and deep cleaning.Only for hard-wearing surfaces. Fits D 43.	
Pad drive board STRONG	4.762-592.0	Required for use of melamine pads, but can also be used for normal pads. Pad drive board with many hooks for holding pads. Extra-strong hold of pad at pad drive board of D 43 cleaning head.	
Pad drive board	4.762-533.0	For cleaning with pads. With quick-change coupling and Centerlock. Fits D 43.	
Pad	6.369-469.0	For perfect polishing results on sealed floors.	
Pad	6.371-081.0	For perfect polishing results on sealed floors.	
Pad	6.369-470.0	For cleaning all floors.	
Pad	6.369-472.0	For removing stubborn dirt and deep cleaning.	
Pad	6.369-473.0	For cleaning heavily soiled floors and for deep cleaning.	
Melamine pad	6.371-023.0	Melamine pad set for the effective cleaning of microporous surfaces.	
V-squeegee	4.777-079.0	900 mm-long, V-shaped squeegee with suction lips made from wear- and oil-resistant polyurethane with a long lifetime and for all floors. With spirit level for precise adjustment.	
Squeegee, straight	4.777-401.0	Straight, with support rollers. Suction lips of oil-resistant,transparent polyurethane.	
Squeegee, curved	4.777-411.0	Curved, with support rollers. Suction lips of oil-resistant,transparent polyurethane.	
Add-on kit drain hose ball valve	2.643-977.0	The drain hose enables convenient metered draining of dirty water from the tanks in our BD 43/25 C and BD 43/35 C scrubber driers. Water flow regulation using a ball valve.	
Battery kit	4.035-447.0	Maintenance-free battery set. Includes 2x 12 V batteries and connection cable.	
Battery kit	4.035-450.0	Low-maintenance battery set. Includes 2x 12 V batteries and connection cable.	
Battery charger	6.654-329.0	Standby battery charger for maintenance-free 24 V batteries of 70 to 105 Ah with order no. 6.654-093.0, 6.654-141.0 and 4.035-449.0.	
Charger	6.654-332.0	Standby battery charger for low-maintenance 24 V batteries with 80 Ah storage capacity (6.654-290.0 and 4.035-450.0).	

22-TO 35-LITRE CLASS

Maximum agility on smaller surfaces

Our BR 45/22 C scrubber drier is ideal for cleaning smaller surfaces. The working width of 450 mm is the perfect size, the longlife lithium-ion batteries allow working for long periods without interruption, and the machine's rotatable roller head follows the direction that the operator drives in. Above all, it is very light, compact and extremely agile.











1 Brush head rotatable by +/- 200° with KART technology

- Enables extreme manoeuvrability of the machine, even in areas with a Makes it possible to drive away from walls at a 90° angle. lot of furniture and when negotiating curves.
- $\hfill \blacksquare$ The brush is always transverse to the direction of travel. The squeegee reliably absorbs the water in every corner.
- Cleaning and vacuuming in reverse is easily possible.

3 Compact machine design

- The lack of machine protrusions make handling easier.

2 Includes high-performance lithium-ion battery

- Completely maintenance-free and with a service life that is up to three Efficiently sweep, scrub and vacuum in a single procedure. times longer than conventional batteries.
- Interim and partial charging possible as required.
- Extremely fast charging times (full charge in three hours, half charge in

4 Includes sweeping function

- Vacuums small stones, splinter of wood and other small parts.
- Promotes optimal operation of the squeegee.

TECHNICAL DATA AND EQUIPMENT

BR 45/22 C Bp Pack

- Lithium-ion battery
- Built-in charger included in delivery
- Height-adjustable handlebar

Working width, vacuuming mm 500 Theoretical area performance m²/h 1800 Fresh/dirty water tank I 22 / 22 Brush contact pressure g/cm² 100-150 Brush speed rpm 750-1050 Voltage, battery V / Ah 25.2 / 42 Voltage, charger V / Hz 220-240 / 50-60	Technical data		
Theoretical area performance m²/h 1800 Fresh/dirty water tank I 22 / 22 Brush contact pressure g/cm² 100-150 Brush speed rpm 750-1050 Voltage, battery V / Ah 25.2 / 42 Voltage, charger V / Hz 220-240 / 50-60	Brush working width	mm	450
Fresh/dirty water tank I 22 / 22 Brush contact pressure g/cm² 100-150 Brush speed rpm 750-1050 Voltage, battery V / Ah 25.2 / 42 Voltage, charger V / Hz 220-240 / 50-60	Working width, vacuuming	mm	500
Brush contact pressure g/cm² 100-150 Brush speed rpm 750-1050 Voltage, battery V / Ah 25.2 / 42 Voltage, charger V / Hz 220-240 / 50-60	Theoretical area performance	m²/h	1800
Brush speed rpm 750-1050 Voltage, battery V / Ah 25.2 / 42 Voltage, charger V / Hz 220-240 / 50-60	Fresh/dirty water tank	I	22 / 22
Voltage, battery V / Ah 25.2 / 42 Voltage, charger V / Hz 220-240 / 50-60	Brush contact pressure	g/cm²	100-150
Voltage, charger V / Hz 220-240 / 50-60	Brush speed	rpm	750-1050
	Voltage, battery	V / Ah	25.2 / 42
Rated input power W up to 550	Voltage, charger	V / Hz	220-240 / 50-60
	Rated input power	W	up to 550
Weight kg 51.1	Weight	kg	51.1
Dimensions (L × W × H) mm 970 × 530 × 1115	Dimensions (L × W × H)	mm	970 × 530 × 1115

Equipment	
Roller brush	
2-tank system	1
Battery and built-in charger included	
Squeegee, straight	1
Variable contact pressure	
Easy to transport over stairs	
Order no.	1.783-460.0
Price	

Accessories	Product		
Product name	name	Order no.	Description
Roller brush	4.762-392.0	For all floors. Fits R 45.	
Roller brush	4.762-406.0	For cleaning heavily structured floors as well as in deep joints and crevices. Fits R 45.	
Roller brush	4.762-407.0	For stubborn dirt and deep cleaning; only for hard-wearing surfaces. Fits R 45.	
Roller brush	4.762-408.0	For stubborn dirt and deep cleaning; only for insensitive floors. Fits R 45.	
Microfibre roller	4.037-093.0	Combines the excellent cleaning properties of microfibres and the advantages of roller technology. No pad roller shaft required.	
Pad roller shaft	4.762-413.0	For mounting roller pads or microfibre rollers. Fits R 45.	
Stripping roller	4.114-011.0	Stripping roller, complete, 45 cm, fits R 45.	
Roller pad on sleeve	6.367-105.0	For polishing and cleaning non-textured floors. In conjunction with pad roller shaft 4.762-413.0	
Roller pad on sleeve	6.367-107.0	For cleaning non-textured floors. In conjunction with pad roller shaft 4.762-413.0	
Roller pad on sleeve	6.367-106.0	For removing stubborn dirt and deep cleaning of non-textured floors. In conjunction with pad roller shaft $4.762-413.0$	
Suction lips	4.037-094.0	Grooved, oil-resistant, polyurethane.	



Independent and manoeuvrable ideal for small surfaces

Very compact scrubber drier with disc engineering and extremely long-lasting, extra-light lithium-ion battery. The perfect solution for smaller areas.





1 Reliable disc technology

- Excellent cleaning power on smooth floor coverings.
- Suitable for use with brushes and pads.

2 High-performance lithium-ion battery

- Completely maintenance-free despite a service life that is three times longer than conventional batteries.
- Quick charging (full in three hours, half full in one hour).

BD 38/12 C Bp Pack

- Lithium-ion battery With disc brush (for smooth surfaces)
- eco!efficiency mode

Technical data		
Brush working width	mm	380
Working width, vacuuming	mm	480
Theoretical area performance	m²/h	1520
Fresh/dirty water tank	I	12 / 12
Brush contact pressure	g/cm² / kg	25-30 / 16-20
Brush speed	rpm	180
Voltage, battery	V / Ah	25.2 / 21
Voltage, charger	V / Hz	220-240 / 50-60
Rated input power	W	500
Weight	kg	36
Dimensions (L × W × H)	mm	940 × 500 × 1100

Equipment	
Roller brush	-
Disc brush	
2-tank system	1
Mains operation	-
Battery and battery charger included	
Variable contact pressure	-
Transport wheels	
Order no.	1.783-430.0
Price	

■ Included in the scope of supply.



Compact machine that masters corners

Manoeuvrable scrubber drier with extra-light, quick-charging and long-lasting high-performance battery. The rotatable roller brush head provides a new ride experience and the utmost efficiency.





- 1 Brush head rotatable by +/- 200° with KART technology, allowing the machine to be steered. For easy negotiation of curves
- Extremely manoeuvrable and effective ideal for areas with a lot of furniture.
- The brush is always transverse to the direction of travel. The squeegee reliably absorbs the water in every corner.
- 2 Includes high-performance lithium-ion battery
- Completely maintenance-free despite a service life that is three times longer than conventional batteries.
- Interim or partial charging is also possible where necessary.

BR 35/12 C Bp Pack

- eco!efficiency mode
- Includes sweeping functionHeight-adjustable handlebar

Technical data		
Brush working width	mm	350
Working width, vacuuming	mm	450
Theoretical area performance	m²/h	1400
Fresh/dirty water tank	I	12 / 12
Brush contact pressure	g/cm² / kg	80-150 / 6-12
Brush speed	rpm	700-1500
Voltage, battery	V / Ah	25.2 / 21
Voltage, charger	V / Hz	220-240 / 50-60
Rated input power	W	500
Weight	kg	35
Dimensions (L × W × H)	mm	930 × 420 × 1100

Equipment	
Roller brush	
Disc brush	-
2-tank system	
Mains operation	-
Battery and battery charger included	
Variable contact pressure	1
Transport wheels	1
Order no.	1.783-450.0
Price	



More functions - more options

The BR 40/10 C Adv is a cost-effective all-rounder. It scrubs floors like a single disc machine, picks up water like a wet suction device and polishes like a high-speed machine.





1 Powerful and fast

- Two high-speed rotating roller brushes with high contact pressure.
- Two suction lip strips soak up the water either forwards or backwards.

2 Low clearance height

- Reaches under furniture effortlessly.
- The push handle can be folded down in both directions.

		BR 40/10 C I Adv	BR 40/10 C Adv
		High scrubbing performanceWith adjustable contact pressureWith green roller brushes and oil-resistant suction bar	High scrubbing performanceWith adjustable contact pressureIncludes roller brushes
Technical data			
Brush working width	mm	400	400
Working width, vacuuming	mm	400	400
Theoretical area performance	m²/h	400	400
Fresh/dirty water tank	I	10 / 10	10 / 10
Brush contact pressure	g/cm² / kg	100-200 / 20-30	100-200 / 20-30
Brush speed	rpm	1100	1100
Mains voltage	V	220-240	220-240
Frequency	Hz	50	50
Rated input power	W	2300	2300
Weight	kg	30	30
Dimensions (L × W × H)	mm	520 × 470 × 380	520 × 470 × 380
Equipment			
Roller brush			
Disc brush		-	-
2-tank system			
Mains operation			
Battery and battery charger included		-	-
Variable contact pressure			•
Transport wheels			
Order no.		1.783-316.0	1.783-311.0
Price			



Deep cleaning of smaller areas, every day

Whether in a restaurant, shop, hotel, kitchen or sanitary facilities: the BR 30/4 C scrubs and dries all small hard surfaces gently and effectively. This machine cleans equally well both backwards and forwards and is as quick and simple to operate as an upright vacuum cleaner.





1 High-speed roller brush

- Ten times higher contact pressure than manual cleaning.
- The roller brush also cleans structured surfaces and crevices.

2 Dries immediately

- The soft suction lips remove moisture backwards and forwards.
- For intensive cleaning, the suction can be switched off via the foot pedal.

		BR 30/4 C Bp Pack	BR 30/4 C Adv	BR 30/4 C BR 30/4 C + MF
		ВК 30/4 C Вр Раск	BR 30/4 C Auv	BR 30/4 C + MF
		Suction can be switched offOperates forwards and backwards	 Suction can be switched off Operates forwards and backwards 	Suction can be switched off
		Battery operation	Manual vacuuming, microfibre roller	
Technical data				
Brush working width	mm	300	300	300
Working width, vacuuming	mm	300	300	300
Theoretical area performance	m²/h	200	200	200
Fresh/dirty water tank	I	4 / 4	4 / 4	4 / 4
Brush contact pressure	g/cm²	100	100	100
Brush speed	rpm	1270	1450	1450
Mains voltage	V	-	220-240	220-240
Frequency	Hz	50-60	50-60	50-60
Rated input power	W	550	820	820
Weight	kg	17.4	12.4	11.5
Dimensions (L × W × H)	mm	390 × 335 × 1180	390 × 335 × 1180	390 × 335 × 1180
Equipment				
Disc brush		-	-	-
2-tank system		•	•	•
Mains operation		-	•	•
Manual vacuuming		-	•	-
Microfibre roller		-	•	- ■
Transport wheels		•		•
Battery operation		=	-	-
Order no.		1.783-225.0	1.783-213.0	1.783-220.0 -223.0

■ Included in the scope of supply.



Clean small surfaces with ease, not by hand

Until now, small areas and especially areas with a lot of furniture could generally only be thoroughly cleaned by hand. Thanks to the BD 30/4 C Bp Pack, this is no longer the case. Powered by a long-lasting lithium-ion battery, the manoeuvrable machine cleans hard and elastic floors, reliably vacuums the dirt water and leaves behind a clean, dry floor that is ready to walk on.









1 Powerful lithium-ion battery, including

- Completely maintenance-free, with a battery life several times longer Reliable suction of water, even in tight curves. than that of conventional batteries.
- Trouble-free partial or intermediate charging possible.

3 Curved squeegee

- Backward suction also possible, if needed.
- Including soft, oil-resistant polyurethane squeegee.

2 Minimal dimensions

- Low space requirements for storage.
- Can also be transported in passenger vehicles.

4 Consistently high-quality components and materials

- Lock and chassis made of high-quality aluminium.
- Robust, durable quality.

TECHNICAL DATA AND EQUIPMENT

BD 30/4 C Bp Pack

- Lithium-ion battery
- With disc brush

Technical data		
Brush working width	mm	280
Working width, vacuuming	mm	325
Theoretical area performance	m²/h	900
Fresh/dirty water tank	1	4 / 4
Brush contact pressure	g/cm² / kg	20 / 10
Brush speed	rpm	150
Input voltage/frequency	V / Hz	100-240 / 50-60
Rated input power	W	max. 240
Weight	kg	21.1
Dimensions (L × W × H)	mm	555 × 375 × 1050

Equipment	
Disc brush	
2-tank system	1
Mains operation	-
Manual vacuuming	-
Microfibre roller	-
Transport wheels	1
Battery operation	
Order no.	1.783-230.0
Price	

Accessories	Product		
Product name	name	Order no.	Description
Disc brush	6.670-128.0	For cleaning and polishing sensitive floors.	
Disc brush	6.670-127.0	Suitable for all common cleaning tasks, even on sensitive floors.	
Pad drive board	6.670-129.0	Pad drive board for pad intake.	
Pad	6.371-153.0	For cleaning all floors. Fits D 55.	
Pad	6.371-154.0	For removing stubborn dirt and deep cleaning. Fits D 55.	
Melamine pad	6.371-019.0	Melamine pad set for the effective cleaning of microporous surfaces.	
Suction lips	6.670-234.0	Suction lip set specifically developed for our handy scrubber drier BD 30/4 C, consisting of front and rear suction lip. Made from durable and oil-resistant polyurethane.	
Set suction lips Linatex	6.670-235.0	Suction lip set specifically developed for our handy scrubber drier BD 30/4 C, consisting of front and rear suction lip. Made from natural rubber.	
Lithium-ion battery	6.670-126.0	Lithium-ion exchangeable battery (36.5 V / 5.2 Ah) – can be charged in the quick charger with plug-in card intended for this purpose.	
Battery charger	6.670-130.0	Universal quick charger with a plug-in card. Please order power cord separately.	

Mop five times faster

The B 60/10 C represents a new kind of floor cleaning. The machine cleans and vacuums all smooth floor coverings. Without any electricity. Hygienic, efficient, safe and user-friendly.











1 Operates without electricity

- No annoying cord.
- Unlimited run time.
- Whisper quiet.

3 Simple and intuitive operation

- Easy to use.
- No training necessary.

2 Dirty water is vacuumed

- Leaves floors dry after cleaning.
- Lower risk of slipping.
- No detergent residue and therefore less subsequent soiling.

4 60-cm-wide pad with squeegee blade

- Highly efficient in open areas.
- The area performance is comparable to a 43 cm scrubber drier: works five times faster than with a mop and bucket.
- For smooth surfaces.

TECHNICAL DATA AND EQUIPMENT

B 60/10 C

- Operates without electricityVery efficientExtremely quiet

Technical data		
Brush working width	mm	640
Working width, vacuuming	mm	610
Theoretical area performance	m²/h	2400
Fresh/dirty water tank	I	10 / 10
Contact pressure, cleaning deck	kg	2.2
Noise level	dB(A)	52
Rated input power		-
Weight	kg	21
Dimensions, operating position (L × W × H)	mm	1055 × 485 × 1040
(L * VV * FI)		
Dimensions, parking position (L × W × H)	mm	820 × 550 × 710

-
-
I
-
-
-
1.006-711.0


Accessories Product name	Product name	Order no.	Description
Pad	8.637-592.0	38 m long, $10 cm$ wide. Perforated strips to be torn off. The coarse dirt fleece is applied to the front of the pad and collects hair and lint.	
Pad	8.637-944.0	White cleaning pad. The attached edges of the slats facilitate the cleaning process.	
Suction lips	8.637-945.0	Made from wear-resistant polyurethane. Very durable and oil-resistant.	
Home Base adapter	5.035-488.0	For attaching to the Home Base rail.	

SINGLE DISC MACHINES

Versatile, powerful and efficient

Whether scrubbing, crystallising, shampooing or diamond polishing - our powerful single-disc machines are just as versatile as they are efficient in everyday use.









1 Powerful motor

- Extremely robust and durable design.
- Powerful for numerous applications.
- Low operation and service costs.

3 Simple operation

- Convenient and easy handling.
- Excellent balance and quiet operation.

2 Robust planet carrier

- Made from hard-wearing metal gear wheels. Reduced wear and tear and maintenance costs compared with belt gear.
- Higher torque than a conventional belt gear.
- Quiet, durable and maintenance-free.

4 Integrated power outlet

- For connection to a suction unit, which reduces dust.
- Increases cleaning performance.

TECHNICAL DATA AND EQUIPMENT

BDS 43/150 C Classic

- Robust and reliablePowerful and versatile
- Simple operation

Technical data		
Brush working width	mm	430
Brush contact pressure	g/cm² / kg	30 / 43
Brush speed	rpm	150
Voltage	V	220-240
Frequency	Hz	50
Rated input power	W	1500
Weight	kg	43
Dimensions (L × W × H)	mm	590 × 430 × 1180

Equipment		
Disc brush		-
Pad drive board		
Tank, optional	I	10
Order no.		1.291-243.0
Price		

■ Included in the scope of supply.

Accessories	Product		
Product name	name	Order no.	Description
Disc brush	6.369-897.0	Polishing brush.	
Disc brush	6.369-895.0	Scrubbing brush.	
Disc brush	6.369-898.0	Scrubbing brush, GRIT.	
Shampooing brush	6.369-896.0	Shampooing brush.	
Pad drive board	6.369-899.0	Low speed.	
Complete tank	9.753-058.0	Enables easy application of the cleaning fleet. Capacity: 10 l.	
Microfibre pad	6.905-526.0	Excellent cleaning power. Also effectively cleans fine stoneware tiles.	
Supplementary weight, 10 kg	2.642-802.0	Increases the contact pressure. For effective coating removal, grinding, crystallising, etc.	

542


SINGLE DISC MACHINES

Unique: two bars for perfect balance

The latest generation of Kärcher single-disc machines is perfectly balanced with two bars – for convenient and powerful cleaning of hard surfaces and textile coverings.









1 Optional tank on the motor casing

- Central weight distribution for increased contact pressure while also being light to carry.
- Very good accessibility and rapid removal in just one action. Convenient filling at the sink.
- Filling level display (continuous water level control).

2 Handle can be completely folded down

- Machine requires significantly less storage space.
- Compact dimensions ideal for transport, for example in a car.
- Robust design with oval aluminium pipes and wide handle for good application of force and effortless operation.

3 might quality

- High-performance motor and all-metal planet carrier.
- Very robust and durable version and high torque for efficient operation

4 Wide, ergonomic handle

- Two robust oval aluminium bars for good balance and effortless operation
- Good application of force is possible.

TECHNICAL DATA AND EQUIPMENT

		BDS 51/180 C Adv	BDS 43/180 C Adv	BDS 33/180 C Adv
		Extra large working widthPowerful and versatileExtremely robust	Powerful and versatileWith additional socket for suction attachment kitVery robust and durable	Powerful and versatileWith additional socket for suction add-onEasy to use
Technical data				
Brush working width	mm	510	430	330
Brush contact pressure	g/cm² / kg	25 / 45	38 / 43	47 / 31
Brush speed	rpm	180	180	180
Voltage	V	220-240	220-240	220-240
Frequency	Hz	50	50	50
Rated input power	w	max. 1000	850	700
Weight	kg	45	43	31
Dimensions (L × W × H)	mm	700 × 510 × 1180	660 × 430 × 1180	500 × 356 × 1180
Equipment				
Disc brush		-	-	-
Pad drive board		-	-	-
Tank, optional	I	10	10	8
Order no.		1.291-227.0	1.291-226.0	1.291-220.0
Price				

■ Included in the scope of supply.

	BDS 43/Duo C I Adv	BDS 43/Duo C Adv	BDP 43/450 C Adv
	Versatile thanks to two speedsVery powerful and robustFor cleaning and polishing	Adjustable speedCan be used anywhereWhisper quiet	High-speed machineWhisper quietFor polishing and cleaning
mm	430	430	430
g/cm² / kg	45 / 51	45 / 47	42 / 46
rpm	125-250	150-300	450
V	220-240	220-240	220-240
Hz	50	50	50
w	1560	1560	1760
kg	51.6	47	45.7
mm	1135 × 441 × 354	660 × 430 × 1180	660 × 430 × 1180
	-	-	-
	-	-	-
1	10	10	-
	1.291-241.0	1.291-223.0	1.291-225.0
	g/cm² / kg rpm V Hz W kg	■ Versatile thanks to two speeds ■ Very powerful and robust ■ For cleaning and polishing mm	■ Versatile thanks to two speeds ■ Very powerful and robust ■ For cleaning and polishing ■ Whisper quiet ■ Majustable speed ■ Can be used anywhere ■ Whisper quiet ■ Whisper quiet ■ Whisper quiet ■ Majustable speed ■ Can be used anywhere ■ Whisper quiet ■ Majustable speed ■ Can be used anywhere ■ Whisper quiet ■ Majustable speed ■ Can be used anywhere ■ Whisper quiet ■ Majustable speed ■ Can be used anywhere ■ Whisper quiet ■ Majustable speed ■ Can be used anywhere ■ Whisper quiet ■ Majustable speed ■ Can be used anywhere ■ Can be used an

ESCALATOR CLEANER

Escalator cleaning while in use



Our escalator cleaners deliver squeaky clean results on all moving walkways and escalators – even while in use. For both maintenance and deep cleaning.



1 Excellent suction power

- The applied water is reliably sucked back into the machine by the two powerful suction turbines together with four straight suction hoses and matching combs.
- Prevents water from dripping into the escalator shaft.

2 Suitable for escalators

- Combs which enter the grooves in the escalator provide the necessary vacuum.
- Different combs are available to suit different types of escalators. This ensures that the moisture is effectively vacuumed from the escalator.

BR 47/35 Esc

- Cleans escalators and travelators while they are running
- Equipped with standard wash brush and pick-up brush
- Reliable water pick up

Technical data		
Brush working width	mm	470
Working width, vacuuming	mm	470
Fresh/dirty water tank	1	35 / 35
Brush speed	rpm	870-1090
Container capacity		-
Brush motor power	W	1100
Suction motor	W	800
Water flow	l/h	60
Pressure	bar	4-7
Voltage	V	220-240
Frequency	Hz	50-60
Weight	kg	90
Dimensions (L × W × H)	mm	1200 × 670 × 1100

Equipment	
Cleaning brush	
Pick-up brushes	
Leading combs*	-
Outlet combs*	-
Order no.	1.310-109.0
Price	

■ Included in the scope of supply.

* Please order separately according to type of escalator.



Non-stop maintenance cleaning

For maintenance/intermediate cleaning: the BR 45/10 Esc is suitable for quick and thorough dry cleaning of escalators and travelators. Cleaning takes place while the escalator is moving.



1 Efficient cleaning

- Ready to use within minutes.
- Cleans moving escalators quickly and efficiently.

Durat auration

- For dust-free operation. The 10-litre filter bag reliably retains dirt.
- Two suction turbines for very high suction power.

BR 45/10 Esc

- Cleans escalators and travelators while they are running
- Dry cleaning
- For maintenance and intermediate cleaning

Technical data		
Brush working width	mm	450
Working width, vacuuming	mm	450
Fresh/dirty water tank	1	-/-
Brush speed	rpm	290
Container capacity	1	10
Brush motor power	W	190
Suction motor	W	1500
Water flow		-
Pressure		-
Voltage	V	220-240
Frequency	Hz	50
Weight	kg	44
Dimensions (L × W × H)	mm	880 × 460 × 220

Equipment	
Cleaning brush	
Pick-up brushes	-
Leading combs	-
Outlet combs	-
Order no.	1.310-121.0
Price	

COMPACT CLASS



The versatile handheld ideal for stairwell cleaning

For small, awkward areas such as stairwells and window sills. For deep cleaning, crystallisation or polishing of hard surfaces and shampooing carpets. Also suitable for vertical surfaces.











1 Light and compact

- $\hfill \blacksquare$ Suitable for small areas such as stairwells or window sills.
- For easy transport.

- 3 Speed 0-470 rpm
- Speed can be adjusted to suit the cleaning task.

2 High-quality components

Device is virtually maintenance-free.

4 Optionally available corner brush

For cleaning right into the corners. (with an optional corner brush for simultaneous horizontal and vertical use)

TECHNICAL DATA AND EQUIPMENT

BD 17/5 C

- For window sills, stairs, etc.Horizontal/vertical cleaning
- Optional: Guide rod and tank

Technical data		
Working width	mm	170-200
Working height	mm	330
Brush speed	rpm	0-470
Voltage	V	220-230
Frequency	Hz	50-60
Rated input power	w	120
Weight	kg	5
Dimensions (L × W × H)	mm	360 × 180 × 330

Equipment	
Disc brush	-
Pad drive board	-
Adjustable brush speed	•
Wheels	I
Tank	-
Guide rod	-
Order no.	1.737-107.0
Price	

Accessories Product name	Product name	Order no.	Description
Disc brush	6.994-112.0	For all surfaces.	
Disc brush	6.994-113.0	For deep cleaning.	
Disc brush	6.994-116.0	For all surfaces, large diameter.	
Disc brush	6.994-117.0	For deep cleaning, large diameter.	
Disc brush	6.994-118.0	For polishing, large diameter.	
Corner brush	6.994-127.0	Ideal for cleaning in corners, for all surfaces.	
Corner brush	6.994-128.0	Ideal for cleaning in corners, for deep cleaning.	
Polishing brush	6.994-114.0	For polishing.	
Shampooing brush	6.994-115.0	For carpets.	
Pad drive board	6.994-119.0	Easy to fit pad drive board for BD 17/5 stair cleaning machine. For cleaning with 170 mm diameter pads.	



The professional for shiny floors

Cable-free, powerful, fast: the manoeuvrable RS polishing machine offers a large working width and speed of 2,000 rpm, meaning that even the most stubborn marks can be removed easily.





1 Automatic contact pressure

- No adjustment of the contact pressure.
- Constant contact pressure, even with worn pads or on uneven surfaces.

2 Integrated passive dust suction

- The polishing dust is collected under the pad and then automatically transported upwards into the filter bag.
- The large filter bag is easily accessible and easy to change.

COMPACT CLASS



Economical and effective polishing

When polishing smooth, high-gloss floors, the BDP 50/1500 C ultra highspeed machine achieves a level of productivity up to 30% greater than conventional high-speed machines.



1 Integrated vacuuming system

- The guard ensures that polishing dust stays under the machine. The dust is collected in the dust container by passive vacuuming to reduce dust impact
- Any dust collected is easy to empty the filter bag is reusable.

2 Automatic contact pressure

- The pad drive board is spring-mounted. The contact pressure is automatically regulated for consistent polishing results.
- The pad maintains optimal surface contact and follows any floor unevenness.

BDP 50/2000 F	RS Bp Pack	

BDP 50/2000 RS Bp

		 Compact and extremely manoeuvrable High speed and maximum productivity Integrated vacuum cleaning 	 Compact and extremely manoeuvrable High speed and maximum productivity Integrated vacuum cleaning
Technical data			
Working width, pad	mm	510	510
Working width, vacuuming	mm	530	530
Theoretical area performance	m²/h	1780	1780
Brush contact pressure	g/cm² / kg	10 / 21	10 / 21
Brush speed	rpm	2000	2000
Rated input power	W	2315	2315
Traction motor	W	155	155
Voltage, charger	V / Hz	230 / 50-60	-
Weight	kg	180	100
Dimensions (L × W × H)	mm	1130 × 595 × 1315	1130 × 595 × 1315

Dimensions (L × W × H)	mm	1130 × 595 × 1315	1130 × 595 × 1315	
Equipment				
Traction drive				
Battery and battery charger included	d	•	-	
Adjustable contact pressure			-	
Drive board with centerlock				
Dust suction			•	
Order no.		1.002-039.0	1.002-041.0	
Price				

■ Included in the scope of supply.

BDP 50/1500 C

- Mains operation for uninterrupted use
- $\hfill \blacksquare$ With central guide wheel polishing up to the edge
- Dust-free operation thanks to built-in dust suction

Technical data		
Working width, pad	mm	510
Working width, vacuuming	mm	560
Theoretical area performance	m²/h	900
Brush contact pressure	g/cm²	4
Brush speed	rpm	1500
Voltage	V	230
Frequency	Hz	50
Rated input power	W	1100
Weight	kg	35.4
Dimensions (L × W × H)	mm	760 × 550 × 1250

Equipment	
Traction drive	-
Battery and battery charger included	-
Adjustable contact pressure	-
Drive board with centerlock	I
Dust suction	T .
Order no.	1.291-141.0
Price	

THE COMPLETE RANGE FOR HARD SURFACE CLEANING

Our scrubber driers are capable of exceptional performance. In order for them to achieve this, they need optimally coordinated accessories and cleaning agents. Only the Kärcher system of machine, original Kärcher accessories and original Kärcher cleaning agents gives you maximum performance and efficiency for a wide variety of applications. Plus the required functionality and safety.



Table of contents: Scrubber/scrubber drier accessories

Scrubber and scrubber drier accessories	Page	554
Single-disc machine accessories	Page	614
Escalator cleaner accessories	Page	620
Stair cleaner accessories	Page	622
Polishing machine accessories	Page	624
Manual Cleaning Equipment	Page	792
Cleaning agents	Page	866



1 Cleaning by colour

Kärcher has implemented the colour system for selecting the right accessory (tried and tested with pad discs) for all roller brushes, roller pads and disc brushes. This makes it extremely easy to find the right accessory for every application. From white = no abrasive effect, to black = highly abrasive. The orange brush has long and deep bristles, and is ideal for structured surfaces.

2 The round solution for grey film

The microfibre roller combines the advantages of roller technology with those of microfibre: A self-cleaning effect and the effective removal of grey film. The best results are achieved on fine stoneware tiles in particular.

3 Melamine pads

Melamine pads are perfect for cleaning greyed coverings deep into the fibres using disc engineering. Using intensive cleaning, grey film can be removed from fine stoneware tiles and artificial stone in particular with minimal effort.

4 Diamonds clean and polish to a high gloss

Diamond pads are Kärcher's innovation for cleaning and polishing using scrubber driers in maintenance cleaning. The system with three different granulations is ingenious: Three weeks of using the white pad, three weeks of using the yellow pad, and then the green pad, for polishing results to a high gloss. This saves a great deal of time and expense, and the surface will take longer to become dirty again. On all natural stone floors, artificial stone and epoxy coverings.

5 Renew coatings faster

Coatings protect the floor and enhance its appearance. Most coatings have to be regularly renewed, usually with a strongly alkaline cleaning agent and single-disc machine, which takes a lot of time. Three innovative Kärcher developments - the S 65 stripping head, the O 51 orbital disc head and the stripping rollers - now accelerate this work with 3 to 10 times the area performance. And without using a cleaning agent! This reduces cleaning costs enormously and reduces the environmental impact. With the top-stripping versions, the existing coating is evenly sanded and then re-coated. The S 65 and O heads are equipped with a quick-change system which means that you do not have to purchase any additional machines. Kärcher stripping rollers can be easily used in the existing roller head.

BRUSH HEADS



Different brush heads - R (roller), D (disc) or S (with vibration technology) - are available for different applications. A disc head is recommended for smooth surfaces with light soiling. Roller heads are ideal for stubborn dirt or structured surfaces. These are all fitted with a sweep tray. This makes the scrubber drier an all-rounder that can sweep, scrub and vacuum in a single operation. The S-head plays a special role in this - it allows very efficient stripping of floors. The brush heads can be very easily replaced on the machine.























	14	15		16			17			•	18		P							
Description		25	B 250 R I + R 100 / B 250 R + R 100 B 250 R I + D 100 / B 250 R + D 100 B 200 B + D 110	B 200 R + R 9 110 B 200 R + R 90 B 150 R Adv + R 90 / B 150 R + R 90	200 R + D 50 / B 150 R AdV + D 50 / B 150 R + L 200 R + R 75 / B 150 R Adv + R 75 / B 150 R + R 200 R + D 75 / B 150 R Adv + D 75 / B 150 R + D	R Adv Dose Bp /	Bp Pack	~	BD 50/40 RS Bp Pack / BD 50/40 RS Bp B 120 W + D 110	B 120 W + R 90 B 120 W + D 90	B 120 W + R 75 B 120 W + D 75	B 80 W Bp + R /5 B 80 W Bp + D 75 B 80 W Bp + D 66 / B 60 W Bp + D 66	B 80 W Bp + D 65 / B 60 W Bp + D 65 B 80 W Bp + S 65 / B 60 W Bp + S 65	B 60 W Ep R 55 / B 40 C Ep + R 55 B 60 W Ep + D 51 / B 40 C Ep + D 51	5 / B 40 C Bp		B 60 W Bp + R 55 B 60 W Bp + D 55 B 40 W Bp + D 65	0) (N 0) (N 0) (N 0) (N 0)	B 40 W Bp + D 43 / B 40 C Bp + D 43 / B 40 C Bp Classic + D 43 B 40 W Bp 0 51	
	1																			
Brush head with two roller brushes, 45 cm working width and 240 V voltage. Brush head with two roller brushes and 45 cm working width.	2		++	++	++			++									++	++	-	_
	3																			
Brush head with one disc brush, 43 cm working width and 240 V voltage.	4																	Ш		
Brush head with one disc brush and 43 cm working width.	5																\perp	r	•	
Brush head with two roller brushes, 55 cm working width and 240 V voltage.	6													•			$\perp \perp$	$\perp \perp$		
Brush head with two roller brushes and 55 cm working width.	7				+	-		+			++	++	+	-		-	++	++	\perp	\perp
Druch hand with one dies house E1 cm working width and 240 V voltage	8				++			+						-		\vdash				
Brush head with one disc brush, 51 cm working width and 240 V voltage. Brush head with one disc brush and 51 cm working width.	9				++			-			-		+	-	-		++	++		+++
For restoring the protective film on hard and resilient flooring, and for the dry removal of	11				++-										-	-	++	++		
polymer coatings. Please order the appropriate pad separately.																			-	
Brush head with two roller brushes and 55 cm working width. Brush replacement without tools. The side skirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fed into the squeegee at an optimum rate, even when negotiating curves. Brush head supplied separately. Brush head with two disc brushes, quick brush switch system for brushes and 55 cm work-	12															•				
ing width. The sideskirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fedinto the squeegee at an optimum rate, even when negotiating curves. Brush head supplied separately.																	•			
Brush head with two roller brushes and 65 cm working width. Brush replacement without tools. The side skirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fed into the squeegee at an optimum rate, even when negotiating curves. Brush head supplied separately.	14												ı							
Brush head with two disc brushes, quick brush switch system for brushes and 65 cm working width. The sideskirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fedinto the squeegee at an optimum rate, even when negotiating curves. Brush head supplied separately.	15												•							
Brush head with disc engineering. Ideal for use in supermarkets, for example. Very low deck. Height-adjustable bumper disc. Surrounding splash guard.	16																			
For restoring shine on hard and resilient floors.	17		++	++	++			++		+++	+	++		+		+	++	++	++	++
Brush head with two roller brushes and 75 cm working width. Brush replacement without tools. The side skirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fed into the squeegee at an optimum rate, even when negotiating curves. Brush head supplied separately.	18										• .									

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

Price Description

Order no.

1 2.763-021.0

2 2.763-020.0

3 2.763-019.0 4 2.763-024.0

5 2.763-023.0

6 2.763-017.0

7 2.763-013.0

8 2.763-011.0

9 2.763-027.0

11 2.763-044.0

10 2.763-026.0

12 2.763-002.0

13 2.763-001.0

14 2.763-004.0

15 2.763-003.0

16 2.763-039.0

17 2.763-030.0

18 2.763-006.0

Brush heads Brush head R 45 Ep

Brush head R 45 C

Brush head R 45 W

Brush head D 43 Ep

Brush head D 43

Brush head R 55 Ep

Brush head R 55 C

Brush head R 55 W Brush head D 51 Ep

Brush head D 51

Brush head R 55 S

D 55 S brush head

Brush head R 65 S

D 65 S brush head

Brush head D 65 R

Brush head R 75 S

Floor head S 65

Brush-head O 51 Orbital

















	Order no.	Price	Description		# + #	3 250 R I + R 100 / B 250 R + R 100 3 250 R I + D 100 / B 250 R + D 100 2 200 R + D 110	Adv + R 90 / B Adv + D 90 / B	Adv + D 75 / B 150 R +	assic Bp Pack / B 90 R Classic Bp	R 55/40 RS	8D 50/40 RS BP PacK / BD 50/40 RS Bp 120 W + D 110	1120 W + D 90	1120 W + D 75 8 80 W Bp + R 75	8 80 W Bp + D 75 8 80 W Bp + R 65 / B 60 W Bp + R 65 8 80 W Bp + D 65 / B 60 W Bp + D 65	V Bp + S Ep + R 55	3 60 W Ep + D 51 / B 40 C Ep + D 51	40 W Bp + D 51 / B 40	66 W Bp + D 55	3 40 W Bp + K 45 3 40 W Bp + D 43 / B 40 C Bp + D 43 / B 40 C Bp Classic + D 43 40 W Bn O 51	4 40 W BP U D 1. 3 40 C Bp + R 45 / B 40 C Bp Classic + R 45 3 40 C Ep + R 45 3 40 C Ep + D 43
D 75 S brush head	19 2.763-005.0		Brush head with two disc brushes, quick brush switch system for brushes and 75 cm working width. The sideskirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fedinto the squeegee at an optimum rate, even when	19										•						1 1
Brush head R 90 S	20 2.763-007.0		negotiating curves. Brush head supplied separately. Brush head with two roller brushes and 90 cm working width. Brush replacement without tools. The side skirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fed into the squeegee at an optimum rate, even when negotiating curves. Brush head supplied separately.	20			•				-	1								
Brush head D 90 S	21 2.763-008.0		Brush head with two disc brushes, quick brush switch system for brushes and 90 cm working width. The sideskirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fedinto the squeegee at an optimum rate, even when negotiating curves. Brush head supplied separately.	21			-					•								
Brush head R 100 S	22 2.763-033.0		Brush head with two roller brushes for stubborn dirt, 100 cm working width and integrated sweeping function. Easy brush replacement possible without tools.	22		•														
D 100 S brush head	23 2.763-035.0		Brush head with two disc brushes, 100 cm working width and height-adjustable side skirts. Convenient brush replacement using foot pedal.	23		-														
D 110 S brush head	24 2.763-040.0		Brush head with two disc brushes, quick brush switch system for brushes and 110 cm working width. The side skirts are height-adjustable and hold the water under the brush head. This allows the cleaning fleet to be fed into the squeegee at an optimum rate, even when negotiating curves. Brush head supplied separately.	24																
Brush head D110 B200R	25 2.763-045.0		D 110 R brush head for extra-wide working width of B 200 R with disc brushes. Incl. bullbar on both sides.	25																
Brush head R 120 S	26 2.763-034.0		Brush head with two roller brushes for stubborn dirt, 120 cm working width and integrated sweeping function. Easy brush replacement possible without tools.	26																
Connection kit S 65	27 4.036-063.0	_	Connection kit for connecting the S 65 floor head to the new generation of B 60 W and B 80 W.	27															#	
Install and addition of the bound by D. 75.0 (2000)	28 4.036-061.0		Kit for connecting the S 65 floor head to the B 90 R.	28					1111	+	+++			++		$\overline{}$	+	+++	++	+
Impact protection attachment kit R 75 S / R 90 S	29 2.643-369.0	_	Protects the brush head against knocks.	30				+++	+++	++			•	++	++	\vdash	+	+++	++	+
Impact protection attachment kit D 75 S	30 2.643-370.0		-					+++	+++	++	+++		-	++		+	++	+++	++	+
Impact protection attachment kit D 90 S	31 2.643-371.0		iginal accessories can be found on the following pages	31										\perp					$\bot\bot\bot$	

Impact protection attachment kit D 90 S 31 | 2.643-371.0 |

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

ROLLER BRUSHES



Roller brushes combine high friction and high contact pressure. For excellent cleaning results.



	Order no.	Hardness / Brush type	Length	Colour	Quantity	Price	Description		B 300 R I D / B 300 R I LPG	B 250 R I + R 120	B 250 R I + R 100 B 250 R + R 120	B 200 R + R 100 B 200 R + R 90 B 200 R + R 75	B 150 R Adv + R 75		B 90 R configured / B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp B 90 R Adv Bp Pack / B 90 R Adv Bp / B 90 R Classic Bp Pack B 90 B Classic Bn	B 9 5 K 7 5	B 55 K 7 + K 0.5 BR 55/40 KS Bp Pack / BR 55/40 RS Bp B 120 W + R 90	B 120 W + R 75 B 80 W Bp + R 75	B 80 W Bp + R 65 B 60 W Ep R 55 / B 60 C Classic + R 55 B 60 W Bp + R 65	B 60 W Bp + R 55 B 40 W Bp + R 55	B 40 W Bp + R 45 B 40 C Bp + R 55	B 40 C Bp + R 45 B 40 C Bp C lassic + R 55	≃	B 40 L ED * K 45 B R 45/2 C B P Back B R 45/17 F B D Dark		30/4 C
Roller brushes		1 6	Lana	1	Le col			1 4																	1 1 1-1-	
Roller brush	1 4.762-452.0		300 mm		1 piece(s)		For cleaning sensitive floors and polishing.	1				\perp		\perp		\perp	+		\perp]
	2 4.762-499.0		300 mm	blue	1 piece(s)		For carpet cleaning.	2		\perp		\perp		\perp		\perp	\perp	+					\perp]
	3 4.762-005.0		300 mm		1 piece(s)		For all floors.	3		\perp		\perp		\perp		\perp	\perp	$\perp \perp \perp$	\perp							4
	4 4.762-484.0	high / low	300 mm	orange	1 piece(s)		For cleaning heavily structured floors as well as in joints and crevices.	4																		3
	5 4.037-036.0	very soft	350 mm	white	1 piece(s)		For cleaning sensitive floors and polishing.	5																		
	6 4.037-031.0	medium	350 mm	red	1 piece(s)		For all floors.	6																		
	7 4.037-037.0	high / low	350 mm	orange	1 piece(s)		For cleaning heavily structured floors and deep grouts.	7																		
	8 4.037-038.0	hard	350 mm	green	1 piece(s)		For stubborn dirt and deep cleaning; only for hard-wearing surfaces.	8																		
	9 4.762-250.0	very soft	400 mm	white	1 piece(s)		For cleaning sensitive floors and polishing.	9			\dashv			\top		\top										7
	10 4.762-274.0	soft	400 mm	natural	1 piece(s)		Horse hair, perfect for cleaning and polishing.	10		\top	\top			\top		\top										7
	11 4.762-003.0	medium	400 mm	red	1 piece(s)		For all floors.	11						\top												
	12 4.762-251.0	high / low	400 mm	orange	1 piece(s)		For cleaning heavily structured floors as well as in joints and crevices.	12																		
	13 4.762-252.0	hard	400 mm	green	1 piece(s)		For stubborn dirt and deep cleaning;only for sensitive floor coverings.	13																		
	14 4.762-481.0	very hard	400 mm	black	1 piece(s)		For stubborn dirt and basic cleaning; only for hard-wearing floors.	14																		
	15 4.762-254.0	soft	400 mm	blue	1 piece(s)		Carpet brush for loop-pile carpets.	15						\top												7
	16 4.762-000.0				1 piece(s)		Carpet brush for velour.	16						\top												-
	17 4.762-405.0	soft	450 mm	white	1 piece(s)		For cleaning sensitive floors and polishing. Fits R 45.	17																		7
	18 4.762-392.0		450 mm	red	1 piece(s)		For all floors. Fits R 45.	18		\top	\top		\top	\top		\top	\top				•	•	• •			7
	19 4.762-406.0	_	450 mm	orange	1 piece(s)		For cleaning heavily structured floors as well as in deep joints and crevices. Fits R 45.	19																		
	20 4.762-407.0	hard	450 mm	green	1 piece(s)		For stubborn dirt and deep cleaning;only for hard-wearing surfaces. Fits R 45.	20																		1
	21 4.762-408.0	very hard	450 mm	black	1 piece(s)		For stubborn dirt and deep cleaning;only for insensitive floors. Fits R 45.	21																		
	22 4.762-409.0	soft	550 mm	white	1 piece(s)		Roller brush, soft, white. Ideal for cleaning sensitive floor coverings and for polishing.	22		$\dagger \dagger$			+			$\dagger \dagger$										1

[■] Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.











		Order no.	Hardness / Brush type	Length	Colour	Quantity	Price	Description		B 300 R I D / B 300 R I LPG B 250 R I + R 120 B 250 R I + R 100	B 250 R + R 120 B 250 R + R 100	B 200 R + R 75	B 150 RADV + R 90 B 150 RADV + R 75 B 150 R + R 90	B 90 R Adv Dose Bp Pack / B 90	/ B 90 R Adv Bp / B 90 R Classic Bp Pa	B 95 RS + R 75 B 95 RS + R 65	of the August Au	B 120 W + R 75 B 80 W Bp + R 75 B 80 W Bp + R 65	B 60 W Ep R 55 / B 60 C Classic + R 55 B 60 W Bp + R 65	B 60 W Bp + R 55 B 40 W Bp + R 55 B 40 W Bn + R 45		B 40 C Bp Classic + R 55 B 40 C Bp Classic + R 45	B 40 C Ep + R 55 B 40 C Ep + R 45 B R 45/22 C Bp Pack	BR 35/12 C Bp Pack BR 40/10 C I Adv	BR 40/10C BR 30/4 C Bp Pack BR 30/4 C Adv / BR 30/4 C / BR 30/4 C + MF
Roller brush	23	4.035-184.0		550 mm	_	1 piece(s)		Roller brush, medium-hard, red. Length: 550 mm. For all common cleaning tasks. Also suitable for sensitive floors. Bristles made from polypropylene; 0.4 mm thick, 20 mm long.	23							1			•	•			•		
	24	4.762-410.0	high / low	550 mm	orange	1 piece(s)		For cleaning heavily structured floors as well as in deep joints and crevices. Fits B 40 C/W/RS R 55.	24								1								
	25	4.762-411.0	hard	550 mm	green	1 piece(s)		Roller brush, hard, green. For deep cleaning, also in the case of extreme soiling. Only suitable for sensitive floor coverings.	25																
	26	4.762-412.0	very hard	550 mm	black	1 piece(s)		For stubborn dirt and deep cleaning;only for insensitive floors. Fits B 40 C/W/RS R 55.	26																
	27	6.906-977.0	soft	532 mm	white	1 piece(s)		For cleaning sensitive floors and polishing. Fits R 55.	27		\dashv	+		П		+				п	+++				++-
		4.035-193.0		532 mm	_	1 piece(s)		For all floors. Fits R 55.	28		\dashv									•					+
		6.906-978.0		532 mm		1 piece(s)		For cleaning heavily structured floors as well as in deep joints and crevices. Fits R 55.	29																
	30	6.906-979.0	hard	532 mm	green	1 piece(s)		For stubborn dirt and deep cleaning;only for hard-wearing surfaces. Fits R 55.	30																
	31	6.906-980.0	very hard	532 mm	black	1 piece(s)		For stubborn dirt and deep cleaning;only for insensitive floors. Fits R 55.	31																
	32	6.906-981.0	soft	638 mm	white	1 piece(s)		For cleaning sensitive floors and polishing. Fits R 65.	32								\top								\top
	33	4.035-187.0	medium	638 mm	red	1 piece(s)		For all floors. Fits R 65.	33									-							
	34	6.906-982.0	high / low	638 mm	orange	1 piece(s)		For cleaning heavily structured floors as well as in deep joints and crevices. Fits R 65.	34																
	35	6.906-983.0	hard	638 mm	green	1 piece(s)		For stubborn dirt and deep cleaning;only for hard-wearing surfaces. Fits R 65.	35																
	36	6.906-984.0	very hard	638 mm	black	1 piece(s)		For stubborn dirt and deep cleaning;only for insensitive floors. Fits R 65.	36																
	37	6.906-985.0	soft	700 mm	white	1 piece(s)		For cleaning sensitive floors and polishing. Fits R 75.	37																
	38	4.035-190.0	medium	700 mm	red	1 piece(s)		For all floors. Fits R 75.	38																

^{38 4.035-190.0} medium 700 mm red 1 piece(s) For all floors. Fits R 75.

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.













1	m.	Time.	411
55			

	Order no.	Hardness / Brush type	Length	Colour	Quantity Price	Description		B 300 R I D / B 300 R I LPG B 250 R I + R 120 B 250 R I + R 120 B 250 R I + R 100 B 250 R R R 120 B 250 R R R 120 B 250 R R R 120 B 250 R R R 100 B 200 R Ad V B 20 B 200 R Ad V B 20 B 150 R Ad V R 50 B 150 R Ad V B 20 B 150 R Ad
Roller brush	39 6.906-986.0		700 mm	+	1 piece(s)	For cleaning heavily structured floors as well as in deep joints	39	
	40 6.906-987.0	hard	700 mm	green	1 piece(s)	and crevices. Fits R 75. For stubborn dirt and deep cleaning;only for hard-wearing surfaces. Fits brush head R 75.	40	
	41 6.906-988.0	very hard	700 mm	black	1 piece(s)	For stubborn dirt and deep cleaning;only for insensitive floors. Fits R 75.	41	
	42 6.906-989.0	soft	800 mm	white	1 piece(s)	For cleaning sensitive floors and polishing. Fits R 90.	42	
	43 6.907-377.0	medium	800 mm	red	1 piece(s)	For all floors, fits R 90.	43	
	44 6.906-991.0	hard	800 mm	green	1 piece(s)	For stubborn dirt and deep cleaning;only for hard-wearing surfaces. Fits on brush head R 90.	44	
	45 6.906-992.0	very hard	800 mm	black	1 piece(s)	For stubborn dirt and deep cleaning;only for insensitive floors. Fits R 90.	45	
	46 6.906-990.0	high / low	800 mm	orange	1 piece(s)	For cleaning heavily structured floors as well as in deep joints and crevices. Fits R 90.	46	
	47 6.906-993.0	soft	914 mm	white	1 piece(s)	For cleaning and polishing sensitive floors, with star attachment. Fits BR 100/250 R and brush head R 100.	47	
	48 6.906-995.0	hard	914 mm	green	1 piece(s)	For stubborn dirt and deep cleaning:only for hard-wearing surfaces.Fits BR 100/250 R and brush head R 100.	48	
	49 6.906-996.0	very hard	914 mm	black	1 piece(s)	For stubborn dirt and deep cleaning:only for hard-wearing surfaces, with star attachment. Fits BR 100/250 R and brush head R 100.	49	
	50 6.906-994.0	high / low	914 mm	orange	1 piece(s)	For cleaning heavily structured floors and deep grouts, with star attachment. Fits BR 100/250 R and brush head R 100.	50	
	51 6.906-855.0	soft	1118 mm	white	1 piece(s)	For cleaning sensitive floors and polishing. Fits BR 120/250 R and brush head R 120.	51	
	52 6.906-853.0	medium	1118 mm	red	1 piece(s)	For all floors, with star attachment. Fits BR 120/250 R and brush head R 120.	52	
	53 6.907-426.0	hard	1118 mm	green	1 piece(s)	For stubborn dirt and deep cleaning;only for hard-wearing surfaces. Fits R 120.	53	
	54 6.906-856.0	very hard	1118 mm	black	1 piece(s)	For stubborn contamination and deep cleaning; only for hard-wearing surfaces. Fits BR 120/250 R and brush head R 120.	54	
	55 6.906-854.0	high / low	1118 mm	orange	1 piece(s)	For cleaning heavily structured floors as well as in deep joints and crevices.	55	
	56 6.680-368.0	medium	1045 mm	black	1 piece(s)	Medium-hard roller brush. The perfect equipment for all	56	

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.













66-67

	Order no.	Hardness / Brush type	Length	Colour	Quantity Price	Description		B 300 R I D / B 300 R I LPG B 250 R I + R 120	B 250 R I + R 100 B 250 R + R 120	B 256 R + R 100 B 200 R + R 90	B 200 R + R 75 B 150 R Adv + R 90	B 150 R Adv + R 75		B 90 R configured / B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp B 90 R Adv Bp Pack / B 90 R Classic Bp Pack B 90 R Classic Bp	9 90 N 5 4 75	5 55 40 TS Bp Pack / BR 55/40 RS Bp B17 55/40 RS Pp B17 55/40 RS Pp	B 120 W + K 9U	B 80 W Bp + R 75 B 80 W Bp + R 65	B 60 W Ep R 55 / B 60 C Classic + R 55 B 60 W Bp + R 65	B 60 W Bp + R 55 B 40 W Bp + R 55	B 40 W Bp + R 45 B 40 C Bp + R 55	B 40 C Bp + R 45 B 40 C Bp Classic + R 55	<u>~</u>	B 40 C Ep + R 45 BR 45/22 C Bp Pack	BR 35/12 C Bp Pack BR 40/10 C I Adv	BR 40/10C BR 30/4 C Bp Pack BR 30/4 C Adv / BR 30/4 C / BR 30/4 C + MF
Roller brush 57	_	very hard	1045 mm		1 piece(s)	Extra hard roller brush for insensitive floors and heavy soiling.	57			+-+-	+	+-+-	+-1		+-+	+-+-	+++	++	+	+	$\overline{}$	++-		+	+++	
Pad roller shaft	7 0.000 000.0	Tery mana	10 10 11111	Dideit	T piece(s)	Extra ridia roner bross for inscristive ridors and nearly soming.	5.	1-1													\dashv	\vdash	\vdash		\vdash	
	8 4.762-009.0		350 mm		1 piece(s)	For attaching roller pads or microfibre rollers.	58						1.1	1.1	1.1	1.1	TT	\top							Int I	
	9 4.762-228.0		400 mm		1 piece(s)	For roller pads or microfibre rollers.	59								+		++	++	+	+	\Box	+-	H	\vdash		
	0 4.762-413.0		450 mm		1 piece(s)	For mounting roller pads or microfibre rollers. Fits R 45.	60							+			++	++	+	+						+
6	1 4.762-432.0		532 mm		1 piece(s)	Fits R 55.	61						1				\top									
6	2 4.762-415.0		550 mm		1 piece(s)	Pad roller shaft suitable for holding roller pads or microfibre	62										\top									
						rollers.				++		++				-	++			\dashv	\coprod	H-'	HĬ	-	+	
	3 4.762-433.0				1 piece(s)	Fits R 65.	63			1 1] [[] [1 [1 1 1	1 1 '	1 1 7	1 1	1 1 1	
			638 mm				6.4										1515	\pm	\rightarrow	\neg	\vdash	 	\vdash	+-	+	
1 6	4 4.762-434.0		700 mm		1 piece(s)	Fits R 75.	64											丰	\blacksquare	\blacksquare	中	\Box				
							64 65 66] [\blacksquare							

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

ROLLER PADS



World innovation: Kärcher combines the excellent properties of microfibres and advantages of roller technology. Perfect for cleaning fine stoneware tiles. Effortlessly cleans tiles leaving them looking like new. Also suitable for nearly all other types of floors.













		Order no.	Hardness , Brush typ	1	Diamete	r Colour	Price	Description		B 250 R I + R 120 B 250 R I + R 100	B 250 R + R 120 B 250 R + R 100	5 2 2 0 1 1 1 2 0 0 0 0 0 0 0 0 0 0 0 0 0	B 200 K + K / 5 B 150 R Adv + R 90 B 150 R Adv + R 75	B 90 R configured / B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp B 90 R Adv Bp Pack / B 90 R Adv Bp / B 90 R Classic Bp Pack	B 90 R Classic Bp B 95 R5 + R 75	B 95 RS + R 65 BR 55/40 RS Bp Pack / BR 55/40 RS Bp R 120 NW + D 90	B 120 W + R 90 B 120 W + R 75 / B 80 W Bp + R 75	60 C Classi	B 60 W Bp + R 65 B 60 W Bp + R 55	B 40 W Bp + R 55 B 40 W Bp + R 45	8 40 tt spr 1 tt s 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	B 40 C Bp + R 45 B 40 C Bp Classic + R 55 R 40 C Bn Classic + P 45	¥	Bp Pack	BR 40/10 C I Adv / BR 40/10C BR 30/4 C Bp Pack BP 30/4 C Adv	BR 30/4 C BR 30/4 C
Roller pads																										
Stripping roller		8.635-691.0		400 mm		brown		Suitable for BRS 40/1000 C; BR 40/10 C; BR 40/25 C.	1							$\perp \perp$	Ш	\Box	\perp	\perp	Ш	$\perp \perp$	$\perp \! \! \perp$			
		4.114-011.0		450 mm		brown		Stripping roller, complete, 45 cm, fits R 45.	2			\perp				$\perp \perp$	$\perp \!\!\! \perp \!\!\! \perp$	\rightarrow	$\perp \!\!\! \perp$] [$\perp \perp$	$\perp \perp$
Dellar and an alassia		8.635-692.0		550 mm	06	brown		Fits B 40 W (R 55); B 60 W Ep (R 55); BR 55/40 RS.	3			-				\Box	+		+		44	$\perp \square$		+++	++	
Roller pad on sleeve		6.369-053.0		350 mm		yellow		For polishing and cleaning non-textured floors. In conjunction with pad roller shaft 4.762-009.0.								\perp			\perp	\perp	$\perp \downarrow$		$\perp \!\!\! \perp$		$\perp \! \! \perp$	\perp
	5	6.369-047.0	medium	350 mm	96 mm	red		For cleaning non-textured floors. In conjunction with pad roller shaft 4.762-009.0.	5											Ш						
	6	6.369-052.0	hard	350 mm	96 mm	green		For removing stubborn dirt and deep cleaning of non-textured floors. In conjunction with pad roller shaft 4.762-009.0.	6									.								
	7	6.369-724.0	soft	400 mm	96 mm	yellow		Roller pads pre-assembled on sleeves, for polishing and cleaning non-textured floors. In conjunction with pad roller shaft 4.762-228.0.	7																	
	8	6.369-726.0	medium	400 mm	96 mm	red		For cleaning non-textured floors. In conjunction with pad roller shaft 4.762-228.0.	8								\Box		\Box		П					П
	9	6.369-725.0	hard	400 mm	96 mm	green		For removing stubborn dirt and deep cleaning of non-textured floors. In conjunction with pad roller shaft 4.762-228.0.	9												П					
	10	6.367-105.0	soft	450 mm	96 mm	yellow		For polishing and cleaning non-textured floors. In conjunction with pad roller shaft 4.762-413.0	10													J []			П
	11	6.367-107.0	medium	450 mm	96 mm	red		For cleaning non-textured floors. In conjunction with pad roller shaft 4.762-413.0	11												1 [] []			\top
	12	6.367-106.0	hard	450 mm	96 mm	green		For removing stubborn dirt and deep cleaning of non-tex- tured floors. In conjunction with pad roller shaft 4.762-413.0	12												1 [ם			
	13	6.369-732.0	soft	530 mm	96 mm	yellow		For polishing and cleaning non-textured floors. In conjunction with pad roller shaft 4.762-415.0	13																	
	14	6.369-734.0	medium	530 mm	96 mm	red		For cleaning non-textured floors. In conjunction with pad roller shaft 4.762-415.0	14																1	\prod
	15	6.369-733.0	hard	530 mm	96 mm	green		For removing stubborn dirt and deep cleaning of non-tex- tured floors. In conjunction with pad roller shaft 4.762-415.0	15																1	
	16	6.371-004.0	medium	862 mm	130 mm	red		Medium-hard, red roller pads designed for pad roller shaft 4.762-436.0. Pre-fitted on sleeve and suitable for deep	16																	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.









		Order no.	Hardness / Brush type	Length	Diameter	Colour Price	Description		B 250 R I + R 120 B 250 R I + R 100 R 250 R 8 R 120	B 250 R + R 120 B 250 R + R 100 B 250 R + R 100	B 200 R + R 75 B 150 R Adv + R 90	B 150 R Adv R 75 R 150 R Adv	Dack / R 90	90 R Classic Bp Pack	B 95 RS + R 75	B 55 K 7 K 7 C 5 C 7 K 7 C 7 C 7 C 7 C 7 C 7 C 7 C 7 C 7	D 120 W + R 50 D 120 W + R 50 D 120 W + R 55	B 80 W EQ * K 55 B 60 W EQ K 55 / B 60 C Classic + R 55	B 60 W Bp + R 65 B 60 W Bp + R 55	B 40 W Bp + R 55 B 40 W Bp + R 45	B 40 C Bp + R 55 B 40 C Bp + R 45	B 40 C Bp Classic + R 55 B 40 C Bp Classic + R 45	B 40 C Ep + R 45	BR 45/22 C Bp Pack BR 35/12 C Bp Pack	BR 40/10 C I Adv / BR 40/10C BR 30/4 C Bp Pack	BR 30/4 C Adv BR 30/4 C	BR 30/4 C + MF
Roller pad on sleeve	17	6.371-003.0	hard	862 mm	130 mm	green	Hard green roller pads, pre-fitted on the sleeve for deep cleaning and removing stubborn dirt on non-structured, insensitive floors. For pad roller shaft 4.762-436.0.	17																			
	18	6.371-006.0	medium	1067 mm	130 mm	red	Medium-hard, red roller pads, pre-fitted on sleeve to save time and designed together with the pad roller shaft 4.762-498.0 for deep cleaning and maintenance cleaning of non-structured floors.	18																			
	19	6.371-005.0	hard	1067 mm	130 mm	green	Developed together with the pad roller shaft 4.762-498.0 for deep cleaning and removing stubborn dirt on non-structured floors and green roller pads pre-fitted on sleeves.	19																			
Roller pad	20	6.369-454.0	soft		105 mm	yellow	20 pcs. For polishing and cleaning non-textured floors. In conjunction with the corresponding pad roller shaft. Per 10 cm shaft length, approx. 7 to 7.5 pads are required.	20																			
	21	6.369-456.0	medium		105 mm	red	20 pcs. For cleaning non-textured floors. In conjunction with the corresponding pad roller shaft. Per 10 cm shaft length, approx. 7 to 7.5 pads are required.	21																			
	22	6.369-455.0	hard		105 mm	green	20 pcs. For removing stubborn contamination and for deep cleaning of non-textured floors. In conjunction with the corresponding pad roller shaft. Per 10 cm shaft length, approx. 7 to 7.5 pads are required.	22																			
Microfibre shaft Microfibre roller	23	4.114-004.0	microfibre	400 mm	96 mm	light green	World innovation: the use of microfibre rollers combines the excellent cleaning properties of microfibres with the advantages of roller technology. In conjunction with pad roller shaft 4.762-228.0.	23																			
	24	4.114-009.0	microfibre	450 mm	96 mm	light green	World innovation: the use of microfibre rollers combines the excellent cleaning properties of microfibres with the advantages of roller technology. In conjunction with pad roller shaft 4.762-413.0	24																			
	25	4.114-010.0	microfibre	550 mm	96 mm	light green	World innovation: the use of microfibre rollers combines the excellent cleaning properties of microfibres with the advantages of roller technology. In conjunction with pad roller shaft 4.762-415.0	25																			
	26	4.114-005.0	microfibre	532 mm	105 mm	light green	the use of microfibre rollers combines the excellent cleaning properties of microfibres with the advantages of roller technology. For use with pad roller shaft 4.762-432.0. Fits R 55.	26																			

□ Available accessories. More Kārcher original accessories can be found on the following pages.

FLOOR SCRUBBERS / SCRUBBER DRIERS





	Order no.	Hardness / Brush type	Length	Diameter	Colour	Price Description		8 250 R I + R 120 8 250 R I + R 100 8 250 R + R 120 8 250 R + R 120	2 2 2 0 1 1 2 2 0 1 2 0	5 200 K + K 7.5 B 150 R Adv + R 90	Adv + R + R 90	8 150 R + R 75 B 90 R configured / B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp B 90 R Adv Bp Pack / B 90 R Adv Bn / B 90 R Classic Bp Pack	assic Bp R 75	8 95 RS + R 65 BR 55/40 RS Bp Pack / BR 55/40 RS Bp	+ R 90 + R 75 / B 80 W B	60 C Classic	8 60 W Bp + R 55 8 40 W Bp + R 55	8 40 W Bp + R 45 B 40 C Bp + R 55	+ R 45 Classic +	Classic + R + R 55	+ R 45 C Bp Pack C Bp Pack	BR 40/10 C I Adv / BR 40/10C BR 30/4 C Bp Pack BR 30/4 C Adv	BR 30/4 C BR 30/4 C + MF
Microfibre roller	27 4.114-006.0	microfibre		105 mm		the use of microfibre rollers combines the excellent cleaning properties of microfibres with the advantages of roller technology. For use with pad roller shaft 4.762-433.0. Fits R 65.	27																
	28 4.114-007.0	microfibre	700 mm	105 mm	light green	the use of microfibre rollers combines the excellent cleaning properties of microfibres with the advantages of roller technology. For use with pad roller shaft 4.762-434.0. Fits R 75.	28																
	29 4.114-008.0	microfibre	800 mm	105 mm	light green	For use with pad roller shaft 4.762-435.0. Fits R 90.	29																П
	30 4.762-453.0	microfibre	300 mm	60 mm	light green	World innovation: the use of microfibre rollers combines the excellent cleaning properties of microfibres with the advan-	30																- -
						tages of roller technology. For a complete cleaning solution.								1 1	1 1	1 1 1		1 1 1		1 1 1		'	
	31 4.037-066.0	microfibre	350 mm	96 mm	light green	Combines the excellent cleaning properties of microfibres and the advantages of roller technology. No pad roller shaft	31																

[■] Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

DISC BRUSHES



Disc brushes come in different colours for easy selection of the required characteristics (white = soft, black = hard).

















6	ALL IN THE STATE OF THE STATE O
21	

	Order no.	Hardness / Brush type	Diameter	Colour	Quantity Price	Description		B 300 R I D / B 300 R I LPG B 250 R I + D 100 / B 250 R + D 100 B 200 R + D 110	B 200 R + D 50 B 200 R + D 75 B 150 R Adv + D 90	B 150 R Adv + D 75 B 150 R + D 90	B 150 K + D / 5 B 90 R configured / B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp B 90 R Adv Bp Pack / B 90 R Adv Bp / B 90 R Classic Bp Pack	B 90 R Classic Bp BD 50/70 R Classic Bp Pack / BD 50/70 R Classic Fleet Bp Pack / BD 50/70 R Classic Bp	BD 50/70 R Classic Fleet Bp B 95 RS + D 65 R	BD 50/40 Ks bp Pack / BD 50/40 Ks bp B 120 W + D 110 B 120 W + D 90	B 120 W + D 75 / B 80 W Bp + D 75 B 80 W Bp + D 65	B 60 W Ep + D 51 / B 60 C Classic + D 51 B 60 W Bp + D 65 B 60 W Bp + D 55	B 40 W Bp + D 51 B 40 W Bp + D 43	B 40 C Bp + D 51 B 40 C Bp + D 43	B 40 C Bp Classic + D 51 B 40 C Bp Classic + D 43		BD 50/50 C Bp Pack Classic / BD 50/50 C Bp Classic / BD 50/60 C Ep Classic BD 43/25 C Bp / BD 43/35 C Ep BD 38/12 C Bp Pack BD 43/25 C Bp / BD 43/35 C Ep BD 38/12 C Bp Pack BD 30/4 C Bp Pack
Disc brushes Disc brush	1 4.905-002.0	medium	550 mm	red	1 piece(s)	For all floors.	1 1				П		TI							1 1	
	2 4.905-007.0		550 mm	natural	1 piece(s)	Made of natural fibres for cleaning and polishing.	2						++			+	+-	+++	\Box		
	3 4.905-008.0		550 mm	white	1 piece(s)	For cleaning sensitive floors and polishing.	3						++			+	+	+++	\Box		
	4 4.905-009.0		550 mm	black	1 piece(s)	For stubborn dirt and deep cleaning. Only for insensitive surfaces.	4						\top								
	5 6.670-128.0	soft	280 mm		1 piece(s)	For cleaning and polishing sensitive floors.	5														
	6 6.670-127.0	medium	280 mm	red	1 piece(s)	Suitable for all common cleaning tasks, even on sensitive floors.	6														-
	7 6.907-154.0	very soft	385 mm	white	1 piece(s)	For cleaning sensitive floors and for polishing.	7														
	8 6.907-153.0	soft	385 mm	natural	1 piece(s)	Made of natural fibres for cleaning and polishing.	8						\Box	\Box		\top		\Box	\Box		
	9 6.907-151.0	medium	385 mm	red	1 piece(s)	For general cleaning.	9														
	10 6.907-152.0	hard	385 mm	black	1 piece(s)	For stubborn dirt and deep cleaning. For hard-wearing surfaces.	10												П		
	11 4.905-024.0	very soft	430 mm	white	1 piece(s)	For cleaning sensitive floors and polishing. Fits D 43.	11						\top								
	12 4.905-023.0	soft	430 mm	natural	1 piece(s)	Made of natural fibres for cleaning and polishing. Fits D 43.	12														
	13 4.905-022.0	medium	430 mm	red	1 piece(s)	For general cleaning of all floors. Standard with D 43.	13														•
	14 4.905-025.0	hard	430 mm	black	1 piece(s)	For stubborn dirt and deep cleaning.Only for hard-wearing surfaces. Fits D 43.	14														
	15 4.905-028.0	very soft	510 mm	white	1 piece(s)	For cleaning sensitive floors and polishing. Fits D 51.	15														
	16 4.905-027.0	soft	510 mm	natural	1 piece(s)	Made of natural fibres for cleaning and polishing. Fits D 51.	16														
	17 4.905-026.0	medium	510 mm	red	1 piece(s)	For general cleaning of all floors. Standard with D 51.	17								ı	-				•	
	18 4.905-029.0	hard	510 mm	black	1 piece(s)	For stubborn dirt and deep cleaning.Only for hard-wearing surfaces. Fits D 51.	18								Г						
	19 4.905-015.0	very soft	300 mm	white	1 piece(s)	For cleaning sensitive floors and polishing. Fits D 55.	19						+	\Box					\Box		
	20 4.905-016.0	soft	300 mm	natural	1 pioco(s)	Made of natural fibres for cleaning and polishing. Fits D 55.	20						+	+			\top	\Box	\Box		
		1 50.1	300 111111	Haturai	1 piece(s)	wade of flatoral fibres for cleaning and polishing. Fits D 33.	20										1 1 .	1 1	1 1	1 1	

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.













	Order no.	Hardness / Brush type Diameter	Colour	Quantity	Price Description		B 300 R I D / B 300 R I LPG B 250 R I + D 100 / B 250 R + D 100 B 200 R + D 110	B 200 R + D 90 B 200 R + D 75	B 150 R Adv + D 30 B 150 R Adv + D 75 B 150 R + D 90	B 150 R + D 75 B 90 R configured / B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp B 90 R Adv Bp Pack / B 90 R Adv Bp / B 90 R Classic Bp Pack	ack / BD 50/70 R Classic Flee	BD 50/70 R Classic Fleet Bp B 95 RS + D 65 R	B 120 W + D 110 B 120 W + D 90	B 120 W + D / S / B 80 W BP + D / S B 80 W Bp + D 65 B 60 W Ep + D 51 / B 60 C Classic + D 51		B 40 W Bp + D 51 B 40 W Bp + D 43	B 40 C Bp + D 51 B 40 C Bp Classic + D 51	B 40 C Bp Classic + D 43 B 40 C Ep + D 51	B 40 C EP + D 43 BD 50/50 C Bp Pack Classic / BD 50/50 C Bp Classic / BD 50/60 C Ep Classic BD 43/25 C Bp Pack / BD 43/25 C Bp / BD 43/35 C Ep BD 3312 C Bp Pack	סט זען יי בי של רמנת
Disc brush	22 4.905-017.0	hard 300 mm	black	1 piece(s)	For stubborn dirt and deep cleaning.Only for hard-wearing surfaces. Fits D 55.	22														1
	23 4.905-011.0	very soft 355 mm	white	1 piece(s)	For cleaning sensitive floors and polishing. Fits D 65.	23														1
	24 4.905-012.0	soft 355 mm	natural	1 piece(s)	Made of natural fibres for cleaning and polishing. Fits D 65.	24														
	25 4.905-010.0	medium 355 mm	red	1 piece(s)	For use in all standard cleaning applications. Standard with D 65.	25						•		•	•					1
	26 4.905-013.0	hard 355 mm	black	1 piece(s)	For stubborn dirt and deep cleaning.Only for hard-wearing surfaces. Fits D 65.	26														
	27 4.905-019.0	very soft 385 mm	white	1 piece(s)	For cleaning sensitive floors and for polishing. Fits D 75.	27							[
	28 4.905-020.0	soft 385 mm	natural	1 piece(s)	Made of natural fibres for cleaning and polishing. Fits D 75.	28							1							
	29 4.905-018.0	medium 385 mm	red	1 piece(s)	For all floors. For use in all standard cleaning applications. Standard for D 75.	29		•	-											
	30 4.905-021.0	hard 385 mm	black	1 piece(s)	For stubborn dirt and deep cleaning. Only for hard-wearing	30														
				, , , ,	surfaces. Fits D 75.			-	\perp	\perp			\perp		$\sqcup \sqcup$		\perp			- 1
	31 8.628-387.0	very soft 508 mm	white	1 piece(s)	surfaces. Fits D 75. For polishing.	31														J
	31 8.628-387.0 32 8.600-043.0					31 32													++++	+
		soft 508 mm	white	1 piece(s)	For polishing.								3							-
	32 8.600-043.0 33 8.600-042.0	soft 508 mm medium 508 mm	white black	1 piece(s) 1 piece(s) 1 piece(s)	For polishing. For cleaning sensitive floors and polishing.	32														- - -
	32 8.600-043.0 33 8.600-042.0 34 4.905-005.0	soft 508 mm medium 508 mm very soft 450 mm	white black blue white	1 piece(s) 1 piece(s) 1 piece(s) 1 piece(s)	For polishing. For cleaning sensitive floors and polishing. For use in all standard cleaning applications. For cleaning sensitive floors and polishing.	32 33 34														_ _ _
	32 8.600-043.0 33 8.600-042.0	soft 508 mm medium 508 mm very soft 450 mm soft 450 mm	white black blue	1 piece(s) 1 piece(s) 1 piece(s)	For polishing. For cleaning sensitive floors and polishing. For use in all standard cleaning applications. For cleaning sensitive floors and polishing. Made of natural fibres for cleaning and polishing. For all floors.	32 33														_ _ _ _
	32 8.600-043.0 33 8.600-042.0 34 4.905-005.0 35 4.905-004.0	soft 508 mm medium 508 mm very soft 450 mm soft 450 mm medium 450 mm	white black blue white natural	1 piece(s) 1 piece(s) 1 piece(s) 1 piece(s) 1 piece(s)	For polishing. For cleaning sensitive floors and polishing. For use in all standard cleaning applications. For cleaning sensitive floors and polishing. Made of natural fibres for cleaning and polishing. For all floors. For general cleaning. For stubborn dirt and deep cleaning.Only for hard-wearing	32 33 34 35														- - - -
	32 8.600-043.0 33 8.600-042.0 34 4.905-005.0 35 4.905-004.0 36 4.905-003.0	soft 508 mm medium 508 mm very soft 450 mm soft 450 mm medium 450 mm hard 450 mm	white black blue white natural red	1 piece(s)	For polishing. For cleaning sensitive floors and polishing. For use in all standard cleaning applications. For cleaning sensitive floors and polishing. Made of natural fibres for cleaning and polishing. For all floors. For general cleaning.	32 33 34 35 36														

■ Included in the scope of supply.
□ Available accessories. More Kärcher original accessories can be found on the following pages.

FLOOR SCRUBBERS / SCRUBBER DRIERS

DISC PADS



Pads have also proven successful on scrubber driers, especially on smooth surfaces. The pad colour indicates the type of use. Microfibre pads are particularly suitable for cleaning fine stoneware









Pad drive board	Order no.	Hardness / Brush type	Diameter	Colour	Quantity	Price Description		B 250 R I + D 100 / B 250 R + D 100 B 200 R + D 110	B 200 R + D 90 B 200 R + D 75	B 150 R Adv + D 90 B 150 R Adv + D 75 B 150 R + D 90	B 150 R + D 75 B 90 R configured B an D Adv Dree Br Dark / R an D Adv Br Dark	90 R Classic Bp	BD 50/70 R Classic Fleet Bp Pack BD 50/70 R Classic Bp	BD 50/70 R Classic Fleet Bp B 95 RS + D 65 R BD 50/40 RS Bp Pack / BD 50/40 RS Bp	B 120 W + D 110 B 120 W + D 90	B 120 W + D 75 / B 80 W Bp + D 75 B 80 W Bp + D 65	B 80 W Bp + 5 65 B 60 W Ep + D 51 B 60 C Classic + D 64	B 60 W Bp + D 65 B 60 W Bp + D 55	B 60 W Bp + S 65 B 40 W Bp + D 51	B 40 W B p + D 43 B 40 W B p 0 51 B 40 C B p + D 51	B 40 C Bp + D 43 B 40 C Bp C lassic + D 51	B 40 C Ep + D 51	B 40 C Ep + D 43 BD 50/50 C Bp Pack Classic / BD 50/50 C Bp Classic / BD 50/60 C Ep Classic BD 43/75 C Bn Dack / Bn 43/75 C Bn	BD 43/23 C Ep BD 43/35 C Ep BD 38/12 C Bp Pack	BD 30/4 C Bp Pack B 60/10 C
Pad drive board STRONG	1 4.762-594.	0	445 mm		1 piece(s)	Required for use of melamine pads, but can also be used for normal pads. Pad drive board with many hooks for holding pads. Extra-strong hold of pad at pad drive board	1																		П
	2 4.762-591.	0	375 mm		1 piece(s)	of D 90 cleaning head. 2 required.	2																		
	3 4.762-590.	0	335 mm		1 piece(s)	of D 75 cleaning head. 2 required. Required for use of melamine pads, but can also be used for normal pads. Pad drive board with many hooks for holding pads. Extra-strong hold of pad at pad drive board of D 65 cleaning head. 2 required.	3																		
	4 4.762-593.	0	479 mm		1 piece(s)		4																		
	5 4.762-592.	0	403 mm		1 piece(s)	Required for use of melamine pads, but can also be used for normal pads. Pad drive board with many hooks for holding pads. Extra-strong hold of pad at pad drive board of D 43 cleaning head.	5																	1 0	
Pad drive board	6 4.762-416.	0	530 mm		1 piece(s)	For cleaning with pads. With quick-change coupling and Centerlock.	6																		
	7 4.762-533.	0	403 mm		1 piece(s)	For cleaning with pads. With quick-change coupling and Centerlock. Fits D 43.	7] 🗆	
	8 4.762-534.	0	479 mm		1 piece(s)	For cleaning with pads. With quick-change coupling and Centerlock. Fits D 51.	8									\bot \top									
	9 4.762-445.	0	280 mm		1 piece(s)	For cleaning with pads. With quick-change coupling and Centerlock. Fits D 55.	9																		
	10 4.762-446.	0	335 mm		1 piece(s)	For cleaning with pads. With quick-change coupling and Centerlock. Fits D 65	10																		
	11 4.762-447.	0	375 mm		1 piece(s)	For cleaning with pads. With quick-change coupling and Centerlock. Fits D 75.	11																		
	12 8.600-041.	0	508 mm		1 piece(s)		12																		

☐ Available accessories. More Kârcher original accessories can be found on the following pages.



















		der no.	Hardness / Brush type	Diameter	Colour		Price	Description			B 250 R I + D 100 / B 250 R + D 100	200 R + D 90	B 200 R + D 75 B 150 R Adv + D 90	B 150 R Adv + D 75 B 150 R + D 90	B 90 K AdV D 105e BP Pack / B 90 K AdV D 105e BP / B 90 K Classic BP Pack B 90 R Classic BP Pack / B 90 R Pack /	BD 50/70 R Classic Fleet Bp Pack BD 50/70 R Classic Bo		BD 50/40 RS Bp Pack / BD 50/40 RS Bp B 120 W + D 110	B 120 W + D 90 B 120 W + D 75 / B 80 W Bp + D 75	B 80 W Bp + D 65 B 80 W Bp + S 65	B 60 VC Ep + D 51 B 60 CClassic + D 51	B 60 W Bp + D 65 B 60 W Bp + D 55 B 60 W Bp + S 65	B 40 W Bp + D 51 B 40 W Bp + D 43	B 40 W B p 0 51 B 40 C B p + D 51	B 40 C Bp + D 43 B 40 C Bp Classic + D 51	B 40 C EP + D 51 B 40 C EP + D 51 B 40 C EP + D 43 B 50 C EP + D 43 B 50 C EP + D 43	סי ר פון נומסטור / פון סט סי כבון	BD 38/12 C Bp Pack BD 30/4 C Bp Pack	B 60/10 C
Pad drive board	13 4.7	762-493.0		445 mm		1 piece(s)		For cleaning with pads. With quick-change coupling and Centerlock. Fits D 90.	13																				
	14 6.6	70-129.0		270 mm		1 piece(s)		Pad drive board for pad intake.	14			\top														\Box	\Box		
	15 6.9	007-150.0		355 mm		1 piece(s)		For cleaning with pads. With quick-change coupling and Centerlock.	15																				
Pads				<u> </u>																								$\rightarrow \rightarrow$	
Pad	16 6.3	869-015.0	hard	533 mm	black	5 piece(s)		For stubborn dirt and deep cleaning.	16	I										1.1		TI			\top	TTT	T = T		
		869-016.0	medium-hard	_		5 piece(s)		For cleaning extremely dirty floors and deep cleaning.	17				+	\dashv					\dashv	+	+				++	+++	+	\Box	\exists
		369-017.0	medium-soft	533 mm		5 piece(s)		For cleaning and cleaners of all types of floors.	18				\top		++					\top	$\dashv \dashv$			\top	++	+++	+	\Box	
		371-030.0 ■		508 mm		2 piece(s)		For restoring the protective film on hard and resilient flooring in conjunction with the D 51 or O 51 floor head. Please only use this on tough flooring surfaces.	19																				
		37-592.0						38 m long, 10 cm wide. Perforated strips to be torn off. The coarse dirt fleece is applied to the front of the pad and collects hair and lint.	20																				•
	21 8.6	37-944.0	soft	635 mm	white	5 piece(s)		White cleaning pad. The attached edges of the slats facilitate the cleaning process.	21																		Ш		•
	22 6.3	369-003.0	medium-soft	356 mm	red	5 piece(s)		For cleaning all types of floors.	22]] [
	23 6.3	369-002.0	medium-hard	356 mm	green	5 piece(s)		For cleaning heavily soiled floors and for deep cleaning.	23										[[
	24 6.3	869-001.0	hard	356 mm	black	5 piece(s)		For removing stubborn dirt and deep cleaning.	24			\perp]] [
	25 6.3	869-791.0	medium-soft	381 mm	red	5 piece(s)		For cleaning all floors.	25																				
		869-790.0	medium-hard	381 mm	green	5 piece(s)		For removing stubborn dirt and deep cleaning.	26											$\perp \perp$	$\perp \perp$	\perp		$\perp \perp$	$\perp \perp$	$\perp \perp \perp$	$\perp \! \! \perp \! \! \! \perp$	$\sqcup \sqcup$	\Box
		869-789.0	hard	381 mm	black	5 piece(s)		For removing stubborn contaminations and deep cleaning.	27								\Box			$\perp \perp$	$\perp \perp$			$\perp \perp$	$\perp \perp$	$\perp \perp \perp$	$\perp \perp \downarrow \downarrow$	$\sqcup \sqcup$	\Box
		369-469.0	very soft	432 mm		5 piece(s)		For perfect polishing results on sealed floors.	28			\perp		$\perp \perp$	$\perp \perp$				$\perp \downarrow \downarrow$	\perp	$\perp \downarrow \downarrow$	$\perp \perp$] [1 0		\sqcup	
	29 6.3	371-149.0	soft	432 mm	beige / natural	5 piece(s)		With natural hair, for polishing. Effectively removes scuff marks.	29																<u> </u>				
	30 6.3	371-081.0	soft	432 mm		5 piece(s)		For perfect polishing results on sealed floors.	30						Ш											1 0			
	31 6.3	369-470.0	medium-soft	432 mm	red	5 piece(s)		For cleaning all floors.	31																<u> </u>]		Ш	

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.















	Order no.	Hardness / Brush type	Diameter	r Colour	Quantity Price	Description		B 250 R I + D 100 / B 250 R + D 100 B 200 R + D 110 B 200 R + D 90	B 200 R + D 75 B 150 R Adv + D 90	B 150 R Adv + D 75 B 150 R + D 90	B 90 R configured B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp / B 90 R Adv Bp Pack B 90 R Adv Bp / B 90 R Classic Bp Pack / B 90 R Classic Bp	BD 50/70 R Classic Bp Pack BD 50/70 R Classic Fleet Bp Pack	BD 50/70 R Classic Bp BD 50/70 R Classic Fleet Bp	B 55 × 4 D 65 K BD 50/40 RS Bp Pack / BD 50/40 RS Bp B 120 W + D 110	B 120 W + D 90 B 120 W + D 75 / B 80 W Bp + D 75	B 80 W Bp + D 65 B 80 W Bp + S 65	B 60 W Ep + D 51 B 60 C Classic + D 51 B 60 W Bp + D 65 B 60 W Bp + D 65	200 W PF + S 65 B 40 W PF + S 65	040 W Dp + D 3	B 40 C Bp + D 51 B 40 C Bp + D 51	B 40 C Bp Classic + D 51 B 40 C Bp Classic + D 43		BD 50/50 C Bp Pack Classic / BD 50/50 C Bp Classic / BD 50/60 C Ep Classic BD 43/25 C Bp Pack / BD 43/25 C Bp BD 43/35 C Ep	BD 38/12 C Bp Pack BD 30/4 C Bp Pack B 60/10 C
Pad	32 6.369-472.0	medium-hard	_	_	5 piece(s)	For removing stubborn dirt and deep cleaning.	32																	
	33 6.369-473.0	hard	432 mm		5 piece(s)	For cleaning heavily soiled floors and for deep cleaning.	33							+										
	34 6.371-146.0	soft	500 mm	beige / natural	5 piece(s)	With natural hair, for polishing. Effectively removes scuff marks.	34																	
	35 6.369-468.0	soft	508 mm		5 piece(s)	Light grit, suitable for polishing floors.	35]					
	36 6.369-079.0	medium-soft	508 mm	red	5 piece(s)	For cleaning all types of floors.	36] [
	37 6.369-078.0	medium-hard	508 mm	green	5 piece(s)	For removing stubborn dirt and deep cleaning.	37] [
	38 6.369-077.0	hard	508 mm	black	5 piece(s)	For cleaning heavily soiled floors and for deep cleaning.	38]					
	39 6.371-153.0	medium-soft	280 mm	red	5 piece(s)	For cleaning all floors. Fits D 55.	39																	
	40 6.371-154.0	medium-hard	280 mm	green	5 piece(s)	For removing stubborn dirt and deep cleaning. Fits D 55.	40]						
	41 6.371-155.0	hard	280 mm	black	5 piece(s)	For cleaning heavily soiled floors and for deep cleaning. Fits D 55.	41																	
	42 6.371-000.0	medium-soft	650 mm	red	5 piece(s)	For cleaning all floors, in combination with the S 65 head.	42																	
	43 4.642-025.0	hard	650 mm		5 piece(s)	For restoring shine with the S 65 head, includes Velcro fastener.	43																	
	44 6.371-320.0	soft	508 mm		5 piece(s)	Without granulation, for polishing floors. Fits D 51.	44		\perp				\perp		$\sqcup \sqcup$	\perp			1					\coprod
	45 6.369-024.0	medium-soft	457 mm		5 piece(s)	For cleaning all floors. Fits D 90.	45																	
	46 6.369-023.0	medium-hard			5 piece(s)	For cleaning heavily soiled floors and for deep cleaning. Fits D 90.	46																	
	47 6.369-022.0	hard	457 mm	black	5 piece(s)	For removing stubborn dirt and deep cleaning. Fits D 90.	47						Ш	\perp					Ш		Ш			
Melamine pads		1			1									, ,										
Melamine pad	48 6.371-024.0				2 piece(s)	Melamine pad set for the effective cleaning of micro-	48							\perp		\perp		\perp	$\perp \perp$	$\perp \perp$				+
	49 6.371-022.0		-	grey/white	2 piece(s)	porous surfaces.	49					\square		_					+	+	\square	$\sqcup \sqcup$		+
	50 6.371-021.0	1	356 mm	-	2 piece(s)	-	50		+				1	1	++			++-	, -					+++
	51 6.371-025.0		508 mm		2 piece(s)	-	51		+						+++			1-1-	1 [+++
	52 6.371-029.0		122 mr-	grey/white	2 piece(s)	-	52		+				++	+	+++	\dashv		14	-	+-				+++
	53 6.371-023.0		432 mm		2 piece(s)	-	53		+				++	++	+++	+		++			+			
	54 6.371-019.0	<u>'</u>	265 mm	grey/white	2 piece(s)		54														\Box			

■ NEW □ Available accessories. More Kärcher original accessories can be found on the following pages.









Diamond pad	Order no.	Hardness / Brush type	Diameter	Colour	Quantity Pr	ce Description		B 250 R I + D 100 / B 250 R + D 100 B 200 R + D 110 B 200 R + D 90	B 200 R + D 75 B 150 R Adv + D 90	B 150 R Adv + D 75	B 150 R + D 75	B 90 R configured B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp / B 90 R Adv Bp Pack	B 90 R Adv Bp / B 90 R Classic Bp Pack / B 90 R Classic Bp BD 50/70 R Classic Bp Pack	BD 50/70 R Classic Fleet Bp Pack	BD 50/70 R Classic Floring	B 95 RS + D 65 R BD 50/40 RS BD Pack / BD 50/40 RS BD	B 120 W + D 110	B 120 W + D 90 B 120 W + D 75 / B 80 W Bp + D 75	B 80 W Bp + D 65 B 80 W Bp + S 65	B 60 W Ep + D 51 B 60 C Classic + D 51	B 60 W Bp + D 65 B 60 W Bp + D 55	B 60 W 50 F 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	B 40 W Bp + D 51 B 40 W Bp + D 43	B 40 W B p O 51 B 40 C B p + D 51	B 40 C Bp + D 43	B 40 C B classic + D 43	B 40 C Ep + D 51 B 40 C Ep + D 43 D	BD 30/30 C BP Pack / BD 43/25 C BP BD 43/25 C BP Pack / BD 43/25 C BP BD 43/35 C EP
Diamond pad	55 6.371-250.0	coarse	356 mm	white	5 piece(s)	For coarse cleaning/restoring. Removes small scratches,	55									Inl	ΙI	1.1	пΙ		Inl	T		T	LT	1 1	T	1 -
riamona paa	56 6.371-252.0		385 mm		5 piece(s)	for a clean, silky matt surface. For surface preparation	56		$\overline{}$	п	\Box		-				+		_	\vdash	H	++	+	+	+	++	++	++++
	57 6.371-256.0	coarse	432 mm		5 piece(s)	prior to using the yellow pad. Also suitable as a crystalli-	57		+		+		_				+	+-+		HH	\vdash	++	+	+	L			
	58 6.371-260.0	coarse	508 mm		5 piece(s)	sation pad for basic crystallisation.	58		+		+	+	П	ПГ	1 0	Нп					\vdash	++-	+	-	+	1	+++	
	59 6.371-246.0	coarse	280 mm	white	5 piece(s)		59		+		+		1		+-	++-					\Box	++-	-	+	++-	1	+++	++++
	60 6.371-258.0	coarse	457 mm		5 piece(s)		60		П	r	1							п		\forall	H	++	+	+	++	++	++	
	61 6.371-251.0	medium	356 mm		5 piece(s)	For coarse cleaning/restoring. Removes fine scratches for a	61		+-		+		\neg				++-	_	п	H		+	+	+	+	+	++	111
	62 6.371-253.0	medium	385 mm		5 piece(s)	more homogeneous and shinier surface. For surface prepa-	62												_	\vdash	\Box	++	+	+	+		++	
	63 6.371-259.0	medium	457 mm		5 piece(s)	ration prior to using the green diamond pad. Also suitable	63		- п		1	+++								H	\vdash	+	+	+	+	+	++	+++
	64 6.371-257.0	medium	432 mm		5 piece(s)	as a crystallisation pad for high-gloss crystallisation.	64		+-		+	++	+				+++	_		\square	\vdash	++	+	+				
	65 6.371-261.0	medium		yellow	5 piece(s)		65		+		+	+	П	ПГ	1 1						\vdash	++	. - 	+	H	1	╁┼┼	+-+-
	66 6.371-247.0		280 mm		5 piece(s)	For coarse cleaning/restoring. Removes fine scratches for a more homogeneous and shinier surface. For surface	66								† <u> </u>												#	
		fine	356 mm	green	5 piece(s)	preparation prior to using the green diamond pad. For effortless polishing of laminated floors, terrazzo and	67		+	+	+		$\neg \vdash \vdash$	\vdash	+		+	+	п	H		++	+	+	+	++	++	
	67 6.371-235.0			J					_		+			\vdash	+	+	+		_	\vdash	+	++	+	+	++	++	++	+++
	67 6.371-235.0 68 6.371-236.0			green		natural stone surfaces. For maintenance cleaning after	68							ı I		\perp						1 1	\rightarrow	+	+			
	68 6.371-236.0	fine	385 mm		5 piece(s)	using white and yellow pads. As a crystallisation pad for	68 69		-		+		\top							+	+							+ +-+
	68 6.371-236.0 69 6.371-238.0	fine fine	385 mm 432 mm	green	5 piece(s) 5 piece(s)		69														Ħ	-		+	屵] [
	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0	fine fine fine	385 mm 432 mm 508 mm	green green	5 piece(s) 5 piece(s) 5 piece(s)	using white and yellow pads. As a crystallisation pad for	69 70															1]		#		1	
	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0 71 6.371-233.0	fine fine fine	385 mm 432 mm 508 mm 280 mm	green green green	5 piece(s) 5 piece(s) 5 piece(s) 5 piece(s)	using white and yellow pads. As a crystallisation pad for	69] []	3					
icrofibre pad	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0	fine fine fine	385 mm 432 mm 508 mm	green green green	5 piece(s) 5 piece(s) 5 piece(s)	using white and yellow pads. As a crystallisation pad for	69 70 71															[
	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0 71 6.371-233.0	fine fine fine fine fine	385 mm 432 mm 508 mm 280 mm	green green green green	5 piece(s) 5 piece(s) 5 piece(s) 5 piece(s)	using white and yellow pads. As a crystallisation pad for	69 70 71															1						
licrofibre pad licrofibre pad	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0 71 6.371-233.0 72 6.371-239.0	fine fine fine fine fine microfibre	385 mm 432 mm 508 mm 280 mm 457 mm	green green green green	5 piece(s) 5 piece(s) 5 piece(s) 5 piece(s) 5 piece(s) 5 piece(s)	using white and yellow pads. As a crystallisation pad for high-gloss crystallisation.	69 70 71 72															1						
	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0 71 6.371-233.0 72 6.371-239.0 73 6.905-060.0	fine fine fine fine fine microfibre microfibre	385 mm 432 mm 508 mm 280 mm 457 mm	green green green green green white	5 piece(s)	using white and yellow pads. As a crystallisation pad for high-gloss crystallisation. Excellent cleaning power. Also effectively cleans fine stone	69 70 71 72															1						
	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0 71 6.371-233.0 72 6.371-239.0 73 6.905-060.0 74 6.371-271.0	fine fine fine fine fine fine fine microfibre microfibre microfibre	385 mm 432 mm 508 mm 280 mm 457 mm 356 mm 508 mm	green green green green green white	5 piece(s)	using white and yellow pads. As a crystallisation pad for high-gloss crystallisation. Excellent cleaning power. Also effectively cleans fine stone	69 70 71 72																					
	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0 71 6.371-233.0 72 6.371-239.0 73 6.905-060.0 74 6.371-271.0 75 6.369-961.0	fine fine fine fine fine fine fine microfibre microfibre microfibre microfibre	385 mm 432 mm 508 mm 280 mm 457 mm 356 mm 508 mm 533 mm	green green green green green green white white white	5 piece(s)	using white and yellow pads. As a crystallisation pad for high-gloss crystallisation. Excellent cleaning power. Also effectively cleans fine stone	69 70 71 72 73 74 75						-									[[] [] [] [] [] [] [] [] [] [
	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0 71 6.371-233.0 72 6.371-239.0 73 6.905-060.0 74 6.371-271.0 75 6.369-961.0 76 6.371-078.0	fine fine fine fine fine fine fine microfibre microfibre microfibre microfibre microfibre microfibre microfibre	385 mm 432 mm 508 mm 280 mm 457 mm 356 mm 508 mm 533 mm 381 mm	green green green green green white white white white	5 piece(s)	using white and yellow pads. As a crystallisation pad for high-gloss crystallisation. Excellent cleaning power. Also effectively cleans fine stone	70 71 72 73 74 75 76					-													2		1	
	68 6.371-236.0 69 6.371-238.0 70 6.371-240.0 71 6.371-233.0 72 6.371-239.0 73 6.905-060.0 74 6.371-271.0 75 6.369-961.0 76 6.371-078.0 77 6.369-959.0	fine fine fine fine fine fine fine microfibre microfibre microfibre microfibre microfibre microfibre microfibre microfibre microfibre	385 mm 432 mm 508 mm 280 mm 457 mm 356 mm 508 mm 533 mm 381 mm 356 mm	green green green green green white white white white white white	5 piece(s)	using white and yellow pads. As a crystallisation pad for high-gloss crystallisation. Excellent cleaning power. Also effectively cleans fine stone	73 74 75 76 77																					

80 6.369-960.0 microfibre 457 mm white 5 piece(s)

Available accessories. More Kärcher original accessories can be found on the following pages.

SQUEEGEES, SQUEEGEE BLADES



Curved or straight squeegees are available. Suction lips are grooved as standard. Suction lips are available for particularly sensitive or rough floors.















13

	Order no.	Length	Colour	Quantity	Price	Description		B 300 R I D / B 300 R I LPG	B 250 R I + R 120 / B 250 R + R 120 B 250 R I + R 100 / B 250 R + R 100	B 250 R + D 100 B 200 R + D 110	B 200 R + R 90 / B 200 R + D 90 / B 150 R Adv + R 90 R 150 R Adv + D 90 / B 150 R + P 90 / B 150 R + D 90	B 200 R + R 75 / B 200 R + D 75 / B 150 R Adv + R 75 B 150 R Adv + D 75 / B 150 R + R 75	B 90 R configured / B 90 R Classic Bp Pack / B 90 R Classic BF B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp / B 90 R Adv Bp	BD 50/70 R Classic Bp Pack / BD 50/70 R Classic Fleet Bp Pac BD 50/70 R Classic Fleet Bp B 95 RS + R 75 / B 95 RS + R 65 / B 95 RS + D 65 R	BR 55/40 RS Bp Pack / BR 55/40 RS Bp BD 50/40 RS Bp Pack / BD 50/40 RS Bp	B 120 W + D 110 B 120 W + R 90 / B 120 W + D 90 B 130 W + D 75 / R 130 W + D 75	B 80 W Bp + R 75 / B 80 W Bp + D 75	B 80 W B p + R 65 / B 80 W B p + D 65 / B 80 W B p + S 65 B 60 W E p R 55 / B 60 W E p + D 51	B 60 C Classic + R 55 / B 60 C Classic + D 51 / B 60 W Bp + R 5	B 60 W Bp + R 65 / B 60 W Bp + D 65 B 60 W Bp + S 65	B 40 W Bp + R 55 / B 40 W Bp + D 51 / B 40 W Bp + R 45 B 40 W Bp + D 43 / B 40 W Bp O 51 / B 40 C Bp + R 55	B 40 C Bp + D 51 / B 40 C Bp + R 45 / B 40 C Bp + D 43 B 40 C Bp Classic + R 55 / B 40 C Bp Classic + D 51 / B 40 C Bp	B 40 C Bp Classic + D 43 / B 40 C Ep + R 55 / B 40 C Ep + D 51 B 40 C Ep + R 45 / B 40 C Ep + D 43	BD 49/20 C Bp Pack Liassac / DD 309/20 C Dp Liassac / DD 33/25 C Bp Pack BD 43/25 C Bp	BD 43/35 C Ep BR 45/22 C Bp Pack	BD 38/12 C Bp Pack BR 35/12 C Bp Pack	BR 40/10 C I Adv BR 40/10C	BR 30/4 C Bp Pack / BR 30/4 C Adv / BR 30/4 C BR 30/4 C + MF	BD 30/4 C Bp Pack B 60/10 C
Squeegee, complete				,																									
V-squeegee	1 4.777-079.0	900 mm	transparen	t 1 piece(s)		900 mm-long, V-shaped squeegee with suction lips made from wear- and oil-resistant polyurethane with a long lifetime and for all floors. With spirit level for precise adjustment.	1]							3 O O					
	2 4.777-080.0	1000 mm	transparen	t 1 piece(s)		Suitable for all conventional floors and with very good gliding properties on crevices: V-shaped squeegee with length of 1000 mm and suction lips made from wear-resistant polyurethane with a long lifetime.	2																						
	3 4.777-081.0	1100 mm	transparen	t 1 piece(s)		With adjustable support rollers and spirit level for precise adjust- ment: V-shaped squeegee, 1100 mm long. Suction lips made from robust, oil-resistant and transparent polyurethane.	3																						
	4 4.777-078.0	1200 mm	transparen	t 1 piece(s)		V-shaped squeegee with length of 1200 mm and adjustable support rollers. Oil-resistant, fluted suction lips made from robust polyure-thane for all conventional floors. Special sliding properties on crevices.	4					1																	
	5 4.777-085.0		transparen	t 1 piece(s)		V-shaped, 1200 mm-long squeegee, specially developed for type B 250 scrubber driers. Suction lips made from oil-resistant and transparent polyurethane with special sliding properties.	5																						
	6 4.777-082.0	1400 mm	transparen	t 1 piece(s)		V-shaped, 1400 mm-long squeegee suitable for type B 250 scrubber driers. The particularly streamlined design of the suction port improves the suction characteristics.	6																						
Squeegee, straight	7 4.777-008.0	300 mm	blue	1 piece(s)		Straight, oil-resistant.	7												Ш'		Ш	Ш					\perp		
	8 4.777-324.0		grey	1 piece(s)		For tackling oil and grease in areas such as kitchens or workshops.	8												'	$\Box\Box$	ш	$\sqcup \sqcup$	$\perp \downarrow \downarrow$	$\perp \perp$	$\sqcup \sqcup$	$\perp \!\!\! \perp \!\!\! \perp$	\perp		$\perp \perp \perp$
	9 4.777-097.0		blue	1 piece(s)		Straight, standard.	9	\perp						$\perp \perp$			\perp	\perp	Ш'	$\Box\Box'$	Ш	ш	$\perp \perp$	$\perp \perp$	Ш	\square		Ш'	Ш
	10 4.777-098.0	■ 435 mm	grey	1 piece(s)		Straight, oil-resistant.	10										$\perp \perp$	\perp	'	Ш'	Ш	Ш	$\perp \perp \perp$	$\perp \perp$	$\sqcup \sqcup$	$\perp \!\!\! \perp \!\!\! \perp$		<u> </u>	Ш
	11 4.777-406.0	850 mm	blue	1 piece(s)		Straight, without support rollers. Soft natural rubber suctionlips.	11											Ш	ot^{-1}	$\Box\Box$		-			-	للـــ	\Box	$\perp \perp^{-1}$	$\perp \perp \perp$
	12 4.777-401.0			t 1 piece(s)		Straight, with support rollers. Suction lips of oil-resistant, transparent	12	\perp																		لـلــ	\perp	↓	\Box
	13 4.777-402.0			t 1 piece(s)		polyurethane.	13							$\perp \perp$					'		Ш	Ш	$\perp \perp$	$\perp \perp$	Ш	$\perp \! \! \perp \! \! \! \perp$	\perp	<u> </u>	Ш
	14 4.777-403.0			t 1 piece(s)			14	$\perp \perp$	\perp					$\perp \perp$			1	\perp	'	Щ'	$\sqcup \sqcup$	$\sqcup \sqcup$	\perp	\perp	$\sqcup \sqcup$	$\perp \! \! \perp \! \! \! \perp$	\vdash	<u> </u>	$\perp \perp \perp$
	15 4.777-404.0	1180 mm	transparen	t 1 piece(s)			15												<u>'</u> للـــــــــــــــــــــــــــــــــــ	$oxedsymbol{oxedsymbol{oxedsymbol{eta}}}'$								<u>'</u>	

16 4.777-405.0 1420 mm transparent 1 piece(s)

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.









	Order no.	Length	Colour	Quantity	Price	Description		B 300 R I D / B 300 R I LPG R 250 R I + R 120 / R 250 R + R 120	B 250 R I + R 100 / B 250 R I + D 100 / B 250 R + R 100 B 250 R + D 100	B 200 R + D 110 B 200 R + R 90 / B 200 R + D 90 / B 150 R Adv + R 90		B 150 R Adv + D 75 / B 150 R + R 75 / B 150 R + D 75 B 90 R configured / B 90 R Classic Bp Pack / B 90 R Classic Bp B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp 7 B 90 R Adv Bp Pack	leet Bp Pac	BD 50/70 R Classic Fleet Bp B 95 RS + R 75 / B 95 RS + R 65 / B 95 RS + D 65 R B 85 RS + R 75 / B 95 RS + R 65 / B 95 RS + D 65 R	BD 50/40 RS Bp Pack / BD 50/40 RS Bp B120 W + D 110	B 120 W + R 90 / B 120 W + D 90 B 120 W + R 75 / B 120 W + D 75	B 80 W Bp + R 75 / B 80 W Bp + D 75 B 80 W Bp + R 65 / B 80 W Bp + D 65 / B 80 W Bp + S 65 B 60 W Ep E 6 / B 60 W Ep + D 64	B 60 C Classic + R 55 / B 60 C Classic + D 51 / B 60 W Bp + R 55 B 60 W Bp + D 55		B 40 W Bp + R 55 / B 40 W Bp + D 51 / B 40 W Bp + R 45 B 40 W Bp + D 43 / B 40 W Bp O 51 / B 40 C Bp + R 55 B 40 C Rn + D 51 / B 40 C Rn + R 45 / R 40 C Rn + D 43	- U	B 40 C Ep + R 45 / B 40 C Ep + D 43 BD 50/50 C Bp Pack Classic / BD 50/50 C Bp Classic / BD 50/60 C Ep Classic	BD 43/25 C Bp BD 43/35 C Ep	BR 45/22 C Bp Pack BD 38/12 C Bp Pack BP 38/12 C Rp Pack	BR 40/10 C I Adv BR 40/10 C	BR 30/4 C Bp Pack / BR 30/4 C Adv / BR 30/4 C BR 30/4 C + MF	BD 30/4 C Bp Pack B 60/10 C
Squeegee, curved	17 8.633-816.0		transparent			Curved, with support rollers. Suction lips made fromoil-resistant	17																				
	18 8.633-666.0	716 mm	transparent	1 piece(s)		polyurethane. Curved, with support rollers. Suction lips of oil-resistant,transparent polyurethane.	18							1													
	19 4.777-416.0	850 mm	blue	1 piece(s)		Curved, without supporting rollers. Soft natural rubber suctionlips.	19																				
	20 4.777-100.0	850 mm	transparent	1 piece(s)		Curved, with support rollers. Suction lips of oil-resistant, transparent	20																				
	21 4.777-411.0	850 mm	transparent	1 piece(s)		polyurethane.	21	\perp																		\Box	
	22 4.777-101.0			1 piece(s)			22	\perp		$\sqcup \sqcup$	\perp	$\perp \perp$						$\perp \perp$								\longrightarrow	\perp
	23 4.777-412.0	+	+	1 piece(s)	-		23	+						\perp				\perp								+++	\perp
	24 4.777-413.0	_		1 piece(s)			24	-										++								++	+
	25 4.777-414.0 26 4.777-415.0	+		1 piece(s)	-		25					++		-				++								\longrightarrow	+
Squeegee, offset	27 4.777-002.0	1400 mm 1160 mm		1 piece(s) 1 piece(s)		Specially angled squeegee with particularly wide swivel range. Suction lip made from oil-resistant, transparent polyurethane withespecially long working time. With support rollers.	27																				
Squeegees for suction bars						manageday fong marking time. That support folicis.													Щ							\dashv	
Suction lips for V-squeegee	28 6.273-023.0	1010 mm	transparent	2-part		Suction lip set, fluted and developed for V-shaped squeegees with length of 900 mm. The suction lips are made of wear- and oil-resistant polyurethane and are suitable for all floors.	28																				
	29 6.273-026.0	1542 mm	transparent	2-part		Suction lip set consisting of front and rear suction lip for squeegee (V-shape) with length of 1400 mm. The front suction lip can be used twice, the rear one can be used four times. Made from polyurethane.	29																				
	30 6.273-016.0					Fluted suction lip set for all conventional floors. Made from oil-resistant, transparent polyurethane with a long lifetime and specially developed for V-shaped, 1200 mm-long squeegees.	30			0 0																	
	31 6.273-025.0					Suction lip set made from robust, transparent polyurethane with fluted structure for V-shaped squeegees with length of 1100 mm. Impressive sliding properties on all floors.	31																				
	32 6.273-024.0	1116 mm	transparent	2-part		Designed for our 1000 mm-long, V-shaped squeegees, this fluted suction lip set impresses on all floors. High-quality, oil-resistant design made from durable polyurethane.	32																				
		1010 mm	1	2-part	1	Slotted, made from natural rubber.	33				-															. — —	

Suction lips 33 8.640-378.0 1010 mm 2-part Slotted, made from natural rubber.


■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.



















								201100000000000000000000000000000000000	300 RI D/ B 300 RI LPG 250 RI + R 120 / B 250 R + R 120 250 RI + R 100 / R 250 RI + D 100 / R 250 R + R 100	250 R + D 100 250 R + D 100	200 R + R 90 / B 200 R + D 90 / B 150 R Adv + R 90 150 R Adv + D 90 / B 150 R + R 90 / B 150 R + D 90	200 R + R 75 / B 200 R + D 75 / B 150 R Adv + R 75 150 R Adv + D 75 / B 150 R + R 75 / B 150 R + D 75	B 90 R configured / B 90 R Classic Bp Pack / B 90 R Classic Bp Pack / B 90 R Adv Dose Bp / B 90 R Adv Bp Pack B 90 R Adv Bp Pack	D 50/70 R Classic Bp Pack / BD 50/70 R Classic Fleet Bp Pack / BD 50/70 R Classic Bp D 50/70 R Classic Bp D 50/70 R Classic Fleet Bp 95 RS + R 65 / B 95 RS + R 65 / B 95 RS + D 65 R	R 55/40 RS Bp Pack / BR 55/40 RS Bp D 50/40 RS Bp Pack / BD 50/40 RS Bp	120 W + D 110 120 W + R 90 / B 120 W + D 90 120 W + R 75 / B 120 W + D 75	80 W Bp + R 75 / B 80 W Bp + D 75 80 W Bp + R 65 / B 80 W Bp + D 65 / B 80 W Bp + S 65	60 W Ep R 55 / B 60 W Ep + D 51 60 C Classic + R 55 / B 60 C Classic + D 51 / B 60 W Bp + R 55	60 W Bp + D 55 60 W Bp + R 65 / B 60 W Bp + D 65	60 W Bp + S 65 40 W Bp + R 55 / B 40 W Bp + D 51 / B 40 W Bp + R 45	40 W Bp + D 43 / B 40 W Bp O 51 / B 40 C Bp + R 55 40 C Bp + D 51 / B 40 C Bp + R 45 / B 40 C Bp + D 43	40 C Bp Lassic + K 35 / B 40 C Bp Lassic + D 51 / B 40 C Bp Lassic + K 45 / B 40 C Bp C Bp C Bp + D 51 / B 40 C Ep + R 45 / B 40 C Ep + R	D 50/50 C Bp Pack Classic / BD 50/50 C Bp Classic / BD 50/60 C Ep Classic D 43/25 C Bp Pack D 43/25 C Bp Pack	0.4/3.5 EP 0.4/3.5 EP 8.4/2.7 E Bn Pack	N 39/12 C Bp Pack R 35/12 C Bp Pack	R 40/10 C I Adv R 40/10C	BR 30/4 C Bp Pack / BR 30/4 C Adv / BR 30/4 C BR 30/4 C + MF	D 30/4 C Bp Pack 60/10 C
Continuities	Order no.	Length	Colour	Quantity	Price	Description Standard Control of C	24	- 0	2 2 2	0 00 0	m m	m m	m m m	<u> </u>		m m m	m m	m m	6 6	8 8	<u> </u>	0 00 00	<u> </u>			<u> </u>	- □ □	<u> </u>
Suction lips	34 6.273-000.0	1300 mm	transparent	t 2-part		Fluted standard suction lip kit for all conventional floors. Made of oil-resistant, transparent polyurethane. With a length of 1300 mm, specially developed for use on angled squeegees.	34																					
	35 6.273-011.0	1300 mm	transparent	2-part		The closed profile of this suction lip kit is ideal for highly structured	35		\top																	\vdash	\Box	
						floors. High quality 1300 mm - made of oil-resistant polyurethane for use on angled squeegees.																						
	36 6.273-014.0	1300 mm	transparent	2-part		This slotted suction lip kit is made of wear-resistant and oil-resistant polyurethane to protect sensitive floors. With a length of 1300 mm - specially developed for use on angled squeegees.	36																					
	37 4.037-094.0	560 mm	transparent	2-part		Grooved, oil-resistant, polyurethane.	37		+																	+	+++	\Box
	38 4.037-059.0		transparent			Made from wear-resistant polyurethane Very durable and oil-resistant.	38		+									\dashv						+		\vdash	\Box	Ш
	39 6.670-234.0		transparent			Suction lip set specifically developed for our handy scrubber drier BD 30/4 C, consisting of front and rear suction lip. Made from	39																					•
	40 8.637-945.0	790 mm	white	1 pioco(c)		durable and oil-resistant polyurethane.	40		++	++-	+-											++-		++		++	$+\!+\!-\!+$	
	41 8.637-590.0		red	1 piece(s) 1 piece(s)		Made from wear-resistant polyurethane. Very durable and oil-resistant. Made from natural rubber.	40	-	+	+		++	+	+	+++				+	$\vdash\vdash\vdash$		+				+	++	
	42 6.273-302.0		blue	10 piece(s)		Rubber lip for squeegee 4.777-323.0.	42		++	++	+	++	+++	++	++				+	$\vdash\vdash\vdash$		++				H_{Γ}	+++	\dashv
	43 4.037-035.0		transparent		+	Grooved, oil-resistant, polyurethane.	43		++	++	+	++	+++	++	++	+		+	+	$\vdash\vdash\vdash$	+	++				++-	+++	\forall
	44 6.273-207.0		transparent			Standard, grooved, oil-resistant.	44		++	++	++	+++														+	+++	+
	45 6.273-229.0	_	transparent	+		Slotted, oil-resistant, polyurethane, for sensitive floors.	45		+	+		++						-								+	++	\forall
	46 6.273-213.0		blue	2-part		Fluted, standard, natural rubber.	46		++	+	+	++						\rightarrow								\vdash	\square	
	47 6.273-290.0		transparent			Closed, oil-resistant, for structured floors.	47											-		-						\Box		
	48 6.273-208.0		transparent			Standard, grooved, oil-resistant.	48		\top																			
	49 6.273-205.0	960 mm	transparent	2-part		Slotted, oil-resistant, for sensitive floors.	49																					
	50 6.273-214.0	960 mm	blue	2-part		Grooved, natural rubber.	50																					
	51 6.273-291.0		transparent			Closed, oil-resistant, for structured floors.	51								\Box											$\perp \perp$	\Box	Ш
	52 8.634-669.0					Oil-resistant, polyurethane, slotted.	52		$\perp \perp$	$\perp \perp$	$\perp \perp$	$\sqcup \sqcup$						\perp	\perp	Ш	\perp	$\perp \perp$				$\perp \perp$	$\perp \! \! \perp \! \! \! \perp \! \! \! \! \! \! \! \! \! \! \! \!$	\square
	53 6.273-294.0		transparent			Standard, grooved, oil-resistant.	53		++	+	1_	$\vdash \vdash$	$\perp \perp \perp$	\perp				\perp	\perp	\square	\perp	+		1		+	$+\!\!-\!\!\!\!-$	H
	54 6.273-206.0					Slotted, oil-resistant.	54		++	+	1010	+++						\perp		\square		+				\vdash	\sqcup	+
	55 6.273-209.0					Standard, grooved, oil-resistant.	55		++	++			+	-	++			+	+	HH	+	++		+	+	+	++	H
	56 6.273-215.0 57 6.273-293.0			2-part		Grooved, natural rubber. Closed, oil-resistant, for structured floors.	56 57		++	++-		+++	+		+++			+	+	$\vdash\vdash\vdash$		++-				+	+	H
	0.273-293.0	1090 111111	ri ai ishai 6111	Z-half		Closed, Oil-Tesistant, 101 Structured moors.	5/													шШ								

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.



								3300 R I D / B 300 R I LPG 2250 R I + R 120 / B 250 R + R 120	1250 RI + R 100 / B 250 RI + D 100 / B 250 R + R 100		1200 R + R 75 / B 200 R + D 75 / B 150 R Adv + R 75 1150 R Adv + D 75 / B 150 R + R 75 / B 150 R + D 75	B 90 R configured / B 90 R Classic Bp Pack / B 90 R Classic Bp B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp / B 90 R Adv Bp Pack B 90 R Adv Bp	10 S0/70 R Classic Bp Pack / BD 50/70 R Classic Fleet Bp Pack / BD 50/70 R Classic Bp ND 50/70 R Classic Fleet Bp	195 RS + R 75 / B 95 RS + R 65 / B 95 RS + D 65 R RR 55/40 RS Bp Pack / BR 55/40 RS Bp	10 50/40 RS BP Pack / BD 50/40 RS BP 1120 W + D 110 1120 W + R 90 / B 120 W + D 90	1120 W + R 75 / B 120 W + D 75 180 W Bp + R 75 / B 80 W Bp + D 75 90 W Bp + R 75 / B 80 W Bp + D 75	100 W BD+ R03/ B 60 W BD+ D03/ B 60 W BD+ 3 03 100 W BD+ R03/ B 60 W BD+ D03/ B 60 W BD+ D03 100 W BD+ D 67/ B 67/ F G F G F G F G F G F G F G F G F G F	1 60 V Bp + R 55 / B 60 V C (1835)(C + D 31 / B 60 W Bp + R 35 160 W Bp + D 55 160 W Bp + R 65 / B 60 W Bp + D 65	160 W B p + S 65 140 W B p + R 55 / B 40 W B p + D 51 / B 40 W B p + R 45	440 W Bp + D 43 / B 40 W Bp O 51 / B 40 C Bp + R 55 140 C Bp + D 51 / B 40 C Bp + R 45 / B 40 C Bp + D 43 140 C Bp Classic + R 55 / B 40 C Bp Classic + D 51 / B 40 C Bp Classic + R 45		ID 50/50 C Bp Pack Classic / BD 50/50 C Bp Classic / BD 50/60 C Ep Classic ID 43/25 C Bp Pack	1D 43/25 C Bp 1D 43/35 C Ep 1R 45/22 C Bn Park	10 38/12 C Bp Pack RR 35/12 C Bp Pack RR 40/10 C I Adv	R 40/10C R 30/4 C Bp Pack / BR 30/4 C Adv / BR 30/4 C	BR 30/4 C + MF BD 30/4 C Bp Pack B 60/10 C
Custian line	Order no.	Length	Colour	Quantity	Price	Description Chardend proposed ail posiebook		- - -				ш ш ш	, 10 10	ш ш і		ш ш п			, , , , , ,	ш ш ш		ш ш і				ш ш ш
Suction lips	58 6.273-252.0		transparen	+		Standard, grooved, oil-resistant.	58				+						+	++	+		+++				+++	+
	59 6.273-296.0 60 6.273-340.0					Closed, oil-resistant, for structured floors.	59 60			+						+++	+	++	+		+++	++	++		+++	
			transparen	+		Grooved, oil-resistant, polyurethane, for sensitive floors.					++		+		-	+++	++	++	+		+++	+	++		+++	+
	61 6.273-210.0 62 6.273-216.0		transparen	_	+	Standard, grooved, oil-resistant.	61			+	++		+++	+		+++	++		+++			+	++		+++	+
	63 6.273-295.0		transparen	_	+	Slotted, oil-resistant.	63			+	++		+	+		+++	+		++			++	++		+++	+
	64 6.680-373.0		transparen	4-part		Closed, oil-resistant, for structured floors. Wear- and oil-resistant, four-part suction lip set made from polyure-thane for our B 300 R I combined scrubber drier/vacuum sweeper. The set consists of a front and rear suction lip.	64																			
	65 6.680-372.0			4-part		Four-part suction lip set, consisting of front and rear suction lip. Standard set for our B 300 R I combined scrubber drier/vacuum sweeper.	65																			
Set suction lips Linatex	66 6.670-235.0	•				Suction lip set specifically developed for our handy scrubber drier BD 30/4 C, consisting of front and rear suction lip. Made from natural rubber.	66																			
Suction lip set, oil-resistant, 10x BR 40/10	67 4.035-288.0		grey	10 piece(s)		Set, consisting of 10 oil-resistant suction lips, to be used with our BR 40/10 scrubber drier.	67																			
Suction lip set 10x BR 40/10	68 4.035-253.0	■ 435 mm	blue	10 piece(s)		Rubber lip for squeegees 4.777-097.0.	68																			

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

HOME BASE ACCESSORIES



With the Home Base accessories, you can make life easier and work more efficiently. You can store utensils for manual cleaning, such as the wiping mop, additional cleaning agent bottles, cloths, utensils basket and much more, easily and securely right on the machine so that they are always within easy reach. This enables you to be prepared for all eventualities, avoid unnecessary walking and save valuable time.

















1	4	
13	I	

	Order no.	Quantity	Price Description		B 200 R + D 110 / B 200 R + R 90 / B 200 R + D 90 B 200 R + R 75 / B 200 R + D 75 / B 150 R Adv + R 90 B 150 R Adv + D 90 / B 150 R Adv + R 75 / B 150 R Adv + D 75 / B 150 R + R 75 / B 150 R + D 75 / B 150 R + R 75 / B 150 R
Home Base accessories	1 4 070 075 0	1 4 =:===(a)	Useli and advates life for attentionant to Users Dans unit of Visionan annihilation		
Universal hook kit	1 4.070-075.0	1 piece(s)	Hook and adapter kit for attachment to Home Base rail of Kärcher scrubber driers. Ideal for space-saving storage of hoses (e.g. spray extraction attachment kit) on the machine.		
Home Base mop holder kit	2 4.035-096.0	-	Holder fits on machine for convenient wiping mop storage.	2	
	3 4.035-374.0	1 piece(s)		3	
	4 4.035-514.0	1 piece(s)		4	
	5 4.039-271.0	1 piece(s)	Mop holder allows you to carry a mop on the machine. Easy attachment, convenient handling.	5	
	6 9.753-023.0	1 piece(s)	Holder fits on machine for convenient wiping mop storage.	6	
Home Base Box Kit	7 4.035-406.0	1 piece(s)	Safe storage of cloths, cleaning agent bottles, etc., whilst cleaning.	7	
Home Base adapter	8 5.035-488.0	1 piece(s)	For attaching to the Home Base rail.	8	
Double hook	9 6.980-077.0	1 piece(s)	Suitable for attaching bin liners, bags, etc. to the machine – only in conjunction with Home Base adapter 5.035-488.0.	9	
Holder handhold grey	10 6.980-078.0	1 piece(s)	Accessory for attaching a mop/brush to the machine – only in conjunction with Home Base adapter 5.035-488.0.	10	
Bottle holder	11 6.980-080.0	1 piece(s)	Suitable for transporting spray bottles - only in conjunction withHome base adapter 5.035-488.0.	11	
Manual rinsing system	12 4.035-515.0	1 piece(s)	Allows the tank to be rinsed using the on-board fresh water. Includes hose, spray nozzle and hose hanger.	12	
Other		•			
Cleaning agent container, complete	13 4.070-006.0	1 piece(s)	Kit consisting of cleaning agent container and Home Base adapter. For connecting Home Base Rail.	13	

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

OTHER ACCESSORIES



Specially developed accessories extend the range of applications of our scrubber driers.















Miscellaneous Miscellaneou					
Add-on kit ecolzero 1 5.388-133.0 1 piece(s) With ecolzero for climate-neutral cleaning: as compensation for the CO ₂ 1	sp Classic / BD	BR 45/22 C Bp Pack BD 38/12 C Bp Pack	BR 35/12 C Bp Pack / BD 30/4 C Bp Pack	BR 40/10 C I Adv / BR 40/10C	BR 30/4 C Bp Pack
which is produced by using the machine, we support climate protection projects worldwide. ABS brush head impact protection					
ABS brush head impact protection 2 2.034-000.0 Extremely robust and stable impact protecting for protecting the brush head when driving close to walls or corners, or in the event of unexpected obstacles. Dirty water tank filter 3 6.414-976.0 1 piece(s) Improves airflow even when damp, thanks to modified filter material. 3			ם נ		
Filling hose 4 6.680-124.0 1.5 m 1 piece(s) Hose for convenient fresh water filling from all standard taps. Extension cable 5 6.647-022.0 20 m 1 piece(s) 20 m. KIK key, yellow 6 5.035-344.0 yellow 1 piece(s) Yellow operator key. Individual access rights can be granted or the display language selected with the grey key that is supplied with the machine.					
Extension cable 5 6.647-022.0 20 m 1 piece(s) 20 m. KIK key, yellow 6 5.035-344.0 yellow 1 piece(s) Yellow operator key. Individual access rights can be granted or the display language selected with the grey key that is supplied with the machine.		П	\Box	\Box	П
KIK key, yellow 6 5.035-344.0 yellow 1 piece(s) Yellow operator key. Individual access rights can be granted or the display language selected with the grey key that is supplied with the machine.			1 0		
display language selected with the grey key that is supplied with the machine.			\Box		T.
KIK key, grey 7 5.035-348.0 grey 1 piece(s) Key for supervisors. Authorised access for operator keys.					
		$\Box\Box$	\Box	Г	\Box
KIK key, white 8 4.035-076.0 white 1 piece(s) White key with keychain. Each key can be individually preset using the grey key supplied with the machine parameters are always the same. The keychain helps to identify the key. This allows parameters to be set for cleaning in summer or winter, in sunshine or rain, on sensitive and hard-wearing floors or in workshops and showrooms.					
KIK key set, yellow 9 4.035-408.0 yellow 5 piece(s) Key for operators. Cannot be adjusted.		П	\Box	\Box	\Box

KIK key set, yellow 9 4.035-408.0 yellow 5 piece(s) Key for operators. Cannot be adjusted.

■ Included in the scope of supply. □ Available accessories. More Kārcher original accessories can be found on the following pages.







	Order no.	Length	Colour	Quantity	rice Description		4	100 / B 250 R + D 100	75	B 150 R Adv + R 90 / B 150 R Adv + R 75 B 150 R Adv + D 90 / B 150 R Adv + D 75	B 150 R + R 90 / B 150 R + R 75 B 150 R + D 90 / B 150 R + D 75	B 90 R configured B 90 R Adv Dose Bp Pack / B 90 R Adv Bp Pack / B 90 R Classic Bp Pack	Adv Bp	/ BD 5	65 / B 95 RS + D	BD 50/40 RS Bp PacK / BD 50/40 RS Bp B 120 W + D 110 / B 120 W + R 90 / B 120 W + R 75 B 130 W + D 60 / B 130 W + R 75	/ Bp + S	8	B 60 W Ep R 55 / B 60 W Ep + D 51 B 60 C Classic + R 55 / B 60 C Classic + D 51	da w 00 a / cc x	+ ~ ·	B 40 C Bp + D 51 / B 40 C Bp + R 45 / B 40 C Bp + D 43 B 40 C Bp Classic + R 55 / B 40 C Bp Classic + D 51 / B 40 C Bp Classic + R 45	51 / B 40 C Ep + R 4	Classic / BD 80/100 W Bp Pack Classic Classic Fleet / BD 80/100 W Bp Pack Classic Fle	ck Classic / BD 50/50 C Bp Classic / BD	BD 50/60 C Ep Classic / BD 43/35 C Ep BR 45/22 C Bp Pack	BD 38/12 C Bp Pack BR 35/12 C Bp Pack / BD 30/4 C Bp Pack	BR 40/10 C I Adv / BR 40/10C BR 30/4 C Bp Pack BR 30/4 C Adv / BR 30/4 C / BR 30/4 C + MF B 60/10 C
KIK key set, white	10 4.035-064.0		white	5 piece(s)	5 white keys with keychain. Each key can be individually preset using the grey key supplied with the machine. This means that the machine parameters are always the same. The keychain helps to identify the key.	10																						
					This allows parameters to be set for cleaning in summer or winter, in sunshine or rain, on sensitive and hard-wearing floors or in workshops and showrooms.																							
Fleet management module EU	11 2.644-096.0			1 piece(s)	The web-based fleet management system Kärcher Fleet allows the com-	11																						
	12 2.644-113.0			1 piece(s)	plete real-time monitoring of your entire fleet in every detail. For Europe,	12																						
	13 2.644-093.0			1 piece(s)	Japan, Australia.	13													1									
	14 2.644-095.0			1 piece(s)		14			\perp	\perp	\perp	\perp	\perp				1	\perp								\perp	\perp	
	15 2.644-098.0			1 piece(s)		15	$\perp \perp$	$\perp \perp$	\perp	\perp	\perp	\perp	\perp			\perp	\perp	\perp	\perp							\perp	\perp	
	16 2.644-097.0			1 piece(s)		16																	\perp				\perp	\perp
	17 2.644-099.0			1 piece(s)		17	 					+	-		\vdash		-	+					-				+	+
	18 2.644-100.0 19 2.644-101.0			1 piece(s)		18			++	+	+	+	+			+	+	++				_					+	
Fleet management module NA	20 2.644-101.0			1 piece(s) 1 piece(s)	The web-based fleet management system Kärcher Fleet allows the com-	20	1"	++	++	++	\dashv	+	+			+	++	++	+	++						+		+
	21 2.644-114.0			1 piece(s)	plete real-time monitoring of your entire fleet down to the finest detail.	21	++	+	++	+	+	+	+	\vdash	++	++	++	+	++	++	+	+	+		++	+++	+	+
	22 2.644-103.0			1 piece(s)	For USA, Canada.	22	+	+	+	+	$\dashv \dashv$	\dashv	$\dashv \dashv$	\vdash	\Box	+		-						++-		+	+	+++
	23 2.644-105.0			1 piece(s)		23		\top		\top	\dashv		$\dashv \dashv$				1	+								$\dashv \uparrow$		+
	24 2.644-108.0			1 piece(s)		24																						
	25 2.644-107.0			1 piece(s)		25								□■														
	26 2.644-109.0			1 piece(s)		26																						
	27 2.644-110.0			1 piece(s)		27			$\perp \perp$	$\perp \perp$	$\perp \! \! \perp \! \! \! \perp$	\perp	$\perp \!\!\! \perp$			\perp	$\perp \perp$	\perp	\perp			$\perp \! \! \perp \! \! \! \perp$	\perp	$\perp \perp$		\perp		\perp
	28 2.644-111.0			1 piece(s)		28																						
Spray units	29 6.394-409.0			1 ninco(c)	For each corruing for cleaning or crustallicing	1 20 1	lala	Lolo	la L								ماماد			alolo	Lolo			- 1 1				
Pump spray bottle	29 6.394-409.0			1 piece(s)	For easy spraying for cleaning or crystallising.	29	Inlo	Inle	1111								الداد		ווחוו	11110	1010	ПП	וחוח					
Dosing aids DS 3 Cleaning Agent Dosing Station	30 2.641-811.0			1 piece(s)	Can be connected to the water tap; water and cleaning agent are simply filled into the fresh water tank. Can also be used with the ABS filling	30																						

system. Not for Dose variants.

Included in the scope of supply.
Available accessories. More Kärcher original accessories can be found on the following pages.















599



1		
L.,	-	
	T	-
_		

Wheels (hures		Order no.	Length	Colour	Quantity	Price	Description			B 300 R I D / B 300 R I LPG B 250 R I + R 120 / B 250 R I + R 100 / B 250 R I + D 100	B 250 R + R 120 / B 250 R + R 100 / B 250 R + D 100 B 200 R + D 110 / B 200 R + D 90 / B 200 R + D 75	B 200 R + R 90 / B 200 R + R 75 B 150 R Adv + R 90 / B 150 R Adv + R 75	B 150 R Adv + D 90 / B 150 R Adv + D 75 B 150 R + R 90 / B 150 R + R 75	B 150 R + D 90 / B 150 R + D 75	B SON CONTINGUES. B SON R Classic Bp Pack / B 90 R Adv Bp Pack / B 90 R Classic Bp Pack B 90 B Classic Bn	B 90 R Adv Dose Bp / B 90 R Adv Bp	BD 50/70 R Classic Bp Pack / BD 56/70 R Classic Bp BD 50/70 R Classic Fleet Bp Pack / BD 50/70 R Classic Fleet Bp	B 95 RS + R 75 / B 95 RS + R 65 / B 99 RS + D 65 R BR 55/40 RS Bp Pack / BR 55/40 RS Bp	BD 50/40 RS Bp Pack / BD 50/40 RS Bp B 120 W + D 110 / B 120 W + R 90 / B 120 W + R 75	B 120 W + D 90 / B 120 W + D 75 B 80 W Bp + R 75 / B 80 W Bp + S 65	B 80 W Bp + D 75 / B 80 W Bp + D 65 B 80 W Bp + R 65	B 60 W Ep R 55 / B 60 W Ep + D 51 B 60 C Classic + R 55 / B 60 C Classic + D 51	B 60 W Bp + R 65 / B 60 W Bp + R 55 / B 60 W Bp + D 55 B 60 W Bp + D 65			B 40 C Bp	B 40 C Ep + R 55 / B 40 C Ep + D 51 / B 40 C Ep + R 45 B 40 C Ep + D 43 B 70 C Ep + D 43 B 70 C Ep + D 43	BD 80/100 W Bp Classic Fleet / BD 80/100 W Bp Pack Classic Fleet BD 50/100 W Bp Pack Classic Fleet BD 50/50 C Bp Classic / BD 43/25 C Bp Pack	CEp	ack ack	BR 35/12 C Bp Pack / BD 30/4 C Bp Pack BR 40/10 C I Adv / BR 40/10C	BR 30/4 C Adv / BR 30/4 C / BR 30/4 C + MF B 60/10 C
Wheels/tyres Rear wheel, non-marking	31	6.680-376.0			1 piece(s)		High-quality, non-marking and oil-resistant solid rubber rear wheel.	31																								
Front wheel, standard	32	6.680-410.0			1 piece(s)		Effectively prevents tyre tracks on light surfaces. Front wheel made from high-quality, non-marking and oil-resistant solid	32		_							+	+											++-			
Fortist design and the	22	6 600 077.0			4 -:(-)		rubber. Avoids tyre tracks on light surfaces.	22		-						++	\perp				\perp					\perp					\vdash	\perp
Front wheel, non-marking, supergrip	33	6.680-377.0			1 piece(s)		For better ground contact, solid rubber wheel, prevents tyre tracks on light surfaces.	33																					'			
Supergrip, rear wheel	34	6.435-092.0		grey	1 piece(s)		For improving adhesion and increasing safety in curves, this oil-resistant	34																								
	35	6.438-010.0					rear wheel is suitable for the B 250 R ride-on scrubber drier (2 required). For improving adhesion and increasing safety in curves, this oil-resistant	35				•					+	+											+		$\dashv \uparrow$	+++
Tyres supergrip	36	6.435-403.0		vellow	1 niece(s)		rear wheel is suitable for the B 150 R ride-on scrubber drier (2 required).	36					-	++			++			+	+					++	++	+++			++	
Tyres, supergrip Sports hall attachment kit	_	4.744-162.0		yellow	1 piece(s) 1 piece(s)		Oil-resistant, with especially good traction. Reduces floor loading to < 0.5 N/mm², in accordance with DIN 18032.	37	-					+		1	+	+	+						+		+	++	+'		$\overline{}$	+
Wheel, oil resistant	_	6.435-702.0			1 piece(s)	-	Machine requires 2.	38						+	+			+											+		$\overline{}$	+
Supergrip front wheels	_	6.435-810.0		purple	1 piece(s)		The combination of the special tyre compound and the V-profile of these oil-resistant front wheel drums increases traction and provides good adhesion on slippery floors.	39																								
	40	6.435-855.0			1 piece(s)		For high traction on gradients of up to 18% on adherent surfaces.	40																								
Wiping flaps		1					Particularly suitable for use in underground car parks.																	ш							\bot	
Set of squeegee blades	41	4.035-404.0	1	1	1 piece(s)	L	Oil-resistant rubber squeegee blades on side of brush head.	41						L	1.1	ΙI	1.1	1-1	1.1	1.1	1.1	1.1			1.1	1.1	1.1	1.1	TI			
Modification kit, squeegee blades for brush head	_				1 piece(s)		Floating squeegee blades adapt to the surface. Fits D 90, D 75 and D 65.	42								$\dagger \dagger$		+														
Carpet kit			·																													
Carpet cleaning attachment kit	43	2.783-005.0			1 piece(s)		For intensive carpet cleaning: 2 suction lips for carpets + 1 blue rollerbrush + 1 RM 764 + 0.5 RM 769.	43																								
■ Included in the scope of supply		2.783-014.0			1 piece(s)		For intensive carpet cleaning: 2 suction lips for carpets + 2 blue rollerbrushes + 1 l RM 764 + 0.5 l RM 769.	44																								

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.

ATTACHMENT KITS



Useful accessories and attachment kits facilitate daily cleaning for excellent results.

They ensure greater safety, reduce the impact on the environment and are cost-effective.

















	F	7
16		No.

								B 300 R I D / B 300 R I LPG B 250 R I + R 120 B 250 R R + D 150 B 250 R R + D 150 B 250 R R 20 R 20 B 250 R R 20
Chandand valley bursh	Order no.	Length	Diameter	Quantity	Price	Description		
Standard roller brush Standard roller brush	1 6.906-375.0	700 mm	285 mm	1 piece(s)	1	Water-resistant universal bristles, durable, suitable for all surfaces.	1	
Standard side brushes	1 0.300 373.0	7 00 11111	200	T prece(s)		Trace resistant dinversal pristres, deliable, solitable reliable solitables.	-	
Side brush, standard	2 6.680-335.0		350 mm	1 piece(s)		With durable, water-resistant universal bristles. Suitable for all surfaces.	2	
	3 6.951-073.0		390 mm	1 piece(s)		Standard side brush with water-resistant universal bristles and a long lifetime. Suitable for all surfaces.	3	
	4 6.905-986.0		450 mm	1 piece(s)		Water-resistant universal bristles, durable, suitable for all surfaces.	4	
Spray extraction mounting kit		İ	ı		1			
Spray suction attachment kit	5 2.642-058.0			1 piece(s)		Fits B 150 R.	5	
	6 2.642-740.0 7 2.642-833.0			1 piece(s)		Fits B 80 W.	6	
	8 2.640-938.0			1 piece(s) 1 piece(s)		Facilitates cleaning in areas inaccessible to the machine.	8	
Other attachment kits	0 2.0 10 330.0			T prece(s)				
Attachment kit side brush right	9 2.643-691.0			1 piece(s)		For sweeping close to the edge on the right side: the side brush attachment kit with lifting arm extends the working width by 35 cm.	9	
Side brush attachment kit, left	10 2.643-692.0			1 piece(s)		For sweeping close to the edge on the left side: the side brush attachment kit with lifting arm extends the working width by 35 cm.	10	
Attachment kit scrubbing deck right	11 2.643-693.0			1 piece(s)		For wet cleaning close to the edge on the right side: side scrubbing deck with lifting arm. Extends the working width by 30 cm.	11	
Attachment kit scrubbing deck left				1 piece(s)		For wet cleaning close to the edge on the left side: side scrubbing deck with lifting arm. Extends the working width by 30 cm.	12	
Dose attachment kit for cleaning agent dosing unit	13 2.643-851.0			1 piece(s)		For easy dosing directly from the can.	13	
Side scrubbing deck	14 2.644-087.0					For wet cleaning close to the edge on the right side: side scrubbing deck with lifting arm. Extends the working width by 20 cm.	14	
Bin liner holder attachment kit	15 2.644-088.0			1 piece(s)		For wet cleaning close to the edge on the right side: side scrubbing deck with lifting arm. Extends the working width by 15 cm. Time-saving and useful accessory part: holder for convenient	15	
Diri iller noider attacılment Kit	10 4.039-209.0	_		1 hiere(2)		attachment of a bin liner or bin bag directly to the machine.	10	













		Order no	Length	Diameter	Quantity Price	Description		3300 R I D / B 300 R I LPG	3 250 R I + R 120 3 250 R I + R 100 / B 250 R I + D 100	B 250 R + R 120 B 250 R + R 100	3 250 R + D 100 3 200 R + D 110	3 200 R + R 90 3 200 R + D 90	3 200 R + R 75	3 150 R Adv + R 90	3 ISO R Adv + D 90 3 ISO R Adv + R 75	3 150 R Adv + D 75 3 150 R + R 90	3 150 R + D 90	3150R + D 75	3 90 R configured / B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp 3 90 R Adv Bp Pack / B 90 R Adv Bp / B 90 R Classic Bp Pack	3 90 R Classic Bp 3D 50/70 R Classic Bp Pack / BD 50/70 R Classic Fleet Bp Pack / BD 50/70 R Classic Bp	3D 50/70 R Classic Fleet Bp 3 120 W + D 110 / B 120 W + R 90 / B 120 W + D 90	B 120 W + R 75	B 80 W Bp + S 65 60 W Ep + D 51	55 / B 60 / B 60 W	60 W Bp + S 65 40 W Bp + R 55 / B 40 W Bp + D 51 / B 40 W Bp +	/ B 40 C Bp + R / B 40 C Bp + D Classic + D 51	40 C Bp Classic + R 55 / B 40 C Bp Classic + D 51 / B 40 C 40 C Bp Classic + D 43 / B 40 C Ep + R 55 / B 40 C Ep + D 5	43 50/50 C Bp C
Attachment kit for the 60 cm pre-sweep mop	17	Order no. 4.039-270.0	Length	Diameter	Quantity Price 1 piece(s)	Description The pre-sweep mop can sweep up coarse dirt and it prevents coarse dirt from getting onto the brush head and into the squeegee.	17																					
ABS drain hose ball valve	18	2.643-986.0 ■				Drain hose for metered draining of dirty water from the tanks in our BD 50/50 C Classic and BD 50/60 C Classic scrubber driers. Water flow regulation using a ball valve.	18																					
	19	2.643-977.0 ■				The drain hose enables convenient metered draining of dirty water from the tanks in our BD 43/25 C and BD 43/35 C scrubber driers. Water flow regulation using a ball valve.	19																					1
Protective roof, high, 2140 mm	20	2.643-944.0			1 piece(s)	High-quality protective roof fully closed at the top provides reliable protection against possible dangers. Total height of machine with roof: 2.14 m.	20																					
Protective roof, low, 2040 mm	21	2.643-696.0			1 piece(s)	High-quality protective roof without glass for optimal protection against falling objects.	21																					\Box
Protective roof	22	2.643-849.0			1 piece(s)	This high-quality protective roof for the B 250 R scrubber drier (height including protective roof 2170 mm) protects the operator from falling objects - tested according to EN IEC 60335-2-72.	22	С																				
	23	2.644-089.0				Robust steel construction. Complies with IEC 60335-2-72.	23																					\Box
Suction hose accessories		4.444-015.0	3.25 m		1 piece(s)	For vacuuming water out of corners or containers (e.g. freezers).	24																					
Support roller kit	25	2.641-773.0			1 piece(s)	Reduces the danger of damaging the floor through abrupt steering at high speeds, sharp breaking on corners or when turning on downhill slopes.	25																					
Working light	26	2.643-848.0			1 piece(s)	For operation in poorly lit areas.	26							\top	$\dashv \dashv$			\top	\top	$\dashv \dashv$	$\dashv \dashv$	$\dashv \dashv$	$\neg \neg$					\top
Working light (manufactured from 8/2018 onwards)		2.034-001.0				Working light for improving safety when working. With front and side lighting on the brush head.	27																					
Flashing beacon	28	2.643-850.0			1 piece(s)	This rotating light increases visibility and safety significantly during operation in dark buildings. The dimensions of the B 250 R remain	28																					
		4.039-267.0				unchanged with the attachment kit. Non-glare flashing beacon increases safety when working in dark							\perp					\perp										\perp

■ NEW □ Available accessories. More Kärcher original accessories can be found on the following pages.







		Order no.	Length	Diameter	Quantity	Price	Description		B 300 R I D / B 300 R I LPG	B 250 R I + R 120 B 250 R I + R 100 / B 250 R I + D 100		B 250 R + D 100 B 200 R + D 110	B 200 R + R 90 B 200 R + D 90	B 200 R + R 75 B 200 R + D 75	B 150 R Adv + R 90	1500 RACK - R 75	B 150 K AGO + U / 5 B 150 R + R 90	B 150 R + R 75	B 150 R configured / B 90 R Adv Dose Bp Pack / B 90 R Adv Dose Bp	ack / B 90 R Adv Bp / B 90 R Classic Bp Par p	leet Bp 120 W + R 90 / B 120 W + D 90	/ B 120 W + D 75 75 / B 80 W Bp + D 75 / B 80 W		c + R 55 / B 60 C D 65 / B 60 W Bp	/ B 40 W	D 43 / B 40 W Bp O 51 / B 40 C Bp + R 55 0 51 / B 40 C Bp + R 45 / B 40 C Bp + D 43 ssic + R 55 / B 40 C Bp Classic + D 51 / B 40	43 / B 40 C Ep + R 55 / B 40 C Ep + D 40 C Ep + D 43	C Bp Pack Classic / E C Bp Pack / BD 43/2
Flashing beacon	30	2.641-718.0			1 piece(s)		Increases the safety of the working environment.	30																				
		4.035-516.0			1 piece(s)			31																				ш
Auto-Fill		2.641-748.0			1 piece(s)		Automatic filling system. Water supply automatically stops when the	32																				
	33	4.035-345.0			1 piece(s)		tanks is full. With safety overflow.	33																				
		4.035-985.0			1 piece(s)			34																				
Water spraying system for side	35	2.643-843.0			1 piece(s)		The nozzles prevent dust dispersion when using the side brush,	35			Inln																	.
brush							whereby the water that is sprayed binds the dusts.																					سلا
Side brush attachment kit R100	36	2.643-846.0			1 piece(s)		Side brush, right and left. Includes lifting motor and deflector. Re-	36																				
							moves loose dirt around edges. Fits machines with brush head R 100.				"																	.
Side brush attachment kit R120	37	2.643-847.0			1 piece(s)		Side brush, right and left. Includes lifting motor and deflector. Re-	37																				
					' ''		moves loose dirt around edges. Fits machines with brush head R 120.																					.
						_		20					-	-	+	_	\rightarrow		+			-	-		\rightarrow		-	
2-point safety belt	1 38	6.989-732.0			1 piece(s)		2-point safety belt for ride-on scrubber driers B 250 R and B 250 R I.	1 381				_			1 1													
2-point safety belt	38	6.989-732.0			1 piece(s)		2-point safety belt for ride-on scrubber driers B 250 R and B 250 R I.	38																				'
							Increases operator work safety considerably.										\parallel										+	
Attachment kit StVZO		6.989-732.0 2.852-213.0			1 piece(s) 1 piece(s)		Increases operator work safety considerably. Necessary for operation on public roads: attachment kit complies	39												+								
							Increases operator work safety considerably.																					

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

BATTERIES, CHARGERS



Only chargers and batteries suitable for the machine ensure a long service life. Kärcher offers high quality batteries and chargers for all its machines.















E
14

4	1						13	14																	
	Order no.	Quantity	Battery voltage	Battery	Battery type	Price Description		B 250 R I + R 120 / B 250 R I + R 100 / B 250 R I + D 100 B 250 R + R 120 / B 250 R + R 100 / B 250 R + D 100		B 150 R Adv + D 90 / B 150 R Adv + R 75 / B 150 R Adv + D 75 B 150 R + R 90 / B 150 R + D 90 / B 150 R + R 75	B 150 R + D 75 B 90 R configured B 90 R Adv Dose Bp Pack	B 90 R Adv Bose Bp	B 90 R Adv Bp B 90 R Classic Bp Pack	B 90 R Classic Bp BD 50/70 R Classic Bp Pack	BD 50/70 R Classic Fleet Bp Pack BD 50/70 R Classic Bp / BD 50/70 R Classic Fleet Bp R 95 p5 + p 75 / R 95 p5 + p 65 / P 95 p5 + D 65 p	B 55 K 7 7 / B 53 K 5 + K 65 / B 59 K 5 + D 65 K BR 55/40 R5 Bp Pack BR 55/40 R5 Bp	BD 50/40 RS Bp Pack BD 50/40 RS Bp	B 120 W + D 110 / B 120 W + R 90 / B 120 W + D 90 B 120 W + R 75 / B 120 W + D 75	B 80 W Bp + R 75 / B 80 W Bp + D 75 / B 80 W Bp + R 65 B 80 W Bp + D 65 / B 80 W Bp + S 65 B 60 C Classic + R 55 / B 60 C Classic + D 51	B 60 W Bp + R 65 / B 60 W Bp + D 65 / B 60 W Bp + R 55 B 60 W Bp + D 55	B 40 W Bp + R 55 / B 40 W Bp + D 51 / B 40 W Bp + R 45 B 40 W Bp + D 43 / B 40 W Bp O 51 / B 40 C Bp + R 55	B 40 C Bp + D 51 / B 40 C Bp + R 45 / B 40 C Bp + D 43 B 40 C Bp Classic + R 55 / B 40 C Bp Classic + D 51 / B 40 C Bp Classic + R 45	B 40 C Bp Classic + D 43 BD 80/100 W Bp Classic BD 50/50 C Bp Pack Classic	BD 50/50 C Bp Classic BD 43/25 C Bp Pack BD 43/25 C Bp BD 38/12 C Bp Pack RP 35/12 C Bp Pack	BD 38/14 L BD PACK / BR 35/12 L BD PACK BR 30/4 C Bp Pack BD 30/4 C Bp Pack
Rechargeable batteries +		Quantity	Voltage	capacity	battery type	Price Description		- -			- - -	. - -			- - -	- - -				- - -	- - -		- - -		-1-1-
36 V Li-ion battery	1 4.654-016.0	_		7.5 Ah		High-performance lithium-ion battery BP 750 (36 V, 7.5 Ah).	1																		
Quick charger	2 6.654-354.0	1 piece(s)	36 V	7.5 Ah		The single-slot quick charger BC 1/7 is designed for high-pe formance lithium-ion batteries, type BP 750.	2																		-
Traction batteries						To make without societies, type at 750.																			
Battery	3 6.654-119.0	1 piece(s)	6 V	240 Ah	maintenance-free	4 required.	3																		
Batteries	1 4 4 6 5 4 000 0	1 nioco(s)	1 26 V	620 Ab	Llow maintenance	Call battory with contral filling system	4	Inlal	1.1	1.1	1.1		1.1	1.1	1 1	1 1					1 1		1 1 1		
Battery	4 4.654-000.0 5 4.035-181.0			630 Ah 170 Ah	low-maintenance maintenance-free	Cell battery, with central filling system. Maintenance-free 6 V traction battery with fleece technolo-	5		+	+	++		\dashv											+++	+++
	0 1.035 101.0	1 piece(s)	.	1707	Thankenance in ce	gy. 170 Ah capacity, four required.					•		•												
	6 6.654-124.0	1 piece(s)	6 V	180 Ah	maintenance-free	Gel battery, B 60 W, B 80 W and B 90 R, 4 required. BD 80/100 W, 6 required.	6																		
	7 4.035-182.0	1 piece(s)	12 V	105 Ah	maintenance-free	Machines with 36 V require three batteries.	7																	-	+
	8 6.654-093.0	1 piece(s)	12 V	76 Ah	maintenance-free	Gel traction battery, maintenance-free. With 12 V/76 Ah	8																		
						(5h). Two batteries required for 24 V machines, three required for 36 V machines.																			
	9 6.654-290.0	1 piece(s)	12 V	80 Ah	low-maintenance	Low-maintenance battery (12 V / 80 Ah) for Kärcher scrubber driers. Please note that 24 V machines need two batteries.	9																		
	10 8.629-184.0	1 piece(s)	6 V	285 Ah	maintenance-free	Maintenance-free AGM battery. With a capacity of 6 V / 285 Ah (C5) or 6 V / 312 Ah (C10).	10																		
	11 4.035-188.0	1 piece(s)	12 V	80 Ah	maintenance-free	Traction battery as a maintenance-free fleece variant, two required.	11																		
Battery kit	12 4.035-447.0		24 V	76 Ah	maintenance-free	Maintenance-free battery set. Includes 2 × 12 V batteries and connection cable.	12																		
	13 4.035-450.0	2-part	24 V	80 Ah	low-maintenance	Low-maintenance battery set. Includes 2 × 12 V batteries and connection cable.	13																		
	14 4.035-449.0	2-part	24 V	105 Ah	maintenance-free		14																		
	15 4.035-070.0	1 piece(s)	36 V	180 Ah	low-maintenance	Low-maintenance battery in tray includes central filling system and acid level indicator.	15											0 0							
	16 4.035-071.0	6-part	36 V	180 Ah	maintenance-free	Gel traction battery, maintenance-free, consists of 6 × 6 V / 180 Ah blocks. Includes connection cable.	16																		

■ NEW ■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.











		Order no.	Quantity	Battery	Battery capacity	Battery type Pric	e Description		B 250 RI+ R 120 / B 250 RI+ R 100 / B 250 RI+ D 100	B 250 R + R 120 / B 250 R + R 100 / B 250 R + D 100 B 200 R + D 110 / B 200 R + R 90 / B 200 R + D 90	B 200 R + R 75 / B 200 R + D 75 / B 150 R Adv + R 90 B 150 R Adv + D 90 / B 150 R Adv + R 75 / B 150 R Adv + D 75	B 150 R + R 90 / B 150 R + D 90 / B 150 R + R 75 B 150 R + D 75	B 90 R configured B 90 R Adv Dose Bp Pack	B 90 R Adv Dose Bp B 90 R Adv Bp Pack	B 90 K Auv Bp B 90 C Classic Bp Pack	B 50/70 R Classic Bp Pack	BD 50/70 R Classic Fleet Bp Pack BD 50/70 R Classic Bp BD 50/70 R Classic Fleet Bp	B 95 K3 + K 75 / B 95 K3 + K 65 / B 95 K3 + D 65 K BR 55/40 R5 Bp Pack RP 55/40 BC Rn	BD 50/40 RS Bp Pack BD 50/40 RS Bo	B 120 W + D 110 / B 120 W + R 90 / B 120 W + D 90 B 120 W + R 75 / B 120 W + D 75	B 80 W Bp + R 75 / B 80 W Bp + D 55 / B 80 W Bp + R 65 B 80 W Bp + D 65 / B 80 W Bp + S 65	B 60 C Classic + R 55 / B 60 C Classic + D 51 B 60 W Bp + R 65 / B 60 W Bp + D 65 / B 60 W Bp + R 55	B 60 W Bp + S 65	B 40 W Bp + R 55 / B 40 W Bp + D 51 / B 40 W Bp + R 45 B 40 W Bp + D 43 / B 40 W Bp O 51 / B 40 C Bp + R 55	B 40 C Bp + D 51 / B 40 C Bp + R 45 / B 40 C Bp + D 43 B 40 C Bp Classic + R 55 / B 40 C Bp Classic + D 51 / B 40 C Bp Classic + R 45 R 40 C Bn Classic + D 43	BD 80/100 W Bp Classic BD 50/50 C Bp Pack Classic	BD 50/50 C Bp Classic BD 43/25 C Bp Pack	BD 43/25 C Bp BD 38/12 C Bp Pack / BR 35/12 C Bp Pack BR 30/4 C Bn Pack	BD 30/4 C Bp Pack
Battery kit	17	4.035-388.0	4-part	24 V	170 Ah	maintenance-free	Maintenance-free battery set. Includes 4x 6 V batteries and connection cable with fleece technology.	17																					
	18	4.035-074.0	6-part	36 V	180 Ah	low-maintenance	Low-maintenance battery set 36 V / 180 Ah. Consists of 6 × 6 V / 180 Ah blocks. Includes connection cable.	18													1			\top					\top
	19	4.035-537.0	6-part	36 V	240 Ah	maintenance-free	Gel traction battery with high capacity, maintenance-free. Consists of 6 × 6 V blocks. Includes connection cable.	19																					
	20	4.035-387.0	4-part	24 V	180 Ah	maintenance-free	Maintenance-free battery set. Includes 4x 6 V batteries and connection cable.	20																					
	21	6.654-130.0	4-part	24 V	180 Ah	maintenance-free	Battery set, maintenance-free gel batteries, $4 \times 6 \text{ V} / 180 \text{ Ah}$ (C5). Includes connection cable.	21																					
	22	4.035-538.0	6-part	36 V	170 Ah	maintenance-free	Traction battery with maintenance-free fleece technology, consists of 6 × 6 V/170 Ah blocks. Includes connection cable.	22													1								
	23	4.035-440.0	4-part	24 V	180 Ah	low-maintenance	Low-maintenance battery set. Includes 4x 6 V batteries and connection cable.	23																					П
	24	6.654-070.0	4-part	24 V	180 Ah	low-maintenance	Battery set includes 4 × 6 V batteries and connection cable.	24								1	\top						\top						
	25	4.035-988.0	1 piece(s)	36 V	180 Ah	low-maintenance	Wet cell battery, with central filling system.	25																					
	26	4.654-307.0	6-part	36 V	180 Ah	maintenance-free	Fits B 150 R; B 150 R Bp.	26																					
	27	4.035-393.0	4-part	24 V	240 Ah	maintenance-free	Maintenance-free battery set. Includes 4x 6 V batteries and connection cable.	27																					
	28	4.654-306.0	6-part	36 V	240 Ah	maintenance-free	Fits B 150 R; B 150 R Bp.	28															\top						\Box
	29	4.035-987.0	1 piece(s)	36 V	240 Ah	low-maintenance	Wet cell battery, with central filling system.	29					\top		\top								\top						\Box
Lithium-ion battery	30	6.670-126.0	1 piece(s)	36.5 V	5.2 Ah	Li-lon	Lithium-ion exchangeable battery (36.5 V / 5.2 Ah) – can be charged in the quick charger with plug-in card intended for this purpose.	30																					•
Battery Chargers																													
Battery charger	31	4.654-001.0	1 piece(s)	36 V		separate	For low-maintenance batteries 36 V / 630 Ah (4.654-000.0 or 6.654-136.0). Charging current 65 A.	31																					
	32	6.654-367.0	1 piece(s)	24 V		separate	Standby battery charger for maintenance-free 24 V batteries of 70 to 105 Ah with order no. 6.654-093.0, 6.654-141.0 and 4.035-449.0.	32								•	• -												

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.



















		Order no.	Quantity	Battery voltage	Battery capacity	Battery type	Price	Description		B 250 R I + R 120 / B 250 R I + R 100 / B 250 R I + D 100	B 250 R + R 120 / B 250 R + R 100 / B 250 R + D 100 B 200 R + D 110 / B 200 R + R 90 / B 200 R + D 90 B 200 R + R 75 / B 200 R + D 75 / B 150 R Adv + R 90	B 150 R Adv + D 90 / B 150 R Adv + R 75 / B 150 R Adv + D 75	B 90 R configured	B 90 R Adv Dose Bp Pack B 90 R Adv Dose Bp	B 90 R Adv Bp Pack B 90 R Adv Bp	B 90 R Classic Bp Pack B 90 R Classic Bp	BD 50/70 R Classic Bp Pack BD 50/70 R Classic Fleet Bp Pack	BD 50/70 R Classic Bp / BD 50/70 R Classic Fleet Bp B 95 RS + R 75 / B 95 RS + R 65 / B 95 RS + D 65 R	BR 55/40 RS Bp Pack BR 55/40 RS Bp BD 50/40 RS Bp Pack	BD 50/40 RS Bp B 120 W + D 110 / B 120 W + R 90 / B 120 W + D 90	B 120 W + R 75 / B 120 W + D 75 B 80 W Bp + R 75 / B 80 W Bp + D 75 / B 80 W Bp + R 65	B 80 W Bp + D 65 / B 80 W Bp + S 65 B 60 C Classic + R 55 / B 60 C Classic + D 51	B 60 W Bp + R 65 / B 60 W Bp + D 65 / B 60 W Bp + R 55 B 60 W Bp + D 55	B 60 W Bp + R 55 / B 40 W Bp + D 51 / B 40 W Bp + R 45	0 51 / B 40 C Bp + R 55 R 45 / B 40 C Bp + D 43	B 40 C Bp Classic + R 55 / B 40 C Bp Classic + D 51 / B 40 C Bp Classic + R 45 B 40 C Bp Classic + D 43 B R 60 / 100 W Bn Classic	BD 80/100 W Bp Classic BD 50/50 C Bp Pack Classic BD 50/50 C Bp Classic	BD 43/25 C Bp Pack BD 43/25 C Bp BD 38/12 C Bp Pack / BR 35/12 C Bp Pack	וי
Battery charger	33	4.654-012.0	1 piece(s)	24 V		separate		24 V battery charger specially for 24 V battery set (order no.	33																\Box	\top			
	34	4.654-013.0	1 piece(s)	24 V		separate		4.035-388.0) with 170 Ah storage capacity. 24 V battery charger, specially for the high-performance, low-maintenance 24 V battery set with 180 Ah storage capacity (order no. 4.035-440.0).	34																				
	35	4.654-316.0	1 piece(s)	24 V		separate		External battery charger for charging the maintenance-free 180 Ah batteries (order no. 6.654-124.0).	35																				
	36	6.654-329.0	1 piece(s)	24 V		separate		Standby battery charger for maintenance-free 24 V batteries of 70 to 105 Ah with order no. 6.654-093.0, 6.654-141.0 and 4.035-449.0.	36																1				
	37	6.654-332.0	1 piece(s)	24 V		separate		Standby battery charger for low-maintenance 24 V batteries	37																Г	3 0			
	38	6.654-344.0		24 V		separate		with 80 Ah storage capacity (6.654-290.0 and 4.035-450.0).	38																[
	39	6.670-130.0	1 piece(s)			separate		Universal quick charger with a plug-in card. Please order power cord separately.	39																				-
	40	6.654-067.0	1 piece(s)	24 V		separate		For low-maintenance 80 Ah batteries (6.654-048.0 and 6.654-097.0).	40																				
	41	6.654-179.0	1 piece(s)	24 V		separate		For operation with 100-230 V. For low-maintenance 24 V batteries with 80 Ah (6.654-097.0).	41																				
	42	6.654-276.0	1 piece(s)	36 V		separate		Charger with 36 V / 12 A voltage, suitable for BD 50/ 40 RS Bp Pack. For battery 3 × 6.654-093.0.	42										• - •										
	43	6.654-072.0	1 piece(s)	24 V		separate		For low-maintenance 24 V batteries from 160-180 Ah (e.g. for 6.654-070.0).	43																				
	44	6.654-078.0	1 piece(s)	24 V		separate		For maintenance-free 160-180 Ah batteries (6.654-124.0 and 6.654-130.0).	44																				
	45	6.654-125.0	1 piece(s)	24 V		separate		For batteries 6.654-124.0 and 6.654-130.0.	45																				
		6.654-180.0				separate		For operation with 100-230 V. For maintenance-free 24 V batteries 160-180 Ah (6.654-124.0 and 6.654-130.0).	46																				
	47	6.654-120.0	1 piece(s)	24 V		separate		For maintenance-free batteries 24 V / 240 Ah (6.654-119.0).	47																				
Battery and charger kits Quick charger set II	48	2.642-555.0	1 piece(s)	36 V	58 Ah	maintenance-free		Battery set with maintenance-free batteries, connection	48																				
36 V / 58 Ah Quick charger set VII	49	2.642-751.0	1 piece(s)	24 V	116 Ah	maintenance-free		cable and charger. Designed for quick interim charges with a charging time < 3 h. Ideal for multiple shift operation.	49													+	+++	+	++	++	+	+	++
24 V/116 Ah Quick charger set V		2.642-558.0			164 Ah	maintenance-free			50													1			+	++	++-	+	++
24 V / 164 Ah Included in the scope of si		- Ameilabla		More Kä	char arigin	-1		A ha fallawing ages																	$\perp \perp$	$\perp \perp$			\perp









	Order no.	Quantity	Battery voltage	Battery capacity	Battery type	Price Description		B 250 R I + R 120 / B 250 R I + R 100 / B 250 R I + D 100 B 250 R + R 120 / B 250 R + R 100 / B 250 R + D 100	B 200 R + D 110 / B 200 R + R 90 / B 200 R + D 90	B 150 R Adv + D 90 / B 150 R Adv + R 75 R 150 R Adv + D 75 R 150 R A 40 / R 150 R + R 75	1 1 2 1 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2	B 90 R connigured B 90 R Adv Dose Bp Pack	B 90 R Adv Dose Bp B 90 R Adv Bp Pack	B 90 R Adv Bp B 90 R Classic Bp Pack	B 90 R Classic B	BD 50/70 R Classif Ept Bp Pack BD 50/70 R Classif Fleet Bp Pack BD 50/70 P Classif R0/70 P Classif R0	B 95 K S K 7 S K 95 K S + R 65 / B 95 R S + D 65 R	BR 55/40 RS Bp PacK BR 55/40 RS Bp	BD 50/40 RS Bp Pack	B 120 W + D 110 / B 120 W + R 90 / B 120 W + D 90	B 120 W + R 75 / B 120 W + D 75 B 80 W Bp + R 75 / B 80 W Bp + D 75 / B 80 W Bp + R 65	B 80 W Bp + D 65 / B 80 W Bp + S 65 B 60 C Classic + R 55 / B 60 C Classic + D 51		B 40 W Bp + R 55 / B 40 W Bp + D 51 / B 40 W Bp + R 45		B 40 C Bp Classic + R 55 / B 40 C Bp Classic + D 51 / B 40 C Bp Classic + R 45 B 40 C Bp Classic + D 43	BD 80/100 W Bp Classic BD 50/50 C Bp Pack Classic	BD 50/50 C Bp Classic BD 43/25 C Bp Pack	BD 43/25 C Bp BD 38/12 C Bp Pack / BR 35/12 C Bp Pack	BR 30/4 C Bp Pack BD 30/4 C Bp Pack
Quick charger set VI 24 V / 116 Ah	51 2.642-559.0	1 piece(s)	24 V	116 Ah	maintenance-free	Battery set with maintenance-free batteries, connection cable and charger. Designed for quick interim charges with a	51																							
Quick charger set I 24 V /	52 2.642-554.0	1 piece(s)	24 V	58 Ah	maintenance-free		52				+		\top			+				+			+							\vdash
Ouick charger attachment	53 2.642-237.0	1 piece(s)	36 V		low-maintenance	Original equipment from Ro model Includes battery	53		\vdash	++	++	+	+		++		++	+	\vdash	++		++	+	++			\perp	+	\vdash	\vdash
Quick charger attachment kit	2.042-237.0	1 biece(2)] JU V		low-maintenance	Original equipment from Bp model. Includes battery 6.654-269.0 and charger 6.654-268.0.																								
Quick charger modification	54 2.882-687.0	1 piece(s)	36 V		low-maintenance	Retrofitting of Bp Pack variants with Kärcher original bat-	54										\top													
kit						tery. Includes battery ventilation and charger 6.654-268.0.			Ш	Ш	Ш		Ш		Ш					Ш	Ш	\perp		$\perp \perp \perp$				\perp	Щ.	Ш
Accessories for batteries	EE 403E 3640	1 pioco/s)			I	Adapter cable for connecting to the battery charger	==		1 1	1 1	1 1	1 1			1 1	1 1	1 1			1 1		1 1	1 1	1 1	1 1					
Adapter cable	55 4.035-264.0	1 piece(s)				Adapter cable for connecting to the battery charger 6.654-329.0.	55									1 0 0	1													
Spacer	56 4.642-021.0	1 piece(s)				Fits quick charger set 2.642-751.0. Prevents the battery	56		\sqcap	\top			$\neg \neg$							\Box		$\neg \Box$	\top	\top						
	E7 4642 040 0	1 pinne(-)				from slipping into the machine.	57		++	++	++	+	+		++		++	+	\vdash	+	11	-		+	+			+	\vdash	+
	57 4.642-019.0	1 piece(s)				Fits quick charger set 2.642-558.0. Prevents the battery from slipping into the machine.	57																	□						
	58 4.642-020.0	1 piece(s)				Fits quick charger set 2.642-559.0. Prevents the battery from slipping into the machine.	58					$\dagger \dagger$								\dagger										
Box with wall holder	59 2.641-243.0	1 piece(s)			low-maintenance	Storage system for refilling wet batteries, easy filling of the batteries possible, saves a lot of time. Install container at a	59																							
Box	60 2.641-244.0	1 piece(s)			low-maintenance	height of 4 metres. Includes hose and flow rate volume meter.	60																							

■ NEW □ Available accessories. More Kärcher original accessories can be found on the following pages.

SINGLE-DISC MACHINE ACCESSORIES



High-quality Kärcher accessories are extremely durable and ideal for daily use with single-disc machines - for excellent cleaning results.



























23

	Hardness / Order no. Brush type	Diameter	Colour	Quantity	Price Description		BDS 43/150 C Classic BDS 51/180 C Adv BDS 51/180 C Adv BDS 33/180 C Adv BDS 33/180 C Adv BDS 33/180 C Adv BDS 33/180 C Adv
Disc brushes		<u>.</u>					
Disc brush	1 6.369-892.0 soft	330 mm	natural	1 piece(s)	Polishing brush.	1	
	2 6.369-890.0 medium	330 mm	red	1 piece(s)	Scrubbing brush.	2	
	3 6.369-893.0 hard	330 mm	black	1 piece(s)	Scrubbing brush, GRIT.	3	
	4 6.369-897.0 soft	430 mm	natural	1 piece(s)	Polishing brush.	4	
	5 6.369-895.0 medium	430 mm	red	1 piece(s)	Scrubbing brush.	5	
	6 6.369-898.0 hard	430 mm	black	1 piece(s)	Scrubbing brush, GRIT.	6	
	7 6.371-206.0 medium	508 mm	red	1 piece(s)	For general cleaning. Also suitable for sensitive floors.	7	
	8 6.371-265.0 hard	508 mm	black	1 piece(s)	For stubborn dirt and deep cleaning.	8	
					For hard-wearing surfaces.		
Shampooing brush	9 6.369-891.0 medium-sof		blue / white		Shampooing brush.	9	
	10 6.369-896.0 medium-sof 11 6.371-266.0 medium-sof		blue / white blue / white		For carpet cleaning.	10	
Dad duive board	11 0.371-200.0 Illedioin-301	308 111111	blue / Willte	I piece(s)	Tor carpet cleaning.	11	
Pad drive board	12 6 360 8040	330 mm	1	1 piece(c)	Low speed	12	
Pad drive board	12 6.369-894.0 13 6.369-899.0	430 mm		1 piece(s)	Low speed.	13	
				1 piece(s)	Duo spood	14	
	14 6.369-901.0	430 mm		1 piece(s)	Duo-speed.		
	15 6.371-208.0	483 mm		1 piece(s)	For cleaning with pads. With quick-change coupling and Centerlock.	15	
Pads				1	und centeriock.		
Pad	16 6.369-903.0 very soft	330 mm	white	5 piece(s)	Smooth, for floor polishing.	16	
	17 6.369-904.0 soft	330 mm		5 piece(s)	For perfect polishing results on sealed floors.	17	
	18 6.369-905.0 medium-sof		red	5 piece(s)	For cleaning all floors.	18	
		d 330 mm	green	5 piece(s)	For cleaning an Hoors. For cleaning heavily soiled floors and deep	19	
	19 0.303-300.0 Illedioin-flai	u 330 IIIIII	BIECH	J piece(s)	cleaning.		
	20 6.369-907.0 hard	330 mm	black	5 piece(s)	For removing stubborn dirt and deep cleaning.	20	
	21 6.369-469.0 very soft	432 mm	white	5 piece(s)	For perfect polishing results on sealed floors.	21	
	22 6.371-149.0 soft	432 mm	beige / natural	5 piece(s)	With natural hair, for polishing. Effectively removes scuff marks.	22	
	23 6.369-471.0 soft	432 mm	blue	5 piece(s)	Especially suitable for deep cleaningof linoleum floors.	23	
	24 6.371-081.0 soft	432 mm	beige	5 piece(s)	For perfect polishing results on sealed floors.	24	
	25 6.369-470.0 medium-sof	t 432 mm	red	5 piece(s)	For cleaning all floors.	25	
	26 6.369-472.0 medium-har	d 432 mm	green	5 piece(s)	For removing stubborn dirt and deep cleaning.	26	
	27 6.369-473.0 hard	432 mm	black	5 piece(s)	For cleaning heavily soiled floors and for deep cleaning.	27	
	28 6.371-146.0 soft	500 mm	beige / natural	5 piece(s)	With natural hair, for polishing. Effectively removes scuff marks.	28	
	29 6.369-468.0 soft	508 mm	beige	5 piece(s)	Light grit, suitable for polishing floors.	29	
	30 6.369-079.0 medium-sof	t 508 mm	red	5 piece(s)	For cleaning all types of floors.	30	
	31 6.369-078.0 medium-har	_	green	5 piece(s)	For removing stubborn dirt and deep cleaning.	31	
	32 6.369-077.0 hard	508 mm	black	5 piece(s)	For cleaning heavily soiled floors and for deep cleaning.	32	

[■] Included in the scope of supply. □ Available accessories. More Karcher original accessories can be found on the following pages.

























		Order no.	Hardness / Brush type	Diameter	Colour	Quantity	Price	Description		BDS 43/150 C Classic BDS 51/180 C Adv BDS 43/180 C Adv BDS 43/180 C Adv BDS 43/Duo C I Adv BDS 43/Duo C I Adv BDS 43/Duo C Adv
Melamine pads				,						
Melamine pad		6.371-025.0 6.371-023.0		508 mm 432 mm	grey/white			Melamine pad set for the effective cleaning of microporous surfaces.	33	
	34	0.371-023.0		432 111111	grey/white	2 piece(s)			34	
	35	6.371-020.0	•	330 mm	grey/white	2 piece(s)		Melamine pad set for the effective cleaning of microporous, textured surfaces, such as natural stone.	35	
Microfibre pad										
Microfibre pad	36	6.369-908.0	microfibre	330 mm	white	5 piece(s)		Excellent cleaning power. Also effectively cleans fine stoneware tiles.	36	
		6.371-271.0		508 mm	white	5 piece(s)		Excellent cleaning power. Also effectively cleans fine stoneware tiles.	37	
	38	6.905-526.0	microfibre	410 mm	white	5 piece(s)		Excellent cleaning power. Also effectively cleans fine stoneware tiles.	38	
Diamond pad					,					
Diamond pad		6.371-256.0 6.371-260.0		432 mm 508 mm	white white	5 piece(s) 5 piece(s)		For coarse cleaning/restoring. Removes small scratches, for a clean, silky matt surface. For surface preparation prior to using the yellow pad. Also suitable as a crystallisation pad for basic crystallisation.	40	
	41	6.371-257.0	medium	432 mm	yellow	5 piece(s)		For coarse cleaning/restoring. Removes fine	41	
		6.371-261.0		508 mm	yellow	5 piece(s)		scratches for a more homogeneous and shinier surface. For surface preparation prior to using the green diamond pad. Also suitable as a crystallisa- tion pad for high-gloss crystallisation.	42	
	43	6.371-238.0	fine	432 mm	green	5 piece(s)		For effortless polishing of laminated floors, terrazzo and natural stone surfaces. For maintenance	43	
	44	6.371-240.0	fine	508 mm	green	5 piece(s)		cleaning after using white and yellow pads. As a crystallisation pad for high-gloss crystallisation.	44	
Accessories for sanding				_	,	_				
Sanding board		6.369-934.0		430 mm		1 piece(s)		For concrete floors.	45	
Drive board for sandpaper		6.369-902.0		405 mm		1 piece(s)		With Centerlock for attaching sandpaper.	46	
Sandpaper, 36 grit		6.990-008.0		410 mm		10 piece(s)		Coarse, 36 grit. For the initial sanding of parquet.	47	
Sandpaper, 60 grit		6.990-009.0		410 mm		10 piece(s)		Medium, 60 grit. For the interim sanding of parquet.	48	
Sandpaper, grain 100	49	6.990-007.0		410 mm		10 piece(s)		Fine, 100 grit. For the final sanding on bare wood or as an interim sanding before the final sealing.	49	
Miscellaneous			1							
Complete tank		9.753-058.0				1 piece(s)		Enables easy application of the cleaning fleet. Capacity: 10 l.	50	
Filling hose	51	6.680-124.0				1 piece(s)		Hose for convenient fresh water filling from all standard taps.	51	
Extension cable		6.647-022.0				1 piece(s)		20 m.	52	
Supplementary weight, 10 kg	53	2.642-802.0				1 piece(s)		Increases the contact pressure. For effective coating removal, grinding, crystallising, etc.	53	

[■] NEW ☐ Available accessories. More Kärcher original accessories can be found on the following pages.







	Order no.	Hardness / Brush type	Diameter	Colour	Quantity	Price Description		BDS 43/150 C Classic BDS 51/180 C Adv BDS 51/180 C Adv BDS 33/180 C Adv BDS 33/180 C Adv BDS 33/180 C Adv BDS 33/140 C Adv
Other attachment kits		•	·	•				
Tank Adv	54 2.642-476.0				1 piece(s)	Easy to remove. Enables easy application of the cleaning fleet. Capacity: 10 l.	54	
Suction unit 43 cm / 17" Adv	55 2.642-674.0				1 piece(s)	Prevents dust when polishing or crystallising.	55	
Tank Adv	56 2.642-495.0				1 piece(s)	Easy to remove. Enables easy application of the cleaning fleet. Capacity: 8 l.	56	
Suction ring 43 cm/17"	57 4.071-223.0				1 piece(s)	Reduces dust development when sanding, crystal- lising, polishing or cleaning in conjunction with a wet and dry vacuum cleaner or the suction unit.	57	
Paper filter bags (two-ply)					•			
Paper filter bags	58 6.904-403.0				10 piece(s)	Dust class M.	58	

[☐] Available accessories. More Kärcher original accessories can be found on the following pages.

ESCALATOR CLEANER ACCESSORIES



Front and rear combs are available for different types of escalators. These prevent water from entering the escalator.



	Order no.	Hardness / Brush type	Colour	Quantity	Price	Description		BR 47/35 ESC BR 45/10 ESC
Brushes							<u> </u>	
Brushes, standard	1 6.680-002.0		white	2 piece(s)		Brushes.	1	
	2 5.762-266.0	soft	white	1 piece(s)		Machine requires 2. For moderate to heavy soiling.	2	
Brushes, hard	3 6.680-001.0	hard		2 piece(s)		Brushes.	3	D
Brushes, intake brushes	4 5.762-268.0		black	1 piece(s)		Machine requires 2.	4	
Brushes, hard	5 5.762-267.0	hard	black	1 piece(s)		Machine requires 2. For removing stubborn dirt on hard-wearing surfaces.	5	
Inlet/outlet combs								
Inlet combs, orange	6 6.371-321.0		orange	2 piece(s)		Fa. Thyssen-Krupp, model FT 983.	6	
Outlet combs, orange	7 6.371-322.0		orange	2 piece(s)			7	
Inlet combs, yellow	8 6.371-272.0		yellow	2 piece(s)		Thyssen-Krupp, Fujitec.	8	
Outlet combs, yellow	9 6.371-273.0		yellow	2 piece(s)			9	
Inlet combs, grey	10 6.369-509.0		grey	2 piece(s)		Companies KONE, O&K.	10	
Outlet combs, grey	11 6.369-519.0		grey	2 piece(s)			11	
Inlet combs, black	12 6.369-510.0		black	2 piece(s)		OTIS, FUJITEL, MONTGOMERY.	12	
Outlet combs, black	13 6.369-520.0		black	2 piece(s)			13	
Inlet combs, green	14 6.369-511.0		green	2 piece(s)		Schindler, Westinghouse, MITSUBISHI.	14	
Outlet combs, green	15 6.369-521.0		green	2 piece(s)			15	
Inlet combs, white	16 6.369-512.0		white	2 piece(s)		CNIM, DONG YANG, HITACHI, TOSHIBA.	16	
Outlet combs, white	17 6.369-522.0		white	2 piece(s)			17	
Inlet combs, blue	18 6.369-914.0		blue	2 piece(s)		OTIS, models 622 and 913.	18	
Outlet combs, blue	19 6.369-915.0		blue	2 piece(s)			19	
Other								
Filter bags	20 6.680-003.0			10 piece(s)		10 l.	20	
Guid rail, standard	21 5.032-932.0			1 piece(s)		Guide rail, standard.	21	
Groove rake	22 6.369-507.0			1 piece(s)		Companies KONE + Schindler; for manual removal of stubborn dirt, such as small stones, etc.	22	
	23 6.369-508.0			1 piece(s)		Companies Thyssen + OTIS; for manual removal of stubborn dirt, such as small stones, etc.	23	
Hand pads								
Hand pads	24 6.369-513.0	medium	green	5 piece(s)		KONE, green, for manual cleaning of vertical surfaces.	24	
	25 6.369-514.0	medium	green	5 piece(s)		OTIS, for manual cleaning of vertical surfaces.	25	
	26 6.369-515.0	medium	green	5 piece(s)		Schindler, for manual cleaning of vertical surfaces.	26	
	27 6.369-516.0	medium	green	5 piece(s)		Thyssen, for manual cleaning of vertical surfaces.	27	

[■] Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

STAIR CLEANING ACCESSORIES



Deep cleaning, polishing, crystallising or shampooing various floor coverings. A wide range of accessories mean that the machine can be used for a wide variety of applications.



And the second s	THE REAL PROPERTY AND ADDRESS.								
	Order no.	Hardness / Brush type	Diameter	Colour	Quantity Price	Description			BD 17/5 C
Disc brushes									
Polishing brush	1 6.994-114.0	soft	170 mm	natural	1 piece(s)	For polishing.	1		
Corner brush	2 6.994-128.0	hard	170 mm	green	1 piece(s)	Ideal for cleaning in corners, for deep cleaning.	2		
	3 6.994-127.0	medium	170 mm	red	1 piece(s)	Ideal for cleaning in corners, for all surfaces.	3		
Disc brush	4 6.994-112.0	medium	170 mm	red	1 piece(s)	For all surfaces.	4		
	5 6.994-113.0	hard	170 mm	green	1 piece(s)	For deep cleaning.	5		
	6 6.994-118.0	soft	200 mm	natural	1 piece(s)	For polishing, large diameter.	6		
	7 6.994-116.0	medium	200 mm	red	1 piece(s)	For all surfaces, large diameter.	7		
	8 6.994-117.0	hard	200 mm	black	1 piece(s)	For deep cleaning, large diameter.	8		
Shampooing brush	9 6.994-115.0	medium-soft	170 mm	blue	1 piece(s)	For carpets.	9		
Pad drive board									
Pad drive board	10 6.994-119.0		170 mm		1 piece(s)	Easy to fit pad drive board for BD 17/5 stair cleaning machine. For cleaning with 170 mm diameter pads.	10		
Pads									
Pad	11 6.994-120.0	very soft	170 mm	white	1 piece(s)	Smooth, for floor polishing.	11		
	12 6.994-126.0	soft	170 mm	white	1 piece(s)	With wool polishing attachment.	12		
	13 6.994-124.0	soft	170 mm	beige	1 piece(s)	Fine grit for floor polishing.	13		
	14 6.994-122.0			red	1 piece(s)	For cleaning all types of floors.	14		
	15 6.994-123.0		170 mm	green	1 piece(s)	For cleaning heavily soiled floors and deep cleaning.	15		
	16 6.994-121.0	hard	170 mm	black	1 piece(s)	For removing stubborn dirt and deep cleaning.	16		
Diamond pad									
Diamond pad	17 6.371-242.0	medium	152 mm	yellow	5 piece(s)	For coarse cleaning/restoring. Removes fine scratches for a more homogeneous and shinier surface. For surface preparation prior to using the green diamond pad. Also suitable as a crystallisation pad for high-gloss crystallisation.	17		
	18 6.371-243.0	coarse	152 mm	white	5 piece(s)	For coarse cleaning/restoring. Removes small scratches, for a clean, silky matt surface. For surface preparation prior to using the yellow pad. Also suitable as a crystallisation pad for basic crystallisation.	18		
	19 6.371-241.0	fine	152 mm	green	5 piece(s)	For effortless polishing of laminated floors, terrazzo and natural stone surfaces. For maintenance cleaning after using white and yellow pads.	19		
Miscellaneous									
Add-on kit tank complete BD 17/5	20 2.644-023.0					Guide rod incl. fresh water tank for our BD 17/5 scrubber. Allows comfortable and fatigue-free working in upright position.	20		
Splash guard	21 6.994-129.0				1 piece(s)	Prevents splashing of detergent at maximum speed. For brushes with a diameter of 170 or 200 mm.	21		
Fresh water tank, 3.5 I	22 6.994-130.0				1 piece(s)	Push-on: for basic and maintenance cleaning.	22		
Fresh water tank, 5 l, with guiding bar	23 6.994-131.0				1 piece(s)	For comfortable working, including fresh water tank.	23		
Extension cable	24 6.647-022.0				1 piece(s)	20 m.	24		

Extension cable 24 | 6.647-022.0 | | 1 pie | 1 pie | Available accessories. More Kārcher original accessories can be found on the following pages.

POLISHING MACHINE ACCESSORIES



Effective ultra-high-speed polishing delivers the best results with the right accessories. Pads with different degrees of hardness are available for various applications.

















	Order no.	Hardness / Brush type	Diameter	Colour	Quantity	Price	Description		BDP 50/2000 RS Bp Pack BDP 50/2000 RS Bp BDP 50/1500 CS Bp
Pads Pad	1 6.371-146.0	coft	500 mm	hoigo /	5 piece(s)		With natural hair, for polishing. Effectively removes scuff	1	
rdu	1 0.371-140.0	SUIT	300 11111	natural	5 piece(s)		marks.	1	
	2 6.369-468.0	soft	508 mm	beige	5 piece(s)		Light grit, suitable for polishing floors.	2	
	3 6.369-079.0	medium- soft	508 mm	red	5 piece(s)		For cleaning all types of floors.	3	
	4 6.371-320.0	soft	508 mm	white	5 piece(s)		Without granulation, for polishing floors. Fits D 51.	4	
Miscellaneous									
Add-on kit eco!zero	5 5.388-133.0				1 piece(s)		With eco!zero for climate-neutral cleaning: as compensation for the CO2 which is produced by using the machine, we support climate protection projects worldwide.	5	
Filter bag	6 8.633-398.0				10 piece(s)		Fits BDP 50/2000 RS.	6	
Pre-spraying unit	7 6.670-020.0				1 piece(s)		For convenient spray cleaner application.	7	
Batteries									
Battery	8 6.654-093.0				1 piece(s)		Gel traction battery, maintenance-free. With 12 V/76 Ah (5h). Two batteries required for 24 V machines, three required for 36 V machines.	8	
	9 6.654-291.0				1 piece(s)		Maintenance-free gel traction battery rated at 12 V and 198 Ah (C5). Three of these are required to operate a 36 V system.	9	
Battery Chargers									
Battery charger	10 6.654-276.0				1 piece(s)		Charger with 36 V / 12 A voltage, suitable for BD 50/ 40 RS Bp Pack. For battery $3 \times 6.654-093.0$.	10	
	11 6.654-292.0				1 piece(s)		For maintenance-free 36 V batteries with 198 Ah (e.g. for 6.654-291.0).	11	

[■] Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

EFFICIENT MACHINES FOR CLEAN FLOORS

Kärcher sweepers/vacuum sweepers are always state of the art. From compact manual sweepers to industrial machines, they all impress with practical details and their efficient sweeping and dust control technology. The machines are versatile and can used for indoor or outdoor cleaning, allowing you to achieve the perfect cleaning results every time. It's this impressive combination of sophisticated ergonomics, ease of use (thanks to EASY Operation), simple handling and outstanding efficiency that makes our sweepers so unique.



Table of contents: Sweepers/vacuum sweepers

Industrial vacuum sweepers	Page	634
Ride-on vacuum sweepers	Page	642
Walk-behind vacuum sweepers	Page	656
Push sweepers-/vacuum sweepers	Page	662
Accessories	Page	666



Your impressive entry-level model to the industry class

Our new entry-level industrial sweeper is the KM 120/250 R Classic. This machine is the equal of its bigger brothers in terms of cleaning performance, robustness, reliability and ease of operation. It is designed for use in heavy industry, such as in foundries or in the metalworking and logistics sectors. You can choose one of various power sources: diesel, LPG, or an emission-free battery-powered machine.



Comfortably advance to the ride-on class

The new KM 85/50 R is your compact entry-level ride-on sweeper. Because driving a sweeper is quite simply more fun than walking along behind one! You can also get your cleaning tasks done much faster thanks to the increased productivity. Our KM 85/50 R will impress you with its compact build and the incredible manoeuvrability this enables. You can even use it to thoroughly clean tight and cluttered spaces.

How to read the machine names:

Model	Working width	Volume	Type	Drive	Equipment
Example: KM	90	60	R	Bp Pack	Adv
KM = Sweeper	Working width with one side brush in centimetres	Volume of the waste container in litres	C = Compact, without traction drive W = Walk-behind with traction drive R = Ride-on machine	G = Petrol-powered (gasoline) D = Diesel LPG = Liquefied Petroleum Gas Bp = Battery-powered Pack = Package (battery and battery charger included in the scope of supply) Fields of application G = Outdoor use D = Outdoor use LPG = Outdoor use, indoor use only in well-ventilated areas (e.g. where the use of LPG forklifts is permitted) Bp = Indoor use and outdoor use Pack = Indoor use and outdoor use	

SWEEPERS/VACUUM SWEEPERS

From push vacuum sweepers, walk-behind models with their own traction drive to ride-on sweepers in large dimensions: Our range of sweepers is just as extensive as the requirements and applications are diverse. Depending on requirements and preferences, you can choose between all relevant drive types – petrol, diesel, LPG or electric – for practically every field of application, from interior cleaning in hotels or exhibition halls through to contract cleaning and applications in foundries, production halls or sports facilities.

		Price	Order no.	Working width without side brush / with 1 side brush / with 2 side brushes / with 3 side brushes (mm)	Max. battery runtime (h)	Waste container (I)	Max. area performance with 1 side brush (m²/h)	Max. area performance with 2 side brushes (m²/h)	Indoor use	Outdoor use	Dustpan principle	Overhead sweeping principle	Traction drive	Page
	Industrial vacuum sweepers		'											
1	KM 170/600 R D		1.186-127.0	1350/1680/2000/2400	-	600	23520	28000	-			-		635
9-16	KM 150/500 R LPG		1.186-123.0	1200/1500/1800/2200	-	500	18000	21600				-		637
	KM 150/500 R D		1.186-124.0	1200/1500/1800/2200	-	500	18000	21600	-			-		637
	KM 150/500 R D Classic		1.186-134.0	1200/1500/1800/-	-	500	18000	21600	-			-		637
	KM 150/500 R Bp		1.186-125.0	1200/1500/1800/2200	2.5	500	12000	14400				-		637
	KM 150/500 R Bp Pack		1.186-130.0	1200/1500/1800/-	2.5	500	12000	14400				-		637
	KM 130/300 R LPG		1.186-121.0	1000/1300/1550/-	-	300	13000	15500				-		639
	KM 130/300 R D		1.186-120.0	1000/1300/1550/-	-	300	13000	15500	-			-		639
20	KM 130/300 R Bp Pack		1.186-129.0	1000/1300/1550/-	2	300	9100	10850				-		639
	KM 130/300 R Bp		1.186-122.0	1000/1300/1550/-	2	300	9100	10850				-		639
1/25	KM 130/300 R D Classic		1.186-139.0	1000/1300/1550/-	-	300	13000	15500	-			-		639
	KM 120/250 R LPG Classic		1.186-001.0	900/1200/1450/-	-	250	10800	13050			•	-		641
	KM 120/250 R D Classic		1.186-000.0	900/1200/1450/-	-	250	10800	13050	-			-		641
	KM 120/250 R Bp Classic		1.186-002.0	900/1200/1450/-	3.5	250	7200	8700				-		641
	KM 120/250 R Bp Pack Classic		1.186-003.0	900/1200/1450/-	3.5	250	7200	8700				-		641
	Ride-on vacuum sweepers		1							_	_			
>	·		1 4 200 450 2	000/1250/1700/	-	130	10000	13600	-		-			645
														045
-	KM 125/130 R G		1.280-150.2	880/1250/1700/- 880/1250/1700/-	_	_			-	-	-			645
E	KM 125/130 R D		1.280-150.2	880/1250/1700/-	-	130	10000	13600	-	•	-	•	•	645
	KM 125/130 R D KM 125/130 R LPG		1.280-150.2 1.280-150.2	880/1250/1700/- 880/1250/1700/-	-	130 130	10000 10000	13600 13600	-	•	-	•	•	645
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp		1.280-150.2 1.280-150.2 1.280-150.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/-	- - 5	130 130 130	10000 10000 10000	13600 13600 13600	-	•	-	•	•	645 645
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/-	- - 5 5	130 130 130 130	10000 10000 10000 10000	13600 13600 13600 13600	- •	•	-	•	•	645 645 645
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/-	- - 5 5	130 130 130 130 130	10000 10000 10000 10000 7350	13600 13600 13600 13600 9800	-	• • •	- - -	•	• • •	645 645 645 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/-	- - 5 5 - -	130 130 130 130 130 110	10000 10000 10000 10000 7350 7350	13600 13600 13600 13600 9800 9800	-	1	- - - -		1 1 1	645 645 645 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R G		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/-	- - 5 5 - -	130 130 130 130 110 110 110	10000 10000 10000 10000 7350 7350 7350	13600 13600 13600 13600 9800 9800 9800	-		- - - -		- - - -	645 645 645 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R G KM 105/110 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/-	- 5 5 - - - 4	130 130 130 130 110 110 110 110	10000 10000 10000 10000 7350 7350 7350 6300	13600 13600 13600 13600 9800 9800 9800 8400	-		- - - -			645 645 645 649 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R G KM 105/110 R Bp KM 105/110 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/-	- 5 5 - - - 4 4	130 130 130 130 110 110 110 110 110	10000 10000 10000 10000 7350 7350 7350 6300 6300	13600 13600 13600 13600 9800 9800 9800 9800 8400	-		- - - - -			645 645 645 649 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R G KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/-	- - 5 5 - - - 4 4	130 130 130 130 110 110 110 110 110 110	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350	13600 13600 13600 13600 9800 9800 9800 8400 8400 9800	-		- - - - -			645 645 649 649 649 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp ack KM 105/100 R LPG		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/-	- - 5 5 - - - 4 4 -	130 130 130 130 110 110 110 110 110 100	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350 7350	13600 13600 13600 13600 9800 9800 9800 8400 8400 9800 9800	-		- - - - - -			645 645 649 649 649 649 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp ack KM 105/100 R D KM 105/100 R D		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/-	- - 5 5 - - - 4 4 - -	130 130 130 130 110 110 110 110 110 100 10	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350 7350 7350	13600 13600 13600 13600 9800 9800 9800 8400 8400 9800 9800 98	-		- - - - - - -			645 645 649 649 649 649 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp Pack KM 105/110 R Bp Pack KM 105/100 R LPG KM 105/100 R D KM 105/100 R D KM 105/100 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/-	- - 5 5 - - - 4 4 - - - 4	130 130 130 130 110 110 110 110 110 100 10	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350 7350 7350 6300	13600 13600 13600 13600 9800 9800 9800 8400 8400 9800 9800 98	- - - - - - - - - - -		- - - - - - -			645 645 649 649 649 649 649 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/100 R Bp KM 105/100 R D KM 105/100 R Bp KM 105/100 R Bp KM 105/100 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/-	- - 5 5 - - 4 4 - - - 4 4	130 130 130 130 110 110 110 110 110 100 10	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350 7350 7350 6300 6300 6300 6300	13600 13600 13600 13600 9800 9800 9800 8400 9800 9800 9800 98	-		- - - - - - - - -			645 645 649 649 649 649 649 649 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R BP KM 105/100 R LPG KM 105/100 R D KM 105/100 R D KM 105/100 R D KM 105/100 R Bp KM 105/100 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 700/1000/1300/-	- - 5 5 - - - 4 4 - - - 4 4	130 130 130 130 110 110 110 110 110 100 10	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350 7350 7350 6300 6300 6300 8000	13600 13600 13600 13600 9800 9800 9800 8400 9800 9800 9800 98			- - - - - - - - - -			645 645 649 649 649 649 649 649 649 649 649
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/100 R LPG KM 105/100 R D KM 105/100 R D KM 105/100 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 700/1000/1300/- 700/1000/1300/-	- - 5 5 - - - 4 4 - - - 4 4	130 130 130 130 110 110 110 110 110 100 10	10000 10000 10000 10000 7350 7350 6300 6300 7350 7350 7350 7350 6300 6300 8000 8000	13600 13600 13600 13600 9800 9800 9800 8400 9800 9800 9800 98	- - - - - - - - - - -		- - - - - - - - - - - - -			645 645 649 649 649 649 649 649 649 649 651
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/100 R LPG KM 105/100 R D KM 105/100 R Bp KM 100/100 R D		1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-10.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 700/1000/1300/- 700/1000/1300/-	- - 5 5 - - - 4 4 - - - 4 4 - -	130 130 130 130 110 110 110 110 110 100 10	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350 7350 6300 6300 6300 8000 8000	13600 13600 13600 13600 9800 9800 9800 8400 9800 9800 9800 98			- - - - - - - - - - - - - - -			645 645 649 649 649 649 649 649 649 651 651
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/10 R Bp KM 105/100 R Bp KM 105/100 R D KM 105/100 R Bp KM 100/100 R Bp Pack		1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/-	- - 5 5 - - 4 4 - - 4 4 - - - - - - -	130 130 130 130 110 110 110 110	10000 10000 10000 10000 7350 7350 6300 6300 7350 7350 7350 6300 6300 8000 8000 8000	13600 13600 13600 13600 9800 9800 9800 8400 8400 9800 9800 98			- - - - - - - - - - - - - - - - - - -			645 645 649 649 649 649 649 649 649 651 651 651
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/100 R Bp KM 105/100 R D KM 105/100 R Bp KM 105/100 R D KM 105/100 R Bp KM 105/100 R Bp KM 105/100 R Bp KM 105/100 R Bp KM 100/100 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-102.0 1.280-103.0	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/-	- - 5 5 - - 4 4 4 - - - 4 4 - - - - 2.5 2.5 2.5 2.5 3.5 3.5 3.5 4.5 4.5 4.5 4.5 4.5 4.5 4.5 4.5 4.5 4	130 130 130 130 110 110 110 110 100 100	10000 10000 10000 10000 7350 7350 6300 6300 7350 7350 7350 6300 8000 8000 8000 6000 6000	13600 13600 13600 13600 9800 9800 9800 8400 9800 9800 9800 98			- - - - - - - - - - - - - - - - - - -			645 645 649 649 649 649 649 649 649 651 651 651
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/100 R Bp KM 105/100 R D KM 105/100 R Bp KM 100/100 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-10.2 1.280-10.2 1.280-105.0 1.280-105.0 1.280-103.0 1.047-300.0	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/-	- - - 5 5 - - - 4 4 - - - - 4 4 4 - - - -	130 130 130 130 110 110 110 110 100 100	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350 7350 6300 6300 8000 8000 8000 6000 6000 7200	13600 13600 13600 13600 9800 9800 9800 8400 9800 9800 9800 98			- - - - - - - - - - - - - - - - - - -			645 645 649 649 649 649 649 649 649 651 651 651 651 653
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R LPG KM 105/110 R Bp KM 105/100 R LPG KM 105/100 R D KM 105/100 R Bp KM 100/100 R D KM 100/100 R Bp KM 90/60 R G Adv KM 90/60 R Bp Pack Adv		1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-10.2 1.280-10.2 1.280-107.0 1.280-105.0 1.280-103.0 1.047-300.0 1.047-300.0	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 670/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 615/900/1150/- 615/900/1150/-	- - 5 5 - - - 4 4 4 - - - 4 4 - - - - -	130 130 130 130 110 110 110 110 100 100	10000 10000 10000 10000 7350 7350 6300 7350 7350 6300 6300 8000 8000 8000 6000 6000 7200	13600 13600 13600 13600 9800 9800 9800 8400 9800 9800 9800 8400 10400 10400 10400 7800 7800 9200 6900						645 645 649 649 649 649 649 649 649 651 651 651 651 653 653
	KM 125/130 R D KM 125/130 R LPG KM 125/130 R Bp KM 125/130 R Bp Pack KM 105/110 R LPG KM 105/110 R D KM 105/110 R Bp KM 105/110 R Bp KM 105/110 R Bp KM 105/100 R Bp KM 105/100 R D KM 105/100 R Bp KM 100/100 R Bp		1.280-150.2 1.280-150.2 1.280-150.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-140.2 1.280-10.2 1.280-10.2 1.280-105.0 1.280-105.0 1.280-103.0 1.047-300.0	880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 880/1250/1700/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 640/1050/1400/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/- 700/1000/1300/-	- - - 5 5 - - - 4 4 - - - - 4 4 4 - - - -	130 130 130 130 110 110 110 110 100 100	10000 10000 10000 10000 7350 7350 7350 6300 6300 7350 7350 6300 6300 8000 8000 8000 6000 6000 7200	13600 13600 13600 13600 9800 9800 9800 8400 9800 9800 9800 98			- - - - - - - - - - - - - - - - - - -			645 645 649 649 649 649 649 649 649 651 651 651 651 653

[■] Included in the scope of supply.

		Price	Order no.	Working width without side brush / with 1 side brush / with 2 side brushes / with 2 side brushes (mm)	Max. battery runtime (h)	Waste container (l)	Max. area performance with 1 side brush (m²/h)	Max. area performance with 2 side brushes (m²/h)	Indoor use	Outdoor use	Dustpan principle	Overhead sweeping principle	Traction drive	Page
	Walk-behind vacuum sweepers													
20	KM 85/50 W Bp Pack Adv		1.351-115.0	610/850/1050/-	2.5	50	3825	4725			-			657
A STATE OF THE PARTY OF THE PAR	KM 85/50 W Bp Pack		1.351-114.0	610/850/1050/-	2.5	50	3825	4725			-			657
	KM 85/50 W Bp Adv		1.351-108.0	610/850/1050/-	2.5	50	3825	4725			-			657
	KM 85/50 W Bp		1.351-107.0	610/850/1050/-	2.5	50	3825	4725			-			657
1	KM 85/50 W G Adv		1.351-110.0	610/850/1050/-	-	50	3825	4725	-	•	-		•	657
	KM 85/50 W G		1.351-109.0	610/850/1050/-	-	50	3825	4725	-		-			657
A 113	KM 75/40 W Bp Pack		1.049-207.0	550/750/-/-	2.5	40	3375	-			-			659
	KM 75/40 W Bp		1.049-206.0	550/750/-/-	2.5	40	3375	-			-			659
15	KM 75/40 W G		1.049-205.0	550/750/-/-	-	40	3375	-	-	•	-		•	659
del	KM 80 W G		1.335-500.0	800/-/-/-	-	40	1680	-	-			-		661
	Push sweepers/vacuum sweepers													
1000	KM 70/30 C Bp Pack Adv		1.517-213.0	480/700/-/-	2.5	42	2800	-				-	-	663
-0-	KM 70/30 C Bp Pack		1.517-214.0	480/700/-/-	2.5	42	2800	-				-	- 1	663
5	KM 70/30 C Bp Adv		1.517-212.0	480/700/-/-	2.5	42	2800	-				-	-	663
//	KM 70/30 C Bp		1.517-211.0	480/700/-/-	2.5	42	2800	-				-	- 1	663
-	KM 70/20 C 2SB		1.517-107.0	480/700/920/-	-	42	-	3680		•		-	-	665
-	KM 70/20 C		1.517-106.0	480/700/-/-	-	42	2800	-	•	•		-	- 1	665
	KM 70/15 C		1.517-151.0	480/700/-/-	-	42	2800	-				-	- 1	665

[■] Included in the scope of supply.

WHICH SWEEPER IS THE RIGHT ONE FOR ME?





Industrial vacuum sweeper

Cleaning area:

4,000 to 100,000 m²

Areas to be cleaned outside:

Outdoor warehouses, open-sided building, loading bays

Areas to be cleaned inside:

Heavy industry hangars, production facilities, warehouses and logistics buildings





Properties:

- High area performance
- Robust
- Suitable for demanding applications

Accessories for special applications:

- Stainless steel waste container
- Water spraying system for side brushes
- Side brush cover
- Vacuum cleaner
- Protective roof
- Cabin
- Lights















Ride-on vacuum sweeper

Cleaning area:

1,200 to 20,000 m²

Areas to be cleaned outside:

Areas all around buildings, car parks, courtyards, sports grounds with rubber floors or artificial turf

Areas to be cleaned inside:

Production facilities, logistics sites, (multi-storey) car parks, exhibition halls





Properties:

- High productivity
- Manoeuvrability
- Intuitive to use

Accessories for special applications:

- Leaf collection kit
- Water spraying system for side brushes
- Side brush cover
- Vacuum cleaner/suction hose
- Carpet sweeping kit
- Artificial turf kit (without granulate)
- Home Base kit



Walk-behind vacuum sweeper

Cleaning area:

400 to 8,000 m²

Areas to be cleaned outside:

Parking spaces, service stations, courtyards

Areas to be cleaned inside:

Stables, warehouses, hallways and rooms with large carpeted areas



Properties:

- High cleaning efficiency
- Smooth running
- Flexible

Accessories for special applications:

- Carpet sweeping kit
- Antistatic main sweeper roller
- Snow blade
- Waste container



Push sweeper/vacuum sweeper

Cleaning area:

200 to 4,000 m²

Areas to be cleaned outside:

Entrance ways, footpaths, courtyards

Areas to be cleaned inside:

Workshops, building sites, showrooms





- Fast and effective cleaning of small and medium-sized areas
- Compact

Accessories for special applications:

- Litter picker
- Roller brush







PERFECTLY ADAPTED TO THE SURFACE AND TYPE OF DIRT

Different floor coverings and types of dirt place different demands on the sweeper and sweeping system. In most cases, the durable standard roller brush is adequate for efficient cleaning. But Kärcher sweepers offer the perfect solution in specific cases too: On very smooth floors, such as in warehouses, it's advisable to use a soft roller brush to sweep the dust effectively, while antistatic roller brushes are recommended for use on carpets. For stubborn dirt on rough floors, roller brushes with steel bristles could also be used.















Standard main sweeper roller

The standard main sweeper roller with medium bristle hardness is suitable for a wide variety of applications. When used on normal road dirt, dry leaves, or in dusty environments on asphalt screed or interlocking stones, it cleans perfectly without leaving any remnants behind.

Main sweeper roller, hard

The hard main sweeper roller has a higher number of significantly harder bristles, some of which also have steel inserts. It is particularly suited to rough surfaces and stubborn dirt or heavy waste.

Main sweeper roller, soft


The soft main sweeper roller is ideal for sweeping dirt and fine dust off smooth floors. It is primarily used indoors, as the softer bristles have less of an impact on delicate floors

Main sweeper roller, antistatic

Antistatic main sweeper rollers are designed for efficient cleaning of carpets. With the right kit, even large carpeted areas in hotels. exhibition halls or sports facilities can be cleaned in next to no time

ECONOMICAL USE

Using the following Kärcher sweepers and vacuum sweepers is cost-effective when the area to be swept is as indicated in the performance column.




Economical area

Figures: Minimum surface area in m² from which use of the machine is cost-effective.

CLEANLY FILTERED - SO THAT DUST DOES NOT ENDANGER YOUR HEALTH

Two different dust classifications are relevant to sweepers. The first is PM (particulate matter), which refers to the particle size. Coarse dust includes dust particles larger than 10 µm. The PM10 category covers dust particles measuring 10 to 2.5 µm. The PM2.5 category applies to particles of between 2.5 and 1 µm. The finest dust particles smaller than 1 µm belong to the PM1 category. The second is dust class, which can be L, M or H. There are different separation degrees between the various types of dust within these classes. All the filters used in our sweepers correspond to dust class M.




APPLICATION-OPTIMISED FILTER SYSTEMS


The performance of a filter system is dependent on three essential criteria: Firstly, the filter area, which determines the intake capacity during operation and the frequency at which cleaning is necessary. Secondly, the separation degree, which determines how much dust the filter can remove from the air. This largely depends on what material the filter is made of. Thirdly, the efficiency with which the filter is cleaned while the sweeper is in operation plays a decisive role. The interplay between all these criteria is crucial to the optimum functioning of the filter system



MEASURES TO REDUCE DUST DURING SWEEPING

The side brush can usually be raised to disturb less dust while you sweep. Reducing the driving speed often achieves good results too. Kärcher sweepers come as standard or have the option to be fitted with special solutions to reduce or prevent dust being stirred up. The water spraying system or side brush cover attachment kits can be fitted on many of our sweepers, for example.







Maximum power for tough cleaning jobs

This extremely robust and powerful machine with 170 cm working width is designed for the most demanding tasks, thanks to its solid construction, large waste container and extensive features.









3 Outstanding user-friendliness

Exceptional ease of servicing.

Easy cab access.

■ EASY Operation operating concept.



1 Effective filter for a long service life

- Effective filter cleaning with dual scraper.

- Flat pleated filter with 10 m² filter area.
- For dust-free sweeping.

- 2 Robust construction
- Solid steel frame.
- Hard-wearing industrial motors with water cooling.
- Fully hydraulic traction drive.

4 Extensive range of accessories and attachment kits

- Easily adapts to individual cleaning requirements.
- Impressive equipment (e.g. comfort cab, air-conditioner, heating).
- Second and third side brushes available on request.

TECHNICAL DATA AND EQUIPMENT

KM 170/600 R D

- Powerful industrial engine
- High working and transport speed
- Non-stop use

Technical data		
Drive		4-stroke diesel engine / Yanmar
Power	kW	35
Max. area performance with 1 / 2 side brushes	m²/h	23520 / 28000
Working width	mm	1350
Working width with 1 or 2 brushes	mm	1680 / 2000
Waste container	I	600
Climbing ability	%	18
Working speed	km/h	14
Filter area	m²	10
Weight	kg	1530
Dimensions (L × W × H)	mm	2450 × 1750 × 1665

Equipment	
Polyester flat pleated filter	1
Manual/Automatic filter cleaning	■ / -
Adjustable main sweeper roller	T .
Steering booster	
Hydraulic high container emptying	1
Order no.	1.186-127.0
Price	

Included in the scope of supply.

Accessories			
Product name	Order no.	Description	Price
Standard roller brush	6.987-441.0	Water-resistant universal bristles, durable, suitable for all surfaces.	
Side brush, standard	6.987-467.0	Water-resistant universal bristles, durable, suitable for all surfaces.	
Water spraying system for side brush	2.851-284.7	For binding dust. Consisting of stainless steel water tank (65 I) and spray nozzles on the side brushes.	
Third side brush attachment kit	2.851-277.7	For increasing the sweeping width and therefore also the area performance by more than 15%.	



High capacity and power for heavy-duty use

The industrial sweeper with 150 cm working width for use in the building materials and metal processing industry, in foundries and in other industries with high levels of dirt accumulation.

The battery version is ideal for noise-sensitive interior areas.













1 Efficient filter system

- Flat pleated filter with 7 m² filter area.
- Effective cleaning with dual scraper.
- For dust-free sweeping.

2 Comfortable workspace

- All control elements are clearly arranged and within easy reach.
- All displays within view.
- Optional: cabs with heating or air conditioning.

3 Simple operation, maintenance and servicing

- Very simple technology with tried-and-tested components: fully hydraulic drive, electric rather than electronic.
- Easy access to the motor compartment for quick and easy servicing.
- Main sweeper roller and flat pleated filter can be changed without

4 Classic version with diesel drive

- Simple operation via lever.
- Large pocket filter with 10.5 m² filter area.
- Fully hydraulic traction drive.

TECHNICAL DATA AND EQUIPMENT

		KM 150/500 R LPG	KM 150/500 R D	KM 150/500 R D Classic
		 High working and transport speed Traction drive and sweeping system fully hydraulic Low-maintenance 	 High working and transport speed Traction drive and sweeping system fully hydraulic Low-maintenance 	High working and transport speedSimple operation via control leverPocket filter with large filter area
Technical data				
Drive		Four-stroke LPG engine / Kubota	4-stroke diesel engine / Yanmar	4-stroke diesel engine / Yanmar
Power	kW	22	22.5	15.8
Voltage	V	-	-	-
Max. area performance with 1 / 2 side brushes	m²/h	18000 / 21600	18000 / 21600	18000 / 21600
Working width	mm	1200	1200	1200
Working width with 1 or 2 brushes	mm	1500 / 1800	1500 / 1800	1500 / 1800
Waste container	1	500	500	500
Climbing ability	%	18	18	18
Working speed	km/h	12	12	12
Filter area	m²	7	7	10.5
Weight	kg	1415	1440	1400
Dimensions (L × W × H)	mm	2442 × 1570 × 1640	2442 × 1570 × 1640	2442 × 1570 × 1640
Equipment				
Polyester flat pleated filter				-
Pocket filter		-	-	•
Manual/Automatic filter cleaning		I / -	■ / -	I / -
Adjustable main sweeper roller		•	•	•
Steering booster			•	•
Hydraulic high container emptying		•	•	•
Order no.		1.186-123.0	1.186-124.0	1.186-134.0
Price				

■ Included in the scope of supply.

KM 150/500 R Bp

KM 150/500 R Bp Pack

		 High working and transport speed Traction drive and sweeping system fully hydraulic Low-maintenance 	 High working and transport speed Traction drive and sweeping system fully hydraulic Low-maintenance
Technical data			
Drive		DC motor	DC motor
Power	kW	10	10
Voltage	V	48	48
Max. area performance with 1 / 2 side brushes	m²/h	12000 / 14400	12000 / 14400
Working width	mm	1200	1200
Working width with 1 or 2 brushes	mm	1500 / 1800	1500 / 1800
Waste container	I	500	500
Climbing ability	%	12	12
Working speed	km/h	8	8
Filter area	m²	7	7
Weight	kg	1380	2690
Dimensions (L × W × H)	mm	2442 × 1550 × 1640	2442 × 1550 × 1640
Equipment			
Polyester flat pleated filter		•	•
Pocket filter		-	-
Manual/Automatic filter cleaning		■ / -	■ / -
Adjustable main sweeper roller			
Steering booster			•
Hydraulic high container emptying			
Order no.		1.186-125.0	1.186-130.0
Price			

■ Included in the scope of supply.

The machine for harsh industrial environments

It removes fine dust and construction waste from industrial areas and, as a battery-powered machine, ensures cleanliness even in noise-sensitive interior areas.













1 Robust construction

- Solid steel frame.
- Hard-wearing industrial motors with water cooling.
- Fully hydraulic traction drive.

Flat pleated filter with 5.5 m² filter area.

2 Effective filter for a long service life

- Effective filter cleaning with dual scraper.
- For dust-free sweeping.

3 Outstanding user-friendliness

- EASY Operation operating concept.
- Easy cab access.
- Exceptional ease of servicing.

4 Classic version with diesel drive

- Simple operation via lever.
- Large pocket filter with 7.8 m² filter area.
- Fully hydraulic traction drive.

TECHNICAL DATA AND EQUIPMENT

		KM 130/300 R LPG	KM 130/300 R D	KM 130/300 R D Classic
		 High working and transport speed Simple brush roller replacement without tools Traction drive and sweeping system fully hydraulic 	 High working and transport speed Simple brush roller replacement without tools Traction drive and sweeping system fully hydraulic 	 High working and transport speed Simple operation via control lever Pocket filter with large filter area
Technical data				
Drive		Four-stroke LPG engine / Kubota	4-stroke diesel engine / Yanmar	4-stroke diesel engine / Yanmar
Power	kW	17.5	15.8	15.8
Voltage	V	-	-	-
Max. area performance with 1 / 2 side brushes	m²/h	13000 / 15500	13000 / 15500	13000 / 15500
Working width	mm	1000	1000	1000
Working width with 1 or 2 brushes	mm	1300 / 1550	1300 / 1550	1300 / 1550
Waste container	I	300	300	300
Climbing ability	%	18	18	18
Working speed	km/h	10	10	10
Filter area	m²	5.5	5.5	7.8
Weight	kg	900	951	921
Dimensions (L × W × H)	mm	2150 × 1330 × 1430	2150 × 1330 × 1430	2150 × 1330 × 1430
Equipment				
Polyester flat pleated filter		•	•	-
Pocket filter		-	-	•
Manual/Automatic filter cleaning		■/-	■ / -	■ / -
Adjustable main sweeper roller			•	•
Steering booster				
Hydraulic high container emptying		•		
Order no.		1.186-121.0	1.186-120.0	1.186-139.0
Price				

■ Included in the scope of supply.

KM 130/300 R Bp Pack

KM 130/300 R Bp

1.186-122.0

		 High working and transport speed Simple brush roller replacement without tools Traction drive and sweeping system fully hydraulic 	 High working and transport speed Simple brush roller replacement without tools Traction drive and sweeping system fully hydraulic
Technical data			
Drive		DC motor	DC motor
Power	kW	5	5
Voltage	V	36	36
Max. area performance with 1 / 2 side brushes	m²/h	9100 / 10850	9100 / 10850
Working width	mm	1000	1000
Working width with 1 or 2 brushes	mm	1300 / 1550	1300 / 1550
Waste container	1	300	300
Climbing ability	%	12	12
Working speed	km/h	7	7
Filter area	m²	5.5	5.5
Weight	kg	840	840
Dimensions (L × W × H)	mm	2150 × 1330 × 1430	2150 × 1330 × 1430
Equipment			
Polyester flat pleated filter			
Pocket filter		-	-
Manual/Automatic filter cleaning		■/-	■ / -
Adjustable main success veller		•	

1.186-129.0

■ Included in the scope of supply.

Order no.

Hydraulic high container emptying




Entry-level model to the industry class

Battery, gas or diesel-powered, the KM 120/250 R is impressive in industrial applications when eliminating dirt – whether coarse rubble or fine dusts. A large pocket filter guarantees dust-free sweeping even in heavily contaminated areas. The operation of the fully hydraulic machine using levers is also simple and user-friendly.









1 Robust design of the machine for safe work

- Permits applications in extreme external conditions.
- Leads to longer service life of components and machine.
- Standard flashing beacon increases safety for user and environment.

3 Simple operation, maintenance and servicing

- Simple technology with tried-and-tested components.
- Easy access to engine compartment permits fast, simple servicing and maintenance.
- Main sweeper roller and pocket filter can be replaced without tools.

2 Large-area pocket filter with vibration motor

- The large filter area guarantees dust-free work.
- Effective filter cleaning by means of vibrating motor.
- $\hfill \blacksquare$ Suitable for particularly large quantities of dust.

4 Dustpan principle

- Guarantees good cleaning results also with fine waste.
- Effortless pick-up of coarse waste.
- Low dust production.

TECHNICAL DATA AND EQUIPMENT

		KM 120/250 R LPG Classic	KM 120/250 R D Classic	KM 120/250 R Bp Pack Classic
		without tools	Robust steel chassis for tough industrial applications Simple brush roller replacement without tools Large pocket filter for dust-free work in dusty environments	 Robust steel chassis for tough industrial applications Simple brush roller replacement without tools Large pocket filter for dust-free work in dusty environments
Technical data				
Drive		Four-stroke LPG engine / Kubota	4-stroke diesel engine / Yanmar	DC motor
Power	kW	17.5	15.8	5
Voltage	V	-	-	36
Max. area performance with 1 / 2 side brushes	m²/h	10800 / 13500	10800 / 13500	7200 / 9000
Working width	mm	900	900	900
Working width with 1 or 2 brushes	mm	1200 / 1500	1200 / 1500	1200 / 1500
Waste container	I	250	250	250
Climbing ability	%	18	18	14
Working speed	km/h	9	9	6
Filter area	m²	6	6	6
Weight	kg	800	880	1220
Dimensions (L × W × H)	mm	2082 × 1250 × 1450	2082 × 1250 × 1450	2082 × 1250 × 1450
Equipment				
Pocket filter			-	-
Manual/Automatic filter cleaning		■ / -	I / -	I / -
Suction volume regulation			•	
Adjustable main sweeper roller		•	•	
Steering booster			•	•
Hydraulic high container emptying			•	
Order no.		1.186-001.0	1.186-000.0	1.186-003.0
Price				

[■] Included in the scope of supply.

KM 120/250 R Bp Classic

- Robust steel chassis for tough industrial applications
- Simple brush roller replacement without tools
- Large pocket filter for dust-free work in dusty environments

Technical data		
Drive		DC motor
Power	kW	5
Voltage	V	36
Max. area performance with 1 / 2 side brushes	m²/h	7200 / 9000
Working width	mm	900
Working width with 1 or 2 brushes	mm	1200 / 1500
Waste container	1	250
Climbing ability	%	14
Working speed	km/h	6
Filter area	m²	6
Weight	kg	750
Dimensions (L × W × H)	mm	2082 × 1250 × 1450

Equipment	
Pocket filter	I .
Manual/Automatic filter cleaning	■/-
Suction volume regulation	I .
Adjustable main sweeper roller	
Steering booster	
Hydraulic high container emptying	
Order no.	1.186-002.0
Price	

■ Included in the scope of supply.

125 CM RIDE-ON MACHINE WITH Tact

User-friendliness meets efficiency




With a working width of 125 cm, this sweeper is ideal for high area performance. Thanks to the hydraulic front-wheel drive, it can turn on the spot and effortlessly sweep out corners with the unique sweeping crescent brush. The main sweeper roller is located on the rear axle to prevent the sweeping system being grounded when driving over obstacles. Another new feature is the fully automatic and permanent filter cleaning system, which uses blasts of compressed air.

















1 Highly effective and automatic Tact filter cleaning system

- Thorough filter cleaning for continuous dust-free working.
- Automatic and permanent filter cleaning.
- Compact nano-coated polyester filter.

2 Sweeping crescent side brush (optional)

- Perfect corner cleaning in only one pass.
- Saves you time and money, since manual pre-cleaning is not required and there is no need to go over the same spot multiple times.
- Only activated when performing turning manoeuvres.

3 Roller brush on rear axle

- Excellent access for checking or changing the roller brush.
- $\hfill \blacksquare$ Safe driving over obstacles and ramps.
- Larger roller brush diameter for improved container filling.

4 Kärcher Intelligent Key

- User rights for machine settings can be assigned.
- Programmable in 19 different languages.
- Display information includes main sweeper roller wear.

CONFIGURATION OPTIONS

Choose: ▶ 1. Drive type: Petrol, diesel, liquid gas or battery ▶ ▶ 2. Attachment kits





Protective roof

Protective roof is compulsory in
high-bay warehouses. For reliable
and effective protection.



ashing beacon r attaching to the m

For attaching to the machine itself or on the protective roof. Improved safety for the user and those in the vicinity.



Working lights approved for road use For driving at dusk or in public



Easy service access
Divided service concept: Everything
the operator needs is under the side
hood, while service items are under
the seat.

CUSTOM FLEXIBILITY FOR YOUR CONFIGURATION

The KM 125/130 R with hydraulic high container emptying system can be emptied up to 1.55 metres. The machine is available with one of four different drive types. Choose from a wide range of accessories to tailor your machine to your needs. With the optional sweeping crescent side brush, efficiency is increased around bends, especially when sweeping out corners or turning. You can also add a comfort seat, flashing beacon, protective roof, weatherproof cab, lighting approved for road use and the Home Base, to name but a few.





1 Drives to meet your needs

The emission-free battery version is ideal for indoor use. The LPG version can also be used in well-ventilated inside areas. Petrol or diesel engines are available for outside areas.

2 High container emptying

Convenient hydraulic emptying up to 1.55 metres. The waste container tips backwards to protect the operator against unnecessary dust impact and prevent them coming into contact with the waste.



Adjustable standard seats or comfort seats with armrests are available.



Home Base

With the practical Home Base system, accessories such as a brush sweeping, especially indoors. or litter picker can be securely attached to the machine.



Side brush cover

Reduces dust dispersion during Robust steel spring under the cover effectively prevents damage to the sweeping. Convenient and easy to machine and the environment.



Water spraying system

A fine spray mist from a 30-litre water tank significantly reduces the amount of dust dispersed when

KM 125/130 R

		KM 125/130 R		
Version		Petrol/LPG	Diesel	Bp/Bp Pack
Motor rating	kW	10.3 / 9.3	6.6	2.5
Driving speed	km/h	8	8	8
Turning circle	m	<2.20	<2.20	<2.20
Sweeping width	mm	880	880	880
Sweeping width with 1 side brush	mm	1250	1250	1250
Sweeping width with 2 side brushes	mm	1700	1700	1700
Waste container capacity	1	130	130	130
Max. unloading height	m	1.55	1.55	1.55
Max. gradient	%	16/12	16	12
Area performance with 1 side brush	m²/h	10000	10000	10000
Area performance with 2 side brushes	m²/h	13600	13600	13600
Ctandard agricument				
Standard equipment Standard seat				
Pneumatic tyres				:
Right side brush			-	
Tact filter cleaning system				:
EASY Operation				
Flexible Footprint system				
(different roller brush contact pressures)		-		•
Teach system (automatic adjustment in the case of sweeper brush wear)		•	•	•
Power Plus system (additional torque on slopes)		•	•	•
Rear storage area				
Traction battery and battery charger		-	-	-/■
Optional accessories				
Sweeping crescent side brush				
Left side brush				
Comfort seat				
Solid rubber tyres				
Non-marking solid rubber tyres				
Protective roof				
Flashing beacon				
Flashing beacon on protective roof				
Home Base kit				
Working lights				
StVZO (approved for road use)				-
Litter picker				
Kärcher Fleet				
Additional weight for 18% climbing ability		□/-	-	-
Noise reduction kit		-		-
Water spraying system				
Side brush cover				
Other accessories				
Side brush, soft				•
Side brush, hard				
Main sweeper roller, soft				<u> </u>

■ Included in the scope of supply.

□ Available.

105 CM RIDE-ON MACHINE WITH Tact



The custom-configurable vacuum sweeper

Ride-on vacuum sweeper with highly effective, patented and fully automatic filter cleaning, unique sweeping crescent side brush (optional), automatic wear adjustment of the main sweeper roller via Teach System and new sweeping concept. With this new sweeping concept, positioned between the rear wheels, the sweeping system is protected when driving over obstacles and enables corners to be swept out in only three passes.

















1 Highly effective and automatic Tact filter cleaning system

- Thorough filter cleaning for continuous dust-free working.
- Automatic and permanent filter cleaning.
- Compact nano-coated polyester filter.

2 Sweeping crescent side brush (optional)

- Perfect corner cleaning in only one pass.
- Saves you time and money, since manual pre-cleaning is not required and there is no need to go over the same spot multiple times.
- Only activated when performing turning manoeuvres.

3 Roller brush on rear axle

- Excellent access for checking or changing the roller brush.
- Safe driving over obstacles and ramps.
- Larger roller brush diameter for improved container filling, including directly into a rubbish bag.

4 Kärcher Intelligent Key

- User rights for machine settings can be assigned.
- Programmable in 19 different languages.
- Display information includes main sweeper roller wear.

CONFIGURATION OPTIONS

Choose: ▶ 1. High or low container emptying ▶ ▶ 2. Drive type: Petrol, diesel, liquid gas or battery

▶ ▶▶ 3. Attachment kits



Protective roof






Kärcher Fleet
















Side brush cover



Left side brush



Sweeping crescent side brush



Pneumatic tyres, solid rubber tyres, non-marking solid rubber tyres

Leaf collection kit

Flashing beacon on a pole or on the protective roof



Protective roof Protective roof is compulsory in high-bay warehouses. For reliable and effective protection.



Flashing beacon For attaching to the machine itself or on the protective roof. Improved safety for the user and those in the

vicinity.



Working lights approved for road use For driving at dusk or in public



Rubbish bag disposal Sweep your waste directly into a rubbish bag for dust-free disposal.

CUSTOM FLEXIBILITY FOR YOUR CONFIGURATION

The KM 105/100 R with two-part container concept and the KM 105/110 R with hydraulic high container emptying are both available with one of four drive types. Choose from a wide range of accessories to tailor your machine to your needs. With the optional sweeping crescent side brush, efficiency is increased around bends, especially when sweeping out corners or turning. You can also add a comfort seat, flashing beacon, protective roof, weatherproof cab, lighting approved for road use and the Home Base, to name but a few.





1 One-of-a-kind leaf collector

Attachment kit to sweep up and collect large amounts of fallen leaves. The 300-litre collection sack fills up completely thanks to the sweep-andthrow principle and the large roller brush diameter. Standard sweeping containers and leaf collectors can be swapped in and out as needed within minutes - without having to use tools.

2 Convenient low container emptying

A two-part low container allows you to easily remove the container and transport it, as well as empty out the waste leaves with ease.



Contact-free high container emptying Home Base

emptying at a height of up to 1.55 metres. The waste container tips backwards to protect the operator against dust and prevent them coming into contact with the waste.



Convenient hydraulic high container With the practical Home Base system, accessories such as a brush sweeping, especially indoors. or litter picker can be securely attached to the machine.



Side brush cover

Reduces dust dispersion during Robust steel spring under the cover effectively prevents damage to the sweeping. Convenient and easy to machine and the environment.



Water spraying system

A fine spray mist from a 30-litre water tank significantly reduces the amount of dust dispersed when

KM 105

		KM 105									
		High containe	er emptying K	M 105/110 R	Low container emptying KM 105/100 R						
Version		Petrol/LPG	Diesel	Bp/Bp Pack	Petrol/LPG	Diesel	Bp/Bp Pack				
Motor rating	kW	6.5 / 5.9	4.5	1.44	6.5 / 5.9	4.5	1.44				
Driving speed	km/h	7	7	6	7	7	6				
Turning circle	m	< 2	< 2	< 2	< 2	< 2	< 2				
Sweeping width	mm	640	640	640	640	640	640				
Sweeping width with 1 side brush	mm	1050	1050	1050	1050	1050	1050				
Sweeping width with 2 side brushes	mm	1400	1400	1400	1400	1400	1400				
Waste container capacity	1	110	110	110	2 × 50	2 × 50	2 × 50				
Max. unloading height	m	1.55	1.55	1.55	Floor	Floor	Floor				
Max. gradient	%	18 / 12	16	12	18 / 12	16	12				
Area performance with 1 side brush	m²/h	7350	7350	6300	7350	7350	6300				
Area performance with 2 side brushes	m²/h	9800	9800	8400	9800	9800	8400				
Area performance with 2 state prosites	/	3000	3000	0400	3000	3000	0400				
Standard equipment											
Standard seat		•	•	•	•	•	•				
Pneumatic tyres		•	•	•	•	•	•				
Right side brush		•	•	•	•	•	•				
Tact filter cleaning system		•		•	•		•				
EASY Operation		•	•	•	•	•	•				
Footprint system (different roller brush contact pressures)		•	•	•	•	•	•				
Teach system (automatic adjustment in the case of swee	per brush wear)	•	•	•	•	•	•				
Power Plus system (additional torque on slopes)		•	•	•	•	•	•				
Rear storage area		•				-					
Traction battery and battery charger Optional accessories				-/■			-/■				
Sweeping crescent side brush											
Left side brush											
Comfort seat											
Solid rubber tyres				-			-				
Non-marking solid rubber tyres											
Protective roof											
Flashing beacon											
Flashing beacon on protective roof											
Home Base kit											
Working lights											
StVZO (approved for road use)				-			-				
Litter picker											
Kärcher Fleet											
Noise reduction kit		-		-	-		-				
Water spraying system		□/-			□/-						
Leaf collection kit		-	-	-							
Side brush cover											
Other accessories											
Side brush, soft				•			•				
Side brush, hard											
Side Di USII, Ildi d				_							
Main sweeper roller, soft				•			-				


■ Included in the scope of supply.
□ Available.

100 CM RIDE-ON MACHINE

Top performance in continuous use the high-performance class

The comfortable ride-on sweeper KM 100/100 R is designed for medium to large-sized interior and exterior surfaces. Thanks to its high sweeping performance, low operating costs and high user-friendliness, the purchase quickly pays for itself.











1 Impact protection

Protects the sweeper and obstacles within the area being cleaned.

3 Easy to maintain

■ Filter and roller brush easy to remove without tools for flexible

2 Large filter area with automatic filter cleaning system

- The filter is automatically cleaned when the machine is switched off for continuous low-dust sweeping for long periods of uninterrupted use.
- Filter cleaning can also take place manually.
- Filter replacement without tools.

4 EASY Operation operating concept

- Clear and logical arrangement of all controls in the handle and field of view for ease of use.
- Standard symbols for all Kärcher sweepers.

TECHNICAL DATA AND EQUIPMENT

		KM 100/100 R Lpg	KM 100/100 R D	KM 100/100 R G
		Automatic filter cleaning systemErgonomic operating conceptFully hydraulic, low maintenance	Automatic filter cleaning systemErgonomic operating conceptFully hydraulic, low maintenance	Automatic filter cleaning systemErgonomic operating conceptFully hydraulic, low maintenance
Technical data				
Drive		Four-stroke LPG engine / Honda	4-stroke diesel engine / Yanmar	Four-stroke petrol engine / Honda
Power	kW	6.7	4.4	6.7
Voltage	V	-	-	-
Max. area performance with 1 / 2 side brushes	m²/h	8000 / 10400	8000 / 10400	8000 / 10400
Working width	mm	700	700	700
Working width with 1 or 2 brushes	mm	1000 / 1300	1000 / 1300	1000 / 1300
Waste container	1	100	100	100
Climbing ability	%	18	18	18
Working speed	km/h	8	8	8
Filter area	m²	6	6	6
Weight	kg	340	340	340
Dimensions (L × W × H)	mm	2006 × 1005 × 1343	2006 × 1005 × 1343	2006 × 1005 × 1343
Equipment				
Polyester round filter			•	•
Manual/Automatic filter cleaning		■/■	■/■	■ / ■
Floating main sweeper roller			•	•
Suction volume regulation				
Battery and built-in charger included		-	-	-
Order no.		1.280-107.0	1.280-115.0	1.280-105.0
Price				

■ Included in the scope of supply.

		KM 100/100 R Bp Pack	KM 100/100 R Bp
		Automatic filter cleaning systemElectric traction driveEmission-free operation	Automatic filter cleaning systemElectric traction driveEmission-free operation
Technical data			
Drive		DC motor	DC motor
Power	kW	2.1	2.1
Voltage	V	24	24
Max. area performance with 1 / 2 side brushes	m²/h	6000 / 7800	6000 / 7800
Working width	mm	700	700
Working width with 1 or 2 brushes	mm	1000 / 1300	1000 / 1300
Waste container	I	100	100
Climbing ability	%	15	15
Working speed	km/h	6	6
Filter area	m²	6	6
Weight	kg	540	320
Dimensions (L × W × H)	mm	2006 × 1005 × 1343	2006 × 1005 × 1343
Equipment			
Polyester round filter			I
Manual/Automatic filter cleaning		■/■	■ / ■
Floating main sweeper roller			
Suction volume regulation		•	•
Battery and built-in charger included			-
Order no.		1.280-112.0	1.280-103.0
Price			
■ Included in the scope of supply.			

90 CM RIDE-ON MACHINE WITH Tact



In addition to its powerful performance, easy handling, driving comfort and manoeuvrability, the KM 90/60 R Adv has many impressive features, including the patented and fully automatic Tact filter cleaning system. Thanks to a large tank volume, the petrol version permits long periods of use. It also has an automatic choke for an optimum start.

The smart way to sweep











1 Robust, compact construction style with pick-up area

- Built to last, high reliability.
- Safety and manoeuvrability.
- Additional components such as a spare canister or manual cleaning machines can be securely fitted and carried along.

3 Tact: fully automatic, continuous filter cleaning

- Highly effective filter cleaning for continuous dust-free operation.
- Compact filter size with long service life.
- Easy access to the filter.

2 EASY Operation operating concept

- Logical and clear.
- All control elements are clearly arranged and within easy reach.

4 Home Base for greater flexibility

- $\hfill \blacksquare$ Different practical connections for other accessories.
- Easy to carry, for example, a litter picker, brush or an additional

TECHNICAL DATA AND EQUIPMENT

		KM 90/60 R G Adv	KM 90/60 R Bp Pack Adv	KM 90/60 R Bp Adv
		 With fully automatic and highly effective Tact filter cleaning system Integrated Home Base Retractable side brush 	 With fully automatic and highly effective Tact filter cleaning system Integrated Home Base Retractable side brush 	 With fully automatic and highly effective Tact filter cleaning system Integrated Home Base Retractable side brush
Technical data				
Power	kW	6.6	1.2	1.2
Max. area performance with 1 / 2 side brushes	m²/h	7200 / 9200	5400 / 6900	5400 / 6900
Working width	mm	615	615	615
Working width with 1 or 2 brushes	mm	900 / 1150	900 / 1150	900 / 1150
Waste container	I	60	60	60
Climbing ability	%	18	12	12
Working speed	km/h	8	6	6
Weight	kg	260	355	225
Dimensions (L × W × H)	mm	1635 × 980 × 1260	1635 × 980 × 1260	1635 × 980 × 1260
Equipment				
Suction volume regulation				

Equipment			
Suction volume regulation	-	•	•
Manual/Automatic filter cleaning	- / I	- / =	- / I
Polyester flat pleated filter		•	•
Floating main sweeper roller			
Battery and built-in charger included	-	•	-
Order no.	1.047-300.0	1.047-302.0	1.047-301.0
Price			

■ Included in the scope of supply.

Accessories			
Product name	Order no.	Description	Price
Flat pleated filter	5.731-635.0	Plastic filter, water-resistant, washable, saves maintenance costs.	
Dual Tact filter cleaning system	2.643-176.0	For sweeping on particularly dusty ground.	
Dual Tact filter cleaning system	2.851-392.7	For sweeping on particularly dusty ground.	
Carpet sweeping kit	2.851-334.7	Carpet sweeping kit for cleaning carpet surfaces, includes antistatic roller brush.	

85 CM RIDE-ON MACHINE



Manoeuvrable and compact the comfortable entry-level model to the ride-on range

Our entry-level model to the world of ride-on sweepers plays to its strengths especially in confined spaces. The high area performance ensures economical and efficient cleaning. The clever concept of the battery-powered device is also impressive with the simple operation and integration of our Home Base system with its various options to carry additional cleaning tools and implements.









1 Clever container concept

- 2 tanks for simple removal and safe emptying of waste.
- Waste container free of rough edges permits emptying without leaving Adjustment of driver's seat without the need for any tools. behind any residues.
- Castors on waste container simplify handling when emptying.

3 Clever ergonomics for high level of comfort at workplace

- Clear and ergonomic attachment of operating elements.
- Height-adjustable steering wheel.

2 Efficient filter system

- Polyester flat pleated filter.
- Effective cleaning with dual scraper. Comfortable operation from
- Access to the filter through wide-opening cover without the need for any tools.

4 Integrated Home Base system and storage areas

- Versatile and practical connection for simple carrying of other cleaning
- For simple carrying of litter picker, brush, cloths or an additional container, for example.
- Large storage area in rear of machine.

TECHNICAL DATA AND EQUIPMENT

■ Included in the scope of supply.

		KM 85/50 R Bp Pack	KM 85/50 R Bp
		 Compact design for maximum manoeuvrability Easy and intuitive operation Retractable side brush 	Compact design for maximum manoeuvrabilityEasy and intuitive operationRetractable side brush
Technical data			
Drive		DC motor	DC motor
Power	w	1000	1000
Voltage	V	24	24
Max. area performance with 1 / 2 side brushes	m²/h	5100 / 6510	5100 / 6510
Working width	mm	615	615
Working width with 1 or 2 brushes	mm	850 / 1085	850 / 1085
Waste container	I	50	50
Climbing ability	%	12	12
Working speed	km/h	6	6
Filter area	m²	2.1	2.1
Weight	kg	237	177.5
Dimensions (L × W × H)	mm	1270 × 870 × 1170	1270 × 870 × 1170
Equipment			
Polyester flat pleated filter			•
Manual/Automatic filter cleaning		■ / -	■ / -
Suction volume regulation		•	•
Adjustable main sweeper roller		-	-
Floating main sweeper roller			I
Wear indicator for main sweeper roller			•
Speed regulation of side brush		•	•
Battery and built-in charger included		•	-
Order no.		1.351-127.0	1.351-126.0
Price			

Accessories			
Product name	Order no.	Description	Price
Standard roller brush	4.762-430.0	Water-resistant universal bristles, durable, suitable for all surfaces.	
Flat pleated filter	5.731-585.0	Plastic filter, water-resistant, washable, saves maintenance costs.	
Attachment kit 2nd side brush, left	2.852-321.0	Complete, including standard side brushes for increased area performance.	
Carpet sweeping kit	2.852-499.0	Carpet sweeping kit for cleaning carpet surfaces, includes antistatic roller brush.	

85 CM WALK-BEHIND SWEEPER

The high-performance walk-behind machine for brilliant cleaning results

The compact and durable KM 85/50 W offers high area coverage and efficiency on medium size areas together with the highest level of comfort. With different equipment details such as a second side brush, reverse gear, etc.









1 Efficient filter system

- 2.1 m² filter area.
- Manual filter cleaning system.
- Washable polyester filter.

2 Two-walled rotating frame

- Robust and corrosion-free.
- For the toughest jobs.

3 Traction Drive

- Intuitive operation.
- With optional reverse gear.

4 Waste pick up and emptying

- Efficient sweeping thanks to large working width.
- Also sweeps wet surfaces.
- 50-litre container for continuous working.

TECHNICAL DATA AND EQUIPMENT

		KM 85/50 W G Adv	KM 85/50 W G	KM 85/50 W Bp Pack Adv
		 Robust double-wall frame Main sweeper roller can be raised Reverse mode, operating hours counter and floating main sweeper roller 	Robust double-wall frameMain sweeper roller can be raisedIntuitive drive operation	 Robust double-wall frame Main sweeper roller can be raised Reverse mode, operating hours counter and floating main sweeper roller
Technical data				
Drive		Four-stroke petrol engine / Honda	Four-stroke petrol engine / Honda	DC motor
Power	w	3300	3300	912
Voltage	V	-	-	24
Max. area performance with 1 / 2 side brushes	m²/h	3825 / 4725	3825 / 4725	3825 / 4725
Working width	mm	610	610	610
Working width with 1 or 2 brushes	mm	850 / 1050	850 / 1050	850 / 1050
Waste container	I	50	50	50
Climbing ability	%	18	18	15
Working speed	km/h	4.5	4.5	4.5
Filter area	m²	2.1	2.1	2.1
Weight	kg	126	123	180
Dimensions (L × W × H)	mm	1355 × 910 × 1155	1355 × 910 × 1155	1355 × 910 × 1155
Equipment				
Polyester flat pleated filter		•	•	
Manual filter cleaning				
Drive with forward and reverse gears		■/■	I / -	■ / ■
Adjustable main sweeper roller		-	•	-
Floating main sweeper roller			-	
Battery and built-in charger included		-	-	•
Order no.		1.351-110.0	1.351-109.0	1.351-115.0
Price				

■ Included in the scope of supply.

		KM 85/50 W Bp Pack	K	M 85/50 W Bp Adv	KM 85/50 W Bp
		Robust double-wall frameMain sweeper roller can be raisedIntuitive drive operation		Robust double-wall frame Main sweeper roller can be raised Reverse mode, operating hours counter and floating main sweep- er roller	 Robust double-wall frame Main sweeper roller can be raised Intuitive drive operation
Technical data					
Drive		DC motor	DO	motor	DC motor
Power	W	912	91	2	912
Voltage	V	24	24	ļ	24
Max. area performance with 1 / 2 side brushes	m²/h	3825 / 4725	38	325 / 4725	3825 / 4725
Working width	mm	610	61	.0	610
Working width with 1 or 2 brushes	mm	850 / 1050	85	0 / 1050	850 / 1050
Waste container	1	50	50)	50
Climbing ability	%	15	15		15
Working speed	km/h	4.5	4.5	5	4.5
Filter area	m²	2.1	2.	1	2.1
Weight	kg	177	11	5	112
Dimensions (L × W × H)	mm	1355 × 910 × 1155	13	55 × 910 × 1155	1355 × 910 × 1155
Equipment					
Polyester flat pleated filter		•			•
Manual filter cleaning					
Drive with forward and reverse gears		I / -		/■	I / -
Adjustable main sweeper roller			-		
Floating main sweeper roller		-			-
Battery and built-in charger included			-		-
Order no.		1.351-114.0	1.3	351-108.0	1.351-107.0
Price					
■ Included in the scope of supply.					

75 CM WALK-BEHIND SWEEPER



Clean entry into the walk-behind class

Compact and agile, the KM 75/40 W cleans small to medium-sized areas with excellent results. With a convenient drive and powerful vacuum system, available with a powerful petrol engine or very quiet battery-powered motor.









1 Waste container with trolley handle

- Waste container with recessed grips easy to remove and empty.
- Short disposal times.

- 3 Easy to maintain
- Filter and roller brush easy to remove without tools for flexible

2 Efficient filter system with mechanical filter cleaning

- 1.8 m² filter area for long operating periods.
- Made of washable polyester for durability.
- $\hfill \blacksquare$ Mechanical filter cleaning system with ergonomic handle.

4 EASY Operation operating concept

- Clear and logical arrangement of all controls in the handle and field of view for ease of use.
- Standard symbols for all Kärcher sweepers.

TECHNICAL DATA AND EQUIPMENT

		KM 75/40 W G	KM 75/40 W Bp Pack	KM 75/40 W Bp
		 Waste container with trolley handle Roller brush replacement without tools Effective filter cleaning system with filter replacement on the clean side without tools 	 Waste container with trolley handle Roller brush replacement without tools Effective filter cleaning system with filter replacement on the clean side without tools 	 Roller brush replacement without tools Effective filter cleaning system
Technical data				
Drive		Four-stroke petrol engine / Honda	DC motor	DC motor
Power	W	3300	400	400
Voltage	V	-	24	24
Max. area performance	m²/h	3375	3375	3375
Working width	mm	550	550	550
Working width with one side brush	mm	750	750	750
Waste container	1	40	40	40
Climbing ability	%	15	12	12
Working speed	km/h	4.5	4.5	4.5
Filter area	m²	1.8	1.8	1.8
Weight	kg	84	124	78
Dimensions (L × W × H)	mm	1430 × 780 × 1180	1430 × 780 × 1180	1430 × 780 × 1180
Equipment				
Fold-down push handle		•	•	
Overhead sweeping principle				
Drive with forward and reverse gears		■ / -	I / -	■ / -
Adjustable main sweeper roller		•		
Coarse dirt flap				•
Suction volume regulation		•	•	
Polyester flat pleated filter				
Order no.		1.049-205.0	1.049-207.0	1.049-206.0
Price				

■ Included in the scope of supply.

Accessories			
Product name	Order no.	Description	Price
Flat pleated filter	5.731-635.0	Plastic filter, water-resistant, washable, saves maintenance costs.	
Standard roller brush	6.906-884.0	Water-resistant universal bristles, extremely durable, suitable for all surfaces.	
Main sweeper roller soft / natural	6.906-886.0	Specially designed with natural bristles for sweeping fine dust on smooth floors indoors.	
Carpet sweeping kit	2.641-571.0	Carpet sweeping kit for cleaning carpeted surfaces, consists of fluff filter, triple steering roller and antistatic roller brush.	

80 CM FRONT SWEEPER



Compact all-rounder, all year round

Whether for normal sweeping (with or without waste container), sweeping snow or for winter use with optional snow blade - the ergonomic and manoeuvrable walk-behind sweeper performs well all year long.









1 Height-adjustable roller brush

- Easy regulation of the brush pressure.
- $\hfill \blacksquare$ For adjusting when worn or for adapting to a particular surface.

3 Snow blade for use with deeper snow

- Folding spring mechanism for optimum shock absorption.
- With gliding skids with four settings.
- Rubber strip which can be used on both sides.

2 Tilting of the roller brush

- Adjustment clip with locking for a fixed tilted position left and right.
- Tilting also possible with the optional snow blade.
- Rubber scrubber protection prevents damage to the surroundings.

4 Waste container

- For direct dirt pick-up.
- The waste container can be easily adjusted when the roller brush is

TECHNICAL DATA AND EQUIPMENT

KM 80 W G

- For use all year round
- Great agility and low space requirement thanks to its compact design
- Multi-functional use thank to optional waste container and snow blade

Drive Four-stroke petrol engine / Honda Power kW 2.6 Max. area performance m²/h 1680 Working width mm 800	
Max. area performance m²/h 1680	
Working width mm 800	
Totally Hadi	
Working width with one side brush -	
Waste container I 40	
Climbing ability % 12	
Working speed km/h 2.1	
Filter area -	
Weight kg 70	
Dimensions (L × W × H) mm 1410 × 800 × 1060	

Equipment		
Fold-down push handle		
Dustpan principle		
Drive with forward and	reverse gears	■ /-
Adjustable main sweep	er roller	
Floating main sweeper	roller -	-
Order no.	1	1.335-500.0
Price		

■ Included	in	the	scope	of	supply.

Accessories			
Product name	Order no.	Description	Price
Standard roller brush	6.963-108.0	Water-resistant universal bristles for good sweeping results for snow or other waste (set consists of two single roller brushes).	
Snow blade	2.851-446.0	For use in winter. With spring-mounted folding mechanism and adjustable gliding skids.	
Waste container	2.851-569.0	For sweeping up grit or other dirt into a waste container that is stable and easy to empty.	

70 CM COMFORT CLASS

Compact, convenient and universal

The extremely compact and efficient KM 70/30 C sweeps silently. The main roller brush and side brushes are battery-powered, ensuring superb sweeping results and reducing physical effort. The KM 70/30 cleans right into the corners and is suitable for indoor and outdoor use.











1 Adjustable push handle

- Excellent ergonomics thanks to three height positions.
- Foldable for space-saving storage.

3 Easy to transport

- Front and rear carrying handles for easy transport and loading
- Wheels protruding to the rear make transporting the unit over steps easier

2 EASY Operation operating concept

Easy to use programme selector switch.

4 Fine dust suction (Adv version only)

- Electric suction fan for the suction of fine dust from the waste container
- Can be switched off for sweeping wet floors.

TECHNICAL DATA AND EQUIPMENT

		KM 70/30 C Bp Pack Adv KM 70/30 C Bp Pack	KM 70/30 C Bp Adv KM 70/30 C Bp
		 With charger and batteries (Bp Pack version) Electrically powered main sweeper roller and side brush Roller brush and side brushes continuously adjustable 	 With charger and batteries (Bp Pack version) Electrically powered main sweeper roller and side brush Roller brush and side brushes continuously adjustable
Technical data			
Drive		Manual	Manual
Power	W	195 150	195 150
Voltage	V	12	12
Area performance	m²/h	2800	2800
Working width	mm	480	480
Working width with one side brush	mm	700	700
Waste container	1	42	42
Filter area	m²	0.61	0.61
Battery charging time	h	12	-
Operation time	h	2.5 3.5	-
Weight	kg	48 45.1	38 32
Dimensions (L × W × H)	mm	1240 × 710 × 1150	1240 × 710 × 1150
Equipment			
Electric sweeping drive		•	
Adjustable main sweeper roller			•
Manual filter cleaning		■ -	■ -
Fold-down push handle		•	
Battery and built-in charger included			-
Suction		■ -	■ -
Order no.		1.517-213.0 -214.0	1.517-212.0 -211.0
Price			

	Included	in	the	scope	of	gaus	ľ
_							

Accessories			
Product name	Order no.	Description	Price
ABS litter picker set	2.640-908.0	For picking up refuse.	
Flat pleated filter	6.904-176.0	Paper filters for optimum fine dust filtering for dust-free sweeping (only Adv).	
Standard roller brush	6.907-041.0	Water-resistant universal bristles, durable, suitable for all surfaces.	
Standard side brushes	6.966-005.0	Water-resistant universal bristles, extremely durable, suitable for all types of surfaces.	

70 CM PUSH CLASS



Lightweight and simple - for quick clean-ups

The KM 70/20 C is ideal for sweeping small areas indoors and outdoors. It cleans better and faster than a broom and is almost dust-free thanks to the controlled air flow and integrated dust filter.









1 Main sweeper roller drive

The main sweeper roller is driven by both wheels – for excellent results when turning to the left or right.

3 Large dirt hopper

■ Ergonomic container handle for easy handling and emptying.

2 Adjustable push handle

- Excellent ergonomics thanks to three height positions.
- Foldable for space-saving storage.

4 Dust filter

Dust filter cleans the exhaust air and prevents dust development while sweeping.

TECHNICAL DATA AND EQUIPMENT

		KM 70/20 C	KM 70/20 C 2SB	KM 70/15 C
		 Roller brush driven by both wheels Push handle adjustable in 3 positions Roller brush and side brushes continuously adjustable 	 Roller brush driven by both wheels Push handle adjustable in 3 positions Roller brush and side brushes continuously adjustable 	 Roller brush driven by both wheels Fold-down push handle 4x adjustable side brush
Technical data				
Drive		Manual	Manual	Manual
Area performance	m²/h	2800	3680	2800
Working width	mm	480	480	480
Working width with one side brush	mm	700	700	700
Working width with 2 side brushes	mm	-	920	-
Waste container	I	42	42	42
Weight	kg	21	26	20
Weight incl. packaging	kg	24.6	26	20
Dimensions (L × W × H)	mm	794 × 406 × 927	1300 × 920 × 1050	1300 × 810 × 1040
Equipment				
Fine dust filter			•	-
Manual sweeping drive			•	

Equipment			
Fine dust filter	•	•	-
Manual sweeping drive	•		
Adjustable main sweeper roller	•	•	-
Seitenbesen klappbar	•		-
Seitenbesen einstellbar	•	•	•
Seitenbesen stufenlos einstellbar	•		-
Fold-down push handle	•	•	-
Order no.	1.517-106.0	1.517-107.0	1.517-151.0
Price			

■ Included in the scope of supply.

Accessories			
Product name	Order no.	Description	Price
ABS litter picker set	2.640-908.0	For picking up refuse.	
Standard roller brush	6.907-041.0	Water-resistant universal bristles, durable, suitable for all surfaces.	
Standard side brushes	6.966-005.0	Water-resistant universal bristles, extremely durable, suitable for all types of surfaces.	
Main sweeper roller, soft	6.903-995.0	Sweeps up fine dust on all surfaces, both on inside and outside areas.	


THE RIGHT EQUIPMENT FOR EVERY APPLICATION.

You can use our sweepers and vacuum sweepers on different surfaces and for a wide variety of cleaning tasks. We offer an extensive range of accessories for this, from roller brushes and filters through to various attachment kits. These enable you to turn your hand to even more applications and maximise your machine's efficiency.



Table of contents: Sweeper/vacuum sweeper accessories

· · · · · · · · · · · · · · · · · · ·		
Filters	Page	66
Roller brushes	Page	67
Side brushes	Page	67
Cabs, protective roofs, flashing beacons	Page	67
Working lights, approval for road use, tyres	Page	68
Attachment kits for special applications and for increasing productivity	Page	68
Accessories for Home Base and other equipment	Page	68
Batteries and battery chargers	Page	68



- 1 High-quality filter with dust class M and 99.9% separation degree
- 2 Cleaning unfilled artificial turf areas with our specially developed attachment kits
- 3 Cleaning large carpeted areas with our specially developed attachment kits
- 4 Tyres for every need: Convenient pneumatic tyres or puncture-proof tyres made of solid rubber, non-marking version also available
- 5 For greater safety: Cabs, protective roofs, flashing beacons or working lights
- 6 Reduce dust dispersion by the side brushes with the water spraying system

- 7 Reduce dust dispersion by the side brushes with the perfectly fitting side brush cover
- 8 Main sweeper rollers for every kind of dirt and surface: Standard, soft or with hard bristles
- 9 Sweep out corners without leaving any dirt behind in a single pass with our unique sweeping crescent side brush
- 10 Increased area performance with additional left-hand side brush
- 11 Snow blade with shock absorbers for winter use
- 12 Ready for use all year round with large waste container

FILTERS




State-of-the-art cleaning, high-quality filter materials, exact adjustment to the respective application and maximum efficiency are the key features of the filter systems in our sweepers. As filtering dust is one of the core tasks of a Kärcher sweeper, we optimise the interaction of filter area, separation degree and type of cleaning in a continuous process. This way we not only ensure the best possible filtering, but also guarantee the protection of the user.
















	/
17	18-19

	Order no.	Price	Description		KM 170/600 R D KM 150/500 R PG / KM 150/500 R D KM 150/500 R D Classic KM 130/500 R Bp / KM 150/500 R Bp Pack KM 130/300 R Bp / KM 150/500 R Bp Pack KM 130/300 R Bp Pack / KM 130/300 R Bp KM 130/300 R Bp Pack / KM 130/300 R Bp KM 120/250 R LPG Classic / KM 120/250 R D Classic / KM 120/250 R Bp Pack Classic KM 120/250 R LPG Classic / KM 120/30 R Bp KM 120/250 R LPG Classic / KM 125/130 R Bp KM 125/130 R Bp / KM 125/130 R Bp KM 125/130 R Bp / KM 125/130 R Bp KM 125/130 R Bp / KM 105/100 R D / KM 105/100 R G KM 105/100 R LPG / KM 105/110 R Bp / KM 105/110 R R KM 105/100 R LPG / KM 105/110 R B / KM 105/100 R G KM 100/100 R Bp Pack / KM 105/100 R Bp KM 100/100 R Bp Pack / KM 105/100 R Bp KM 100/100 R Bp Pack / KM 105/100 R Bp KM 100/100 R Bp Pack / KM 105/100 R Bp KM 85/50 W G Adv / KM 85/50 R Bp KM 85/50 W Bp Pack / KM 85/50 W Bp KM 85/50 W Bp Pack / KM 85/50 W Bp KM 70/30 C Bp Pack KM 70/30 C Bp KM 70/30 C Bp KM 70/30 C Bp KM 70/30 C BP
Pocket filter	Order 110.	Price	Description		
Pocket filter, white	1 6.988-490.0	1	Pocket filter with very large filter area for particularly dusty application areas. Ideal for very fine	1	
r ochec micr, winte	2 6.988-657.0		dusts and large quantities of dirt.	2	
	3 6.988-804.0			3	
Pocket filter, green	4 6.988-704.0		Water-resistant pocket filter with very large filter area. Ideal for dusty application areas and	4	
	5 6.988-658.0		intake of large quantities of fine dust.	5	
	6 6.988-805.0			6	
Round filter					
Round filter	7 6.414-532.0		Plastic filter, water-resistant, washable, reduces maintenance costs.	7	
Flat pleated filter					
Flat pleated filter, green	8 6.988-160.0		Flat pleated filter with high separation degree, saves on maintenance costs, ensures optimum	8	
	9 6.988-159.0		waste air cleaning.	9	
	10 6.988-158.0			10	
Flat pleated filter, white	11 6.987-691.0		Plastic filter for standard use.	11	
	12 6.987-177.0			12	
Electrical Char	13 6.987-519.0		Physic Character with the selection of t	13	
Flat pleated filter	14 6.907-519.0		Plastic filter, water-resistant, washable, reduces maintenance costs.	14	
	15 5.731-585.0		-	15 16	
Elat pleated filter paper	16 5.731-635.0			10	
Flat pleated filter, paper Flat pleated filter, paper	17 6.904-367.0		Paper, dust class M.	17	
Foam filter	17 0.304 307.0		1 aper, door class in.		
Filter inlay	18 5.731-625.0		Plastic filter, water-resistant, washable, reduces maintenance costs.	18	
-	19 5.731-642.0			19	
■ Included in the scope of supply		More Kär	Legional accessories can be found on the following pages		

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.

ROLLER BRUSHES



Our standard roller brushes are made of high-quality materials for durability. They are water-resistant and suitable for all types of surfaces. Other roller brushes are available as accessories, ideally adapted for specific home cleaning tasks.



























	Order no.	Length / width	Diameter	Price Description		KM 150/500 R D KM 150/500 R LPG / KM 150/500 R D KM 150/500 R BP C Classic KM 150/500 R BP / KM 150/500 R BP Pack KM 130/300 R BP / KM 130/300 R BP Pack KM 130/300 R BP Pack / KM 130/300 R BP KM 130/300 R BP Pack / KM 130/300 R BP KM 130/300 R BP Pack / KM 130/300 R BP KM 120/300 R BP Classic KM 120/30 R BP Classic KM 125/130 R BP / KM 125/130 R C / KM 125/130 R LPG KM 125/130 R BP / KM 125/130 R BP Pack KM 125/130 R BP / KM 125/130 R BP Pack KM 125/130 R BP / KM 125/130 R BP Pack KM 125/130 R BP / KM 105/100 R BP Pack KM 105/100 R BP / KM 105/100 R BP Pack KM 105/110 R BP / KM 105/100 R BP KM 105/110 R BP Pack / KM 105/100 R BP KM 105/100 R BP Pack / KM 100/100 R BP KM 105/100 R BP Pack / KM 100/100 R BP KM 105/100 R BP Pack / KM 100/100 R BP KM 85/50 W B Pack / KM 85/50 R BP KM 85/50 W BP Pack / KM 75/40 W BP KM 85/50 W BP KM 85/50 W BP KM 75/40 W BP Pack / KM 70/30 C BP Pack / KM 70/30 C BP AdV KM 75/40 W BP KM 70/30 C BP Pack / KM 70/30 C 25B KM 70/30 C C 25B KM 70/30 C C 25B
Standard roller brush						
Standard roller brush	1 6.987-441.0	1344 mm	400 mm	Water-resistant universal bristles, durable, suitable for all surfaces.	1	
	2 6.987-085.0	1194 mm	380 mm		2	
	3 6.987-438.0	1000 mm	300 mm		3	
	4 6.988-800.0	900 mm	280 mm		4	
	5 4.762-525.0	880 mm	400 mm		5	
	6 4.762-529.0	640 mm	400 mm		6	
	7 6.906-375.0	700 mm	285 mm		7	
	8 4.762-430.0	615 mm	250 mm		8	
	9 6.906-508.0	620 mm			9	
	10 6.906-509.0	620 mm			10	
	11 6.906-884.0	550 mm			11	
	12 6.906-041.0	480 mm			12	
	13 6.907-041.0	480 mm			13	
	14 6.963-108.0	300 mm		Water-resistant universal bristles for good sweeping results for snow or other waste (set consists of two single roller brushes).	14	
Main sweeper roller, soft						
Main sweeper roller, soft	15 6.987-469.0	1344 mm	400 mm	Specially designed with polypropylene bristles for fine dust sweeping	15	
	16 6.987-464.0	1194 mm	380 mm	on smooth floors in both inside and outside areas.	16	
	17 6.987-460.0	1000 mm	300 mm		17	
	18 6.988-801.0		280 mm		18	
	19 6.903-995.0			Sweeps up fine dust on all surfaces, both on inside and outside areas.	19	
Main sweeper roller, soft/natural	20 6.987-443.0		400 mm	Specially designed with natural bristles for sweeping fine dust on	20	
	21 6.987-437.0		380 mm	smooth floors indoors.	21	
	22 6.987-440.0		300 mm		22	
	23 4.762-526.0		400 mm		23	
	24 4.762-523.0		400 mm		24	
	25 6006 5220	1				
	25 6.906-533.0	700 mm	285 mm		25	
	26 4.762-442.0	615 mm	250 mm		26	
		615 mm 620 mm				

[■] Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.













					R D R LPG / KM 150/500 R D	K D Classic R Bp / KM 150/500 R Bp Pack R LPG / KM 130/300 R D	R D Classic R Bp Pack / KM 130/300 R Bp R LPG Classic / KM 120/250 R D Classic / KM 120/250 R Bp Pack Class		R Bp / KM 105/100 R Bp Pack R D / KM 105/100 R G / KM 105/100 R LPG	R B / KM 105/110 R Bp Pack R D / KM 105/110 R G / KM 105/110 R LPG	N R Lpg / KM 100/100 R D / KM 100/100 R G R Bp Pack / KM 100/100 R Bp G Adv / KM 90/60 R Bn Pack Adv / KM 90/60 R Bn Adv	3	V G V Bp Pack Adv	W Bp Pack W Bp Adv	W BP W G W Bp Pack / KM 75/40 W Bp	. Bp Pack Adv / KM 70/30 C Bp Pack / KM 70/30 C Bp Adv . Rn	./ KM 70/20 C 2SB
	Order no. Length / wid	th Diameter	Price Description		KM 170/600 KM 150/500	KM 150/500 KM 150/500 KM 130/300	KM 130/300 KM 130/300 KM 120/250	KM 120/250 KM 125/130 KM 125/130	KM 105/100 KM 105/100	KM 105/110 KM 105/110	KM 100/100 KM 100/100 KM 90/60 R	KM 85/50 R KM 85/50 V	KM 85/50 V KM 85/50 V	KM 85/50 KM 85/50 KM	KM 75/40 KM 75/40	KM 80 W G KM 70/30 C KM 70/30 C	KM 70/20 C KM 70/15 C
Main sweeper roller, hard	Order no. Length / wid	th Diameter	Price Description		KM 170/600 KM 150/500	KM 150/500 KM 130/300	KM 130/300 KM 130/300 KM 120/250	KM 120/250 KM 125/130 KM 125/130	KM 105/100 KM 105/100	KM 105/110 KM 105/110	KM 100/100 KM 100/100 KM 90/60 R	KM 85/50 N KM 85/50 V	KM 85/50 V KM 85/50 V	KM 85/50 V	KM 75/40 KM 75/40 KM 75/40	KM 80 W G KM 70/30 C	KM 70/20 C KM 70/15 C
Main sweeper roller, hard Main sweeper roller, hard	Order no. Length / wid	th Diameter	Price Description For the removal of stubborn dirt outdoors.	29	KM 170/600 KM 150/500	KM 150/500 KM 150/500 KM 130/300	KM 130/300 KM 130/300 KM 120/250	KM 120/250 KM 125/130 KM 125/130	KM 105/100	KM 105/110 KM 105/110	KM 100/100 KM 100/100 KM 90/60 R	KM 85/50 R KM 85/50 V	KM 85/50 V	KM 85/50 V	KM 85/50 KM 75/40 KM 75/40	KM 80 W G KM 70/30 C	KM 70/20 C KM 70/15 C
				29		KM 130/300 KM 130/300 KM 130/300	KM 130/300 KM 130/300 KM 120/250	KM 120/250 KM 125/130 KM 125/130	KM 105/100	KM 105/110 KM 105/110	KM 100/100 KM 100/100 KM 90/60 R	KM 85/50 W	KM 85/50 V	KM 85/50 KM 85/50 KM 85/50 KM 85/50 KM 85/50 KM	KM 85/50 KM 75/40 KM 75/40	KM 80 W G KM 70/30 C	KM 70/20 C
	29 6.987-442.0 1344 mm	400 mm			KM 170/600 KM 150/500 KM 150/500	KM 130/300 KM 130/300 KM 130/300	KM 130/300 KM 130/300 KM 120/250 KM	KM 120/250 KM 125/130 KM 125/130	KM 105/100	KM 105/110 KM 105/110	KM 100/100 KM 100/100 KM 90/60 R	KM 85/50 V	KM 85/50 V	KM 85/50 KM	KM 85/50 KM 75/40 KM 75/40	KM 80 W G KM 70/30 C	KM 70/15 C
	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm	400 mm 380 mm		30	KM 170/600	KM 130/300	KM 130/300 KM 130/300 KM 130/300 KM 120/250 KM	KM 120/250 KM 125/130 KM 125/130 KM 125/130	KM 105/100 KM 105/100	KM 105/110 KM 105/110	KM 100/100 KM 100/100 KM 90/60 R	KM 85/50 W	KM 85/50 V	KM 85/501 KM 85/501	KM 85/50 KM 75/40 KM 75/40	KM 80 W G KM 70/30 C	KM 70/15 C
	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm	400 mm 380 mm 300 mm		30 31	KM 170/600 KM 150/500 KM	KM 130/300	KM 130/300 KM 130/300 KM 130/300 KM 130/300 KM 120/250 KM	KM 120/250 KM 125/130 KM 125/130	KM 105/100	KM 105/110 KM	KM 100/100 KM 100/100 KM 90/60 R	KM 85/50 V	KM 85/50 V	KM 85/50 KM 85/50 KM 85/50 KM	KM 85/50 KM 75/40 KM 75/40	KM 80 W G KM 70/30 C KM 70/30 C	KM 70/15 C
	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm	400 mm 380 mm 300 mm 400 mm		30 31 32		KM 130/300	KM 130/300 KM 130/300 KM 120/250	KM 120/250 KM 125/130 KM 125/130				KM 85/50 W	KM 85/50 V	KM 85/50 1	KM 85/50 KM 75/40 KM 75/40	KM 80 W G KM 70/30 C	KM 70/20 C KM 70/20 C KM 70/15 C
	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm	400 mm 380 mm 300 mm 400 mm		30 31 32 33	KM 170/600	KM 150/500		KM 126/130 KM 125/130	KM 105/100	KM 105/110	KM 100/100 KM 100/100 KM 90/60 R		KM 85/50 V	KM 85/50 KM	KM 25/50 KM 75/40 KM 75/40	KM 80 W G KM 70/30 G KM 70/30 G	KM 70/20 C
	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm 34 6.906-532.0 700 mm	400 mm 380 mm 300 mm 400 mm 400 mm 285 mm		30 31 32 33 34	KM 170/600	KM 130/300	CKM 130/300 CKM 130/300 CKM 130/300 CKM 130/300 CKM 130/300 CKM 120/250	KM 120/250 KM 125/130	KM 105/100	KM 105/110	KM 100/100	KM 85/50 V	KM 85/50 V	KM 85/50 KM	KM 75/40 KM 75/40	KM 80 W G KM 70/30 G KM 70/30 G	KM 70/20 C
	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm 34 6.906-532.0 700 mm 35 4.762-443.0 615 mm	400 mm 380 mm 300 mm 400 mm 400 mm 285 mm		30 31 32 33 34 35	KM 170/600	NM 150/500 KM 150/500 KM 150/500 KM 150/500 KM 130/300 KM	CKM 130/300 CKM 130/300 CKM 130/300 CKM 130/300 CKM 130/300 CKM 120/250	KM 120/250 KM 125/130 KM 125/130		KM 105/110	KM 100/100	KM 85/50 V			NM 85/50 NM 75/40 NM 75/40	KM 70/30 C	KM 70/20 C
	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm 34 6.906-532.0 700 mm 35 4.762-443.0 615 mm 36 6.906-558.0 620 mm	400 mm 380 mm 300 mm 400 mm 400 mm 285 mm		30 31 32 33 34 35 36	KM 170/600	KM 150/500		KM 120/250 KM 120/250 KM 125/130 CM		KM 105/110 KM 105/110		KM 85/50 V			NM 82/50 NM 82/50 NM 75/40 NM 75/40	KM 70/30 C	KM 70/20 C
Main sweeper roller, hard	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm 34 6.906-532.0 700 mm 35 4.762-443.0 615 mm 36 6.906-558.0 620 mm 37 6.906-885.0 550 mm	400 mm 380 mm 300 mm 400 mm 400 mm 285 mm		30 31 32 33 34 35 36 37		KM 150/500	KM 130/300 KM 130/300 KM 130/300 KM 120/250 KM 120/250	KM 120/250 KM 120/250 KM 125/130 CM		KM 105/110		KM 85/50 V	KM 85/50 V	KM 85/50 KM	KM 85/50 KM 75/40 KM 75/40	KM 80 W G	KM 70/20 C
	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm 34 6.906-532.0 700 mm 35 4.762-443.0 615 mm 36 6.906-558.0 620 mm 37 6.906-885.0 550 mm	400 mm 380 mm 300 mm 400 mm 400 mm 285 mm		30 31 32 33 34 35 36 37	KM 170/600	KM 150/500 KM 150/500 KM 150/500 CM KM 150/500 CM CM 130/300 CM CM 130/300 CM	KM 130/300 KM 130/300 KM 130/300 KM 120/250 KM 120/250	KM 120/250 KM 120/250 KM 125/130 CM	KM 105/100	KM 105/110		KM 85/50 V	KM 85/50 V		KM 85/50 KM 75/40 KM 75/40	KM 80 W G	KM 70/20 C KM 70/20 C KM 70/15 C
Main sweeper roller, hard Main sweeper roller, antistatic	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm 34 6.906-532.0 700 mm 35 4.762-443.0 615 mm 36 6.906-558.0 620 mm 37 6.906-885.0 550 mm 38 6.903-999.0 480 mm	400 mm 380 mm 300 mm 400 mm 400 mm 285 mm 250 mm	For the removal of stubborn dirt outdoors.	30 31 32 33 34 35 36 37 38	KM 170/600	KM 150/500	KM 130/300 KM 130/300 KM 120/250 KM 120/250	N 120/250 KM 120/250 KM 125/130 KM 1	KM 105/100	KM 105/110	KM 100/100 KM 100/100 KM 90/60 R				KM 85/50 KM 75/40 KM 75/40	KM 80 W G KM 70/30 G KM 70/30 G	KM 70/20 C KM 70/20 C KM 70/15 C
Main sweeper roller, hard Main sweeper roller, antistatic	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm 34 6.906-532.0 700 mm 35 4.762-443.0 615 mm 36 6.906-558.0 620 mm 37 6.906-885.0 550 mm 38 6.903-999.0 480 mm	400 mm 380 mm 300 mm 400 mm 400 mm 285 mm 250 mm	For cleaning surfaces subject to static build up (carpets for example).	30 31 32 33 34 35 36 37 38	KM 170/600 KM 150/500	KM 130/300 KM 130/300 KM 130/300	KM 130/300 KM 130/300 KM 120/250 KM 120/250	KM 120/250 KM 125/130 KM 125/130			KM 100/100 KM 90/60 R	KM 85/50 V			KM 85/50 KM 75/40		KM 70/20 C KM 70/20 C KM 70/15 C
Main sweeper roller, hard Main sweeper roller, antistatic	29 6.987-442.0 1344 mm 30 6.987-436.0 1194 mm 31 6.987-439.0 1000 mm 32 4.762-527.0 880 mm 33 4.762-524.0 640 mm 34 6.906-532.0 700 mm 35 4.762-443.0 615 mm 36 6.906-558.0 620 mm 37 6.906-885.0 550 mm 38 6.903-999.0 480 mm	400 mm 380 mm 300 mm 400 mm 400 mm 285 mm 250 mm	For the removal of stubborn dirt outdoors.	30 31 32 33 34 35 36 37 38	KM 170/600 KM 150/500	KM 130/300 KM 130/300 KM 130/300	KM 130/300 KM 130/300 KM 120/250 KM 120/250	KM 120/250 KM 120/250 CM 125/130 CM 125/130 CM 125/130 CM CM CM 125/130 CM CM CM 125/130 CM			KM 100/100 KM 90/60 R	KM 85/50 V					KM 70/20 C

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

SIDE BRUSHES



The high-quality and water-resistant universal bristles of our side brushes are standard and suitable for every surface and purpose. If you spend a lot of time working inside in dusty areas, then we recommend soft bristles to reduce the dispersion of any dust. The use of a side brush with extra-hard bristles is useful for very stubborn dirt. If you want to extend the area performance, it is possible to install a second side brush on the left side of the machine.























		Order no.	Installation ex works	Diameter Pri	e Description		KM 170/600 R D	KM 150/500 R LPG / KM 150/500 R D KM 150/500 R D Classic	KM 150/500 R Bp / KM 150/500 R Bp Pack	KM 130/300 R LPG / KM 130/300 R D	KM 130/300 R D Lassic KM 130/300 R Bp Pack (KM 130/300 R Bp WM 130/350 R I Pack (Lassic / UM 130/350 R Bp	KM 120/250 R LPG Classic / KM 120/250 R D Classic / KM 120/250 R Bp Pack Classi KM 120/250 R Bp Classic	KM 125/130 R D / KM 125/130 R G / KM 125/130 R LPG	KM 105/100 R Bp / KM 105/100 R Bp Pack	KM 105/100 R D / KM 105/100 R G / KM 105/100 R LPG KM 105/110 R Bn / KM 105/110 R Bb Pack	KM 105/110 RD / KM 105/110 R G / KM 105/110 R LPG	KM 100/100 R Lpg / KM 100/100 R D / KM 100/100 R G KM 100/100 R Bp Pack / KM 100/100 R Bp	KM 90/60 R G Adv / KM 90/60 R Bp Pack Adv / KM 90/60 R Bp Adv	KM 85/50 R Bp Pack / KM 85/50 K Bp KM 85/50 W G Adv / KM 85/50 W G / KM 85/50 W Bp Pack Adv	KM 85/50 W Bp Pack / KM 85/50 W Bp Adv / KM 85/50 W Bp KM 75/40 W G / KM 75/40 W Bp Pack / KM 75/40 W Bp	KM 70/30 C Bp Pack Adv / KM 70/30 C Bp Pack / KM 70/30 C Bp Adv KM 70/30 C Bp / KM 70/20 C / KM 70/20 C 25B	KM 70/15 C
Standard side brushes																						
Side brush, standard		6.987-467.0		650 mm	Water-resistant universal bristles, durable, suitable for all surfaces.	1	-	\perp	\perp	_	\perp	'	\vdash	\perp	_	\perp		\perp	$\perp \!\!\! \perp$		$\perp \perp$	\perp
		6.987-083.0		550 mm		2	+	•	-	_		44		+			-	\vdash	+	\vdash	++	\perp
		6.966-063.0		600 mm		3	+	+	++	+	++	+-'		44] ■	_	++	+	-	++	-
		6.905-986.0		450 mm		4	+	+	++	+	++	+-'	\vdash	+	+	+	• •	-			\vdash	+
		6.906-132.0		420 mm	_	5	++	+	++	+	++	+-	\vdash	++	+	++			4-			+
Sido bruch coft	0	6.966-005.0		330 mm		6	\perp	\perp		_			4		\perp		\perp	ш				-
Side brush, soft Side brush, soft	7	6.987-466.0	l	650 mm	Sweeps fine dust on all surfaces, water-resistant, for indoor and outdoor	7	ІпІ		TT		TI			T T		T T						
5.de 5.65.1, 56.10		6.905-620.0		550 mm	use.	8	+		+	$\overline{}$			\vdash	++	+	++		++	+	\vdash	+-	+
		6.966-065.0		600 mm	_	9	++	+	+-+	\pm	+++	77				計	+	+	++	\vdash	+	\top
		6.906-133.0		450 mm		10	\Box	\top	+	\top	+	+	一	+	\top	+			+	\Box		+
		6.905-626.0		420 mm	_	11	\top	\top	\Box	\top	\top	\top		\top	\top	\top	\top					\Box
Side brush, hard								$\overline{}$							$\overline{}$							
Side brush, hard		6.987-468.0		650 mm	Removes stubborn dirt outdoors, moisture-proof, mildly abrasive.	12				\perp						$\perp \perp$						
		6.905-773.0		550 mm		13	$\perp \perp \mid$		101			'	\perp	$\perp \perp$	\perp	$\perp \perp$		\sqcup	$\perp \!\!\! \perp$	\vdash	$\perp \perp$	Ш
		6.906-705.0		600 mm		14	\perp	\perp	$\perp \perp$	_	\perp			10'				$\perp \perp$	Ш		$\perp \perp$	Ш
		6.906-065.0		450 mm		15	\perp	\perp	+	_	+		\vdash	+	\perp	44'		$\perp \perp$	$\perp \!\!\! \perp$	-		44
	16	6.905-625.0		420 mm		16	$\perp \perp \perp$	\bot	Ш	\perp	\perp		Щ	Ш	\perp	Ш					Ш	Щ
Side brush, hard Side brush, steel bristles	17	6.905-619.0	ı	550 mm	For stripping, removing moss, abrasive, for outdoor use only.	17	1.1		Inl	пΙ	Inl	4		1.1		1.1			11			
Side brosii, steel bristies		6.906-022.0		450 mm	To stripping, removing moss, abrasive, for obtaour ose only.	18	++	+	+++	+	+	+-	+	++	+	++		++	+	\vdash		+
Side brushes, left	10	0.300 022.0	L	130		10	\rightarrow	\vdash	+	\vdash			\vdash	_	\vdash	Н,		\vdash	\dashv	\rightarrow	\vdash	
Add-on kit second side broom left	19	2.851-275.0	2.851-275.7		Complete, including standard side brushes for increased area coverage.	19		\top	TT		TT			TT	\top	TT	\top		\Box			
	20	2.851-274.0	2.851-274.7		=	20	\top		1		\top			\Box	\top	+	\top		\top	\Box		\top
		2.851-272.0				21	\top	\top	\Box		7	77	\Box	\Box		\Box	\top		\Box	\Box		\Box
		2.851-273.0				22			\Box					$\perp \uparrow$								
		2.852-518.0				23				I	Г		П				\perp					
		2.851-256.0	DE_28512567			24																
		2.851-254.0				25		$\perp \Gamma$	$\perp \! \! \perp \! \! \! \perp$		$\perp \perp$			1		1		\Box		ட		
	26	2.852-318.0				26						17	1 I						\perp			

 26
 2.852-318.0

 ■ Included in the scope of supply.
 Available accessories.

 More Kärcher original accessories can be found on the following pages.























45

		Order no.	Installation ex works	Diameter	Price Description		KM 170/600 R D KM 150/500 R D	KM 150/500 R D Classic KM 150/500 R BD / KM 150/500 R BD Pack	KM 130/300 R LPG / KM 130/300 R D		KM 120/250 R LPG Classic / KM 120/250 R D Classic / KM 120/250 R Bp Pack Classic KM 120/250 R Bp Classic KM 120/250 R Bp Classic	KM 125/130 R D / KM 125/130 R G / KM 125/130 R LPG KM 125/130 R Bh / KM 125/130 R Bb Pack	NM 125/130 R BU / NM 125/130 R	KM 105/100 KD / KM 105/100 K U/ KM 105/100 K LPU KM 105/110 R Bp / KM 105/110 R Bp Pack	KM 105/110 R D / KM 105/110 R G / KM 105/110 R LPG KM 100/100 R Lpg / KM 100/100 R D / KM 100/100 R G	KM 100/100 R Bp Pack / KM 100/100 R Bp KM 90/60 R G Adv / KM 90/60 R Bp Pack Adv / KM 90/60 R Bp Adv	KM 85/50 R Bp Pack / KM 85/50 R Bp KM 85/50 W G Adv / KM 85/50 W G / KM 85/50 W Bp Pack Adv	KM 85/50 W Bp Pack / KM 85/50 W Bp Adv / KM 85/50 W Bp KM 75/40 W G / KM 75/40 W Bp Pack / KM 75/40 W Bp	KM 70/30 C Bp Pack Adv / KM 70/30 C Bp Pack / KM 70/30 C Bp Adv KM 70/30 C Bb / KM 70/20 C / KM 70/20 C 25B	KM 70/15 C
Add-on kit second side broom left	27	2.851-049.0	2.851-049.7		Complete, including standard side brushes for increased area coverage.	27														
	28	2.850-571.0	2.850-571.7		Complete, including standard side brushes for increased area performance (up to serial number 11857).	28				I										
	29	2.851-050.0	2.851-050.7		Complete, including standard side brushes for increased area coverage.	29														
	30	2.640-284.0	2.640-284.7		Complete, including standard side brushes for increased area coverage (up to serial number 11857).	30														
		2.642-693.0			Complete, including standard side brushes for increased area coverage.	31			П	\perp		Ш	\perp	Ш						\Box
		2.852-321.0				32			\vdash	+	\vdash	++	++	\dashv	\perp	\perp		_		\sqcup
Configurable side buret	33	2.640-441.0	2.640-441.7			33			ш	_	Ш	ш	\perp	Ш		\perp		ЦПП	Ш	
Configurable side brush Side brush, right	34		DE_28520377		Standard, right side brush attached to machine.	34			LI			Inl	TT	1.1	1 1	1 1	1.1	1 1		
Side Brosh, right	35		DE_28520227		Standard, right side order attached to machine.	35			+	+	+	+++	1	+	+		+			+
	36		DE_28520187			36			+	+	++	++-	+	7	пН					\forall
Side brush, right +	37		DE_28520387		Standard, right side brush attached to machine. Includes sweeping	37			+	+	+	I	++	++	_	\dashv				\forall
sweeping crescent brush	38		DE_28520237		crescent brush for easy sweeping of corners.	38			+	+	++-	H		+						\forall
	39		DE_28520197			39			+	+	+	#	+-	計		\dashv	+			\forall
Right + left side brushes	40		DE_28520397		Standard, right side brush attached to machine. Includes left side brush.	40			\Box	+	+		++	+						Н
	41		DE_28520267			41			\Box	+				\top						П
	42		DE_28520247			42			\Box	\top			<u>, </u>				\top			П
	43		DE_28520207			43				\top				亓						П
Right + left side brushes +	44		DE_28520407		Standard, right side brush attached to machine. Includes left side brush	44			\Box	\top				\top		$\neg \neg$				П
sweeping crescent brush	45		DE_28520257		and sweeping crescent brush for easy sweeping of corners.	45				\top			1							П

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

CABS, PROTECTIVE ROOFS, FLASHING BEACONS



When working in areas which have higher safety requirements for the user, such as in shelf warehouse areas, the use of protective roofs or cabs (can also be ordered with heating or airconditioning) is a practical extension to the respective device. A flashing beacon also increases safety on the premises both for the driver and the surrounding area.

















1	Ģ
18-20	1

						T	$\neg \neg$	$\neg \neg$	\top	\top	T	\top			
	Order no.	Installation ex works	Price	Description			KM 170/600 R D	KM 150/500 R LPG KM 150/500 R D VAA 150/500 R D FISSEIC	KM 150/500 R Bp / KM 150/500 R Bp Pack KM 130/300 R LPG / KM 130/300 R D	KM 130/300 R D Classic KM 130/300 R Bb Pack / KM 130/300 R Bb	ram 130/1300 n. bp. ram / ram 130/1300 n. bp RM 120/130 n. LPG Classic / KM 120/250 n. D. Classic / KM 120/250 n. Bp Pack Classic KM 130/750 n. Bm Classic	KM 120/250 K BP Classic KM 125/130 R D / KM 125/130 R G / KM 125/130 R LPG	KM 125/130 R Bp / KM 125/130 R Bp Pack KM 105/100 R Bp / KM 105/100 R Bp Pack / KM 105/100 R D KM 105/100 R G / KM 105/100 R LPG / KM 105/110 R Bb	KM 105/110 R Bp Pack / KM 105/110 R D / KM 105/110 R G KM 105/110 R LPG	KM 100/100 R Lpg / KM 100/100 R D / KM 100/100 R G KM 100/100 R Bp Pack / KM 100/100 R Bp KM 90/60 R G Adv / KM 90/60 R Bp Pack Adv / KM 90/60 R Bp Adv KM 85/50 R Bp Pack / KM 85/50 R Bp
Driver's protective cabin	order no.	CX WOLKS	11100	positifyton				-1-1-	-1-1-	1-1-		-1-1-	-1-1-	.1-1-1	=1=1=1=1
Comfort cabin with heating and air	1	2.851-674.7		Robust tubular steel frame. Glass all-round. Hinged rear window. Left side window.	1			\Box	TI	TT	TT	TT		I = I	
conditioning	2	2.851-266.7		-	2		++	$\exists \exists \vdash$	+	+	+	++			+
Comfort cabin with heating	3	2.851-265.7		-	3		+	+	+	++	++	++			+
•	4	2.852-133.7		-	4		1	$\overline{}$	+		+	++			
Comfort cabin	5	2.851-264.7		-	5					\top	\top	\top			
Weather protection cabin	6	2.851-271.7		Robust tubular steel frame. Windscreen with windscreen wiper. Plastic cladding on the sides and rear.	6					1 0	1				
Protective cabin with windscreen and	7	2.851-270.7		Robust tubular steel frame. Windscreen with windscreen wiper.	7										
windscreen wiper	8	2.851-269.7			8					1 0	1				
Protective cabin	9	2.851-268.7		Robust tubular steel frame.	9						$\perp \perp$				
	10	2.851-267.7			10		$\perp \perp \perp$								
Protective roof	1 1	- 1		In a contract of the contract	1		1-1		1-1	4	4	4			
Protective roof	11 2.851-686.0			Robust steel construction. Complies with IEC 60335-2-72.	11		\Box		1-		+	++			
	12 2.852-191.0			_	12		\rightarrow	++	+	100	4	+++			+
	13 2.851-262.0				13		++	++	+	++	++				
Protective reaf with 250° warning horsen		DE_28512617			14									110101	
Protective roof for operator with 360°		2.640-468.7	ı	Robust steel construction. Complies with IEC 60335-2-72.	15		1.1		1 1		1 1	1.1	1.1	1 1 1	
Protective roof for operator with 360° warning beacon	15 16	2.640-496.7		Nobose steer construction, compiles with the 00000 2772.	16		++	++	++	++	++	++	++	+++	
Warning beacon	10	2.040 450.7			10						$\perp \perp \perp$				
Warning beacon on protective roof	17 2.852-058.0	DE_28520587		For increased occupational safety.	17		TI	TI		TT	TT	Intr	nlnln		
Warning beacon	18 2.852-057.0			1	18		+	++	++	+	++				+++
-	19 2.643-886.0			-	19		++	++	+	++	++	++		+ + - +	
	20 2.643-887.0			-	20		++	++	+	+	+	++	+		
	21 2.852-500.0			-	21		+	++	+	+	+	++			
				1		4									

☐ Available accessories. More Kärcher original accessories can be found on the following pages.


WORK LIGHTING, ROAD APPROVAL, TYRES



Poor weather conditions or dark work environments mean higher safety requirements. Various working lights provide a remedy here, improve both the visibility conditions for the user and his visibility of the surrounding area. In addition, we also offer solutions for special conditions in the area of tyres, such as resistant and long-lasting full rubber wheels for production areas where metal shavings or glass splinters are common. And also non-marking tyres for machines operating on light surfaces.

























Calle	
Charles and the	
100	
17.	
28	

	Order no.	Installation ex works Price	Description		KM 170/600 R D KM 150/500 R LPG KM 150/500 R LPG KM 150/500 R D KM 150/500 R D KM 150/500 R B KM 150/500 R B KM 150/500 R B KM 130/300 R LPG KM 130/300 R LPG KM 130/300 R LPG KM 130/300 R D KM 130/300 R D KM 130/300 R D KM 130/300 R B KM 130/300 R B KM 120/250 R LPG Classic KM 130/300 R B KM 120/250 R LPG Classic KM 120/250 R BP Pack / KM 120/250 R B KM 120/250 R BP Pack / KM 125/130 R LPG KM 125/130 R B KM 125/130 R B KM 125/130 R B KM 105/110 R B KM 106/100 R B KM 106/100 R B KM 106/100 R B KM 106/100 R B KM 90/60 R B KM 85/50 R B KM 85/50 R B KM 85/50 R B
Lighting		l a a s . a s !	Tarana a sama	1	
Working lights	1 2.851-279.0		For increased visibility, e.g. in underground garages or warehouses.	1	
	2 2.852-082.0			2	
	3 2.852-059.0	DE_28520597		3	
	4 2.640-551.0			4	
Decid Politics	5 2.852-496.0	20524547	For the control of th	5	
Road lighting	6	2.852-151.7	For increased work safety on the premises: road lighting consisting of indicators and working lights.	6	
StVZO lighting	7	2.851-280.7	Attachment kit consisting of flashing beacon, lights, indicators, horn, brake lights	7	
	8	2.851-941.7	and hazard lights certified and approved according to the German Road Traffic	8	
	9	DE_28514707	Licensing Ordinance.	9	
StVZO lighting on cab	10	2.852-201.7	For the road approval of our sweeper KM 130/300 R D and installation on the cabins: StVZO kit, consisting of flashing beacon, lights, brake lights, indicators, hazard lights and horn.	10	
TÜV approved	11	2.851-285.7	Review for use on public roads in Germany.	11	
	12	2.851-982.7		12	
Tyres		· ·			
Pneumatic tyre wheel set	13 4.515-332.0	4.515-332.7	Convenient pneumatic tyres for standard use.	13	
	14 2.851-382.0	DE_28513827		14	
	15 2.851-683.0	DE_28516837		15	
	16 2.852-502.0			16	
Tyres, puncture-proof					
Puncture-proof tyres (set), full rubber	17 4.515-331.0		Recommended for sweeping metal shavings, glass shards, etc.	17	
	18 4.515-329.0			18	
	19 2.851-383.0	DE_28513837		19	
	20	2.640-431.7		20	
	21 4.040-801.0		Recommended for sweeping metal shavings, glass shards, etc. From machine serial number 10035 (LPG Adv), 10196 (G Adv) and 10255 (G Adv Edition).	21	
	22 2.642-936.0	2.642-936.7	Recommended for sweeping metal shavings, glass shards, etc. From machine serial number 10034 (LPG Adv), 10195 (G Adv) and 10254 (G Adv Edition).	22	
Puncture-proof tyres (set), full rubber,	23 4.515-112.0	4.515-112.7	Recommended for sweeping metal shavings, glass shards, etc. Avoids tyre tracks	23	
non-marking	24 4.515-328.0	4.515-328.7	on light surfaces.	24	
	25 2.851-384.0			25	
	26 2.851-685.0	DE_28516857		26	
	27	2.641-129.7		27	
	28 2.852-501.0	2.852-501.7	Recommended for sweeping metal shavings, glass shards, etc.	28	

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

ATTACHMENTS FOR SPECIAL APPLICATIONS AND FOR INCREASING **PRODUCTIVITY**



Special requirements demand special solutions. As a result, we are always expanding our portfolio of accessories. In order to prevent or reduce the dispersion of dust, we offer, e.g. side brushes with integrated spray system or with a complete cover. Enhancements or upgrades ensure excellent results when working on carpets or artificial grass, whereas an on-board vacuum cleaner permits the efficient cleaning of shelves or corners. Even large quantities of leaves can be effortlessly removed thanks to the unique leaf collection kit.























	Order no.	Installation ex works	Price	Description		KM 170/600 R D KM 150/500 R LPG KM 150/500 R LPG KM 150/500 R LPG KM 130/300 R LPG KM 125/130 R LPG KM 105/100 R LPG KM 100/100 R L
Water spraying system	1	I			1	
Water spraying system for side brushes	1 2.851-284.0	2.851-284.7		For binding dust. Consisting of stainless steel water tank (65 I) and spray water nozzles on the side brushes.	1	
	2 2.852-596.0	2.852-596.7		For binding dust. Consisting of stainless steel water tank (60 I) and spray	2	
	3 2.851-282.0			water nozzles on the side brushes.	3	
	4 2.851-492.0	2.851-492.7		For binding dust. Consisting of stainless steel water tank (50 l) and spray	4	
	5 2.851-281.0	2.851-281.7		water nozzles on the side brushes.	5	
	6 2.852-241.0	DE_28522417	'	Water spraying system for vacuum sweepers. For binding dust as required,	6	
	7 2.852-242.0	DE_28522427	,	with 30-litre plastic container, water discharge, belt attachment and nozzles	7	
Sweeping/Vacuuming		1		for the right and left side brush.		
Third side brush	8	2.851-277.7	1	For variable sweeping width - ideal for sweeping on different levels or	8	
				around obstacles.		
Side brush cover	9 2.851-287.0			Side brush cover for reducing dust dispersion.	9	
	10 2.851-286.0				10	
	11 2.852-244.0	DE_28522447	'	For avoiding dust when working with vacuum sweepers: cover of the side	11	
	12 2.852-243.0	DE_28522437	'	brush prevents dust dispersion, effectively protecting the surroundings and machine against dust.	12	
Vacuum cleaner	13 2.643-833.0	2.643-833.7		Vacuum cleaner attachment kit with extra high suction power for cleaning	13	
				corners, shelves or between pallets. Incl. suction hose DN40.		
	14	2.641-448.7		For extra strong suction power in corners and over long distances.	14	
Suction hose	15 2.641-689.0	2.641-689.7		For cleaning corners.	15	
Artificial turf kit	16	2.851-320.7		The artificial turf manufacturer's technical data must be observed. Suitable only for lawns without granulate.	16	
Carpet sweeping kit	17	2.851-334.7		Carpet sweeping kit for cleaning carpet surfaces, includes antistatic roller	17	
	18 2.852-499.0 ■	2.852-499.7		brush.	18	
Other mounting kits						
Stainless steel waste container	19	6.961-928.7		Stainless steel waste container for waste and areas of application with increased risk of corrosion.	19	
Comfort seat	20 6.373-014.0			For increased driving comfort.	20	
Stainless steel waste container	21	6.961-927.7		Stainless steel waste container for waste and areas of application with	21	
	22	6.961-926.7		increased risk of corrosion.	22	
Sound-damping attachment kit KM 125/130 F				The sound-damping also reduces the noise level.	23	
Standard seat	24 2.851-380.0			Standard seat with good working comfort.	24	
Comfort seat Kärcher Fleet Services KM	25 2.851-381.0 26 2.643-381.0			For increased driving comfort. Kärcher Fleet is the innovative solution for professional fleet management.	25 26	
Narcher Freet Services KIVI	20 2.043-361.0	DE_2043361/		The web-based portal enables transparency of machines, cleaning applications and fleet deployment.	20	
Additional weights 18% gradient	27 2.852-085.0	DE_28520857	,	Inclines of up to 18% can be overcome with the additional weights.	27	
Sound-damping attachment kit KM 105/1X0 I		DE_28517987		The sound-damping also reduces the noise level.	28	

■ NEW ☐ Available accessories. More Kärcher original accessories can be found on the following pages.

















6		-
U	M	
40		
40		


	Order no.	Installation ex works	Price	Description		KM 170/600 R D	KM 150/500 K LPG KM 150/500 R BP / KM 150/500 R Bp Pack	KM 130/300 R LPG KM 130/300 R D KM 130/300 R Bp Pack / KM 130/300 R Bp	KM 125/130 R D KM 125/130 R G KM 125/130 R L P G	KM 125/130 R Bp / KM 125/130 R Bp Pack KM 105/100 R Bp / KM 105/100 R Bp Pack KM 105/100 R D	KM 105/100 R G / KM 105/100 R LPG KM 105/110 R Bp / KM 105/110 R Bp Pack KM 105/110 R D	KM 105/110 R G / KM 105/110 R LPG KM 100/100 R Lpg / KM 100/100 R D / KM 100/100 R G KM 100/100 R Bp Pack / KM 100/100 R Bp	KM 90/60 R G Adv KM 90/60 R Bp Pack Adv / KM 90/60 R Bp Adv	KM 85/50 R Bp Pack / KM 85/50 R Bp KM 85/50 W G Adv KM 85/50 W G	KM 85/50 W Bp Pack Adv KM 85/50 W Bp Pack KM 87/50 W Bp Addv	KM 85/50 W Bp KM 75/40 W G	KM 75/40 W Bp Pack / KM 75/40 W Bp KM 80 W G
Leaf collection bag attachment kit KM 105/100 R				Unique on the market: leaf collection bag for collecting large quantities of	29					<u> </u>	<u> </u>	<u> </u>			+++	+ + +	
Lear Collection bag attachment kit kiw 103/100 K	25 2.032-243.0	DL_20322437		leaves with the vacuum sweeper. Attached to the rear of the machine, just like on lawnmowers.	23												
Dual Tact filter cleaning system	30 2.643-176.0			For sweeping on particularly dusty ground.	30												. —
	31	2.851-392.7			31												
Double filter shaker	32 2.851-000.0			Dual filter scraper for increased cleaning performance in very dusty environ-	32											1 0	. —
	33 2.851-040.0			ments.	33												
Brake	34 2.640-301.0			For reliable braking on gradients > 2 %.	34											1	
Carpet sweeping kit	35 2.641-571.0			Carpet sweeping kit for cleaning carpeted surfaces, consists of fluff filter, triple steering roller and antistatic roller brush.	35												
Snow blade	36 2.851-446.0			For use in winter. With spring-mounted folding mechanism and adjustable gliding skids.	36												
Waste container	37 2.851-569.0			For sweeping up grit or other dirt into a waste container that is stable and easy to empty.	37												
Miscellaneous				·													
KIK-Key yellow KM	38 5.035-943.0			Key for operators. Cannot be adjusted.	38												. []
KIK-Key grey KM	39 5.035-944.0			Key for supervisors. Authorised access for operator keys.	39												
5-piece KIK keys, yellow	40 4.035-542.0			Key for operators. Cannot be adjusted.	40		$ \cdot $.]


■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

ACCESSORIES FOR HOME BASE AND OTHER EQUIPMENT



The clever and sophisticated Home Base system extends the options of our sweepers in day-to-day work. Various cleaning utensils and accessories can be easily carried. Thanks to the various hooks, clips and containers, equipment such as the litter picker, cloths, buckets, cleaning agents, dustpans, brushes and beverages are available at any time and are ready to hand.















	Order no. Price	Description		KM 125/130 R D / KM 125/130 R G / KM 125/130 R LPG KM 125/130 R BD / KM 125/130 R BP Pack / KM 105/100 R BP KM 105/100 R BP Pack / KM 105/100 R D / KM 105/100 R BP KM 105/100 R LPG / KM 105/110 R BP / KM 105/110 R RP KM 105/100 R LPG / KM 105/110 R BC / KM 105/110 R LPG KM 105/100 R LPG / KM 35/50 R BP KM 305/50 R BP Pack / KM 35/50 R BP KM 30/50 R BP Pack / KM 35/50 R BP KM 30/30 C BP Pack / KM 70/30 C BP Pack / KM 70/30 C BP AdV KM 70/30 C BP / KM 70/20 C / KM 70/20 C 25B KM 70/15 C
Home Base accessories			' '	
Home Base litter picker kit	1 4.035-524.0	Litter picker including fastener on the machine.	1	
Home Base brush holder kit	2 4.035-523.0	Holder fits on machine for convenient brush storage.	2	
Home Base Kit litter picker	3 2.852-497.0	Litter picker including fastener on the machine.	3	
Home Base mop holder kit	4 4.035-374.0	Holder fits on machine for convenient mop storage.	4	
Home Base adapter	5 5.035-488.0	For attaching to the Home Base rail.	5	
Double hook	6 6.980-077.0	Suitable for attaching bin liners, bags, etc. to the machine – only in conjunction with Home Base adapter 5.035-488.0.	6	
ABS litter picker set	7 2.640-908.0	For picking up refuse.	7	
Holder handhold grey	8 6.980-078.0	Accessory for attaching a mop/brush to the machine – only in conjunction with Home Base adapter 5.035-488.0.	8	
Other			, , , , , , , , , , , , , , , , , , , ,	
Cleaning agent container, complete	9 4.070-006.0	Kit consisting of cleaning agent container and Home Base adapter. For connecting Home Base Rail.	9	

☐ Available accessories. More Kärcher original accessories can be found on the following pages.

BATTERIES AND CHARGERS



Our batteries are available in many different versions. Whether they have higher or lower capacity, are low maintenance or maintenance-free: You get the exact batteries you need in your day-to-day work. The relevant battery chargers are matched to the respective battery type.

















Traction batteries	Order no.	Battery voltage	Battery capacity	Battery type	Price Description			KM 150/500 R Bp		KM 125/130 R D / KM 125/130 R G / KM 125/130 R LPG KM 125/130 R Bp / KM 125/130 R Bp Pack	KM 105/100 R Bp KM 105/100 R Bp Pack VM 105/110 B Rn	KM 105/110 R Bp Pack KM 105/110 R Bp Pack KM 100/100 R Lpg / KM 100/100 R G		KM 90/60 R Bp Pack Adv KM 90/60 R Bp Adv	KM 85/50 R Bp Pack KM 85/50 R Bp KM 85/50 W Bp Pack Adv	KM 85/50 W Bp Pack KM 85/50 W Bp Adv KM 85/50 W Bp	KM 75/40 W Bp Pack KM 75/40 W Bp KM 70/30 C Bp Pack Adv / KM 70/30 C Bp Pack
Traction batteries	1 6.654-280.0	18 V	700 Ah	Low-maintenance	With central filling system. Charge lasts fo	or up to 3 hours	1 1		1 1 1	1.1	11	11		1.1	1 1 1		
Battery	2 6.654-282.0		360 Ah				2			+	++	++					+++
	3 6.654-156.0		400 Ah	Low-maintenance	With central filling system. Charge lasts for Charge lasts for up to 4 hours.	ii up to 2.5 flours.	3				++	++	+++	+	+		++
	4 6.654-119.0		240 Ah	Low-maintenance Maintenance-free			4										+++
	5 6.654-112.0		240 Ah	Low-maintenance	4 required. With central filling system		5		+		\rightarrow			+	+		++
	6 6.654-048.0		80 Ah	Low-maintenance	With central filling system. 2 required.		6		+					-	-		
	7 6.654-226.0		60 Ah	Maintenance-free	2 required.		7		+	++	++	++	+++	+			
	8 6.654-202.0		26 Ah	Maintenance-free	Traction battery.		8			+	++	++					
	9 6.654-124.0		180 Ah	Maintenance-free	Traction battery, maintenance-free.		9		+	++	++	++	+++	_ _	+		┌┼┼
Pattorios	3 0.034-124.0	10 V	100 AII	Walliterlance-free	maction battery, maintenance-nee.		3							- -			\Box
Batteries Battery	10 6.654-124.0	6 V	180 Ah	Maintenance-free	Gel battery, B 60 W, B 80 W and B 90 R, 4 6 pc. required.	required. BD 80/100 W,	10]							
	11 4.035-182.0		105 Ah	Maintenance-free	Machines with 36 V require three batterie	² S.	11			\perp	\perp	\perp					
Chausaus	12 6.654-141.0	12 V	105 Ah	Maintenance-free			12			\perp			Ш				Щ
Charger	13 6.654-281.0	18 V	1	senarate	For battery 6 65 4-280 0		13		1 1 1	1 1	1.1			1.1	1 1 1		
Charger	14 6.654-283.0			separate	For battery 6.654-280.0.		14			+	++	++	++	+	+++	++	+++
	15 6.654-143.0			separate built-in	For battery 6.654-282.0. For battery 6.654-112.0.		15		╅┩	++	++	++		++	+++		$\overline{}$
	16 6.654-120.0				For maintenance-free batteries 24 V / 24) Ab (6.654-119.0)	16		+	+	++	++	 	+	+	- - - 	$\overline{}$
	17 6.654-107.0			separate separate	For battery 6.654-112.0.	7 ATT (0.034-113.0).	17		+	++	++	++		++	+		\Box
	18 4.839-389.0			built-in	For battery 6.654-124.0.		18		+	+	++	++	+		+	+++	\vdash
	19 6.654-140.0			built-in	For battery 6.654-141.0.		19		+	++	++	++	+++	-			$\overline{}$
	20 6.654-225.0			built-in	For battery 6.654-226.0.		20		+	++	++	++	++	++	+ -		
	21 6.654-068.0			separate	For battery 6.654-021.0.		21		+++	++	++	++	+++	++	+++		
	22 6.654-203.0			built-in	For battery 6.654-202.0.		22		+	++	++	++		+	+++		
	23 6.654-367.0			separate	Standby battery charger for maintenance- 105 Ah with order no. 6.654-093.0, 6.654		23				+	+					

■ NEW ■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.





		Order no.	Battery voltage	Battery capacity	Battery type	Price	Description		KM 150/500 R BD KM 150/500 R BD KM 130/300 R BD Pack KM 130/300 R BD Pack KM 130/300 R BD Pack KM 135/130 R B P Pack KM 125/130 R BP Pack KM 105/100 R BP Pack KM 100/100 R BP Pack KM 100/10
Charger	24	6.654-067.0	24 V		separate		For low-maintenance 80 Ah batteries (6.654-048.0 and 6.654-097.0).	24	
	25	6.654-102.0	24 V		separate		For maintenance-free 24 V batteries 70-80 Ah (6.654-093.0).	25	
	26	6.654-078.0	24 V		separate		For maintenance-free 160-180 Ah batteries (6.654-124.0 and 6.654-130.0).	26	
Traction batteries and									
Battery	27	7.654-001.0	12 V	44 Ah	Low-maintenance		Starter battery.	27	
Accessories for batteri									
Box with wall holder	28	2.641-243.0			Low-maintenance		Storage system for refilling wet batteries, easy filling of the batteries possible, saves a lot of time. Install container at a height of 4 metres. Includes hose and flow rate volume meter.	28	

■ Included in the scope of supply. □ Available accessories. More Kärcher original accessories can be found on the following pages.

MUNICIPAL EQUIPMENT PERFECTION

We know your needs and requirements extremely well. The work you carry out is diverse - from maintaining green areas to street cleaning, from snow clearing to plant watering - and we have precisely the municipal equipment you need for success: Powerful vacuum sweepers, versatile implement carriers, universal and specialist implements, and the latest battery-powered machines. In short: Effective equipment for maximum efficiency.



Table of contents: Municipal equipment

Vacuum sweepers Page 698 Page 704 Light waste vacuum cleaners Implement carriers Page 706 Implements Page 716



MC 130 Plus - a machine for all seasons

This is your sweeper in the 3.5 tonne class for year-round use. Our MC 130 Plus will impress you with its 49 kW (66 hp) common rail engine with diesel particulate filter and convenient operation using a joystick and multifunctional display.

MIC 35/42 and MC 80 - a delight for drivers, construction yard managers and service staff

Our MIC 35/42 multifunctional implement carriers and the MC 80 sweeper are a delight for drivers, construction yard managers and service (42 hp) or 26 kW (35 hp) and diesel particle filter — compatible with virtually all Kärcher municipal are much cleaner than the exhaust emissions standard STAGE V demands. And this means that you can use these municipal vehicles anywhere you want, including in fine dust zones.

WRS 200 - the hot water professional

With your WRS 200 implement, you have a real all-rounder for tasks ranging from the large-scale removal of weeds using hot water, to high-pressure cleaning using cold and hot water, through vehicles, e.g. MIC 42, MIC 70, MC 130.

How to read the machine names:

MC = Municipal Cleaner MIC = Municipal Implement Carrier


MUNICIPAL EQUIPMENT

		Price	Variable sweeping width (mm)	Waste hopper volume (I)	Max. area performance (m²/h)	Cleaning applications	Year-round use	All-wheel drive	Traction control	Individual brush control	Hydraulic high container emptying	Air conditioning	Heating	Page
	Vacuum sweepers													
E A	MC 130 Adv		1200-2400	1000	24000					•				699
1 delay	MC 130 Plus		1200-2400	1000	24000					•				699
THE REAL PROPERTY.	MC 80		550-1630	800	16300		-	-	-	•				701
- 100 P.C	MC 50 Adv Comfort		900-1400	500	14000				-	-				703
	MC 50 Adv		900-1400	500	14000				-	-		-		703

		Price	Working width (mm)	Waste hopper volume (I)	Max. area performance (m²/h)	Indoor use	Outdoor use	15 I storage compartment	Traction drive, hydraulic	Coarse dirt flap	Electro start	Flashing beacon	Curb climbing aid	Page
-	Light waste vacuum cleaners													
2	IC 15/240 W Adv		100	240	-	-								705
1	IC 15/240 W		100	240	-	-	•		•	•	•	-	-	705

		Price	<u>e</u>	Hydraulic system (I/min)	Total permissible weight (kg)	Year-round use	Air conditioning	Heating	Comfort seat	Traction control	Warning light	Safety belt	Page
W7101	Implement carriers												
11611	MIC 84		84	0-120	5000								707
	MIC 70		66	100	3500								709
SILVE CO.	MIC 50 Adv		50	80	3500								711
-	MIC 50		50	80	2600								711
TO AL	MIC 42		42	40+20	2500								713
The state of the s	MIC 35		35	40 / 20	2500								713
0	MIC 34 C		34	40	1750	•	•	•		-	•		715
	MIC 26 C Adv		26	40	1750					-			715

■ NEW ■ Included in the scope of supply. □ Available accessories.




ECONOMICAL USE ALL YEAR ROUND

Kärcher municipal sweepers deliver exceptional performance everywhere: On large areas, difficult surfaces, roads, paths, car parks, turfed areas and sports facilities. From spring cleaning to garden maintenance in summer and autumn, as well as winter jobs. Each of these robust machines with diverse implements forms an application-optimised solution in terms of power, operability and efficiency. And in turn, an investment that retains its value for years.









1 Robustness

Drivers should be able to completely rely on their machines in any situation. To ensure that everything works perfectly even during difficult tasks, Kärcher only uses top-quality materials and components. The high level of quality of our implement carriers and vacuum sweepers facilitates regular maintenance and forms the basis of a long product service life. In combination with the latest user-friendly technology, our machines can cope with anything – from January through to December.

Safety

Kärcher does not compromise on safety. Whether on the road or during daily work routines – the modern assistance systems of our implement carriers and vacuum sweepers meet the highest safety requirements and ensure that work does not become a risk.

Convenience

Optimal freedom of movement: Kärcher offers the most spacious cabin in this machine class – a decisive advantage, not just during long periods of use. The vibration-cushioned cabin can be individually equipped and provides a healthy working environment with pleasantly reduced noise.

2 Flexible and compatible

Kärcher municipal machines are profitable investments. Their built-in flexibility and broad range of applications mean they have many uses on a daily basis. The machines are always ready to use – regardless of the season, wind and weather, day or night. Fast implement changing and high transport speed reduce setup and non-productive times. Attention to detail and an efficient operating concept with excellent ergonomics result in effective working at low cost all year round.

3 Made in Germany

Kärcher implement carriers and vacuum sweepers are produced solely in Germany. Kärcher, a traditional family-owned company, has always maintained a close dialogue with municipalities and therefore always put its customers' specific requirements at the forefront of machine development.

4 Leasing and financing

Kärcher is on hand not only to offer you help and advice in selecting the right machine, but also to offer the appropriate financing model. Because for Kärcher, a good partnership means working successfully together with its customers. Place your trust in us!





Sweening



Winter service



Wet cleaning

MIDDLE CLASS



2-seater machine for year-round use

Vacuum sweeper and implement carrier in one: Our MC 130 combines both of these functions in a single 3.5-tonne machine, which performs well in both large, open spaces and more confined spaces in town and city centres. And it goes without saying that it can be used all year round. It boasts a comfortable, two-seater cab and an intuitive operating concept, with two joysticks, an "eco" button and a central multifunctional display.









1 Kärcher multi-function display

- Directly integrated in the steering wheel rim, therefore visible to the driver at all times.
- Operating elements on the ergonomic armrest allow for convenient individual brush control.

3 Quick-change system for implements

- Tool-free change of the implements mounted on the rear via hydraulic tipping frame.
- Brush system is removed using a trolley.

2 Comfortable two-seat cab

- 360° visibility and pleasant cab climate.
- Hydrodynamic 4-fold suspension ensures low noise level and low-vibration driver comfort.

4 3.5-tonne class

- Suitable for footpath use thanks to a permissible total weight of 3.5 toppes
- A class B driving licence is sufficient for operation.

CONFIGURATION OPTIONS



MC 130 Adv

1.442-230.2

MC 130 Plus

1.442-233.2

699

- Powerful, hydraulic all-wheel drive Powerful, hydraulic all-wheel drive ■ Traction control with optional differential lock ■ Traction control with optional differential lock Technical data Drive / Engine 4-cylinder diesel engine / Kubota 4-cylinder diesel engine with DPF / Kubota Power kW / hp 36.5 / 50 48.6 / 66 STAGE IIIA STAGE IIIB km/h 1200 Working width 1200 Max. working width 2600 2600 with 3 side brushes Turning circle (inner) 1210 1210 1000 Container capacity 1000 195 195 Fresh water tank 2275 Weight, empty 2275 Total permissible weight 3500 3500 3950 × 1200 × 1990 3950 × 1200 × 1990 Dimensions (L × W × H) Equipment Air conditioning system Multifunctional display Driver's seat Configurable Configurable 3rd side brush optional optional Water recycling system High-pressure cleaner Wander hose
- Included in the scope of supply.

 Available accessories.

COMPACT CLASS



Clean. Powerful. Cost-effective.

With its compact design, excellent manoeuvrability, intuitive operating concept and spacious cab that offers outstanding comfort to its occupants, our MC 80 sweeper scores highly on all fronts. Not only this, but the 35-hp diesel engine with particle filter falls well within the limits set out in the EU STAGE V regulations that are due to come into force, which means that the machine can even be used in town and city centre areas where the emissions rules are particularly strict.













1 Intuitive operating concept from the 3.5 tonne class

- Operator terminal integrated ergonomically in the armrest for intuitive
 Easy-to-install two-brush system with individual brush control operation with simple symbols.
- Automatically in working operation at the touch of a button. Individual
 CFD-optimised 800 I waste container with water circulation system, control of functions is also possible if needed.
- Individual control and lifting of brush increase precision.

2 Maximum operating comfort

- Largest cab in its class (1.45 m³ air volume), 360° panoramic view, ergonomic and clearly arranged.
- Windows on both sides, lockable storage compartment, USB charging
- Entry and exit on both sides for maximum flexibility when working.

3 The highest standard of sweeping

- 185 I fresh water tank for long work intervals.
- Optional 3rd side brush, e.g. for sweeping kerbs or weed brush for removing weeds.

4 Economical and environmentally friendly drive

- Common rail direct injection and diesel particulate filter lower the emission values below STAGE V.
- For applications in urban green zones.
- Lower fuel consumption protects the environment and lowers the

CONFIGURATION OPTIONS



MC 80

- Large spacious cab with volume of 1.45 m³
 Environmentally friendly diesel engine with optional particulate filter
- Individual brush control and lifting

recilifical data		
Drive / Engine		Three-cylinder diesel engine/Yanmar (DPF optional)
Power	kW / hp	26 / 35
Exhaust emissions standard		STAGE V ready
Speed	km/h	25
Working width		-
Max. working width with 3 side brushes	mm	2240
Turning circle (inner)	mm	910
Container capacity	I	800
Fresh water tank	1	185
Weight, empty	kg	1900
Total permissible weight	kg	2500
Dimensions (L × W × H)		3237 / 1070 / 1980
Equipment		
Air conditioning system		
Multifunctional display		-
Driver's seat		Configurable
3rd side brush		optional
Water recycling system		
High-pressure cleaner		
Wander hose		
Order no.		1.442-252.2
Price		
☐ Available accessories.		

Technical data

COMPACT CLASS

SV. AX 8

The agile, compact device for year-round use

Even adverse weather conditions and low temperatures do not harm the MC 50 Adv. Developed for year-round use, it offers optimal sweeping properties and extremely user-friendly handling. Implements such as the mower or snowplough and spreader can be changed in an instant without the need for any tools and – like the brush system – can be operated intuitively and easily using a hand-size joystick.









1 Parallelogram guided brush system

- Pendulum-suspended sweeper mechanism with load relief and hydraulic floating position for constant contact pressure.
- Optimal sweeping results, even on uneven ground.
- Low fuel and water consumption and reduction of exhaust gas quantity and operating noise.

3 Straight suction channel

- Minimises the risk of blockages.
- The suction tube between the suction mouth and the waste container can be extracted using two handles and with no need for tools.

2 Automatic coarse dirt flap

- Opens automatically for larger objects and closes again as quickly as possible
- Guarantees ideal suction results with no residues.

4 Innovative vacuum technology

- The machine's innovative suction system was designed based on computer-aided CFD flow simulations.
- Robust, rust-free waste container with 500 litre capacity and 100 per cent fill level.

CONFIGURATION OPTIONS



MC 50 Adv Comfort

MC 50 Adv

		Comfortable driver cabinHeatingAir conditioning system	Prepared for year-round useSweeping, mowing, winter maintenanceHighly efficient vacuum system
Technical data			
Drive / Engine		4-stroke diesel engine / Yanmar	4-stroke diesel engine / Yanmar
Power	kW / hp	19.2 / 26	19.2 / 26
Exhaust emissions standard		STAGE IIIA	STAGE IIIA
Speed	km/h	20	20
Working width	mm	1400	1400
Max. working width with 3 side brushes	mm	2000	2000
Turning circle (inner)	mm	750	750
Container capacity	I	500	500
Fresh water tank	I	165	165
Weight, empty	kg	1150	1150
Total permissible weight	kg	1750	1750
Dimensions (L × W × H)	mm	2960 × 1090 × 1970	2960 × 1090 × 1970
Equipment			
Air conditioning system			-
Multifunctional display		-	-
Driver's seat		Configurable	Configurable
3rd side brush		optional	optional
Water recycling system			
High-pressure cleaner			
Wander hose			
Order no.		1.442-204.2	1.442-204.2
Price			

□ Available accessories.

LIGHT WASTE VACUUM CLEANER.

Great suction power for small areas

Ideal for grassed and hard surfaces in industrial and municipal facilities: the walk-behind IC 15/240 W litter vacuum deposits leaves and refuse, e.g. large PET bottles in a standard refuse bin.







- 1 One-hand operation via drawbar
- Easy machine handling and control one hand is always free.
- 3 Designed for standard refuse bin (240 I), available worldwide
- Easy disposal by changing refuse bins.
- 2 Hydrostatic, maintenance-free traction drive (forwards/backwards)
- Comfortable working even on gradients; easy to transport.

TECHNICAL DATA AND EQUIPMENT

■ Included in the scope of supply.

		IC 15/240 W Adv	IC 15/240 W
		 Hydraulic traction drive with forward and reverse gears. Suction pipe with arm-guide Public-service equipment (flashing beacon, fine dust filter, curb climbing aid) 	Hydraulic traction drive with forward and reverse gearsSuction pipe with arm-guide
Technical data			
Power	kW	4	4
Working speed	km/h	6	6
Operating hours on one tankful	h	2.5	2.5
Container capacity	I	240	240
Load capacity	kg	70	70
Working width	mm	100	100
Climbing ability	%	15	15
Equipment			
Suction hose with suction tube			•
Elapsed time counter			
240-litre rubbish bin			•
Lockable storage compartment		•	
Electro start			II.
Hinged bulk waste flap		•	
Flashing beacon			-
Curb climbing aid		•	-
Polyester flat pleated filter			-
Order no.		1.183-904.0	1.183-903.0
Price			

Accessories			
Product name	Order no.	Description	Price
Blow tube with parison	2.850-831.0	For blow-sweeping leaves and light debris.	
Fine dust filter (kit)	2.850-832.0	For dust-free working.	
Holding machine for rubbish bags	2.850-845.0	Easy refuse bag filling and removal.	

HEAVY IMPLEMENT CARRIERS



The beefy powerhouse

Do you need a machine offering ultimate power that can be finely adjusted to suit any task? The MIC 84 makes work easier. This powerful and versatile machine can be used for additional applications in municipal use such as asphalt milling or removing weeds using hot steam and can be fitted with a front loader. The extreme power of this machine can be infinitely adjusted via a potentiometer to suit the particular implement used.









1 Comfort features

- The spacious cab, clear overview, and pneumatic heated seat guarantee Variable hydraulic system. a high level of comfort.
- The low noise level is pleasant for the driver and the environment.

3 Variable power

- Preprogrammed programmes for front loader, mowing unit and winter service implements.


2 Central multifunction display

■ Engine speed, speed, temperature, driving mode, and fuel levels can be ■ Suitable for year-round use for lawn-mowing, winter service, and viewed at a glance.

4 Numerous implements for an extremely wide range of applications

- Preset programs for front loader, snow blades, mower, cylinder mower, and other implements.

CONFIGURATION OPTIONS



MIC 84

- Efficient 2-speed traction drive
- Powerful, hydraulic all-wheel drive

		■ Traction control
Technical data		
Drive / Engine		4-cylinder diesel engine / Kubota
Power	kW / hp	61.7 / 84
Exhaust emissions standard		STAGE IIIA
Speed	km/h	40
Working speed	km/h	20
Fuel tank	1	78
Turning circle (inner)	mm	1500
Weight, empty	kg	2562
Total permissible weight	kg	5000
Dimensions (L × W × H)	mm	3215 × 1590 × 2130
Equipment		
A in some distancians as setoms		

Equipment	
Air conditioning system	
Heating	
Driver's seat	Configurable
Heated windscreen	-
Sweeping system	-
Hydraulic tilting frame	-
Load damping	
Front loader	
Order no.	1.442-012.2
Price	

□ Available accessories.

709

MIDDLE CLASS



Full power, all year round

A small powerhouse for really big jobs: 20 hp more power than the MIC 50 gives the compact MIC 70 the necessary power for numerous applications using heavy implements, e.g. the front loader developed by Kärcher. In addition, the 4-cylinder diesel engine with 66 hp has a soot particle filter for lower exhaust emissions as standard.









1 High hydraulic power

- A powerful tandem pump (100 l/min) drives even the heaviest implements with ease.
- The power output can be distributed between front and rear (50 + 50 I/ min front or 50 + 50 l/min rear).

3 Central display

- The working hydraulics are adjusted using the central display.
- Display of driving speed and regeneration phase of the diesel particulate filter.

2 Low-emission engine

- Economical and powerful 4-cylinder kubota common rail diesel engine Quick-change system via hydraulic tilting frame for implements with 48.6 kW (66 HP).
- Exhaust gas treatment and diesel particulate filter mean that it can be
 Tool-free, rapid mounting and removing by one person, with virtually certified in accordance with STAGE IIIB and Tier 4 Final.

4 Quick-change system for implements

- no force required.

CONFIGURATION OPTIONS



MIC 70

- Efficient 2-speed traction drive
- Powerful, hydraulic all-wheel drive
 Traction control with optional differential lock

Technical data		
Drive / Engine		4-cylinder diesel engine with DPF / Kubota
Power	kW/hp	48 / 66
Exhaust emissions standard		STAGE IIIB
Speed	km/h	40
Working speed	km/h	20
Fuel tank	I	50
Turning circle (inner)	mm	1148
Weight, empty	kg	1785
Total permissible weight	kg	3500
Dimensions (L × W × H)	mm	2947 × 1368 × 1998

Equipment	
Air conditioning system	
Heating	
Driver's seat	Configurable
Heated windscreen	
Sweeping system	-
Hydraulic tilting frame	1
Load damping	
Front loader	
Order no.	1.442-240.2
Price	

☐ Available accessories.

MIDDLE CLASS



Compact can be powerful

The MIC 50 is a compact implement carrier in the 3.5 tonne class especially developed for municipal use and is suitable for on-road and off-road use. A working width of up to 3 metres is possible for mowing. Customise your MIC 50. Only the vehicle chassis and cabin are always the same. Traction drive, wheels and hydraulic system can be individually combined.









1 High-quality components

- Removable motor housing provides easy access to all components for Small external dimensions make it suitable for use on footpaths. maintenance purposes.
- 3 Compact in all dimensions

2 Clearly visible and comfortable

- Implements and the immediate environment are visible at all times.
- A spacious cab and low operating noise provide for maximum operator

4 Quick-change system for implements

Tool-free, quick change of implements.

CONFIGURATION OPTIONS



		MIC 50 Adv	MIC 50
		 2-speed traction drive Powerful, hydraulic all-wheel drive Traction control with optional differential lock 	1-speed traction drivePowerful, hydraulic all-wheel driveTraction control
Technical data			
Drive / Engine		4-cylinder diesel engine / Kubota	4-cylinder diesel engine / Kubota
Power	kW/hp	36.5 / 50	36.5 / 50
Exhaust emissions standard		STAGE IIIA	STAGE IIIA
Speed	km/h	40	30
Working speed	km/h	20	20
Fuel tank	I	50	50
Turning circle (inner)	mm	1148	1148
Weight, empty	kg	1655	1655
Total permissible weight	kg	3500	2600
Dimensions (L × W × H)	mm	2848 × 1368 × 1998	2848 × 1368 × 1998
Equipment			
Air conditioning system			
Heating			
Driver's seat		Configurable	Configurable
Heated windscreen			
Sweeping system		-	-
Hydraulic tilting frame			
Load damping			
Front loader			
Order no.		1.442-220.2	1.442-220.2
Price			
☐ Available accessories.			

713

COMPACT CLASS



Whatever needs doing, consider it done. Even in low-emission zones

With its generously proportioned, 1.45 m³ cab, all-round visibility, intuitive operating concept and integrated quick-change system, it is rare to find such a comfortable, user-friendly workstation. The environmentally friendly engine, which even complies with the STAGE-V exhaust emissions standard, enables our economical MIC 35/42 implement carrier to be used even in low-emission zones, where it effortlessly tackles all kinds of municipal jobs.













1 Economical and environmentally friendly drive

- Common rail direct injection and diesel particulate filter lower the emission values below STAGE V.
- For applications in urban green zones.
- Lower fuel consumption protects the environment and lowers the operating costs.

3 Maximum operating comfort

- Largest cab in its class (1.45 m³ air volume), 360° panoramic view, ergonomic and clearly arranged.
- Windows on both sides, lockable storage compartment, USB charging port, bottle holder.

2 Integrated quick-change system

- Mounting of front implements via standard coupling triangle KAT
- Replacement of implements at the rear using quick-change system with hydraulic tilting frame.
- Optional multi-coupler system for fast and drip-free connection of hydraulics.

4 Extremely easy to maintain

- The high-quality components allow very long maintenance intervals of
- Access to all maintenance components possible without the need for any tools, e.g. via the swing-out motor cover.
- The cooler can be put in a defined maintenance position for cleaning.

CONFIGURATION OPTIONS



		MIC 42	MIC 35
		 42 HP diesel engine with up to 60 l hydraulic output Quick-change concept for front- and rear-mounted implements Year-round use 	 Powerful, hydraulic all-wheel drive Quick-change concept for front- and rear-mounted implements Year-round use
Technical data			
Drive / Engine		Three-cylinder diesel engine with DPF/Yanmar	Three-cylinder diesel engine with Yanmar (DPF optional)
Power	kW/hp	31 / 42	26 / 35
Exhaust emissions standard		STAGE V ready	STAGE V ready
Speed	km/h	25	25
Working speed	km/h	25	25
Fuel tank	I	41	41
Turning circle (inner)	mm	910	910
Weight, empty	kg	1400	1400
Total permissible weight	kg	2500	2500
Dimensions (L × W × H)	mm	3085 × 1070 × 1980	3085 × 1070 × 1980
Equipment			
Air conditioning system			
Heating		•	
Driver's seat		Comfort with air suspension	Comfort seat (optional)
Heated windscreen		-	-
Sweeping system			
Hydraulic tilting frame		•	
Load damping			
Front loader		-	-
Order no.		1.442-250.2	1.442-251.2
Price			
■ Included in the scope of suppl	y. 🗆 Available	e accessories.	

COMPACT CLASS



Powerful machine – to make your work easier

Where it is not possible to use large vehicles, it is time for our implement carriers MIC 26 C and MIC 34 C. Their slim design makes these perfect for paths or in parks – without compromising the power or performance. With its powerful 24 kW turbo diesel engine, the MIC 34 C also easily tackles energetic tasks such as mowing with grass pick-up or weed removal.







3 Quick-change system for implements



1 Robust power transmission

- Powerful working hydraulics adapted to the motor rating.
- Enables mowing with grass collection as well as weed removal in a single pass.

1 Robost power transmission

2 Powerful and durable

- The 34-HP turbo diesel engine taps into a wide range of potential possible applications.
- The 40-litre working hydraulics also easily drive power-intensive implements such as snow throwers and mowers.
- $\hfill \blacksquare$ A second hydraulic circuit increases the versatility of the machine.

- Quick-change system for tool-free changeover of various implements by just one person.
- Switch from sweeper to mower or winter vehicle in less than five minutes.

4 Air conditioning system

Optimal room climate in all weathers with air-conditioning, heating, and rotating air nozzles.

CONFIGURATION OPTIONS



		Comfortable driver cabinHeatingAir conditioning system	Comfortable driver cabinHeatingAir conditioning (optional)
Technical data			
Drive / Engine		4-stroke diesel engine / Kubota	4-stroke diesel engine / Yanmar
Power	kW/hp	24 / 34	19.2 / 26
Exhaust emissions standard		STAGE IIIA	STAGE IIIA
Speed	km/h	20	20
Working speed	km/h	20	20
Fuel tank	I	37	37
Turning circle (inner)	mm	750	750
Weight, empty	kg	950	850
Total permissible weight	kg	1750	1750
Dimensions (L × W × H)	mm	2470 × 1090 × 1970	2470 × 1090 × 1970
Equipment			
Air conditioning system		•	-
Heating			
Driver's seat		Configurable	Configurable
Heated windscreen		-	-
Sweeping system			•

MIC 26 C Adv

1.442-211.2

MIC 34 C

1.442-214.2

■ Included in the scope of supply.

Hydraulic tilting frame Load damping Front loader

WRS 200



Mobile weed removal and high-pressure cleaning

A machine for various professional cleaning tasks and extraordinary mobility. When combined with a Kärcher municipal vehicle, weeds can be removed using hot water and professional hot water high-pressure cleaning even in the most remote places.









1 Suitable for diverse tasks on the move

- Targeted, efficient weed removal using hot water: Automatically using the front bar or manually with the hand lance.
- Professional cold and hot water high-pressure cleaning.
- Efficient removal of chewing gum residue on hard floor coverings.

2 Compact design

- Reduced risk of damage since the vehicle rear remains visible in the exterior mirror even when driving round corners.
- Thanks to its high manoeuvrability, the machine can also be easily used in narrow and tight spaces.
- Does not affect the machine width regardless of the carrier vehicle used.

3 Low vehicle centre of gravity

- Quick assembly via coupling triangle on the vehicle rear for optimum weight distribution.
- The low vehicle centre of gravity ensures comfortable handling when
- Water tanks up to a volume of 800 litres are possible depending on the

4 Highly efficient periods of work

- The highly efficient burner is ready to use in no time at all.
- Features tried-and-tested efficient K\u00e4rcher burner technology for low fuel consumption.
- Powerful Kärcher high-pressure pump for working pressures of up to

TECHNICAL DATA AND EQUIPMENT

WRS 200

Weed	remov	al
Profe	ssional	high-pressure cleaning

Chewing gum removal

Technical data		
Drive		Vehicle hydraulics 40 I/min
Fuel		Diesel
Diesel consumption	I/h	8
Flow rate	I/h	900-1700
Working pressure	bar	70-200
Max. temperature	°C	98
Empty weight	kg	312
Dimensions (L \times W \times H)	mm	608 × 1032 × 1217

Pressure adjustment	
Water softening	•
Spray gun	
Front bar	
Weed removers	
Water tank	
Coupling triangle adapter	
Order no.	2.200-000.0
Price	

■ Included in the scope of supply.

Available accessories.

MIC 34 C, sweeping

VACUUM SWEEPERS AND MUNICIPAL IMPLEMENT CARRIERS IN USE





MIC 34 C, winter service

































MIC 42, rotary mower

MIC 50, weed removal

MIC 50, V-plough

MC 130, scrubbing deck

MIC 84, weed brush

MIC 84, snow thrower













MC 80, sweeping system

MIC 50, sickle mower

MIC 84, sickle mower

MIC 84, front loader MIC 84, asphalt cutter

EVERYTHING FOR A CLEAN VEHICLE

You know what you want: The ideal system for cleaning cars and commercial vehicles, inside and out - designed to be highly efficient, have a long service life, produce perfect cleaning results, consume little water and be eco-friendly. Our wash systems are just what you need: tailored precisely to suit your requirements.



Table of contents: Wash systems

Gantry car washes	Page	73
Commercial vehicle washes	Page	73
Self-service wash systems	Page	73
Steel framework for self-service wash bays	Page	74
Central vacuum systems	Page	74
Self-service vacuum cleaners	Page	74
Forecourt units	Page	74
Cleaning and care agents	Page	87



CWB 3 Klean!Star iQ. MORE SKILL. MORE TO OFFER. HIGHER IQ.

With our CWB 3 Klean!Star iQ three-brush gantry car wash, vehicle washing becomes an experience. With innovative and unique functions which will impress even the most demanding customers of this premium gantry. And with a large range of different designs – through to a fully customised version.

CWB 3 Klean!Star. OFFER MORE. ACHIEVE MORE. BE MORE.

Our CWB 3 Klean!Star iQ three-brush gantry car wash boasts extensive equipment options along with excellent performance when washing and drying. It is an attractive solution for virtually any site, particularly if the focus is on costs.

OVERVIEW

Wash systems from Kärcher: we offer a system to suit any location and requirements. Sophisticated, efficient, powerful and tailored to your specific needs.

		Price	Order no.	Number of brushes	Wash heights (mm)	Fresh water connection (I/min, bar)	Power supply (Ph / V / H2)	Page
	Gantry car washes							
	CWB 3 Klean!Star iQ		on request	3	2900 / 2800 / 2700 2600 / 2500 / 2400 2300 / 2200 / 2100	80, 4	3 / 400 / 50	727
	CWB 3 Klean!Star		on request	3	2900 / 2800 / 2700 2600 / 2500 / 2400 2300 / 2200 / 2100	80, 4	3 / 400 / 50	729
	CB 5		on request	5	2800 / 2500 / 2300	100, 4-6	3 / 400 / 50	731
	CB 3		on request	3	2800 / 2500 / 2300	min. 50, 4-6	3 / 400 / 50	733
	Commercial vehicle washes							
F	TB 50		on request	3	5050	100, 4-6	3 / 400 / 50	735
THE RESERVE TO	TB 46		on request	3	4600	100, 4-6	3 / 400 / 50	735
Name of Street	TB 42		on request	3	4250	100, 4-6	3 / 400 / 50	735
	TB 36		on request	3	3600	100, 4-6	3 / 400 / 50	735
	RBS 6014		1.826-405.0 1.826-415.0 1.826-425.0	1	4205	80, 3-6	3 / 400 / 50 3 / 230 / 50 1 / 240 / 50	737
	RBS 6012		1.826-205.0 1.826-215.0	1	3645	80, 3-6	3 / 400 / 50 3 / 230 / 50	737
■ NEW								

		Price	Order no.	Number of wash bays	Flow rate (I/h)*	Working pressure (bar)	Operating temperature (°C)	Hot water temperature (°C)	Power supply (Ph / V / Hz)	Page
	Self-service wash systems									
= ii -	SB MU		on request	4-8	900 / 500	120 / 100	max. 40	max. 60	3 / 400 / 50	739
94	SB MB		on request	2-4	900 / 500	120 / 100	max. 40	max. 60	3 / 400 / 50	741
	SB MC 2		1.319-000.2	1-2	900 / 500	120 / 100	-20 to +40	max. 40	3 / 400 / 50	743

^{*} Per pump.

		Price	Order no.	Number of vacuuming bays	Air flow rate (I/s)	Vacuum (mbar)	Dirt container capacity (l)	Power input (KW)	Sound pressure level dB(A)	Power supply (Ph / V / Hz)	Dimensions (L×W×H in mm)	Page
	Self-service vacuum cleaners											
_ [[]	SB VC 2 Ec		1.070-003.2	2	2×60	2×244	2×36	2×1.38	65	1 / 230 / 50 / 60	600×1220×2200	747
	SB VC 1 Ec		1.070-003.2	1	60	244	36	1.38	62	1 / 230 / 50 / 60	600×850×2200	747
	SB VC 2		1.070-003.2	2	2×74	2×254	2×36	2×1.38	63	1 / 230 / 50 / 60	600×1220×2200	747
	SB VC 1		1.070-003.2	1	74	254	36	1.38	60	1 / 230 / 50 / 60	600×850×2200	747

		Price	Order no.	Power input (kW)	Protection class (IP)	Power supply (Ph / V / Hz)	Dimensions (L × W × H in mm)	Frost protection	Calibration*	Storage compartment	Start button	Electronic coin acceptor	Page
	Forecourt units												
THE PROPERTY.	AWT-C Fp		1.534-913.0	0.45	44	1 / 230 / 50	423 × 423 × 1550						749
温 略 国	AWT-C		1.534-912.0	0.45	44	1 / 230 / 50	423 × 423 × 1550		•			•	749
P 2 2	AWT Fp		1.534-903.0	0.45	44	1 / 230 / 50	423 × 423 × 1550						749
	AWT		1.534-902.0	0.45	44	1 / 230 / 50	423 × 423 × 1550					•	749
4	AT-C Fp		1.534-911.0	0.45	44	1 / 230 / 50	423 × 423 × 1550		•				749
	AT-C		1.534-910.0	0.45	44	1 / 230 / 50	423 × 423 × 1550						749
	AT Fp		1.534-901.0	0.45	44	1 / 230 / 50	423 × 423 × 1550						749
	AT		1.534-900.0	0.45	44	1 / 230 / 50	423 × 423 × 1550						749
	PT Fp		1.534-909.0	0.30	44	1 / 230 / 50	423 × 423 × 1550						749
	PT		1.534-908.0	0.30	44	1 / 230 / 50	423 × 423 × 1550						749
	SB F M80 S		1.534-905.0	0.40	44	1 / 230 / 50	1511×531×1071						749
	SB F M80		1.534-904.0	0.40	44	1 / 230 / 50	1097×531×1071						749
	SB F M80 3 S		1.534-907.0	0.40	44	3 / 400 / 50	1511×531×1071					•	749
	SB F M80 3		1.534-906.0	0.40	44	3 / 400 / 50	1097×531×1071					•	749
	SB F M80 Sm S	•	1.534-915.0	0.40	44	1 / 230 / 50	1511 × 531 × 1071						749
	SB F M80 Sm	•	1.534-914.0	0.40	44	1 / 230 / 50	1097 × 531 × 1071						749

[■] NEW ■ Included in the scope of supply.
* Please check whether a calibrated machine is required according to legislation in the country of use.



1 Gantry car washes

A machine concept that is well thought-out in every detail and combines excellent reliability and minimum maintenance with optimum accessibility and easy operation. The system can be individually adapted to local conditions and specific customer requirements.





2 Commercial vehicle washes

There are no compromises when it comes to operating commercial vehicle ble, efficient and durable. The equipment and operation of the system can be tailored to individual customer requirements.

3 Self-service wash systems

With our self-service wash systems you get the ideal cleaning solution for washes. The use of hot-dip galvanised steel constructions, belt drives, direct a fast, gentle manual vehicle wash. And if it's perfection you're after, take a drives and intelligent Can Bus controls makes these Kärcher systems relialook at our steel framework, central vacuum cleaners, self-service vacuum cleaners and forecourt units.



Highest standards. Easily met

Nearly everything can be better. Many customers know this and therefore always expect more. They want more performance, more functions and, of course, everything tailor-made for their own vehicle. With our CWB 3 Klean!Star iQ premium gantry car wash, you are already meet these high standards.













1 At first glance: quality and design

- Available in eight further colours in addition to the Kärcher design.
- The front doors are available in three different designs: either with or without a washing phase indication or as a custom design in line with customer requirements.

3 Clever savings conserve resources

- The brushes are supplied with reclaim water in the second pass and with fresh water only in the rinsing process.
- Full cleaning performance at lower operating costs.


2 Taller. Wider. Better

- There is a continuing trend for vehicles to be taller and wider.
- The Klean!Star iQ is wider at mirror and wheel height.

4 Clever frame concept

- Time-saving and safe assembly.
- Low installation costs.

CONFIGURATION OPTIONS



CWB 3 Klean!Star iQ

		•
Technical data		
Wash height	mm	2900 / 2800 / 2700 / 2600 / 2500 / 2400 / 2300 / 2200 / 2100
Plant height incl. roof brush splash guard	mm	3730 / 3630 / 3530 / 3430 / 3330 / 3230 / 3130 / 3030 / 2930
Drive through width at mirror height	mm	2450
Fresh water connection	I/min, bar	80, 4
Power supply	Ph / V / Hz	3 / 400 / 50











K!Brush iQ

Every brush segment adapts individually to the relevant vehicle contour - for optimum washing results even with challenging contours. With CareTouch brushes and K!Back iQ.

K!Back iO

rear, the side brushes swivel out behind the vehicle at 90°, tilt by 15° washer for thorough rim cleaning. and adapt perfectly to the contours.

K!Planet iO

For optimum cleaning of the vehicle Gentle and efficient, even on the most stubborn dirt: planetary gear

High performance roof drier with nozzle bars that swivel by +/- 135°. For optimum drying in just one pass, even with extremely difficult



Needs-based investment


Not everything that is technically possible using equipment makes economic sense at every site. This is why we are offering you a gantry car wash - Klean!Star - that takes both aspects into account: excellent equipment and a highly cost-effective solution.













1 Taller. Wider. Better

- There is a continuing trend for vehicles to be taller and wider.
- The Klean!Star is wider at mirror and wheel height.
- 3 Clever frame concept
- Time-saving and safe assembly.
- Low installation costs.


2 Clever savings conserve resources

- The brushes are supplied with reclaim water in the second pass and with fresh water only in the rinsing process.
- Full cleaning performance at lower operating costs.

4 High quality overall appearance

Available in four further colour versions and in two different front door designs in addition to the K\u00e4rcher design.

CONFIGURATION OPTIONS




CWB 3 Klean!Star

Technical data		
Wash height	mm	2900 / 2800 / 2700 / 2600 / 2500 / 2400 / 2300 / 2200 / 2100
Plant height incl. roof brush splash guard	mm	3730 / 3630 / 3530 / 3430 / 3330 / 3230 / 3130 / 3030 / 2930
Drive through width at mirror height	mm	2450
Fresh water connection	l/min, bar	80, 4
Power supply	Ph / V / Hz	3 / 400 / 50

reclamation systems





We offer several high-pressure solutions – you decide which suits your site and select everything down to the high-pressure pump.



Intelligent contour detection

For optimum vehicle contour detection, the side brushes are tilted (15°) or locked depending on the pass.



Precise wheel wash

The linear scissor wheel washer reliably reaches the wheels even on vehicles which are not positioned centrally or have a narrow track, as well as on small cars.



Adjustable roof drier

The roof drier, which can be adjusted by $+/-30^\circ$, follows the vehicle contours exactly and thus enables even better drying at the front and rear.



Minimum size maximum performance

The CB 5 is the alternative for sites with more than 1,200 washes per month. Operators profit from express washes in only two passes and increased vehicle throughput with much shorter waiting times for customers.













1 Express wash

The express wash is ideal for vehicles that are only slightly dirty. Vehicles The comparably low investment costs are covered very quickly due to the are washed and dried in only two passes, meaning waiting time for customers is kept to a minimum and profits increase at the same time.

3 High vehicle throughput

high vehicle throughput. The result is profit and satisfied customers.


2 Compact and compatible

The CB 5 fits easily into a standard wash hall (hall length 10 m) - without any additional assembly and installation costs. The perfect alternative for short tunnels.

4 Low-maintenance technology

Bearings and guides, side brush inclination with direct drives and flat belts for lifting movements are extremely low-maintenance and therefore generate virtually no extra costs.

CONFIGURATION OPTIONS



CB 5

Technical data		
Wash heights	mm	2800 / 2500 / 2300
Plant height	mm	3715 / 3415 / 3215
Fresh water connection	I/min, bar	100, 4-6
Power input	kW	22
Power supply	Ph/V/Hz	3 / 400 / 50











The VehiclePro Klear!Rim Foam RM 802 Dirt remaining on the vehicle after removes stubborn dirt and brake dust effortlessly and gently, contrib- and gently by the brush wash and uting to customer satisfaction and increasing the attractiveness of the site.

Gentle brush wash

the prewash is removed thoroughly VehiclePro Brush Shampoo RM 811

Super Finish

With the VehiclePro Foam Polish RM 837, the Super Finish programme produces gleaming results: visible long-lasting protection that lasts for drying results. up to 10 more washes.

Perfect drying

VehiclePro Drying Aid RM 829 Classic in combination with our powerful dryers ensures spotless



Flexible, fast and economical

Fast can be this flexible. Economical can be this fast. And flexible can be this economical. The CB 3 combines these three attributes in a gantry car wash that leaves nothing to be desired. The CB 3 is also available as a Takt system (downstream gantry for washing and drying two vehicles at the same time).













1 Kärcher Fleet-compatible control

The intelligent control allows the CB 3 to be connected to Kärcher Fleet, our This powerful high-pressure module (1,300 l/h, 70 bar) is mounted on the cloud-based data management system, which supplies all relevant system data in real time.

3 High-pressure pump on board

gantry, thus eliminating the need for an additional technical room.

2 Water saving function

Fresh water consumption is reduced by about 60 per cent per wash. This helps conserve natural resources and reduce costs for the operator.

4 Low-maintenance technology

Low-maintenance technology, including bearings and guides, side brush inclination with direct drives and the flat belt for lifting movements reduce service costs considerably.

CONFIGURATION OPTIONS

Optimum contour detection

Intelligent start and Different covering packages and operating systems custom design options **Powerful drying** Different high-pressure versions Different brush materials Effective wheel wash

CB 3

Technical data		
Wash heights	mm	2800 / 2500 / 2300
Plant height*	mm	3715 / 3415 / 3215
Fresh water connection	I/min, bar	min. 50, 4-6
Power input**	kW	8 / 16
Power supply	Ph / V / Hz	3 / 400 / 50

 * For gantries with "Basic" covering package without front cover, the plant height is reduced by 65 mm.

Powerful underchassis wash

Technical data refers to the CB 3; data for the CB 3 as a Takt gantry varies accordingly.





The VehiclePro Klear!Rim Foam RM 802 The combination of our effective removes stubborn dirt and brake dust thoroughly and gently. Shiny rims increase both customer satisfaction and customer numbers.



Gentle brush wash

brush wash and VehiclePro Brush Shampoo RM 811 Classic removes residual contamination after the prewash effortlessly, gently and



Super Finish

In combination with VehiclePro Foam Polish RM 837, the Super Finish programme gives the paintwork visible, long-lasting protection.



Efficient operation with

water reclamation systems

Perfect drying

Rinsing with the VehiclePro Drying Aid RM 829 Classic and subsequent drying with our powerful drier ensures optimal results.



Economical and reliable

Fast, thorough and efficient, user-friendly, low-maintenance and reliable – the innovative and powerful TB commercial vehicle wash for cleaning different vehicle types used by forwarding agencies, contract cleaners, car dealers and municipal authorities.











1 Low-maintenance

Reliable belt drives and direct drives make lubricating the system unnecessary.

2 Outstanding variability

The height and width of each basic version are variable. The height can be reduced by up to 300 mm (in 100 mm steps) and the width per side by up to 100 mm. The wash height and width vary accordingly.


3 Flawless wash process

Sophisticated solutions ensure that the wash process runs smoothly. The patented side brush bearing allows the brushes unhindered freedom of movement in all directions, which prevents the shafts from bending. The contact pressure of the side brushes can be adapted to suit the particular vehicle which, in combination with the precise contour detection, ensures optimum washing results.


4 Maximum flexibility

The innovative, universal CAN bus control ensures quick and easy installation and flexible wash programme configuration.

CONFIGURATION OPTIONS



		TB 50	TB 46	TB 42	TB 36
Technical data					
Wash height	mm	5050	4600	4250	3600
Plant height without splash guard	mm	5989	5539	5189	4539
Plant height with splash guard	mm	6047	5597	5247	4597
Fresh water connection	I/min, bar	100, 4-6	100, 4-6	100, 4-6	100, 4-6
Power input	kW	5.3	5.3	5.3	5.3
Power supply	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50





Dirt in hard-to-reach areas is removed quickly, easily and cost-effectively using a manual prewash.



Individual programme selection

A suitable programme for the particular vehicle type can be individually selected on a large, robust and clearly arranged control panel.



Effective brush wash

The combination of brush wash and our VehiclePro Brush Shampoo RM 811 Classic effectively removes dirt remaining on the vehicle after pre-cleaning.



Optimum drying

For optimum drying, VehiclePro Liquid Leather RM 833 can be used as an additional option.

MOBILE SINGLE-BRUSH COMMERCIAL VEHICLE WASH



Economical for small vehicle fleets

For quick and easy vehicle cleaning for small fleets: the RBS mobile single-brush commercial vehicle wash for targeted cleaning of the front, rear and sides of buses and vans. Cleaning is carried out by a rotating brush that moves around the vehicle.









1 Clean into the smallest nooks

■ With vertical contour detection and thanks to the tilting mechanism with adjusting wheel, the RBS reaches tilted vehicle fronts down to an angle of just 10°.

3 Simple operation

- Assisted by the brush rotation, the operator can easily move the system forward using the control and safety handle.
- The brush stops rotating when the handle is released.

2 Economic dosing

■ Kärcher cleaning agent can be added as required via a dosing pump.

4 Easy to manoeuvre

- Lightweight aluminium construction in conjunction with two track wheels and four castors ensures excellent manoeuvrability and good stability.
- Extremely resistant to external influences.
- The half-shell cladding reliably protects the operator from splash

		RBS 6014	RBS 6012
Technical data			
Wash height	mm	4205	3645
Plant height	mm	4370	3810
Fresh water connection	l/min / bar	80 / 3-6	80 / 3-6
Connection load	kW	1.15	1.15
Voltage	V	400 230 240	400 230
Frequency	Hz	50	50
Number of current phases	Ph	3 3 1	3 3
Order no.		1.826-405.0 -415.0 -425.0	1.826-205.0 -215.0

SELF-SERVICE MULTI BAY UNIT

Modular for up to 8 wash bays



This system couldn't be more flexible: the modular concept of the Kärcher SB MU offers self-service wash centres maximum freedom of configuration (anything between 4 and 8 wash bays is possible) and adaptation to local conditions.













1 Reliable functionality

Pneumatic dosing pumps ensure process reliability and consequently a smooth workflow at every wash bay, even during peak times.

3 Easy, time-saving and cost-saving installation on site

The pump modules are pre-mounted on a frame upon delivery and undergo extensive function testing.


2 Diverse programme options

able wet/dry foam ensure greater flexibility and increase the attractiveness water and thus reduce energy consumption and costs. of the site.

4 Optimum energy efficiency

Additional options such as the foam polish wash programme or the switch-

CONFIGURATION OPTIONS



SB MU

Technical data		
Number of wash bays		4-8
Working pressure	bar	120 / 100
Flow rate per pump	I/h	900 / 500
Hot water temperature	°C	max. 60
Power input per pump	kW	4.7 / 2.8
Power supply	Ph / V / Hz	3 / 400 / 50



simply needs to be installed and connected.

Components version

Ready to use! The technical equipment can be assembled in a container and Components are delivered and installed in a technical room on site.

SELF-SERVICE MULTI BAY UNIT

Compact for up to 4 wash bays

The Kärcher SB MB is designed for operating up to four wash bays and can be custom configured to suit virtually any requirements. It goes without saying that all parts of the unit that are susceptible to corrosion are made of stainless steel, which in addition to offering advanced and reliable technology also increases service life and efficiency.











1 Reliable dosing

Pneumatic dosing pumps ensure process reliability and consequently satisfied customers at every wash bay, even during peak times.

3 Simple maintenance

Assemblies are easily accessible through the large front doors with detachable middle section - this saves maintenance time and your system is quickly ready to use again.

2 Protection against theft and vandalism

For external protection, there is a high-quality security lock from BKS, which can easily be exchanged for a lock from your own locking system on request.

4 Optimum energy efficiency


Energy consumption and costs remain low thanks to the pole-changing, water-cooled pumps, which use their waste heat to heat the wash water.


CONFIGURATION OPTIONS





SB MB

Technical data		
Number of wash bays		2-4
Working pressure	bar	120 / 100
Flow rate per pump	I/h	900 / 500
Hot water temperature	°C	max. 60
Power input per pump	kW	4.7 / 2.8
Power supply	Ph / V / Hz	3 / 400 / 50









Skid version

The technical equipment is pre-mounted on a frame and installed in a technical room on site. remote control location.

Cab version

Installed outside the wash bays. Simple programme selection via

Cab 1 and Cab 2 version

The Cab 1 version with combi wash tool (brush and high-pressure lance) or the Cab 2 version with separate wash tools (separate brush and high-pressure lance) are installed between the wash bays.

SELF-SERVICE MULTI BAY UNIT



It couldn't be more compact and flexible

The compact design of the SB MC 2 with low space requirements is customised to your needs and is available both as a one- and two-bay version with intelligent wash tool storage device for a maximum of two wash tools per wash bay. Building on selected components from our product portfolio, the clever concept follows an innovative platform idea.









3 Innovative design



1 Configurable machine

- Can be configured precisely to your requirements.
- Site-specific solutions.

2 Platform idea

■ Use of existing components from the Kärcher product portfolio.


4 Intelligent wash tool storage device

Holds up to two wash tools per wash bay.

Appealing, innovative and ergonomic design.

Safe storage protects the wash tools against damage.


CONFIGURATION OPTIONS



SB MC 2

Technical data		
Number of wash bays		1-2
Working pressure	bar	120 /100
Flow rate per pump	l/h	900 / 500
Operating temperature	°C	-20 to +40
Hot water temperature	°C	max. 40
Power supply	Ph / V / Hz	3 / 400 / 50





Available as either a one- or twobay version entirely according to requirements and spatial conditions. wash tool or separate wash tools.



Wash tools as required

High-pressure lance and foam brush are available either as a combi



Extra programme options

High-pressure cleaning, foam wash, rinse and wax are standard. Dirt removal is available as an option.



Hot or cold water

You have the choice of operation with hot or cold water, depending on the application.

STEEL FRAMEWORK



Highly functional

The modular concept of the Kärcher steel framework allows custom equipping of wash and care centres for one to eight wash bays. The steel framework is available in two different versions: operators normally choose the light version, while the heavy version is intended for regions that experience heavy snow and strong winds.









1 A range of roof versions

The domed roof is made of transparent polycarbonate - a trapezoidal version is also available.

2 Various partition wall materials

The partition walls can be made from glass, Trespa® or tarpaulin, and can be The steel framework with special roof attachment enables advertisement arranged as required.

3 Lighting concept using LED technology

Reduces power consumption by 55 per cent compared with conventional fluorescent tubes and makes the service life of the lamps three to five times longer. This sophisticated lighting concept with integrated feel-good effect also helps customers find their way around the system.

4 Customer-specific adaptation

boards to be installed and your CI to be attached. The design shown is reserved exclusively for Clean-Park operators.

CENTRAL VACUUM SYSTEMS FOR SELF-SERVICE OPERATION



Vehicle vacuuming - made easy

A central vacuum system combines drive, filter and control in one compact unit which requires very little space. The latest technology provides an outstanding vacuuming experience at low running costs. For operators, low maintenance and reliable operation are key attributes. For example, only one collection container needs to be emptied directly in the main building, saving you time. Tried-and-tested components designed for continuous operation reduce the susceptibility to faults to zero. Consistently high suction power saves time for operators and ensures satisfied customers.









1 Optimum power adaptation

- A side channel blower with intelligent control ensures consistently high suction power.
- The modern drive concept also reduces energy consumption to the necessary minimum.

2 Easy to use and easy to operate

- Coin in and ready to go an intuitive operating and handling concept makes for convenient vacuuming.
- Suction hose guidance from above provides easy access even in hard-to-reach corners of the vehicle.

3 Variety of configurations

- The central components are available with or without enclosure as
- The number of vacuum points can be adapted to suit individual customer requirements for maximum flexibility.

4 Low-maintenance

- Thanks to automatic filter cleaning, the system is low-maintenance and
- A bypass ensures a steady flow of air through the pipe, which produces a self-cleaning effect.

SELF-SERVICE VACUUM CLEANERS




Powerful. Convenient. Individual

Designed to meet the highest standards in suction power, comfort and design, our SB VC can be customised to your exact requirements, so you always have the machine you need on your site. Clever technical details not only make vacuuming easier for your customers, but also ensure simple operation and minimum servicing.















1 Tact, the patented, automatic filter cleaning system

- Fully automatic self-cleaning of filter.
- Suction power remains constantly high.
- Low maintenance costs and long filter life.

3 Optimised, ergonomic suction nozzle

- Special surface structure in grip area for optimum handling.
- Excellent cleaning results both in areas such as luggage compartments and for joints and gaps typical of vehicle interiors.


2 Hose recovery with fibreglass pole

- Intelligent concept helps avoid the suction hose coming into contact with the ground.
- Protects the hose and prevents dirt penetrating the vehicle.
- Hose can be easily replaced.

4 Ergonomic dirt container


- Full use of container volume.
- Can go a long time without emptying.
- Simple and convenient emptying.

CONFIGURATION OPTIONS



		SB VC 2 Ec	SB VC 1 Ec	SB VC 2	SB VC 1
Technical data					
Number of vacuuming bays		2	1	2	1
Air flow rate	I/s	2×60	60	2×74	74
Vacuum	mbar	2×244	244	2×254	254
Dirt container capacity	I	2×36	36	2×36	36
Power input	kW	2×1.38	1.38	2×1.38	1.38
Sound pressure level	dB(A)	65	62	63	60
Power supply	Ph / V / Hz	1 / 230 / 50 / 60	1 / 230 / 50 / 60	1 / 230 / 50 / 60	1 / 230 / 50 / 60
Dimensions (L x W x H)	mm	600 × 1220 × 2200	600 × 850 × 2200	600 × 1220 × 2200	600 × 850 × 2200





Thanks to the customisable and simple programming concept, you can collect different coins and tokens with a single coin acceptor.



Digital remaining time display in seconds

Shows your customers the remaining vacuuming time precisely to the



Custom colour

The half shells are available in all standard RAL colours – precisely to match your requirements.



Long-life Ec turbine

Our brushless DC motor outperforms traditional technology thanks to low wear and consequently a significantly longer service life.





Minimum use, maximum profit

Make more from your site and increase customer frequency and turnover with our versatile forecourt units - compact, quick to install and extremely easy to use. A very easy way to extend your product range and increase customer satisfaction at the same time.









1 Air Water Tower AWT

Precise tyre pressure checking and adjustment with water refill option, for example for cleaning windscreens, in a single machine. Also available with integrated frost protection on request.

3 Perfume Tower PT

Immediately neutralises unpleasant odours in the vehicle, such as cigarette

2 Air Tower AT

748

For precise tyre pressure checking and adjustment - also available with integrated frost protection on request.

4 Mat Cleaner SB F M80

The machine for cleaning mats without water. Also available with a storage area for temporarily storing mats during the cleaning process.

		AWT-C Fp	AWT-C	AWT Fp	AWT
Technical data					
Power input	kW	0.45	0.45	0.45	0.45
Protection class	IP	44	44	44	44
Power supply	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50	1 / 230 / 50	1 / 230 / 50
Dimensions (L × W × H)	mm	423 × 423 × 1550	423 × 423 × 1550	423 × 423 × 1550	423 × 423 × 1550
Equipment					
Frost protection			-		-
Calibration*		•		-	-
Order no.		1.534-913.0	1.534-912.0	1.534-903.0	1.534-902.0
		AT-C Fp	AT-C	AT Fp	AT
Technical data					
Power input	kW	0.45	0.45	0.45	0.45
Protection class	IP	44	44	44	44
Power supply	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50	1 / 230 / 50	1 / 230 / 50
Dimensions (L × W × H)	mm	423 × 423 × 1550	423 × 423 × 1550	423 × 423 × 1550	423 × 423 × 1550
Dimensions (L × W × H)	mm	423 × 423 × 1550	423 × 423 × 1550	423 × 423 × 1550	423 × 42

		PT Fp	PT
Technical data			
Power input	kW	0.30	0.30
Protection class	IP	44	44
Power supply	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50
Dimensions (L × W × H)	mm	423 × 423 × 1550	423 × 423 × 1550
Equipment			
Frost protection		•	-
Order no.		1.534-909.0	1.534-908.0

1.534-910.0

1.534-901.0

1.534-900.0

749

1.534-911.0

		SB F M80 S	SB F M80	SB F M80 3 S	SB F M80 3	SB F M80 Sm S	SB F M80 Sm
Technical data							
Power input	kW	0.40	0.40	0.40	0.40	0.40	0.40
Protection class	IP	44	44	44	44	44	44
Power supply	Ph / V / Hz	1 / 230 / 50	1 / 230 / 50	3 / 400 / 50	3 / 400 / 50	1 / 230 / 50	1 / 230 / 50
Dimensions (L × W × H)	mm	1511×531×1071	1097×531×1071	1511×531×1071	1097×531×1071	1511×531×1071	1097×531×107
Equipment							
Storage compartment			-	•	-	•	-
Electronic coin acceptor		•	•	•	•	-	-
Start button		-	-	-	-		
Order no.		1.534-905.0	1.534-904.0	1.534-907.0	1.534-906.0	1.534-915.0	1.534-914.0
Accessories							
Dirt container							
Order no.		4.070-351.0	4.070-351.0	4.070-351.0	4.070-351.0	4.070-351.0	4.070-351.0
■ Included in the scope of supp	ly. □ Optional acc	essories. * Please	check whether a cali	ibrated machine is re	equired according to	legislation in the co	untry of use.

Equipment Frost protection Calibration*

WATER RECLAMATION - ENVIRONMENTALLY-FRIENDLY AND ECONOMICAL

The recovery and treatment of dirty water produced in vehicle wash plants and commercial high-pressure cleaning is often prescribed by law. Our reclamation systems not only comply with legal standards and requirements, but also reduce consumption and costs for fresh water and cleaning agents considerably. This means that you save up to 95%.



Table of contents: Water reclamation systems

Water reclamation for vehicle wash plants Page 754
Water reclamation for high-pressure cleaners Page 758
Treatment chemicals for water treatment Page 880



WRB Bio

Thanks to its very high reclamation quota of up to 95%, this compact system is suitable for all vehicle wash plants in car dealerships, workshops, service stations and car care centres that use reclaimed water. The system is highly reliable and delivers high-quality reclaimed water at competitive investment costs.

How to read the unit names:

WRB = Water Reclamation Biology

(Machine for the reduction of biodegradable substances)

Model	Flow performance	Equipment
Example: WRH	1200	Classic
WRP = Water Reclamation Particles (Machine for the reduction of particles) WRH = Water Reclamation Hydrocarbons (Machine for the reduction of oil/hydrocarbons)	Flow performance in litres per hour	Classic = Basic equipment with manual filter return rinse Car Wash = For use in gantry car washes



Kärcher offers a tailor-made water reclamation solution for the use of high-pressure cleaners. Modular standard components are combined to form individual systems, which ensure compliance with required limit values and offer potential savings.




Hydrocyclones or sand filters are used for the removal of suspended matter. For the removal of oil, tried-and-tested methods such as active carbon filters or precipitation/flocculation are used depending on the degree of oil pollution.

WATER RECLAMATION FOR VEHICLE WASH PLANTS



85% water saving. 100% cleanliness

This Kärcher system is designed for fast and thorough cleaning of vehicles, from cars to lorries and coaches. With the reduction in fresh water consumption of up to 85 per cent, Kärcher water reclamation systems can bring about enormous savings.



1 Chemical-free solution

- Low operating costs.
- Robust filtration process.

2 Modular concept

Location-specific and customised solutions.


WRP 16000 WRP 8000 Fresh water savings of up to 85% ■ Fresh water savings of up to 85% Flow of up to 16000 l/h Flow of up to 8000 I/h ■ Easy to install ■ Easy to install Technical data 16000 8000 230 Voltage 230 50 50 Frequency 375 255 Weight 760 × 760 × 1300 610 × 610 × 1100 1.217-152.0 1.217-151.0 Order no. Price

WATER RECLAMATION FOR VEHICLE WASH PLANTS



85% water savings with hydrocyclone

The WRP Car Wash water reclamation system for vehicle wash plants with hydrocyclone has a flow performance of up to 3,000 l/h. The system reduces fresh water consumption by up to 85 per cent.



1 Physical treatment without any maintenance effort

- No filter return rinse necessary.
- No replacement of filter material required.

2 Compact system

- Low space requirement.
- Easy retrofitting option.

WRP Car Wash

- Fresh water savings of up to 85%
- No filter change necessary
- Low operating costs

Technical data		
Reclaimed water production	I/h	3000
Voltage	V	230
Frequency	Hz	50
Weight	kg	39.5
Dimensions (L × W × H)	mm	220 × 603 × 1863
Order no.		1.217-153.0
Price		

BIOLOGICAL WASTE WATER TREATMENT FOR VEHICLE WASHES



Save up to 95% fresh water with WRB Bio

WRB Bio, our biological waste water treatment system, treats the waste water from vehicle wash plants without flocculants or cleavage agents reliably and without harming the environment; it returns crystal-clear reclaim water back to the circuit and thereby helps to save up to 95% fresh water. In addition, the system impresses with an excellent cost/benefit ratio.









1 Very high reclaim water quality

- Best possible water quality with no cloudiness.
- Odourless reclaim water.
- Enables a fresh water saving of up to 95 percent.

3 With type approval

- Maximum reclamation according to Appendix 49 AbwV.
- No oil separator required.

2 Compact design

- Can also be installed in confined areas.
- Pre-existing gravel filters can be retrofitted.
- $\hfill \blacksquare$ Retrofitting without costly earthworks.

4 Biological waste water treatment

- Reliable decomposition of cleaning agents and drying aids.
- Does not use flocculation agents and other chemicals.

TECHNICAL DATA AND EQUIPMENT

		WRB 4000 Bio	WRB 2000 Bio
		Competitive investment costsIdeal for gantry car washesLow maintenance effort	■ Competitive investment costs■ Ideal for gantry car washes■ Low maintenance effort
Technical data			
Reclaimed water production	l/h	4000	2000
Voltage	V	3 × 400	3 × 400
Frequency	Hz	50	50
Weight	kg	400	300
Dimensions (L × W × H)	mm	900 × 600 × 1800	900 × 600 × 1800
Order no.		on request	on request
Price			

Water treatment without chemistry

The chemical-free water reclamation systems WRH 1200 Classic and WRP 1000 Classic supply high-pressure cleaners in continuous operation with recycled water (1,000 l/h) from manual vehicle cleaning.





1 Chemical-free solution


- Low operating costs.
- Supplies high-pressure cleaners directly.
- 2 Backwash filters
- Effective elimination of particles > 5 um.
- Exceptional price/performance ratio.





The solution to oil pollution

The tried-and-tested HDR 777 system is the ideal solution for all washing processes using high-pressure cleaners which produce a high level of oil pollution. The Kärcher HDR 777 treats washing water with an oil content of 30 to 100 mg/l so that it can be reused for washing processes or drained into the sewerage system with the addition of special flocculants.





1 Automatic flocculant dosage

Easy operation and reliable compliance with limits for hydrocarbons.

2 Chemical flocculation

■ Effective removal of oil and pollutants.

WRH 1200 Classic WRP 1000 Classic ■ For oil-free waste water: < 5 mg/l ■ For medium oil content: 5-30 mg/l Fresh water saving of up to 85% ■ Fresh water saving of up to 85% Flow of up to 1200 l/h Flow of up to 1000 l/h Technical data 1200 1000 Voltage 230 Frequency 50 110 45 Weight 1000 × 480 × 1600 660 × 450 × 1100 1.217-111.0 1.217-108.0

HDR 777 HDR 777-VA ■ For high oil content: 30-100 mg/l ■ For high oil content: 30-100 mg/l ■ Fresh water saving of up to 85% Fresh water saving of up to 85% Flow of up to 800 l/h Flow of up to 800 l/h Technical data 600-800 600-800 Reclaimed water production Voltage 230 230 Frequency 50 50 485 485 Weight mm 1300 × 630 × 1300 1300 × 630 × 1300 1.208-102.0 1.208-100.0

USTRIAL

BECAUSE IN INDUSTRY YOU NEED A PARTNER WHO CAN OFFER YOU ADVANTAGES.

In industry, there are a large number of cleaning tasks which are often very specific: machines and systems, moulds and parts, as well as interior and exterior transport routes and storage locations. Each of these areas is very complex. Integrating them into a functioning system of the highest efficiency requires a great deal of expertise and experience. As a world market leader for cleaning technology, we have this expertise and more than 75 years of experience. We have the unique Karcher system. And we have the solution for every one of your tasks. What does that mean for you? All of the advantages.

Increase efficiency with intelligent cleaning management. Increase quality with general cleanliness in all areas. Care and value retention with innovative, gentle and preservative cleaning Maintain industry-specific standards for hygiene and safety and Tailor-made solutions Uninterrupted applications for special production environments parallel to production processes guarantee short downtimes. and with minimal conversion and Critical substances are removed with special applications, without attacking systems. Easy handling of machines for specific requirements. Pure power removes heavy and hardened encrustations - cleaning with **Ecologically responsible** ultra-high pressure. treatment of production residues

WE ALWAYS HAVE ONE SOLUTION MORE THAN YOU HAVE TASKS.

We have everything you need. Even if we are unable to present every solution here. We cover every need in all areas of industry with our industrial vacuums, dry ice blasters, tank interior cleaning systems, high- and ultra high-pressure blasting machines, floor cleaners and sweepers. Simply tell us what you want to clean. We will tell you how it can be done in the most effective and efficient way.















1 Industrial vacuums/extraction systems (Page 329)

For vacuuming

- Metal shavings, granulate, punchings
- Health-endangering or explosive dusts
- Coolants, lubricants and oils

2 Ultra high-pressure solutions (Page 204)

- Concrete restoration and removal
- Cleaning of tubes, pipe bundles and heat exchangers
- All types of surface removal

3 Dry ice blasting systems (Page 778)

Dry ice blasting of

- Robots, moulds and filling systems
- Transport and conveyor systems
- Hydraulic and electrical installations

4 Parts cleaning (Page 790)

Cleaning of parts in

- Metalworking
- Maintenance and production

5 Tank/Silo/Container solutions (Page 768)

Cleaning of

- Tanks and silos
- 20-foot containers
- Rail tank cars
- Trucks

6 System solutions for reactors and boilers (Page 774)

Cleaning of

- Mixing agitators
- IBC and barrels
- Reactors and boilers

7 Stationary systems (Page 182)

Stationary high-pressure cleaning in/on

- Butchers, abattoirs and food production in general
- Swimming pools and thermal baths
- Decks on cruise ships

EVERYTHING FOR A CLEAN INTERIOR

For over 40 years, the name Kärcher has been synonymous with reliable and powerful systems for tank interior cleaning. These cleaning tasks are generally complex and can be very specific. They involve different materials and containers for all types of storage, transport and material handling. Whatever has to be cleaned, we design your Kärcher system solution in detail based on modular components. We accompany you from the consultation and planning stage to construction through to the handover and ongoing maintenance of the machines.



Table of contents: Container cleaning systems

Tank interior cleaning Page 764
Container/Reactor cleaning Page 770
Cleaning agents Page 882



Tank interior cleaning

The principle here is: the container comes "to you", e.g. to your stationary cleaning system. This could be trucks with tanks or silos, ISO containers or tank wagons, i.e. often very big containers. We have a new innovation for you: our new self-driven tank interior cleaning head ICH 80/16 Ps. Superb cleaning performance is achieved with this innovative drive engineering. External drive energy is not required.

Container/Reactor cleaning

The principle here is: "you come to the containers", this means you clean fixed containers such as mixing agitator tanks directly on site.

But you can also clean barrels, IBC and other containers used in the chemical industry. We have a completely new solution for these applications: our HDCI range. These high-pressure pumps are available in 3 basic models for different media: for demineralised water, acids and lyes or solvents.

Each as a stationary or mobile machine and often also as an ATEX version.


How to read the unit names:

Unit type	Flow rate	Working	Motor	Version	Medium	Equipment
		pressure				
Example: HDCI	30	10	-4	Mob	Dw	Ex
HDCI = High-pressure pump for chemical industry	× 100 in I/h	in MPa	-4-pole	Mob = Mobile St = Stationary	<pre>Dw = Demineralised water Ad/Ly = Acid/Lye So = Solvent</pre>	Ex = Explosion protection

Unit type	Flow range	Operating pressure	Drive
Example: ICH	80	16	hp
ICH = Interior cleaning head	× 100 in l/h	in MPa	Ps = Self-powered


SOLUTIONS FOR TANK INTERIOR CLEANING

In a networked industry, transport and logistics play a key role. Not only do the processes have to be coordinated, but the means of transportation must be available and ready for use, irrespective of the goods transported. Cleaning according to specific intervals or whenever required must be effective, fast and reliable. Tank vehicles, wagons, ISO containers, IBC and reusable containers place diverse requirements on machines, accessories and cleaning agents. The Kärcher system, with its perfectly tailored components, is the optimal solution for all cleaning tasks in this sector as well.









1 Tank and silo cleaning

- Interior cleaning of liquids and solids.
- Used in combined transport by rail and road.
- Up to 5 chambers with a volume of 9 to 28 m³ per chamber.
- Reduced use of energy and chemicals thanks to special Kärcher software and innovative chemical application.

2 Cleaning ISO containers

- In combined transport by sea, rail and road.
- Kärcher tailor-made cleaning station with crane track system.
- Special procedure for cleaning latex and synthetic resin.

3 Tank wagon cleaning


- Cleaning of tank wagons for liquids/hazardous products.
- Can be designed as a multi-track system for simultaneous operation.
- Cleaning of rail tankers up to 24 metres in length.
- Sometimes extreme external conditions require intelligent procedures for preheating highly viscous materials.

ITAINER CLEANING

767

CUSTOMISED SOLUTIONS BASED ON IN-HOUSE DEVELOPED MODULES

Kärcher system solutions are designed for container cleaning using modular components. Both custom designs and on-site issues are taken into consideration. One of the main tasks of engineering is choosing efficient components to ensure that energy and operating costs are kept to a minimum. One big advantage is that the components used are developed specifically for cleaning container interiors. Our many years of experience in container interior cleaning influence the product definition. Industrial quality standards are a given. A wide range of modular components ensures an optimal solution for almost any application.



Customer-specific system controllers



Kärcher offers the complete spectrum of customer-specific system controllers. These range from controllers for small systems with simple control logic to large systems with complex cleaning requirements, including a wide variety of options. All processes are controlled as a whole, starting with customer registration and programme selection to communication between the control room and wash area through to quality assurance and documentation.

- Manual cleaning or automatic programme selection and control via PLC.
- Visual depiction of the components that are in
- Validation of the programme parameters such as pressure, temperature, flow and cleaning agent dosing

MODULAR INTERIOR CLEANING HEAD



Withstands everything. Cleans any container

Our innovative self-driven interior cleaning head made from stainless steel has been specially designed for cleaning a wide range of containers, such as silos, 20-foot containers and rail tankers. It has an ATEX certification, is highly-resistant to acids, lyes, solvents and demineralised water, and can be freely configured in terms of flow rate, pressure and speed.





- 1 Constant speed thanks to innovative drive turbine
- For optimum cleaning results.
- Nozzle assembly can be freely selected.
- 2 Self-drive due to volume throughput
- No external power supply required.

ICH 80/16 Ps

- Stainless steel interior cleaning head with ATEX certification
- Innovative liquid spray gearbox
- Freely configurable flow rate, pressure and speed

Technical data		
Flow rate	l/h	2000-8000
Pressure	bar	60-160
Temperature	°C	max. 90
Drive		liquid spray
Tank opening	mm	150
Rotational speed	rpm	12-30
Weight	kg	10
Nozzles	piece(s)	2 / 4
Order no.		1.509-400.2
Price		

Technical data Throughput

Pressure

Temperature

Electric drive

Pneumatic drive

Min. tank opening

Rotation speed

Protection class

Weight

Order no. Price

SELECTION OF MODULAR INTERIOR CLEANING HEADS



50 / 70

10-20

3.631-008.0

har

mm

kg

bar / I/min



HKS 100

200

8-40

3.632-030.0

speed control



HKF 200 E



ICH 140/14 Ps F2

500

170

10-20

2.631-002.0

 Stainless steel interior cleaning head with ATEX certification Adjustable speed with pneumatic drive Variable throughput and pressure PTFE sealing Acid-, lye- and solvent-resistant 	 Stainless steel interior cleaning head with ATEX certification Small size Liquid spray gearbox Adjustable speed Variable throughput and pressure PTFE sealing Acid-, lye- and solvent-resistant 	 Stainless steel interior cleaning head with ATEX certification Constant speed with electric drive Variable throughput and pressure PTFE sealing Acid-, lye- and solvent-resistant 	 Stainless steel interior cleaning head with ATEX certification Rail tanker centre of gravity Liquid spray gearbox Steaming via separate nozzle Increased coverage with folding mechanism Suitable for 4- and 8-axle rail tankers
max. 1500	1200-6000	max. 10000	7200-14000
max. 100	30-100	max. 200	30-140
max. 95	max. 60 (80)	max. 95	max. 95
4-7 / 450	-	-	-
-	-	3 / 400 / 50	-

180 / 200

4.631-002.0

18.5

65

SELECTION OF MODULAR INDUSTRIAL PUMPS



		HDI 30/10	HDI 38/12	HDI 60/10	HDI 60/14
Technical data					
Throughput	l/h	max. 3000	max. 3800	max. 6000	max. 6000
Pressure	bar	max. 100	max. 120	max. 100	max. 140
Temperature	°C	max. 60	max. 60	max. 85	max. 85
Electric drive	Ph/V/Hz/KW	3 / 400 / 50 / 11	3 / 400 / 50 / 15.5	3 / 400 / 50 / 22	3 / 400 / 50 / 30
Weight	kg	190	220	250	275
Order no.		1.509-002.0	1.509-003.0	1.509-006.0	1.509-007.0
Price					

OTHER COMPONENTS: HOT WATER GENERATORS



HWE 4000 Gas modular eco!efficiency

- Optimal cleaning power. The setpoint temperature can be easily and precisely adjusted +/- 2°C

 Diverse applications with flexible flow volumes
- (attachment kit steam, spray lance)
- Long life of the high-pressure pumps as they are operated with cold water as a result of hot water generation on the pressure side
- Small footprint thanks to compact, upright design
- High-quality heating coil made from resistant stainless steel ensures low maintenance costs

Technical data		
Throughput	I/h	1300-8000
Pressure	bar	max. 160
Heat output	kW	420
Temperature	°C	max. 95
Electric drive	V / Hz / kW	1 × 230 / 50 / 0.75
Weight	kg	550

OTHER COMPONENTS: DRYING




Drying with heat exchanger

- Central drying unit with circulating air
- Optimal drying result thanks to high air flow rate
- High-quality materials and components e.g. finned tubes with galvanised fins, corrugated panels in stainless steel
- Suitable for operation with water, steam or thermal oil

Technical data		
Air flow rate	m³/h	4000
Compression	Pa	3800
Drive	V / Hz / kW	3 × 400 / 50 / 7.5
Weight	kg .	150

SOLUTIONS FOR CLEANING IN THE CHEMICAL INDUSTRY

Storage tanks, pipelines and process containers must be emptied completely and cleaned thoroughly at regular intervals; products are often adhesive, caustic, explosive or flammable. There are organic and inorganic base materials as well as numerous intermediate and end products. Such complex tasks require perfectly tailored cleaning systems for maximum effect, safety and efficiency. The Kärcher system has the right solution for individual requirements.









1 Mixing agitators and reactors

- Various sizes and products in the chemical and paint industry.
- Customised solutions, e.g. for paints and solvents.
- Special applications for reactor cleaning.
- Recirculation system for the conservation of valuable resources and protection of the environment.

2 IB containers

- For material transport within company and delivery to customer.
- From food to chemicals.
- $\hfill \blacksquare$ Container capacities from 250 to 3,000 litres in different materials.
- Can be reused multiple times.

3 Barrels / Drums

- Cleaning light containers up to 750 mm in diameter.
- Irrespective of shape.
- Pre-assembled wash bay.
- Easy handling.
- Immediately ready to use.

HDCI RANGE



Multiple versions for optimum container cleaning

High-pressure pumps for stationary or mobile high-pressure supply for container cleaning. The devices available in various versions – right through to ATEX certification – are specially designed for industrial requirements and enable a wide application spectrum. Suitable for use with a wide range of media, such as demineralised water, acids, lyes and solvents.













- 1 Pump sets in various versions
- Ecobrass enables the use of water and solvents.
- Stainless steel (VA) pump set enables the use of acids and lyes.
- 3 Highly versatile
- Enabled by a variety of attachment kits.
- Available as stationary and mobile versions.

- 2 Various operating units are available as an option
- With a monitoring function adapted to the specific application.
- 4 Optional automatic start/stop function
- Using the "Pressure and flow switch" attachment kit.

TECHNICAL DATA AND EQUIPMENT

		HDCI 30/10-4 St Dw HDCI 30/10-4 Mob Dw Ex	HDCI 30/10-4 St Ad/Ly HDCI 30/10-4 Mob Ad/Ly Ex	HDCI 30/5-4 St So Ex HDCI 30/5-4 Mob So Ex	
		 Suitable for use with demineralised water Stationary and mobile versions available The mobile version is also available as an Ex version 	 Suitable for use with acids and lyes Stationary and mobile versions available The mobile version is also available as an Ex version 	 Suitable for use with solvents Stationary and mobile versions available Also available as an Ex version 	
Technical data					
Throughput	l/h	3000	3000	3000	
Max. pressure	bar / MPa	100 / 10	100 / 10	50 / 5	
Temperature	°C	60	60	60	
Electric drive	Ph / V / Hz / kW	3 / 400 / 50 / 11	3 / 400 / 50 / 11	3 / 400 / 50 / 5.5	
Weight	kg	190 / 310	190 / 310	242	
Equipment					

Equipment			
Attachment kit control			
Without control			
Attachment kit motor protection main switch			
Attachment kit E-control cabinet			
Attack mont list game und			
Attachment kit general			
Without attachment kit, general			
Pulsation damper, steel		-	-
Pulsation damper, VA			-
Supply hose			-
Float tank	П		-
Overflow valve			-
Pressure switch	er.	-	
Order no.	1.509-010.0 -011.0	1.509-012.0 -013.0	1.509-014.0 -015.0
Price			

□ Optional.

ICE COLD IN THE FACE OF DIRT - GENTLE ON SURFACES

Many components and machines are difficult to clean: casting moulds, extruders, processing machines in the food and plastics industries, etc. Our powerful dry ice blasters are the right solution when other procedures are not effective, practical or economical. And that is often the case: whenever water and steam cannot be used as cleaning agents due to the risk of corrosion. Or if residues from blasting material such as sand or glass must be avoided. For hygiene reasons or because of sensitive surfaces. Or to avoid time-consuming polishing after cleaning.






Table of contents: Dry ice cleaning

Dry ice cleaners Page 776
Accessories Page 780







1 Advantages of dry ice blasting

Cleaning without disassembling

Machines do not have to be disassembled for cleaning. The pellets easily reach into even the smallest nooks and crannies.

Short machine downtimes

thanks to fast and effective cleaning.

Environmentally friendly cleaning

without additional chemicals or spray agents.

Surfaces are not damaged

No residues

Dry ice sublimates completely to $\mathrm{CO}_{\mathrm{2}}.$ It leaves no residues such as spray agents or wastewater.



2 Cleanliness = cold times acceleration

The Ice Blaster accelerates the dry ice pellets, which are up to 3 millimetres in size, with compressed air to over 150 m/s. At a temperature of -79 °C the dirt freezes and cracks. The dry ice pellets ejected at high speed remove the dirt effortlessly. A highly effective method for removing almost any dirt in a way that is gentle on materials.

3 From carbon dioxide to ice

In the production process, liquid carbon dioxide flows into the press cylinder of the pelletizer and turns to dry ice snow as a result of the pressure drop. A hydraulic cylinder condenses this dry ice snow, which is then pressed by an extruder plate. This creates small rods of dry ice, which then break into pellets.

4 Ice Blasters from Kärcher offer the right solution for every application. The robust design of the machines and reliable technology cannot fail to impress. A host of features, such as residual ice discharge, a cleverly designed protective handle, lockable blasting parameters, integrated water separator and many more, make everyday work significantly easier.

How to read the unit names:

Mode

IB = Ice Blaster

IP = Ice Pelletizer

ICE CI FANING

777

SUPER CLASS



Cleaning performance redefined

The IB 15/120 Ice Blaster is one of the most powerful dry ice blasting machines on the market. Among its outstanding features are its robustness, highly reliable technology and top results in dry ice blasting.



1 Nozzle case holder

- Blasting spray nozzles and tools are always at hand on the machine.
- The nozzle case is attached to the side of the machine to protect it from dirt.

2 Outstanding mobility

- $\hfill \blacksquare$ Optimum balancing of the device for convenient manoeuvring on uneven terrain.
- Bars at the front and rear of the device make it easy to negotiate stairs.

IB 15/120

- Robust and reliable
- Oil and water separator
- For the most intensive jobs

Technical data		
Voltage	V	220-240
Frequency	Hz	50-60
Connection load	kW	0.6
Compressed air connection		Claw coupling (DIN 3238)
Casing/frame		Stainless steel (1.4301)
Cable length	m	7
Air pressure	bar / MPa	2-16 / 0.2-1.6
Air flow	m³/min	2-12
Sound pressure level	dB(A)	125
Dry ice capacity	kg	40
Dry ice pellets (diameter)	mm	3
Dry ice consumption	kg/h	30-120
Weight without accessories	kg	91.5
Dimensions (L × W × H)	mm	720 × 850 × 1100

Equipment	
Flat jet nozzle	1
Round jet nozzle, XL, long	1
Spray hose with electrical control cable and quick coupling	•
"Air only" or "Air and ice" switch on the blasting trigger gun	•
Includes ground strap coil	1
Integrated oil and water separator	1
Order no.	1.574-104.0
Price	
■ Included in the scene of supply	

■ Included in the scope of supply.

MIDDLE CLASS



Highly mobile – for use with in-house compressors

The spray process with dry ice pellets is ideal for gentle cleaning of sensitive surfaces. The compact IB 7/40 for in-house compressed air networks ensures impeccable cleanliness, even at 2 bar.



1 Clear displa

The values in the settings are easy to read and simple to operate thanks to large buttons and electronic controls.

2 Automatic residual ice discharge

■ The ability to empty the residual ice tank at the touch of a button prevents the device from icing up once work is complete.

IB 7/40 Adv

IB 7/40 Classic

		Operation by the trigger gunOil and water separatorFor in-house compressed air networks	Compact and agileOil and water separatorFor in-house compressed air networks
Technical data			
Voltage	V	220-240	220-240
Frequency	Hz	50-60	50-60
Connection load	kW	0.6	0.6
Compressed air connection		Claw coupling (DIN 3238)	Claw coupling (DIN 3238)
Casing/frame		Stainless steel (1.4301)	Stainless steel (1.4301)
Cable length	m	7	7
Air pressure	bar / MPa	2-10 / 0.2-1	2-10 / 0.2-1
Air flow	m³/min	0.5-3.5	0.5-3.5
Sound pressure level	dB(A)	99	99
Dry ice capacity	kg	15	15
Dry ice pellets (diameter)	mm	3	3
Dry ice consumption	kg/h	15-50	15-50
Weight without accessories	kg	70	69
Dimensions (L × W × H)	mm	768 × 510 × 1100	768 × 510 × 1100
Equipment			
Flat jet nozzle		•	•
Round jet nozzle, XL, long		-	-
Spray hose with electrical control cable and quick coupling		•	•
"Air only" or "Air and ice" switch on the blasting trigger gun			-
Includes ground strap coil		•	-
Integrated oil and water separator		•	
Order no.		1.574-002.0	1.574-001.0
Price			


■ Included in the scope of supply.

PELLETIZER



Make your own dry ice

Never buy dry ice pellets again! Thanks to the Kärcher Pelletizer, it is now extremely easy to produce these pellets yourself. This saves waiting time and purchasing and transport costs.



778

1 For time- and cost-saving on-site production of dry ice pellets for cleaning and cooling purposes

2 Extruder plate for creating dry ice pellets with the diameters 1.7 mm, 3 mm or 16 mm

	IP 280		IP 120	IP 55	
		Pellets with the highest densityHydraulically operatedDurable and robust	Pellets with the highest densityHydraulically operatedDurable and robust	Pellets with the highest densityHydraulically operatedDurable and robust	
Technical data					
Production quantity	Production quantity kg/h 28		120	55	
Current type	Ph / V / Hz	3 / 400 / 50	3 / 400 / 50	3 / 400 / 50	
Connection load	kW	5.6	4	1.6	
CO₂ storage tank (liquid phase)		CO₂ storage tank; liquid phase 13-21 bar	CO₂ storage tank; liquid phase 13-21 bar	CO₂ storage tank; liquid phase 13-21 bar	
CO ₂ supply connection		1/2" BSP socket	1/2" BSP socket	1/2" BSP socket	
Weight without accessories	kg	540	360	147	
Dimensions (L × W × H)	mm	1560 × 800 × 1450	1320 × 700 × 1430	1150 × 600 × 1300	
Order no.		On request	1.574-111.0	1.574-110.0	
Price					

Nozzle sizes

		IB 7/40 Air flow rate index/ Nozzle sizes	IB 15/120 Air flow rate ind Nozzle sizes	ex/			
Cleaning performance	Pressure in bar	XS Ø 5	S Ø 6	M Ø 7	L Ø8	XL Ø 9	XXL Ø 10
Very low blasting force For cleaning very light dirt on very sensitive	2	0.4	1.0	0.7	1.0	1.6	1.1
surfaces, e.g. dust from rubber or grease and oil from soft plastics.	3	0.7	1.3	1.1	1.6	2.3	2.0
Low blasting force For cleaning light dirt, e.g. oil and grease, light	4	0.9	1.7	1.7	2.2	3.0	2.8
encrustations, glue residues, separating agents, rubber residues, cleaning of injection moulds.	5	1.1	2.0	2.3	2.9	3.6	3.7
	6	1.3	2.4	2.7	3.5	4.3	4.5
Medium blasting force For cleaning stubborn dirt, e.g. removing rust	7	1.6	2.7	3.1	4.0	5.0	5.0
film or underbody coating, or cleaning welding guns.	8	1.8	3.0	3.6	4.6	5.7	5.9
	9	2.0	3.4	4.0	5.3	6.4	6.7
	10	2.3	3.7	4.5	6.0	6.7	7.5
High blasting force For cleaning very stubborn dirt, e.g. paint re-	11		4.0	5.0	6.5	7.4	8.4
moval, cleaning heat exchangers or die-casting tools.	12		4.4	5.5	7.1	8.2	9.3
	13		4.7	5.9	8.0	8.9	10.3
Very high blasting force For cleaning extremely stubborn dirt, e.g. paint	14		5.1	6.5	8.4	9.6	11.2
removal, cleaning casting tools, cleaning power plant furnaces.	15		5.4	7.0	9.0	10.4	12.0
	16		5.7	7.5	9.7	11.2	12.9
Area performance							

The air consumption is shown in m^3/min in the table.

up to 1 m³/min:	Industrial in-house compressed air supply; entry-level compressor, e.g. Kaeser M 17, CompAir C14
1-2 m³/min:	Industrial in-house compressed air supply; small compressor, e.g. Kaeser M 31, CompAir C20GS
2-3 m³/min:	medium compressor, e.g. Kaeser M 57, CompAir C35
3-5 m³/min:	medium compressor, e.g. Kaeser M 57, CompAir C35
5-7 m³/min:	medium compressor, e.g. Kaeser M 80, CompAir C55
7-10 m³/min:	large compressor, e.g. Kaeser M 122, CompAir C105
> 10 m³/min:	very large compressor, e.g. Kaeser M 250, CompAir C200

DRY ICE CLEANING ACCESSORIES



Special nozzles, lights, protective gear: Kärcher provides accessories for all your needs: flat jet nozzles and round spray nozzles in a long and short version, adjustable miniature angled nozzles for delicate work in tight spaces or round and flat angled nozzles.

























	en en
	20

				3 15/120 3 7/40 Adv 2 37/40 Classic 2 280 120 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
Blasting gun	Order no. Prio	ce Description		= = = = =
Jet gun, XXL, heavy duty	1 4.775-836.0	Ergonomic and light jet gun with safety machine to prevent unintentional triggering. Switch for selecting "air and dry ice" or only "compressed air".	1	•
Jet gun, XXL, Adv	2 4.775-837.0	Ergonomically designed jet gun. The compact design of this gun makes it especially light and handy.	2	
Jet gun, XS, Adv	3 4.775-785.0	Includes a safety function to prevent unintentional triggering. The Advanced jet gun features an integrated remote control. The ice delivery rate and jet pressure can be adjusted directly from the gun. Also includes a switch to choose between "air only" and "air and ice".	3	
Jet gun, XS, classic	4 4.775-794.0	Ergonomically designed jet gun. The compact design of this gun makes it especially light and handy. Includes a safety function to prevent unintentional triggering.	4	
High-pressure spray nozzles				
Flat jet nozzle, 50 mm	5 4.574-033.0	Flat jet nozzle with optimised nozzle geometry. Excellent cleaning results with a high area coverage.	5	
Flat jet nozzle, XXL, 75 mm	6 4.574-054.0	Flat jet nozzle (75 mm jet width) for the Kärcher Ice Blaster. The innovative nozzle geometry ensures an extremely even spray pattern across the entire width during dry ice blasting.	6	
Flat jet nozzle, XXL, 100 mm	7 4.574-056.0	Ice Blaster flat jet nozzle with 100 mm jet width and new geometry. Ideal for dry ice blasting over very large areas. For an extremely even spray pattern across the entire width.	7	
Flat jet nozzle insert, S	8 4.574-031.0	Nozzle insert for regulating air flow.	8	
Flat jet nozzle insert, L	9 4.574-030.0		9	
Flat jet nozzle insert, XXL	10 4.574-032.0		10	
Round spray nozzle, S, long	11 4.574-050.0	Powerful round spray nozzle with an innovative nozzle contour for maximum cleaning performance and very low air consumption. Ideal for stubborn dirt. Air volume index: S.	11	
Round spray nozzle, M, long	12 4.574-048.0	Powerful round spray nozzle with an innovative nozzle contour for maximum cleaning performance and low air consumption. Ideal for stubborn dirt. Air volume index: M.	12	
Round spray nozzle, M, short	13 4.574-028.0	Short, practical round spray nozzle for small areas. Air volume index: M.	13	
Round spray nozzle, L, long	14 4.574-051.0	Powerful round spray nozzle with an innovative nozzle contour for maximum cleaning performance and moderate air consumption. Ideal for stubborn dirt. Air volume index: L.	14	
Round spray nozzle, L, short	15 4.574-029.0	Short, practical round spray nozzle for medium-sized areas. Air volume index: L.	15	
Round spray nozzle, XL, long	16 4.574-049.0	Practical round spray nozzle with innovative nozzle contour for maximum cleaning performance. The optimal solution for stubborn dirt. Air volume index: XL.	16	
Round spray nozzle, XL, extra long	17 4.574-047.0	45 cm round spray nozzle with innovative nozzle contour for maximum cleaning performance. The optimal solution for extremely stubborn dirt. Air volume index: XL.	17	
Low pressure - blasting nozzles				
Flat jet nozzle, XS, short	18 4.574-040.0	Optimised nozzle geometry makes the nozzle particularly efficient and quiet. Very short and compact nozzle. Especially suited for use in small spaces.	18	
Flat jet nozzle, XS, long	19 4.574-038.0	Optimised nozzle geometry makes the nozzle particularly efficient and quiet. Excellent cleaning results with a high area coverage.	19	• •
Round spray nozzle, XS, short	20 4.574-039.0	Optimised nozzle geometry makes the nozzle particularly efficient and quiet. Very short and compact nozzle. Especially suited for use in small spaces.	20	
Round spray nozzle, XS, long	21 4.574-037.0	Optimised nozzle geometry makes the nozzle particularly efficient and quiet. Very powerful for stubborn dirt.	21	
Angled nozzle, XS, flat	22 4.574-042.0	The angled nozzle deflects the spray at a 90° angle. Ideal for cleaning injection moulds.	22	
Angled nozzle, XS, round	23 4.574-041.0		23	
Mini angled nozzle, 60°, XS	24 4.574-044.0	Miniature angled nozzle for tight spaces. Deflects the jet about 60° laterally. Protrudes 57 mm to the side, length: 260 mm. Set consists of 4 parts: $1 \times$ union nut, $1 \times$ extension piece, 100 mm (5.321-971.0) $1 \times$ angle piece, 60° (5.321-972.0) $1 \times$ nozzle tip (5.321-977.0). Any number of extension pieces can be attached. The angle and nozzle tip can be ordered separately.	24	
Mini angled nozzle, 90°, XS	25 4.574-043.0	Miniature angled nozzle for tight spaces. Deflects the jet about 90° laterally. Protrudes 63 mm to the side, length: 240 mm. Set consists of 4 parts: 1 × union nut, 1 × extension piece, 100 mm (5.321-971.0) 1 × angle piece, 90° (5.321-973.0) 1 × nozzle tip (5.321-977.0). Any number of extension pieces can be attached. The angle and nozzle tip can be ordered separately.	25	
Extension, 100 mm	26 5.321-971.0	100 mm extension tube for miniature angled nozzles (60°, 90°, 135°).	26	

■ Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.



						<mark> v</mark>
						20
						15/1/ 7/40 280
		Ouden ne	Duine	Beautistics		
gle, 90°	27	Order no. 5.321-973.0	Price	Description Angle piece, 90°, for all miniature angled nozzles.	27	
gle, 60°	_	5.321-973.0		Angle piece, 50°, for all miniature angled nozzles. Angle piece, 60°, for all miniature angled nozzles.	28	
placement nozzle		5.321-977.0		Nozzle tip for all miniature angled nozzles.	29	
aight adapter for angled nozzle	_	5.321-992.0		Can be attached to all miniature angled nozzles. Converts a miniature angled nozzle to a straight nozzle.	30	
vity nozzle, XS	_	4.574-045.0		Diameter: 22 mm. Any number of extension pieces can be attached.	31	
zzle accessories	31	4.374 043.0		Diameter, 22 mm. Any number of extension pieces can be attached.	J1	
ambler	32	4.574-026.0		The innovative Scrambler, patented by Kärcher, is mounted between the trigger gun and spray nozzle	32	
inibici	52	4.574 020.0		and breaks up the 3 mm dry ice pellets into fine particles. This makes it possible to clean very sensi-	52	
				tive surfaces. There are three pellet breaking force levels.		
uble scrambler	33	4.574-052.0		Additional Scrambler that, together with the standard Scrambler, produces even finer blast particles.	33	
				The Double Scrambler can be fitted onto the standard Scrambler, taking up minimal extra space.		
zzle extension, XXL, 170 mm	34	4.574-027.0		170 mm nozzle extension.	34	
zzle extension, XXL, 500 mm	35	4.574-060.0		500 mm nozzle extension.	35	
zzle extension, XS, 300 mm	36	4.574-046.0		300 mm nozzle extension.	36	
ndle, IB 7/40	37	4.321-248.0		Handle for attachment to nozzle extension (4.574-046.0, 300 mm). For convenient two-handed use.	37	
idle, IB 15/120	38	6.321-206.0		Handle for use with nozzle extension.	38	
zle light, IB 15/120	39	2.815-010.0		Nozzle light is screwed onto the jet gun. For optimum illumination of the spray area.	39	
zle light, IB 7/40	40	2.815-011.0		Nozzle light is screwed onto the jet gun to illuminate the work area.	40	
en-end wrench (size 27 mm)	41	7.815-009.0		Open-end wrench for mounting nozzles (2 required).	41	
ase for nozzle thread, silicone-free	_	6.288-088.0		The thread of the spray nozzles must be regularly treated with this silicone-free grease.	42	
ermediate piece for angled spray		4.574-034.0		Intermediate piece for all available angled spray lances. Can also be used as a flat jet nozzle insert	43	
ces				(14 mm).		
° angled spray lance, XXL	44	4.574-035.0		90° angled spray lance can be combined with all available nozzles. Requires the use of intermediate piece 4.130-425.0.	44	
5° angled spray lance, XXL	45	4.574-036.0		105° angled spray lance can be combined with all available nozzles. Requires the use of intermediate	45	
				piece 4.130-425.0.		
sting hose, compressed air hose						
ray hose, 1/2"	46	4.013-042.0		5 m spray hose with electric control cable and quick couplings, non-marking outer layer, silicone-free (1/2" diameter).	46	= =
ray hose, 3/4"	47	4.013-043.0		8 m spray hose with electric control cable and quick couplings, non-marking outer layer, silicone-free	47	
				(3/4" diameter). Hoses can be extended without additional adapters.		•
se trolley	48	4.574-057.0		Hose reel including all adaptors. This practical tool for dry ice blasting using the Ice Blaster is designed	48	
				for 80 m long compressed air hoses with a diameter of 1".		
mpressed air hose, 1", 5 m	49	6.574-279.0		The compressed air hose (1", 5 m) for the Ice Blaster is very light and keeps its shape. Ideal for	49	
				connecting to the hose reel with the compressor.		
npressed air hose, 1", 20 m	50	6.574-280.0		The compressed air hose (1", 20 m) for the Ice Blaster is very light and keeps its shape. Once the dry	50	
				ice blasting is finished, the hose can be wound up again perfectly on the Kärcher hose reel.		
npressed air hose, 1", 60 m	51	6.574-281.0		The compressed air hose (1", 60 m) for the Ice Blaster is very light and keeps its shape. Once the dry	51	
				ice blasting is finished, the hose can be wound up again perfectly on the Kärcher hose reel.		
npressed air hose, 10 m	_	6.390-284.0		Foldable compressed air hose with inner diameter of 3/4" and length of 10 m.	52	
mpressed air hose, 20 m		6.390-285.0		Foldable compressed air hose with inner diameter of 3/4" and length of 20 m.	53	
		6.667-214.0		100 m roll of hose foil. Protects the spray hose from contamination and damage. If the foil is damaged,	54	

it can easily be replaced.

Included in the scope of supply.
Available accessories. More Kärcher original accessories can be found on the following pages.

DRY ICE CLEANING

DRY ICE CLEANING



















		Order no.	Price	Description		IB 15/120 IB 7/40 Adv IB 7/40 Classic IP 280 IP 120 IP 55
Protective equipment						
Safety goggles	55	6.321-208.0		Safety goggles.	55	
Protective gloves	56	6.321-210.0		Cold-protection glove in size 10 with slip-resistant profile (category 3 in accordance with EN 511, Level 12X EN 388, Level 2121).	56	
Hearing protection	57	6.321-207.0		Effective hearing protection with average noise insulation of 35 dB(A) in accordance with SNR (Single Number Rating).	57	
Mounting kits and other accessories						
Foam insert for case IB 15/120	58	5.365-369.0		Empty foam insert for the transport case with order no. 6.421-355.0. The insert is ready-made with matching spaces for different nozzles for dry ice blasting.	58	
Case for nozzles and accessories	59	6.421-355.0		The storage case for spray nozzles can be easily attached with clips to the rear of the IB 15/120. The height of the nozzle case is 120 mm.	59	
Y adapter, air supply	60	2.641-880.0		Y-adapter for connecting the air hose to two 1/4" quick coupling connections.	60	
Wheel, puncture-proof, 305 × 105	61	6.515-002.0		Puncture-proof, fully foamed wheel with metal rim.	61	
Ground strap coil	62	2.641-741.0		Automatic ground strap coil with about 6 m ground strap and sturdy clamp. The ground strap coil reliably prevents static build-up on the object being blasted and prevents arcing between the object and nozzle.	62	
Shovel	63	4.321-198.0		For filling the Ice Blaster tank with dry ice pellets.	63	
Pelletizer	,	•				
CO ₂ Detector with sensor	64	6.574-278.0		The CO_2 detector indicates the CO_2 concentration in the air. This attachment kit contains a CO_2 detector as well as a CO_2 sensor. Since CO_2 gas is heavier than air, the CO_2 sensor should be installed at the lowest point of the building.	64	
Extruder plate, 3 mm	65	6.574-046.0		High-quality extruder plate for creating 3 mm dry ice pellets.	65	
	66	6.574-061.0			66	
	67	6.574-001.0			67	
Extruder plate, 1.7 mm	68	6.574-200.0		This extruder plate produces dry ice pellets 1.7 mm in diameter.	68	
Extruder plate, 16 mm	69	6.574-060.0		High-quality extruder plate for creating 16 mm dry ice pellets.	69	
	70	6.574-002.0			70	
	71	6.574-045.0			71	
Timer module	72	6.574-181.0		Production control system for automatic filling. The timer module can be used to set the pelletizer to a	72	
	73	6.574-197.0		specific run time. The pelletizer automatically stops dry ice production when the set time has elapsed.	73	
■ Included in the scope of supply.	□ Avai	lable accessories	. More	Kärcher original accessories can be found on the following pages.		

OTC CLEANING

787

KÄRCHER PARTS CLEANERS – EVERY PART PERFECTLY CLEANED

There is no room for compromise when it comes to modern parts cleaning. Kärcher parts cleaners are only made of high-quality materials. Intensive cleaning is carried out with solvent-free, water-based cleaning agents that effortlessly remove grease, oils, and other dirt. Using the correct cleaning agents preserves and protects components longer.



Table of contents: Parts cleaning

Biological parts cleaning	Page	788
Automatic parts cleaning	Page	789
Accessories	Page	790
Cleaning agents	Page	881



1 Parts cleaners – indispensable in industry and commerce

Kärcher parts cleaners are essential to industrial manufacturing and maintenance. They thoroughly and gently clean dirty components and tools before or after processes such as welding and assembly. In vehicle workshops as well as service and maintenance companies: the best solution for cleaning motors, gearbox housings and machine parts. In addition to automatic parts cleaners, Kärcher offers manual biological parts cleaners that take things a step further: specialised microbes biologically degrade the dislodged dirt.




2 Biological parts cleaning – a water-based solution

The cleaning agent used is pH-neutral and dermatologically tested. The cleaning agent works without solvents and is therefore very environmentally friendly. It guarantees consistently high cleaning performance in combination with the microbes. There is no need to completely change and dispose of the cleaning agent. As a result of biological degradation of the contaminants, use of the cleaning agent is theoretically unlimited. All the user needs to do is regularly top up evaporated liquid or liquid that has been used up during the work process.

How to read the unit names:

модеі	diameter	capacity	Machine class	principle
Example: PC	60	130	T	
PC = Parts cleaner	Basket diameter in cm	-	<pre>M2 = Manual, two station T = Top loader</pre>	Bio = Microbe



The biological cleaning process under the microscope:

organic substances are biologically broken down into carbon dioxide and water through the use of a water-based cleaning agent and microbes.

RTS CLEANING

789

BIOLOGICAL PARTS CLEANING



Parts cleaner for industrial and commercial use

Thorough and eco-friendly: biological parts cleaners made of impact resistant plastic, are suitable for cleaning tools, motor components and other parts contaminated with oil or grease up to a weight of 100 kg.



1 Convenient, safe and economical

High-quality, hard-wearing and long-lasting materials guarantee a long service life.

2 Replaceable filter mat

Cleanliness guaranteed: for the filtration of fine particles up to 50 μm and releasing fresh microbes.

PC 100 M2 Bio

■ Washstand, large rinsing basin

■ 1 tap, 2 brushes, 2 drains

Technical data		
Pressure	bar / MPa	0.3 / 0.03
Flow rate	I/h	900
Connection load	kW	1
Working area	mm	1041 × 660
Casing/frame		HDPE - Plastic
Max. temperature	°C	40
Load capacity	kg	100
Tank capacity	1	80
Weight	kg	44
Dimensions (D × W × H)	mm	952 × 1181 × 1067
Voltage	V	220-240

Equipment	
Brush (pervaded with cleaning agent)	•
Тар	
Water level control	1
Order no.	1.626-722.0
Price	
= to deal of the construction	

■ Included in the scope of supply.

AUTOMATIC PARTS CLEANING



Effective and reliable

Production, maintenance, workshop, metal processing – automatic parts cleaners are very versatile. The parts cleaners work on the basis of aqueous solutions without solvents.



Technical data



1 Automatic parts cleaners

Robust and high-quality: all stainless steel design; with three-dimensional nozzle system for excellent cleaning results.

2 Detergent

For light or stubborn dirt: Kärcher always has the right cleaning agent.

PC 60/130 T

Fully automatic parts cleaning

■ Motor-driven rotary disc

Three-dimensional nozzle system

recilifical data		
Pressure	bar / MPa	1.5 / 0.15
Flow rate	I/h	4500
Connection load	kW	5.5
Working diameter	mm	600
Usable height	mm	310
Casing/frame		Stainless steel (1.4301)
Max. temperature	°C	80
Adjustable cleaning time	min	1-30
Load capacity	kg	130
Tank capacity	I	100
Weight	kg	165
Dimensions (D × W × H)	mm	1080 × 1000 × 1250
Equipment		
Elapsed time counter		•
Retainer ring (stainless steel, for rotary disc)		
Small parts cage with cover (stainless steel)		-
Oil separator		-
Timer for cleaning cycle		
Water level control		
Order no.		1.626-704.0
Drice		

■ Included in the scope of supply.

RTS CLEANING

PARTS CLEANER ACCESSORIES



Kärcher offers high-quality accessories to extend the uses of parts cleaners. Kärcher also offers spare parts for service, maintenance and other uses. This increases the efficiency and useful life of the machines

















	Order no. Pric	te Description		PC 100 M2 Bio
Parts cleaner				
Filter mat with microbes, 1-ply	1 6.626-041.0	The filter mat filters out dirt particles up to 50 µm. When the machine is initially filled, the microbes contained in the filter mat are washed into the tank and activated. The filter mat must be replaced every 4 to 8 weeks depending on the degree of contamination.	1	
Filter mat with microbes, 3-ply	2 6.626-042.0	The filter mat filters out dirt particles up to 50 µm. When the machine is initially filled, the microbes contained in the filter mat are washed into the tank and activated. The multi-layer filter mat has three fleece layers. This means that the soiled layer on top can be removed after 1 to 2 weeks, leaving the next clean fleece layer underneath.	2	
Flow-through brush, long hose	3 6.626-039.0	The brush is soaked in cleaning agent and used to remove dirt from parts. It has an extra-long hose.	3	
Flow-through brush, angled	4 6.626-040.0	The angled cleaning brush is used to remove dirt from parts and can even get into tiny corners.	4	
Roller cart	5 6.626-043.0	A trolley increases the flexibility of the machine by making it mobile.	5	
Two-channel timer	6 6.631-551.0	Two-channel timer for fully automatic control of the heating system and oil separator of the parts cleaner. The heating system and oil separator can be programmed separately from each other for each day of the week.	6	
Oil separator (skimmer) attachment kit	7 2.642-465.0	The oil separator (skimmer) considerably extends the useful life of the cleaning fluid. The oil in the cleaning fluid floats to the top when not in use, e.g. at night. The skimmer can then be used to remove this oil from the cleaning fluid.	7	
Filtration attachment kit (250 μ)	8 2.642-193.0	The filter is mounted between the pump and the nozzles. The filter casing and sieve are made of high-grade stainless steel.	8	
Small parts cage	9 6.626-086.0	Small parts cage.	9	
Replacement filter sieve	10 6.626-081.0	Replacement filter sieve.	10	


[■] Included in the scope of supply.

Available accessories. More Kärcher original accessories can be found on the following pages.

CLEANING DAILY - CLEANING EFFICIENTLY

Even with modern, efficient cleaning machines, manual cleaning remains a common practice in daily maintenance cleaning. Surfaces can be quickly and affordably cleaned by hand in places that machines cannot reach. And with the unparalleled precision and touch of the human hand. As the world's leading provider of cleaning technology, we are continuously expanding our range of professional and highquality manual cleaning tools. Innovative cleaning and system solutions that you need and want.






792

Floors	Page	794
Surfaces	Page	810
Cleaning and transport trolleys	Page	818
Vindows	Page	826
leaning agents	Page	840







1 Complete range

The Kärcher system offers a complete product range of cleaning machines, cleaning agents and manual tools.

2 Numerous colours - a single cleaning objective

Our manual tools can be sorted into areas of use according to their colour codes, thus avoiding cross-contamination.

3 Perfect ergonomics and feel


The height, handle shape and handling of our manual cleaning equipment are designed so that the user needs minimal effort to operate them.

4 Effective and efficient

Because our handles and attachments are all standardised and compatible with each other, you save on spare parts since you can use tools you already have.

FLOOR CLEANING - DOUBLY EFFECTIVE

You can clean floors with one of two fundamentally different methods: dry or wet. Which one you choose will depend on the type of flooring you have and how dirty it is. We can provide you with multifunctional, effective tools for any task and textiles with any kind of fibre and fibre structure. For the best manual floor cleaning at Kärcher standards.









1 The daily hard surface cleaner

- Cleans all sensitive areas, wiped surfaces and hard surfaces.
- The efficient mop press makes for light work.
- 2 separate, colour-coded 15-litre buckets for optimal hygiene.

2 Quick and easy

- Much lighter than a bucket.
- Fast emptying and filling.
- Cleaning agent is dispensed at the push of a button.

3 Environmentally friendly

- Eco-friendly, with less waste.
- No more bending, mop clamps automatically in place.
- Improved hygiene, no contact with dirt and cleaning agents.

MANUAL CLEANIN

SWEEPING

Dustpan with rubber profile with sweeping ECO!Broom and waste Litter picker 100 cm slide container Brush set universal Description For picking up coarse dirt The sweep-collect system, con- Ideal for working with one conveniently. sisting of a sweeping slide and hand: the very lightweight dustpan with an ergonomic ECO!Broom features a waste handle and rubber profile, is container for removing coarse perfect for removing coarse and dirt and a squeegee which wet dirt. adapts to the ground conditions. 100 32 × 15 × 96 28 × 29 × 85 35 × 22 × 7 Dimensions (L × W × H) cm Quantity 6.999-191.0 6.999-226.0 3.337-614.0 6.999-113.0

SWEEPING AND SCRAPING

		Broom PVC 35 cm	Broom PVC 60 cm	Window and floor scraper, 120 cm long, with blade	Scraper with long handle and blade
Description		In combination with aluminium handle 6.999-115.0 and aluminium telescopic handle 6.999-100.0.	In combination with wooden handle 6.999-117.0.	With 120 cm handle for easy operation, with protective cover for increased safety.	For removing chewing gum, paint residue and coarse dirt on smooth surfaces.
Dimensions (L × W × H) cn	n	35	60	120 × 10	32 × 10.5
Quantity pi	ece(s)	1	1	1	1
PU		10	10	10	25
Order no.		6.999-114.0	6.999-116.0	3.345-154.0	6.999-127.0
Price					

DUST BINDING - DUST MOP COVERS

		Cotton dust mop 60 cm	Cotton dust mop 80 cm	Cotton dust mop 120 cm	Cotton dust mop 160 cm
				CALL	- Andrews
Description		100% cotton. For dry mopping medium-sized surfaces. For dust mop holder 6.999-092.0.	100% cotton. For dry mopping large surfaces. For dust mop holder 6.999-093.0.	100% cotton. For dry mopping large surfaces. For dust mop holder 6.999-108.0.	Dust mop made from 100% cotton. With 160 cm diameter, suitable for dry dusting in large areas, e.g. in gyms. Washable up to 60 °C. For dust mop holder 6.999-243.0.
Dimensions (L × W × H)	cm	60 × 13	80 × 13	120 × 13	160 × 13
Quantity	piece(s)	1	1	1	-
PU		30	30	15	-
Order no.		6.999-090.0	6.999-091.0	6.999-110.0	6.999-242.0
Price					

DUST BINDING - DUST MOP COVERS

		Acrylic dust mop 60 cm	Acrylic dust mop 80 cm
Description		For dry mopping medium-sized surfaces. For dust mop holder 6.999-092.0.	For dry mopping large surfaces. For dust mop holder 6.999-093.0.
Dimensions (L × W × H)	cm	60 × 13	80 × 13
Quantity	piece(s)	1	1
PU		30	30
Order no		6,000,140,0	6,000,140,0

DUST BINDING - HOLDERS

		Dust mop holder 60 cm	Dust mop holder 80 cm	Rigid dust mop holder 120 cm	Dust mop holder, fixed 160 cm
					NEW
Description		In combination with aluminium handle 6.999-096.0 or tele–scopic handle 6.999-111.0. For dust mop 6.999-090.0 and 6.999-148.0.	In combination with aluminium handle 6.999-096.0 or tele–scopic handle 6.999-111.0. For dust mop 6.999-091.0 and 6.999-149.0.	In combination with aluminium handle 6.999-096.0 or tele–scopic handle 6.999-111.0.	Fixed holder for dust mop, 160 centimetres long. Suitable for use with aluminium handle 6.999-096.0 or telescopic handle 6.999-111.0.
Dimensions (L × W × H)	cm	60 × 9	80 × 9	120 × 9	160 × 9
Quantity	piece(s)	1	1	1	1
PU		30	30	10	10
Order no.		6.999-092.0	6.999-093.0	6.999-108.0	6.999-243.0
Price					

DUST BINDING - HOLDERS

Ho	lder with squeegees	Holder with squeegees		
40	cm	60 cm	Duster ECO 540	Pad sole, corrugated



Description		Structured slat holder (40 cm) for daily maintenance cleaning with dust binding cloths 3.337-999.0, 3.338-003.0, 3.338-004.0 and 3.338-006.0. With fixing system for convenient application.	Very hygienic, easy-to-sterilise slat holder (60 cm) for daily maintenance cleaning with dust binding cloths 3.337-999.0, 3.338-003.0, 3.338-004.0 and 3.338-006.0.	For perfect dusting with the corresponding dust binding cloths.	For duster ECO 540.
Dimensions (L × W × H)	cm	40 × 11	60 × 11	58 × 10	58 × 10
Quantity	piece(s)	1	1	1	1
PU		1	1	20	10
Order no.		6.999-057.0	6.999-152.0	3.335-752.0	3.335-856.0
Price					

DUST BINDING - DUST BINDING CLOTHS

		Dust binding cloth neolinn BASIC	Dust binding cloth neolinn CLASSIC	Dust binding cloth roll neolinn CLASSIC	Dust binding cloth neolinn ECO
		To the second se			Attopunium kus torganium musu 2
Description		Oil-impregnated disposable cloth for all smooth floor coverings.	Disposable cloth with special adh coverings, surfaces and objects.	nesive for all smooth floor	Oil-impregnated disposable cloth for all smooth floor coverings.
Dimensions (L × W × H)	cm	60 × 30	60 × 26	32 × 20	60 × 24
Quantity	piece(s)	50	25	900	1000
PU		8	18	1	1
Order no.		3.337-999.0	3.338-004.0	3.338-003.0	3.338-006.0
Price					

WET CLEANING

Pad holder, hand	Pad holder with joint	Pad, white	Pad, green
	1		
	-		

Description	For cleaning corners and edges that machines cannot reach. For white pad 6.999-102.0 and green pad 6.999-103.0.	For cleaning corners and edges that machines cannot reach. For white pad 6.999-102.0 and green pad 6.999-103.0 In combination with aluminium handle 6.999-096.0 or telescopic handle 6.999-111.0.	For cleaning corners and edges that machines cannot reach. For hand pad holder 6.999-101.0 and pad holder with joint 6.999-158.0.	
Dimensions (L × W × H) cm	23 × 10	23 × 10	24.5 × 12 × 2	24.5 × 12 × 2
Quantity piece(s)	1	1	1	1
PU	12	12	12	12
Order no.	6.999-101.0	6.999-158.0	6.999-102.0	6.999-103.0
Price				

MANUAL CLEANING EOUIPMENT

WET CLEANING - WATER SQUEEGEE

Rubber squeegee 55 cm



Description		Plastic water squeegee.
Dimensions (L × W × H)	cm	55
Quantity	piece(s)	1
PU		10
Order no.		6.999-089.0
Price		

WET CLEANING - MOP COVERS FLAP SYSTEM

	Microfibre mop,		Microfibre mop,
Cotton mop	short fibre	Microfibre mop, loop	short fibre, abrasive









WET CLEANING - MOP COVERS POCKET SYSTEM

Microfibre mop, Microfibre mop, short fibre, abrasive short fibre ECO!Mop set, red ECO!Mop set, blue



Description		Microfibres and PP fibres for more abrasive cleaning power. Perfect for non-slip tiles. Pocket attachment.	Microfibre, short fibre. Pocket attachment.	Microfibre loop mop for excellent dirt pick-up. Pocket attachment.	
Dimensions (L × W × H)	cm	40 × 13	40 × 13	40 × 13	40 × 13
Quantity	piece(s)	1	1	1	1
PU		25	25	25	25
Order no.		6.999-131.0	6.999-132.0	6.999-136.0	6.999-143.0
Price					

WET CLEANING - MOP COVERS POCKET SYSTEM

Basic cotton mop Basic microfibre mop short fiber 50 cm mop press 15 l

Quantity PU Order no.	piece(s)	1 50 3.337-959.0	1 50 3.337-957.0	1 25 6.999-277.0	1 1 6.999-227.0
Dimensions (L × W × H)		40 × 13	40 × 13	50 × 13	46 × 32 × 36
Description		With pocket and flap, as well as loops on the inside and fringes outside.	With pocket and flap, as well as abrasive strips for more effective dirt removal.	Colour-coded short-fibre mi- crofibre mop (50 cm) with bag for efficient cleaning. Washable up to 90 °C, dryer up to max. 45 °C.	15-litre bucket with carrying handle and a mop roller press that can be operated using a foot pedal on the bucket. The simple system is perfect for cleaning small surfaces.

WET CLEANING - MOP CLOTH VELCRO SYSTEM

Microfibre velcro cover, abrasive, 40 cm NEW NEW NEW Cotton velcro cover, 40 cm NEW

Description		Microfibre velcro cover, abrasive, 40 cm, with velcro fastening. Developed especially for cleaning safety tiles, where abrasive cleaning power is desired.	Microfibre velcro cover with impressive cleaning and dirt absorption capacities for efficient cleaning. With velcro fastening, 40 cm wide.	Cotton velcro cover with excellent water absorption capacity. 40 cm wide and with velcro fastening.
Dimensions (L × W × H)	cm	40 × 13	40 × 13	40 × 13
Quantity	piece(s)	1	1	1
PU		25	25	25
Order no.		6.999-273.0	6.999-274.0	6.999-275.0
Price				

WET CLEANING - MOP HOLDERS

Mop holder, flaps, 40 cm	Mop holder with clip, 40 cm

Description		In combination with aluminium handle 6.999-096.0 or telescopic handle 6.999-111.0.		
Dimensions (L × W × H)	cm	40 × 11	40 × 11	
Quantity	piece(s)	1	1	
PU		10	10	
Order no.		6.999-098.0	6.999-144.0	
Price				

WET CLEANING - MOP HOLDERS

		Mop holder with clip 50 cm	Velcro holder 40 cm	Velcro holder with block system 40 cm
		NEW	NEW	NEW
		CI 75		
Description		Mop holder with 360° rotation and pocket for rapid change. With back-friendly clip attachment. Suitable for aluminium handle 6.999-096.0 or telescopic handle 6.999-111.0.	High-quality plastic velcro holder in 40 cm width. Simple and quick to use.	High-quality plastic velcro holder with block system for fast and easy use.
Dimensions (L × W × H)	cm	50 × 11	40 × 9.5	40 × 9.5
Quantity	piece(s)	1	1	1
PU		10	10	10
Order no.		6.999-276.0	6.999-271.0	6.999-272.0

WET CLEANING - MOP SYSTEMS

		ECO!Mop system, 97-184 cm	Mop system	ECO!Spray mop system
Description		Mop holder including telescopic handle. Thanks to the pocket attachment, mops can be switched quickly and easily. In addition, mops are fastened with a clip, so there is no need to bend down. Locking option on the universal joint, making it ideal for vertical cleaning tasks.	Includes mop holder, 140 cm aluminium handle and mop clip.	Spray mop system with 0.66-litre bottle and spray unit. The cleaning solution is sprayed directly onto the mop and ensures fast and ergonomic cleaning of small areas
Dimensions (L × W × H)	cm	40 × 184	40 × 140	40 × 155
Quantity	piece(s)	1	1	1
PU		1	1	1
Order no.		5.999-024.0	6.999-145.0	5.999-045.0
Price				

804

ANUAL CLEANING

WET CLEANING - WARNING SIGNS

WET CLEANING - WARNING SIGNS



WET CLEANING - WARNING SIGNS

		Chain barrier, 1 m	Warning sign for door	Door stop with handle
		1	STOP	
Description		Yellow chain barrier made from polypropylene. Length: 1 metre.	Hanging sign "STOP - no access" with suction cup.	Ergonomic universal door stopper with rubber edge and aluminium handle. Suitable for any type of door.
Dimensions (L \times W \times H)	cm	100	50 × 30	15.7 × 7.9 × 90
Quantity	piece(s)	1	1	1
PU		10	10	6
Order no.		6.999-185.0	6.999-229.0	6.999-206.0
Price				

HANDLES

Aluminium handle 140 cm / D 23 mm

Telescopic handle 97-184 cm



Order no.		100 6.999-096.0	10 6.999-111.0
Quantity	piece(s)	1	1
Dimensions (L × W × H)	cm	140	184
Description		For all mop holders and rubber squeegees.	

HANDLES

Aluminium telescopic handle	Aluminium handle with thread	Wooden handle 140 cm
2 × 150 cm	140 cm	D 25 mm



Description		Long aluminium handle for use with broom 6.999-114.0 and scraper 6.999-126.0.	For broom 6.999-114.0.	In combination with broom 6.999-116.0.
Dimensions (L \times W \times H)	cm	300	140	140
Quantity	piece(s)	1	1	1
PU		10	25	20
Order no.		6.999-100.0	6.999-115.0	6.999-117.0
Price				

ACCESSORIES FOR CLEANING FLOORS















		Order no.	Number of units	PU	Description	Price
Designation						
Red replacement bottle, 650 ml	1	6.999-166.0	1	1	Red replacement bottle with 650 ml filling capacity for spray mop with order no. 5.999-045.0.	
Green replacement bottle, 650 ml	2	6.999-167.0	1	1	Green replacement bottle with 650 ml filling capacity for spray mop with order no. 5.999-045.0.	
Blue replacement bottle, 650 ml	3	6.999-168.0	1	1	Blue replacement bottle with 650 ml filling capacity for spray mop with order no. 5.999-045.0.	
Yellow replacement bottle, 650 ml	4	6.999-169.0	1	1	Yellow replacement bottle with 650 ml filling capacity for spray mop with order no. 5.999-045.0.	
Grey replacement bottle, 650 ml	5	6.999-170.0	1	1	Grey replacement bottle with 650 ml filling capacity for spray mop with order no. 5.999-045.0.	
Replacement blades for scraper	6	6.999-076.0	25	10	For scraper, short handle 6.999-126.0 and scraper, long handle, 25 cm, with order number: 6.999-127.0.	
Universal handle holder	7	6.999-270. 0 ■	1	50	Holder for different handle diameters. No slipping along the handle thanks to special rubber coating. Stays at the handle and not at the trolley.	

[■] NEW More Kärcher original accessories can be found on the following pages.

5 ·


COMBINATIONS







Handle - holder



Handle - attachment

	200	THE REAL PROPERTY.	and the same
	6.999-126.0	6.999-114.0	6.999-116.0
 6.999-100.0	•	•	
 6.999-115.0		•	
6.999-117.0			•
		•	•

Mop cover - holder

		The state of the s	The second	- LANGE	1	-	1
		6.999-276.0	6.999-144.0	6.999-098.0	6.999-271.0 6.999-272.0	l .	3.335-752.0
6.	.999-277.0	•					
3	.337-959.0		•				
3.	.337-957.0		•				
6.	.999-136.0		•				
6.	.999-143.0		•				
6.	.999-131.0		•				
6.	.999-132.0		•				
6.	.999-146.0		•				
6.	.999-147.0		•				
6.	.999-094.0			•			
6.	.999-097.0			•			
6.	.999-095.0			•			
6.	.999-099.0			•			
- 6.	.999-273.0				•		
6.	.999-274.0				•		
6.	.999-275.0				•		
3	.335-856.0						•
3.	.337-999.0					•	•
<u> </u>	.338-004.0					•	•
3.	.338-003.0					•	•
3	.338-006.0					•	•
			_		,		•

							The same of
		6.999-092.0	6.999-093.0	6.999-108.0	6.999-243.0	6.999-119.0	6.999-158.0 6.999-101.0
-	6.999-090.0	•					
	6.999-091.0		•				
	6.999-148.0	•					
	6.999-149.0		•				
	6.999-110.0			•			
-	6.999-242.0				•		
	6.999-118.0					•	
	6.999-142.0					•	
	6.999-102.0						•
	6.999-103.0						•


CLEAN SURFACES SUPER EASILY

Our perfect textiles and tools adapted to any need take the challenge out of cleaning surfaces. They remove the dirt quickly and effectively with higher cleaning performance. Our range is sorted according to the three main types of cleaning: dry, wet and glass cleaning. This will help you make the right choice of product to save time and effort in any area.









1 Colour-coded cloths

With our colour coding method you can correctly assign and identify each cloth to each area to be cleaned, without the risk of mix-ups. This will give you the right cloth for each area of application.

2 Dimensionally stable and temperature-resistant

The shape of our cloths remains stable even at high temperatures and over many wash cycles. This allows you to reduce the number of bacteria, thus increasing hygiene. And thanks to their high quality, the cloth continues to feel good to the touch even after many wash cycles.

3 Easy and effective wet cleaning

Our cloths' high water absorption allows for great wet cleaning and means they pick up more dirt, which is useful for various different applications. So you will easily achieve the perfect cleaning performance.

SCRAPING

Scraper with short Replacement blades Replacement blades handle and blade for scraper, glass for scraper 25× Glass scraper Description For removing chewing gum, Ideal for cleaning glass or other Replacement blade set for glass Pack of 25 replacement blades. paint residue and coarse dirt on smooth glass surfaces. scraper 6.999-156.0. Suitable for the scraper with short handle (6.999-126.0) and long handle (6.999-127.0). 10

100

6.999-157.0

25

10

6.999-254.0

9.5 × 5

6.999-156.0

50

DUST BINDING

Dimensions (L × W × H) cm


Quantity

Order no.

24 × 10.5

6.999-126.0

25



DUST BINDING - DUST BINDING CLOTHS

		Dust binding cloth neolinn CLASSIC	Dust binding cloth roll neolinn CLASSIC
		of the sales	
Description		Disposable cloth with special adhesive for all smooth floor co	verings, surfaces and objects.
Dimensions (L × W × H)	cm	60 × 26	32 × 20
Quantity	piece(s)	25	900
PU		18	1
Order no.		3.338-004.0	3.338-003.0

DAMP AND WET CLEANING - CLEANING CLOTHS

		Premium microfibre cloth, red	Premium microfibre cloth, blue	Premium microfibre cloth, yellow	Premium microfibre cloth, green
Description		Knitted microfibre cloth with im	pressive dirt pick-up.		
Dimensions (L × W × H)	cm	40 × 40	40 × 40	40 × 40	40 × 40
DITTIETISTOTIS (L × W × H)		10	10	10	10
Quantity	piece(s)				
	piece(s)	20	20	20	20
Quantity	piece(s)	20 3.338-272.0	20 3.338-274.0	20 3.338-276.0	20 3.338-278.0

DAMP AND WET CLEANING - CLEANING CLOTHS

Velour microfibre Velour microfibre Velour microfibre **Velour microfibre** cloth, red cloth, blue cloth, yellow cloth, green



Price					
Order no.		3.338-264.0	3.338-266.0	3.338-268.0	3.338-270.0
PU		20	20	20	20
Quantity	piece(s)	10	10	10	10
Dimensions (L \times W \times H)	cm	40 × 40	40 × 40	40 × 40	40 × 40
Description		Voven silk velour cloth with high cleaning performance.			

DAMP AND WET CLEANING - CLEANING CLOTHS

Microspun microfibre Microspun microfibre Microspun microfibre cloth, red cloth, blue cloth, yellow cloth, green









Order no.		3.338-247.0	3.338-248.0	3.338-249.0	3.338-250.0	
PU		10	10	10	10	
Quantity	piece(s)	10	10	10	10	
Dimensions (L × W × H)	cm	38 × 37.5	38 × 37.5	38 × 37.5	38 × 37.5	
Description		Fine microfibre cloth with high cleaning performance.				

DAMP AND WET CLEANING - CLEANING CLOTHS

Multi-purpose cloth, red	Multi-purpose cloth, blue	Multi-purpose cloth, yellow	Multi-purpose cloth, green



Description		Jniversal cleaning cloth for daily work.			
Dimensions (L × W × H)	cm	40 × 40	40 × 40	-	-
Quantity	piece(s)	10	10	10	10
PU		10	10	10	10
Order no.		3.338-260.0	3.338-261.0	3.338-262.0	3.338-263.0
Price					

FEUCHT- UND NASSREINIGUNG - GLAS

Hand pad holder, Microfibre cover for Microfibre cover, glass, for hand pad holder velcro fastener 30 cm hand pad holder Microfibre cloth, glass



SANITARY

WC Set, white



Order no.		3.345-543.0
PU		10
Quantity	piece(s)	1
Dimensions (L \times W \times H)	cm	39 × 12 × 12
Description		WC Drusii iiici. Į


COMBINATIONS







Covers and blades - holders




MANUAL CL EQUIPMENT

819

ALWAYS YOUR TROLLEY

We put together each of our robust cleaning trolleys individually according to their area of use. That means you will always have the right trolley to comfortably and professionally store the equipment you need. Your Kärcher trolley offers extensive storage capabilities and a colour-coded bucket system for various different uses. You can also expand your cleaning trolley with modules or reduce its size, adapting it perfectly to your needs.











1 Everything on board

- 3 drawers for storing all required utensils.
- 3 colour-coded buckets for different applications.
- The foldable and robust rubbish bag holder further extends the storage capabilities.

2 Integrated floor cleaning system

- Floor cleaning equipment is integrated in the trolley.
- Various wiping systems are possible.
- Pre-conditioned mops or bucket method the choice is yours.

3 Safe waste disposal

- Simple, ergonomic rubbish disposal.
- $\hfill \blacksquare$ Robustness is the highest priority and is guaranteed.

4 Complete surface cleaning system

- Buckets are on board for wet surface cleaning.
- Storage area for cloths and cleaning agents.
- Everything is nicely stored and readily to hand.

MANUAL CLEAN

CLEANING TROLLEY - PREMIUM

Trolley Trolley Trolley Trolley ECO!Clean Liner Press ECO!Clean Liner ECO!Clean Liner Mini **ECO!First Liner** Description With double bucket mop press, Compact, flexible, ergonomic, Fast wet cleaning system with Corrosion-resistant cleaning covered 150 I bin liner holder robust and corrosion-resistant pre-conditioning and covered trolley made from 100% polyand closable drawer compartcleaning trolley made from propylene. Perfect for quick and 100% polypropylene. With easy maintenance cleaning. practical storage options for Protected bin liner holder, can easy handling. Protected bin be operated using the foot liner holder, can be operated pedal. using the foot pedal. Dimensions (L × W × H) cm 140 × 65 × 110 108 × 53 × 115 84 × 60 × 109 66 × 52 × 110 Quantity 6.999-162.0 5.999-021.0 6.999-165.0 5.999-019.0 Order no.

CLEANING TROLLEY - PREMIUM

Price

820

Trolley Clean Liner Classic I



Description		Ergonomic, corrosion-resistant cleaning trolley made from 100% polypropylene. With two colour-coded 15-litre buckets and user-friendly universal press, fold-up bin liner holder, three colour-coded buckets and three drawers in different sizes.
Dimensions (L \times W \times H)	cm	128 × 65 × 110
Quantity	piece(s)	1
PU		1
Order no.		5.999-044.0
Price		

CLEANING TROLLEY - CLASSIC

Trolley Clean Liner

		Classic II	Classic III	Classic IV	Trolley Classic I
Description		With double bucket roller mop press and bin liner holder. For mop with flaps.	With double bucket mop press and bin liner holder.	Fast wet cleaning system with pre-conditioning and bin liner holder.	Ideal for quick maintenance cleaning: cleaning trolley with two colour-coded 4-litre buckets.
Dimensions (L × W × H)	cm	92 × 65 × 110	92 × 65 × 110	78 × 58 × 109	107 × 66 × 112
Quantity	piece(s)	1	1	1	1
PU		1	1	1	1
Order no.		6.999-080.0	6.999-163.0	6.999-164.0	6.999-216.0
Price					

Trolley Clean Liner

Trolley Clean Liner


CLEANING TROLLEY - CLASSIC

	Cleaning trolley with user- friendly mop press and two colour-coded 4-litre and 15-litre buckets.	Generous storage space included: cleaning trolley with four colour-coded 4-litre buckets, mop press and a removable double bucket cart.	With mop press for flexible application: cleaning trolley with generous storage space and four 4-litre and two 15-litre buckets. All buckets are colourcoded.	Cleaning trolley with generous storage space for precondition ing. Includes two 20-litre mop boxes and four colour-coded 4-litre buckets.
m	107 × 66 × 112	140 × 65 × 112	135 × 65 × 112	114 × 52 × 112
iece(s)	1	1	1	1
	1	1	1	1
	6.999-217.0	6.999-218.0	6.999-219.0	6.999-220.0
		friendly mop press and two colour-coded 4-litre and 15-litre buckets. m 107 × 66 × 112 iece(s) 1	friendly mop press and two colour-coded 4-litre and 15-litre buckets. m 107 × 66 × 112 140 × 65 × 112 1 1 1 1	friendly mop press and two colour-coded 4-litre and 15-litre buckets. mop press and a removable double bucket cart. m 107 × 66 × 112 140 × 65 × 112 1 1 cleaning trolley with four colour-coded 4-litre buckets, mop press and a removable double bucket cart. 140 × 65 × 112 150 × 65 × 112 160 × 112 170 × 11

MOBILE BUCKET CART



MOBILE BUCKET CART AND CLEANING BUCKET





822

		6	0	
Description		Single mobile bucket made from high- quality plastic, corrosion-resistant and very mobile. With "U" sliding handle, mop press and a blue 25-litre bucket.	Very mobile, corrosion-resistant single mobile bucket made from high-quality plastic with side sliding handle. With a blue 25-litre bucket and user-friendly mop press.	15-litre bucket with carrying handle and a mop roller press that can be operated using a foot pedal on the bucket. The simple system is perfect for cleaning small surfaces.
Dimensions (L × W × H)	cm	62 × 43 × 91	53 × 43 × 93	46 × 32 × 36
Quantity	piece(s)	1	1	1
PU		1	1	1
Order no.		6.999-208.0	6.999-210.0	6.999-227.0

TRANSPORT CART - PREMIUM

		Trolley Hotel Premium I	Trolley Hotel Premium II
Description		High-quality hotel cart for 6 to 8 rooms. Includes fold-up 120-litre bin liner holder and thanks to the 125 mm wheels with bumpers, it is easy to manoeuvre, even with a heavy load.	125 mm wheels with bumpers enable easy manoeuvrability of this hotel cart with bin liner holder (120 litres), even with a heavy load. Suitable for 10 to 12 rooms.
Dimensions (L × W × H)	cm	113 × 64 × 142.5	197 × 64 × 142.5
Quantity	piece(s)	1	1
PU		1	1
Order no.		6.999-224.0	6.999-225.0
Price			

TRANSPORT CART - CLASSIC

		Trolley Hotel Classic I	Trolley Hotel Classic II	Trolley Hotel Classic III
Description		Hotel cart with fold-up 120-litre bin liner	Suitable for cleaning 15 to 18 rooms: hotel	A fold-up, 120-litre bin liner holder is in-
- cocpo		holder. The cart is suitable for 12 to 15	cart with fold-up 120-litre bin liner holder,	cluded in the basic equipment of the hote cart for 10 to 12 rooms. It also features
		rooms and features three wooden shelves and five 125 mm wheels.	three wooden shelves and five 125 mm wheels.	three wooden shelves and five 125 mm wheels.
Dimensions (L × W × H)	cm			three wooden shelves and five 125 mm
Dimensions (L × W × H) Quantity	cm piece(s)	and five 125 mm wheels.	wheels.	three wooden shelves and five 125 mm wheels.
		and five 125 mm wheels. $117 \times 53 \times 128$	wheels. 127 × 53 × 128	three wooden shelves and five 125 mm wheels. $107 \times 53 \times 128$
Quantity		and five 125 mm wheels. 117 × 53 × 128 1	wheels. 127 × 53 × 128 1	three wooden shelves and five 125 mm wheels. $107 \times 53 \times 128$ 1

ACCESSORIES























		Order no.	Number of units	PU	Description	Price
Designation		order no.	or ornes	1.0	Description .	Titee
ECO!First Liner Console	1	5.999-020.0	1	1	In combination with ECO!First Liner Trolley 5,999-019.0. Additional space for cleaning equipment.	
Bucket, yellow (4 l)	2	5.999-049.0	1	1	Yellow 4-litre bucket with colour-coded cleaning system.	
Bucket, red (4 l)	3	5.999-050.0	1	1	Red 4-litre bucket with colour-coded cleaning system.	
Bucket, blue (4 I)	4	5.999-051.0	1	1	Blue 4-litre bucket with colour-coded cleaning system.	
Bucket, green (4 I)	5	6.999-186.0	1	1	Green 4-litre bucket with colour-coded cleaning system.	
Hinged lid for bucket (4 l)	6	6.999-187.0	1	1	Replacement hinged lid for our colour-coded 4-litre buckets with order nos. 5.999-049.0, 5.999-050.0, 5.999-051.0 and 6.999-186.0.	
Accessories holder, double bucket cart	7	6.999-077.0	1	10	In combination with double bucket cart 6.999-025.0. For additional equipment or bottles.	
Blue laundry net with strap (50 l)	8	6.999-128.0	1	10	For storage and for gentle washing of used mops in the washing machine. In blue. Capacity: 50 l.	
Red laundry net with strap (20 l)	9	6.999-129.0	1	10	For storage and for gentle washing of used mops in the washing machine. In red. Capacity: 20 I.	
White laundry net with strap (70 l)	10	6.999-130.0	1	10	For storage and for gentle washing of used mops in the washing machine. In neutral white. Capacity: 70 l.	
Mop box blue with lid (10 l)	11	6.999-199.0	1	1	Blue mop box with 10 I volume, for preconditioning mop cloths. Available in combination with Premium cleaning trolley 5.999-021.0, 6.999-164.0 and 6.999-165.0, 6.999-190.0.	
Mop box red with lid (10 l)	12	6.999-200.0	1	1	For pre-conditioning mop cloth: red mop box with a volume of 10 l. Available in combination with our ECO!Clean Liner cleaning trolley, order no. 5.999-021.0.	
Roller press	13	6.999-195.0	1	1	Replacement roller press for cleaning trolley 6.999-080.0 and mobile bucket cart 6.999-021.0.	
Mop press	14	6.999-196.0	1	1	Mop press (spare part). Suitable for the Premium and Classic cleaning trolleys and for mobile bucket carts.	
Mop rest	15	6.999-192.0	1	1	Rest for mop holder. Suitable for all cleaning trolleys and the Classic transport trolley.	
PVC bin liner with zipper, red (120 l)	16	6.999-160.0	1	1	Plastic bin liner. May be used for Clean Liner Classic Trolleys.	
PVC bin liner with zipper, blue (120 l)	17	6.999-161.0	1	1	Plastic bin liner. May be used for Clean Liner Classic Trolleys.	
PVC bin liner with zipper (120 l)	18	6.999-228.0	1	1	Plastic bin liner. Suitable for all transport and cleaning trolleys.	
Drawer with key (40 l)	19	6.999-177.0	1	1	40-litre replacement drawer with key for Premium cleaning trolley.	
Drawer with key (22 I)	20	6.999-176.0	1	1	22-litre replacement drawer with key for Premium cleaning trolley.	
Drawer with key (10 l)	21	6.999-204.0	1	1	10-litre replacement drawer with key for Premium cleaning trolley.	

More Kärcher original accessories can be found on the following pages.

ACCESSORIES





























			Number			
Parlamentaria		Order no.	of units	PU	Description	Price
Designation	١.	l =	L	Ι.	la company of the com	
Foldable rubbish bag holder	1	5.999-048.0	1	1	Space-saving, foldable rubbish bag holder as an additional accessory for our Clean Liner Trolleys 6.999-080.0, 5.999-044.0, 6.999-163.0, 6.999-164.0 and 6.999-190.0.	
Mop box, blue, 20 I	2	5.999-052.0	1	1	Blue mop box for pre-conditioning mops.	
Mop box, red, 20 I	3	5.999-053.0	1	1	Red mop box for pre-conditioning mops.	
Mop box holder	4	5.999-054.0	1	1	The holder for mop box models 6.999-052.0 and 6.999-053.0 for pre-conditioning mops can be attached to the cleaning trolley with the order no. 6.999-021.0.	
Handle for double bucket cart with press	5	6.999-180.0	1	1	The ergonomic handle is a practical addition to our single and double bucket carts (6.999-210.0, 6.999-209.0, 6.999-207.0, 6.999-209.0 and 6.999-025.0).	
Bucket, 15 I, red	6	6.999-172.0	1	1	Red 15-litre bucket with colour-coded cleaning system.	
Bucket, 15 I, blue	7	6.999-173.0	1	1	Blue 15-litre bucket with colour-coded cleaning system.	
Yellow Clean Liner Classic lid	8	6.999-174.0	1	1	Additional yellow rubbish bin lid for our rubbish bag holders 6.999-080.0, 5.999-044.0, 6.999-163.0, 6.999-164.0 and 6.999-190.0 and for all Clean Liner Classic models.	
Mop box lid (for 10 l and 20 l buckets)	9	6.999-175.0	1	1	Additional accessories for the mop box on our rubbish bag holders: mop box lid to cover 5-litre buckets. Reliably protects cleaning fleet and cloth against the ingress of dirt.	
Wheel, 80 mm	10	6.999-182.0	1	1	80-mm wheel, suitable for rubbish bag holders 6.999-025.0, 6.999-207.0, 6.999-208.0, 6.999-210.0, 6.999-209.0 and 6.999-021.0.	
Wheel, 100 mm	11	6.999-183.0	1	1	100-mm wheel, suitable for rubbish bag holders 6.999-080.0, 5.999-019.0, 5.999-021.0, 5.999-044.0, 6.999-162.0, 6.999-164.0, 6.999-165.0, 6.999-224.0 and 6.999-225.0.	
Rubber wheel, 125 mm	12	6.999-184.0	1	1	Rubber wheel with 125 mm diameter for improving stability under load and reducing roller noise of many models in the Trolley Clean Liner range.	
Trolley wheel, rigid, 150 mm	13	6.999-203.0	1	1	150-mm wheel with special fixture for rubbish bag holders 5,999-019.0, 5,999-044.0, 6,999-162.0, 6,999-164.0, 6,999-165.0, 6,999-221.0, 6,999-222.0, 6,999-223.0, 6,999-224.0, 6,999-225.0.	
Grey rubbish bag holder	14	6.999-235.0	1	1	Rubbish bag holder as an addition to our single and double bucket carts with a waste collection segment (6.999-210.0, 6.999-209.0, 6.999-207.0, 6.999-209.0 and 6.999-025.0).	
"U" sliding handle	15	6.999-213.0	1	1	Ergonomic U-shaped sliding handle for transporting our single and double bucket carts easily (6.999-210.0, 6.999-209.0, 6.999-207.0, 6.999-209.0 and 6.999-025.0).	
Cover plate, yellow ECO!First Liner and ECO!Clean Liner	16	5.999-033.0	1	1	Colour-coded yellow rubbish bin lid to expand the equipment available for our rubbish bag holders 5.999-019.0, 5.999-021.0, 6.999-162.0 and 6.999-165.0.	
Separating strip ECO!Trolley	17	5.999-035.0	1	1	Practical separation for rubbish bags. Ideal for fastening multiple mop racks or rubbish bags to the trolley. Suitable for product nos. 5.999-019.0 and 5.999-021.0	
Accessories kit for ECO!Liner	18	5.999-025.0	1	1	Suitable for all cleaning trolleys: ECO!Liner accessories kit with bucket for pre-conditioning mops, mop box holder pan, as well as a hook and rubbish bag separator.	

More Kärcher original accessories can be found on the following pages.

CLEAN TO A SHINE WITH VISION

We have developed multifunctional tools for cleaning glass, façades and buildings that combine ergonomic design, reliable connection systems and safe, effortless work. This tried-and-tested professional quality delivers perfect and streak-free cleaning results without exception, while offering an efficient solution that helps you to reduce your use of water, energy and cleaning agents.











1 Gentle scraper

Our scraper allows you to remove stubborn or dried-on dirt easily and quickly.

2 Washing made easy

Our washing squeegee has an ergonomic, non-slip handle, meaning you can always apply your cleaning agent solution perfectly.

3 Simple removal

The quickly detachable handle is adjustable and easy to change, allowing you to clean thoroughly and without streaks.





4 Streak-free drying

The high-quality textiles we use are absorbent and clean without leaving streaks behind.

5 All-in-one, always to hand

Professionally complement your equipment with our all-in-one solution.

Work faster and more flexibly with your equipment always quickly to hand.

WINDOW SCRAPERS

Window and floor Window and floor Bionic window scraper, scraper, 25 cm long, scraper, 120 cm long, Glass scraper 10 cm, with blade with blade with blade



Description	Ideal for cleaning glass or other smooth glass surfaces.	Ergonomic handle, large scraper surface, secure and sturdy, perfect for using with the telescopic lance.	More power thanks to the 25 cm handle, with protective cover for increased safety.	With 120 cm handle for easy operation, with protective cover for increased safety.
Dimensions (L × W × H) cm	9.5 × 5	10	25 × 10	120 × 10
Quantity piece(s)	1	1	1	1
PU	50	10	10	10
Order no.	6.999-156.0	3.345-151.0	3.345-153.0	3.345-154.0
Price				

WASHERS

White Star washer	White Star washer	White Star washer







Order no.		3.345-497.0	3.345-128.0	3.345-129.0
PU		10	10	10
Quantity	piece(s)	1	1	1
Dimensions (L × W × H)	cm	25	35	45
Description				

WASHERS

 Blue Star washer	Blue Star washer	Blue Star washer

Description Blended fabric made from PES a			es, long-pile, high water absorption and dirt pic	k-up.
Dimensions (L × W × H)	cm	25	35	45
Quantity	piece(s)	1	1	1
PU		10	10	10
Order no.		3.345-498.0	3.345-130.0	3.345-131.0
Price				

WASHERS

Microfibre washer	Microfibre washer	Microfibre washer

Description Microfibre cleaning cloth with high water absorption and powerful cleaning action.				
Dimensions (L × W × H)	cm	25	35	45
Quantity	piece(s)	1	1	1
PU		10	10	10
Order no.		3.345-499.0	3.345-132.0	3.345-133.0
Price				

WASHERS



Description		Blended fabric made from high-quality fibres, short-pile with additional pad surface.		
Dimensions (L × W × H)	cm	35	45	
Quantity	piece(s)	1	1	
PU		10	10	
Order no.		3.345-134.0	3.345-135.0	
Price				

T-BEAMS

 Aluminium T-beam	Aluminium T-beam	Aluminium T-beam	Bionic T-beam, movable
T	T	T	1
-	-	-	8

Description					Flexible, handle is individually adjustable by 45°, rests securely in the hand and provides reliable support when using the telescopic lance.
Dimensions (L × W × H) cm		25	35	45	35
Quantity pie	ce(s)	1	1	1	1
PU		10	10	10	10
Order no.		3.345-500.0 3.345-136.0 3.345-137.0		3.345-138.0	
Price					

T-BEAMS

 Bionic T-beam, movable	Bionic T-beam	Bionic T-beam
1		
	8	8

Price				
Order no.		3.345-139.0	3.345-140.0	3.345-141.0
PU		10	10	10
Quantity	piece(s)	1	1	1
Dimensions (L \times W \times H)	cm	45	35	45
Description Flexible, handle is individually adjustable by 45°, rests securely in the hand and provides reliable support when using the telescopic lance.		Ergonomic shape, secure hold, perfect for use with the telescopic lance.		

WINDOW WIPER HANDLES

3.345-142.0

		Bionic quick-release handle	Bionic wiper handle, movable	Soft grip wiper handle
Description		Ergonomic shape, secure hold, fast and easy rail replacement.	Ergonomic shape, 180° adjustable working angle, robust design.	Soft grip design for easy handling, easy rail replacement.
Dimensions (L × W × H)	cm	15.5 × 10 × 4	20 × 8.5 × 3	14 × 9 × 3
Quantity	piece(s)	1	1	1
PU		15	20	20

3.345-143.0

3.345-144.0

WIPER RAILS



Description	Professional rail made from stainless steel with V cut-out, adjustable rail position.				
Dimensions (L × W × H)	cm	25	35	45	55
Quantity	piece(s)	1	1	1	1
PU		25	25	25	25
Order no.		3.345-145.0	3.345-146.0	3.345-147.0	3.345-148.0
Price					

WASH BRUSHES

832

	Wash brush, soft	Wash brush, hard	Adapter for brush
Description	With soft synthetic bristles and brass thread.	With hard synthetic bristles and brass thread.	Suitable for all standard brushes.

Description		With soft synthetic bristles and brass thread.	With hard synthetic bristles and brass thread.	Suitable for all standard brushes.
Dimensions (L × W × H)	cm	30	30	4.5 × 2.5 × 2.5
Quantity	piece(s)	1	1	1
PU		1	1	1
Order no.		3.345-181.0	3.345-182.0	3.345-163.0
Price				

BELT AND HOLSTER

		Holster	Belt for holster
Description		Ideal for working on a ladder, suitable for window wipers and washers.	Fits holster.
Dimensions (L \times W \times H)	cm	41 × 9.5 × 10	90 × 0.5 × 6
Quantity	piece(s)	1	1
PU		5	5
Order no		3 3/15-171 0	3 3/15-172 0

BUCKETS AND ACCESSORIES

		Bucket 22 I	Lid	Stainless steel strainer	Replacement rollers
Description		Rectangular bucket for 45 cm washers.	For 22-litre bucket.		
Dimensions (L \times W \times H)	cm	48 × 24 × 24	54 × 27.5 × 2.5	42 × 10 × 11.5	8.5 × 5.5 × 4.5
Quantity	piece(s)	1	1	1	4
PU		6	1	1	1
Order no.		3.345-173.0	3.345-174.0	3.345-175.0	3.345-176.0
Price					

WATER SQUEEGEES

Water squeegee, rein- Water squeegee for forced, oil-resistant Squeegee, reinforced Squeegee, reinforced hygienic areas



Description				Oil-resistant for difficult tasks, dries floors streak-free.	For hygienic areas, dries floors streak-free.
Dimensions (L × W × H)	cm	55	75	55	55
Quantity	piece(s)	1	1	1	1
PU		10	10	10	10
Order no.		3.345-177.0	3.345-178.0	3.345-179.0	3.345-380.0
Price					

DRYING

Media chamois



Description		Perfect quality for cleaning glass surfaces, rectangular.
Dimensions (L × W × H)	cm	70 × 45
Quantity	piece(s)	1
PU		10
Order no.		3.345-184.0
Price		

WINDOW CLEANING KIT

Glass and window cleaning kit



Description		Kit for special applications, full range of basic equipment with sturdy nylon bag.
Dimensions (L × W × H)	cm	131 × 22 × 4
Quantity	piece(s)	1
PU		5
Order no.		3.345-187.0
Price		

ACCESSORIES - BRUSHES


Bionic wall brush, oval Bionic pipe brush, curved





Description		Ergonomic handle for cleaning round surfaces and pipes.	Ergonomic handle for cleaning walls and rough surfaces.
Dimensions (L × W × H)	cm	40 × 20 × 12	32 × 27 × 9
Quantity	piece(s)	1	1
PU		1	1
Order no.		3.345-159.0	3.345-160.0
Price			

ACCESSORIES - HOLDERS



REPLACEMENT WIPER RUBBERS

 Replacement wiper rubber, hard	Replacement wiper rubber, soft
0	


Description		Special shape, very reliable and durable.	
Dimensions (L × W × H)	cm	92	92
Quantity	piece(s)	1	1
PU		10	10
Order no.		3.345-149.0	3.345-150.0
Price			

BLADE HOLDERS AND REPLACEMENT BLADES

	Replacement blades	Blade holder	Replacement blades
Description	For Bionic window scraper, 10 cm long.	Loose blade holder, made from stainless steel.	For blade holder, 10 cm long.
Dimensions (L × W × H) cm	10	10	10
Quantity piece(s)	10	1	25
PU	10	25	10
Order no.	3.345-152.0	3.337-550.0	3.337-996.0

COMBINATIONS


Window cleaning



Window wiping

	3.345-145.0	3.345-146.0	3.345-147.0	3.345-148.0
3.345-142.0	•	•	•	
3.345-143.0	•	•	•	•
3.345-144.0	•	•	•	•
3.345-149.0	•	•	•	•
3.345-150.0	•	•	•	•
	3.345-144.0 3.345-144.0 3.345-149.0	3.345-142.0	3.345-142.0	3.345-142.0

Handles



Wash brushes

		1		/		/	1
		3.345-181.0	3.345-182.0	3.345-177.0	3.345-178.0	3.345-179.0	3.345-380.0
-	3.345-163.0						•
	3.345-164.0	•					
	3.345-180.0			•	•	•	•

NOTHING LESS THAN THE BEST FOR YOU

For optimal cleaning results, the system being used – consisting of machine and cleaning agent – must work perfectly. We recognised this very early on and have consistently relied on our own research and development. We develop our cleaning and care agents specifically for use with Kärcher cleaning machines. This means that you can get the most out of your system's performance capabilities. And you can be sure that you are always getting the maximum possible effectiveness, efficiency and reliability.





Table of contents: cleaning and care agents

Cleaning and care agents and disinfection for high pressure	Page	842
Cleaning and care agents for carpets and upholstery	Page	850
Cleaning agents for surfaces	Page	854
Cleaning agents for wash rooms	Page	860
Cleaning and care agents, and disinfection, for hard and resilient floors	Page	866
Cleaning and care agents for vehicles	Page	874
Freatment chemicals for water treatment	Page	880
Cleaning agents for industrial parts	Page	881
Cleaning agents for container/deposit cleaning	Page	882

RESEARCHED, DEVELOPED AND MANUFACTURED FOR YOU

Kärcher cleaning and care agents are just as versatile and powerful as the machines in which they are used - because they are specially developed for use with Kärcher cleaning machines. Only in this way can the performance of the system, consisting of machine and cleaning agent, be fully utilised. Kärcher recognised this early on and has consistently relied on its own research and development. It is the foundation of our success and the core of our thoughts and actions.





1 Benchmark for cleanliness

Research and development are becoming increasingly important as demands and requirements increase, not just for the machines themselves, but for the overall package. How can the full potential be realised and at the same time the environmental impact be reduced? How can costs be reduced without compromising on power or quality? Questions to which Kärcher is seeking the best possible answers in collaboration with experts from various fields of technology and chemistry. With an interdisciplinary approach and also in close cooperation with suppliers and professional operators. Our experts analyse every type of dirt on all surfaces so that they can be professionally removed, picked up and disposed of, Right from the very start, the products that we develop are systematic in every sense of the word. And they are developed entirely at Kärcher. The high performance and efficiency of Kärcher cleaning agents is the result of over 30 years of research and development in our own laboratory. As the world's leading manufacturer of cleaning machines, we pursued the path to becoming a system provider early on and today have expertise and technology that set standards.

2 In-house production

As a system provider of cleaning solutions, Kärcher not only develops cleaning agent formulas for use in Kärcher cleaning machines, but also produces these cleaning products itself. The in-house production of cleaning agents is a key aspect that allows us to offer our customers products with consistently high quality and the best delivery capacity, and at the same time to reduce the environmental impact of unnecessary transportation.


PressurePro - FULL POWER WITH A SYSTEM

The advantages speak for themselves: faster and improved cleaning with low energy consumption and less waste water pollution.

Kärcher cleaning and care agents deliver brilliant performance in industry, trade and the food industry. High-pressure cleaners and cleaning agents perfectly balanced.













1 Stable under high pressures and temperatures

Kärcher cleaning and care agents are specially formulated for use with high-pressure cleaners. Special formulas that remain stable under high pressure and demonstrate their effectiveness. Temperature-stable up to 150°C for safe use in hot water high-pressure cleaners.

2 Precise and reliable dosing

SwitchChem, the integrated cleaning agent dosing system, allows precise and reliable dosing, quick and easy opening and closing as well as cleaning agent dosing control. No more inconvenient manual dosing. No overdosing. Changing between different cleaning agents can take place quickly without wasting unused cleaning agent. This saves costs. At the same time, the tank stays clean and free from microbial load through cleaning agent residue.

Protection and care for high efficiency and long service life of the machine

The optional high-pressure system care offers continuous, precisely dosed and reliable protection against limescale (PressurePro Machine Protector Advance 1 RM 110) and corrosion (PressurePro Machine Protector Advance 2 RM 111). Integrated care components ensure constant maximum high-pressure cleaner power and extend the total product life.

4 Calcification protection

Where hot water high-pressure cleaners are used in hard water areas, Kärcher high-pressure cleaning agents reliably protect all parts in contact with water against calcification. As a result, the full heating coil power is maintained with optimal heat transfer and water flow rate. No trace of limescale in the machine and on the cleaned surface. Success: perfect power and cleaning results and a longer machine service life.

5 Corrosion protection

Kärcher cleaning agents not only clean highly effectively, but also protect and care for the cleaning machine. When using soft water, special corrosion protection components provide reliable protection against corrosion and black water. This ensures constant maximum performance of the cleaning machine and cleaning agent.

Product	A	tivity				Soilin	g				App	licati	on ar	rea					Pro	pert	ies	Page
	Dva-ripaning	1	Foam cleaning	Disinfection	Care, protection, preservation	Oil, grease, soot, emission contamination, wax, excrement, food residues, protein, insect residue	Smoke resin, sugar glaze	Limescale, rust, urine/milkstone, cement, salt deposits	Graffiti, moss, lichen	Bacteria, fungi, viruses	Agriculture	Vehicles	Vehicle parts (e.g. engine)	Food industry, kitchens, sanitary	Industrial components	Solar	Façades	Cleaning machines	ASF (easily separable in oil separators)	IHO listing	VAH/DGHM listing	
PressurePro Oil and Grease Cleaner Extra RM 31		•				•					•								~			844
PressurePro Oil and Grease Cleaner Extra RM 31 ecolefficiency		-				•					•		•	•					-			844
PressurePro Active Cleaner, alkaline RM 81						•													V			844
PressurePro Active Cleaner, alkaline RM 81 ecolefficiency		•				•					•	•		•					~			844
PressurePro Foam Cleaner RM 838						•						•										844
PressurePro Wax Remover RM 36		•				•						•										844
VehiclePro Rim Cleaner, acidic RM 800								•											V			844
VehiclePro Rim Cleaner, alkaline RM 801 Classic		•				•						•										844
VehiclePro Prewash RM 803 Classic		ı										•							~			844
PressurePro Active Cleaner, powder RM 80						•						•							V			845
PressurePro Car Shampoo, powder RM 22						•						•							V			845
PressurePro Hot Wax RM 41					•						•	•										845
VehiclePro Spray Wax RM 821 Classic					•							•										845
PressurePro Foam Cleaner, neutral RM 57			•			•								•				Ш	~		Ш	845
PressurePro Foam Cleaner, alkaline RM 58			•			•								•					~			845
PressurePro Foam Cleaner, acidic RM 59			•					•						•					~		Ш	845
PressurePro Grease and Protein Remover RM 731	4					•															Ш	845
Disinfectant Cleaner RM 732	4	•	_	•		•								•						~		846
Disinfectant Cleaner, foaming RM 734			•	•		•								•								846
Disinfectant RM 735		-		•				_						•						~	~	846
PressurePro Active Cleaner, acidic RM 25	\parallel							•											~			846
PressurePro Intensive Deep Cleaner RM 750	+	-	-			-	_							•					~			846
PressurePro Smoke Resin Remover RM 33	-	•	-								_			-					~			847
PressurePro Foam Cleaner, alkaline RM 91 Agri PressurePro Soaking Agent, alkaline RM 92 Agri			•								i										H	847
						•															\vdash	847
PressurePro Surface Cleaner, acidic RM 93 Agri PressurePro Active Cleaner, neutral RM 55		H						-			-								V			847
Blasting Abrasive, fine	+	-												-								847
Blasting Abrasive, rine Blasting Abrasive, coarse																	i					847
PressurePro Façade Cleaner, gel RM 43	+	-							-													847
PressurePro Solar Cleaner RM 99																						847
PartsPro Cleaner RM 39						-													V		П	848
PressurePro Phosphating Agent RM 48					•										•				V			848
PressurePro Descaling Acid RM 101		•						•										•	V			848
	\dashv																		V			848
PressurePro Machine Protector RM 110								_														
PressurePro Machine Protector RM 110 PressurePro Machine Protector Advance 1 RM 110	╢																	•	V		П	848

■ NEW ■ usable □ usable subject to conditions

	Product description	Application	Primary mixture	Dosage	Properties	Packaging size	PU	Order no./ quantity	Price
rehicle	PressurePro Oil and Grease Cleaner Extra RM 31 Highly concentrated high-pressure deep cleaning agent. At all temperature rang- es, highly efficient lifting off the most stubborn dirt, such as oil, grease, tar, soot and smoke resin.	High-pressure cleaner Spray units	1+3	1.5-10 % 25 %	alkaline pH: 13	2.5	1 1 1	6.295-584.0 6.295-068.0 6.295-069.0 6.295-422.0 6.295-072.0	
	PressurePro Oil and Grease Cleaner Extra RM 31 ecolefficiency Highly concentrated deep cleaning agent for high-pressure cleaning. Effectively removes stubborn dirt, e.g. oil, grease, soot and smoke resin at all temperatures. With the ecolefficiency formulation, particularly economical, effective and environmentally friendly.	High-pressure cleaner (80 °C) High-pressure cleaner (60 °C) Spray units ecolefficiency		0.75-4 % 1-5 % 5-25 %	alkaline pH: 13.5	2.5	1 1	6.295-646.0 6.295-647.0 6.295-648.0 6.295-649.0	
	PressurePro Active Cleaner, alkaline RM 81 Efficiently and gently acting high-pressure cleaning concentrate for heavy oil, grease and mineral soiling. Suitable for cleaning vehicles, tarpaulins and engines. NTA-free.	High-pressure cleaner Spray units	1+3	1-5 % 5-25 %	alkaline pH: 12.3	2.5	1 1 1	6.295-555.0 6.295-556.0 6.295-557.0 6.295-558.0 6.295-559.0	
	PressurePro Active Cleaner, alkaline RM 81 ecolefficiency High-pressure cleaning concentrate with a powerful and gentle cleaning action for removing stubborn oil, grease and mineral contamination. Suitable for vehicle and engine washing as well as tarpaulin cleaning. With the ecolefficiency formulation, it is very economical, effective and environmentally friendly.	High-pressure cleaner (80 °C) High-pressure cleaner (60 °C) Spray units ecolefficiency		0.75-4 % 1-5 % 5-25 %	alkaline pH: 12.3	2.5 l	1 1	6.295-642.0 6.295-643.0 6.295-644.0 6.295-645.0	
The second	PressurePro Foam Cleaner RM 838 The alkaline Foam Cleaner RM 838 for contactless vehicle washing effortlessly removes heavy oil and grease stains, insect residues and road dirt and is gentle on paintwork. ¹⁾	NEW		1-2 %	alkaline pH: 12.6	1 1 3 1	12	6.296-034.0 6.295-979.0	
To realize	PressurePro Wax Remover RM 36 Wax stripper; gently removes protective wax coatings and grease residue from paintwork surfaces. Ideal for use with high-pressure cleaners.	High-pressure cleaner		1-5 %		201	1	6.295-423.0	
N. S.	VehiclePro Rim Cleaner, acidic RM 800 Highly effective rim cleaner concentrate. Active foam enables the gentle removal of all common rim dirt, like brake dust, tyre wear, winter salt residues, lime stains and salt deposits.	Spray units Self-service wash bays Commercial vehicle washes		10 % 10 % 10 %	acidic pH: 0.3	20 1 200 1 4		6.295-441.0 6.295-452.0	
	VehiclePro Rim Cleaner, alkaline RM 801 Classic Special rim cleaner for all coated light metal and steel rims (excludes uncoated, high-gloss special rims). Gentle action, effectively removes the most stubborn rim dirt, e.g. road dust, baked-on brake dust, tyre wear and winter salt residues. Does not attack concrete floors or wheel arches. ²⁾	Spray units Self-service wash bays Commercial vehicle washes		10 % 10-20 % 10-20 %	alkaline pH: 13.5	201	1	6.295-323.0	
E.	VehiclePro Prewash RM 803 Classic VehiclePro Prewash RM 803 Classic: Active, gentle high-pressure pre-spraying agent. Accelerates the softening and removal of oils and greases, as well as insect residues.	High-pressure cleaner Commercial vehicle washes Self-service wash bays Spray units	1+2	1.5-6 % 0.5-2 % 1.5-6 % 2 %	alkaline pH: 13	10 I 20 I 200 I 200 I	1	6.295-547.0 6.295-548.0 6.295-549.0	

1)	VDA-compliant class A.
2)	VDA-compliant class B.

	Product description	Application	Primary mixture	Dosage	Properties	Packag size	ging	PU	Order no./ quantity	Price
Till .	PressurePro Active Cleaner, powder RM 80 Highly concentrated, pourable and water-soluble powder with a fresh scent. Dissolves oil, grease and emission-related soiling, effective at all temperature ranges, gentle action.	High-pressure cleaner Self-service wash bays	1+9	0.5 %	slightly alkaline pH: 10.9				6.295-237.0	
	PressurePro Car Shampoo, powder RM 22 Powerful shampoo powder for removing stubborn oil, grease and mineral contamination. Ideal for engine cleaning and vehicle washing. NTA-free.	High-pressure cleaner Spray units	1+9	0.5-2 % 5 %	alkaline pH: 12.7	20 kg	■ ▲	1	6.295-537.0	
	PressurePro Car Shampoo, powder RM 22 Powerful shampoo powder for removing stubborn oil, grease and mineral contamination. Ideal for engine cleaning and vehicle washing.	High-pressure cleaner Spray units	1+9	0.5-2 % 5 %	alkaline pH: 12.9	20 kg	A	1	6.295-254.0	
	PressurePro Hot Wax RM 41 Paintwork preservation and care product with high natural carnauba wax content. Produces a high-lustre finish.	High-pressure cleaner Manual	1+3	1-2 % 1-2 %	slightly acidic pH: 4.5	10 l 20 l	:	1	6.295-153.0 6.295-154.0	
	VehiclePro Spray Wax RM 821 Classic This liquid spray wax gives vehicles a brilliant shine and long-term protection. Unaffected by water quality, it provides a spotless finish without blow drying. VDA compliant. ¹⁾	High-pressure cleaner Self-service wash bays	1+9	1-2 % 1-2 %	slightly acidic pH: 4	2.5 l 20 l 200 l	:	1 1	6.295-583.0 6.295-431.0 6.295-084.0	
od industry	PressurePro Foam Cleaner, neutral RM 57 Gentle foam cleaning agent for light oil, grease and protein stains. Stable foam blanket enhances cleaning action and is easily rinsed away.	High-pressure cleaner High-pressure cleaner with foam nozzle Spray units Manual		1-2 % 3-10 % 10 % 10 %	neutral pH: 6.7	20	■ ▲	1	6.295-178.0	
	PressurePro Foam Cleaner, alkaline RM 58 Reliably removes stubborn grease, oil and protein stains as well as food residue on tiles and containers. Foam blanket permits long periods of contact for intensive cleaning action on vertical surfaces.	Spray units High-pressure cleaner High-pressure cleaner with foam nozzle Manual		4-6 % 1-2 % 4-10 %	alkaline pH: 13.1	20		1	6.295-100.0	
10.78	PressurePro Foam Cleaner, acidic RM 59 Effortlessly removes stubborn deposits and coatings like lime, rust, grease, pro- tein, beer stone and milk stone on tiles and containers. Very stable foam blanket ensures intensive cleaning effect on all surfaces.	High-pressure cleaner with foam nozzle Spray units		1-2 % 3-10 % 6 % 10 %	acidic pH: 1.8	20	•	1	6.295-192.0	
	PressurePro Grease and Protein Remover RM 731 Removes even the toughest grease, protein, oil and soot contamination from floors, working areas, machines, etc. (particularly suitable for use in the food processing industry). Fasy-to-use with a	High-pressure cleaner Spray units Manual		1-6 % 1-6 % 1-6 %	alkaline pH: 13.1	51		1	6.295-402.0	

without residues.

processing industry). Easy-to-use, with a gentle cleaning action. Washes clean

CLEANING AND CARE AGENTS

⁵⁾ Included in the VAH list of disinfectants of 1 April 2012 (mhp Verlag GmbH Wiesbaden).

⁶⁾ Included in the IHO list of disinfectants for animal husbandry.

Nitrilotriacetate-free (NTA-free).

[▲] Easily separable in oil separator systems (ASF).

¹⁾ VDA-compliant class A. 2) VDA-compliant class B.

⁵⁾ Included in the VAH list of disinfectants of 1 April 2012 (mhp Verlag GmbH Wiesbaden).

⁶⁾ Included in the IHO list of disinfectants for animal husbandry.

[■] Nitrilotriacetate-free (NTA-free).

[▲] Easily separable in oil separator systems (ASF).

	Product description	Application	Primary mixture	Dosage	Properties	Packag size	ging	PU	Order no./ quantity	Price
	Disinfectant Cleaner RM 732	High-pressure cleaner		1-3 %	slightly alkaline			1	6.295-596.0	
	Disinfectant cleaning agent. With bacte-	Maintenance cleaning		1-3 %	pH: 9.9	200 1		1	6.295-417.0	
	ricidal, fungicidal and limited virucidal	Spray units		1-3 %	p				0.230 117.0	
5	properties. Offers very good cleaning	Manual		1-3 %						
==	power. Use biocides safely. Always read									
2	the label and product information before	housingsteen High								
	USE. ⁵⁾⁶⁾									
	Disinfectant Cleaner, foaming RM 734	High-pressure cleaner with		2-5 %	alkaline	25 I		1	6.295-282.0	
1	Disinfectant foam cleaning agent. With fungicidal, virucidal, sporicidal and	foam nozzle		2-5 %	pH: 13.7					
	bactericidal properties. At the same time	Spray units		2-5 %						
	removes grease, protein, oil and soot	Walloal		2-3 /0						
	stains. Stable foam blanket allows use									
	on vertical surfaces. Use biocides safely.									
	Always read the label and product									
	information before use.									
	Disinfectant RM 735	High-pressure cleaner		0.75-2 %	neutral	2.5 I		4	6.295-585.0	
	Effective, neutral disinfectant. With	Spray units		0.75-2 %	pH: 7.6	5 I			6.295-597.0	
-	bactericidal, fungicidal and limited	Manual		0.75-2 %						
=	virucidal properties (e.g. hepatitis B).									
= "	Use biocides safely. Always read the									
1	label and product information before	Hancino Biologicos BHO								
	USE. ⁵⁾⁶⁾									
-	PressurePro Active Cleaner, acidic RM 25	High-pressure cleaner	1+3	0.5-10 %	acidic	2.5 l		4	6.295-588.0	
-	Acidic high-pressure deep cleaner for	Spray units		25 %	pH: 0.2	10 l		1	6.295-113.0	
	sanitary areas. Removes limescale, rust,					20 I		1	6.295-420.0	
	beer stone and milk stone, grease and					200 I		1	6.295-421.0	
	albumen stains. Ideal for cleaning inside tanks in the food industry.									
-	taliks in the lood industry.									
	PressurePro Oil and Grease Cleaner	High-pressure cleaner (80 °C)	1+3	0.75-4 %	alkaline	2.5		4	6.295-646.0	
-	Extra RM 31 eco!efficiency	High-pressure cleaner (60 °C)		1-5 %	pH: 13.5	10			6.295-647.0	
-	Highly concentrated deep cleaning agent			5-25 %	p 22.2	20			6.295-648.0	
	for high-pressure cleaning. Effectively					200 I		1	6.295-649.0	
1	removes stubborn dirt, e.g. oil, grease,	e								
	soot and smoke resin at all temperatures.	eco!efficiency								
	With the ecolefficiency formulation,									
	particularly economical, effective and environmentally friendly.									
_	environmentally menally.									
-	PressurePro Oil and Grease Cleaner	High-pressure cleaner	1+3	1.5-10 %	alkaline	2.5 l	I		6.295-584.0	
	Extra RM 31	Spray units		25 %	pH: 13	10			6.295-068.0	
Tomas .	Highly concentrated high-pressure deep cleaning agent. At all temperature					20	I 4		6.295-069.0	
Table 1	ranges, highly efficient lifting of the					200 I 1000 I			6.295-422.0	
1	most stubborn contaminations, such as					10001		1	6.295-072.0	
	oil, grease, tar, soot and smoke resin.									
	Alkaline Active Cleaner RM 81	High-pressure cleaner	1+3	1-5 %	alkaline	2.5		4	6.295-555.0	
100	Efficiently and gently acting high-pres-	Spray units		5-25 %	pH: 12.3	10 I			6.295-556.0	
	sure cleaning concentrate for heavy oil,					20 I		1	6.295-557.0	
The same of	grease and mineral soiling. Suitable for					200 I		1	6.295-558.0	
	cleaning vehicles, tarpaulins and engines.					1000 l		1	6.295-559.0	
	NTA-free.									
	ProceuroPro Intensive Been Cleaner	High proceure closes	1,2	1 = 0	alkalina	10.1	_	. 1	6 20E E20 0	
W	PressurePro Intensive Deep Cleaner RM 750	High-pressure cleaner Scrubber driers - Stripping	1+3	1-5 % 10-50 %	alkaline pH: 13.7	10 I 200 I			6.295-539.0 6.295-540.0	
	Powerful deep cleaner effectively	Scrubber-driers -		5-50 %	pi i. 15.7	2001		1	0.295-540.0	
5		deep cleaning								
4	as oil, grease, soot, blood and proteins.	Manual		5-50 %						
Y I	Low foaming. Particularly suited for floor									
_	cleaning by machine and for processing									
	with hard surface cleaners. NTA-free.									

- VDA-compliant class A.
 VDA-compliant class B.
- 2) VDA-Compilant class B.
 5) Included in the VAH list of disinfectants of 1 April 2012 (mhp Verlag GmbH Wiesbaden).
 6) Included in the IHO list of disinfectants for animal husbandry.
 Nitrilotriacetate-free (NTA-free).
 A Easily separable in oil separator systems (ASF).

	Product description	Application	Primary mixture	Dosage	osage Properties		Packaging size PU		Order no./ quantity	Price
	PressurePro Smoke Resin Remover	High-pressure cleaner	1+3	4-8 %	alkaline	20			6.295-560.0	
-	RM 33	Spray units		10 %	pH: 13.5	200 I		1	6.295-561.0	
	Very powerful liquid deep cleaning agent for removing stubborn stains such as oil, fat, tar, soot, resinous soot, and burnt-on sugar glazes. NTA-free.									
culture										
The state of the s	PressurePro Foam Cleaner, alkaline RM 91 Agri The foam cleaner has excellent grease-dissolving properties and effort-lessly removes organic material such as dung and dirt. Ideal for cleaning poultry, pig and cattle sheds as well as milking parlours.	High-pressure cleaner		3-5 %	alkaline pH: 13.5	10	•	1	6.295-654.0	
	PressurePro Soaking Agent, alkaline RM 92 Agri The soaking agent loosens dried dung to reduce cleaning time and water consumption. Corrosion inhibitors preserve stable fixtures. Ideal for stables and milk parlours.	High-pressure cleaner		1-3 %	alkaline pH: 14	10	•	1	6.295-656.0	
11.11	PressurePro Surface Cleaner, acidic RM 93 Agri Acid surface cleaner for milk parlours, milk rooms and stables. Removes even the most stubborn deposits, such as limescale, minerals and rust. Corrosion inhibitors preserve stable fixtures.	High-pressure cleaner		1-3 %	acidic pH: 1.4	10	•	1	6.295-658.0	
des and so										
Town.	PressurePro Active Cleaner, neutral	High-pressure cleaner		0.5-8 %	slightly alkaline		<u> </u>		6.295-579.0	
2	RM 55 All-purpose, gentle high-pressure liquid	Spray units Manual		10 % 2 %	pH: 10	10 l	<u> </u>		6.295-090.0	-
	concentrate for removing grease, oil and emission contamination. Ideal for clean- ing façades and sensitive surfaces.	Weiled		2 70		200 I 1000 I		1	6.295-411.0 6.295-412.0 6.295-093.0	
	Blasting Abrasive, fine Grit size 0.2-0.8 mm - ideal for cleaning clinker, brick, sandstone, terrazzo, steel, hardwood or concrete.	High-pressure cleaner with jet system and jet gun		tailored to individual require- ments		25 kg		1	6.295-564.0	
-0.	Blasting Abrasive, coarse	High-pressure cleaner with		tailored to		25 kg		1	6.295-565.0	
	Grit size 0.25-1.4 mm - highly effective on steel, granite, aerated concrete and washed concrete. Also ideal for removing rust, paint and graffiti.			individual require- ments						
THE RESERVE	PressurePro Façade Cleaner, gel RM 43 Powerful façade cleaner with gel formula. Removes soot, oil, grease and environmental stains. Suitable for façades clad with stone, brick, rough-cast plaster, plastic, wood and glass.	High-pressure cleaner Spray units		6 % 6-8 %	alkaline pH: 13.8	20		1	6.295-447.0	
	PressurePro Solar Cleaner RM 99	High-pressure cleaner	1+3	0.5-1 %	slightly alkaline	10.1			6.295-798.0	
-	Highly efficient, gentle and biodegrad-	THE PICSSOIC CICALICI	1.0	0.5 1 /0	pH: 9	10	÷		6.295-798.0	
	able cleaning agent for residue-free, streak-free cleaning of solar and photo- voltaic systems. Prevents the formation of limescale. For all water hardness levels. For removing stubborn bird drop- pings, pollen, rust and dust. Also suitable					101			3.233 / 30.0	

- 1) VDA-compliant class A.
- 2) VDA-compliant class B.
 5) Included in the VAH list of disinfectants of 1 April 2012 (mhp Verlag GmbH Wiesbaden).
 6) Included in the IHO list of disinfectants for animal husbandry.

for aluminium frames.

- Nitrilotriacetate-free (NTA-free).
- ▲ Easily separable in oil separator systems (ASF).

			Primary			Packag	ging		Order no./	
	Product description	Application	mixture	Dosage	Properties	size		PU	quantity	Price
arts cleaning a	nd phosphating									
	PartsPro Parts Cleaner RM 39	High-pressure cleaner		2-5 %	slightly alkaline			1	6.295-165.0	
E.	Gentle cleaning and degreasing agent effectively removes oil, grease and soot stains from metal parts and provides temporary corrosion protection.	Parts cleaners		1-5 %	pH: 10.5	200	•	1	6.295-424.0	
	PressurePro Phosphating Agent RM 48	High-pressure cleaner		0.5-1 %	acidic	20 I		1	6.295-219.0	
-	For degreasing and phosphating in a	riigii pressore cicariei		0.5 1 %	pH: 2	200			6.295-410.0	
	single operation. Provides temporary protection against corrosion and produces a good base for paints. When processed, it leaves bluish-yellow iron phosphate layers.					2001			0.233 410.0	
aintenance an	d care of high-pressure cleaners									
	PressurePro Descaling Acid RM 101 Hydrochloric acid basis for fast descaling. Quickly removes the most stubborn limescale and detergent residues and offers long-lasting corrosion protection. Particularly suitable for heating coils in high-pressure cleaners.	Heater coil descaling		10 %	acidic pH: 0	5		1	6.295-398.0	
	PressurePro Machine Protector RM 110	Hot water high-pressure		6 ml/°dH m³	neutral	1		6	6.295-312.0	
	Calcification protection for hot water	cleaners			pH: 7	10 I		1	6.295-303.0	
=	high-pressure cleaners. This new formula					20			6.295-488.0	
15 M	offers improved protection from lime					200			6.295-305.0	
	deposits in heater coil systems (up to 150°C) as well as integrated corrosion protection for all HDS machine components that come into contact with water.									
	PressurePro Machine Protector	Hot water high-pressure		6 ml/°dH m³	neutral	1		6	6.295-625.0	
- Alle	Advance 1 RM 110 Scale inhibitor for hot water high-pressure cleaners with integral corrosion protection, especially for use in new HDS units with System Care option. The Machine Protector Advance 1 RM 110 formula offers improved protection against limescale deposits on heater coils (up to 150 °C) and provides integral corrosion protection for components in contact with water.	cleaners			pH: 7					
	PressurePro Machine Protector Advance 2 RM 111	Hot water high-pressure cleaners		6 ml/°dH m³	alkaline pH: 12.3	1	■ ▲	6	6.295-629.0	
	Maximum machine protection for hot water high-pressure cleaners with system care adaptation. Machine Protector Advance 2 RM 111 offers the following protective functions for your machine: protection against limescale deposits in heating coils (up to 150°C), pump care additive for continuous lubrication and care of the high-pressure pump, protection against black water (rust generation in the heating coil with very soft water). Corrosion protection for all parts that come into contact with water.									
and cleaning										
	Hand Cleaning Paste RM 200	Manual		undiluted	neutral	10 I		1	6.291-030.0	
-	Rich, gentle hand cleanser based on wood flour. For stubborn oil, grease, pigment and paint stains.				pH: 6.4	800 m	•	6	6.295-631.0	

	Ġ.		3.	8	
	s	F.	Σ.	e	
-	5		*	1	

- 1) VDA-compliant class A. 2) VDA-compliant class B. 5) Included in the VAH list of disinfectants of 1 April 2012 (mhp Verlag GmbH Wiesbaden).
- 6) Included in the IHO list of disinfectants for animal husbandry.
- Nitrilotriacetate-free (NTA-free).
- ▲ Easily separable in oil separator systems (ASF).

	Product description	Pressure	Dosing range	Dispensing volume	Extendable	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Dilution device	s									
60	DS 2 Dosing Unit DVGW-certified dosing unit for filling floor cleaning machines and buckets and for preparation of HD/HDS primary mixtures. Includes backflow preventer according to DIN EN 1717.	1.7-3.5 bar	0.3-25 %	14 I/min	•	355 × 300 × 210 mm	1.86 kg	1	6.394-653.0	
-	DS 3 Cleaning Agent Dosing Station After connecting to a tap, cleaning	2-6 bar	0.2-13.5 %	15 l/min	•	390 × 390 × 150 mm	3.85 kg	1	2.641-811.0	



tank and diluted as required. Can also be used with the filling system attachment kit. Includes backflow preventer (DIN EN 1717).

	Product description	Suitable for bulk size	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Dispensing ai	ds						
=	Container valve, 5 I Practical aid for efficient filling and dosing of cleaning agents from containers.	51	85 × 48 × 40 mm	0.02 kg	1	6.394-819.0	
=	Container valve, 10I Practical aid for efficient filling and dosing of cleaning agents from containers.	10	60 × 90 × 70 mm	0.04 kg	1	6.394-758.0	
	Container valve, 201	20	75 × 110 × 60 mm	0.04 kg	1	6.394-759.0	



Container valve, 201 Practical aid for efficient filling and dosing of cleaning agents from containers.



drums.

Drum tap, 200 I For dispensing cleaning agents from 200 I


200 I



Drum pump, 200 I Practical pump for dosed and efficient dispensing of cleaning agents from drums. Accurate and easy to use.

1560 × 175 × 90 mm	1.1 kg	1	6.291-108.0

150 × 100 × 65 mm 0.08 kg 1 6.412-438.0



steel



Mobile and compact: low-pressure spray unit for effective dispensing of cleaning agent for wide area coverage. With integrated manual pump, ergonomic pump handle and level control.

Accessory for a long reach for use with EK 1 Cleaning Agent Sprayer. Extendable from 860 to 1520 mm including nozzle for precise application.


Telescopic spray lance	875 × 45 × 20 mm	0.366 kg 1	6.393-313.0
Accessory for a long reach for use			

848

Price

CarpetPro - A STRONG TEAM TO SAVE YOU LOTS OF TIME

The CarpetPro line gently and effectively cleans and protects textile surfaces. This innovative system reduces cleaning and drying times and delays resoiling, protecting treated surfaces as well as the environment and your budget. CarpetPro line is based on iCapsol technology, which encapsulates and binds the dirt. Rinsing carpets is no longer necessary as the encapsulated residual contamination is simply vacuumed during subsequent maintenance cleaning. Carpets dry quickly and are ready to walk on in no time.











1 iCapsol technology

The patented iCapsol technology can be used not only for intermediate cleaning of carpets, but also for deep cleaning.

This is unique worldwide. iCapsol active ingredients bind the dirt and surfactants after cleaning to prevent resoiling of the carpet fibres. iCapsol active ingredients form a crystalline structure when dry. These crystals are simply vacuumed during the next maintenance cleaning. This results in time savings of up to 50% even when deep cleaning, as there is no need to rinse and the drying time is shorter. The advantages are noticeable even without previous rinsing, because resoiling is delayed and carpets stay cleaner longer.

2 Phosphate-free formulas

Kårcher is aware of its responsibility for the environment and people. Our cleaning agents demonstrate that powerful cleaning is also possible without using harmful content materials like phosphates.

3 Integrated odour absorber

An integrated odour absorber cuts the time needed for intermediate and deep cleaning of textile surfaces. Carpets and upholstery are not only left clean, but also smell clean.

4 WoolSafe-certified

Many Kärcher CarpetPro products carry the WoolSafe seal. The worldwide certification programme for textile cleaning products confirms that Kärcher CarpetPro products are suitable for wool and other sensitive textile fibres and are safe when used properly. Products with WoolSafe ensure professional treatment and care of carpets and upholstery which retain their value.

5 Patented water-soluble film: simple and safe

The deep cleaning power of the CarpetPro Cleaner iCapsol RM 760 tablets is wrapped in a patented water-soluble film: the film dissolves to release the cleaning power of the tablets. This allows quick and reliable dosing directly at the place of use without the need for protective gear. RM 760 Tablets dissolve quickly - cleaning can start immediately. Each tab contains the right amount of cleaning agent - this prevents incorrect dosing, protects the environment and saves money.

Product	Acti	Activity Soiling			Machine/Tool					Properties					Page					
	Stain removal	Intermediate cleaning	Deep cleaning	Care, protection	Grease, earth, protein and road dirt	Rust, urine, mineral deposits	Ink, biro/felt tip pens, adhesives, tar, shoe polish	Cleaning agent residue	Foam reduction	Puzzi	BRC	BRS	BDS	Manual (cloth, brush, spray unit)	iCapsol technology	Odour absorber	Surfactant-free	Phosphate-free	WoolSafe-certified	
Universal Stain Remover RM 769							•													852
CarpetPro Cleaner iCapsol RM 768		•			•						•	•	•		~				~	852
CarpetPro Cleaner iCapsol RM 768 OA											•	•			~	~				852
CarpetPro Cleaner RTS Classic		•			•					•	•									852
CarpetPro Cleaner iCapsol, powder RM 760 OA															~	~		~	~	852
CarpetPro Cleaner iCapsol, tablet RM 760			•		•					•					~			~	~	852
CarpetPro Cleaner RM 764 OA			•		•					•	•					~		~	~	852
CarpetPro Cleaner, quick-drying RM 767 OA			•		•					•	•					V				852
Universal Cleaner, surfactant-free RM 770			•							•							~			852
CarpetPro Cleaner, powder RM 760 Classic					•															852
CarpetPro Conditioner RM 763																			~	853
Foam Blocker RM 761		•	•						•	•										853
CarpetPro Protector RM 762				-															V	853
																	1			

■ usable ⊔ usable subject to conditions

CLEANING AND


	Product description	Application	Primary mixture	Dosage	Properties	Packaging s	ize	PU	Order no./ quantity	Price
Stain removal	Universal Stain Remover RM 769 Universal Stain Remover RM 769 for all textile coverings, upholstery and hard surfaces – removes oil, tar, shoe polish, adhesive, etc., from solvent-resistant surfaces.	Manual		undiluted		500 ml	•	6	6.295-490.0	
ntermediate cl	eaning									
	CarpetPro Cleaner iCapsol RM 768 CarpetPro Cleaner iCapsol RM 768 for intermediate cleaning. Dry foam with encapsulation technology: Dirt is encapsulated and vacuumed during the next maintenance cleaning.	Intermediate cleaning		6 %	neutral pH: 6.1	10	•	1	6.295-562.0	
	CarpetPro Cleaner iCapsol RM 768 OA Powerful dry foam CarpetPro Cleaner iCapsol RM 768 OA with odour elimina- tor. With encapsulation technology: Dirt is encapsulated and is vacuumed off when you next clean.	Intermediate cleaning ABSORS ODDURS		6 %	slightly alkaline pH: 8.5	10	•	1	6.295-634.0	
	CarpetPro RTS Classic Cleaner Effective carpet cleaner for thorough and hygienic spray extraction cleaning of textile floor coverings and uphol- stery, as well as for gentle removal of stains.	Deep cleaning Intermediate cleaning		5-10 % 1-5 %	neutral pH: 7.8	10	•	1	3.334-104.0	
eep cleaning										
The last of the la	CarpetPro Cleaner iCapsol RM 760 Powder OA The CarpetPro Cleaner iCapsol RM 760 Powder OA is a spray extraction cleaner with outstanding cleaning performance, iCapsol encapsulation technology and odour absorber. No time-consuming rinsing.	Deep cleaning Intermediate cleaning		1 % 1 %	neutral pH: 7.7	0.8 kg 10 kg	•	1	6.295-849.0 6.295-847.0	
	CarpetPro Cleaner iCapsol RM 760	Deep cleaning		2 tablets in		16 Tablets		20	6.295-850.0	
1 45 110	Tablet CarpetPro Cleaner iCapsol RM 760 Tablet is a spray extraction deep cleaner in tablet form. With encapsula- tion technology. In a practical foil that is water-soluble. No time-consuming rinsing.	Intermediate cleaning		8 litres of water 2 tablets in 8 litres of water	pH: 7	200 Tablets	•	1	6.295-851.0	
	CarpetPro Cleaner RM 764 OA CarpetPro Cleaner RM 764 OA, the deep cleaning spray extraction cleaner. For all textile floor coverings (including mixed and fully-synthetic fibres), upholstery and wall surfaces.	Deep cleaning Intermediate cleaning		1 % 1 %	slightly alkaline pH: 9.2	10	•	1	6.295-854.0	
	CarpetPro Cleaner, quick-drying RM 767 OA Liquid fast-drying spray extraction agent CarpetPro Cleaner RM 767 OA for textile surfaces and upholstery eliminates unwanted odours and improves floor hygiene.	Deep cleaning Intermediate cleaning ASSORES OCCURRENT		1.2 % 1.2 %	neutral pH: 6.4	10	•	1	6.295-198.0	
M. 34	Universal Cleaner RM 770, surfactant-free Powerful surfactant-free universal cleaner for all textiles, resilient and hard floor coverings as well as ceilings and walls. Removes stubborn oil, grease and nicotine stains. Offers lasting protection against dirt and stains, cleaning intervals are extended.	Spray units Manual Spray extraction machines Single disc machines	5	5-50 % 5-50 % 12.5 % 5-12 %	slightly alkaline pH: 8.6	11	•	6	6.295-489.0	
L	CarpetPro Cleaner RM 760 Powder Classic Powerful spray extraction deep cleaner CarpetPro Cleaner RM 760 Powder Classic. For textile floor coverings, walls and upholstery (also blended fabrics and fully synthetic fibres).	Deep cleaning Intermediate cleaning		1 % 1 %	slightly alkaline pH: 8.2	0.8 kg 10 kg	•	4 1	6.290-175.0 6.291-388.0	

Product description Application Primary mixture Dosage Properties Packaging size PV quantity Price Supplementary deep cleaning CarpetPro Conditioner RM 763 The effective CarpetPro Conditioner RM 763 for all types of fibres reduces rinsing time, removes dirt and sur- factant residues, neutralises the fibres and freshens up the colours. Wet and dry vacuum forming in wastewater tanks and forming in wastewater tanks and formation with all machines. Compatible with all machines. CarpetPro Protector RM 762 CarpetPro Protector RM 762 Spray units CarpetPro Protector RM 762 Spray vartaction machines and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them hard-wearing.										
CarpetPro Conditioner RM 763 The effective CarpetPro Conditioner RM 763 for all types of fibres reduces rinsing time, removes dirt and surfactant residues, neutralises the fibres and freshens up the colours. Wet and dry vacuum 1,5 % 1,8 slightly acidic pH: 3.8 Foam Blocker RM 761 The Foam Blocker RM 761 reduces foaming in wastewater tanks and increases the device's duration of use. Compatible with all machines. Compatible with all machines. Carpet Pro Protector RM 762 CarpetPro Protector RM 762 for carpets CarpetPro Protection against both wet and dry dirt. Seals the fibres and makes them Spray extraction machines 1,8 slightly acidic pH: 3.8 Ill 1 1 2 6.295-844.0 1 1 6.291-389.0 2.5 I 1 6.291-389.0 2.5 I 1 6.291-389.0 2.5 I 1 6.291-389.0 2.5 I 1 6.291-389.0 3.5 % 4.5 Spray extraction machines 4.5 No. 5 % 4.5 Spray extraction machines 5.5 No. 5 % 4.5 I 2 6.295-852.0 4.5 I 2 6.295-852.0		Product description	Application	 Dosage	Properties	Packaging	size	PU		Pric
The effective CarpetPro Conditioner RM 763 for all types of fibres reduces rinsing time, removes dirt and surfactant residues, neutralises the fibres and freshens up the colours. Foam Blocker RM 761 The Foam Blocker RM 761 reduces foaming in wastewater tanks and increases the device's duration of use. Compatible with all machines. Compatible with all machines. Carpet Pro Protector RM 762 Carpet Pro Protector RM 762 for carpets and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them	Supplementary	deep cleaning								
The Foam Blocker RM 761 reduces foaming in wastewater tanks and increases the device's duration of use. Compatible with all machines. Compatible with all machines. Carpet Cleaners Floor cleaning units Parts cleaners CarpetPro Protector RM 762 CarpetPro Protector RM 762 Spray units CarpetPro Protector RM 762 for carpets and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them	H. M.	The effective CarpetPro Conditioner RM 763 for all types of fibres reduces rinsing time, removes dirt and sur- factant residues, neutralises the fibres	Spray extraction machines	1 %		11	i	12	6.295-844.0	
foaming in wastewater tanks and increases the device's duration of use. Compatible with all machines. Compatible with all machines. Compatible with all machines. Spray extraction machines 0.5 % 0		Foam Blocker RM 761	Wet and dry vacuum	 0.5 %		2.5	•	1	6.291-389.0	
increases the device's duration of use. Compatible with all machines. Compatible with all machines. Floor cleaning units Parts cleaners Carpet Pro Protector RM 762 Spray units 20 % neutral 5 l 2 6.295-852.0 CarpetPro Protector RM 762 for carpets and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them	_	The Foam Blocker RM 761 reduces		0.5 %						
Compatible with all machines. Floor cleaning units Parts cleaners Impregnation CarpetPro Protector RM 762 Spray units 20 % neutral 5 l 2 6.295-852.0 CarpetPro Protector RM 762 for carpets Spray extraction machines and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them	00	foaming in wastewater tanks and	Spray extraction machines	0.5 %						
Parts cleaners CarpetPro Protector RM 762 Spray units 20 % neutral 5 l 2 6.295-852.0 CarpetPro Protector RM 762 for carpets and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them	Me	increases the device's duration of use.	Carpet cleaners							
CarpetPro Protector RM 762 Spray units 20 % neutral 5 l 2 6.295-852.0 CarpetPro Protector RM 762 for carpets Spray extraction machines 20 % pH: 5.5 and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them	-	Compatible with all machines.		0.5 %						
CarpetPro Protector RM 762 for carpets Spray extraction machines 20 % pH: 5.5 and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them	Impregnation								,	
and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them		CarpetPro Protector RM 762	Spray units	20 %	neutral	5 I		2	6.295-852.0	
		and textile surfaces. Effective long-term protection against both wet and dry dirt. Seals the fibres and makes them		20 %	pH: 5.5					

Nitrilotriacetate-free	(NTA-free

	Product description	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Sales tools						
	Premium demo case Robust demonstration case with many storage options, convenient large opening, telescopic handle and smooth-running castors. Ideal for all utensils for cleaning agent demonstrations.	44 × 30 × 44 cm	4.5 kg	1	6.999-247.0	
	Starter set for Premium demo case Basic and safety equipment for demonstrations and applications of cleaning agents. Incl. pH measurement, cloths, brushes, cutter and scraper.		2 kg	1	2.200-006.0	
	Refill set for Premium demo case		1.5 kg	1	2.200-007.0	
J.	Incl. all consumables from the starter set such as Ph measuring strips, cloths, brushes, cutter, blades, scraper, gloves, bin liners.					
5	Clean Card 25 Clean Cards for the detection of dirt containing protein and surfactants from cleaning agent or disinfectant residues on visibly clean surfaces. For hygieni- cally sensitive areas.		1.5 kg	1	6.999-313.0	

DEEP CLEANING WITH iCapsol ENCAPSULATION TECHNOLOGY











INTERMEDIATE CLEANING WITH iCapsol ENCAPSULATION TECHNOLOGY









CLEANING AND CARE AGENTS

SurfacePro - AN ALL-ROUNDER FOR EVERY SURFACE

All Kärcher products for manual cleaning are specially designed for the requirements of cleaning service providers. They quickly and reliably remove all typical dirt without adversely affecting surfaces. Cleaning performance alone no longer meets the professional demands of cleaning service providers and facility management. The cleaning agent of your choice has to offer much more: a pleasant scent, contemporary environmental sustainability, reliable dosing of concentrates and ideal handling, i.e. ergonomic bottles.















1 Unique diversity

With our innovative, complete product range for manual cleaning, you have all the options – from glass cleaning to surface cleaning. Colourcoding and language-neutral labels clearly indicate the right application.

2 Consistent sustainability

Kärcher is a member of the sustainability initiative Association for Soaps, Detergents and Maintenance Products in Europe (AISE). All products in our green cleaning agent range carry the EU Ecolabel – EU Flower – and the Austrian Ecolabel. Our advanced formulas improve effectiveness and are also eco-friendly – from production to wastewater treatment. Concentrates reduce packaging. And the spray heads are reusable.

3 Optimal results

Our products set standards when it comes to the tricky task of glass cleaning. They always achieve optimum cleaning performance while keeping surfaces streak-free.

4 Good and safe handling

The optimised form and function of our spray heads and bottles offer you exemplary user-friendliness and ergonomics. The 0.5 litre spray bottles are easy to handle, even during long periods of use. The spray heads fit comfortably in your hand and can be operated using up to three fingers. The variable foam nozzle prevents aerosol formation and increases work safety.

856
856
856
856
856
856
856
856
856
857
857
857
857
857
ч—
857
857 857

■ NEW ■ usable □ usable subject to conditions

CLEANING AN

	Product description	Primary oduct description Application mixture				Packaging size Pl			Order no./ quantity	Price
urface - Mainto	enance cleaning									
•	SurfacePro Alcal Alcohol-Based Cleaner Alcal alcohol-based yet material-friend- ly cleaner for manual application. For gentle and efficient cleaning of all water-resistant, smooth and shiny			1-2 %	neutral pH: 8	101	•	12	3.334-034.0 3.334-033.0	
	an water-resistant, smooth and sniny surfaces.									
	SurfacePro Maintenance Cleaner,	Intermediate cleaning		2-4 %	slightly alkaline	1			3.334-025.0	
	odourless Allflex Our odourless Allflex universal cleaner is predominantly used in the food industry to remove dirt of plant- and animal-based origin.	Maintenance cleaning		0.5-1 %	pH: 9.8	10	•	1	3.334-024.0	
	Universal Cleaner RM 770,	Spray units		5-50 %	slightly alkaline	1	_	6	6.295-489.0	
M. FIL	surfactant-free Powerful surfactant-free universal cleaner for all textiles, resilient and hard floor coverings as well as ceilings and walls. Removes stubborn oil, grease and nicotine stains. Offers lasting pro- tection against dirt and stains, cleaning intervals are extended.	Manual Spray extraction machines Single disc machines		5-50 % 12.5 % 5-12 %	pH: 8.6					
	Fleural Perfumed Cleaner	Intermediate cleaning		1-2 %	slightly alkaline	1		12	3.334-030.0	
-	For all types of washable surface and	Maintenance cleaning		0.5-1 %	pH: 9.3	10 I		1	3.334-029.0	
Milmin.	furnishings: our deep cleaning Fleural universal cleaner with a pleasant fragrance.									
-	SurfacePro Surface Cleaner CA 30 C	Maintenance cleaning		1 %	neutral	1		12	6.295-681.0	
	ecolperform Universal, fast surface cleaning concentrate for floors and interior with streak-free drying – also for high-gloss surfaces. With EU eco label certification.	@ eco!perform			pH: 7.4	51	•	2	6.295-682.0	
-	SurfacePro Surface Cleaner CA 30 C	Maintenance cleaning		1 %	slightly alkaline	1			6.296-085.0	
	eco!perform Swan SurfacePro Surface Cleaner CA 30 C: Surface cleaning concentrate for manual application. Universal, also on high-gloss surfaces and furniture. With Nordic Swan certification.	NEW @eco!perform			pH: 9.6	51	•		6.296-086.0	
	SurfacePro Surface Cleaner CA 30 R	Maintenance cleaning		undiluted	slightly alkaline	0.5 I		12	6.295-686.0	
	ecolperform Ready-to-use surface cleaner for manual application. Dries quickly and streak-free. Pack of 12 bottles including 2 spray heads. Up to 40 applications per spray head.	eco!perform			pH: 8.6					
N	SurfacePro Surface Cleaner CA 30 R eco!perform Swan With Nordic Swan certification: Surface-	Maintenance cleaning		undiluted	slightly alkaline pH: 8.6	0.5 1	•	12	6.296-087.0	
T.	Pro Surface Cleaner CA 30 R. Ready- to-use, fast and streak-free drying, for manual application (12 bottles, incl. 2 spray heads).	NEW eco!perform								
	SurfacePro RAG Classic Multi-Purpose Cleaner The gentle RAG multi-purpose cleaner with an active fresh fragrance is ideal	Manual - maintenance cleaning		0.2-3 %	neutral pH: 7.5	10	•		3.334-083.0	

[■] Nitrilotriacetate-free (NTA-free).

	Product description	Application	Primary mixture	Dosage	Properties	Packagi size	ng	PH	Order no./ quantity	Price
urface - Intern	mediate cleaning	Аррисаціон	IIIIXCOTC	Dosage	rioperties	3120			quantity	
	SurfacePro Cleaner, alkaline Induflex Induflex alkaline cleaner, specially developed for removing grease and other organic deposits. For manual and mechanical cleaning of surfaces and floor coverings.	Deep cleaning Intermediate cleaning Maintenance cleaning		10-20 % 2-5 % 0.5-1 %	alkaline pH: 13.3	10	•	1	3.334-021.0	
	SurfacePro Scouring Agent Inoxal Inoxal ready-to-use liquid scouring agent. For removing adhesive deposits on waterproof surfaces such as chrome-plated steel, ceramic, porcelain and plastic.	Maintenance cleaning		undiluted	neutral pH: 7	500 ml 10 l	:	12	3.334-040.0 3.334-039.0	
T MIN	Universal Stain Remover RM 769 Universal Stain Remover RM 769 for all textile coverings, upholstery and hard surfaces – removes oil, tar, shoe polish, adhesive, etc., from solvent-resistant surfaces.	Manual		undiluted		500 ml	•	6	6.295-490.0	
as - Intermed	liate cleaning									
400	SurfacePro Sural Glass and Surface	Maintenance cleaning		undiluted	slightly alkaline	500 ml		12	3.334-038.0	
	Cleaner Gently and efficiently removes even very oily and greasy soiling: our ready- to-use Sural glass and surface cleaner. Also perfect for eliminating finger marks and dust.				pH: 9	10	•	1	3.334-037.0	
-	SurfacePro Glass Cleaner CA 40 R	Maintenance cleaning		undiluted	neutral	0.5		12	6.295-687.0	
	ecolperform Ready-to-use glass cleaner - also suitable for plastic surfaces. Dries quickly and streak-free. Pack of 12 bottles including 2 spray heads. Up to 40 applications per spray head.	eco!perform			pH: 5.2	51	•	2	6.295-688.0	
-	SurfacePro Glass Cleaner CA 40 R	Maintenance cleaning		undiluted	neutral	0.5 l			6.296-088.0	
J. J. Const.	ecolperform Swan Ready-to-use SurfacePro Glass Cleaner CA 40 R suitable for glass and plastic surfaces with Nordic Swan certification. Fast, streak-free drying (unit with 12 bottles).	NEW ecolperform			pH: 5.2	5 I	•		6.296-089.0	
	SurfacePro RGR Classic Glass and Surface Cleaner RGR Classic, the alcohol-based glass cleaner, removes grease, smears, rust and fingerprints from shiny, varnished, polished and all other washable surfac- es, without leaving any streaks.	Maintenance cleaning		undiluted undiluted	slightly alkaline pH: 10.5	10	•		3.334-090.0	
lass – Deep cle	eaning									
	SurfacePro Glasal Glass Cleaner High-strength Glasal concentrated glass cleaner. Excellent cleaning performance and high dirt removal capacity. For washing glass surfaces, good adhesive properties and leaves no streaks.	Manual - window cleaning		0.1-0.5 %	neutral pH: 7.3	10	•		3.334-035.0	

■ Nitrilotriacetate-free (NTA-free).

	Product description	Packaging size	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
pty contair	· · · · · · · · · · · · · · · · · · ·		(2.11.1)			4	
	SurfacePro empty bottle,	0.5	65 × 65 × 225 mm		12	6.295-715.0	
	Surface Cleaner CA 30 C-D eco!perform						
	Labelled empty bottle, reusable,						
N.L.	for individual dosing of ready-to-use						
400	surface cleaner from concentrate.						
100	Economical and environmentally						
	friendly.						

	Product description	Pressure	Dosing range	Dispensing volume	Extendable	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Dilution device	s									
A	Dosing head Easy-to-use dosing head for precise and efficient cleaning agent dosing. Head fits on all 1 I concentrate bottles.		5-20 ml			310 × 35 × 35 mm	0.015 kg	12	6.295-724.0	
blo	DS 2 Dosing Unit DVGW-certified dosing unit for filling floor cleaning machines and buckets and for preparation of HD/HDS primary mixtures. Includes backflow preventer according to DIN EN 1717.	1.7-3.5 bar	0.3-25 %	14 l/min	•	355 × 300 × 210 mm	1.86 kg	1	6.394-653.0	
09	DS 3 Cleaning Agent Dosing Station After connecting to a tap, cleaning agent can be added to the fresh water tank and diluted as required. Can also be used with the filling system attach- ment kit. Includes backflow preventer (DIN EN 1717).	2-6 bar	0.2-13.5 %	15 l/min	•	390 × 390 × 150 mm	3.85 kg	1	2.641-811.0	

	Product description	Suitable for bulk size	Dimensions (L × W × H)	Weight		Order no./ quantity	Price
Dispensing aid	Sprayer, blue Durable spray head for CA 30 R Surface Cleaner, ready-to-use. With 3-finger trigger and adjustable, uniform spraying pattern. For minimum 15,000 actua- tions (40 × 0.5 I bottles).		120 × 90 × 35 mm	0.037 kg	12 (6.295-723.0	
=	Container valve, 5 I Practical aid for efficient filling and dosing of cleaning agents from containers.	5	85 × 48 × 40 mm	0.02 kg	1 6	6.394-819.0	

	Product description	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Sales tools						
	Premium demo case Robust demonstration case with many storage options, convenient large open- ing, telescopic handle and smooth-run- ning castors. Ideal for all utensils for cleaning agent demonstrations.	44 × 30 × 44 cm	4.5 kg	1	6.999-247.0	
	Starter set for Premium demo case		2 kg	1	2.200-006.0	-
	Starter set for Premium demo case: Basic and safety equipment for demonstrations and applications of cleaning agents. Incl. pH measurement, cloths, brushes, cutter and scraper.					
	Refill set for Premium demo case		1.5 kg	1	2.200-007.0	
Ų,	Refill set for Premium demo case. Incl. all consumables from the starter set such as Ph measuring strips, cloths, brushes, cutter, blades, scraper, gloves, bin liners.					
	Clean Card		0,1 kg	1	6.999-313.0	
	25 Clean Cards for the detection of dirt containing protein and surfactants from cleaning agent or disinfectant residues on visibly clean surfaces. For hygienically sensitive areas.					

Properties

SanitPro - PEAK PERFORMANCE IN SANITARY FACILITIES

With our specially designed cleaning agents, you'll be all set for perfectly hygienic cleaning in sensitive sanitary facilities. Lime deposits, urine scale, grease and soap residue as well as other stubborn dirt stand no chance against this cleaning power - they are completely removed without damaging materials at all. The result is hygienic cleanliness that you can both see and smell. You can choose between a fresh or discreet scent.













1 Unique diversity

With our innovative, complete product range for manual cleaning, you have all the options from WC cleaning to surface cleaning. Colour-coding and language-neutral labels clearly indicate the right application.

2 Consistent sustainability

Kärcher is a member of the sustainability initiative Association for Soaps, Detergents and Maintenance Products in Europe (AISE). All products in our green cleaning agent range carry the EU Ecolabel - EU Flower - and the Austrian Ecolabel. Our advanced formulas improve effectiveness and are also eco-friendly - from production to wastewater treatment. Concentrates reduce packaging. And the spray heads are reusable.

3 Easy-to-clean effect

The water repellent effect on fittings and surfaces prevents dirt adhesion and lime stains and makes subsequent cleaning easy.

4 Powerful and safe

Thanks to their innovative acids, our products set standards when it comes to the tricky task of sanitary cleaning. They always achieve optimum cleaning performance while keeping surfaces streak-free.

5 Good and safe handling

The optimised form and function of our spray heads and bottles offer you exemplary user-friendliness and ergonomics. The 0.5 litre spray bottles are easy to handle even during long periods of use, the spray heads fit comfortably in the hand and can be operated with up to three fingers. The variable foam nozzle prevents aerosol formation and increases work safety.

Product	~~	ivity	'	301	IIIIg			Ap	Pilca	LIOII	ai ea				FIU	pert						Page
	Maintenance cleaning	Intermediate cleaning	aning	Oll, grease, protein, body fat	Limescale, rust, urine scale, cement	Ink, biro/felt tip pen, adhesives	fungi, viruses	t, PE, PU, epoxy resin			, screed	Fine stone, unglazed	Ceramic, tiles, granite, porphyry	terrazzo	Very low foaming	Highly streak-free / shine-enhancing	Odour-absorbent	Blankets the smell	rm of a gel		wan	
	Maintena	Intermed	Deep cleaning	Oil, greas	Limescal	Ink, biro/	Bacteria,	PVC, PUR,	Linoleum	Rubber	Concrete, screed	Fine stor	Ceramic,	Marble, terrazzo	Very low	Highly s	Odour-a	Blankets	In the form of	Ecolabel	Nordic Swan	
SanitPro WC Cleaner Tolisan	Maintena	Intermed	Deep cle	Oil, greas	■ Limescal	Ink, biro/	Bacteria,	PVC, PUR	Linoleun	Rubber	Concrete	Fine stor	■ Ceramic,	Marble, 1	Very low	Highly S	Odour-a	Blankets	√ In the fo	Ecolabel	Nordic S	862
SanitPro WC Cleaner Tolisan SanitPro WC and Deep Cleaner CA 10 C eco!perform	Ш.	Intermed	Deep cle	■ Oil, greas		Ink, biro/	Bacteria,	PVC, PUR	Linoleun	Rubber	Concrete	Fine stor		Marble, 1	Very low	Highly S	Odour-a	Blankets		▼ Ecolabel	Nordic S	862 862
		Intermed	Deep cle		•	Ink, biro/	Bacteria,	PVC, PUR	Linoleun	Rubber	Concrete	Fine stor	•	Marble, 1	Very low	Highly S	Odour-a	Blankets	V		Nordic S	
SanitPro WC and Deep Cleaner CA 10 C eco!perform	-	Intermed	Deep cle	•	-	Ink, biro/	Bacteria,	PVC, PUR	Linoleun	Rubber	Concrete	■ Fine stor	•	Marble, 1	Very low	Highly S	Odour-a	Blankets	v v			862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan			Deep cle	•		Ink, biro/	Bacteria,	■ PVC, PUR	Linoleun	Rubber	Concrete		•	■ Marble, 1	Very low	✓ Highly Si	Odour-a	♦ Blankets	v v			862 862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan SanitPro Maintenance Cleaner Allsan			Deep cle	•		Ink, biro/	Bacteria,						•		Very low		Odour-a		v v			862 862 862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan SanitPro Maintenance Cleaner Allsan Perfumed Cleaner Citral	- - - -		Deep cle		=	Ink, biro/	Bacteria						•		Very low	<i>V</i>	Odour-a		v v	<i>'</i>		862 862 862 862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan SanitPro Maintenance Cleaner Allsan Perfumed Cleaner Citral SanitPro Daily Cleaner CA 20 C eco!perform	1 1 1 1		Deep cle			Ink, biro/	Bacteria,						•		Very low	V V	Odour-a		v v	<i>'</i>	v	862 862 862 862 862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan SanitPro Maintenance Cleaner Allsan Perfumed Cleaner Citral SanitPro Daily Cleaner CA 20 C eco!perform SanitPro Daily Cleaner CA 20 C eco!perform Swan	8 8 9 9		Deep cle		-	Ink, biro/	Bacteria						•		Very low	V V	Odour-a		v v	v 	v	862 862 862 862 862 862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan SanitPro Maintenance Cleaner Allsan Perfumed Cleaner Citral SanitPro Daily Cleaner CA 20 C eco!perform SanitPro Daily Cleaner CA 20 C eco!perform Swan SanitPro Daily Cleaner CA 20 R eco!perform			Deep cle			Ink, biro/	Bacteria								Very low	V V	Odour-a		v v	v 	v v	862 862 862 862 862 862 862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan SanitPro Maintenance Cleaner Allsan Perfumed Cleaner Citral SanitPro Daily Cleaner CA 20 C eco!perform SanitPro Daily Cleaner CA 20 C eco!perform Swan SanitPro Daily Cleaner CA 20 R eco!perform SanitPro Daily Cleaner CA 20 R eco!perform			Deep cle		-	Ink, biro/	Bacteria								Very low	V V	Odour-a	<i>y</i>	v v	v 	v v	862 862 862 862 862 862 862 862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan SanitPro Maintenance Cleaner Allsan Perfumed Cleaner Citral SanitPro Daily Cleaner CA 20 C eco!perform SanitPro Daily Cleaner CA 20 C eco!perform Swan SanitPro Daily Cleaner CA 20 R eco!perform SanitPro Daily Cleaner CA 20 R eco!perform SanitPro Daily Cleaner CA 20 R eco!perform Swan SanitPro Scented Cleaner RSD Classic			Deep cle		-	Ink, biro/	Bacteria						1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		Very low	V V	✓ Odour-a	<i>y</i>	v v	v 	v v	862 862 862 862 862 862 862 862 862
SanitPro WC and Deep Cleaner CA 10 C eco!perform SanitPro WC Cleaner CA 10 C eco!perform Swan SanitPro Maintenance Cleaner Allsan Perfumed Cleaner Citral SanitPro Daily Cleaner CA 20 C eco!perform SanitPro Daily Cleaner CA 20 C eco!perform Swan SanitPro Daily Cleaner CA 20 R eco!perform SanitPro Daily Cleaner CA 20 R eco!perform SanitPro Daily Cleaner CA 20 R eco!perform Swan SanitPro Scented Cleaner RSD Classic SanitPro Deep Cleaner Unisan Plus			Deep cle		-	Ink, biro/		•	•	•	•		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		✓ Very low	V V		<i>y</i>	v v	v 	v v	862 862 862 862 862 862 862 862 862 863

Activity Soiling

Application area

■ NEW ■ usable □ usable subject to conditions

	Product description	Application	Primary mixture	Dosage	Properties	Packagir size	ng	PU	Order no./ quantity	Price
C - Maintena										
2	SanitPro Tolisan WC Cleaner Tolisan ready-to-use, gel-forming toilet cleaning agent for thorough removal of	Maintenance cleaning		undiluted	acidic pH: 0.8	750 ml	•	15	3.334-043.0 3.334-041.0	
II.	lime and urine scale deposits in toilets and urinals.									
-	SanitPro WC and Deep Cleaner CA 10 C			undiluted	acidic	1			6.295-677.0	
	ecolperform Active, viscous deep cleaning concentrate with fresh fragrance for manual cleaning of soiled sanitary surfaces. Developed with a special gel formula for better adherence to vertical surfaces, for example in toilets and urinals.	Deep cleaning eco!perform		10-100 %	рН: 0.6	51	•	2	6.295-678.0	
	SanitPro WC Cleaner CA 10 C	Maintenance cleaning		undiluted	acidic	1		12	6.296-080.0	
-	eco!perform Swan Active, viscose SanitPro WC Cleaner				pH: 2	5 I		2	6.296-081.0	
	CA 10 C with fresh fragrance for manual cleaning. Adheres well to upright areas of toilets and urinals. With Nordic Swan certification.	NEW eco!perform								
rface - Maint	enance cleaning									
	SanitPro Allsan Everyday Cleaner Our everyday cleaner ensures clean-	Intermediate cleaning Maintenance cleaning		4-5 % 1-2 %	slightly acidic pH: 5	101	<u>: </u>	12	3.334-047.0	
Highline	liness and reliably preserves valuable sanitary fittings at the same time. In addition, regular use effectively prevents the build up of lime deposits.	maniterance dealing		1 2 %	рн. <i>3</i>	101	•	1	3.334-046.0	
-										
and I	Citral Perfumed Cleaner With Citral, our pleasantly fragrant	Intermediate cleaning Maintenance cleaning		1-2 % 0.5-1 %	slightly alkaline pH: 8.7	10	-	12	3.334-032.0	
	everyday cleaner, you can remove soiling from all washable surfaces and furnishings both gently and thoroughly.					101	_	1	3.334-031.0	
	SanitPro Daily Cleaner CA 20 C	Maintenance cleaning		1-8 %	slightly acidic	1	•	12	6.295-679.0	
	ecolperform Eco-friendly sanitary everyday cleaner with gentle cleaning action. Ideal for everyday cleaning of sanitary facilities.	eco!perform			pH: 2.1	51	•	2	6.295-680.0	
	SanitPro Daily Cleaner CA 20 C	Maintenance cleaning		1-8 %	slightly acidic	1	•	12	6.296-082.0	
	ecolperform Swan Gentle cleaning action, environmental- ly-friendly: SanitPro Everyday Cleaner CA 20 C. Ideal for everyday cleaning of sanitary facilities. With Nordic Swan certification.	NEW @ eco!perform			pH: 2.1	51	•	2	6.296-083.0	
	SanitPro Daily Cleaner CA 20 R	Maintenance cleaning		undiluted	slightly acidic	0.5		12	6.295-685.0	
	ecolperform Ready to use sanitary everyday cleaner. Gentle cleaning action, environmentally- friendly. Pack of 12 bottles including 2 spray heads. One spray head is sufficient for up to 40 applications.	eco!perform			рН: 2.1					
	SanitPro Daily Cleaner CA 20 R	Maintenance cleaning		undiluted	slightly acidic	0.5		12	6.296-084.0	
	ecolperform Swan Ready-to-use SanitPro Everyday Cleaner CA 20 R with Nordic Swan certification. Gentle cleaning action and environmentally friendly (unit with 12 bottles, incl. 2 spray heads).	NEW @ecolperform			pH: 2.1					
	SanitPro Scented Cleaner RSD Classic Ideal for daily cleaning of all acid- resistant surfaces and furnishings in swimming pools, toilet facilities and	Deep cleaning Maintenance cleaning		undiluted 0.5-1 %	acidic pH: 1.5	10	•	1	3.334-093.0	

■ Nitrilotriacetate-free (NTA-fre	e).
-----------------------------------	-----

	Product description	Application	Primary mixture	Dosage	Properties	Packag size	ing	PU	Order no./ quantity	Price
rface - Intern	nediate cleaning									
	SanitPro Unisan Plus Deep Cleaner	Deep cleaning		5-20 %	acidic	1 l		12	3.334-045.0	
HARRING I	Unisan Plus concentrated deep cleaner with a fresh fragrance for manual deep cleaning of soiled sanitary surfaces and for the removal of stubborn lime deposits.	Maintenance cleaning		1-5 %	pH: 1.11	10	•	1	3.334-044.0	
*	SanitPro Urisan Deodoriser Urisan deodoriser uses the microbio-	Scrubber-driers - deep cleaning		3 %	slightly alkaline pH: 8.7	1	•	12	3.334-010.0	
	logical decomposition of unpleasant odorants to eliminate the smell of urine	Scrubber driers - maintenance cleaning		0.8-1.5 %						
	in highly frequented sanitary facilities. For daily maintenance cleaning.	Manual - maintenance cleaning		0.4 %						
-	FloorPro Deep Cleaner, acidic RM 751	Deep cleaning		5-25 %	acidic	2.5 I		4	6.295-586.0	
	Acidic deep cleaner for floor cleaners.	Maintenance cleaning		1-5 %	pH: 0.7	10 I		1	6.295-129.0	
	Effectively removes cement film, deposits and residue, e.g. limescale, rust, beer or milk residues. Ideal for final cleaning on building sites.	Manual		0.5-1 %		200	•	1	6.295-130.0	
	SanitPro RSA Classic Deep Cleaner	Deep cleaning		undiluted	acidic	10		1	3.334-097.0	
	RSA Classic sanitary cleaning agent with fresh scent for intensive cleaning of all acid-resistant surfaces and facilities in swimming pools, toilets and sanitary facilities.	Maintenance cleaning		0.5-1 %	pH: 1					

	Product description	Packaging size	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
ty contain	ners						
• 120	SanitPro empty bottle, Everyday Cleaner CA 20 C-D Eco Labelled empty bottle, reusable, for individual dosing of ready to use sanitary everyday cleaner from concen- trate. Economical and environmentally friendly.	0.5	65 × 65 × 225 mm		12	6.295-714.0	

	Product description	Pressure	Dosing range	Dispensing volume	Extendable	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Dilution devices	5									
1	Dosing head Easy-to-use dosing head for precise and efficient cleaning agent dosing. Head fits on all 1 concentrate bottles.		5-20 ml			310 × 35 × 35 mm	0.015 kg	12	6.295-724.0	
bla	DS 2 Dosing Unit DVGW-certified dosing unit for filling floor cleaning machines and buckets and for preparation of HD/HDS primary mixtures. Includes backflow preventer according to DIN EN 1717.	1.7-3.5 bar	0.3-25 %	14 l/min	•	355 × 300 × 210 mm	1.86 kg	1	6.394-653.0	
090	DS 3 Cleaning Agent Dosing Station After connecting to a tap, cleaning agent can be added to the fresh water tank and diluted as required. Can also be used with the filling system attach- ment kit. Includes backflow preventer (DIN EN 1717).	2-6 bar	0.2-13.5 %	15 l/min	•	390 × 390 × 150 mm	3.85 kg	1	2.641-811.0	

	Product description	Suitable for bulk size	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Dispensing aids	1						
*	Sprayer, red with foam nozzle Durable spray head including foam nozzle for CA 20 R Sanitary Everyday Cleaner, ready to use. With 3-finger trigger and adjustable, uniform spraying pattern. Sufficient for 40 applications.	0.5	120 × 90 × 35 mm	0.037 kg	12	6.295-722.0	
۵	Spray nozzle, red Practical aid for application of ready to use sanitary everyday cleaner for wide area coverage. Spraying pattern can be adjusted in combination with the red sprayer.		17 × 15 × 15 mm	3 g	12	6.295-725.0	
*	Container valve, 5 I Practical aid for efficient filling and dosing of cleaning agents from containers.	5	85 × 48 × 40 mm	0.02 kg	1	6.394-819.0	

	Product description	Suitable for bulk size	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Sales tools							
	Premium demo case Robust demonstration case with many storage options, convenient large open- ing, telescopic handle and smooth-run- ning castors. Ideal for all utensils for cleaning agents demonstrations.		44 × 30 × 44 cm	4.5 kg	1	6.999-247.0	
	Starter set for Premium demo case			2 kg	1	2.200-006.0	
	Starter set for Premium demo case: Basic and safety equipment for demon- strations and applications of cleaning agents. Incl. pH measurement, cloths, brushes, cutter and scraper.						
	Refill set for Premium demo case			1.5 kg	1	2.200-007.0	
1	Refill set for Premium demo case. Incl. all consumables from the starter set such as Ph measuring strips, cloths, brushes, cutter, blades, scraper, gloves, bin liners.						
	Clean Card			0.1 kg	1	6.999-313.0	
	25 Clean Cards for the detection of dirt containing protein and surfactants from cleaning agent or disinfectant residues on visibly clean surfaces. For hygienically sensitive areas.						

FloorPro - POWERFUL AND RELIABLE SUCCESS

Kärcher FloorPro cleaning agents are highly effective and excellent cleaning results are achieved in the shortest time with less effort. In the Kärcher cleaning system, machines, accessories and cleaning agents are perfectly matched. This makes work easier, faster and more convenient. At the same time, optimal protection of the cleaning machines and surfaces to be cleaned is an added benefit.











1 Concentrated cleaning performance

We want you to get the best possible cleaning result in combination with a very high area performance in every application. Economical consumption of cleaning agents is a deciding factor here. We develop and produce our cleaning agents in concentrations with which you can clean in doses from 0.25 percent. The user's safety is also very important to us, which is why you also find cleaning agents without a hazard designation in the Kärcher system.

2 Machine protection included

Cleaning agents should remove dirt completely and at the same time protect the machines and tools used. We adapt the contents of our cleaning agents perfectly to the materials of the cleaning machines. Through extreme material tests and long-term testing we ensure that seals, wheels, surfaces, etc., are not damaged. For you, this means: with our machines, accessories and cleaning agents in the Kärcher system you also have the safest and most efficient solutions in the long term.

3 Easy and efficient application

Highly developed Kärcher cleaning agents for scrubber driers combine high cleaning performance with low foam formation in the water tank. Exemplary low foam formulas allow easy and efficient processing. The entire waste water tank volume can be used and the intervals between emptying are longer.

4 Precise and reliable dosing

Dose, the integrated cleaning agent dosing unit from Kärcher, enables, in addition to reliable and precise dosing, quick and easy opening and closing as well as cleaning agent dosing control from 2.5 I and 10 I Kärcher containers. No more inconvenient manual dosing. No overdosing. Changing between different cleaning agents can take place quickly without wasting unused cleaning agent. This saves costs. At the same time, the tank stays clean and free from microbial load through cleaning agent residue.

Product		Act	tivit	у				ı	ı	So	iling						Ap	plica	tior	are	a			Pro	opei	rties	ı		ı			Pag
		Stain removal	Maintenance cleaning	Intermediate cleaning	Deep cleaning	Disinfection	Maintenance care	Intermediate care	Care, protection	Oil, grease, soot, wax, protein, road dirt	Rubber wear, heel marks and footprints	Limescale, rust, urine scale, cement	Ink, biro/felt tip pen, adhesives	Foam reduction	Bacteria, fungi, viruses	Care/protective film (polymer and wax coatings)	PVC, PUR, PE, PU, epoxy resin	Linoleum	Rubber	Concrete, screed	Fine stone, unglazed	Ceramic, tiles, granite, porphyry	Marble, terrazzo	Surfactant-free	High wetting ability (special surfactant mixture)	Very low foaming	Highly streak-free / shine-enhancing	Anti-slip DIN 51131, DIN EN 13893, sports halls DIN EN 14904	Anti-slip, sports halls DIN EN 18032	Ecolabel	Nordic Swan	
FloorPro Tyre and Abrasion	1										•									•	•	•										81
Trace Remover RM 776													_						_	-												-
Universal Stain Remover RM 769	- -	•								_			•						-	_	•	_										8
FloorPro Multi Cleaner RM 756	\parallel		Н																					-	~	H .						8
FloorPro Fine Stoneware Cleaner RM 753	4					L				-											•			~		~						8
All-purpose Cleaner Tefral			Ц			-											Ц	Ц	Ц	П		Ц		~		~						8
FloorPro Cleaner CA 50 C eco!perform	_		Ц			\vdash												Ц			_					~	~			~		8
FloorPro Cleaner CA 50 C eco!perform Swan										•									•		•	•				-	-				-	8
FloorPro Everyday Cleaner Solisal Classic	Ш																															8
FloorPro Wipe Care Extra RM 780	4																П	П									~		~			8
FloorPro Wipe Care RM 746	4		◨		╙	╙	•			•									◨							╙					Щ	8
FloorPro Spray Cleaner RM 748																																8
FloorPro Industrial Cleaner RM 69	•			•						•																~						8
FloorPro Deep Cleaner RM 69																																8
FloorPro Deep Cleaner RM 69 eco!efficiency				•																		•										8
FloorPro Shine Cleaner RM 755																										V	V					8
FloorPro Industrial Cleaner RIR Classic	\exists			•						•									•	•						~						8
FloorPro Intensive Deep Cleaner Extra RM 752					•					•							•			•	•	•										8
FloorPro Allround Deep Cleaner RM 754										•																						8
PressurePro Intensive Deep Cleaner RM 750					•					П							•			•	•	•										8
FloorPro Deep Cleaner, acidic RM 751												•																				8
FloorPro Escalator Cleaner, neutral RM 758					•					П																						8
Foam Blocker RM 761			П											П																		8
Disinfectant Cleaner RM 732	\dashv		H		Ē					П				_	П		П	П	П			П	П									8
Disinfectant Cleaner KM 732	\dashv									Ē					Ħ								\vdash									8
FloorPro Protect Dispersion Extra									•						_		•	•		-		_						V	PVC			8
RM 782							-	_	-									_										-				-
FloorPro Care Dispersion RM 784							•	•	H														П					~				8
FloorPro Crystallising Agent RM 749																																

■ NEW ■ usable □ usable subject to conditions

867

	Product description	Application	Primary mixture	Dosage	Properties	Packagi size	ng	PU	Order no./ quantity	Price
Stain removal										
-	FloorPro Tyre and Abrasion Marks	Deep cleaning		40 ml/m ²	alkaline	10		1	6.295-545.0	
-	Remover RM 776				pH: 13.3	20 I		1	6.295-546.0	
-	Highly active special cleaner for remov- ing rubber abrasion marks and marks					200 I		1	6.295-572.0	
-	caused by forklift trucks. Also effective-									
1	ly removes stubborn oil and soot									
	contamination as well as polymer and									
	wax coatings. Adhesive tape residue is									
	efficiently removed.									
-	Universal Stain Remover RM 769	Manual		undiluted		500 ml		6	6.295-490.0	
73	Universal Stain Remover RM 769 for all									
- 6	textile coverings, upholstery and hard									
-	surfaces - removes oil, tar, shoe polish, adhesive, etc., from solvent-resistant									
120	surfaces.									
aintenance cle	eaning FloorPro Multi Cleaner RM 756	Manual - maintenance		0.25-1 %	slightly alkaline	1		12	6.295-913.0	
	High wetting ability, universal and very			0.25-1 %	pH: 9	2.5 I		4	6.295-915.0	
	economical: RM 756 FloorPro Multi	Scrubber driers -				10 I		1	6.295-914.0	
	Everyday Cleaner for mechanical and manual cleaning of floors and surfaces.	maintenance cleaning								
	manual cleaning of moors and sorraces.									
	FloorPro Fine Stoneware Cleaner	Deep cleaning		5-20 %	slightly alkaline	2.5 l	• 4	4	6.295-587.0	
0	RM 753	Maintenance cleaning		3-5 %	pH: 10.5	10 I		1	6.295-082.0	
=	Special cleaner for all fine stoneware	Manual		3 %						
#T 97	tiles. Reliably dissolves oil, grease and mineral soiling. Does not impair an-									
	ti-slip properties of tiles. Free from									
	tensides and readily separating.									
	Tefral Multi-Purpose Cleaner	Maintenance cleaning		1-2 %	neutral	10 I		1	3.334-028.0	
Siller.	Surfactant-free Tefral multi-purpose				pH: 7					
-	cleaner. Odourless and designed for use									
	in both manual and mechanical mainte-									
1	nance cleaning of all water-resistant surfaces.									
	30114003.									
	FloorPro Cleaner CA 50 C eco!perform	Maintenance cleaning		0.3-1 %	neutral	1		12	6.296-053.0	
Clar	FloorPro Cleaner CA 50 C: Floor cleaner				pH: 7.4	5 I		2	6.296-054.0	
1 500	for manual and mechanical application on all hard and flexible floors. Also suit-	(\emptyset)								
12.0	able for high-gloss surfaces and furni-	eco!perform								
	ture. With EU eco label certification.									
	FloorPro Cleaner CA 50 C eco!perform	Maintenance cleaning		0.3-1 %	neutral	1	-	12	6.296-092.0	
-	Swan				pH: 8	5 I		2	6.296-093.0	
11-3	FloorPro Cleaner CA 50 C floor cleaner	NEW Ø								
141	for manual and machine cleaning of	eco!perform								
	hard and flexible floors, as well as for high-gloss surfaces and furniture.	- cco:periorili								
	With Nordic Swan certification.									
-	FloorPro Solisal Classic Deep Cleaner	Maintenance cleaning		0.5-1 %	neutral	10 l		1	3.334-022.0	
	Solisal neutral universal cleaner for	Intermediate cleaning		2-5 %	pH: 6.4					
180										
-	manual and mechanical cleaning of all									

- 5) Included in the VAH list of disinfectants of 1 April 2012 (mhp Verlag GmbH Wiesbaden).
 6) Included in the IHO list of disinfectants for animal husbandry.
- Nitrilotriacetate-free (NTA-free).
- ▲ Easily separable in oil separator systems (ASF).

	Product description		Primary mixture Dosage	Properties	Packagi size	ing	PU	Order no./ quantity	Pri
laintenance cl	eaning and care								
	FloorPro Wipe Care Extra RM 780	Maintenance cleaning	0.5-2 %	slightly alkaline	2.5 I		4	6.295-580.0	
	Powerful cleaning and care agent for	Manual	1-3 %	pH: 9	10 I		1	6.294-997.0	
-	maintenance cleaning of all water-re-				20		1	6.295-468.0	
-	sistant hard and resilient floors and								
1	coverings. Specially suited for gyms and								
	multi-purpose halls, as expert report in								
	accordance with DIN V 18032-2:2001-								
	04 concerning anti-slip properties is available. Wipe Care Extra RM 780								
	dries streak-free.								
	uries streak-free.								
		Matakasasasalasatas	4.20	- Palatina Barbara	101			6 205 456 0	
-	FloorPro Wipe Care RM 746 Active neutral soap cleaner. Produces	Maintenance cleaning Manual	1-3 % 1-3 %	slightly alkaline pH: 9.2	10		1	6.295-156.0	
	an anti-slip and dirt-repellent care film.	Walloal	1 3 %	pri. 3.2					
Guerra	Polishes very easily. Produces a gleam-								
	ing high-gloss finish.								
	FloorDro Care Dispossion PM 794	Coating	undiluted	neutral	51		2	6 205 017 0	
	FloorPro Care Dispersion RM 784 Polymer dispersion for initial, interim	Spray Cleaner	20-30 %	pH: 7.6	5 I			6.295-817.0	
1-	and maintenance care of floor cover-	Wipe restoration	30-50 %	pri. 7.0					
1	ings. Forms an anti-slip, dirt-repellent	Wipe care	1-3 %						
= 0	and abrasion-resistant protective film.								
1	High covering power.	FIGA							
		tested							
		San Cross II							
ermediate cl	eaning and care (e.g. with a spray cleaner	or mop)							
	FloorPro Spray Cleaner RM 748	Cleanern	5 ml/m²	slightly alkaline	10 I		1	6.295-162.0	
	Wax-based slip-resistant spray emul-			pH: 8.5					
1=	sion for all coated hard surfaces. Re-								
1	pairs and restores coated floors. Re-								
HE W	moves heel marks and footprints, while								
	applying a anti-slip finish.								
	FloorPro Care Dispersion RM 784	Coating	undiluted	neutral	5 I		2	6.295-817.0	
	Polymer dispersion for initial, interim	Spray Cleaner	20-30 %	pH: 7.6					
-	and maintenance care of floor cover-	Wipe restoration	30-50 %						
1	ings. Forms an anti-slip, dirt-repellent	Wipe care	1-3 %						
1=0	and abrasion-resistant protective film.	FIGA							
	High covering power.	tested							
	High covering power.	teste							
ermediate cl		(East)							
ermediate cl	eaning FloorPro Industrial Cleaner RM 69	Maintenance cleaning	0.5-3 %	slightly alkaline	2.5	■ ▲	. 4	6.296-058.0	
ermediate cl	eaning FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69	Maintenance cleaning Intermediate cleaning	0.5-3 % 3-10 %	slightly alkaline pH: 10.3	2.5 I 10 I		_	6.296-058.0 6.296-049.0	
ermediate cl	eaning FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial						1	-	
ermediate cl	eaning FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of	Intermediate cleaning			10 I 20 I		1	6.296-049.0 6.296-050.0	
ermediate cl	FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral				10 l		1 1	6.296-049.0	
ermediate cl	FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination.	Intermediate cleaning NEW			10 I 20 I 200 I		1 1	6.296-049.0 6.296-050.0 6.296-051.0	
ermediate cl	FloorPro Deep Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination.	NEW Maintenance cleaning	3-10 %	pH: 10.3	10 l 20 l 200 l 1000 l		1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0	
ermediate cl	FloorPro Deep Cleaner RM 69 PloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes	Intermediate cleaning NEW	3-10 %	pH: 10.3	10 I 20 I 200 I 1000 I		1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0	
ermediate cl	FloorPro Deep Cleaner RM 69 Powerful cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral	NEW Maintenance cleaning	3-10 %	pH: 10.3	10 l 20 l 200 l 1000 l		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0	
ermediate cl	FloorPro Deep Cleaner RM 69 PloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes	NEW Maintenance cleaning	3-10 %	pH: 10.3	10 I 20 I 200 I 1000 I 2.5 I 10 I		1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0	
ermediate cl	FloorPro Deep Cleaner RM 69 Powerful cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral	NEW Maintenance cleaning	3-10 %	pH: 10.3	20 I 200 I 1000 I 2.5 I 10 I 20 I		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0	
ermediate cl	FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral soiling from floors and industrial floors.	NEW Maintenance cleaning Intermediate cleaning	0.5-3 % 3-10 %	pH: 10.3 alkaline pH: 12.1	20 l 200 l 1000 l 2.5 l 10 l 200 l 200 l		4 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0 6.295-416.0 6.295-123.0	
ermediate cl	FloorPro Deep Cleaner RM 69 FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral soiling from floors and industrial floors. FloorPro Deep Cleaner RM 69 ecoleffi-	NEW Maintenance cleaning Intermediate cleaning Scrubber-driers -	3-10 %	alkaline pH: 12.1	20 I 200 I 1000 I 2.5 I 10 I 20 I 200 I 1000 I		4 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0 6.295-416.0 6.295-123.0	
ermediate cl	FloorPro Deep Cleaner RM 69 Powerful cleaner RM 69 FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral soiling from floors and industrial floors. FloorPro Deep Cleaner RM 69 ecoleffi- ciency	NEW Maintenance cleaning Intermediate cleaning Scrubber-driers - deep cleaning (ecolefficiency)	0.5-3 % 3-10 %	pH: 10.3 alkaline pH: 12.1	200 l 200 l 200 l 1000 l 2.5 l 200 l 200 l 200 l 1000 l		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0 6.295-416.0 6.295-123.0 6.295-650.0 6.295-650.0	
ermediate cl	FloorPro Deep Cleaner RM 69 Powerful cleaner RM 69 FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral soiling from floors and industrial floors. FloorPro Deep Cleaner RM 69 ecoleffi- ciency Powerful cleaning agent for flooring	NEW Maintenance cleaning Intermediate cleaning Intermediate cleaning Scrubber-driers - deep cleaning (ecolefficiency) Maintenance cleaning	3-10 % 0.5-3 % 3-10 % 7-20 % 0.5-1 %	alkaline pH: 12.1	200 200 1000 2.5 10 200 200 1000 2.5 10 2.5 10 2.5		4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0 6.295-416.0 6.295-650.0 6.295-650.0 6.295-651.0 6.295-652.0	
ermediate cl	FloorPro Deep Cleaner RM 69 Powerful cleaner RM 69 FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral soiling from floors and industrial floors. FloorPro Deep Cleaner RM 69 ecoleffi- ciency	Maintenance cleaning Intermediate cleaning Intermediate cleaning Scrubber-driers - deep cleaning (ecolefficiency) Maintenance cleaning Manual	0.5-3 % 3-10 %	alkaline pH: 12.1	200 l 200 l 200 l 1000 l 2.5 l 200 l 200 l 200 l 1000 l		4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0 6.295-416.0 6.295-123.0 6.295-650.0 6.295-650.0	
ermediate cl	FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes Stubborn oil, grease, soot and mineral soiling from floors and industrial floors. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral soiling from floors and industrial floors. FloorPro Deep Cleaner RM 69 ecolefficiency Powerful cleaning agent for flooring and industrial floors effortlessly	NEW Maintenance cleaning Intermediate cleaning Intermediate cleaning Scrubber-driers - deep cleaning (ecolefficiency) Maintenance cleaning	3-10 % 0.5-3 % 3-10 % 7-20 % 0.5-1 %	alkaline pH: 12.1	200 200 1000 2.5 10 200 200 1000 2.5 10 2.5 10 2.5		4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0 6.295-416.0 6.295-650.0 6.295-650.0 6.295-651.0 6.295-652.0	
ermediate cl	FloorPro Deep Cleaner RM 69 Powerful cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral soiling from floors and industrial floors. FloorPro Deep Cleaner RM 69 ecolefficiency Powerful cleaning agent for flooring and industrial floors effortlessly removes stubborn oil, grease, soot	Maintenance cleaning Intermediate cleaning Intermediate cleaning Scrubber-driers - deep cleaning (ecolefficiency) Maintenance cleaning Manual	3-10 % 0.5-3 % 3-10 % 7-20 % 0.5-1 %	alkaline pH: 12.1	200 200 1000 2.5 10 200 200 1000 2.5 10 2.5 10 2.5		4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0 6.295-416.0 6.295-650.0 6.295-650.0 6.295-651.0 6.295-652.0	
ermediate cl	eaning FloorPro Industrial Cleaner RM 69 FloorPro Industrial Cleaner RM 69 for low-foam cleaning of industrial and other floors. Powerful removal of stubborn grease, oil, soot and mineral contamination. FloorPro Deep Cleaner RM 69 Powerful cleaner, effortlessly removes stubborn oil, grease, soot and mineral soiling from floors and industrial floors. FloorPro Deep Cleaner RM 69 ecolefficiency Powerful cleaning agent for flooring and industrial floors effortlessly removes stubborn oil, grease, soot and mineral contamination. With the	Maintenance cleaning Intermediate cleaning Intermediate cleaning Scrubber-driers - deep cleaning (ecolefficiency) Maintenance cleaning Manual	3-10 % 0.5-3 % 3-10 % 7-20 % 0.5-1 %	alkaline pH: 12.1	200 200 1000 2.5 10 200 200 1000 2.5 10 2.5 10 2.5		4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.296-049.0 6.296-050.0 6.296-051.0 6.296-052.0 6.295-582.0 6.295-120.0 6.295-415.0 6.295-416.0 6.295-650.0 6.295-650.0 6.295-651.0 6.295-652.0	

- 5) Included in the VAH list of disinfectants of 1 April 2012 (mhp Verlag GmbH Wiesbaden).
 6) Included in the IHO list of disinfectants for animal husbandry.
- Nitrilotriacetate-free (NTA-free).
- ▲ Easily separable in oil separator systems (ASF).

	Product description	Application	Primary mixture	Dosage	Properties	Packagi size	ing	Pl	Order no./ J quantity	Pric
-	FloorPro Shine Cleaner RM 755	Maintenance cleaning		0.5-1 %	alkaline	2.5 l		4	6.295-846.0	
-U-2	Citrus-fresh low-foam floor shine	Intermediate cleaning		1-5 %	pH: 12	10 l		1	6.295-174.0	
=	cleaner for all hard floors. RM 755					20 I		1	6.295-409.0	
200	dries completely streak-free. Ideal for high-gloss stone floors.					200 I		1	6.295-176.0	
	High gloss stone hours.					1000 I		1	6.295-177.0	
	FloorPro RIR Classic Industrial Cleaner	Intermediate cleaning		1-2 %	alkaline	10 I		1	3.334-103.0	
	Our RIR Classic is a thoroughly powerful cleaner for industrial purposes and machinery, with a fresh fragrance. Recommended for all types of alkaline-resistant surfaces and hard floor coverings.	Maintenance cleaning		1 %	pH: 12					
Deep cleaning										
-	FloorPro Intensive Deep Cleaner Extra	Deep cleaning (care film)		20-50 %	alkaline	10 l		1	6.295-813.0	
10.	RM 752	Deep cleaning (dirt)		5-20 %	pH: 13.2	200 I		1	6.295-814.0	
	Extra powerful deep cleaning agent for removal of stubborn dirt and coatings of alkali-resistant floors. Removes even the most stubborn oil, grease and mineral stains.	Tashed				1000		1	6.295-815.0	
-	FloorPro Allround Deep Cleaner RM 754			15-50 %	slightly alkaline	10 l		1	6.295-811.0	
-	Highly efficient deep cleaning agent for			10-20 %	pH: 10.5					
=	easy removal of wax and polymer coat-	Maintenance cleaning		1-3 %						
	ings on water-resistant and alkali-sensi- tive floors. No time-consuming rinsing	FIGA								
	required.	(Deltod)								
	PressurePro Intensive Deep Cleaner	High-pressure cleaner	1+3	1-5 %	alkaline	10 I		1	6.295-539.0	
1	RM 750	Scrubber driers - Stripping		10-50 %	pH: 13.7	200 I		1	6.295-540.0	
	Powerful deep cleaner effectively re-	Scrubber-driers -		5-50 %						
2000	moves the most stubborn stains, such as oil, grease, soot, blood and proteins.	deep cleaning Manual		5-50 %						
	Low foam production. Particularly suit-	Walloal		3 30 %						
	ed for floor cleaning by machine and									
	for processing with hard surface cleaners. NTA-free.									
-	FloorPro Deep Cleaner, acidic RM 751	Deep cleaning		5-25 %	acidic	2.5 I	•	4	6.295-586.0	
3	Acidic deep cleaner for floor cleaners.	Maintenance cleaning		1-5 %	pH: 0.7	10 l		1	6.295-129.0	
	Effectively removes cement film, de-	Manual		0.5-1 %		200 I		1	6.295-130.0	
	posits and residue, e.g. limescale, rust, beer or milk residues. Ideal for final cleaning on building sites.									
	FloorPro Escalator Cleaner, neutral	Escalator cleaning		10-40 %	neutral	20 I	•	1	6.295-408.0	
-	RM 758				pH: 6.7					
- L	Intensive hard floor cleaner for escala- tors and travelators additionally pro-									
	tects the machine and escalator materi-									
No. of Lot,	als from corrosion. Removes oil, grease									
1	and mineral contamination. For escala-									
	tors manufactured by KONE, Otis, Fuji-									
	tel, Schindler, Mitsubishi, CNIM, DONG, YANG, HITACHI and TOSHIBA, among									
	others.									
Supplement dee						_				
	Foam Blocker RM 761	Wet and dry vacuum cleaners	5	0.5 %		2.5 l		1	6.291-389.0	
	The Foam Blocker RM 761 reduces	Spray extraction machines		0.5 %						
0										
-0	foaming in wastewater tanks and increases the device's duration of use.	Carpet cleaners Floor cleaning units		0.5 %						

5)	Included	in the	VAH li	st of	disir	nfectants	of 1	April	2012	(mhp	Verlag	GmbH	Wiesbaden).

S) Included in the IHO list of disinfectants for animal husbandry.
 Nitrilotriacetate-free (NTA-free).
 Easily separable in oil separator systems (ASF).

Disinfericidal, proper power, the lab fore us Disinfericidal, proper power, the lab fore us Disinfericidal, proper power, the lab fore us Use big label a use. State label a use. State label a suse. State label a use. State label la	vectant RM 735 ve, neutral disinfectant. With cidal, fungicidal and limited lal properties (e.g. hepatitis B). ocides safely. Always read the nd product information before	High-pressure cleaner Maintenance cleaning Spray units Manual High-pressure cleaner Spray units Manual Coating		1-3 % 1-3 % 1-3 % 1-3 % 1-3 %	slightly alkaline pH: 9.9 neutral pH: 7.6	5 I 200 I 2.5 I 5 I	:	1 1	6.295-596.0 6.295-417.0 6.295-585.0 6.295-597.0	
Disinfericidal, proper power, the lab fore us Disinfericidal, proper power, the lab fore us Disinfericit bacteri virucide Use bid label a use. Siel label	ctant cleaning agent. With bacte- fungicidal and limited virucidal ties. Offers very good cleaning Use biocides safely. Always read lel and product information be- lec. Signature (1998) Extant RM 735 Extent RM 736 Maintenance cleaning Spray units Manual High-pressure cleaner Spray units Manual Manual		1-3 % 1-3 % 1-3 % 0.75-2 % 0.75-2 %	pH: 9.9	2.5	•	1	6.295-417.0		
ricidal, proper power. the lab fore us Disinfe Effecti bacteri virucid Use bid label a use. 516 Gare and protection FloorP RM 78 Extra r ter-res	fungicidal and limited virucidal ties. Offers very good cleaning Use biocides safely. Always read led and product information bele, significant RM 735 ver, neutral disinfectant. With cidal, fungicidal and limited lal properties (e.g. hepatitis B). ocides safely. Always read the nd product information before	Spray units Manual High-pressure cleaner Spray units Manual		1-3 % 1-3 % 0.75-2 % 0.75-2 %	neutral	2.5	•		6.295-585.0	
Disinfe Effecti bacteri Virucic Use bic label a use. 510 Floorp RM 78 Extra r ter-res	ties. Offers very good cleaning Use biocides safely. Always read el and product information be- ie.5(5)(6) Ectant RM 735 ve, neutral disinfectant. With cidal, fungicidal and limited all properties (e.g. hepatitis B). ocides safely. Always read the nd product information before ro Protect Dispersion Extra	Manual High-pressure cleaner Spray units Manual		0.75-2 % 0.75-2 %				4		
Disinfe Effecti bacteri virucia Use bia label a use. 510 Care and protection Floorp RM 78 Extra r ter-res	Use biocides safely. Always read el and product information be- ectant RM 735 ve, neutral disinfectant. With cidal, fungicidal and limited al properties (e.g. hepatitis B). ocides safely. Always read the nd product information before ro Protect Dispersion Extra	High-pressure cleaner Spray units Manual		0.75-2 % 0.75-2 %				4		
Disinfe Effecti bacteri virucio Use bio label a use.510 Care and protection FloorP RM 78 Extra r ter-res	el and product information be- ie. (5)(6) Ectant RM 735 ve, neutral disinfectant. With cidal, fungicidal and limited lal properties (e.g. hepatitis B). ocides safely. Always read the nd product information before ro Protect Dispersion Extra 2	High-pressure cleaner Spray units Manual		0.75-2 %				4		
Disinfe Effecti bacteri virucic Use bic label a use. Sign Care and protection FloorP RM 78 Extra r ter-res	ectant RM 735 ve, neutral disinfectant. With cidal, fungicidal and limited lal properties (e.g. hepatitis B). ocides safely. Always read the nd product information before ro Protect Dispersion Extra	High-pressure cleaner Spray units Manual		0.75-2 %				4		
Disinfe Effecti bacteri virucic Use bie label a use. 516 Care and protection FloorP RM 78 Extra r ter-res	ectant RM 735 ve, neutral disinfectant. With cidal, fungicidal and limited lal properties (e.g. hepatitis B). ocides safely. Always read the nd product information before ro Protect Dispersion Extra	High-pressure cleaner Spray units Manual		0.75-2 %				4		
Effecti bacteri virucic Use bii label a use. ⁵⁽⁶⁾ Care and protection FloorP RM 78 Extra r ter-res	ve, neutral disinfectant. With cidal, fungicidal and limited lal properties (e.g. hepatitis B). ocides safely. Always read the nd product information before	Spray units Manual		0.75-2 %				4		
bacteri virucio Use bio label a use. ^{5(a)} Care and protection FloorP RM 78 Extra r ter-res	cidal, fungicidal and limited lal properties (e.g. hepatitis B). ocides safely. Always read the nd product information before ro Protect Dispersion Extra	Manual American IHO			pH: 7.6	51	•		6.295-597.0	
virucio Use bio label a use. ^{5(a)} are and protection FloorP RM 78 Extra r ter-res	lal properties (e.g. hepatitis B). ocides safely. Always read the nd product information before ro Protect Dispersion Extra	Learning IHO		0.75-2 %						
Use bid label a use. 500 are and protection FloorP RM 78 Extra r ter-res	ocides safely. Always read the nd product information before ro Protect Dispersion Extra									
label a use.50 are and protection FloorP RM 78 Extra r ter-res	nd product information before ro Protect Dispersion Extra									
use.90 FloorP RM 78 Extra r ter-res	ro Protect Dispersion Extra 2									
FloorP RM 78. Extra r ter-res	2	Coating								
RM 78. Extra r ter-res	2	Coating								
Extra r ter-res				undiluted		5 I		2	6.295-816.0	
ter-res		FIGA			pH: 8.6					
9.5	istant floors. Excellent covering	losted								
DOWEL.	adhesion, slip resistance and									
the same of the sa	on resistance. Increased resist-									
ance to	alcohol and disinfectant.									
FloorP	ro Care Dispersion RM 784	Coating		undiluted	neutral	5 I		2	6.295-817.0	
	er dispersion for initial, interim	Spray Cleaner		20-30 %	pH: 7.6					
and the second	aintenance care of floor cover-	Wipe restoration		30-50 %						
	orms an anti-slip, dirt-repellent rasion-resistant protective film.	Wipe care		1-3 %						
	overing power.	FIGR								
TIIGH	overing power.	tested								
		COTO!								
FloorP	ro Crystallising Agent RM 749	Crystallising		10 ml/m²	acidic	10 I		1	6.295-284.0	
	lising liquid for treating and				pH: 0.8					
a married	ing calcareous floors such as									
	, terrazzo and cast stone.									
The second secon	ystallised floor is then harder ore wear-resistant.									
and me	ore wear-resistant.									
	ro High Gloss Crystallising Agent,	Crystallising		30 g/m²	acidic	5 kg		1	6.295-117.0	
	r RM 775				pH: 1.4					
	lising powder for treating and									
	ing marble and terrazzo floors. rystallisation, the floor has an									
	ive high gloss and is harder and									
	esistant to wear.									
	list of disinfectants of 1 April 201	2 (mbn Vorlag Cmbil Wi	andon)						,	

[▲] Easily separable in oil separator systems (ASF).

	Product description	Pressure	Dosing range	Dispensing volume	Extendable	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Dilution devices										
bla	DS 2 Dosing Unit DVGW-certified dosing unit for filling floor cleaning machines and buckets and for preparation of HD/HDS primary mixtures. Includes backflow preventer according to DIN EN 1717.	1.7-3.5 bar	0.3-25 %	14 I/min	•	355 × 300 × 210 mm	1.86 kg	1	6.394-653.0	
	DS 3 Cleaning Agent Dosing Station	2-6 bar	0.2-13.5 %	15 l/min	•	390 × 390 × 150 mm	3.85 kg	1	2.641-811.0	
000	After connecting to a tap, cleaning agent can be added to the fresh water tank and diluted as required. Can also be used with the filling system attachment kit. Includes backflow preventer (DIN EN 1717).									
	Product description	Suitable for	bulk size			Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Dispensing aids										
=	Container valve, 5 I Practical aid for efficient filling and dosing of cleaning agents from containers.	51				85 × 48 × 40 mm	0.02 kg	1	6.394-819.0	
	Container valve, 10l	10				60 × 90 × 70 mm	0.04 kg	1	6.394-758.0	
8	Practical aid for efficient filling and dosing of cleaning agents from containers.									
	Container valve, 20I	20				75 × 110 × 60 mm	0.04 kg	1	6.394-759.0	
est.	Practical aid for efficient filling and dosing of cleaning agents from containers.									
	Drum tap, 200 I	200 l				150 × 100 × 65 mm	0.08 kg	1	6.412-438.0	
70	For dispensing cleaning agents from drums.									
	Drum pump, 200 I	200 l				1560 × 175 × 90 mm	1.1 kg	1	6.291-108.0	
1	Practical pump for dosed and efficient dispensing of cleaning agents from drums. Accurate and easy to use.									

	Product description	Pressure	Filling volume	Material	Dispensing volume	Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Spray units						<u>, , , , , , , , , , , , , , , , , , , </u>			4	
4.9	Cleaning Agent Sprayer Easy and convenient to use cleaning agent sprayer with sturdy plastic container and comfortable carrying strap for cleaning agent and disinfectant application.	3 bar	51	plastic	0.46-1.22 l/min	520 × 200 × 200 mm	1.8 kg	1	6.394-255.0	
1	EK 1 Cleaning Agent Sprayer Mobile and compact: low-pressure spray unit for effective dispensing of cleaning agent for wide area coverage. With integrated manual pump, ergo- nomic pump handle and level control.	0.5-6 bar	10	stainless steel	0.78 l/min	640 × 285 × 270 mm	4.7 kg	1	6.394-628.0	
	Telescopic spray lance Accessory for a long reach for use with EK 1 Cleaning Agent Sprayer. Extend- able from 860 to 1520 mm including nozzle for precise application.					875 × 45 × 20 mm	0.366 kg	1	6.393-313.0	
İ	Pump spray bottle 1-litre pump spray bottle - including pump and pressure tank - easy, uniform spraying for cleaning or crystallising.		1	plastic	0.22-0.38 l/min	195 × 140 × 310 mm	0.56 kg	1	6.394-409.0	
	Product description					Dimensions (L × W × H)	Weight	PU	Order no./ quantity	Price
Sales tools										
	Premium demo case Robust demonstration case with many storage options, convenient large open- ing, telescopic handle and smooth- running castors. Ideal for all utensils for cleaning agent demonstrations.					44 × 30 × 44 cm	4.5 kg	11	6.999-247.0	
	Starter set for Premium demo case Basic and safety equipment for demonstrations and applications of cleaning agents. Incl. pH measurement, cloths, brushes, cutter and scraper.						2 kg		2.200-006.0	
	Refill set for Premium demo case Incl. all consumables from the starter set such as Ph measuring strips, cloths,						1.5 kg	1	2.200-007.0	

brushes, cutter, blades, scraper, gloves, bin liners.

Clean Card 25 Clean Cards for the detection of dirt containing protein and surfactants from cleaning agent or disinfectant residues on visibly clean surfaces. For hygienically sensitive areas.


Clean Card

0,1 kg 1 6.999-313.0

VehiclePro - WHEN YOU ARE DRIVEN BY PERFECTION

The cleaning and care agents of our innovative VehiclePro Klear!Line guarantee excellent cleaning results, superb care and a high level of efficiency.











1 A product line that convinces in every aspect

Our new VehiclePro Klear!Line offers you the complete vehicle wash with ultra-high cleaning concentrates that are extremely economical to difficult contours. And with our new fragrance concept Pine Active you put the final touch to a perfect washing result.

2 Complete vehicle cleaning

Our range of cleaning and care agents for washing vehicles offers products for all applications. From rim cleaning, prewash, high-pressure and foam wash to drying aids and conservation.

3 Easily separable formulas (ASF)

Many Kärcher cleaning agents fulfil two tasks with special easily separable formulas (ASF). Firstly: the effective removal of grease and contamination dose: Klear!Prewash, Klear!Foam, Klear!Brush, Klear!Glow and Klear!Dry. containing mineral oil. Secondly: assurance of the reliability of the separator. New contents guarantee a perfect washing result, also for vehicles with Kärcher cleaning agents with ASF also ensure that surfactants quickly separate again from water and contamination containing grease/mineral oil - for more complete and faster separation in the oil separator.

4 Compliance with the highest industrial standards

Many Kärcher cleaning agents for vehicle washes comply with the high standards of the German Association of the Automotive Industry (VDA). These VDA-compliant cleaning agents ensure gentle and thorough cleaning.

5 Care and protection without contact

Foam technology is a decisive factor in contactless vehicle washing. Here, Kärcher sets standards with products like the VehiclePro Foam Cleaner RM 838 and the VehiclePro Foam Polish RM 837. Foam Cleaner RM 838 offers high cleaning performance and perfect, long-acting foam. The VehiclePro Foam Polish RM 837 with repair effect provides long-lasting protection.

									- 1	- 1		1 1				Page
		residues	, salt deposits			8		2	1			oil separators)				
Care, protection	Drying	Oil, grease, soot, insect residues	Limescale, rust, cement, salt deposits	SB	2 pumps	3 pumps	>4 pumps	2 pumps	3 pumps	Train	Washing hall	ASF (easily separable in	NTA-free	VDA class	Nordic Swan	
				•		■ (1)	•					~	~	Α		876
						■ (1)		■ (V)	■ (V)				~	В		876
			•	•		■ (1)	_		■ (V)			V	~			876
						■ (1)		■ (V)	■ (V)				~	В		876
$\overline{}$	П					П	\neg	\neg	\neg	\Box		П	~	В	П	876
						■ (1)						V	V			876
\top						■ (1)						V	~		П	876
						■ (1)						V	V		V	876
$\overline{}$	\Box			•	\neg	\Box	\neg		\neg	\neg		V	V		\Box	877
									■ (1)			V	~			877
							\neg		■ (1)				~			877
					■ (1)	(2)							V	Α		877
-				•			\neg		■ (1)	\neg		V	~			877
												V	~			877
							\neg		\neg	\neg		V	~	В	\Box	877
					■ (1)	(2)		■ (1)	(2)			V	~	В		877
				_	■ (1)		_	■ (1)	_			V	~	В		877
					■ (1)			_(-,	_(_,			V	V	В		878
				_	■ (1)							~	V	В	\vdash	878
				_	■ (1)	-						V	V	В		878
				_	■ (1)								~	В	~	878
		_			■ (1)								V	A		878
	_		+	_	■ (2)	-							v	A	-	878
					■ (2)								V	A		878
	_		-	_		■ (3)							V	A	\blacksquare	878
	-			_		-	_									
	_	•	-	-	■ (2)	■ (3)	-	= (2)	■ (2)				V	Α	~	878
	-	-					_	■ (2) ■	_	-			V	А		_
	_		-					■ (2)	■ (3)						\blacksquare	879
	_												V	A		879 879
				-			_						V			_
			-										~	А		879
			-	-			-								\blacksquare	879
•				\rightarrow			-		\dashv			\square			\blacksquare	879
•							\rightarrow							А	\blacksquare	879
•			_ +	\rightarrow	$\overline{}$							~	~		\vdash	879 879
+																

■ NEW ■ usable □ usable subject to conditions

() Pump/e.g.: (2) means possible product for a second pump

(V) Prespray, i.e. no pump application

Price

	Product description	Dosage	Primary mixture	Dosage	Properties	Packaş size		Order no./ U quantity	Pric
re-cleaning -	Premium rim cleaner VehiclePro Klear!Rim Foam RM 802 High-foaming rim cleaner for aluminium and steel rims. Highly effective against stubborn dirt, gentle on materials and the environment.	Self-service wash bays Commercial vehicle washes		2-3 % 2-3 %	alkaline pH: 13.1	20	■ 1	6.295-934.0	
	VehiclePro Klear!Rim RM 896 Premium rim cleaner for all coated alloy and steel rims. Removes stubborn dirt, without damaging concrete floors and wheel arches. ²⁾	Spray units Self-service wash bays Commercial vehicle washes		10 % 10-20 % 10-20 %	alkaline pH: 13.5	10 I 20 I	■ 1 ■ 1		
re-cleaning -	Classic rim cleaner								
The country of the co	VehiclePro Rim Cleaner, acidic RM 800 Highly effective rim cleaner concentrate. Active foam enables the gentle removal of all normal rim contamination, like brake dust, tyre wear, winter salt residues, lime stains and salt deposits.	Spray units Self-service wash bays Commercial vehicle washes		10 % 10 % 10 %	acidic pH: 0.3	20 I 200 I	II A 1		
	VehiclePro Rim Cleaner, alkaline RM 801 Classic Special rim cleaner for all coated light metal and steel rims (excludes uncoated, high-gloss special rims). Gentle action, effectively removes the most stubborn rim contamination, e.g. road dust, bakedon brake dust, tyre wear and winter salt residues. Does not attack concrete floors or wheel arches. ²⁰	Spray units Self-service wash bays Commercial vehicle washes		10 % 10-20 % 10-20 %	alkaline pH: 13.5	201	1	6.295-323.0	
WE'S	Rim Cleaner, alkaline CP 901 Special rim cleaner for coated light metal and steel rims (excludes uncoated, high-gloss special rims). Gentle action, effectively removes even the most stubborn contamination, e.g. baked-on brake dust, tyre wear and winter salt deposits. Overdosage can easily be avoided thanks to the colour of the cleaning agent. ²⁰	Spray units Self-service wash bays Commercial vehicle washes		10 % 10-20 % 10-20 %	alkaline pH: 13.5	20	■ 1	6.295-676.0	
ro-cloaning -	Premium surface								
Te-Cleaning -	VehiclePro Klear!Prewash RM 890 Alkaline, removes road dirt, greases and insects in no time. VDA-compliant and suitable for all processed water systems and all types of water hardness. ²⁾	Commercial vehicle washes		0.5-2 %	alkaline pH: 13	10 I 20 I 200 I	■ A 1 ■ A 1	6.296-004.0	
re-cleaning -	Classic surface								
	VehiclePro Prewash RM 803 Classic Active, gentle high-pressure pre-spraying agent. Accelerates the softening and removal of oils and greases, as well as insect residues.	High-pressure cleaner Commercial vehicle washes Self-service wash bays Spray units		1.5-6 % 0.5-2 % 1.5-6 % 2 %	alkaline pH: 13	10 I 20 I 200 I		6.296-062.0	
T.	VehiclePro Prewash RM 803 eco!perform with Nordic Swan certification: Environmentally friendly pre-spraying agent. Accelerates the softening and removal of oils, greases and insect residues.	Commercial vehicle washes Self-service wash bays		1.5-6 % 0.5-2 % 1.5-6 % 2 %	alkaline pH: 13	10 I 20 I 200 I		6.296-068.0	

2)	VDA-compliant Class B.
1)	VDA-compliant Class A.

	Product description	Dosage	Primary mixture	Dosage	Properties	Packagi size	IIIR	PLI	Order no./ quantity	F
	Intensive Dirt Remover CP 930	High-pressure cleaner	matore	0.5-2 %	alkaline	20		1	6.295-515.0	·
	Active pre-spraying agent, effortlessly	Spray units		0.5-2 %	pH: 13	200		1	6.295-516.0	
_	removes the most stubborn grease and oil	Self-service wash bays		0.5-2 %		2001			0.233 310.0	
	stains. It easily accelerates the softening and removal of insect residues.			0.5-2 %						
	VehiclePro Truck Cleaner, acidic RM 804	High-pressure cleaner		1-3 %	acidic	20 I		1	6.295-595.0	_
ALC:	Acid pre-spraying agent for commercial	Commercial vehicle washes		1-3 %	pH: 1	200 I		1	6.295-598.0	
	vehicle brush and high pressure washing facilities. Removes mineral soiling such as plaster, lime, mortar and concrete from construction site vehicles and steel structures.	Spray units		1-3 %						
	VehiclePro Truck Cleaner, alkaline	Spray units		1-3 %	alkaline	20 I		1	6.295-550.0	_
STAT-	RM 805	High-pressure cleaner		1-3 %	pH: 12.8					
	The pre-spraying agent in commercial vehicle washes effectively supports the removal of the most stubborn dirt, like lubricants, soot, oil, tar, insects and grey film on all types of commercial vehicles.	Commercial vehicle washes		1-3 %						
in cleaning	- Premium SB wash									
	VehiclePro Foam Cleaner RM 838 The alkaline Foam Cleaner RM 838 for	Self-service wash bay with MultiApp lance	1+3	1-2 %	alkaline pH: 13	20 1	-	1	6.295-838.0	
-	contactless vehicle washing effortlessly	High-pressure cleaner with		1-2 %	pn. 13	200 I		1	6.295-839.0	
	removes heavy oil and grease stains, insect residues and road dirt and is gentle on paintwork. ¹⁾	foam nozzle								
	VehiclePro High-Pressure Wash RM 806	High-pressure cleaner	1+3	0.8-2 %	alkaline	20 I	•	1	6.295-553.0	
E	This cleaning concentrate has a broad dirt-dissolving range and removes the most stubborn road dirt, such as dust, oil, lubricating grease, insects, tree resin and mud.	Self-service wash bays		0.8-2 %	pH: 13.3	200	•	1	6.295-554.0	
in cleaning	- Classic SB wash									
	High-Pressure Wash CP 935	High-pressure cleaner		0.3-2 %	alkaline	20 I		1	6.295-517.0	
-	Highly effective cleaning concentrate	Self-service wash bays		0.3-2 %	pH: 12.2	200 I		1	6.295-518.0	
F	with an apple scent for vehicle washes. Removes the most stubborn soiling such as dusts, oil, lubricants, insect residues, tree resin and mud.	Spray units		0.3-2 %						
	Active Foam CP 940	High-pressure cleaner		1.3-2 %	alkaline	20 1	•	1	6.295-519.0	
	Slightly alkaline cleaning shampoo,	Commercial vehicle washes		1.3-2 %	pH: 11.4	200 I		1	6.295-520.0	
=	produces a stable foam in clean park systems and in self-service wash bays.	Self-service wash bays High-pressure cleaner with		0.2 % 1.3-2 %						
	Active Foam CP 940 is gentle on the	foam nozzle		1.5-2 /0						
3	surfaces and can be easily rinsed away. It has a pleasant fresh lemon scent. ²⁾									
ain cloaning	·									
anii Cleanning	- Premium brush shampoo VehiclePro Klear!Brush RM 891	Commercial vehicle washes		0.2 %	slightly alkaline	10 I		1	6.295-995.0	
Mary Mary	For intensive cleaning that's gentle on	A Commercial Vernete Washes		0.2 %	pH: 8.7	20		1	6.295-996.0	
21	paintwork, helps brushes self-clean and	NEW				200 I		1	6.295-997.0	_
	lengthens their service life. Accelerates drying and is VDA-compliant. ²⁾									
ain cleaning	- Classic brush shampoo VehiclePro Brush Shampoo RM 811	Commercial vehicle washes		0.2 %	slightly alkaline	20 I		1	6.295-439.0	
	Classic	commercial vehicle wastles		J. Z /U	pH: 8.7	2001		1	6.295-140.0	
1=	Highly active, wax-compatible brush								1.223 1 10.0	_



shampoo for brush washing in automatic washing bays. Special active ingredient combination supports brush sliding ability

and protects the vehicle surface. VDA-compliant.2)

[■] Nitrilotriacetate-free (NTA-free).

[▲] Easily separable in oil separator systems (ASF).

²⁾ VDA-compliant Class B.
1) VDA-compliant Class A.

Nitrilotriacetate-free (NTA-free).

[▲] Easily separable in oil separator systems (ASF).

	Duadust dessuichter	Decade	Primary	Decare	Duon	Packag	ging	ъ.	Order no./	P' -
Aain cleaning -	Product description Premium foam wash	Dosage	mixture	Dosage	Properties	size		PU	quantity	Price
ani cicannig	VehiclePro Klear!Foam RM 892	Commercial vehicle washes		0.2 %	slightly alkaline	10 I		1	6.295-998.0	
	Excellent foaming properties. High				pH: 8.9	20 I		1	6.295-999.0	
1	dirt-removing power, easy to rinse off, compatible with drying aids and waxes.	NEW				200 I		1	6.296-000.0	
100	VDA-compliant and gentle on paintwork. ²⁾									
in cleaning -	Classic foam wash									
	VehiclePro Active Foam Wash Nano	Commercial vehicle washes		0.2 %	slightly alkaline	20 I		1	6.295-440.0	
	RM 816 Classic Highly active, wax-compatible brush				pH: 8.7	200 I		1	6.295-322.0	
	shampoo for brush cleaning in automatic									
	washing bays. A special active ingredient combination improves brush sliding									
	ability to protect the vehicle surface and									
	prepare it optimally for treatment with									
	Gloss Dryer Nano RM 832. VDA-compli- ant. ²⁾									
	VehiclePro Active Foam RM 812 Classic	Self-service wash bays	1+3	0.8 %	slightly alkaline	20 I		1	6.295-430.0	
	Very powerful, intensive active foam.	Commercial vehicle washes	1.0	0.8 %	pH: 8.9	200 I			6.295-430.0	
13	Specially formulated content materials to							_		
	protect vehicle surfaces as well as the brushes. VDA-compliant. ²⁾									
	brosnes. VB/V compilant.									
The same	VehiclePro Foam Wash RM 812 eco!perform	Self-service wash bays Commercial vehicle washes		0.8 %	slightly alkaline pH: 8.9	10	A		6.296-070.0	
6-	with Nordic Swan certification: Environ-	commercial vehicle wasnes		U.Z 76	μп. б.Э	20 I 200 I			6.296-071.0 6.296-072.0	
82	mentally friendly, strong active foam.	NEW Ø				200 1		1	6.296-072.0	
	Its contents protect vehicle surfaces and brushes. ²⁾	eco!perform								
	5. 65.165.									
ng and care	- Premium drying aids VehiclePro Klear!Dry RM 893	Commercial vehicle washes		0.3 %	slightly acidic	10 I		1	6.296-001.0	
426	Breaks down the water film quickly to	A Commercial Vernere Washes		0.5 %	pH: 5	20			6.296-002.0	
=	minimise beading on the surface and	NEW								
	provide optimum drying results. Use sparingly, frost-proof (-10 °C), VDA-com-									
-	pliant. ²⁾									
ng and care	- Classic drying aids		-							
	VehiclePro Gloss Dryer Nano RM 832	Commercial vehicle washes		0.1-0.2 %	slightly acidic	20 1		1	6.295-432.0	
	Classic Liquid pearl wax with special nano parti-	Self-service wash bays High-pressure cleaner	1+9	0.1-0.2 % 1-2 %	pH: 4	200 I		1	6.295-320.0	
	cles for use in car wash stations, self-									
	service wash systems and high-pressure machines. The Nano shine dryer quickly									
	breaks down the water film to produce									
	very good drying results. VDA-compli-									
	ant.1)									
	VehiclePro Super Pearl Wax RM 824	Commercial vehicle washes	undiluted	0.1-0.2 %	slightly acidic	20 I		1	6.295-438.0	
1	Classic	High-pressure cleaner	1+9	1-2 %	pH: 4	200 I		1	6.295-074.0	
	Drying, protection and care all in one. This liquid pearl wax quickly breaks down									
-	the water film and ensures very good									
	drying characteristics, especially if hard									
	water is used. VDA compliant. ¹⁾									
	VehiclePro Drying Aid RM 829 Classic	Commercial vehicle washes		0.1-0.3 %	slightly acidic	10 I	•	1	6.296-064.0	
1	Allows the water film to break down	Self-service wash bays		0.1-0.3 %	pH: 5	20 1		1	6.296-065.0	
1	quickly and creates preservative, long-lasting protection. Also for soft and					200 I		1	6.296-066.0	
	osmosis water. VDA-compliant.1)	NEW								
	VehiclePro Drying Aid RM 829	Commercial vehicle washes	-	0.1-0.3 %	slightly acidic	10 l		1	6.296-073.0	
	eco!perform	Self-service wash bays		0.1-0.3 %	pH: 5	20	-	1	6.296-074.0	
====	VehiclePro Drying Aid RM 829 eco!per- form with Nordic Swap certification: Suit-									
-	form with Nordic Swan certification: Suitable for all water hardness levels. Allows	NEW Ø								
	the water film to break down quickly and	eco!perform								
	creates preservative, long-lasting protection. ¹⁾									
	tion.									

	Product description	Dosage	Primary mixture	Dosage	Properties	Packag size	ing	PU	Order no./ quantity	Pric
	VehiclePro Liquid Leather RM 833	Commercial vehicle washes	1+3	0.4-0.8 %	alkaline	20 I		1	6.295-391.0	
-	Special drying aid for washes without				pH: 12	200 I		1	6.295-392.0	
	blow drying. Lets water run off over large									
	surfaces and dries without spots and									
	streaks. Suitable for high-pressure clean-									
	ers as well.									
	Vahiala Dua Carray Way DM 024 Classic	High assessment alone as	1.0	1 2 0/		20.1			C 205 424 0	
	VehiclePro Spray Wax RM 821 Classic This liquid spray wax gives vehicles a	High-pressure cleaner Self-service wash bays	1+9	1-2 % 1-2 %	slightly acidic pH: 4	20 1		1	6.295-431.0	
	brilliant shine and long-term protection.	Scii Sci vice wasii bays		1 2 /0	pri. 4	200 I		1	6.295-084.0	
	Unaffected by water quality, it provides a									
	spotless finish without blow drying. VDA									
	compliant.1)									
	Top Care CP 950 Liquid spray wax for conservation and	Self-service wash bays			slightly acidic	20	•	1	6.295-523.0	
	shiny finish care. Insensitive to water	High-pressure cleaner		0.02-0.05 %	рп. э.э					
The second second	hardness, it generates a stable high-lustre									
100 miles (100 miles (film, allows water to be removed from									
	large surfaces and dries without leaving									
	streaks or spots. VDA-compliant.1)									
	- Premium waxes									
	VehiclePro Klear!Glow RM 894	Commercial vehicle washes		0.3 %	neutral	_10 I		_1	6.295-993.0	
	VehiclePro Klear!Glow RM 894: For out-				pH: 6.3	20 1		1	6.295-994.0	
	standing paintwork protection against the elements. With a special high-gloss effect	NEW								
	and long-lasting preservation with mini-									
	mal use. VDA-compliant.2)									
	VehiclePro Kärcher Polish Plus RM 831	Commercial vehicle washes		40-80 ml/	slightly acidic	10	_	1	6.295-110.0	
	Innovative vehicle care agent with special			vehicle	pH: 3.5	20 I		1	6.295-427.0	
	care formula for long-lasting wax conser- vation. Protects vehicles against road dirt,									
	insects, acid rain and other harmful envi-									
	ronmental influences. VDA-compliant. ¹⁾									
	Mahida Bara Baran Ballah Baran	C		20. 40	-Patata 1 - Pa	20.1			6 205 770 0	
	VehiclePro Foam Polish RM 837 Clearly visible, long-lasting preservation	Commercial vehicle washes		20-40 ml/ vehicle	slightly acidic pH: 4	20 1		1	6.295-779.0	
	with repair effect. Protects the surface	Self-service wash bays		20-40 ml/	pri. 4					
	from environmental influences. Increases			vehicle						
	shine. With lotus blossom extract.									
rving and care	- Classic waxes									
	VehiclePro Hot Wax RM 820 Classic	High-pressure cleaner	1+9	1-2 %	neutral	20 I		1	6.295-428.0	
	This liquid thermo wax produces a	Commercial vehicle washes		0.1-0.2 %	pH: 6.3	200 I		1	6.295-143.0	
	weather-resistant preservative layer	Self-service wash bays		1-2 %		-				
100000000000000000000000000000000000000	to protect vehicles against corrosion.									
	Contains natural carnauba wax. VDA compliant. ¹⁾									
-										
	Thermo wax CP 945	High-pressure cleaner		0.2-0.4 %	slightly acidic	20		1	6.295-521.0	
	This thermo-wax concentrate produces a	Self-service wash bays		0.2-0.4 %	pH: 4.5					
	water-repellent, long-lasting preservative									
	layer with a high-gloss effect. With a high natural carnauba wax content. VDA-com-									
	pliant.1)									
-										
pplementary p	products									
	VehiclePro Washing Bay and Tile Cleaner			20-50 %	acidic	20 1		1	6.295-419.0	
	RM 841 This acidic washing bay and tile cleaning	Maintenance cleaning		5-10 %	pH: 0.3					
	concentrate quickly and efficiently									
The second second	removes lime, grease, wax, cleaning agent									
	residue and traces of rust.									
						95.				
	residue and traces of rust. VehiclePro Softening Salt Specially formulated to soften water in	Commercial vehicle washes				25 kg	•	1	6.287-016.0	

2) VDA-compliant Class B.
1) VDA-compliant Class A.
Nitrilotriacetate-free (NTA-free).
A Easily separable in oil separator systems (ASF).

2) VDA-compliant Class B.
1) VDA-compliant Class A.
Nitrilotriacetate-free (NTA-free).
A Easily separable in oil separator systems (ASF).

CLEANING AND CARE AGENTS

878 879 CHEMICALS FOR WATER TREATMENT CLEANING AGENTS FOR INDUSTRIAL PARTS

BRINGING OUT THE BEST

Kärcher provides suitable treatment chemicals for trouble-free operation and excellent treatment results. Our products have been tried and tested over a number of years and are perfectly adapted to suit specific applications and systems.







SAFE AND EFFICIENT

In industrial production, millions of parts have to be cleaned each day in preparation for coatings or final assembly. The demands on cleaning power, surface protection and absence of residues are extremely high in this sector. As a result, Kärcher has developed specific, highly effective cleaning agents that achieve impressive results when used with conventional parts cleaners as well as Kärcher Bio parts cleaners. Kärcher Bio parts cleaners PC Bio 10 and PC Bio 20 received the "Automechanika Award". All Kärcher parts cleaning agents are NTA and solvent-free (VOC-free).



Product description



Primary

mixture Dosage



Order no./

PU quantity

Packaging

	Product description	Primary Application mixture Dosage Properties		Properties	Packag size	ing	PU	Order no./ quantity	Price	
Water treatme	nt .								· · ·	
11/	WaterPro Separating Agent, powder RM 846 Reagent for the treatment of washing water containing mineral oil. Forms large, stable flakes that can be easily filtered away.	Water treatment systems		0.1 %	slightly alkaline pH: 8.7	20 kg	•	1	6.295-164.0	
(II) (III) •	WaterPro Flocculating Agent RM 847 For the effective treatment of contaminated water from car and engine washes. Forms large and easily filtered flakes.	Water treatment systems	1+9	0.07 %	neutral pH: 5.3	11	•	2	6.295-630.0	
I	WaterPro Active Oxygen RM 851 Reliably eliminates all unpleasant odours in the washing water circuit through oxidation with active oxygen.	Water treatment systems		0.002 %	slightly acidic pH: 3	201	•	1	6.295-450.0	
	WaterPro Active Chlorine RM 852 Effortlessly eliminates unpleasant odours in the washing water circuit through oxidation with active chlorine.	Water treatment systems Drinking water treatment systems		0.002 % 0.0003 %	alkaline pH: 13.1	20 1	•	1	6.295-451.0	
•))(((()	WaterPro Hardness Stabiliser RM 5000 Prevents scaling on membranes for drinking water treatment and acts as a dispersing agent.	Drinking water treatment systems		According to untreat- ed water composi- tion	slightly acidic pH: 4.5	1 l 23 kg	:	1	6.295-229.0 6.290-991.0	
	WaterPro Flocculating Agent RM 5001 Highly effective product for cleaning fresh water containing suspended matter in drinking water preparation.	Drinking water treatment systems		According to untreat- ed water composi- tion	acidic pH: 0	10	•	1	6.295-168.0	

arts cleaning								
11.11	PartsPro Cleaner PC Bio 10 Biologically active cleaning agent, water-based, pH-neutral, skin-friendly and solvent-free. Particularly suitable for workshops and service companies for removing oil, grease, and soot contamination from parts.	Bio parts cleaners	undiluted	neutral pH: 7	20	•	1	6.295-260.0
THE STATE OF THE S	PartsPro Cleaner PC Bio 20 Biologically active cleaning agent, water-based, skin-friendly and solvent- free. Ideal for cleaning sensitive metals, e.g. aluminium, silver, titanium, etc., to remove oil, grease and other contami- nation.	Bio parts cleaners	undiluted	slightly alkaline pH: 8.8	20	•	1	6.295-261.0
C. Williams	PartsPro Microbe Suspension Reactivates the biological breakdown process in biological parts cleaners. Increases microbe activity in parts cleaners that have been standing for some time and in cases where the cleaning agent is particularly dirty.	Bio parts cleaners	undiluted	neutral pH: 6	250 ml	•	24	6.295-262.0
The state of the s	PartsPro Cleaner RM 39 Gentle cleaning and degreasing agent effectively removes oil, grease and soot stains from metal parts and provides temporary corrosion protection.	High-pressure cleaner Parts cleaners	2-5 % 1-5 %	slightly alkaline pH: 10.5	20 l 200 l	•	1	6.295-165.0 6.295-424.0
E.I.	PartsPro Cleaner Extra, powder RM 63 Removes even the most stubborn stains such as oils, greases, drawing lubri- cants, soot, etc. For cleaning parts that are not sensitive to alkali, such as en- gines, gearboxes, small hardware, cast- ings, etc.		5 %	alkaline pH: 13.2	20 kg	■ 4	1	6.295-255.0

Application

■ Nitrilotriacetate-free (NTA-free).

OUR MOST POWERFUL

Special regulations and requirements apply to professional tank and container cleaning. With the new Kärcher TankPro series, which is precisely matched to the machine technology, we offer a perfect solution for all cleaning requirements. Nothing is too much for us – these TankPro products offer our customers a solution that is perfectly tailored to their individual requirements. All products are high concentrates and therefore particularly economical and efficient. We are fully aware of our responsibility towards people, machines and the environment and do not use any substances that are harmful to the environment and to health, while maintaining the highest quality.







	Product description	Application	Primary mixture	Dosage	Properties	Packaging size	PU	Order no./ quantity	Price
Cleaning									
-	TankPro Cleaner, acidic RM 870	Tank and silo cleaning	1+3	0.5-3 %	acidic	20 1	1	6.295-916.0	
	TankPro Cleaner, acidic RM 870 for		1+10	0.5-3 %	pH: 0	200 Ⅰ	1	6.295-917.0	
E-,	interior and exterior cleaning of tanks,					1000 I	1	6.295-918.0	
10 m	silos and containers. Also gently removes heavy lime deposits, building								
	material and food residues.								
	material and rood residues.								
	TankPro Cleaner, alkaline RM 875	Tank and silo cleaning	1+4	0.5-3 %	alkaline	20	1	6.295-919.0	
	TankPro Cleaner, alkaline RM 875 for		1+10	0.5-3 %	pH: 13.2	200 Ⅰ	1	6.295-920.0	
-	thorough cleaning of heavy oil and					1000 I	1	6.295-921.0	
1	grease contamination in, e.g. tanks,								
	silos or containers. Foam-reduced, powerful and gentle cleaning action.								
	power for and gentle cleaning action.								
	TankPro Cleaner, Polymer RM 880	Tank and silo cleaning	1+4	0.5-5 %	alkaline	20	1	6.295-922.0	
	TankPro Cleaner, Polymer RM 880 for		1+10	0.5-5 %	pH: 14	200 I	1	6.295-923.0	
=	tank interior cleaning. This alkaline,					1000 I	1	6.295-924.0	
100	foam reduced and gentle cleaning								
	concentrate is ideal for dirt such as flour, latex or rubber.								
1	floor, latex of Tobber.								
	TankPro Latex Remover RM 885	Tank and silo cleaning		1-10 %	alkaline	20	1	6.295-990.0	
	TankPro RM 885 latex remover is an	_			pH: 14	200	1	6.295-991.0	
-	extra-strong, low-foam cleaner for					1000	1	6.295-992.0	
=	tackling the inside of tanks. It can re-	NEW				1000.		1.133 332.0	
-	move stubborn polymer dispersions								
1	and latex effectively while being gentle								
	on the material underneath.								

[■] Nitrilotriacetate-free (NTA-free).

Product	Soi	ling																	Pro	perti	ies			Page
	Flour, grains, potato flour	Protein, milk powder, animal feed, flour	Cocoa powder, chocolate	Sugar, salt	Gelatin, fruit juice	Cement, calcium carbonate, gypsum, chalk	Quartz, sand, slate	Plastic granulate (PVC/PP/PE)	Liquid plastics, polymers, latex and rubber	Mineral oil, fuel oil, wax	Tar, asphalt, grease	Solvent-based organic compounds, e.g. fatty acids, grease crayon, animal and plant-based oils	Coal dust, activated carbon	Acids	Alkalis	Phosphates, nitrates	Raw cleaning agent materials	Talc	Solvent-free	Foam-reduced	No artificial scents or colours	Corrosion inhibitors (stainless steel,aluminium)	Temperature-stable up to 90 °C	
TankPro Cleaner, acidic RM 870																			~	~	~	~	~	882
TankPro Cleaner, alkaline RM 875		•	•	•	•		•	•		•		•	•	•		•	•	•	~	~	~	~	~	882
TankPro Cleaner, Polymer RM 880	•																			~	~	~	~	882
TankPro Latex Remover RM 885 ■																				V	~	~	~	882

[■] NEW ■ usable □ usable subject to conditions

Equipment

A	Page
AB 20 Ec	431
Acrylic dust mop 60 cm	797
Acrylic dust mop 80 cm	797
Adapter for brush	832, 836
AF 100	461
AFG 100, anthracite	459
AFG 100, white	459
Aluminium handle 140 cm / D 23 mm	806
Aluminium handle with thread 140 cm	806
Aluminium T-beam	830
Aluminium telescopic handle 2 × 150 cm	806
AP 100/50 M	117
AT	749
AT-C	749
AT-C Fp	749
AT Fp	749
AWT	749
AWT-C	749
AWT-C Fp	749
AWT Fp	749
В	Page
B 40 C Bp / Classic	525
B 40 C Ep	525
B 40 W Bp	524
B 60/10 C	541
B 60 W Bp	521
B 60 W Ep / B 60 C Bp Classic	520
B 80 W Bp	516
B 80 W Bp	517
B 90 R Adv Bp	501
B 90 R Adv Bp Pack	501
B 90 R Adv Dose Bp	501
B 90 R Adv Dose Bp Pack	501
B 90 R Classic Bp	501
B 90 R Classic Bp Pack	501
B 95 RS	507
B 120 W	513
B 150 R	495
B 150 R Adv	495
B 200 R	491
B 250 R	487
B 250 R I	487
B 300 R I D	483
B 300 R I LPG	483
Barrel cleaner BC 14/12	113
Basic cotton mop	801
Basic microfibre mop	801
Battery charger: BC Adv	237
BD 17/5 C	549
BD 30/4 C Bp Pack	539
BD 38/12 C Bp Pack	534
BD 43/25 C Bp	531
BD 43/25 C Bp Pack	531
BD 43/35 C Ep	531
BD 50/40 RS Bp	509
BD 50/40 RS Bp Pack	509
BD 50/50 C Bp Classic	529
BD 50/50 C Bp Pack Classic	529
BD 50/60 C Ep Classic	529
BD 50/70 R Classic Bp	503
BD 50/70 R Classic Bp Pack	503
BD 50/70 R Classic Fleet Bp	503
BD 50/70 R Classic Fleet Bp Pack	503
BD 80/100 W Bp Classic	527
BD 80/100 W Bp Classic Fleet	527
BD 80/100 W Bp Pack Classic	527
BD 80/100 W Bp Pack Classic Fleet	527
BDP 43/450 C Adv	545
BDP 50/1500 C	551
BDP 50/2000 RS Bp	550
BDP 50/2000 RS Bp Pack	550

BDS 33/180 C Adv	545
BDS 43/150 C Classic	543
BDS 43/180 C Adv	545
BDS 43/Duo C Adv	545
BDS 43/Duo C I Adv	545
BDS 51/180 C Adv	545
Belt for holster	833
Bionic pipe brush, curved	835
Bionic quick-release handle	831
Bionic T-beam	831
Bionic T-beam, movable	830, 831
Bionic wall brush, oval	835
Bionic window scraper, 10 cm, with blade	828
Bionic wiper handle, movable	831
Blade holder	837
Blue Star washer	829
Bp 200 Adv	237
Bp 400 Adv	237
Bp 800 Adv	237
Bp 2400 Adv	237
BR 30/4 C	537
BR 30/4 C Adv	537
BR 30/4 C Bp Pack	537
BR 30/4 C + MF	537
BR 35/12 C Bp Pack	535
BR 40/10 C Adv	536
BR 40/10 C I Adv	536
BR 45/10 Esc	547
BR 45/22 C Bp Pack	533
BR 47/35 Esc	546
BR 55/40 RS Bp	508
BR 55/40 RS Bp Pack	508
BRC 30/15 C	435
BRC 40/22 C	433
BRC 45/45 C	434
Broom PVC 35 cm	796
Broom PVC 60 cm	796
Brush head D 75 D 65 D 55	501
Brush head R 75 R 75 R 65 R 55	503
Brush holder	836
Brush set universal	796
Bucket 22 I	833
Bucket cart with press 28 I	822
Bucket with mop press 15 I	801
Bucket with mop press 15 l	822
BV 5/1	395
BV 5/1 Bp	395
A	Page
Caution wet floor sign, English	804
Caution wet floor sign, German	804

A	Page
Caution wet floor sign, English	804
Caution wet floor sign, German	804
Caution wet floor sign, Russian	804
CB 3	733
CB 5	731
Chain barrier, 1 m	805
Cotton dust mop 60 cm	797
Cotton dust mop 80 cm	797
Cotton dust mop 120 cm	797
Cotton dust mop 160 cm	797
Cotton mop	800
Cotton velcro cover, 40 cm	802
CS 330 Bp	241
CV 30/1	407
CV 38/2	405
CV 38/2 Adv	405
CV 48/2	405
CV 48/2 Adv	405
CV 60/2 RS	401
CV 60/2 RS Bp	401
CV 66/2	403
CWB 3 Klean!Star	729
CWB 3 Klean!Star iQ	727

D	Page
Door stop with handle	805
Double bucket cart with press 2 × 15 I	822
Double bucket cart with press 2 × 25 I	822
Drying with heat exchanger	769
Dust binding cloth neolinn BASIC	799
Dust binding cloth neolinn CLASSIC	799
Dust binding cloth neolinn CLASSIC	813
Dust binding cloth neolinn ECO	799
Dust binding cloth roll neolinn CLASSIC	799
Dust binding cloth roll neolinn CLASSIC	813
Duster ECO 540	798
Dust mop holder 60 cm	798
Dust mop holder 80 cm	798
Dust mop holder, fixed 160 cm	798
Dustpan with rubber profile with sweeping slide	796

E	Page
Ear defenders	231
Earplugs	231
EB 30/1 Adv Li-Ion	399
EB 30/1 Li-lon	399
ECO!Broom and waste container	796
ECO!Duster 97-184 cm	812
ECO!Mop set, blue	801
ECO!Mop set, red	801
ECO!Mop system, 97-184 cm	803
ECO!Spray mop system	803

F	Page
Fall protection	111
Feather duster holder 60 cm	812
Fixi bracket	836
Glass and window cleaning kit	835
Glass scraper	812, 828
GS jet gun	116
Hand pad holder, velcro fastener 30 cm	815
HD 5/11 Cage Classic	107
HD 5/11 P	93
HD 5/11 P Plus	93
HD 5/12 C	91
HD 5/12 C Plus	91
HD 5/12 CX Plus	91
HD 5/15 C	91
HD 5/15 C Plus	91
HD 5/15 CX Plus	91
HD 5/17 C	91
HD 5/17 C Plus	91
HD 5/17 CX Plus	91
HD 6/13 C	91
HD 6/13 C Plus	91
HD 6/13 CX Plus	91
HD 6/14-4 M Cage	89
HD 6/15-4 Classic	105
HD 6/15 G Classic	109
HD 6/15 M	85
HD 6/15 M Cage	89
HD 6/15 M Plus	85
HD 6/15 M St	87
HD 6/15 MX Plus	85
HD 7/10 CXF	101
HD 7/11-4 Cage Classic	106
HD 7/11-4 Classic	105
HD 7/14-4 M	85
HD 7/14-4 M Cage	89
HD 7/14-4 M Plus	85
HD 7/14-4 MX Plus	85
HD 7/15 G	103
HD 7/16-4 Cage Classic	106
HD 7/16-4 M	85
HD 7/16-4 M Cage	89
HD 7/16-4 M Plus	85
HD 7/16-4 MX Plus	85
HD 7/16-4 St	194

HD 7/16-4 St	195
HD 7/17 M	85
HD 7/17 M Cage	89
HD 7/17 M Plus	85
HD 7/17 M St	87
HD 7/17 MX Plus	85
HD 7/18-4 Classic	105
HD 7/20 G Classic	109
HD 8/18-4 M	85
HD 8/18-4 M Cage	89
HD 8/18-4 M Plus	85
HD 8/18-4 M St	87
HD 8/18-4 MX Plus	85
HD 8/20 G	103
HD 8/23 G Classic	109
HD 9/18-4 Cage Classic	106
HD 9/18-4 St	194
HD 9/18-4 St	195
HD 9/20-4 Classic	105
HD 9/20-4 M HD 9/20-4 M Plus	81 81
HD 9/20-4 MX Plus	81
HD 9/21 G	103
HD 9/23 De	103
HD 9/23 De Tr1	95
HD 9/23 G	103
HD 9/23 Ge Tr1	95
HD 9/50-4 Cage	210
HD 9/50 Ge Cage	211
HD 9/100-4 Cage Adv	208
HD 9/100-4 Cage Classic	208
HD 10/15-4 Cage Food	100
HD 10/16-4 Cage Ex	99
HD 10/23-4 S	79
HD 10/23-4 S Plus	79
HD 10/23-4 SX Plus	79
HD 10/25-4 Cage Plus	97
HD 10/25-4 S	79
HD 10/25-4 S Plus	79
HD 10/25-4 SX Plus	79
HD 13/12-4 St	194
HD 13/12-4 St	195
HD 13/18-4 S Plus	79
HD 13/18-4 SX Plus	79
HD 13/35-4 Cage HD 13/35 Ge Cage	210
HD 16/15-4 Cage Plus	211 96
HD 17/14-4 S Plus	79
HD 17/14-4 SX Plus	79
HD 18/50-4 Cage Adv	209
HD 18/50-4 Cage Classic	209
HD 20/15-4 Cage Plus	96
HD 25/15-4 Cage Plus	96
HD 715	98
HD 728 B Cage	103
HDC Advanced	190
HDC Classic	191
HDCI 30/5-4 Mob So Ex	773
HDCI 30/5-4 St So Ex	773
HDCI 30/10-4 Mob Ad/Ly Ex	773
HDCI 30/10-4 Mob Dw Ex	773
HDCI 30/10-4 St Ad/Ly	773
HDCI 30/10-4 St Dw	773
HDC Standard	190
HDI 30/10	768
HDI 38/12	768
HDI 60/10	768
HDI 60/14	768
HDR 777	759
HDR 777-VA	759
HDS 5/11 U	63
HDS 5/11 UX	63
HDS 5/12 C	61
HDS 5/13 U	63

HDS 5/13 UX	63
HDS 5/15 U	63
HDS 5/15 UX	63
HDS 6/14-4 C	61
HDS 6/14-4 CX	61
HDS 6/14 C	61
HDS 6/14 CX	61
HDS 7/12-4 M	59
HDS 7/12-4 MX	59
HDS 7/16 C	61
HDS 7/16 CX	61
HDS 8/17 C	61
HDS 8/17 CX	61
HDS 8/18-4 C	61
HDS 8/18-4 CX	61
HDS 8/18-4 M	59
HDS 8/18-4 MX	59
HDS 9/14-4 St	189
HDS 9/16-4 St Gas	189
HDS 9/18-4 M	59
HDS 9/18-4 MX	59
HDS 9/50 De	67
HDS 10/20-4 M	59
HDS 10/20-4 MX	59
HDS 12/14-4 St	189
HDS 12/14-4 St Gas	189
HDS 12/14-4 St Gas LPG	189
HDS 12/18-4 S	57
HDS 12/18-4 SX	57
HDS 13/20-4 S	57
HDS 13/20-4 SX	57
HDS 13/20 De	67
HDS 13/35 De	67
HDS 17/20 De	67
HDS 801 B	71
HDS 801 D	71
HDS 1000 Be	70
HDS 1000 Be	70
HDS 2000 Super	68
HDS-E 8/16-4 M 12 kW	69
HDS-E 8/16-4 M 24 kW	69
HDS-E 8/16-4 M 36 kW	69
HG 43	73
HG 64	73
High-pressure overall	229
HKF 50 P HKF 200 E	768 768
HKS 100 speed control	768
Holder with squeegees 40 cm	798
Holder with squeegees 60 cm	798
Holster	833
HT 615 Bp	245
HV 1/1 Bp As	397
HV 1/1 Bp Cs	397
HV 1/1 Bp Fs	397
HWE 860	194
HWE 4000 Gas modular eco!efficiency	769
I	Page
IB 7/40 Adv	777
IB 7/40 Classic	777

HWE 860	194
HWE 4000 Gas modular eco!efficiency	769
1	Page
IB 7/40 Adv	777
IB 7/40 Classic	777
IB 15/120	776
IC 15/240 W	705
IC 15/240 W Adv	705
ICH 80/16 Ps	767
ICH 140/14 Ps F2	768
IP 55	778
IP 120	778
IP 280	778
iSolar 400	111
iSolar 800	111
iSolar TL 7 H	111
iSolar TL 10 H TL 10 C	111
iSolar TL 14 C	111
IVC 60/12-1 Ec H Z22	348

IVC 60/12-1 Tact Ec	343
IVC 60/24-2 Ap	34:
IVC 60/24-2 Tact ²	34:
IVC 60/24-2 Tact ² Lp	342
IVC 60/24-2 Tact ² M	34:
IVC 60/30 Ap	340
IVC 60/30 Ap M Z22	348
IVC 60/30 Tact ²	340
IVC 60/30 Tact ² Lp	342
IVL 50/24-2	35!
IVM 60/30	331
IVM 60/30 M Z22	34!
IVM 60/36-3	331
IVR 35/20-2 Pf Me	339
IVR 40/15 Pf	338
IVR 40/30 Pf	338
IVR 50/40 Pf	338
IVR 100/40 Pf	336
IVR-B 30/15 Me	349
IVR-B 50/30	349
IVR-L 40/12-1	354
IVR-L 65/12-1 Tc	354
IVR-L 100/24-2	353
IVR-L 100/24-2 Me	353
IVR-L 100/24-2 Tc	353
IVR-L 100/24-2 Tc Me	35:
IVR-L 100/24-2 Tc Me Dp	353
IVR-L 100/30	350
IVR-L 120/24-2 Tc	35:
IVR-L 120/24-2 Tc Me	35:
IVR-L 120/24-2 Tc Me Dp	35:
IVS 100/40	33!
IVS 100/40 Lp	33!
IVS 100/40 M	335
IVS 100/55 Lp	33!
IVS 100/55 M	33!
IVS 100/55 M Z22	34
IVS 100/75 Lp	335
IVS 100/75 M	33!
IVS 100/75 M Z22	34
W	Pa s
K	Page

K	Page
KM 70/15 C	665
KM 70/20 C	665
KM 70/20 C 2SB	665
KM 70/30 C Bp	663
KM 70/30 C Bp Adv	663
KM 70/30 C Bp Pack	663
KM 70/30 C Bp Pack Adv	663
KM 75/40 W Bp	659
KM 75/40 W Bp Pack	659
KM 75/40 W G	659
KM 80 W G	661
KM 85/50 R Bp	655
KM 85/50 R Bp Pack	655
KM 85/50 W Bp	657
KM 85/50 W Bp Adv	657
KM 85/50 W Bp Pack	657
KM 85/50 W Bp Pack Adv	657
KM 85/50 W G	657
KM 85/50 W G Adv	657
KM 90/60 R Bp Adv	653
KM 90/60 R Bp Pack Adv	653
KM 90/60 R G Adv	653
KM 100/100 R Bp	651
KM 100/100 R Bp Pack	651
KM 100/100 R D	651
KM 100/100 R G	651
KM 100/100 R Lpg	651
KM 105	649
KM 120/250 R Bp Classic	641
KM 120/250 R Bp Pack Classic	641
KM 120/250 R D Classic	641
KM 120/250 R LPG Classic	641
KM 125/130 R	645

KM 130/300 R Bp	639
KM 130/300 R Bp Pack	639
KM 130/300 R D	639
KM 130/300 R D Classic	639
KM 130/300 R LPG	639
KM 150/500 R Bp	637
KM 150/500 R Bp Pack	637
KM 150/500 R D	637
KM 150/500 R D Classic	637
KM 150/500 R LPG	637
KM 170/600 R D	635
L	Page
LB 850 Bp	239
Lid	833
Litter picker 100 cm	796
M	Page
MC 50 Adv	703
MC 50 Adv Comfort	703
MC 80	701
MC 130 Adv	699
MC 130 Plus	699
Media chamois	834
MIC 26 C Adv	715
MIC 34 C	715
MIC 35	713
MIC 42	713
MIC 50	711
MIC 50 Adv	711
MIC 70	709
MIC 84	707
Microfibre cleaning cloth for feather duster 60 cm	812
Microfibre cloth, glass	815
Microfibre cover for hand pad holder	815
Microfibre cover, glass, for hand pad holder	815
Microfibre mop, loop	800
Microfibre mop short fiber 50 cm	801
Microfibre mop, short fibre	800, 801
Microfibre mop, short fibre, abrasive	800,801
Microfibre velcro cover 40 cm	802
Microfibre velcro cover, abrasive, 40 cm	802
Microfibre washer	
Microspun microfibre cloth, blue	829
	814
Microspun microfibre cloth, green	814 814
Microspun microfibre cloth, green Microspun microfibre cloth, red	814 814 814
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow	814 814 814 814
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm	814 814 814 814 802
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm	814 814 814 814 802 802
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm	814 814 814 814 802 802 803
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system	814 814 814 814 802 802 803 803
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue	814 814 814 814 802 802 803 803 803
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green	814 814 814 814 802 802 803 803 815 815
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red	814 814 814 802 802 803 803 803 815 815
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green	814 814 814 814 802 802 803 803 815 815
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow	814 814 814 802 802 803 803 815 815
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow	814 814 814 802 802 803 803 815 815 815
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow	814 814 814 802 802 803 803 815 815 815 815
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap	814 814 814 802 802 803 803 815 815 815
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap NT 20/1 Ap Te NT 20/1 Me Classic Edition	814 814 814 802 802 803 803 815 815 815 815 825 8281
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap Te NT 20/1 Me Classic Edition NT 22/1 Ap L	814 814 814 802 802 803 803 815 815 815 815 815 281 281
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap Te NT 20/1 Ap L NT 22/1 Ap L NT 22/1 Ap Te L	814 814 814 802 802 803 803 815 815 815 815 825 828 8281 281 283 283
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap Te NT 20/1 Ap L NT 22/1 Ap L NT 22/1 Ap Te L NT 27/1	814 814 814 802 802 803 803 815 815 815 815 815 815 825 828 828 83 84 84 84 84 85 86 86 87 88 88 88 88 88 88 88 88 88 88 88 88
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap Te NT 20/1 Ap L NT 22/1 Ap Te L NT 27/1 NT 27/1 Adv	814 814 814 802 802 803 803 815 815 815 815 815 281 281 281 283 283 283
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap T 20/1 Ap Te NT 20/1 Ap L NT 22/1 Ap Te L NT 27/1 NT 27/1 Adv NT 27/1 Me	814 814 814 814 802 802 803 803 803 815 815 815 82 Page 281 293 283 283 289 289
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap NT 20/1 Ap Te NT 20/1 Me Classic Edition NT 22/1 Ap Te NT 27/1 Adv NT 27/1 Me NT 27/1 Me NT 27/1 Me NT 27/1 Me Adv	814 814 814 814 802 802 803 803 803 815 815 815 815 82 Page 281 293 283 283 289 289 289
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap T 20/1 Ap Te NT 20/1 Me Classic Edition NT 22/1 Ap Te NT 27/1 Adv NT 27/1 Me NT 27/1 Me NT 27/1 Me NT 27/1 Me Adv NT 30/1 Ap L	814 814 814 814 802 802 803 803 803 815 815 815 815 82 82 82 83 83 83 84 85 85 86 86 87 87 88 88 88 88 88 88 88 88 88 88 88
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap NT 20/1 Ap Te NT 20/1 Me Classic Edition NT 22/1 Ap Te NT 27/1 Adv NT 27/1 Me NT 27/1 Me NT 27/1 Me NT 27/1 Me Adv NT 30/1 Ap L NT 30/1 Ap Te NT 30/1 Ap Te	814 814 814 814 802 802 803 803 803 815 815 815 815 293 283 283 289 289 289 279
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap NT 20/1 Ap Te NT 20/1 Me Classic Edition NT 22/1 Ap L NT 27/1 NT 27/1 Me NT 27/1 Me NT 27/1 Me Adv NT 30/1 Ap L NT 30/1 Ap Te NT 30/1 Ap Te NT 30/1 Ap Te	814 814 814 814 802 802 803 803 803 815 815 815 82 82 83 88 88 88 88 88 88 88 88 88 88 88 88
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap NT 20/1 Ap E NT 20/1 Me Classic Edition NT 22/1 Ap L NT 22/1 Ap Te NT 27/1 Me Adv NT 30/1 Ap L NT 30/1 Ap Te NT 30/1 Ap Te NT 30/1 Ap L NT 30/1 Ap L NT 30/1 Ap Classic Edition NT 30/1 Ap Classic Edition	814 814 814 814 802 802 803 803 803 815 815 815 825 828 828 83 88 88 88 88 88 88 88 88 88 88 88 88
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap NT 20/1 Ap E NT 20/1 Me Classic Edition NT 22/1 Ap L NT 22/1 Ap Te NT 27/1 Mdv NT 27/1 Me NT 27/1 Me NT 27/1 Me Adv NT 30/1 Ap L NT 30/1 Ap Te NT 30/1 Ap Te NT 30/1 Ap Classic Edition NT 30/1 Ap L NT 30/1 Ap Classic Edition	814 814 814 814 814 802 802 803 803 815 815 815 815 82 82 83 281 281 293 283 283 289 289 289 289 279 279 293 275 296
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap NT 20/1 Ap E NT 20/1 Me Classic Edition NT 22/1 Ap L NT 22/1 Ap L NT 27/1 Mdv NT 27/1 Me NT 27/1 Me NT 27/1 Me Adv NT 30/1 Ap L NT 30/1 Ap Te NT 30/1 Ap E NT 30/1 Ap L NT 30/1 Tact L NT 30/1 Tact Te H NT 30/1 Tact Te L	814 814 814 814 814 802 802 803 803 815 815 815 815 825 828 281 281 283 283 289 289 289 289 289 279 279 293 275 296
Microspun microfibre cloth, green Microspun microfibre cloth, red Microspun microfibre cloth, yellow Mop holder, flaps, 40 cm Mop holder with clip, 40 cm Mop holder with clip 50 cm Mop system Multi-purpose cloth, blue Multi-purpose cloth, green Multi-purpose cloth, red Multi-purpose cloth, yellow N NT 20/1 Ap NT 20/1 Ap NT 20/1 Ap E NT 20/1 Me Classic Edition NT 22/1 Ap L NT 22/1 Ap Te NT 27/1 Mdv NT 27/1 Me NT 27/1 Me NT 27/1 Me Adv NT 30/1 Ap L NT 30/1 Ap Te NT 30/1 Ap Te NT 30/1 Ap Classic Edition NT 30/1 Ap L NT 30/1 Ap Classic Edition	814 814 814 814 814 802 802 803 803 815 815 815 815 82 82 83 281 281 293 283 283 289 289 289 289 279 279 293 275 296

0	Page
NT 611 Mwf	298
NT 611 Eco K	298
NT 90/2 Me Classic Edition	291
NT 80/1 B1 M S	295
NT 75/2 Tact ² Me Tc Adv	265
NT 75/2 Tact ² Me Tc	265
NT 75/2 Tact² Me	267
NT 75/2 Ap Me Tc	277
NT 75/1 Tact Me Te H	296
NT 75/1 Me Ec H Z22	295
NT 70/3 Tc	285
NT 70/3 Me Tc	285
NT 70/3	287
NT 70/2 Tc	285
NT 70/2 Me Tc	285
NT 70/2 Me Classic Edition	291
NT 70/2 Me	287
NT 70/2 Adv	287
NT 70/2	287
NT 70/1	287
NT 65/2 Tact ² Tc	265
NT 65/2 Tact ²	267
NT 65/2 Ap	203
NT 55/2 Tact ² Me I	265
NT 55/1 Tact Bs	299
NT 50/2 Me Classic Edition	291
NT 50/1 Tact Te M	297
NT 50/1 Tact Te L	270
NT 50/1 Tact Te H	296
NT 50/1 Me Classic Edition	291
NT 48/1 Te	289
NT 48/1	289
NT 45/1 Tact Te Ec	272
NT 40/1 Tap L NT 40/1 Tact Te L	279
NT 38/1 Me Classic Edition NT 40/1 Ap L	293 279

0-00	
	Page
Pad, green	799
Pad holder, hand	799
Pad holder with joint	799
Pad sole, corrugated	798
Pad Strip washer	830
Pad, white	799
PC 60/130 T	789
PC 100 M2 Bio	788
PGG 3/1	246
PGG 6/1	246
PGG 8/3	246
Premium microfibre cloth, blue	813
Premium microfibre cloth, green	813
Premium microfibre cloth, red	813
Premium microfibre cloth, yellow	813
Protective gloves, long cuff	233
Protective gloves, short cuff	233
PT	749
PT Fp	749
Puzzi 8/1 C	429
Puzzi 10/1	428
Puzzi 10/2 Adv	428
Puzzi 30/4	427
Puzzi 30/4 E	427
PW 30/1	430
PW 30/1	430

Replacement ear defenders for helmet

Replacement pane, clear	232
Replacement pane, contrast-enhancing	232
Replacement pane, sun protection	232
Replacement rollers	833
Replacement visor for helmet	231
Replacement wiper rubber, hard	836
Replacement wiper rubber, soft	836
Rigid dust mop holder 120 cm	798
-	
Rubber squeegee 55 cm	800
S	Page
Safety goggles, clear	232
Safety goggles, contrast-enhancing	232
Safety goggles, sun protection	232
Safety helmet set, with hearing protection and visor	231
SB F M80	749
SB F M80 3	749
SB F M80 3 S	749
SB F M80 S	749
SB F M80 Sm	749
SB F M80 Sm S	749
SB MB	741
SB MC 2	743
SB MU	739
SB VC 1	747
SB VC 1 Ec	747
SB VC 2	747
SB VC 2 Ec	747
Scraper with long handle and blade	796
Scraper with short handle and blade	812
Set of safety goggles	232
SG 4/4	447
SGG 1	449
SGV 6/5	445
SGV 8/5	445
Single mobile bucket with handle 25 I	822
Single mobile bucket with press 25 I	822
Single mobile bucket with press and "U" sliding handle 25 I	822
Soft grip wiper handle	831
Squeegee, reinforced	834
Squeegee, reinforced	834
ST 400 Bp	243
Stainless steel strainer	833
T 7/1 Classic	393
,	385
T 7/1 ecolefficiency	
T 8/1 Classic	393
T 8/1 L	391
T 9/1 Bp	394
T 10/1	390
T 10/1 Adv	390
T 10/1 ecolefficiency	385
	389
T 12/1	
T 12/1 T 12/1 ecolefficiency	385
	385
T 12/1 ecolefficiency T 12/1 Hf	389
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic	389 393
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1	389 393 387
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency	389 393 387 385
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA	389 393 387 385 387
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36	389 393 387 385 387 735
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36 TB 42	389 393 387 385 387 735
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36 TB 42 TB 46	389 393 387 385 387 735 735
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36 TB 42 TB 46 TB 50	389 393 387 385 387 735 735 735 735
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36 TB 42 TB 46 TB 50 Telescopic handle 97-184 cm	389 393 387 385 387 735 735 735 735 806
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36 TB 42 TB 46 TB 50 Telescopic handle 97-184 cm Trolley Classic I	389 393 387 385 387 735 735 735 735 806 821
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36 TB 42 TB 46 TB 50 Telescopic handle 97-184 cm Trolley Classic I	389 393 387 385 387 735 735 735 735 806
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36 TB 42 TB 46 TB 50 Telescopic handle 97-184 cm Trolley Classic I	389 393 387 385 387 735 735 735 735 806 821
T 12/1 ecolefficiency T 12/1 Hf T 14/1 Classic T 15/1 T 15/1 ecolefficiency T 15/1 HEPA TB 36 TB 42 TB 46 TB 50 Telescopic handle 97-184 cm Trolley Classic I	389 393 387 385 387 735 735 735 735 806 821 821

Trolley Classic V	821
Trolley Clean Liner Classic I	820
Trolley Clean Liner Classic II	821
Trolley Clean Liner Classic III	821
Trolley Clean Liner Classic IV	821
Trolley ECO!Clean Liner	820
Trolley ECO!Clean Liner Mini	820
Trolley ECO!Clean Liner Press	820
Trolley ECO!First Liner	820
Trolley Hotel Classic I	823
Trolley Hotel Classic II	823
Trolley Hotel Classic III	823
Trolley Hotel Premium I	823
Trolley Hotel Premium II	823
V	Page
Velcro holder 40 cm	803
Velcro holder with block system 40 cm	803
Velour microfibre cloth, blue	814
Velour microfibre cloth, green	814
Velour microfibre cloth, red	814
Velour microfibre cloth, yellow	814
V-rail, stainless steel	832

231

W	Page
Warning sign Danger of slipping FR	804
Warning sign Danger of slipping IT	804
Warning sign Danger of slipping PL	804
Warning sign for door	805
Wash brush, hard	832
Wash brush, soft	832
Water squeegee for hygienic areas	834
Water squeegee, reinforced, oil-resistant	834
WC Set, white	816
Wet work protection jacket, Advanced	230
Wet work protection suit, Advanced	230
Wet work protection suit, Classic	230
Wet work protection trousers, Advanced	230
White Star washer	828
Window and floor scraper, 25 cm long, with blade	828
Window and floor scraper, 120 cm long, with blade	796, 828
Wooden handle 140 cm D 25 mm	806
WPC 80 RO	469
WPC 100 RO	468
WPC 120 UF	469
WPD 50	467
WPD 50 Ws	467
WPD 100	464, 465
WPD 200	464, 465
WPD 600	464, 465
WR 10	115
WR 20	115
WR 50	115
WR 100	115
WRB 2000 Bio	757
WRB 4000 Bio	757
WRH 1200 Classic	758
WRP 1000 Classic	758
WRP 8000	754
WRP 16000	754
WRP Car Wash	755
WRS 200	717
WS 50	112
WS 100	112
WS Regenerator	112
WVP 10 Adv	255
WVP 10 *EU	255
WWP 45	247
<u> </u>	

Cleaning Agents

PartsPro Cleaner PC Bio 10

A	Page
Active Foam CP 940	877
Alkaline Active Cleaner RM 81	846
3	Page
Blasting Abrasive, coarse	847
Blasting Abrasive, fine	847
	Page 1
: CarpetPro Cleaner iCapsol RM 760 Powder OA	Pag (852
CarpetPro Cleaner iCapsol RM 760 Tablet	852
CarpetPro Cleaner iCapsol RM 768	852
CarpetPro Cleaner iCapsol RM 768 OA	852
CarpetPro Cleaner, quick-drying RM 767 OA	852
CarpetPro Cleaner RM 760 Powder Classic	852
CarpetPro Cleaner RM 764 OA	852
CarpetPro Conditioner RM 763	853
CarpetPro Protector RM 762	853
CarpetPro RTS Classic Cleaner	852
Citral Perfumed Cleaner	862 853, 859, 865, 873
Cleaning Agent Sprayer	853, 859, 865, 873
Container valve, 5 I	849, 858, 864, 872
Container valve, 101	849, 872
Container valve, 201	849, 872
	Page
Disinfectant Cleaner, foaming RM 734	846
Disinfectant Cleaner RM 732	846, 87
Disinfectant RM 735	846, 87
Dosing head Drum pump, 200 I	858, 86- 849, 872
Orum tap, 200 I	849, 87
DS 2 Dosing Unit	849, 858, 864, 872
DS 3 Cleaning Agent Dosing Station	849, 858, 864, 87
E EK 1 Cleaning Agent Sprayer	Pag 849, 873
	2.2, 2.
	Page
Fleural Perfumed Cleaner	856
FloorPro Allround Deep Cleaner RM 754	870
FloorPro Care Dispersion RM 784	869, 87
FloorPro Cleaner CA 50 C eco!perform	868
FloorPro Cleaner CA 50 C eco!perform Swan FloorPro Crystallising Agent RM 749	87
FloorPro Deep Cleaner, acidic RM 751	863, 870
FloorPro Deep Cleaner RM 69	869
FloorPro Deep Cleaner RM 69 eco!efficiency	869
FloorPro Escalator Cleaner, neutral RM 758	870
FloorPro Fine Stoneware Cleaner RM 753	868
FloorPro High Gloss Crystallising Agent, powder RM 775	87
FloorPro Industrial Cleaner RM 69	869
FloorPro Intensive Deep Cleaner Extra RM 752 FloorPro Multi Cleaner RM 756	870
FloorPro Multi Cleaner RM 756 FloorPro Protect Dispersion Extra RM 782	868
FloorPro RIR Classic Industrial Cleaner	87
FloorPro Shine Cleaner RM 755	870
FloorPro Solisal Classic Deep Cleaner	868
FloorPro Spray Cleaner RM 748	869
FloorPro Tyre and Abrasion Marks Remover RM 776	868
FloorPro Wipe Care Extra RM 780	869
loorPro Wipe Care RM 746	869
oam Blocker RM 761	853, 870
1	Pag
Hand Cleaning Paste RM 200	848
High-Pressure Wash CP 935	87
	Page
	87
ntensive Dirt Remover CP 930	
	Page
ntensive Dirt Remover CP 930 PartsPro Cleaner Extra, powder RM 63	

PartsPro Cleaner PC Bio 20			881
PartsPro Cleaner RM 39			881
PartsPro Microbe Suspension			881
PartsPro Parts Cleaner RM 39			848
Premium demo case	853, 859,	865.	
PressurePro Active Cleaner, acidic RM 25	,,	,	846
PressurePro Active Cleaner, alkaline RM 81			844
PressurePro Active Cleaner, alkaline RM 81 ecolefficiency			844
PressurePro Active Cleaner, neutral RM 55			847
PressurePro Active Cleaner, powder RM 80			845
PressurePro Car Shampoo, powder RM 22			845
PressurePro Descaling Acid RM 101			848
PressurePro Facade Cleaner, gel RM 43			847
PressurePro Foam Cleaner, acidic RM 59			845
PressurePro Foam Cleaner, alkaline RM 58			845
PressurePro Foam Cleaner, alkaline RM 91 Agri			847
PressurePro Foam Cleaner, neutral RM 57			845
PressurePro Foam Cleaner RM 838			844
PressurePro Grease and Protein Remover RM 731			845
PressurePro Hot Wax RM 41			845
PressurePro Intensive Deep Cleaner RM 750		846,	870
PressurePro Machine Protector Advance 1 RM 110			848
PressurePro Machine Protector Advance 2 RM 111			848
PressurePro Machine Protector RM 110			848
PressurePro Oil and Grease Cleaner Extra RM 31		844,	846
PressurePro Oil and Grease Cleaner Extra RM 31 ecolefficience	.y	844,	846
PressurePro Phosphating Agent RM 48			848
PressurePro Smoke Resin Remover RM 33			847
PressurePro Soaking Agent, alkaline RM 92 Agri			847
PressurePro Solar Cleaner RM 99			847
PressurePro Surface Cleaner, acidic RM 93 Agri			847
PressurePro Wax Remover RM 36			844
Pump spray bottle			873
R			Page
Refill set for Premium demo case	853, 859,		
Pim Cloaner alkaling CD 001	, ,		076

S	Page
SanitPro Allsan Everyday Cleaner	862
SanitPro Daily Cleaner CA 20 C eco!perform	862
SanitPro Daily Cleaner CA 20 C eco!perform Swan	862
SanitPro Daily Cleaner CA 20 R eco!perform	862
SanitPro Daily Cleaner CA 20 R eco!perform Swan	862
SanitPro empty bottle, Everyday Cleaner CA 20 C-D Eco	864
SanitPro RSA Classic Deep Cleaner	863
SanitPro Scented Cleaner RSD Classic	862
SanitPro Tolisan WC Cleaner	862
SanitPro Unisan Plus Deep Cleaner	863
SanitPro Urisan Deodoriser	863
SanitPro WC and Deep Cleaner CA 10 C eco!perform	862
SanitPro WC Cleaner CA 10 C eco!perform Swan	862
Sprayer, blue	858
Sprayer, red with foam nozzle	864
Spray nozzle, red	864
Starter set for Premium demo case 853, 859, 865	, 873
SurfacePro Alcal Alcohol-Based Cleaner	856
SurfacePro Cleaner, alkaline Induflex	857
SurfacePro empty bottle, Surface Cleaner CA 30 C-D eco!perform	858
SurfacePro Glasal Glass Cleaner	857
SurfacePro Glass Cleaner CA 40 R eco!perform	857
SurfacePro Glass Cleaner CA 40 R eco!perform Swan	857
SurfacePro Maintenance Cleaner, odourless Allflex	856
SurfacePro RAG Classic Multi-Purpose Cleaner	856
SurfacePro RGR Classic Glass and Surface Cleaner	857
SurfacePro Scouring Agent Inoxal	857
SurfacePro Sural Glass and Surface Cleaner	857
SurfacePro Surface Cleaner CA 30 C eco!perform	856
SurfacePro Surface Cleaner CA 30 C eco!perform Swan	856

Refill set for Premium demo case Rim Cleaner, alkaline CP 901

T	Page
TankPro Cleaner, acidic RM 870	882
TankPro Cleaner, alkaline RM 875	882
TankPro Cleaner, Polymer RM 880	882
TankPro Latex Remover RM 885	882

881

Tefral Multi-Purpose Cleaner	868
Telescopic spray lance	849, 873
Thermo wax CP 945	879
Top Care CP 950	879
U	Page
Universal Cleaner RM 770, surfactant-free	852, 856
Universal Stain Remover RM 769	852, 857, 868
V	Page
VehiclePro Active Foam RM 812 Classic	878
VehiclePro Active Foam Wash Nano RM 816 Classic	878
VehiclePro Brush Shampoo RM 811 Classic	877
VehiclePro Drying Aid RM 829 Classic	878
VehiclePro Drying Aid RM 829 eco!perform	878
VehiclePro Foam Cleaner RM 838	877
VehiclePro Foam Polish RM 837	879
VehiclePro Foam Wash RM 812 eco!perform	878
VehiclePro Gloss Dryer Nano RM 832 Classic	878
VehiclePro High-Pressure Wash RM 806	877
VehiclePro Hot Wax RM 820 Classic	879
VehiclePro Kärcher Polish Plus RM 831	879
VehiclePro Klear!Brush RM 891	877
VehiclePro Klear!Dry RM 893	878

VehiclePro Klear!Foam RM 892	87
VehiclePro Klear!Glow RM 894	87
VehiclePro Klear!Prewash RM 890	87
VehiclePro Klear!Rim Foam RM 802	87
VehiclePro Klear!Rim RM 896	87
VehiclePro Liquid Leather RM 833	87
VehiclePro Prewash RM 803 Classic	844, 87
VehiclePro Prewash RM 803 eco!perform	87
VehiclePro Rim Cleaner, acidic RM 800	844, 87
VehiclePro Rim Cleaner, alkaline RM 801 Classic	844, 87
VehiclePro Softening Salt	87
VehiclePro Spray Wax RM 821 Classic	845, 87
VehiclePro Super Pearl Wax RM 824 Classic	87
VehiclePro Truck Cleaner, acidic RM 804	87
VehiclePro Truck Cleaner, alkaline RM 805	87
VehiclePro Washing Bay and Tile Cleaner RM 841	87
w	Pa
WaterPro Active Chlorine RM 852	88
WaterPro Active Oxygen RM 851	88
WaterPro Flocculating Agent RM 847	88
WaterPro Flocculating Agent RM 5001	88
WaterPro Hardness Stabiliser RM 5000	88
WaterPro Separating Agent, powder RM 846	88

《 OUR PICTOGRAMS

→ ALL THE BEST AND LOTS OF NEW THINGS



The new things first

Innovation is one of our strengths. And because you are incredibly interested in everything that benefits you in your work, we present our current innovations right at the start of a chapter. This way you see what's new straight away and at a glance.

Model	Container capacity Working width	Turbines	Type and equipm	ent	Configuration options
Example: T Example: CV Example: EB Example: HV	15 38 30 1	1 2 1 1	ecolefficiency Adv		Li-ion Bp Fs
T = Dry vacuum cleaner BV = Backpack Vacuum EB = Eleteric Broom, battery-powered CV = Carpet Vacuum, upright brush-type vacuum cleaner HV = Handheld Vacuum, battery-powered	In machine names with a combination of numbers for dry vacuum cleaners the first number indicates the container capacity in litres). For EB and CV machines, the first number indicates the working width of the roller brush (in centimetres).	In machine names with a combination of numbers, the second number indicates the number of turbines.	Classic Adv RS	n = Standard = Basic equipment = Advanced, with additional equipment = Ride-on/Step-on machine = Machine with ecolefficiency function	Li-ion = Lithium-ion battery

Our product names say it all

Do you sometimes not understand what a product name should mean? Not with us. We developed a strict and clear system for naming our products. Here you see, using the example of our vacuum cleaner, what the abbreviations and numbers represent. We call it "descriptive product names" because they mention the most important machine features. You find this overview before every chapter.







Together we are even stronger

Our cleaning agents can be found in a separate chapter. You have a complete overview of all our cleaning agents and can easily compare, select and compile your individual requirement. And a separate chapter also highlights the huge importance of our cleaning agents for your success.

OUR PICTOGRAMS



Indicates the maximum working pressure of a machine here: 2800 bar.

Absorbs odours

Allergy-friendly

ANTI!Twist

Hose with freely

Auto Shutdown

closed.

Automatic shutdown

of motor and pump

Average application

Recommended maxi-

mum duration of use

n hours per day.

Machine is powered

with rechargeable

Machine that is sui-

table for operation

with biodiesel

Cold/Hot water

Configurable

Configurable

powered by diesel

Scrubber driers

with a patented

cleaning agent

dosing unit.

EASY!Force

HP trigger gun

with zero holding

force for effortless

machine.

High-pressure cleaner

with cold-water or

hot-water operation

Battery drive

Biodiesel

when the trigger gun is

rotating connections.

substances in the air.



EASY!Lock

Robust, long-lasting quick fastener: five times faster than screws.



LPG engine

Machine powered by liquid gas (LPG).



Indicates cleaning agents that reduce unpleasant odorous substances.



EASY Operation

Electric

crubber drier with single button control.

Indicates electrically

Energy efficiency IE2

equipped with highly

efficient motors.

powered machines.



Mains and battery operation

Can be powered from the mains or with batteries.



Noise level

Noise values for machines. Noise level indication in dB(A).

Puncture-proof wheels

Guarantees a perma-

nently high degree

of mobility, even on

uneven ground.

Servo Control

Regulation of

volume on the

trigger gun.

Very quiet

60 dB(A).

VOC-Sensor

Precise detection

of gaseous air

pollution.

pressure and water

StVZO (approved for

Machines that have been approved for

Indicates the sound

pressure level, e.g.

use on German roads)



Machine that is powered by petrol.



E-Start

Machine with electro start.

Machines are



Machine is explosion



proof.



Machine with certified explosion





FACT

Scrubber drier with an application-optimised cleaning



Full ceramic valve

High-tech ceramic for a service life up to five times longer



Laser sensor



Precise detection of particulate air pollution.



Lead batteries

contain lead.



Machine equipped with rechargeable lithium-ion batteries.



agent.



Batteries which





Low foam Low-foam cleaning



Machines with zone 22 certification.



Please contact us for more information:

Head Office Germany

Alfred Kärcher SE & Co. KG Alfred-Kärcher-Straße 28-40 71364 Winnenden

Phone +49 7195-14-0 Fax +49 7195-14-2212

www.kaercher.com

North America

Kärcher North America 4555 Airport Way Denver, CO 80239 USA

Phone +1 303-738-5805 Fax +1 303-865-2758

www.karcherna.com

United Kingdom

Kärcher (UK) Ltd Kärcher House Brookhill Way Banbury Oxon OX16 3ED

Phone +44 1295-752-000 Fax +44 1295-752-103

www.karcher.co.uk

Ireland

Kärcher Ltd Unit 4 E.P. Mooney Business Park Walkinstown Avenue Dublin 12

Phone +353 1-409-7777 Fax +353 1-409-7775

www.karcher.ie

South East Asia

Regional Head Office South East Asia

Karcher South East Asia Pte Ltd 3 Depot Close #01-01 Singapore 109840

Phone +65 6897-1811 Fax +65 6897-1611

www.karcher.com.sg

Hong Kong

Kärcher Limited Unit 05, 13/F, Nanyang Plaza 57 Hung To Road Kwun Tong, Kowloon

Phone +852 2-357-5863 Fax +852 2-357-5632

www.karcher.com.hk

Australia

Karcher Pty Ltd 40 Koornang Road Scoresby VIC 3179 Melbourne, Victoria

Phone +61 3-9765-2300 Fax +61 3-9765-2398

www.karcher.com.au

New Zealand

Karcher Ltd 66 Allens Road East Tamaki Auckland 2013

Phone +64 9-274-4603 Fax +64 9-274-6932

www.karcher.co.nz

South Africa

Kärcher (Pty) Ltd Cnr Mount Joy & George Allen Rd Wilbart Ext. 2 PO Box 11818 Vorna Valley, 1686

Phone +27 11-657-7300 Fax +27 11-657-7440

www.karcher.co.za

Dubai

Karcher FZE Quality Cleaning Systems Jebel Ali Free Zone Plot No. S-10104 South Zone RA 08, XB 1, Jebel Ali

Phone +971 4-886-1177 Fax +971 4-886-1575

www.kaercher.com