- ✓ Integrated Recovery
- ✓ Temperatures up to 120°C
- ✓ Integrate high quality toggle swivel
- \checkmark Ready to use



Mosmatic Surface Cleaner Aqua with Integrated Recovery. The dirty water is recovered and expelled with the Venturi principle eliminating the need for a vacuum system. Simply place your export hose to a desired drain point. Areas both large and small are cleaned effectively and efficiently without requiring bulky vacuum systems and long runs of hosing.



TECHNICAL DATA

Pressure Temperature Inlet

275 bar 120°C G3/8" F




FL-SAR



FEATURES

Integrated recovery

The black anodized aluminum suction device collects the dirty water via the Venturi and double housing principal. Mount your export hose on the suction device and place it into the desired port to drain the water. The use of a vacuum system is no longer needed.



Rotor Arms

Can withstand up to 275 bar, are precision welded and balanced.

2w2 (2 Arms / 2 Nozzles) Part No. 82.623 (ø250mm)

Swiss Engineering

High rpm stainless steel swivel features reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.

KDYF Toggle Swivel

Part No. 58.912

Stainless Steel Caster

Heavy duty ø60mm casters with custom mounting brackets ensure easy manoeuvring even in confined spaces.



Part No. 80.943

Name	Part No.	Ø	Weight	Swivel	Rotor Arm	Nozzles	HP-Gun	Casters
FL-SAR	78.243	300	5.9kg	1x KDYF	2x 1/8" NPTF	2x 1503 / 1x #3*	1x	3x ø60

Accessories

Name	Part No.	Nozzles
Nozzles package	78.983	2x 1502 / 1x #2*

* #2 and #3 internal nozzles self recovery



VWW MOSMATIC CI