

Cat Pumps pump model nummers

Standaard Catpumps hogedrukpompen kunnen worden aangepast en worden voorzien van andere kleppen en afdichtingen en overige aanpassingen. Onderstaand word een overzicht weergegeven van alle afkortingen en de engelse omschrijvingen. Het laatste cijfer en / of achtervoegsel in elk modelnummer geeft de specifieke opties aan. Neem contact op met Wilting Hogedruk Techniek voor meer informatie.

| | |
|---------|--|
| 1.0000 | 316SS Manifolds (304S Valves - Piston Pumps) (316SS Valves - Plunger Pumps) |
| 2.0000 | Unchromed 304S Cylinders and Sleeves and 304S Manifolds (Piston Pumps) Duplex SS Block-Style (Plunger Pumps) |
| 3.0000 | Machined High Pressure Cups (standard on 323, 333, 623 Piston Pumps) |
| 0.3000 | HT-LPS (Plunger Pumps) V-Hot Cups (Piston Pumps) |
| 0.3400 | HT OR ST-LPS, ST-HPS OR V/P |
| 0.6000 | Silicone Free Seals and O-Rings |
| 0.7000 | PTFE Free Seals and O-Rings |
| 4.0000 | Super Duplex (Plunger Pumps) |
| 5.0000 | Pulse Ported Discharge Manifold |
| 6.0000 | Unchromed Cylinders and Sleeves Standard Manifold (Piston Pumps) |
| 7.0000 | Nickel Aluminum Bronze |
| 8.0000 | Hasteloy |
| 0.9000 | Rebuilt |
| 0.0090 | All 90 Duro O-Rings |
| 0.0100 | FPM Seals |
| 0.0110 | FPM Seals and O-Rings |
| 0.0220 | EPDM Seals and O-Rings |
| 0.0300 | Blue Dot Seal with Wicks |
| 0.0330 | NBR (Buna-N) |
| 0.0700 | PTFE Seals, Buna O-Rings |
| 0.0710 | PTFE Seals, FPM O-Rings |
| 0.0770 | PTFE Seals, Isolast O-Rings |
| 0.0001 | Flat Valve Assemblies (3FR, 4FR, 5FR, 10FR Piston Pumps standard with Quiet Valves) (25FR, 60FR standard with Flat Valve) |
| 0.0005 | Inverted Discharge and Inlet Manifolds |
| 0.0008 | Inverted Inlet Manifolds |
| 0.0009 | Inverted Discharge Manifolds |
| 0.44101 | TEG Pumps |
| .C | Flushed Inlet Manifold - Standard Plunger |
| .K | Flushed Inlet Manifold - Block-Style Plunger |



Catpump model 3CP1241.44101



CatPumps model 781K

Cat Pumps pomp en accessoires codes

Standaard Catpumps hogedrukpompen kunnen worden aangepast en worden voorzien van andere kleppen en afdichtingen en overige aanpassingen. Onderstaand word een overzicht weergegeven van alle afkortingen en de engelse omschrijvingen. Zie individuele datasheets voor meer gedetailleerde informatie over alle producten.

| | |
|------|--|
| BB | Brass |
| BBCP | Brass/Chrome Plated |
| BC | Bearing Cover |
| BPH | By-Pass Hose |
| C/C | Crankcase |
| CS | Single Shaft-Right Side |
| CSS | Single Shaft-Right Side, Side-Gauge Left |
| DS | Dual Shaft Extensions |
| EPDM | Ethylene Propylene Diene Monomer |
| FBB | Forged Brass |
| FPM | Fluorocarbon |
| FV | 304SS Flat Valves |
| HS | Hi-Pressure Drive-end |
| HT | Special Blend Polytetrafluorethylene |
| IPFE | Isolast [Special PTFE] |
| NAB | Nickel Aluminum Bronze |
| NBR | Medium Nitrile (Buna-N) |
| POP | Polypropylene |
| POV | Pop-off Valve |
| PTFE | Pure Polytetrafluoroethylene |
| QV | 304SS Quiet Valves |
| RC | Rear Cover |
| RTP | Reinforced Thermal Composite |
| RV | Relief Valve |
| S | 304SS |
| S/P | Shaft Protector |
| SBCP | Special Brass-chrome plated |
| SFTK | PTFE/Aramid Fiber Blend |
| SS | 316SS Manifolds |
| SSD | Duplex Stainless |
| ST | Special Blend Polytetrafluorethylene |
| ST2 | Special Blend PTFE |
| ST4 | Special Blend PTFE |
| STHT | Special PTFE High Temperature |
| STL | Steel |
| TEG | Triethylene Glycol |
| W770 | Special Alloy Manifolds |
| ZP | Zinc Plated |



CatPump model 5CP4120CSS



CatPumps model 3541DHS